



Numerics

- 802.1D
 - See STP
- 802.1Q
 - and trunk ports [11-3](#)
 - configuration limitations [12-19](#)
 - encapsulation [12-16](#)
 - native VLAN for untagged traffic [12-23](#)
 - trunk mode [3-11](#)
- 802.1S
 - See MSTP
- 802.1W
 - See RSTP
- 802.1X
 - See port-based authentication
- 802.3AD
 - See EtherChannel
- 802.3Z flow control [11-15](#)

A

- abbreviating commands [2-4](#)
- ABRs [29-30](#)
- AC (command switch) [6-11, 6-21](#)
- access-class command [26-18](#)
- access control entries
 - See ACEs
- access-denied response, VMPS [12-28](#)

- access groups
 - applying ACLs to interfaces [26-19](#)
 - IP [26-20](#)
 - Layer 2 [26-19](#)
 - Layer 3 [26-20](#)
- accessing
 - clusters, switch [6-14](#)
 - CMS [3-30](#)
 - command switches [6-12](#)
 - HTTP port [3-31](#)
 - member switches [6-14](#)
 - stack members [5-16](#)
 - switch clusters [6-14](#)
- access lists
 - See ACLs
- access ports
 - defined [11-2](#)
 - in switch clusters [6-10](#)
- accounting
 - with RADIUS [9-28](#)
 - with TACACS+ [9-11, 9-17](#)
- ACEs
 - and QoS [27-7](#)
 - defined [26-2](#)
 - Ethernet [26-2](#)
 - IP [26-2](#)
- ACLs
 - ACEs [26-2](#)
 - any keyword [26-12](#)

ACLs (continued)

applying

- on bridged packets [26-38](#)
- on multicast packets [26-40](#)
- on routed packets [26-39](#)
- on switched packets [26-37](#)
- time ranges to [26-16](#)
- to an interface [26-19](#)
- to QoS [27-7](#)

classifying traffic for QoS [27-37](#)comments in [26-18](#)compiling [26-21](#)configuring with VLAN maps [26-36](#)defined [26-1, 26-7](#)examples of [26-21, 27-37](#)

extended IP

- configuring for QoS classification [27-38](#)
- creating [26-10](#)
- matching criteria [26-7](#)

hardware and software handling [26-20](#)host keyword [26-12](#)

IP

- applying to interface [26-19](#)
- applying to interfaces [26-19](#)
- creating [26-7](#)
- fragments and QoS guidelines [27-29](#)
- implicit deny [26-9, 26-13, 26-15](#)
- implicit masks [26-9](#)
- matching criteria [26-7](#)
- named [26-14](#)
- terminal lines, setting on [26-18](#)
- undefined [26-20](#)
- violations, logging [26-15](#)

limiting actions [26-37](#)logging messages [26-10](#)log keyword [26-15](#)MAC extended [26-26, 27-39](#)matching [26-7, 26-20](#)monitoring [26-41](#)

ACLs (continued)

named [26-14](#)number per QoS class map [27-29](#)numbers [26-8](#)port [26-2](#)precedence of [26-2](#)QoS [27-7, 27-37](#)router [26-2](#)

standard IP

- configuring for QoS classification [27-37](#)
- creating [26-9](#)
- matching criteria [26-7](#)

supported features [26-20](#)support for [1-6](#)time ranges [26-16](#)unsupported features [26-6](#)using router ACLs with VLAN maps [26-36](#)

VLAN maps

- configuration guidelines [26-29](#)
- configuring [26-29](#)

active router [30-1](#)address aliasing [18-2](#)

addresses

displaying the MAC address table [7-27](#)

dynamic

- accelerated aging [15-9](#)
- changing the aging time [7-23](#)
- default aging [15-9](#)
- defined [7-22](#)
- learning [7-22](#)
- removing [7-24](#)

MAC

discovering [7-28](#)

multicast

- group address range [31-3](#)
- STP address management [15-9](#)

static

- adding and removing [7-26](#)
- defined [7-22](#)

- address resolution [7-28, 29-9](#)
- Address Resolution Protocol
 - See ARP
 - See ARP table
- adjacency tables, with CEF [29-66](#)
- administrative distances
 - defined [29-79](#)
 - OSPF [29-35](#)
 - routing protocol defaults [29-68](#)
- advertisements
 - CDP [20-1](#)
 - IGRP [29-25](#)
 - RIP [29-20](#)
 - VTP [12-19, 13-3](#)
- aggregate addresses, BGP [29-61](#)
- aggregated ports
 - See EtherChannel
- aggregate policers [27-45](#)
- aggregate policing [1-7](#)
- aggregator template [5-7, 8-1](#)
- aging, accelerating [15-9](#)
- aging time
 - accelerated
 - for MSTP [16-21](#)
 - for STP [15-9, 15-23](#)
 - MAC address table [7-23](#)
 - maximum
 - for MSTP [16-22](#)
 - for STP [15-23](#)
- alarms, RMON [23-3](#)
- allowed-VLAN list [12-21](#)
- alternate routes, IGRP [29-26](#)
- Apply button [3-29](#)
- area border routers
 - See ABRs
- ARP [1-4, 7-28](#)
 - configuring [29-10](#)
 - defined [29-9](#)
 - encapsulation [29-11](#)
 - static cache configuration [29-10](#)
- ARP table
 - address resolution [7-28](#)
 - managing [7-28](#)
- ASBRs [29-30](#)
- AS-path filters, BGP [29-55](#)
- attributes, RADIUS
 - vendor-proprietary [9-31](#)
 - vendor-specific [9-29](#)
- audience [xxxiii](#)
- authentication
 - EIGRP [29-43](#)
 - HSRP [30-8](#)
 - local mode with AAA [9-37](#)
 - NTP associations [7-5](#)
 - RADIUS
 - key [9-21](#)
 - login [9-23](#)
 - See also port-based authentication
 - TACACS+
 - defined [9-11](#)
 - key [9-13](#)
 - login [9-14](#)
- authentication keys, and routing protocols [29-80](#)
- authoritative time source, described [7-2](#)
- authorization
 - with RADIUS [9-27](#)
 - with TACACS+ [9-11, 9-16](#)
- authorized ports with 802.1X [10-4](#)
- autoconfiguration [4-3](#)

- automatic discovery
 - adding member switches [6-19](#)
 - considerations
 - beyond a non-candidate device [6-8](#)
 - brand new switches [6-10](#)
 - connectivity [6-5](#)
 - different VLANs [6-7](#)
 - management VLANs [6-8](#)
 - non-CDP-capable devices [6-6](#)
 - non-cluster-capable devices [6-6](#)
 - routed ports [6-9](#)
 - creating a cluster standby group [6-21](#)
 - in switch clusters [6-5](#)
 - See also CDP
 - automatic QoS
 - See QoS
 - automatic recovery, clusters [6-11](#)
 - See also HSRP
 - autonegotiation
 - duplex mode [1-3](#)
 - interface configuration guidelines [11-13](#)
 - mismatches [34-12](#)
 - autonomous system boundary routers
 - See ASBRs
 - autonomous systems, in BGP [29-49](#)
 - Auto-RP, described [31-5](#)
 - autosensing, port speed [1-3](#)
 - auxiliary VLAN
 - See voice VLAN
 - availability, features [1-5](#)
-
- B**
- BackboneFast
 - described [17-8](#)
 - enabling [17-17](#)
 - support for [1-5](#)
 - bandwidth graphs [3-9](#)
 - banners
 - configuring
 - login [7-21](#)
 - message-of-the-day login [7-20](#)
 - default configuration [7-19](#)
 - when displayed [7-19](#)
 - BGP
 - aggregate addresses [29-61](#)
 - aggregate routes, configuring [29-61](#)
 - CIDR [29-61](#)
 - clear commands [29-64](#)
 - community filtering [29-57](#)
 - configuring neighbors [29-59](#)
 - default configuration [29-47](#)
 - described [29-46](#)
 - enabling [29-49](#)
 - monitoring [29-64](#)
 - multipath support [29-52](#)
 - neighbors, types of [29-49](#)
 - path selection [29-52](#)
 - peers, configuring [29-59](#)
 - prefix filtering [29-56](#)
 - resetting sessions [29-51](#)
 - route dampening [29-63](#)
 - route maps [29-54](#)
 - route reflectors [29-62](#)
 - routing domain confederation [29-61](#)
 - show commands [29-64](#)
 - supernets [29-61](#)
 - support for [1-8](#)
 - Version 4 [29-46](#)
 - binding cluster group and HSRP group [30-9](#)
 - blocking packets [19-5](#)
 - booting
 - boot loader, function of [4-2](#)
 - boot process [4-1](#)
 - manually [4-13](#)
 - specific image [4-14](#)

- boot loader
 - accessing [4-15](#)
 - described [4-2](#)
 - environment variables [4-15](#)
 - prompt [4-15](#)
 - trap-door mechanism [4-2](#)
 - bootstrap router (BSR), described [31-5](#)
 - Border Gateway Protocol
 - See BGP
 - BPDU
 - error-disabled state [17-3](#)
 - filtering [17-3](#)
 - RSTP format [16-10](#)
 - BPDU filtering
 - described [17-3](#)
 - enabling [17-15](#)
 - support for [1-5](#)
 - BPDU guard
 - described [17-3](#)
 - enabling [17-14](#)
 - support for [1-5](#)
 - bridged packets, ACLs on [26-38](#)
 - bridge groups
 - See fallback bridging
 - bridge protocol data unit
 - See BPDU
 - broadcast flooding [29-17](#)
 - broadcast packets
 - directed [29-14](#)
 - flooded [29-14](#)
 - broadcast storm-control command [19-3](#)
 - broadcast storms [19-1, 29-14](#)
 - browser configuration [3-1](#)
 - buttons, CMS [3-29](#)
-
- C**
- cables, monitoring for unidirectional links [21-1](#)
 - Cancel button [3-29](#)
 - candidate switch
 - adding [6-19](#)
 - automatic discovery [6-5](#)
 - defined [6-4](#)
 - HC [6-21](#)
 - passwords [6-19](#)
 - requirements [6-4](#)
 - standby group [6-21](#)
 - See also command switch, cluster standby group, and member switch
 - caution, described [xxxiv](#)
 - CC (command switch) [6-21](#)
 - CDP
 - and trusted boundary [27-34](#)
 - automatic discovery in switch clusters [6-5](#)
 - configuring [20-2](#)
 - default configuration [20-2](#)
 - described [20-1](#)
 - disabling for routing device [20-3, 20-4](#)
 - enabling and disabling
 - on an interface [20-4](#)
 - on a switch [20-3](#)
 - monitoring [20-5](#)
 - overview [20-1](#)
 - support for [1-4](#)
 - switch stack considerations [20-2](#)
 - transmission timer and holdtime, setting [20-2](#)
 - updates [20-2](#)
 - CEF [29-66](#)
 - CGMP
 - as IGMP snooping learning method [18-7](#)
 - clearing cached group entries [31-51](#)
 - enabling server support [31-33](#)
 - joining multicast group [18-2](#)
 - overview [31-7](#)
 - server support only [31-7](#)
 - switch support of [1-3](#)
 - change notification, CMS [3-31](#)
 - CIDR [29-61](#)

- Cisco 7960 IP Phone [14-1](#)
- Cisco Discovery Protocol
 - See CDP
- Cisco Express Forwarding
 - See CEF
- Cisco Group Management Protocol
 - See CGMP
- Cisco IOS File System
 - See IFS
- Cisco StackWise technology [1-2](#)
 - See also stacks, switch
- CiscoWorks 2000 [1-4, 25-5](#)
- classless interdomain routing
 - See CIDR
- classless routing [29-7](#)
- class maps for QoS
 - configuring [27-40](#)
 - described [27-7](#)
 - displaying [27-64](#)
- class of service
 - See CoS
- clearing interfaces [11-22](#)
- CLI
 - abbreviating commands [2-4](#)
 - command modes [2-1](#)
 - described [1-4](#)
 - editing features
 - enabling and disabling [2-7](#)
 - keystroke editing [2-7](#)
 - wrapped lines [2-8](#)
 - error messages [2-5](#)
 - filtering command output [2-9](#)
 - getting help [2-3](#)
 - history
 - changing the buffer size [2-5](#)
 - described [2-5](#)
 - disabling [2-6](#)
 - recalling commands [2-6](#)
 - CLI (continued)
 - managing clusters [6-24](#)
 - no and default forms of commands [2-4](#)
 - client mode, VTP [13-3](#)
 - clock
 - See system clock
 - Cluster Management Suite
 - See CMS
 - clusters
 - switch
 - home page [3-2](#)
 - clusters, switch
 - accessing [6-14](#)
 - adding member switches [6-19](#)
 - automatic discovery [6-5](#)
 - automatic recovery [6-11](#)
 - benefits [1-2](#)
 - command switch configuration [6-18](#)
 - compatibility [6-4](#)
 - creating [6-18](#)
 - creating a cluster standby group [6-21](#)
 - described [6-1](#)
 - managing
 - through CLI [6-24](#)
 - through SNMP [6-25](#)
 - planning [6-4](#)
 - planning considerations
 - automatic discovery [6-5](#)
 - automatic recovery [6-11](#)
 - CLI [6-24](#)
 - host names [6-14](#)
 - IP addresses [6-14](#)
 - passwords [6-15](#)
 - RADIUS [6-17](#)
 - SNMP [6-15, 6-25](#)
 - switch-specific features [6-17](#)
 - switch stacks [6-15](#)
 - TACACS+ [6-17](#)

- clusters, switch (continued)
 - redundancy [6-21](#)
 - troubleshooting [6-23](#)
 - verifying [6-22](#)
 - See also candidate switch, command switch, cluster standby group, member switch, and standby command switch
- cluster standby group
 - and HSRP group [30-9](#)
 - automatic recovery [6-13](#)
 - considerations [6-12](#)
 - creating [6-21](#)
 - defined [6-2](#)
 - requirements [6-3](#)
 - virtual IP address [6-12](#)
 - See also HSRP
- cluster tree
 - described [3-6](#)
 - icons [3-6](#)
- CMS
 - accessing [3-30](#)
 - benefits [1-2](#)
 - change notification [3-31](#)
 - cluster tree [3-6](#)
 - described [1-2, 1-4, 3-1](#)
 - different versions of [3-33](#)
 - displaying system messages [3-19](#)
 - error checking [3-31](#)
 - features [3-3](#)
 - Front Panel images [3-7](#)
 - Front Panel view [3-5](#)
 - interaction modes [3-25](#)
 - launching [3-2](#)
 - menu bar [3-16](#)
 - online help [3-27](#)
 - requirements [3-30](#)
 - saving configuration changes [3-32](#)
 - toolbar [3-20](#)
 - tool tips [3-26](#)
- CMS (continued)
 - Topology view [3-11](#)
 - verifying configuration changes [3-31](#)
 - window components [3-28](#)
 - wizards [3-26](#)
- collapsed cluster view [3-12](#)
- command-line interface
 - See CLI
- command modes [2-1](#)
- commands
 - abbreviating [2-4](#)
 - no and default [2-4](#)
 - setting privilege levels [9-8](#)
- command switch
 - accessing [6-12](#)
 - active (AC) [6-11, 6-21](#)
 - command switch with HSRP disabled (CC) [6-21](#)
 - configuration conflicts [34-12](#)
 - defined [6-2](#)
 - enabling [6-18](#)
 - passive (PC) [6-11, 6-21](#)
 - password privilege levels [6-24](#)
 - priority [6-11](#)
 - recovery
 - from command-switch failure [6-11](#)
 - from failure [34-9](#)
 - from lost member connectivity [34-12](#)
 - redundant [6-11, 6-21](#)
 - replacing
 - with another switch [34-11](#)
 - with cluster member [34-9](#)
 - requirements [6-3](#)
 - standby (SC) [6-11, 6-21](#)
 - See also candidate switch, cluster standby group, member switch, and standby command switch
- community list, BGP [29-58](#)

- community strings
 - configuring [6-15, 25-8](#)
 - for cluster switches [25-4](#)
 - in clusters [6-15](#)
 - overview [25-4](#)
 - SNMP [6-15](#)
- compatibility, software
 - See stacks, switch
- config.text [4-12](#)
- configuration, switch, saving changes [3-32](#)
- configuration conflicts, recovering from lost member connectivity [34-12](#)
- configuration examples, network [1-11](#)
- configuration files
 - clearing the startup configuration [B-20](#)
 - creating using a text editor [B-11](#)
 - default name [4-12](#)
 - deleting a stored configuration [B-20](#)
 - described [B-9](#)
 - downloading
 - automatically [4-12](#)
 - preparing [B-11, B-14, B-17](#)
 - reasons for [B-9](#)
 - using FTP [B-14](#)
 - using RCP [B-18](#)
 - using TFTP [B-12](#)
 - guidelines for creating and using [B-10](#)
 - invalid combinations when copying [B-5](#)
 - limiting TFTP server access [25-15](#)
 - obtaining with DHCP [4-7](#)
 - password recovery disable considerations [9-5](#)
 - specifying the filename [4-13](#)
 - system contact and location information [25-15](#)
 - types and location [B-10](#)
- configuration files (continued)
 - uploading
 - preparing [B-11, B-14, B-17](#)
 - reasons for [B-9](#)
 - using FTP [B-16](#)
 - using RCP [B-19](#)
 - using TFTP [B-12](#)
- configuration settings, saving [4-10](#)
- configure terminal command [11-7](#)
- config-vlan mode [2-2, 12-7](#)
- conflicts, configuration [34-12](#)
- connections, secure remote [9-38](#)
- connectivity problems [34-13, 34-15](#)
- consistency checks in VTP version 2 [13-4](#)
- console port, connecting to [2-10](#)
- conventions
 - command [xxxiv](#)
 - for examples [xxxiv](#)
 - publication [xxxiv](#)
 - text [xxxiv](#)
- corrupted software, recovery steps with XMODEM [34-2](#)
- CoS
 - in Layer 2 frames [27-2](#)
 - override priority [14-5](#)
 - trust priority [14-5](#)
- CoS input queue threshold map for QoS [27-14](#)
- CoS output queue threshold map for QoS [27-16](#)
- CoS-to-DSCP map for QoS [27-47](#)
- counters, clearing interface [11-22](#)
- crashinfo file [34-21](#)
- cross-stack EtherChannel
 - configuration guidelines [28-12](#)
 - configuring
 - on Layer 2 interfaces [28-12](#)
 - on Layer 3 physical interfaces [28-15](#)
 - described [28-2](#)
 - illustration [28-3](#)
 - support for [1-5](#)

- cross-stack UplinkFast, STP
 - described [17-5](#)
 - enabling [17-17](#)
 - fast-convergence events [17-7](#)
 - Fast Uplink Transition Protocol [17-6](#)
 - normal-convergence events [17-7](#)
 - support for [1-5](#)
- cryptographic software image
 - Kerberos [9-32](#)
 - SSH [9-38](#)
 - switch stack considerations [5-2, 5-11, 9-38](#)
- CWDM GBIC modules, wavelength colors on CMS [3-8](#)

D

- daylight saving time [7-14](#)
- debugging
 - enabling all system diagnostics [34-18](#)
 - enabling for a specific feature [34-17](#)
 - redirecting error message output [34-18](#)
 - using commands [34-17](#)
- default commands [2-4](#)
- default configuration
 - 802.1X [10-11](#)
 - auto-QoS [27-18](#)
 - banners [7-19](#)
 - BGP [29-47](#)
 - booting [4-12](#)
 - CDP [20-2](#)
 - DNS [7-18](#)
 - EIGRP [29-40](#)
 - EtherChannel [28-10](#)
 - fallback bridging [33-4](#)
 - HSRP [30-4](#)
 - IGMP [31-27](#)
 - IGMP filtering [18-19](#)
 - IGMP snooping [18-5](#)
 - IGRP [29-26](#)
 - initial switch information [4-3](#)
 - default configuration (continued)
 - IP addressing, IP routing [29-5](#)
 - IP multicast routing [31-9](#)
 - Layer 2 interfaces [11-12](#)
 - MAC address table [7-23](#)
 - MSDP [32-4](#)
 - MSTP [16-13](#)
 - MVR [18-15](#)
 - NTP [7-4](#)
 - optional spanning-tree features [17-12](#)
 - OSPF [29-31](#)
 - password and privilege level [9-2](#)
 - RADIUS [9-20](#)
 - RIP [29-20](#)
 - RMON [23-3](#)
 - RSPAN [22-11](#)
 - SNMP [25-6](#)
 - SPAN [22-11](#)
 - standard QoS [27-27](#)
 - STP [15-13](#)
 - switch stacks [5-15](#)
 - system message logging [24-4](#)
 - system name and prompt [7-16](#)
 - TACACS+ [9-13](#)
 - UDLD [21-3](#)
 - VLAN, Layer 2 Ethernet interfaces [12-19](#)
 - VLANs [12-8](#)
 - VMPS [12-29](#)
 - voice VLAN [14-3](#)
 - VTP [13-7](#)
 - default gateway [4-10, 29-12](#)
 - default networks [29-69](#)
 - default routes [29-69](#)
 - default routing [29-2](#)
 - deleting VLANs [12-10](#)
 - description command [11-17](#)
 - designing your network, examples [1-11](#)
 - desktop template [5-7, 8-1](#)
 - destination addresses, in ACLs [26-11](#)

- destination-IP address based forwarding, EtherChannel [28-8](#)
- destination-MAC address forwarding, EtherChannel [28-8](#)
- detecting indirect link failures, STP [17-8](#)
- device discovery protocol [20-1](#)
- device icons, Front Panel view [3-6](#)
- device information [3-14](#)
- Device Manager [3-4](#)
 - See also Switch Manager
- device pop-up menu
 - Front Panel view [3-21](#)
 - Topology view [3-23](#)
- DHCP-based autoconfiguration
 - client request message exchange [4-4](#)
 - configuring
 - client side [4-3](#)
 - DNS [4-6](#)
 - relay device [4-6](#)
 - server-side [4-5](#)
 - TFTP server [4-5](#)
 - example [4-8](#)
 - lease options
 - for IP address information [4-5](#)
 - for receiving the configuration file [4-5](#)
 - overview [4-3](#)
 - relationship to BOOTP [4-4](#)
 - relay support [1-8](#)
 - support for [1-4](#)
- Differentiated Services architecture, QoS [27-1](#)
- Differentiated Services Code Point [27-2](#)
- Diffusing Update Algorithm (DUAL) [29-39](#)
- directed unicast requests [1-4](#)
- directories
 - changing [B-4](#)
 - creating and removing [B-4](#)
 - displaying the working [B-4](#)
- discovery, clusters
 - See automatic discovery
- display options, Topology view [3-16](#)
- Disqualification Code option [3-25](#)
- Distance Vector Multicast Routing Protocol
 - See DVMRP
- distance-vector protocols [29-3](#)
- distribute-list command [29-78](#)
- DNS
 - and DHCP-based autoconfiguration [4-6](#)
 - default configuration [7-18](#)
 - displaying the configuration [7-19](#)
 - overview [7-17](#)
 - setting up [7-18](#)
 - support for [1-4](#)
- documentation
 - feedback [xxxvi](#)
 - obtaining
 - CD-ROM [xxxv](#)
 - world wide web [xxxv](#)
 - ordering [xxxvi](#)
 - related [xxxv](#)
- document conventions [xxxiv](#)
- domain names
 - DNS [7-17](#)
 - VTP [13-8](#)
- Domain Name System
 - See DNS
- downloading
 - configuration files
 - preparing [B-11, B-14, B-17](#)
 - reasons for [B-9](#)
 - using FTP [B-14](#)
 - using RCP [B-18](#)
 - using TFTP [B-12](#)
 - image files
 - deleting old image [B-25](#)
 - preparing [B-23, B-26, B-30](#)
 - reasons for [B-21](#)
 - using FTP [B-27](#)
 - using RCP [B-32](#)
 - using TFTP [B-24](#)

- DSCP [1-7, 27-2](#)
 - DSCP input queue threshold map for QoS [27-14](#)
 - DSCP output queue threshold map for QoS [27-16](#)
 - DSCP-to-CoS map for QoS [27-50](#)
 - DSCP-to-DSCP-mutation map for QoS [27-51](#)
 - DTP [1-6, 12-17](#)
 - DUAL finite state machine, EIGRP [29-39](#)
 - duplex mode, configuring [11-13](#)
 - DVMRP
 - autosummarization
 - configuring a summary address [31-47](#)
 - disabling [31-49](#)
 - connecting PIM domain to DVMRP router [31-39](#)
 - enabling unicast routing [31-43](#)
 - interoperability
 - with Cisco devices [31-37](#)
 - with IOS software [31-7](#)
 - mrinfo requests, responding to [31-42](#)
 - neighbors
 - advertising the default route to [31-41](#)
 - discovery with Probe messages [31-37](#)
 - displaying information [31-42](#)
 - prevent peering with nonpruning [31-45](#)
 - rejecting nonpruning [31-44](#)
 - overview [31-7](#)
 - routes
 - adding a metric offset [31-49](#)
 - advertising all [31-49](#)
 - advertising the default route to neighbors [31-41](#)
 - caching DVMRP routes learned in report messages [31-43](#)
 - changing the threshold for syslog messages [31-46](#)
 - deleting [31-51](#)
 - displaying [31-51](#)
 - favoring one over another [31-49](#)
 - limiting the number injected into MBONE [31-46](#)
 - limiting unicast route advertisements [31-37](#)
 - routing table [31-7](#)
 - source distribution tree, building [31-7](#)
 - DVMRP (continued)
 - support for [1-8](#)
 - tunnels
 - configuring [31-39](#)
 - displaying neighbor information [31-42](#)
 - dynamic access mode [3-10](#)
 - dynamic access ports
 - characteristics [12-4](#)
 - configuring [12-31](#)
 - defined [11-3](#)
 - dynamic addresses
 - See addresses
 - dynamic auto trunking mode [12-18](#)
 - dynamic desirable trunking mode [12-18](#)
 - Dynamic Host Configuration Protocol
 - See DHCP-based autoconfiguration
 - dynamic port VLAN membership
 - described [12-29](#)
 - reconfirming [12-32](#)
 - troubleshooting [12-33](#)
 - types of connections [12-31](#)
 - dynamic routing [29-3](#)
 - Dynamic Trunking Protocol
 - See DTP
-
- ## E
- EBGP [29-45](#)
 - editing features
 - enabling and disabling [2-7](#)
 - keystrokes used [2-7](#)
 - wrapped lines [2-8](#)
 - EIGRP
 - and IGRP [29-41](#)
 - authentication [29-43](#)
 - components [29-39](#)
 - configuring [29-41](#)
 - default configuration [29-40](#)
 - definition [29-39](#)

EIGRP (continued)

- interface parameters, configuring [29-42](#)
- monitoring [29-44](#)
- support for [1-8](#)
- elections
 - See stack master
- enable password [9-4](#)
- enable secret password [9-4](#)
- encryption for passwords [9-4](#)
- Enhanced IGRP
 - See EIGRP
- environment variables
 - function of [4-16](#)
- equal-cost routing [1-8, 29-67](#)
- error checking, CMS [3-31](#)
- error messages during command entry [2-5](#)

EtherChannel

- 802.3AD, described [28-6](#)
- automatic creation of [28-5, 28-6](#)
- channel groups
 - binding physical and logical interfaces [28-4](#)
 - numbering of [28-4](#)
- configuration guidelines [28-11](#)
- configuring
 - Layer 2 interfaces [28-12](#)
 - Layer 3 physical interfaces [28-15](#)
 - Layer 3 port-channel logical interfaces [28-14](#)
- configuring Layer 2 interfaces [28-12](#)
- default configuration [28-10](#)
- described [28-2](#)
- displaying status [28-22](#)
- forwarding methods [28-7, 28-17](#)
- interaction
 - with STP [28-11](#)
 - with VLANs [28-11](#)

EtherChannel (continued)

- LACP
 - described [28-6](#)
 - displaying status [28-22](#)
 - hot-standby ports [28-20](#)
 - interaction with other features [28-7](#)
 - modes [28-7](#)
 - port priority [28-21](#)
 - system priority [28-20](#)
- LACP, support for [1-3](#)
- Layer 3 interface [29-4](#)
- load balancing [28-7, 28-17](#)
- logical interfaces, described [28-4](#)
- number of interfaces per [28-2](#)
- PAgP
 - aggregate-port learners [28-18](#)
 - compatibility with Catalyst 1900 [28-19](#)
 - described [28-5](#)
 - displaying status [28-22](#)
 - interaction with other features [28-6](#)
 - learn method and priority configuration [28-18](#)
 - modes [28-5](#)
 - silent mode [28-6](#)
 - support for [1-3](#)
- port-channel interfaces
 - described [28-4](#)
 - numbering of [28-4](#)
- port groups [11-5](#)
- stack changes, effects of [28-9](#)
- support for [1-3](#)
- Ethernet VLANs
 - adding [12-8](#)
 - defaults and ranges [12-8](#)
 - modifying [12-8](#)
- events, RMON [23-3](#)

- examples
 - conventions for [xxxiv](#)
 - network configuration [1-11](#)
 - expanded cluster view [3-11](#)
 - expanded stack view [3-13](#)
 - expert mode [3-26](#)
 - express setup [3-2](#)
 - extended-range VLANs
 - configuration guidelines [12-13](#)
 - configuring [12-12](#)
 - creating [12-13](#)
 - defined [12-1](#)
 - extended system ID
 - MSTP [16-15](#)
 - STP [15-4, 15-16](#)
 - Extensible Authentication Protocol over LAN [10-1](#)
 - exterior routes, IGRP [29-25](#)
 - external BGP
 - See EBGp
 - external neighbors, BGP [29-49](#)
-
- ## F
- failover support [1-5](#)
 - fallback bridging
 - and protected ports [33-4](#)
 - bridge groups
 - creating [33-4](#)
 - described [33-2](#)
 - displaying [33-11](#)
 - function of [33-2](#)
 - number supported [33-5](#)
 - removing [33-5](#)
 - bridge table
 - clearing [33-11](#)
 - displaying [33-11](#)
 - configuration guidelines [33-4](#)
 - connecting interfaces with [11-6](#)
 - default configuration [33-4](#)
 - fallback bridging (continued)
 - described [33-1](#)
 - frame forwarding
 - flooding packets [33-2](#)
 - forwarding packets [33-2](#)
 - overview [33-1](#)
 - stack changes, effects of [33-3](#)
 - STP
 - disabling on an interface [33-11](#)
 - forward-delay interval [33-10](#)
 - hello BPDU interval [33-9](#)
 - interface priority [33-7](#)
 - maximum-idle interval [33-10](#)
 - path cost [33-8](#)
 - VLAN-bridge spanning-tree priority [33-7](#)
 - VLAN-bridge STP [33-2](#)
 - support for [1-8](#)
 - SVIs and routed ports [33-1](#)
 - VLAN-bridge STP [15-12, 33-2](#)
 - fan fault indication [3-6](#)
 - Fast Uplink Transition Protocol [17-6](#)
 - feedback to Cisco Systems, web [xxxvi](#)
 - FIB [29-66](#)
 - fiber-optic, detecting unidirectional links [21-1](#)
 - files
 - copying [B-5](#)
 - crashinfo
 - description [34-21](#)
 - displaying the contents of [34-21](#)
 - location [34-21](#)
 - deleting [B-6](#)
 - displaying the contents of [B-8](#)
 - tar
 - creating [B-6](#)
 - displaying the contents of [B-7](#)
 - extracting [B-8](#)
 - image file format [B-22](#)

file system

- displaying available file systems [B-2](#)
- displaying file information [B-3](#)
- local file system names [B-1](#)
- network file system names [B-5](#)
- setting the default [B-3](#)

filtering

- in a VLAN [26-29](#)
- non-IP traffic [26-26](#)
- show and more command output [2-9](#)

filtering show and more command output [2-9](#)

filters, IP

See ACLs, IP

Flash device, number of [B-1](#)flash updates, IGRP [29-26](#)flooded traffic, blocking [19-6](#)flow-based packet classification [1-7](#)

flowcharts

- QoS classification [27-6](#)
- QoS egress queueing and scheduling [27-15](#)
- QoS ingress queueing and scheduling [27-13](#)
- QoS policing and marking [27-9](#)

flow control [1-3, 11-15](#)

forward-delay time

- MSTP [16-21](#)
- STP [15-23](#)

Forwarding Information Base

See FIB

forwarding non-routable protocols [33-1](#)Front Panel images, CMS [3-7](#)

Front Panel view

- cluster tree [3-6](#)
- command switch [3-5](#)
- described [3-5](#)
- pop-up menus [3-21](#)
- port icons [3-7](#)
- port LEDs [3-9](#)
- RPS LED [3-8](#)
- switch images [3-7](#)

FTP

- accessing MIB files [A-3](#)
- configuration files
 - downloading [B-14](#)
 - overview [B-13](#)
 - preparing the server [B-14](#)
 - uploading [B-16](#)
- image files
 - deleting old image [B-29](#)
 - downloading [B-27](#)
 - preparing the server [B-26](#)
 - uploading [B-29](#)

G

- get-bulk-request operation [25-3](#)
- get-next-request operation [25-3, 25-5](#)
- get-request operation [25-3, 25-5](#)
- get-response operation [25-3](#)
- Gigabit modules
 - See SFPs
- global configuration mode [2-2](#)
- graphs, bandwidth [3-9](#)
- guest VLAN and 802.1X [10-8](#)
- guide
 - audience [xxxiii](#)
 - purpose of [xxxiii](#)
- guide mode [1-2, 3-25](#)

H

- hardware limitations and Layer 3 interfaces [11-18](#)
- HC (candidate switch) [6-21](#)
- hello time
 - MSTP [16-20](#)
 - STP [15-22](#)
- help, for the command line [2-3](#)
- Help button, CMS [3-29](#)

Help Contents [3-27](#)

history

changing the buffer size [2-5](#)

described [2-5](#)

disabling [2-6](#)

recalling commands [2-6](#)

history table, level and number of syslog messages [24-10](#)

host name list, CMS [3-28](#)

host names

abbreviations appended to [6-21](#)

in clusters [6-14](#)

hosts, limit on dynamic ports [12-33](#)

Hot Standby Router Protocol

See HSRP

HP OpenView [1-4](#)

HSRP

authentication string [30-8](#)

automatic cluster recovery [6-13](#)

binding to cluster group [30-9](#)

cluster standby group considerations [6-12](#)

command-switch redundancy [1-1, 1-5](#)

configuring [30-3](#)

default configuration [30-4](#)

definition [30-1](#)

guidelines [30-4](#)

monitoring [30-10](#)

overview [30-1](#)

priority [30-6](#)

routing redundancy [1-8](#)

switch stack considerations [30-2](#)

timers [30-8](#)

tracking [30-6](#)

See also clusters, cluster standby group, and standby command switch

HTTP access [3-31](#)

Hypertext Transfer Protocol

See HTTP access

IBPG [29-45](#)

ICMP

redirect messages [29-12](#)

support for [1-8](#)

unreachable messages [26-19](#)

unreachables and ACLs [26-20](#)

ICMP ping

executing [34-14](#)

overview [34-13](#)

ICMP Router Discovery Protocol

See IRDP

icons

cluster tree [3-6](#)

colors

cluster tree [3-6](#)

Topology view [3-15](#)

Front Panel view [3-7](#)

toolbar [3-20](#)

Topology view [3-14](#)

IDS appliances

and ingress RSPAN [22-21](#)

and ingress SPAN [22-14](#)

IEEE 802.1P [14-1](#)

IFS [1-4](#)

IGMP

configuring the switch

as a member of a group [31-27](#)

statically connected member [31-32](#)

controlling access to groups [31-28](#)

default configuration [31-27](#)

deleting cache entries [31-51](#)

displaying groups [31-51](#)

fast switching [31-32](#)

host-query interval, modifying [31-30](#)

IGMP (continued)

- joining multicast group [18-2](#)
- join messages [18-2](#)
- leave processing, enabling [18-9](#)
- leaving multicast group [18-4](#)
- multicast reachability [31-27](#)
- overview [31-2](#)
- queries [18-3](#)
- support for [1-3](#)

Version 1

- changing to Version 2 [31-29](#)
- described [31-3](#)

Version 2

- changing to Version 1 [31-29](#)
- described [31-3](#)
- maximum query response time value [31-31](#)
- pruning groups [31-31](#)
- query timeout value [31-31](#)

IGMP filtering

- configuring [18-19](#)
- default configuration [18-19](#)
- described [18-19](#)
- monitoring [18-22](#)
- support for [1-3](#)

IGMP groups, setting the maximum number [18-21](#)

IGMP profile

- applying [18-20](#)
- configuration mode [18-19](#)
- configuring [18-20](#)

IGMP snooping

- and address aliasing [18-2](#)
- and stack changes [18-5](#)
- configuring [18-5](#)
- default configuration [18-5](#)
- definition [18-2](#)
- enabling and disabling [18-6](#)
- global configuration [18-6](#)
- Immediate Leave [18-4](#)
- in the switch stack [18-5](#)

IGMP snooping (continued)

- method [18-6](#)
- monitoring [18-10](#)
- support for [1-3](#)
- VLAN configuration [18-6](#)

IGP [29-30](#)

IGRP

- advertisements [29-25](#)
- alternate routes [29-26](#)
- configuring [29-27](#)
- default configuration [29-26](#)
- described [29-25](#)
- exterior routes [29-25](#)
- flash updates [29-26](#)
- interior routes [29-25](#)
- load balancing [29-26](#)
- poison-reverse updates [29-26](#)
- split horizon [29-29](#)
- support for [1-8](#)
- system routes [29-25](#)
- traffic sharing [29-27](#)
- unequal-cost load balancing [29-26](#)

Immediate-Leave, IGMP [18-4](#)

initial configuration

- defaults [1-9](#)
- See also hardware installation guide

interaction modes, CMS [3-25](#)

interface

- number [11-7](#)
- range macros [11-10](#)

interface command [11-6, 11-7](#)interface configuration mode [2-3](#)

interfaces

- configuration guidelines [11-13](#)
- configuring [11-7](#)
- configuring duplex mode [11-13](#)
- configuring speed [11-13](#)
- counters, clearing [11-22](#)
- described [11-17](#)

- interfaces (continued)
 - descriptive name, adding [11-17](#)
 - displaying information about [11-21](#)
 - flow control [11-15](#)
 - management [1-4](#)
 - monitoring [11-21](#)
 - naming [11-17](#)
 - physical, identifying [11-6](#)
 - range of [11-8](#)
 - restarting [11-22](#)
 - shutting down [11-22](#)
 - supported [11-6](#)
 - types of [11-1](#)
- interfaces range macro command [11-10](#)
- interface types [11-6](#)
- Interior Gateway Protocol
 - See IGP
- Interior Gateway Routing Protocol
 - See IGRP
- interior routes, IGRP [29-25](#)
- internal BGP
 - See IBGP
- internal neighbors, BGP [29-49](#)
- Internet Control Message Protocol
 - See ICMP
- Internet Group Management Protocol
 - See IGMP
- Inter-Switch Link
 - See ISL
- inter-VLAN routing [1-8, 29-2](#)
- Intrusion Detection System
 - See IDS
- inventory, cluster [6-22](#)
- IOS File System
 - See IFS
- ip access group command [26-20](#)
- IP ACLs
 - applying to an interface [26-19](#)
 - extended, creating [26-10](#)
 - for QoS classification [27-7](#)
 - implicit deny [26-9, 26-13, 26-15](#)
 - implicit masks [26-9](#)
 - logging [26-15](#)
 - named [26-14](#)
 - standard, creating [26-9](#)
 - undefined [26-20](#)
 - virtual terminal lines, setting on [26-18](#)
- IP addresses
 - candidate or member [6-4, 6-14](#)
 - classes of [29-6](#)
 - cluster access [6-2](#)
 - command switch [6-3, 6-12, 6-14](#)
 - default configuration [29-5](#)
 - discovering [7-28](#)
 - entering in browser window [3-2](#)
 - for IP routing [29-5](#)
 - MAC address association [29-9](#)
 - monitoring [29-18](#)
 - redundant clusters [6-12](#)
 - standby command switch [6-12, 6-14](#)
 - See also IP information
- IP broadcast address [29-16](#)
- ip cef distributed command [29-66](#)
- IP directed broadcasts [29-14](#)
- ip igmp profile command [18-19](#)
- IP information
 - assigned
 - manually [4-9](#)
 - through DHCP-based autoconfiguration [4-3](#)
 - default configuration [4-3](#)

IP multicast routing

addresses

- all-hosts [31-3](#)
- all-multicast-routers [31-3](#)
- host group address range [31-3](#)

administratively-scoped boundaries, described [31-35](#)

and IGMP snooping [18-2](#)

Auto-RP

- adding to an existing sparse-mode cloud [31-14](#)
- benefits of [31-14](#)
- clearing the cache [31-51](#)
- configuration guidelines [31-10](#)
- filtering incoming RP announcement messages [31-17](#)
- overview [31-5](#)
- preventing candidate RP spoofing [31-17](#)
- preventing join messages to false RPs [31-16](#)
- setting up in a new internetwork [31-14](#)
- using with BSR [31-22](#)

bootstrap router

- configuration guidelines [31-10](#)
- configuring candidate BSRs [31-20](#)
- configuring candidate RPs [31-21](#)
- defining the IP multicast boundary [31-19](#)
- defining the PIM domain border [31-18](#)
- overview [31-5](#)
- using with Auto-RP [31-22](#)

Cisco implementation [31-2](#)

configuring

- basic multicast routing [31-10](#)
- IP multicast boundary [31-35](#)

default configuration [31-9](#)

enabling

- multicast forwarding [31-11](#)
- PIM mode [31-11](#)

group-to-RP mappings

- Auto-RP [31-5](#)
- BSR [31-5](#)

IP multicast routing (continued)

MBONE

- deleting sdr cache entries [31-51](#)
- described [31-34](#)
- displaying sdr cache [31-52](#)
- enabling sdr listener support [31-34](#)
- limiting DVMRP routes advertised [31-46](#)
- limiting sdr cache entry lifetime [31-35](#)
- SAP packets for conference session announcement [31-34](#)
- Session Directory (sdr) tool, described [31-34](#)

monitoring

- packet rate loss [31-52](#)
- peering devices [31-52](#)
- tracing a path [31-52](#)

multicast forwarding, described [31-6](#)

PIMv1 and PIMv2 interoperability [31-9](#)

protocol interaction [31-2](#)

reverse path check (RPF) [31-6](#)

routing table

- deleting [31-51](#)
- displaying [31-52](#)

RP

- assigning manually [31-12](#)
- configuring Auto-RP [31-14](#)
- configuring PIMv2 BSR [31-18](#)
- monitoring mapping information [31-23](#)
- using Auto-RP and BSR [31-22](#)

stacking

- stack master functions [31-8](#)
- stack member functions [31-8](#)

statistics, displaying system and network [31-51](#)

See also CGMP

See also DVMRP

See also IGMP

See also PIM

- IP phones
 - and QoS [14-1](#)
 - automatic classification and queuing [27-18](#)
 - configuring [14-4](#)
 - ensuring port security with QoS [27-34](#)
 - trusted boundary for QoS [27-34](#)
- IP precedence [27-2](#)
- IP-precedence-to-DSCP map for QoS [27-48](#)
- IP protocols
 - in ACLs [26-11](#)
 - routing [1-8](#)
- IP routes, monitoring [29-81](#)
- IP routing
 - connecting interfaces with [11-6](#)
 - enabling [29-19](#)
- IP unicast routing
 - address resolution [29-9](#)
 - administrative distances [29-68, 29-79](#)
 - ARP [29-9](#)
 - assigning IP addresses to Layer 3 interfaces [29-6](#)
 - authentication keys [29-80](#)
 - broadcast
 - address [29-16](#)
 - flooding [29-17](#)
 - packets [29-14](#)
 - storms [29-14](#)
 - classless routing [29-7](#)
 - configuring static routes [29-68](#)
 - default
 - addressing configuration [29-5](#)
 - gateways [29-12](#)
 - networks [29-69](#)
 - routes [29-69](#)
 - routing [29-2](#)
 - directed broadcasts [29-14](#)
 - dynamic routing [29-3](#)
 - enabling [29-19](#)
 - EtherChannel Layer 3 interface [29-4](#)
 - IGP [29-30](#)
 - IRDP
 - configuring [29-13](#)
 - definition [29-13](#)
 - support for [1-8](#)
 - ISL
 - and trunk ports [11-3](#)
 - encapsulation [1-6, 12-16](#)
 - trunk mode [3-10](#)
- IP unicast routing (continued)
 - inter-VLAN [29-2](#)
 - IP addressing
 - classes [29-6](#)
 - configuring [29-5](#)
 - IRDP [29-13](#)
 - Layer 3 interfaces [29-4](#)
 - MAC address and IP address [29-9](#)
 - passive interfaces [29-77](#)
 - protocols
 - distance-vector [29-3](#)
 - dynamic [29-3](#)
 - link-state [29-3](#)
 - proxy ARP [29-9](#)
 - redistribution [29-70](#)
 - reverse address resolution [29-9](#)
 - routed ports [29-4](#)
 - static routing [29-2](#)
 - steps to configure [29-5](#)
 - subnet mask [29-6](#)
 - subnet zero [29-7](#)
 - supernet [29-7](#)
 - UDP [29-16](#)
 - with SVIs [29-4](#)
 - See also BGP
 - See also EIGRP
 - See also IGRP
 - See also OSPF
 - See also RIP

J

- Java Plug-in [3-2](#)
- Java plug-in configuration [3-1](#)
- join messages, IGMP [18-2](#)

K

KDC

described [9-32](#)

See also Kerberos

Kerberos

authenticating to

boundary switch [9-35](#)

KDC [9-35](#)

network services [9-35](#)

configuration examples [9-32](#)

configuring [9-36](#)

credentials [9-32](#)

cryptographic software image [9-32](#)

described [9-32](#)

KDC [9-32](#)

operation [9-34](#)

realm [9-33](#)

server [9-33](#)

support for [1-7](#)

switch as trusted third party [9-32](#)

terms [9-33](#)

TGT [9-34](#)

tickets [9-32](#)

key distribution center

See KDC

L

LACP

See EtherChannel

Layer 2 frames, classification with CoS [27-2](#)Layer 2 interfaces, default configuration [11-12](#)

Layer 2 traceroute

and ARP [34-16](#)

and CDP [34-16](#)

described [34-15](#)

IP addresses and subnets [34-16](#)

MAC addresses and VLANs [34-16](#)

multicast traffic [34-16](#)

multiple devices on a port [34-16](#)

supported switches [34-15](#)

unicast traffic [34-15](#)

usage guidelines [34-16](#)

Layer 2 trunks [12-17](#)Layer 3 features [1-8](#)

Layer 3 interfaces

assigning IP addresses to [29-6](#)

changing from Layer 2 mode [29-6](#)

types of [29-4](#)

Layer 3 packets, classification methods [27-2](#)leave processing, IGMP [18-9](#)

LEDs

port [3-9, 3-10](#)

port modes [3-9](#)

RPS [3-8](#)

legend, CMS icons and labels [3-20](#)line configuration mode [2-3](#)

Link Aggregation Control Protocol

See EtherChannel

See LACP

link information [3-14](#)link pop-up menu, Topology view [3-22](#)links, unidirectional [21-1](#)link state advertisements (LSAs) [29-34](#)link-state protocols [29-3](#)lists, CMS [3-29](#)load balancing, IGRP [29-26](#)logging messages, ACL [26-10](#)Logical Link Content window [3-23](#)

login authentication
 with RADIUS [9-23](#)
 with TACACS+ [9-14](#)

login banners [7-19](#)

log messages

See system message logging

Long-Reach Ethernet (LRE) technology [1-12, 1-20](#)

loop guard

described [17-11](#)

enabling [17-18](#)

support for [1-5](#)

M

MAC addresses

aging time [7-23](#)

and VLAN association [7-23](#)

building the address table [7-22](#)

default configuration [7-23](#)

discovering [7-28](#)

displaying [7-27](#)

dynamic

learning [7-22](#)

removing [7-24](#)

in ACLs [26-26](#)

IP address association [29-9](#)

static

adding [7-27](#)

characteristics of [7-26](#)

removing [7-27](#)

MAC address notification, support for [1-8](#)

MAC address-to-VLAN mapping [12-28](#)

MAC extended access lists

applying to Layer 2 interfaces [26-28](#)

configuring for QoS [27-39](#)

creating [26-26](#)

defined [26-26](#)

for QoS classification [27-5](#)

manageability features [1-4](#)

management access

in-band

browser session [1-4](#)

CLI session [1-4](#)

SNMP [1-4](#)

out-of-band console port connection [1-4](#)

management options

benefits

clustering [1-3](#)

CMS [1-2](#)

switch stacks [1-2](#)

CLI [2-1](#)

CMS [3-1](#)

overview [1-4](#)

management VLAN

considerations in switch clusters [6-8](#)

discovery through different management VLANs [6-8](#)

mapping tables for QoS

configuring

CoS-to-DSCP [27-47](#)

DSCP [27-47](#)

DSCP-to-CoS [27-50](#)

DSCP-to-DSCP-mutation [27-51](#)

IP-precedence-to-DSCP [27-48](#)

policed-DSCP [27-49](#)

described [27-10](#)

marking

action in policy map [27-42](#)

action with aggregate policers [27-45](#)

described [27-3, 27-8](#)

matching, ACLs [26-7](#)

maximum aging time

MSTP [16-22](#)

STP [15-23](#)

maximum hop count, MSTP [16-22](#)

maximum-paths command [29-52, 29-67](#)

membership mode, VLAN port [3-10, 12-3](#)

- member switch
 - adding [6-19](#)
 - automatic discovery [6-5](#)
 - defined [6-2](#)
 - managing [6-24](#)
 - passwords [6-14](#)
 - recovering from lost connectivity [34-12](#)
 - requirements [6-4](#)
 - See also candidate switch, cluster standby group, and standby command switch
- menu bar
 - described [3-16](#)
 - variations [3-16](#)
- messages
 - logging ACL violations [26-15](#)
 - system [3-19](#)
 - to users through banners [7-19](#)
- metrics, in BGP [29-53](#)
- metric translations, between routing protocols [29-74](#)
- MIBs
 - accessing files with FTP [A-3](#)
 - location of files [A-3](#)
 - overview [25-1](#)
 - SNMP interaction with [25-5](#)
 - supported [A-1](#)
- mini-point-of-presence
 - See POP
- mirroring traffic for analysis [22-1](#)
- mismatches, autonegotiation [34-12](#)
- Mode button [3-9](#)
- modes
 - port [3-9](#)
 - VLAN port membership [3-10](#)
- Modify button [3-29](#)
- module number [11-7](#)
- monitoring
 - access groups [26-41](#)
 - ACL configuration [26-41](#)
 - BGP [29-64](#)
 - cables for unidirectional links [21-1](#)
 - CDP [20-5](#)
 - CEF [29-67](#)
 - EIGRP [29-44](#)
 - fallback bridging [33-11](#)
 - features [1-8](#)
 - HSRP [30-10](#)
 - IGMP
 - filters [18-22](#)
 - snooping [18-10](#)
 - interfaces [11-21](#)
 - IP
 - address tables [29-18](#)
 - multicast routing [31-50](#)
 - routes [29-81](#)
 - MSDP peers [32-19](#)
 - multicast router interfaces [18-11](#)
 - MVR [18-18](#)
 - network traffic for analysis with probe [22-2](#)
 - OSPF [29-38](#)
 - port
 - blocking [19-15](#)
 - protection [19-15](#)
 - RP mapping information [31-23](#)
 - source-active messages [32-19](#)
 - speed and duplex mode [11-14](#)
 - traffic flowing among switches [23-1](#)
 - traffic suppression [19-15](#)
 - VLAN
 - filters [26-41](#)
 - maps [26-41](#)
 - VLANs [12-16](#)
 - VMPS [12-33](#)
 - VTP [13-16](#)

MSDP

- benefits of [32-3](#)
- clearing MSDP connections and statistics [32-19](#)
- controlling source information
 - forwarded by switch [32-12](#)
 - originated by switch [32-8](#)
 - received by switch [32-14](#)
- default configuration [32-4](#)
- dense-mode regions
 - sending SA messages to [32-17](#)
 - specifying the originating address [32-18](#)
- filtering
 - incoming SA messages [32-14](#)
 - SA messages to a peer [32-12](#)
 - SA requests from a peer [32-11](#)
- join latency, defined [32-6](#)
- meshed groups
 - configuring [32-16](#)
 - defined [32-16](#)
- originating address, changing [32-18](#)
- overview [32-1](#)
- peer-RPF flooding [32-2](#)
- peers
 - configuring a default [32-4](#)
 - monitoring [32-19](#)
 - peering relationship, overview [32-1](#)
 - requesting source information from [32-8](#)
 - shutting down [32-16](#)
- source-active messages
 - caching [32-6](#)
 - clearing cache entries [32-19](#)
 - defined [32-2](#)
 - filtering from a peer [32-11](#)
 - filtering incoming [32-14](#)
 - filtering to a peer [32-12](#)
 - limiting data with TTL [32-14](#)
 - monitoring [32-19](#)
 - restricting advertised sources [32-9](#)
- support for [1-8](#)

MSTP

- boundary ports
 - configuration guidelines [16-14](#)
 - described [16-5](#)
- BPDU filtering
 - described [17-3](#)
 - enabling [17-15](#)
- BPDU guard
 - described [17-3](#)
 - enabling [17-14](#)
- CIST, described [16-3](#)
- configuration guidelines [16-13, 17-12](#)
- configuring
 - forward-delay time [16-21](#)
 - hello time [16-20](#)
 - link type for rapid convergence [16-23](#)
 - maximum aging time [16-22](#)
 - maximum hop count [16-22](#)
 - MST region [16-14](#)
 - path cost [16-19](#)
 - port priority [16-18](#)
 - root switch [16-15](#)
 - secondary root switch [16-17](#)
 - switch priority [16-20](#)
- CST
 - defined [16-3](#)
 - operations between regions [16-4](#)
- default configuration [16-13](#)
- default optional feature configuration [17-12](#)
- displaying status [16-24](#)
- enabling the mode [16-14](#)
- extended system ID
 - effects on root switch [16-15](#)
 - effects on secondary root switch [16-17](#)
 - unexpected behavior [16-16](#)
- instances supported [15-10](#)
- interface state, blocking to forwarding [17-2](#)
- interoperability and compatibility among modes [15-11](#)

MSTP (continued)

interoperability with 802.1D

described [16-6](#)

restarting migration process [16-23](#)

IST

defined [16-3](#)

master [16-3](#)

operations within a region [16-3](#)

loop guard

described [17-11](#)

enabling [17-18](#)

mapping VLANs to MST instance [16-14](#)

MST region

CIST [16-3](#)

configuring [16-14](#)

described [16-2](#)

hop-count mechanism [16-5](#)

IST [16-3](#)

supported spanning-tree instances [16-2](#)

optional features supported [1-5](#)

overview [16-2](#)

Port Fast

described [17-2](#)

enabling [17-13](#)

preventing root switch selection [17-10](#)

root guard

described [17-10](#)

enabling [17-18](#)

root switch

configuring [16-16](#)

effects of extended system ID [16-15](#)

unexpected behavior [16-16](#)

shutdown Port Fast-enabled port [17-3](#)

stack changes, effects of [16-6](#)

status, displaying [16-24](#)

multicast groups

Immediate Leave [18-4](#)

joining [18-2](#)

leaving [18-4](#)

static joins [18-9](#)

multicast packets

ACLs on [26-40](#)

blocking [19-6](#)

multicast router interfaces, monitoring [18-11](#)

multicast router ports, adding [18-8](#)

Multicast Source Discovery Protocol

See MSDP

multicast storm-control command [19-3](#)

multicast storms [19-1](#)

Multicast VLAN Registration

See MVR

multiple links in Topology view [3-23](#)

Multiple Spanning Tree Protocol

See MSTP

MVR

and address aliasing [18-15](#)

configuring interfaces [18-17](#)

default configuration [18-15](#)

described [18-12](#)

in the switch stack [18-14](#)

modes [18-16](#)

monitoring [18-18](#)

setting global parameters [18-15](#)

support for [1-3](#)

N

named IP ACLs [26-14](#)

native VLAN

configuring [12-23](#)

default [12-23](#)

- negotiate trunk mode [3-11](#)
 - neighbor discovery/recovery, EIGRP [29-39](#)
 - neighboring devices, types of [3-14](#)
 - neighbors, BGP [29-59](#)
 - network configuration examples
 - cost-effective wiring closet [1-13](#)
 - high-performance wiring closet [1-13](#)
 - increasing network performance [1-11](#)
 - large network [1-18](#)
 - providing network services [1-12](#)
 - redundant Gigabit backbone [1-14](#)
 - small to medium-sized network [1-17](#)
 - network design
 - performance [1-11](#)
 - services [1-12](#)
 - network management
 - CDP [20-1](#)
 - RMON [23-1](#)
 - SNMP [25-1](#)
 - Network Time Protocol
 - See NTP
 - no commands [2-4](#)
 - non-IP traffic filtering [26-26](#)
 - nontrunking mode [12-18](#)
 - normal-range VLANs
 - configuration modes [12-6](#)
 - defined [12-1](#)
 - no switchport command [11-3](#)
 - note, described [xxxiv](#)
 - not-so-stubby areas
 - See NSSA
 - NSSA, OSPF [29-34](#)
 - NTP
 - associations
 - authenticating [7-5](#)
 - defined [7-2](#)
 - enabling broadcast messages [7-7](#)
 - peer [7-6](#)
 - server [7-6](#)
 - default configuration [7-4](#)
 - displaying the configuration [7-11](#)
 - overview [7-2](#)
 - restricting access
 - creating an access group [7-9](#)
 - disabling NTP services per interface [7-10](#)
 - source IP address, configuring [7-10](#)
 - stratum [7-2](#)
 - support for [1-4](#)
 - synchronizing devices [7-6](#)
 - time
 - services [7-2](#)
 - synchronizing [7-2](#)
-
- O**
- OK button [3-29](#)
 - online help [3-27](#)
 - Open Shortest Path First
 - See OSPF
 - optimizing system resources [8-1](#)
 - options, management [1-4](#)
 - OSPF
 - area parameters, configuring [29-34](#)
 - configuring [29-32](#)

OSPF (continued)

- default configuration
 - metrics [29-35](#)
 - route [29-35](#)
 - settings [29-31](#)
 - described [29-30](#)
 - interface parameters, configuring [29-33](#)
 - LSA group pacing [29-37](#)
 - monitoring [29-38](#)
 - router IDs [29-37](#)
 - route summarization [29-35](#)
 - support for [1-8](#)
 - virtual links [29-35](#)
- out-of-profile markdown [1-7](#)
- overheating indication, switch [3-6](#)

P

- packet modification, with QoS [27-17](#)

PAgP

See EtherChannel

- parallel paths, in routing tables [29-67](#)

passive interfaces

- configuring [29-77](#)
- OSPF [29-35](#)

passwords

- default configuration [9-2](#)
- disabling recovery of [9-5](#)
- encrypting [9-4](#)
- for security [1-6](#)
- in clusters [6-15, 6-19](#)
- in CMS [3-30](#)
- overview [9-1](#)
- recovery of [34-4](#)

passwords (continued)

- setting
 - enable [9-3](#)
 - enable secret [9-4](#)
 - Telnet [9-6](#)
 - with usernames [9-7](#)
 - VTP domain [13-8](#)
- path cost
- MSTP [16-19](#)
 - STP [15-20](#)
- PBR
- defined [29-74](#)
 - enabling [29-76](#)
 - fast-switched policy-based routing [29-77](#)
 - local policy-based routing [29-77](#)
- PC (passive command switch) [6-11, 6-21](#)
- peers, BGP [29-59](#)
- performance, network design [1-11](#)
- performance features [1-3](#)
- per-VLAN spanning-tree plus
- See PVST+
- physical ports [11-2](#)
- PIM
- default configuration [31-9](#)
 - dense mode
 - overview [31-4](#)
 - rendezvous point (RP), described [31-4](#)
 - RPF lookups [31-7](#)
 - displaying neighbors [31-52](#)
 - enabling a mode [31-11](#)
 - overview [31-3](#)
 - router-query message interval, modifying [31-26](#)
 - shared tree and source tree, overview [31-23](#)
 - shortest path tree, delaying the use of [31-25](#)

- PIM (continued)
 - sparse mode
 - join messages and shared tree [31-4](#)
 - overview [31-4](#)
 - prune messages [31-5](#)
 - RPF lookups [31-7](#)
 - support for [1-8](#)
 - versions
 - interoperability [31-9](#)
 - troubleshooting interoperability problems [31-23](#)
 - v2 improvements [31-4](#)
- PIM-DVMRP, as snooping method [18-7](#)
- ping
 - character output description [34-14](#)
 - executing [34-14](#)
 - overview [34-13](#)
- poison-reverse updates, IGRP [29-26](#)
- policed-DSCP map for QoS [27-49](#)
- policers
 - configuring
 - for each matched traffic class [27-42](#)
 - for more than one traffic class [27-45](#)
 - described [27-3](#)
 - displaying [27-64](#)
 - number of [27-29](#)
 - types of [27-8](#)
- policing
 - described [27-3](#)
 - token-bucket algorithm [27-9](#)
- policy-based routing
 - See PBR
- policy maps for QoS
 - characteristics of [27-42](#)
 - configuring [27-42](#)
 - described [27-7](#)
 - displaying [27-64](#)
- POP [1-20](#)
- port ACLs
 - defined [26-2](#)
 - types of [26-4](#)
- Port Aggregation Protocol
 - See EtherChannel
 - See PAgP
- port-based authentication
 - authentication server
 - defined [10-2](#)
 - RADIUS server [10-2](#)
 - client, defined [10-2](#)
 - configuration guidelines [10-12](#)
 - configuring
 - 802.1X authentication [10-13](#)
 - guest VLAN [10-19](#)
 - host mode [10-18](#)
 - manual re-authentication of a client [10-16](#)
 - periodic re-authentication [10-15](#)
 - quiet period [10-16](#)
 - RADIUS server [10-15](#)
 - RADIUS server parameters on the switch [10-14](#)
 - switch-to-client frame-retransmission number [10-17](#)
 - switch-to-client retransmission time [10-17](#)
 - default configuration [10-11](#)
 - described [10-1](#)
 - device roles [10-2](#)
 - displaying statistics [10-20](#)
 - EAPOL-start frame [10-3](#)
 - EAP-request/identity frame [10-3](#)
 - EAP-response/identity frame [10-3](#)
 - encapsulation [10-2](#)
 - guest VLAN
 - configuration guidelines [10-8](#)
 - described [10-8](#)
 - initiation and message exchange [10-3](#)
 - method lists [10-13](#)

- port-based authentication (continued)
 - multiple-hosts mode, described [10-18](#)
- per-user ACLs
 - AAA authorization [10-13](#)
 - configuration tasks [10-9](#)
 - described [10-9](#)
 - RADIUS server attributes [10-9](#)
- ports
 - authorization state and dot1x port-control command [10-4](#)
 - authorized and unauthorized [10-4](#)
 - voice VLAN [10-6](#)
- port security
 - and voice VLAN [10-6](#)
 - described [10-6](#)
 - interactions [10-6](#)
 - multiple-hosts mode [10-18](#)
- resetting to default values [10-20](#)
- stack changes, effects of [10-10](#)
- statistics, displaying [10-20](#)
- switch
 - as proxy [10-2](#)
 - RADIUS client [10-2](#)
- topologies, supported [10-5](#)
- upgrading from a previous release [10-12](#)
- VLAN assignment
 - AAA authorization [10-13](#)
 - characteristics [10-7](#)
 - configuration tasks [10-8](#)
 - described [10-7](#)
- voice VLAN
 - described [10-6](#)
 - PVID [10-6](#)
 - VVID [10-6](#)
- port blocking [1-3, 19-5](#)
- port-channel
 - See EtherChannel
- Port Fast
 - described [17-2](#)
 - enabling [17-13](#)
 - mode, spanning tree [12-30](#)
 - support for [1-5](#)
- port icons, Front Panel view [3-7](#)
- port LEDs
 - described [3-10](#)
 - DUPLX [3-9](#)
 - port modes [3-9](#)
 - SPEED [3-9](#)
 - STACK [3-9](#)
 - STAT [3-9](#)
- port membership modes, VLAN [3-10, 12-3](#)
- port modes
 - described [3-9](#)
 - LEDs [3-9](#)
- port pop-up menu, Front Panel view [3-22](#)
- port priority
 - MSTP [16-18](#)
 - STP [15-19](#)
- ports
 - 802.1Q trunk [3-11](#)
 - access [11-2](#)
 - blocking [19-5](#)
 - dynamic access [3-10, 12-4](#)
 - ISL trunk [3-10](#)
 - negotiate trunk [3-11](#)
 - protected [19-4](#)
 - routed [11-3](#)
 - secure [19-7](#)
 - static-access [3-10, 12-3, 12-11](#)
 - switch [11-2](#)
 - trunks [12-3, 12-16](#)
 - VLAN assignments [12-11](#)

- port security
 - aging [19-13](#)
 - and QoS trusted boundary [27-34](#)
 - and stacking [19-14](#)
 - configuring [19-10](#)
 - default configuration [19-9](#)
 - described [19-7](#)
 - displaying [19-15](#)
 - on trunk ports [19-11](#)
 - sticky learning [19-8](#)
 - violations [19-8](#)
 - with other features [19-9](#)
 - port-shutdown response, VMPS [12-28](#)
 - preferential treatment of traffic
 - See QoS
 - prefix lists, BGP [29-56](#)
 - preventing unauthorized access [9-1](#)
 - priority
 - HSRP [30-6](#)
 - overriding CoS [14-5](#)
 - trusting CoS [14-5](#)
 - private VLAN edge ports
 - See protected ports
 - privileged EXEC mode [2-2](#)
 - privilege levels
 - changing the default for lines [9-9](#)
 - command switch [6-24](#)
 - exiting [9-10](#)
 - logging into [9-10](#)
 - mapping on member switches [6-24](#)
 - overview [9-2, 9-8](#)
 - setting a command with [9-8](#)
 - protected ports [1-6, 19-4](#)
 - protocol-dependent modules, EIGRP [29-40](#)
 - Protocol-Independent Multicast Protocol
 - See PIM
 - proxy ARP
 - configuring [29-11](#)
 - definition [29-9](#)
 - with IP routing disabled [29-12](#)
 - pruning, VTP
 - enabling [13-14](#)
 - enabling on a port [12-23](#)
 - examples [13-5](#)
 - overview [13-4](#)
 - pruning-eligible list
 - changing [12-23](#)
 - for VTP pruning [13-5](#)
 - VLANs [13-14](#)
 - publications for products, technologies, and network solutions [xxxvii](#)
 - PVST+
 - 802.1Q trunking interoperability [15-11](#)
 - described [15-10](#)
 - instances supported [15-10](#)
-
- ## Q
- QoS
 - auto-QoS
 - categorizing traffic [27-18](#)
 - configuration and defaults display [27-26](#)
 - configuration guidelines [27-22](#)
 - described [27-18](#)
 - disabling [27-23](#)
 - displaying generated commands [27-23](#)
 - displaying the initial configuration [27-26](#)
 - effects on running configuration [27-22](#)
 - egress queue defaults [27-19](#)
 - enabling for VoIP [27-22](#)
 - example configuration [27-24](#)
 - ingress queue defaults [27-19](#)
 - list of generated commands [27-20](#)

QoS (continued)

- basic model [27-3](#)
- classification
 - class maps, described [27-7](#)
 - defined [27-3](#)
 - flowchart [27-6](#)
 - forwarding treatment [27-3](#)
 - in frames and packets [27-2](#)
 - IP ACLs, described [27-5, 27-7](#)
 - MAC ACLs, described [27-5, 27-7](#)
 - options for IP traffic [27-5](#)
 - options for non-IP traffic [27-5](#)
 - policy maps, described [27-7](#)
 - trust DSCP, described [27-5](#)
 - trusted CoS, described [27-5](#)
 - trust IP precedence, described [27-5](#)
- class maps
 - configuring [27-40](#)
 - displaying [27-64](#)
- configuration guidelines
 - auto-QoS [27-22](#)
 - standard QoS [27-29](#)
- configuring
 - aggregate policers [27-45](#)
 - auto-QoS [27-18](#)
 - default port CoS value [27-33](#)
 - DSCP maps [27-47](#)
 - DSCP trust states bordering another domain [27-35](#)
 - egress queue characteristics [27-57](#)
 - ingress queue characteristics [27-52](#)
 - IP extended ACLs [27-38](#)
 - IP standard ACLs [27-37](#)
 - MAC ACLs [27-39](#)
 - policy maps [27-42](#)
 - port trust states within the domain [27-31](#)
 - trusted boundary [27-34](#)
- default auto configuration [27-18](#)
- default standard configuration [27-27](#)
- displaying statistics [27-64](#)

QoS (continued)

- egress queues
 - allocating buffer space [27-57](#)
 - buffer allocation scheme, described [27-15](#)
 - configuring shaped weights for SRR [27-61](#)
 - configuring shared weights for SRR [27-62](#)
 - described [27-4](#)
 - displaying the threshold map [27-60](#)
 - flowchart [27-15](#)
 - mapping DSCP or CoS values [27-59](#)
 - scheduling, described [27-4](#)
 - setting WTD thresholds [27-57](#)
 - WTD, described [27-16](#)
- enabling globally [27-30](#)
- flowcharts
 - classification [27-6](#)
 - egress queueing and scheduling [27-15](#)
 - ingress queueing and scheduling [27-13](#)
 - policing and marking [27-9](#)
- implicit deny [27-7](#)
- ingress queues
 - allocating bandwidth [27-55](#)
 - allocating buffer space [27-54](#)
 - buffer and bandwidth allocation, described [27-14](#)
 - configuring shared weights for SRR [27-55](#)
 - configuring the priority queue [27-56](#)
 - described [27-3](#)
 - displaying the threshold map [27-53](#)
 - flowchart [27-13](#)
 - mapping DSCP or CoS values [27-53](#)
 - priority queue, described [27-14](#)
 - scheduling, described [27-3](#)
 - setting WTD thresholds [27-53](#)
 - WTD, described [27-14](#)
- IP phones
 - automatic classification and queueing [27-18](#)
 - detection and trusted settings [27-18, 27-34](#)
- limiting bandwidth on egress interface [27-63](#)

QoS (continued)

mapping tables

CoS-to-DSCP [27-47](#)displaying [27-64](#)DSCP-to-CoS [27-50](#)DSCP-to-DSCP-mutation [27-51](#)IP-precedence-to-DSCP [27-48](#)policed-DSCP [27-49](#)types of [27-10](#)marked-down actions [27-43](#)marking, described [27-3, 27-8](#)overview [27-1](#)packet modification [27-17](#)

policers

configuring [27-43, 27-45](#)described [27-8](#)displaying [27-64](#)number of [27-29](#)types of [27-8](#)policies, attaching to an interface [27-9](#)

policing

described [27-3, 27-8](#)token bucket algorithm [27-9](#)

policy maps

characteristics of [27-42](#)configuring [27-42](#)displaying [27-64](#)QoS label, defined [27-3](#)

queues

configuring egress characteristics [27-57](#)configuring ingress characteristics [27-52](#)location of [27-11](#)SRR, described [27-12](#)WTD, described [27-11](#)rewrites [27-17](#)support for [1-7](#)

QoS (continued)

trust states

bordering another domain [27-35](#)described [27-5](#)trusted device [27-34](#)within the domain [27-31](#)

quality of service

See QoS

queries, IGMP [18-3](#)

R

RADIUS

attributes

vendor-proprietary [9-31](#)vendor-specific [9-29](#)

configuring

accounting [9-28](#)authentication [9-23](#)authorization [9-27](#)communication, global [9-21, 9-29](#)communication, per-server [9-21](#)multiple UDP ports [9-21](#)default configuration [9-20](#)defining AAA server groups [9-25](#)displaying the configuration [9-31](#)identifying the server [9-21](#)in clusters [6-17](#)limiting the services to the user [9-27](#)method list, defined [9-20](#)operation of [9-19](#)overview [9-18](#)suggested network environments [9-18](#)support for [1-7](#)tracking services accessed by user [9-28](#)

range

macro [11-10](#)of interfaces [11-8](#)rapid convergence [16-8](#)

- rapid per-VLAN spanning-tree plus
 - See rapid PVST+
- rapid PVST+
 - 802.1Q trunking interoperability [15-11](#)
 - described [15-10](#)
 - instances supported [15-10](#)
- Rapid Spanning Tree Protocol
 - See RSTP
- RARP [29-9](#)
- rcommand command [6-24](#)
- RCP
 - configuration files
 - downloading [B-18](#)
 - overview [B-17](#)
 - preparing the server [B-17](#)
 - uploading [B-19](#)
 - image files
 - deleting old image [B-33](#)
 - downloading [B-32](#)
 - preparing the server [B-30](#)
 - uploading [B-34](#)
- reconfirmation interval, VMPS, changing [12-32](#)
- recovery procedures [34-1](#)
- redundancy
 - EtherChannel [28-2](#)
 - HSRP [30-1](#)
 - STP
 - backbone [15-8](#)
 - multidrop backbone [17-5](#)
 - path cost [12-26](#)
 - port priority [12-24](#)
- redundant clusters
 - See cluster standby group
- redundant links and UplinkFast [17-16](#)
- redundant power system
 - See RPS
- Refresh button [3-29](#)
- reliable transport protocol, EIGRP [29-39](#)
- reloading software [4-17](#)
- Remote Authentication Dial-In User Service
 - See RADIUS
- Remote Copy Protocol
 - See RCP
- Remote Network Monitoring
 - See RMON
- Remote SPAN
 - See RSPAN [22-1](#)
- resets, in BGP [29-51](#)
- resetting a UDLD-shutdown interface [21-5](#)
- restricting access
 - NTP services [7-8](#)
 - overview [9-1](#)
 - passwords and privilege levels [9-2](#)
 - RADIUS [9-18](#)
 - TACACS+ [9-10](#)
- retry count, VMPS, changing [12-32](#)
- reverse address resolution [29-9](#)
- Reverse Address Resolution Protocol
 - See RARP
- RFC
 - 1058, RIP [29-20](#)
 - 1112, IP multicast and IGMP [18-2](#)
 - 1157, SNMPv1 [25-2](#)
 - 1163, BGP [29-45](#)
 - 1166, IP addresses [29-6](#)
 - 1253, OSPF [29-30](#)
 - 1267, BGP [29-45](#)
 - 1305, NTP [7-2](#)
 - 1587, NSSAs [29-30](#)
 - 1757, RMON [23-2](#)
 - 1771, BGP [29-45](#)
 - 1901, SNMPv2C [25-2](#)
 - 1902 to 1907, SNMPv2 [25-2](#)
 - 2236, IP multicast and IGMP [18-2](#)
 - 2273-2275, SNMPv3 [25-2](#)

RIP

- advertisements [29-20](#)
- authentication [29-23](#)
- configuring [29-21](#)
- default configuration [29-20](#)
- described [29-20](#)
- hop counts [29-20](#)
- split horizon [29-23](#)
- summary addresses [29-23](#)
- support for [1-8](#)

RMON

- default configuration [23-3](#)
- displaying status [23-6](#)
- enabling alarms and events [23-3](#)
- groups supported [23-2](#)
- overview [23-1](#)
- statistics
 - collecting group Ethernet [23-6](#)
 - collecting group history [23-5](#)
- support for [1-8](#)

root guard

- described [17-10](#)
- enabling [17-18](#)
- support for [1-5](#)

root switch

- MSTP [16-15](#)

root switch, STP [15-16](#)route calculation timers, OSPF [29-36](#)route dampening, BGP [29-63](#)routed packets, ACLs on [26-39](#)

routed ports

- configuring [29-4](#)
- defined [11-3](#)
- in switch clusters [6-9](#)
- IP addresses on [11-18, 29-4](#)

route-map command [29-76](#)

route maps

- BGP [29-54](#)
- policy-based routing [29-75](#)

router ACLs

- defined [26-2](#)
- types of [26-3](#)

route reflectors, BGP [29-62](#)router ID, OSPF [29-37](#)route selection, BGP [29-52](#)route summarization, OSPF [29-35](#)

routing

- default [29-2](#)
- dynamic [29-3](#)
- redistribution of information [29-70](#)
- static [29-2](#)

routing domain confederation, BGP [29-61](#)

Routing Information Protocol

- See RIP

routing protocol administrative distances [29-68](#)RPS LED [3-8](#)

RSPAN

- and stack changes [22-10](#)
- characteristics [22-9](#)
- configuration guidelines [22-17](#)
- default configuration [22-11](#)
- destination ports [22-8](#)
- displaying status [22-24](#)
- in a switch stack [22-2](#)
- interaction with other features [22-9](#)
- monitored ports [22-6](#)
- monitoring ports [22-8](#)
- overview [1-8, 22-1](#)
- received traffic [22-5](#)
- session limits [22-11](#)
- sessions
 - creating [22-18](#)
 - defined [22-4](#)
 - limiting source traffic to specific VLANs [22-23](#)
 - specifying monitored ports [22-18](#)
 - with ingress traffic enabled [22-21](#)

- RSPAN (continued)
 - source ports [22-6](#)
 - transmitted traffic [22-6](#)
 - VLAN-based [22-7](#)
- RSTP
 - active topology, determining [16-7](#)
 - BPDU
 - format [16-10](#)
 - processing [16-11](#)
 - designated port, defined [16-7](#)
 - designated switch, defined [16-7](#)
 - interoperability with 802.1D
 - described [16-6](#)
 - restarting migration process [16-23](#)
 - topology changes [16-11](#)
 - overview [16-7](#)
 - port roles
 - described [16-7](#)
 - synchronized [16-9](#)
 - proposal-agreement handshake process [16-8](#)
 - rapid convergence
 - cross-stack rapid convergence [16-9](#)
 - described [16-8](#)
 - edge ports and Port Fast [16-8](#)
 - point-to-point links [16-8, 16-23](#)
 - root ports [16-8](#)
 - root port, defined [16-7](#)
 - See also MSTP
 - running configuration, saving [4-10](#)
- SDM
 - described [8-1](#)
 - switch stack consideration [5-7](#)
 - templates
 - configuring [8-4](#)
 - number of [8-1](#)
 - SDM mismatch mode [5-7, 8-2](#)
 - SDM template
 - aggregator [8-1](#)
 - configuring [8-3](#)
 - desktop [8-1](#)
 - secure MAC addresses
 - and switch stacks [19-14](#)
 - deleting [19-12](#)
 - maximum number of [19-8](#)
 - types of [19-7](#)
 - secure ports
 - and switch stacks [19-14](#)
 - configuring [19-7](#)
 - secure remote connections [9-38](#)
 - Secure Shell
 - See SSH
 - security, port [19-7](#)
 - security features [1-6](#)
 - sequence numbers in log messages [24-8](#)
 - server mode, VTP [13-3](#)
 - service-provider network
 - MSTP and RSTP [16-1](#)
 - set-request operation [25-5](#)
 - setup program, failed command switch replacement [34-9, 34-11](#)
 - severity levels, defining in system messages [24-9](#)
 - SFPs
 - numbering of [11-7](#)
 - security and identification [34-13](#)
 - shaped round robin
 - See SRR
 - show access-lists hw-summary command [26-21](#)
 - show and more command output, filtering [2-9](#)

S

- SC (standby command switch) [6-11, 6-21](#)
- scheduled reloads [4-17](#)

- show cdp traffic command [20-5](#)
- show cluster members command [6-24](#)
- show configuration command [11-17](#)
- show forward command [34-19](#)
- show interfaces command [11-14, 11-17](#)
- show platform forward command [34-19](#)
- show running-config command
 - displaying ACLs [26-19, 26-30, 26-33](#)
 - interface description in [11-17](#)
- shutdown command on interfaces [11-22](#)
- Simple Network Management Protocol
 - See SNMP
- small form-factor pluggable modules
 - See SFPs
- SNAP [20-1](#)
- SNMP
 - accessing MIB variables with [25-5](#)
 - agent
 - described [25-4](#)
 - disabling [25-7](#)
 - authentication level [25-10, 25-11](#)
 - community strings
 - configuring [25-8](#)
 - for cluster switches [25-4](#)
 - overview [25-4](#)
 - configuration examples [25-16](#)
 - default configuration [25-6](#)
 - engine ID [25-7](#)
 - groups [25-7, 25-9](#)
 - host [25-7](#)
 - in-band management [1-4](#)
 - in clusters [6-15](#)
 - informs
 - and trap keyword [25-12](#)
 - described [25-5](#)
 - differences from traps [25-5](#)
 - enabling [25-15](#)
 - limiting access by TFTP servers [25-15](#)
 - limiting system log messages to NMS [24-10](#)
- SNMP (continued)
 - manager functions [1-4, 25-3](#)
 - managing clusters with [6-25](#)
 - MIBs
 - location of [A-3](#)
 - supported [A-1](#)
 - notifications [25-5](#)
 - overview [25-1, 25-5](#)
 - status, displaying [25-17](#)
 - system contact and location [25-15](#)
 - trap manager, configuring [25-14](#)
 - traps
 - described [25-3, 25-5](#)
 - differences from informs [25-5](#)
 - enabling [25-12](#)
 - enabling MAC address notification [7-24](#)
 - overview [25-1, 25-5](#)
 - types of [25-12](#)
 - users [25-7, 25-9](#)
 - versions supported [25-2](#)
- SNMPv1 [25-2](#)
- SNMPv2C [25-2](#)
- SNMPv3 [25-2](#)
- snooping, IGMP [18-2](#)
- software compatibility
 - See stacks, switch
- software images
 - location in Flash [B-21](#)
 - recovery procedures [34-2](#)
 - scheduling reloads [4-17](#)
 - tar file format, described [B-22](#)
 - See also downloading and uploading
- source addresses, in ACLs [26-11](#)
- source-and-destination-IP address based forwarding, EtherChannel [28-8](#)
- source-and-destination MAC address forwarding, EtherChannel [28-8](#)
- source-IP address based forwarding, EtherChannel [28-8](#)
- source-MAC address forwarding, EtherChannel [28-8](#)

SPAN

- and stack changes [22-10](#)
- configuration guidelines [22-11](#)
- default configuration [22-11](#)
- destination ports [22-8](#)
- displaying status [22-24](#)
- interaction with other features [22-9](#)
- monitored ports [22-6](#)
- monitoring ports [22-8](#)
- overview [1-8, 22-1](#)
- received traffic [22-5](#)
- session limits [22-11](#)
- sessions
 - configuring ingress forwarding [22-15, 22-22](#)
 - creating [22-12](#)
 - defined [22-4](#)
 - limiting source traffic to specific VLANs [22-16](#)
 - removing destination (monitoring) ports [22-13](#)
 - specifying monitored ports [22-12](#)
 - with ingress traffic enabled [22-14](#)
- source ports [22-6](#)
- transmitted traffic [22-6](#)
- VLAN-based [22-7](#)
- spanning tree and native VLANs [12-19](#)

Spanning Tree Protocol

See STP

SPAN traffic [22-5](#)speed, configuring on interfaces [11-13](#)

split horizon

IGRP [29-29](#)

RIP [29-23](#)

SRR

configuring

- shaped weights on egress queues [27-61](#)
- shared weights on egress queues [27-62](#)
- shared weights on ingress queues [27-55](#)

SRR (continued)

- described [27-12](#)
- shaped mode [27-12](#)
- shared mode [27-12](#)
- support for [1-7](#)

SSH [1-4](#)

- configuring [9-38](#)
- cryptographic software image [9-38](#)
- described [9-38](#)
- displaying settings [9-38](#)
- switch stack considerations [5-11, 9-38](#)

stack changes, effects on

- 802.1X port-based authentication [10-10](#)
- ACL configuration [26-6](#)
- CDP [20-2](#)
- cross-stack EtherChannel [28-12](#)
- EtherChannel [28-9](#)
- fallback bridging [33-3](#)
- HSRP [30-2](#)
- IGMP snooping [18-5](#)
- IP routing [29-3](#)
- MAC address tables [7-23](#)
- MSTP [16-6](#)
- multicast routing [31-8](#)
- MVR [18-12](#)
- port security [19-14](#)
- SDM template selection [8-2](#)
- SNMP [25-1](#)
- SPAN and RSPAN [22-10](#)
- STP [15-12](#)
- switch clusters [6-15](#)
- system message log [24-2](#)
- VLANs [12-6](#)
- VTP [13-6](#)

- stack master
 - bridge ID (MAC address) [5-6](#)
 - defined [5-1](#)
 - election [5-5](#)
 - re-election [5-5](#)
 - See also stacks, switch
- stack member
 - accessing CLI of specific member [5-16](#)
 - configuring
 - member number [5-15](#)
 - priority value [5-16](#)
 - defined [5-1](#)
 - displaying information of [5-16](#)
 - hot-swappable [5-10](#)
 - number [5-6](#)
 - priority value [5-7](#)
 - See also stacks, switch
- stack member number [11-7](#)
- stack protocol version [5-8](#)
- stacks, switch
 - accessing CLI of specific member [5-16](#)
 - assigning information
 - member number [5-15](#)
 - priority value [5-16](#)
 - benefits [1-2](#)
 - bridge ID [5-6](#)
 - CDP considerations [20-2](#)
 - compatibility, software [5-7](#)
 - configuration file [5-9](#)
 - configuration scenarios [5-12](#)
 - default configuration [5-15](#)
 - default settings [5-15](#)
 - description of [5-1](#)
 - displaying information of [5-16](#)
 - hot-swappable [5-10](#)
 - HSRP considerations [30-2](#)
 - in clusters [6-15](#)
 - MAC address considerations [7-23](#)
 - management connectivity [5-11](#)
 - stacks, switch (continued)
 - managing [5-1](#)
 - membership [5-3](#)
 - merged [5-3](#)
 - MSTP instances supported [15-10](#)
 - multicast routing, stack master and member roles [31-8](#)
 - partitioned [5-3, 34-8](#)
 - See also stack master and stack member
 - software compatibility [5-7](#)
 - software image version [5-8](#)
 - stack protocol version [5-8](#)
 - STP
 - bridge ID [15-3](#)
 - instances supported [15-10](#)
 - root port selection [15-3](#)
 - stack root switch election [15-3](#)
 - system messages
 - hostnames in the display [24-1](#)
 - remotely monitoring [24-2](#)
 - system prompt consideration [7-16](#)
 - system-wide configuration considerations [5-10](#)
 - upgrading [B-35](#)
 - StackWise technology, Cisco [1-2](#)
 - See also stacks, switch
 - Standby Command Configuration window [6-22](#)
 - standby command switch
 - configuring [6-21](#)
 - considerations [6-12](#)
 - defined [6-2](#)
 - priority [6-11](#)
 - requirements [6-3](#)
 - virtual IP address [6-12](#)
 - See also cluster standby group and HSRP
 - standby group, cluster
 - See cluster standby group and HSRP
 - standby ip command [30-5](#)
 - standby router [30-1](#)
 - standby timers, HSRP [30-8](#)

- startup configuration
 - booting
 - manually [4-13](#)
 - specific image [4-14](#)
 - clearing [B-20](#)
 - configuration file
 - automatically downloading [4-12](#)
 - specifying the filename [4-13](#)
 - default boot configuration [4-12](#)
- static access mode [3-10](#)
- static access ports
 - assigning to VLAN [12-11](#)
 - defined [11-3, 12-3](#)
- static addresses
 - See addresses
- static IP routing [1-8](#)
- static MAC addressing [1-6](#)
- static routes, configuring [29-68](#)
- static routing [29-2](#)
- static VLAN membership [12-2](#)
- statistics
 - 802.1X [10-20](#)
 - CDP [20-5](#)
 - interface [11-21](#)
 - IP multicast routing [31-51](#)
 - OSPF [29-38](#)
 - QoS ingress and egress [27-64](#)
 - RMON group Ethernet [23-6](#)
 - RMON group history [23-5](#)
 - SNMP input and output [25-17](#)
 - VTP [13-16](#)
- status bar
 - change notification [3-31](#)
 - error notification [3-31](#)
- sticky learning [19-8](#)
- storm control
 - configuring [19-3](#)
 - described [19-1](#)
 - displaying [19-15](#)
 - support for [1-3](#)
 - thresholds [19-1](#)
- STP
 - 802.1D and bridge ID [15-4](#)
 - 802.1D and multicast addresses [15-9](#)
 - 802.1T and VLAN identifier [15-4](#)
 - accelerating root port selection [17-4](#)
 - BackboneFast
 - described [17-8](#)
 - enabling [17-17](#)
 - BPDU filtering
 - described [17-3](#)
 - enabling [17-15](#)
 - BPDU guard
 - described [17-3](#)
 - enabling [17-14](#)
 - BPDU message exchange [15-3](#)
 - configuration guidelines [15-14, 17-12](#)
 - configuring
 - forward-delay time [15-23](#)
 - hello time [15-22](#)
 - maximum aging time [15-23](#)
 - path cost [15-20](#)
 - port priority [15-19](#)
 - root switch [15-16](#)
 - secondary root switch [15-18](#)
 - spanning-tree mode [15-15](#)
 - switch priority [15-21](#)
 - counters, clearing [15-24](#)

STP (continued)

- cross-stack UplinkFast
 - described [17-5](#)
 - enabling [17-17](#)
- default configuration [15-13](#)
- default optional feature configuration [17-12](#)
- designated port, defined [15-4](#)
- designated switch, defined [15-4](#)
- detecting indirect link failures [17-8](#)
- disabling [15-16](#)
- displaying status [15-24](#)
- extended system ID
 - effects on root switch [15-16](#)
 - effects on the secondary root switch [15-18](#)
 - overview [15-4](#)
 - unexpected behavior [15-16](#)
- features supported [1-5](#)
- inferior BPDU [15-3](#)
- instances supported [15-10](#)
- interface state, blocking to forwarding [17-2](#)
- interface states
 - blocking [15-6](#)
 - disabled [15-7](#)
 - forwarding [15-6, 15-7](#)
 - learning [15-7](#)
 - listening [15-7](#)
 - overview [15-5](#)
- interoperability and compatibility among modes [15-11](#)
- limitations with 802.1Q trunks [15-11](#)
- load sharing
 - overview [12-24](#)
 - using path costs [12-26](#)
 - using port priorities [12-24](#)
- loop guard
 - described [17-11](#)
 - enabling [17-18](#)
- modes supported [15-10](#)
- multicast addresses, effect of [15-9](#)

STP (continued)

- optional features supported [1-5](#)
- overview [15-2](#)
- path costs [12-26, 12-27](#)
- Port Fast
 - described [17-2](#)
 - enabling [17-13](#)
- port priorities [12-25](#)
- preventing root switch selection [17-10](#)
- protocols supported [15-10](#)
- redundant connectivity [15-8](#)
- root guard
 - described [17-10](#)
 - enabling [17-18](#)
- root port, defined [15-3](#)
- root port selection on a switch stack [15-3](#)
- root switch
 - configuring [15-16](#)
 - effects of extended system ID [15-4, 15-16](#)
 - election [15-3](#)
 - unexpected behavior [15-16](#)
- shutdown Port Fast-enabled port [17-3](#)
- stack changes, effects of [15-12](#)
- status, displaying [15-24](#)
- superior BPDU [15-3](#)
- timers, described [15-22](#)
- UplinkFast
 - described [17-4](#)
 - enabling [17-16](#)
 - VLAN-bridge [15-12](#)
- stratum, NTP [7-2](#)
- stub areas, OSPF [29-34](#)
- subnet mask [29-6](#)
- subnet zero [29-7](#)
- success response, VMPS [12-28](#)
- summer time [7-14](#)
- SunNet Manager [1-4](#)
- supernet [29-7](#)

- SVIs
 - and IP unicast routing [29-4](#)
 - and router ACLs [26-3](#)
 - connecting VLANs [11-5](#)
 - defined [11-4](#)
 - routing between VLANs [12-2](#)
 - switch clustering technology [6-1](#)
 - See also clusters, switch [1-3](#)
 - See clusters, switch
 - switch console port [1-4](#)
 - Switch Database Management
 - See SDM
 - switched packets, ACLs on [26-37](#)
 - Switched Port Analyzer
 - See SPAN
 - switched ports [11-2](#)
 - Switch Manager [3-33](#)
 - switchport block multicast command [19-6](#)
 - switchport block unicast command [19-6](#)
 - switchport command [11-12](#)
 - switchport protected command [19-5](#)
 - switch priority
 - MSTP [16-20](#)
 - STP [15-21](#)
 - switch software features [1-1](#)
 - switch virtual interface
 - See SVI
 - synchronization, BGP [29-49](#)
 - syslog
 - See system message logging
 - system clock
 - configuring
 - daylight saving time [7-14](#)
 - manually [7-12](#)
 - summer time [7-14](#)
 - time zones [7-13](#)
 - displaying the time and date [7-12](#)
 - overview [7-2](#)
 - See also NTP
 - system message logging
 - default configuration [24-4](#)
 - defining error message severity levels [24-9](#)
 - disabling [24-4](#)
 - displaying the configuration [24-13](#)
 - enabling [24-5](#)
 - facility keywords, described [24-13](#)
 - level keywords, described [24-10](#)
 - limiting messages [24-10](#)
 - message format [24-2](#)
 - overview [24-1](#)
 - sequence numbers, enabling and disabling [24-8](#)
 - setting the display destination device [24-5](#)
 - stack changes, effects of [24-2](#)
 - synchronizing log messages [24-6](#)
 - syslog facility [1-8](#)
 - timestamps, enabling and disabling [24-8](#)
 - UNIX syslog servers
 - configuring the daemon [24-11](#)
 - configuring the logging facility [24-12](#)
 - facilities supported [24-13](#)
 - system messages on CMS [3-19](#)
 - system name
 - default configuration [7-16](#)
 - default setting [7-16](#)
 - manual configuration [7-16](#)
 - See also DNS
 - system prompt
 - default setting [7-16](#)
 - manual configuration [7-17](#)
 - system resources, optimizing [8-1](#)
 - system routes, IGRP [29-25](#)
-
- T**
- tables, CMS [3-29](#)
 - tabs, CMS [3-29](#)

- TAC
 - toll-free telephone numbers [xxxvii](#)
 - website [xxxvi](#)
- TACACS+
 - accounting, defined [9-11](#)
 - authentication, defined [9-11](#)
 - authorization, defined [9-11](#)
 - configuring
 - accounting [9-17](#)
 - authentication key [9-13](#)
 - authorization [9-16](#)
 - login authentication [9-14](#)
 - default configuration [9-13](#)
 - displaying the configuration [9-17](#)
 - identifying the server [9-13](#)
 - in clusters [6-17](#)
 - limiting the services to the user [9-16](#)
 - operation of [9-12](#)
 - overview [9-10](#)
 - support for [1-6](#)
 - tracking services accessed by user [9-17](#)
- tar files
 - creating [B-6](#)
 - displaying the contents of [B-7](#)
 - extracting [B-8](#)
 - image file format [B-22](#)
- technical assistance
 - case priority definitions [xxxvii](#)
 - opening a case [xxxvii](#)
 - TAC website [xxxvi](#)
 - toll-free telephone numbers [xxxvii](#)
- Telnet
 - accessing management interfaces [2-10](#)
 - from a browser [2-11](#)
 - number of connections [1-4](#)
 - setting a password [9-6](#)
- templates, SDM [8-1](#)
- Terminal Access Controller Access Control System Plus
 - See TACACS+
- terminal lines, setting a password [9-6](#)
- TFTP
 - configuration files
 - downloading [B-12](#)
 - preparing the server [B-11](#)
 - uploading [B-12](#)
 - configuration files in base directory [4-6](#)
 - configuring for autoconfiguration [4-5](#)
 - image files
 - deleting [B-25](#)
 - downloading [B-24](#)
 - preparing the server [B-23](#)
 - uploading [B-25](#)
 - limiting access by servers [25-15](#)
- TFTP server [1-4](#)
- threshold, traffic level [19-2](#)
- time
 - See NTP and system clock
- time-range command [26-16](#)
- time ranges in ACLs [26-16](#)
- timestamps in log messages [24-8](#)
- time zones [7-13](#)
- Token Ring VLANs
 - support for [12-5](#)
 - VTP support [13-4](#)
- toolbar [3-20](#)
- tool tips [3-26](#)
- Topology view
 - collapsed cluster view [3-12](#)
 - described [3-4, 3-11](#)
 - device icons [3-15](#)
 - device information [3-14](#)
 - display options [3-16](#)
 - expanded cluster view [3-11](#)
 - expanded stack view [3-13](#)
 - icons [3-14](#)
 - link information [3-14](#)

- Topology view (continued)
 - multiple links [3-23](#)
 - neighboring devices [3-14](#)
 - pop-up menus [3-22](#)
 - TOS [1-7](#)
 - traceroute, Layer 2
 - and ARP [34-16](#)
 - and CDP [34-16](#)
 - described [34-15](#)
 - IP addresses and subnets [34-16](#)
 - MAC addresses and VLANs [34-16](#)
 - multicast traffic [34-16](#)
 - multiple devices on a port [34-16](#)
 - supported switches [34-15](#)
 - unicast traffic [34-15](#)
 - usage guidelines [34-16](#)
 - traffic
 - blocking flooded [19-6](#)
 - fragmented [26-5](#)
 - unfragmented [26-5](#)
 - traffic policing [1-7](#)
 - traffic suppression [19-1](#)
 - transparent mode, VTP [13-3, 13-12](#)
 - trap-door mechanism [4-2](#)
 - traps
 - configuring MAC address notification [7-24](#)
 - configuring managers [25-12](#)
 - defined [25-3](#)
 - enabling [7-24, 25-12](#)
 - notification types [25-12](#)
 - overview [25-1, 25-5](#)
 - troubleshooting
 - connectivity problems [34-13, 34-15](#)
 - detecting unidirectional links [21-1](#)
 - determining packet forwarding [34-19](#)
 - displaying crash information [34-21](#)
 - PIMv1 and PIMv2 interoperability problems [31-23](#)
 - SFP security and identification [34-13](#)
 - show forward command [34-19](#)
 - troubleshooting (continued)
 - with CiscoWorks [25-5](#)
 - with debug commands [34-17](#)
 - with ping [34-13](#)
 - with system message logging [24-1](#)
 - trunking encapsulation [1-6](#)
 - trunk ports
 - configuring [12-20](#)
 - defined [11-3, 12-3](#)
 - encapsulation [12-20, 12-25, 12-27](#)
 - secure MAC addresses on [19-10](#)
 - trunks
 - allowed-VLAN list [12-21](#)
 - configuring [12-20, 12-25, 12-27](#)
 - ISL [12-16](#)
 - load sharing
 - setting STP path costs [12-26](#)
 - using STP port priorities [12-24, 12-25](#)
 - native VLAN for untagged traffic [12-23](#)
 - parallel [12-26](#)
 - pruning-eligible list [12-23](#)
 - to non-DTP device [12-17](#)
 - understanding [12-17](#)
 - trusted boundary for QoS [27-34](#)
 - trusted port states
 - between QoS domains [27-35](#)
 - classification options [27-5](#)
 - ensuring port security for IP phones [27-34](#)
 - support for [1-7](#)
 - within a QoS domain [27-31](#)
 - twisted-pair Ethernet, detecting unidirectional links [21-1](#)
 - type-of-service
 - See TOS
-
- ## U
- UDLD
 - default configuration [21-3](#)
 - echoing detection mechanism [21-2](#)

- UDLD (continued)
 - enabling
 - globally [21-4](#)
 - per interface [21-4](#)
 - link-detection mechanism [21-1](#)
 - neighbor database [21-2](#)
 - overview [21-1](#)
 - resetting an interface [21-5](#)
 - status, displaying [21-5](#)
 - support for [1-5](#)
 - UDP, configuring [29-16](#)
 - unauthorized ports with 802.1X [10-4](#)
 - unequal-cost load balancing, IGRP [29-26](#)
 - unicast storm control command [19-3](#)
 - unicast storms [19-1](#)
 - unicast traffic, blocking [19-6](#)
 - UniDirectional Link Detection protocol
 - See UDLD
 - UNIX syslog servers
 - daemon configuration [24-11](#)
 - facilities supported [24-13](#)
 - message logging configuration [24-12](#)
 - unrecognized Type-Length-Value (TLV) support [13-4](#)
 - upgrading software images
 - See downloading
 - UplinkFast
 - described [17-4](#)
 - enabling [17-16](#)
 - support for [1-5](#)
 - uploading
 - configuration files
 - preparing [B-11, B-14, B-17](#)
 - reasons for [B-9](#)
 - using FTP [B-16](#)
 - using RCP [B-19](#)
 - using TFTP [B-12](#)
 - image files
 - preparing [B-23, B-26, B-30](#)
 - reasons for [B-21](#)
 - using FTP [B-29](#)
 - using RCP [B-34](#)
 - using TFTP [B-25](#)
 - uploading (continued)
 - User Datagram Protocol
 - See UDP
 - user EXEC mode [2-2](#)
 - username-based authentication [9-7](#)
-
- V**
- verifying changes in CMS [3-31](#)
 - version-dependent transparent mode [13-4](#)
 - version mismatch (VM) mode [5-9](#)
 - virtual IP address
 - cluster standby group [6-12, 6-21](#)
 - command switch [6-12, 6-21](#)
 - See also IP addresses
 - virtual router [30-1, 30-2](#)
 - vlan.dat file [12-4](#)
 - VLAN 1, disabling on a trunk port [12-22](#)
 - VLAN 1 minimization [12-21](#)
 - VLAN ACLs
 - See VLAN maps
 - vlan-assignment response, VMPS [12-28](#)
 - VLAN configuration
 - at bootup [12-7](#)
 - saving [12-7](#)
 - VLAN configuration mode [2-2, 12-7](#)
 - VLAN database
 - and startup configuration file [12-7](#)
 - and VTP [13-1](#)
 - VLAN configuration saved in [12-7](#)
 - VLANs saved in [12-4](#)

- vlan database command [12-7](#)
- VLAN filtering, and SPAN [22-7](#)
- vlan global configuration command [12-7](#)
- VLAN ID, discovering [7-28](#)
- VLAN management domain [13-2](#)
- VLAN Management Policy Server
 - See VMPS
- VLAN map entries, order of [26-29](#)
- VLAN maps
 - applying [26-33](#)
 - common uses for [26-33](#)
 - configuration example [26-34](#)
 - configuration guidelines [26-29](#)
 - configuring [26-29](#)
 - creating [26-30](#)
 - defined [26-2](#)
 - denying access example [26-35](#)
 - denying and permitting packets [26-31](#)
 - displaying [26-41](#)
 - examples [26-35](#)
 - support for [1-6](#)
 - with router ACLs [26-41](#)
- VLAN membership
 - confirming [12-32](#)
 - modes [3-10, 12-3](#)
- VLAN Query Protocol
 - See VQP
- VLANs
 - adding [12-8](#)
 - adding to VLAN database [12-8](#)
 - aging dynamic addresses [15-9](#)
 - allowed on trunk [12-21](#)
 - and spanning-tree instances [12-3, 12-13](#)
 - configuration guidelines, extended-range VLANs [12-13](#)
 - configuration guidelines, normal-range VLANs [12-6](#)
 - configuration options [12-6](#)
 - configuring [12-1](#)
 - configuring IDs 1006 to 4094 [12-13](#)
 - connecting through SVIs [11-5](#)
 - VLANs (continued)
 - creating in config-vlan mode [12-9](#)
 - creating in VLAN configuration mode [12-10](#)
 - default configuration [12-8](#)
 - deleting [12-10](#)
 - described [11-2, 12-1](#)
 - displaying [12-16](#)
 - extended-range [12-1, 12-12](#)
 - features [1-5](#)
 - illustrated [12-2](#)
 - internal [12-13](#)
 - in the switch stack [12-6](#)
 - limiting source traffic with RSPAN [22-23](#)
 - limiting source traffic with SPAN [22-16](#)
 - modifying [12-8](#)
 - native, configuring [12-23](#)
 - normal-range [12-1, 12-4](#)
 - number supported [1-5](#)
 - parameters [12-5](#)
 - port membership modes [3-10, 12-3](#)
 - static-access ports [12-11](#)
 - STP and 802.1Q trunks [15-11](#)
 - supported [12-3](#)
 - Token Ring [12-5](#)
 - traffic between [12-2](#)
 - VLAN-bridge STP [15-12, 33-2](#)
 - VTP modes [13-3](#)
- VLAN Trunking Protocol
 - See VTP
- VLAN trunks [12-16, 12-17](#)
- VMPS
 - administering [12-33](#)
 - configuration example [12-34](#)
 - configuration guidelines [12-30](#)
 - default configuration [12-29](#)
 - description [12-28](#)

VMPS (continued)

- dynamic port membership
 - described [12-29](#)
 - reconfirming [12-32](#)
 - troubleshooting [12-33](#)
- entering server address [12-30](#)
- mapping MAC addresses to VLANs [12-28](#)
- monitoring [12-33](#)
- reconfirmation interval, changing [12-32](#)
- reconfirming membership [12-32](#)
- retry count, changing [12-32](#)

voice-over-IP [14-1](#)

voice VLAN

- Cisco 7960 phone, port connections [14-1](#)
- configuration guidelines [8-4, 14-3](#)
- configuring IP phones for data traffic
 - override CoS of incoming frame [14-5](#)
 - trust CoS priority of incoming frame [14-5](#)
- configuring ports for voice traffic in
 - 802.1P priority tagged frames [14-5](#)
 - 802.1Q frames [14-4](#)
- connecting to an IP phone [14-4](#)
- default configuration [14-3](#)
- described [14-1](#)
- displaying [14-6](#)

VQP [1-5, 12-28](#)

VTP

- adding a client to a domain [13-15](#)
- advertisements [12-19, 13-3](#)
- and extended-range VLANs [13-2](#)
- and normal-range VLANs [13-2](#)
- client mode, configuring [13-11](#)
- configuration
 - global configuration mode [13-7](#)
 - guidelines [13-8](#)
 - privileged EXEC mode [13-7](#)
 - requirements [13-9](#)
 - saving [13-7](#)
 - VLAN configuration mode [13-8](#)

VTP (continued)

- configuration mode options [13-7](#)
- configuration requirements [13-9](#)
- configuration revision number
 - guideline [13-15](#)
 - resetting [13-15](#)
- configuring
 - client mode [13-11](#)
 - server mode [13-9](#)
 - transparent mode [13-12](#)
- consistency checks [13-4](#)
- default configuration [13-7](#)
- described [13-1](#)
- disabling [13-12](#)
- domain names [13-8](#)
- domains [13-2](#)
- modes
 - client [13-3, 13-11](#)
 - server [13-3, 13-9](#)
 - transitions [13-3](#)
 - transparent [13-3, 13-12](#)
- monitoring [13-16](#)
- passwords [13-8](#)
- pruning
 - disabling [13-14](#)
 - enabling [13-14](#)
 - examples [13-5](#)
 - overview [13-4](#)
 - support for [1-6](#)
- pruning-eligible list, changing [12-23](#)
- server mode, configuring [13-9](#)
- statistics [13-16](#)
- support for [1-6](#)
- Token Ring support [13-4](#)
- transparent mode, configuring [13-12](#)
- using [13-1](#)
- version, guidelines [13-9](#)
- version 1 [13-4](#)

VTP (continued)

version 2

configuration guidelines [13-9](#)

disabling [13-13](#)

enabling [13-13](#)

overview [13-4](#)

W

web-based management software

See CMS

weighted tail drop

See WTD

window components, CMS [3-28](#)

wizards [1-2, 3-26](#)

WTD

described [27-11](#)

setting thresholds

egress queue-sets [27-57](#)

ingress queues [27-53](#)

support for [1-7](#)

X

XMODEM protocol [34-2](#)