



## INDEX

## Numerics

10-Gigabit Ethernet interfaces

    configuration guidelines **10-16**

    defined **10-6**

802.1D

    See STP

802.1Q

    and trunk ports **10-3**

    configuration limitations **12-19**

    encapsulation **12-16**

    native VLAN for untagged traffic **12-23**

    tunneling

        compatibility with other features **16-6**

        defaults **16-4**

        described **16-1**

    tunnel ports with other features **16-6**

802.1s

    See MSTP

802.1w

    See RSTP

802.1x

    See port-based authentication

802.3ad

    See EtherChannel

802.3af

    See PoE

802.3z flow control **10-19**

## A

abbreviating commands **2-3**

ABRs **34-25**

access-class command **31-21**

access control entries

    See ACEs

access-denied response, VMPS **12-28**

access groups

    applying ACLs to interfaces **31-22**

    IP **31-22**

    Layer 2 **31-22**

    Layer 3 **31-22**

accessing stack members **4-22**

access lists

    See ACLs

access ports

    and Layer 2 protocol tunneling **16-11**

    defined **10-3**

accounting

    with 802.1x **9-5, 9-22**

    with RADIUS **8-28**

    with TACACS+ **8-11, 8-17**

ACEs

    and QoS **32-7**

    defined **31-2**

    Ethernet **31-2**

    IP **31-2**

ACLs

    ACEs **31-2**

    any keyword **31-14**

    applying

        on bridged packets **31-39**

        on multicast packets **31-41**

        on routed packets **31-40**

        on switched packets **31-39**

        time ranges to **31-18**

- ACLs (continued)
  - applying (continued)
    - to an interface **31-21**
    - to QoS **32-7**
  - ACLs (continued)
    - classifying traffic for QoS **32-42**
    - comments in **31-20**
    - compiling **31-24**
    - configuring with VLAN maps **31-38**
    - defined **31-1, 31-8**
    - examples of **31-24, 32-42**
    - extended IP
      - configuring for QoS classification **32-44**
      - creating **31-11**
      - matching criteria **31-8**
    - hardware and software handling **31-23**
    - host keyword **31-14**
    - IP
      - applying to an interface **31-21**
      - applying to interfaces **31-21**
      - creating **31-8**
      - fragments and QoS guidelines **32-33**
      - implicit deny **31-10, 31-15, 31-17**
      - implicit masks **31-10**
      - matching criteria **31-8**
      - named **31-16**
      - terminal lines, setting on **31-21**
      - undefined **31-23**
      - violations, logging **31-17**
    - limiting actions **31-39**
    - logging messages **31-11**
    - log keyword **31-17**
    - MAC extended **31-28, 32-45**
    - matching **31-8, 31-22**
    - monitoring **31-41**
    - named **31-16**
    - number per QoS class map **32-33**
    - numbers **31-9**
    - port **31-2**
  - ACLs (continued)
    - precedence of **31-3**
    - QoS **32-7, 32-42**
    - resequencing entries **31-16**
    - router **31-2**
    - standard IP
      - configuring for QoS classification **32-43**
      - creating **31-10**
      - matching criteria **31-8**
    - supported features **31-23**
    - support for **1-7**
    - time ranges **31-18**
    - unsupported features **31-7**
    - using router ACLs with VLAN maps **31-38**
    - VLAN maps
      - configuration guidelines **31-31**
      - configuring **31-31**
    - active links **20-1**
    - active router **35-1**
    - address aliasing **23-2**
    - addresses
      - displaying the MAC address table **6-28**
      - dynamic
        - accelerated aging **17-9**
        - changing the aging time **6-22**
        - default aging **17-9**
        - defined **6-20**
        - learning **6-21**
        - removing **6-23**
      - MAC, discovering **6-28**
      - multicast
        - group address range **36-3**
        - STP address management **17-9**
      - static
        - adding and removing **6-25**
        - defined **6-20**
    - address resolution **6-28, 34-9**
    - Address Resolution Protocol
      - See ARP

- adjacency tables, with CEF **34-61**
- administrative distances
- defined **34-72**
  - OSPF **34-31**
  - routing protocol defaults **34-63**
- advertisements
- CDP **25-1**
  - RIP **34-20**
  - VTP **12-19, 13-3**
- aggregate addresses, BGP **34-55**
- aggregated ports
- See EtherChannel
- aggregate policers **32-57**
- aggregate policing **1-9**
- aggregator template **4-10, 7-1**
- aging, accelerating **17-9**
- aging time
- accelerated
    - for MSTP **18-21**
    - for STP **17-9, 17-23**
  - MAC address table **6-22**
  - maximum
    - for MSTP **18-22**
    - for STP **17-23**
- alarms, RMON **28-3**
- allowed-VLAN list **12-21**
- area border routers
- See ABRs
- ARP
- configuring **34-10**
  - defined **1-5, 6-28, 34-9**
  - encapsulation **34-11**
  - static cache configuration **34-10**
  - table
    - address resolution **6-28**
    - managing **6-28**
- ASBRs **34-25**
- AS-path filters, BGP **34-50**
- asymmetrical links, and 802.1Q tunneling **16-4**
- attributes, RADIUS
- vendor-proprietary **8-31**
  - vendor-specific **8-29**
- audience **xxxvii**
- authentication
- EIGRP **34-38**
  - HSRP **35-9**
  - local mode with AAA **8-36**
  - NTP associations **6-5**
  - RADIUS
    - key **8-21**
    - login **8-23**
  - TACACS+
    - defined **8-11**
    - key **8-13**
    - login **8-14**
- See also port-based authentication
- authentication keys, and routing protocols **34-73**
- authoritative time source, described **6-2**
- authorization
- with RADIUS **8-27**
  - with TACACS+ **8-11, 8-16**
- authorized ports with 802.1x **9-4**
- autoconfiguration **3-3**
- automatic advise (auto-advise) in switch stacks **4-12**
- automatic copy (auto-copy) in switch stacks **4-12**
- automatic QoS
- See QoS
- automatic upgrades (auto-upgrade) in switch stacks **4-12**
- autonegotiation
- duplex mode **1-3**
  - interface configuration guidelines **10-17**
  - mismatches **39-13**
- autonomous system boundary routers
- See ASBRs
- autonomous systems, in BGP **34-44**
- Auto-RP, described **36-5**
- autosensing, port speed **1-3**

auxiliary VLAN

  See voice VLAN

availability, features **1-5**

---

## B

BackboneFast

  described **19-7**

  disabling **19-17**

  enabling **19-16**

  support for **1-6**

backup interfaces

  See Flex Links

backup links **20-1**

banners

configuring

  login **6-20**

  message-of-the-day login **6-19**

default configuration **6-18**

when displayed **6-18**

BGP

aggregate addresses **34-55**

aggregate routes, configuring **34-55**

CIDR **34-55**

clear commands **34-59**

community filtering **34-52**

configuring neighbors **34-54**

default configuration **34-41**

described **34-41**

enabling **34-43**

monitoring **34-59**

multipath support **34-47**

neighbors, types of **34-43**

path selection **34-47**

peers, configuring **34-54**

prefix filtering **34-51**

resetting sessions **34-46**

route dampening **34-58**

route maps **34-49**

BGP (continued)

  route reflectors **34-57**

  routing domain confederation **34-56**

  show commands **34-59**

  supernets **34-55**

  support for **1-9**

  Version 4 **34-41**

binding cluster group and HSRP group **35-11**

binding database

  address, DHCP server

  See DHCP, Cisco IOS server database

DHCP snooping

  See DHCP snooping binding database

bindings

  address, Cisco IOS DHCP server **21-5**

  DHCP snooping database **21-5**

  IP source guard **21-14**

binding table, DHCP snooping

  See DHCP snooping binding database

blocking packets **24-6**

booting

  boot loader, function of **3-2**

  boot process **3-1**

  manually **3-13**

  specific image **3-13**

boot loader

  accessing **3-14**

  described **3-2**

  environment variables **3-14**

  prompt **3-14**

  trap-door mechanism **3-2**

bootstrap router (BSR), described **36-5**

Border Gateway Protocol

  See BGP

BPDU

  error-disabled state **19-3**

  filtering **19-3**

  RSTP format **18-10**

BPDU filtering  
described **19-3**  
disabling **19-15**  
enabling **19-14**  
support for **1-6**

BPDU guard  
described **19-3**  
disabling **19-14**  
enabling **19-13**  
support for **1-6**

bridged packets, ACLs on **31-39**

bridge groups  
See fallback bridging

bridge protocol data unit  
See BPDU

broadcast flooding **34-17**

broadcast packets  
directed **34-14**  
flooded **34-14**

broadcast storm-control command **24-4**

broadcast storms **24-1, 34-14**

**C**

cables, monitoring for unidirectional links **26-1**

candidate switch  
defined **5-3**  
requirements **5-3**  
See also command switch, cluster standby group, and member switch

CA trustpoint  
configuring **8-45**  
defined **8-42**

caution, described **xxxviii**

CDP  
and trusted boundary **32-39**  
configuring **25-2**  
default configuration **25-2**  
described **25-1**

CDP (continued)  
disabling for routing device **25-3 to 25-4**  
enabling and disabling  
on an interface **25-4**  
on a switch **25-3**

Layer 2 protocol tunneling **16-8**

monitoring **25-5**

overview **25-1**

power negotiation extensions **10-6**

support for **1-5**

switch stack considerations **25-2**

transmission timer and holdtime, setting **25-2**

updates **25-2**

CEF **34-60**

CGMP  
as IGMP snooping learning method **23-8**  
clearing cached group entries **36-50**  
enabling server support **36-33**  
joining multicast group **23-3**  
overview **36-7**  
server support only **36-7**  
switch support of **1-4**

CIDR **34-55**

CipherSuites **8-43**

Cisco 7960 IP Phone **15-1**

Cisco Discovery Protocol  
See CDP

Cisco Express Forwarding  
See CEF

Cisco Group Management Protocol  
See CGMP

Cisco intelligent power management **10-6**

Cisco IOS DHCP server  
See DHCP, Cisco IOS DHCP server

Cisco IOS File System  
See IFS

Cisco Network Assistant  
See Network Assistant

- Cisco StackWise technology **1-3**  
 See also stacks, switch
- CiscoWorks 2000 **1-4, 30-4**
- classless interdomain routing  
 See CIDR
- classless routing **34-7**
- class maps for QoS  
 configuring **32-46**  
 described **32-7**  
 displaying **32-77**
- class of service  
 See CoS
- clearing interfaces **10-27**
- CLI  
 abbreviating commands **2-3**  
 command modes **2-1**  
 described **1-4**  
 editing features  
   enabling and disabling **2-6**  
   keystroke editing **2-6**  
   wrapped lines **2-8**  
 error messages **2-4**  
 filtering command output **2-8**  
 getting help **2-3**  
 history  
   changing the buffer size **2-5**  
   described **2-4**  
   disabling **2-5**  
   recalling commands **2-5**  
 managing clusters **5-4**  
 no and default forms of commands **2-4**  
 client mode, VTP **13-3**  
 clock  
   See system clock  
 cluster requirements **xxxix**
- clusters, switch  
 benefits **1-2**  
 described **5-1**  
 managing  
   through CLI **5-4**  
   through SNMP **5-5**  
 planning considerations  
   CLI **5-4**  
   SNMP **5-5**
- See also Getting Started with Cisco Network Assistant
- cluster standby group  
 and HSRP group **35-11**  
 requirements **5-2**
- Coarse Wave Division Multiplexer  
 See CWDM SFPs
- command-line interface  
 See CLI
- command modes **2-1**
- commands  
 abbreviating **2-3**  
 no and default **2-4**  
 commands, setting privilege levels **8-8**  
 command switch  
   configuration conflicts **39-13**  
   defined **5-2**  
   password privilege levels **5-4**  
   recovery  
     from command-switch failure **39-9**  
     from lost member connectivity **39-13**  
   replacing  
     with another switch **39-11**  
     with cluster member **39-10**  
   requirements **5-2**  
   See also candidate switch, cluster standby group, member switch, and standby command switch
- community list, BGP **34-53**
- community ports **14-2**

community strings  
 configuring **30-8**  
 for cluster switches **30-4**  
 overview **30-4**

community VLANs **14-2, 14-3**

compatibility, feature **24-11**

compatibility, software  
 See stacks, switch

config.text **3-12**

configuration, initial  
 defaults **1-11**  
 Express Setup **1-2**  
 See also getting started guide and hardware installation guide

configuration conflicts, recovering from lost member connectivity **39-13**

configuration examples, network **1-13**

configuration files  
 clearing the startup configuration **B-19**  
 creating using a text editor **B-10**  
 default name **3-12**  
 deleting a stored configuration **B-19**  
 described **B-8**  
 downloading  
     automatically **3-12**  
     preparing **B-10, B-13, B-16**  
     reasons for **B-8**  
     using FTP **B-13**  
     using RCP **B-17**  
     using TFTP **B-11**  
 guidelines for creating and using **B-9**  
 invalid combinations when copying **B-5**  
 limiting TFTP server access **30-15**  
 obtaining with DHCP **3-7**  
 password recovery disable considerations **8-5**  
 specifying the filename **3-12**  
 system contact and location information **30-15**  
 types and location **B-10**

configuration files (continued)  
 uploading  
 preparing **B-10, B-13, B-16**  
 reasons for **B-8**  
 using FTP **B-14**  
 using RCP **B-18**  
 using TFTP **B-12**

configuration settings, saving **3-10**

configure terminal command **10-11**

config-vlan mode **2-2, 12-7**

conflicts, configuration **39-13**

connections, secure remote **8-38**

connectivity problems **39-15, 39-16, 39-18**

consistency checks in VTP Version 2 **13-4**

console port, connecting to **2-9**

conventions  
 command **xxxviii**  
 for examples **xxxviii**  
 publication **xxxviii**  
 text **xxxviii**

corrupted software, recovery steps with Xmodem **39-2**

CoS  
 in Layer 2 frames **32-2**  
 override priority **15-6**  
 trust priority **15-6**

CoS input queue threshold map for QoS **32-16**

CoS output queue threshold map for QoS **32-19**

CoS-to-DSCP map for QoS **32-59**

counters, clearing interface **10-27**

crashinfo file **39-25**

cross-stack EtherChannel  
 configuration guidelines **33-12**

configuring  
 on Layer 2 interfaces **33-12**  
 on Layer 3 physical interfaces **33-16**

described **33-2**

illustration **33-3**

support for **1-5**

cross-stack UplinkFast, STP  
described **19-5**  
disabling **19-16**  
enabling **19-16**  
fast-convergence events **19-7**  
Fast Uplink Transition Protocol **19-6**  
normal-convergence events **19-7**  
support for **1-6**  
cryptographic software image  
Kerberos **8-32**  
SSH **8-37**  
SSL **8-42**  
switch stack considerations **4-2, 4-17, 8-38**  
CWDM SFPs **1-24**

**D**

daylight saving time **6-13**  
debugging  
enabling all system diagnostics **39-22**  
enabling for a specific feature **39-21**  
redirecting error message output **39-22**  
using commands **39-21**  
default commands **2-4**  
default configuration  
802.1Q tunneling **16-4**  
802.1x **9-11**  
auto-QoS **32-20**  
banners **6-18**  
BGP **34-41**  
booting **3-12**  
CDP **25-2**  
DHCP **21-7**  
DHCP option 82 **21-7**  
DHCP snooping **21-7**  
DHCP snooping binding database **21-7**  
DNS **6-17**  
dynamic ARP inspection **22-5**  
EIGRP **34-35**

default configuration (continued)  
EtherChannel **33-10**  
fallback bridging **38-3**  
Flex Links **20-2**  
HSRP **35-5**  
IGMP **36-27**  
IGMP filtering **23-20**  
IGMP snooping **23-6**  
IGMP throttling **23-20**  
initial switch information **3-3**  
IP addressing, IP routing **34-5**  
IP multicast routing **36-8**  
IP source guard **21-15**  
Layer 2 interfaces **10-15**  
Layer 2 protocol tunneling **16-11**  
MAC address table **6-22**  
MSDP **37-4**  
MSTP **18-13**  
MVR **23-15**  
NTP **6-4**  
optional spanning-tree configuration **19-12**  
OSPF **34-26**  
password and privilege level **8-2**  
PIM **36-8**  
private VLANs **14-7**  
RADIUS **8-20**  
RIP **34-20**  
RMON **28-3**  
RSPAN **27-11**  
SNMP **30-6**  
SPAN **27-11**  
SSL **8-44**  
standard QoS **32-31**  
STP **17-13**  
switch stacks **4-20**  
system message logging **29-4**  
system name and prompt **6-15**  
TACACS+ **8-13**  
UDLD **26-4**

- default configuration (continued)
- VLAN, Layer 2 Ethernet interfaces **12-19**
  - VLANs **12-8**
  - VMPS **12-29**
  - voice VLAN **15-3**
  - VTP **13-7**
- default gateway **3-10, 34-12**
- default networks **34-63**
- default routes **34-63**
- default routing **34-2**
- deleting VLANs **12-10**
- description command **10-23**
- designing your network, examples **1-13**
- desktop template **4-10, 7-1**
- destination addresses, in ACLs **31-13**
- destination-IP address-based forwarding, EtherChannel **33-8**
- destination-MAC address forwarding, EtherChannel **33-8**
- detecting indirect link failures, STP **19-8**
- device **B-19**
- device discovery protocol **25-1**
- device manager
- benefits **1-2**
  - described **1-2, 1-4**
  - in-band management **1-5**
  - requirements **xxxviii**
  - upgrading a switch **B-19**
- DHCP
- Cisco IOS server database
  - configuring **21-12**
  - default configuration **21-7**
  - described **21-5**
  - enabling
  - relay agent **21-9**
  - server **21-8**
- DHCP-based autoconfiguration
- client request message exchange **3-4**
  - configuring
  - client side **3-3**
  - DNS **3-6**
  - relay device **3-6**
  - server side **3-5**
  - server-side **21-8**
  - TFTP server **3-5**
  - example **3-8**
  - lease options
  - for IP address information **3-5**
  - for receiving the configuration file **3-5**
- overview **3-3**
- relationship to BOOTP **3-4**
- relay support **1-5, 1-10**
- support for **1-5**
- DHCP binding database
- See DHCP snooping binding database
- DHCP binding table
- See DHCP snooping binding database
- DHCP option 82
- circuit ID suboption **21-4**
  - configuration guidelines **21-8**
  - default configuration **21-7**
  - displaying **21-13**
  - forwarding address, specifying **21-9**
  - helper address **21-9**
  - overview **21-3**
  - packet format, suboption
  - circuit ID **21-4**
  - remote ID **21-4**
  - remote ID suboption **21-4**

- DHCP snooping
- and private VLANs [21-12](#)
  - binding database
    - See DHCP snooping binding database
    - configuration guidelines [21-8](#)
    - default configuration [21-7](#)
    - displaying binding tables [21-13](#)
    - message exchange process [21-4](#)
    - option 82 data insertion [21-3](#)
    - trusted interface [21-2](#)
    - untrusted interface [21-2](#)
    - untrusted messages [21-2](#)
  - DHCP snooping binding database
    - adding bindings [21-12](#)
    - binding file
      - format [21-6](#)
      - location [21-5](#)
    - bindings [21-5](#)
    - clearing agent statistics [21-13](#)
    - configuration guidelines [21-8](#)
    - configuring [21-12](#)
    - default configuration [21-7](#)
    - deleting
      - binding file [21-13](#)
      - bindings [21-13](#)
      - database agent [21-13](#)
    - described [21-5](#)
    - displaying [21-13](#)
      - binding entries [21-13](#)
      - status and statistics [21-13](#)
    - enabling [21-12](#)
    - entry [21-5](#)
    - renewing database [21-13](#)
    - resetting
      - delay value [21-13](#)
      - timeout value [21-13](#)
    - updating process [21-6](#)
  - DHCP snooping binding table
    - See DHCP snooping binding database

- Differentiated Services architecture, QoS [32-2](#)
- Differentiated Services Code Point [32-2](#)
- Diffusing Update Algorithm (DUAL) [34-34](#)
- directed unicast requests [1-5](#)
- directories
  - changing [B-4](#)
  - creating and removing [B-4](#)
  - displaying the working [B-4](#)
- Distance Vector Multicast Routing Protocol
  - See DVMRP
- distance-vector protocols [34-3](#)
- distribute-list command [34-71](#)
- DNS
  - and DHCP-based autoconfiguration [3-6](#)
  - default configuration [6-17](#)
  - displaying the configuration [6-18](#)
  - overview [6-16](#)
  - setting up [6-17](#)
  - support for [1-5](#)
  - documentation, related [xxxviii](#)
  - document conventions [xxxviii](#)
  - domain names
    - DNS [6-16](#)
    - VTP [13-8](#)
  - Domain Name System
    - See DNS
  - dot1q-tunnel switchport mode [12-18](#)
  - double-tagged packets
    - 802.1Q tunneling [16-2](#)
    - Layer 2 protocol tunneling [16-10](#)
  - downloading
    - configuration files
      - preparing [B-10, B-13, B-16](#)
      - reasons for [B-8](#)
      - using FTP [B-13](#)
      - using RCP [B-17](#)
      - using TFTP [B-11](#)

downloading (continued)

- image files
  - deleting old image **B-23**
  - preparing **B-21, B-25, B-29**
  - reasons for **B-19**
  - using CMS **1-2**
  - using FTP **B-26**
  - using HTTP **1-2, B-19**
  - using Network Assistant **1-2**
  - using RCP **B-31**
  - using TFTP **B-22**
  - using the device manager or Network Assistant **B-19**
- drop threshold for Layer 2 protocol packets **16-11**
- DSCL **1-8, 32-2**
- DSCL input queue threshold map for QoS **32-16**
- DSCL output queue threshold map for QoS **32-19**
- DSCL-to-CoS map for QoS **32-62**
- DSCL-to-DSCL-mutation map for QoS **32-63**
- DSCL transparency **32-39**
- DTP **1-6, 12-17**
- DUAL finite state machine, EIGRP **34-34**
- duplex mode, configuring **10-16**
- DVMRP

  - autosummarization
    - configuring a summary address **36-47**
    - disabling **36-49**
  - connecting PIM domain to DVMRP router **36-39**
  - enabling unicast routing **36-43**
  - interoperability
    - with Cisco devices **36-37**
    - with Cisco IOS software **36-7**
  - mrinfo requests, responding to **36-42**
  - neighbors
    - advertising the default route to **36-41**
    - discovery with Probe messages **36-37**
    - displaying information **36-42**
    - prevent peering with nonpruning **36-45**
    - rejecting nonpruning **36-43**
  - overview **36-7**

DVMRP (continued)

- routes
  - adding a metric offset **36-49**
  - advertising all **36-49**
  - advertising the default route to neighbors **36-41**
  - caching DVMRP routes learned in report messages **36-43**
  - changing the threshold for syslog messages **36-46**
  - deleting **36-50**
  - displaying **36-51**
  - favoring one over another **36-49**
  - limiting the number injected into MBONE **36-46**
  - limiting unicast route advertisements **36-37**
  - routing table **36-7**
  - source distribution tree, building **36-7**
  - support for **1-10**
  - tunnels
    - configuring **36-39**
    - displaying neighbor information **36-42**
  - dynamic access ports
    - characteristics **12-4**
    - configuring **12-30**
    - defined **10-3**
  - dynamic addresses
    - See addresses
  - dynamic ARP inspection
    - ARP cache poisoning **22-1**
    - ARP requests, described **22-1**
    - ARP spoofing attack **22-1**
    - clearing
      - log buffer **22-15**
      - statistics **22-15**
    - configuration guidelines **22-6**
    - configuring
      - ACLs for non-DHCP environments **22-8**
      - in DHCP environments **22-7**
      - log buffer **22-12**
      - rate limit for incoming ARP packets **22-4, 22-10**
    - default configuration **22-5**

dynamic ARP inspection (continued)  
 denial-of-service attacks, preventing **22-10**  
 described **22-1**  
 DHCP snooping binding database **22-2**  
 displaying  
 ARP ACLs **22-14**  
 configuration and operating state **22-14**  
 log buffer **22-15**  
 statistics **22-15**  
 trust state and rate limit **22-14**  
 error-disabled state for exceeding rate limit **22-4**  
 function of **22-2**  
 interface trust states **22-3**  
 log buffer  
   clearing **22-15**  
   configuring **22-12**  
   displaying **22-15**  
 logging of dropped packets, described **22-5**  
 man-in-the middle attack, described **22-2**  
 network security issues and interface trust states **22-3**  
 priority of ARP ACLs and DHCP snooping entries **22-4**  
 rate limiting of ARP packets  
   configuring **22-10**  
   described **22-4**  
   error-disabled state **22-4**  
 statistics  
   clearing **22-15**  
   displaying **22-15**  
   validation checks, performing **22-11**  
 dynamic auto trunking mode **12-18**  
 dynamic desirable trunking mode **12-18**  
 Dynamic Host Configuration Protocol  
   See DHCP-based autoconfiguration  
 dynamic port VLAN membership  
   described **12-28**  
   reconfirming **12-31**  
   troubleshooting **12-33**  
   types of connections **12-30**

dynamic routing **34-3**  
 Dynamic Trunking Protocol  
   See DTP

---

**E**

EBGP **34-40**  
 editing features  
   enabling and disabling **2-6**  
   keystrokes used **2-6**  
   wrapped lines **2-8**  
 EIGRP  
   authentication **34-38**  
   components **34-34**  
   configuring **34-36**  
   default configuration **34-35**  
   definition **34-34**  
   interface parameters, configuring **34-37**  
   monitoring **34-39**  
   support for **1-9**  
 elections  
   See stack master  
 enable password **8-4**  
 enable secret password **8-4**  
 encryption, CipherSuite **8-44**  
 encryption for passwords **8-4**  
 Enhanced IGRP  
   See EIGRP  
 environment variables, function of **3-15**  
 equal-cost routing **1-9, 34-62**  
 error messages during command entry **2-4**  
 EtherChannel  
   802.3ad, described **33-6**  
   automatic creation of **33-5, 33-6**  
   channel groups  
     binding physical and logical interfaces **33-4**  
     numbering of **33-4**  
   configuration guidelines **33-11**

- EtherChannel (continued)
- configuring
    - Layer 2 interfaces **33-12**
    - Layer 3 physical interfaces **33-16**
    - Layer 3 port-channel logical interfaces **33-15**
  - default configuration **33-10**
  - described **33-2**
  - displaying status **33-23**
  - forwarding methods **33-7, 33-18**
  - interaction
    - with STP **33-11**
    - with VLANs **33-12**
  - LACP
    - described **33-6**
    - displaying status **33-23**
    - hot-standby ports **33-20**
    - interaction with other features **33-7**
    - modes **33-6**
    - port priority **33-22**
    - system priority **33-21**
  - Layer 3 interface **34-4**
    - load balancing **33-7, 33-18**
    - logical interfaces, described **33-4**
  - PAgP
    - aggregate-port learners **33-19**
    - compatibility with Catalyst 1900 **33-19**
    - described **33-5**
    - displaying status **33-23**
    - interaction with other features **33-6**
    - learn method and priority configuration **33-19**
    - modes **33-5**
    - support for **1-4**
  - port-channel interfaces
    - described **33-4**
    - numbering of **33-4**
  - port groups **10-5**
  - stack changes, effects of **33-9**
  - support for **1-3**
- EtherChannel guard
- described **19-10**
  - disabling **19-17**
  - enabling **19-17**
- Ethernet VLANs
- adding **12-9**
  - defaults and ranges **12-8**
  - modifying **12-9**
  - events, RMON **28-3**
  - examples
    - conventions for **xxxviii**
    - network configuration **1-13**
  - expedite queue for QoS **32-76**
  - Express Setup **1-2**
    - See also getting started guide
  - extended-range VLANs
    - configuration guidelines **12-13**
    - configuring **12-12**
    - creating **12-14**
    - defined **12-1**
  - extended system ID
    - MSTP **18-15**
    - STP **17-4, 17-16**
  - Extensible Authentication Protocol over LAN **9-1**
  - external BGP
    - See EBGP
  - external neighbors, BGP **34-43**
- 
- F**
- failover support **1-5**
  - fallback bridging
    - and protected ports **38-4**
    - bridge groups
      - creating **38-4**
      - described **38-2**
      - displaying **38-11**
      - function of **38-2**

- fallback bridging (continued)
- bridge groups (continued)
    - number supported **38-5**
    - removing **38-5**
  - bridge table
    - clearing **38-11**
    - displaying **38-11**
  - configuration guidelines **38-4**
  - connecting interfaces with **10-9**
  - default configuration **38-3**
  - described **38-1**
  - frame forwarding
    - flooding packets **38-2**
    - forwarding packets **38-2**
  - overview **38-1**
  - protocol, unsupported **38-4**
  - stack changes, effects of **38-3**
  - STP
    - disabling on an interface **38-11**
    - forward-delay interval **38-10**
    - hello BPDU interval **38-9**
    - interface priority **38-7**
    - keepalive messages **17-2**
    - maximum-idle interval **38-10**
    - path cost **38-8**
    - VLAN-bridge spanning-tree priority **38-7**
    - VLAN-bridge STP **38-2**
  - support for **1-9**
  - SVIs and routed ports **38-1**
  - unsupported protocols **38-4**
  - VLAN-bridge STP **17-12**
  - Fast Uplink Transition Protocol **19-6**
  - features, incompatible **24-11**
  - FIB **34-60**
  - fiber-optic, detecting unidirectional links **26-1**
  - files
    - copying **B-5**
    - crashinfo
      - description **39-25**
      - displaying the contents of **39-25**
      - location **39-25**
    - deleting **B-5**
    - displaying the contents of **B-8**
  - tar
    - creating **B-6**
    - displaying the contents of **B-7**
    - extracting **B-7**
    - image file format **B-20**
  - file system
    - displaying available file systems **B-2**
    - displaying file information **B-3**
    - local file system names **B-1**
    - network file system names **B-5**
    - setting the default **B-3**
  - filtering
    - in a VLAN **31-31**
    - non-IP traffic **31-28**
    - show and more command output **2-8**
  - filtering show and more command output **2-8**
  - filters, IP
    - See ACLs, IP
  - flash device, number of **B-1**
  - Flex Links
    - configuration guidelines **20-2**
    - configuring **20-3**
    - default configuration **20-2**
    - description **20-1**
    - monitoring **20-3**
    - flooded traffic, blocking **24-7**
  - flow-based packet classification **1-8**

flowcharts  
 QoS classification **32-6**  
 QoS egress queueing and scheduling **32-17**  
 QoS ingress queueing and scheduling **32-15**  
 QoS policing and marking **32-11**

flow control **1-3, 10-19**

forward-delay time  
 MSTP **18-21**  
 STP **17-23**

Forwarding Information Base  
 See FIB

forwarding nonroutable protocols **38-1**

FTP  
 accessing MIB files **A-3**  
 configuration files  
   downloading **B-13**  
   overview **B-12**  
   preparing the server **B-13**  
   uploading **B-14**

image files  
 deleting old image **B-28**  
 downloading **B-26**  
 preparing the server **B-25**  
 uploading **B-28**

**G**

get-bulk-request operation **30-3**  
 get-next-request operation **30-3, 30-4**  
 get-request operation **30-3, 30-4**  
 get-response operation **30-3**  
 Gigabit modules  
 See SFPs  
 global configuration mode **2-2**  
 guest VLAN and 802.1x **9-8**  
 guide  
 audience **xxxvii**  
 purpose of **xxxvii**

guide mode **1-2**  
 GUIs  
 See device manager and Network Assistant **1-4**

**H**

hardware limitations and Layer 3 interfaces **10-24**  
 hello time  
 MSTP **18-20**  
 STP **17-22**  
 help, for the command line **2-3**  
 hierarchical policy maps **32-8**  
 configuration guidelines **32-33**  
 configuring **32-51**  
 described **32-10**  
 history  
 changing the buffer size **2-5**  
 described **2-4**  
 disabling **2-5**  
 recalling commands **2-5**  
 history table, level and number of syslog messages **29-10**  
 host ports  
 configuring **14-12**  
 kinds of **14-2**  
 hosts, limit on dynamic ports **12-33**  
 Hot Standby Router Protocol  
 See HSRP  
 HP OpenView **1-4**  
 HSRP  
 authentication string **35-9**  
 binding to cluster group **35-11**  
 command-switch redundancy **1-1, 1-5**  
 configuring **35-4**  
 default configuration **35-5**  
 definition **35-1**  
 guidelines **35-5**  
 monitoring **35-11**  
 overview **35-1**  
 priority **35-7**

- HSRP (continued)
- routing redundancy **1-9**
  - support for ICMP redirect messages **35-11**
  - switch stack considerations **35-4**
  - timers **35-9**
  - tracking **35-7**
- HTTP over SSL
- see HTTPS
- HTTPS **8-42**
- configuring **8-45**
  - self-signed certificate **8-43**
- HTTP secure server **8-42**
- 
- I**
- IBPG **34-40**
- ICMP
- redirect messages **34-12**
  - support for **1-10**
  - time-exceeded messages **39-18**
  - traceroute and **39-18**
  - unreachable messages **31-22**
  - unreachables and ACLs **31-23**
- ICMP ping
- executing **39-15**
  - overview **39-15**
- ICMP Router Discovery Protocol
- See IRDP
- IDS appliances
- and ingress RSPAN **27-21**
  - and ingress SPAN **27-15**
- IEEE 802.1p **15-1**
- ifIndex values, SNMP **30-5**
- IFS **1-5**
- IGMP
- configuring the switch
    - as a member of a group **36-27**
    - statically connected member **36-32**
  - controlling access to groups **36-28**
- IGMP (continued)
- default configuration **36-27**
  - deleting cache entries **36-51**
  - displaying groups **36-51**
  - fast switching **36-32**
  - host-query interval, modifying **36-30**
  - joining multicast group **23-3**
  - join messages **23-3**
  - leave processing, enabling **23-10**
  - leaving multicast group **23-5**
  - multicast reachability **36-27**
  - overview **36-2**
  - queries **23-4**
  - report suppression
    - described **23-5**
    - disabling **23-10**
  - support for **1-4**
  - Version 1
    - changing to Version 2 **36-29**
    - described **36-3**
  - Version 2
    - changing to Version 1 **36-29**
    - described **36-3**
    - maximum query response time value **36-31**
    - pruning groups **36-31**
    - query timeout value **36-31**
- IGMP filtering
- configuring **23-20**
  - default configuration **23-20**
  - described **23-19**
  - monitoring **23-24**
  - support for **1-4**
- IGMP groups
- configuring filtering **23-23**
  - setting the maximum number **23-22**
- IGMP profile
- applying **23-21**
  - configuration mode **23-20**
  - configuring **23-21**

IGMP snooping  
 and address aliasing **23-2**  
 and stack changes **23-6**  
 configuring **23-6**  
 default configuration **23-6**  
 definition **23-1**  
 enabling and disabling **23-7**  
 global configuration **23-7**  
**Immediate Leave** **23-5**  
 in the switch stack **23-6**  
 method **23-7**  
 monitoring **23-11**  
 support for **1-4**  
 VLAN configuration **23-7**

IGMP throttling  
 configuring **23-23**  
 default configuration **23-20**  
 described **23-20**  
 displaying action **23-24**

**IGP** **34-25**

**Immediate Leave, IGMP**  
 described **23-5**  
 enabling **23-10**

initial configuration  
 defaults **1-11**  
**Express Setup** **1-2**  
 See also getting started guide and hardware installation guide

interface  
 number **10-10**  
 range macros **10-13**

interface command **10-10 to 10-11**

interface configuration mode **2-2**

interfaces  
 configuration guidelines  
   10-Gigabit Ethernet **10-16**  
   duplex and speed **10-17**

interfaces (continued)  
 configuring  
   duplex mode **10-16**  
   procedure **10-11**  
   speed **10-16**  
 counters, clearing **10-27**  
 described **10-23**  
 descriptive name, adding **10-23**  
 displaying information about **10-26**  
 flow control **10-19**  
 management **1-4**  
 monitoring **10-26**  
 naming **10-23**  
 physical, identifying **10-10**  
 range of **10-11**  
 restarting **10-28**  
 shutting down **10-28**  
 status **10-26**  
 supported **10-10**  
 types of **10-1**  
 interfaces range macro command **10-13**  
 interface types **10-10**

**Interior Gateway Protocol**  
 See IGP

internal BGP  
 See IBGP

internal neighbors, BGP **34-43**

**Internet Control Message Protocol**  
 See ICMP

**Internet Group Management Protocol**  
 See IGMP

**Inter-Switch Link**  
 See ISL

inter-VLAN routing **1-9, 34-2**

**Intrusion Detection System**  
 See IDS appliances

ip access group command **31-22**

- IP ACLs
- applying to an interface **31-21**
  - extended, creating **31-11**
  - for QoS classification **32-7**
  - implicit deny **31-10, 31-15, 31-17**
  - implicit masks **31-10**
  - logging **31-17**
  - named **31-16**
  - standard, creating **31-10**
  - undefined **31-23**
  - virtual terminal lines, setting on **31-21**
- IP addresses
- candidate or member **5-3**
  - classes of **34-6**
  - command switch **5-2**
  - default configuration **34-5**
  - discovering **6-28**
  - for IP routing **34-5**
  - MAC address association **34-9**
  - monitoring **34-18**
  - See also IP information
- IP broadcast address **34-16**
- ip cef distributed command **34-61**
- IP directed broadcasts **34-14**
- ip igmp profile command **23-20**
- IP information
- assigned
    - manually **3-9**
    - through DHCP-based autoconfiguration **3-3**
  - default configuration **3-3**
- IP multicast routing
- addresses
    - all-hosts **36-3**
    - all-multicast-routers **36-3**
    - host group address range **36-3**
  - administratively-scoped boundaries, described **36-35**
  - and IGMP snooping **23-1**
- IP multicast routing (continued)
- Auto-RP
    - adding to an existing sparse-mode cloud **36-14**
    - benefits of **36-14**
    - clearing the cache **36-51**
    - configuration guidelines **36-10**
    - filtering incoming RP announcement messages **36-17**
    - overview **36-5**
    - preventing candidate RP spoofing **36-17**
    - preventing join messages to false RPs **36-16**
    - setting up in a new internetwork **36-14**
    - using with BSR **36-22**
  - bootstrap router
    - configuration guidelines **36-10**
    - configuring candidate BSRs **36-20**
    - configuring candidate RPs **36-21**
    - defining the IP multicast boundary **36-19**
    - defining the PIM domain border **36-18**
    - overview **36-5**
    - using with Auto-RP **36-22**
  - Cisco implementation **36-2**
  - configuring
    - basic multicast routing **36-10**
    - IP multicast boundary **36-35**
    - default configuration **36-8**
  - enabling
    - multicast forwarding **36-11**
    - PIM mode **36-11**
  - group-to-RP mappings
    - Auto-RP **36-5**
    - BSR **36-5**
  - MBONE
    - deleting sdr cache entries **36-51**
    - described **36-34**
    - displaying sdr cache **36-52**
    - enabling sdr listener support **36-34**
    - limiting DVMRP routes advertised **36-46**
    - limiting sdr cache entry lifetime **36-35**

- IP multicast routing (continued)
  - MBONE (continued)
    - SAP packets for conference session announcement **36-34**
  - Session Directory (sdr) tool, described **36-34**
  - monitoring
    - packet rate loss **36-52**
    - peering devices **36-52**
    - tracing a path **36-52**
  - multicast forwarding, described **36-6**
  - PIMv1 and PIMv2 interoperability **36-9**
  - protocol interaction **36-2**
  - reverse path check (RPF) **36-6**
  - routing table
    - deleting **36-51**
    - displaying **36-51**
  - RP
    - assigning manually **36-12**
    - configuring Auto-RP **36-14**
    - configuring PIMv2 BSR **36-18**
    - monitoring mapping information **36-23**
    - using Auto-RP and BSR **36-22**
  - stacking
    - stack master functions **36-8**
    - stack member functions **36-8**
  - statistics, displaying system and network **36-51**
  - See also CGMP
  - See also DVMRP
  - See also IGMP
  - See also PIM
  - IP phones
    - and QoS **15-1**
    - automatic classification and queueing **32-20**
    - configuring **15-4**
    - ensuring port security with QoS **32-38**
    - trusted boundary for QoS **32-38**
  - IP precedence **32-2**
  - IP-precedence-to-DSCP map for QoS **32-60**
- IP protocols
  - in ACLs **31-13**
  - routing **1-9**
- IP routes, monitoring **34-74**
- IP routing
  - connecting interfaces with **10-9**
  - disabling **34-19**
  - enabling **34-19**
- IP source guard
  - and 802.1x **21-15**
  - and DHCP snooping **21-14**
  - and EtherChannels **21-15**
  - and port security **21-15**
  - and private VLANs **21-15**
  - and routed ports **21-15**
  - and TCAM entries **21-15**
  - and trunk interfaces **21-15**
  - and VRF **21-15**
- binding configuration
  - automatic **21-14**
  - manual **21-14**
- binding table **21-14**
- configuration guidelines **21-15**
- default configuration **21-15**
- described **21-14**
- disabling **21-16**
- displaying
  - bindings **21-17**
  - configuration **21-17**
- enabling **21-16**
- filtering
  - source IP address **21-14**
  - source IP and MAC address **21-14**
  - source IP address filtering **21-14**
  - source IP and MAC address filtering **21-14**
- static bindings
  - adding **21-16**
  - deleting **21-16**

- IP traceroute  
 executing **39-19**  
 overview **39-18**
- IP unicast routing  
 address resolution **34-9**  
 administrative distances **34-63, 34-72**  
**ARP** **34-9**  
 assigning IP addresses to Layer 3 interfaces **34-6**  
 authentication keys **34-73**  
 broadcast  
   address **34-16**  
   flooding **34-17**  
   packets **34-14**  
   storms **34-14**  
 classless routing **34-7**  
 configuring static routes **34-62**  
 default  
   addressing configuration **34-5**  
   gateways **34-12**  
   networks **34-63**  
   routes **34-63**  
   routing **34-2**  
 directed broadcasts **34-14**  
 disabling **34-19**  
 dynamic routing **34-3**  
 enabling **34-19**  
 EtherChannel Layer 3 interface **34-4**  
**IGP** **34-25**  
 inter-VLAN **34-2**  
 IP addressing  
   classes **34-6**  
   configuring **34-5**  
**IRDP** **34-13**  
 Layer 3 interfaces **34-4**  
 MAC address and IP address **34-9**  
 passive interfaces **34-70**
- IP unicast routing (continued)  
 protocols  
   distance-vector **34-3**  
   dynamic **34-3**  
   link-state **34-3**  
   proxy ARP **34-9**  
   redistribution **34-64**  
   reverse address resolution **34-9**  
   routed ports **34-4**  
   static routing **34-2**  
   steps to configure **34-5**  
   subnet mask **34-6**  
   subnet zero **34-7**  
   supernet **34-7**  
   UDP **34-16**  
   with SVIs **34-4**  
 See also BGP  
 See also EIGRP  
 See also OSPF  
 See also RIP
- IRD**  
 configuring **34-13**  
 definition **34-13**  
 support for **1-10**
- ISL**  
 and trunk ports **10-3**  
 encapsulation **1-6, 12-16**  
 trunking with 802.1 tunneling **16-5**
- isolated port **14-2**  
 isolated VLANs **14-2, 14-3**
- 
- J**
- join messages, IGMP **23-3**

**K**

KDC

described **8-32**

See also Kerberos

keepalive messages **17-2**

Kerberos

authenticating to

boundary switch **8-35**KDC **8-35**network services **8-35**configuration examples **8-32**configuring **8-36**credentials **8-32**cryptographic software image **8-32**described **8-32**KDC **8-32**operation **8-34**realm **8-33**server **8-33**support for **1-8**switch as trusted third party **8-32**terms **8-33**TGT **8-34**tickets **8-32**

key distribution center

See KDC

**L**l2protocol-tunnel command **16-13**

LACP

Layer 2 protocol tunneling **16-9**

See EtherChannel

Layer 2 frames, classification with CoS **32-2**Layer 2 interfaces, default configuration **10-15**

Layer 2 protocol tunneling

configuring **16-10**configuring for EtherChannels **16-14**default configuration **16-11**defined **16-8**guidelines **16-12**

Layer 2 traceroute

and ARP **39-17**and CDP **39-17**broadcast traffic **39-17**described **39-17**IP addresses and subnets **39-17**MAC addresses and VLANs **39-17**multicast traffic **39-17**multiple devices on a port **39-18**unicast traffic **39-17**usage guidelines **39-17**Layer 2 trunks **12-17**Layer 3 features **1-9**

Layer 3 interfaces

assigning IP addresses to **34-6**changing from Layer 2 mode **34-6**types of **34-4**Layer 3 packets, classification methods **32-2**

LEDs, switch

See hardware installation guide

line configuration mode **2-2**

Link Aggregation Control Protocol

See EtherChannel

link redundancy

See Flex Links

links, unidirectional **26-1**link state advertisements (LSAs) **34-29**link-state protocols **34-3**load balancing **35-3**logging messages, ACL **31-11**

login authentication

  with RADIUS **8-23**

  with TACACS+ **8-14**

login banners **6-18**

log messages

  See system message logging

Long-Reach Ethernet (LRE) technology **1-15, 1-23**

loop guard

  described **19-11**

  enabling **19-18**

  support for **1-6**

## M

MAC addresses

  aging time **6-22**

  and VLAN association **6-21**

  building the address table **6-21**

  default configuration **6-22**

  discovering **6-28**

  displaying **6-28**

  displaying in the IP source binding table **21-17**

  dynamic

    learning **6-21**

    removing **6-23**

  in ACLs **31-28**

  IP address association **34-9**

  static

    adding **6-26**

    allowing **6-27**

    characteristics of **6-25**

    dropping **6-27**

    removing **6-26**

MAC address notification, support for **1-10**

MAC address-to-VLAN mapping **12-28**

MAC extended access lists

  applying to Layer 2 interfaces **31-30**

  configuring for QoS **32-45**

  creating **31-28**

  defined **31-28**

  for QoS classification **32-5**

macros

  See Smartports macros

manageability features **1-5**

management access

  in-band

    browser session **1-5**

    CLI session **1-5**

    device manager **1-5**

    SNMP **1-5**

  out-of-band console port connection **1-5**

management options

  CLI **2-1**

  clustering **1-3**

  Network Assistant **1-2**

  overview **1-4**

  switch stacks **1-3**

mapping tables for QoS

  configuring

    CoS-to-DSCP **32-59**

    DSCP **32-59**

    DSCP-to-CoS **32-62**

    DSCP-to-DSCP-mutation **32-63**

    IP-precedence-to-DSCP **32-60**

    policed-DSCP **32-61**

  described **32-12**

marking

  action in policy map **32-48**

  action with aggregate policers **32-57**

  described **32-4, 32-8**

matching, ACLs **31-8**

maximum aging time  
 MSTP **18-22**  
 STP **17-23**

maximum hop count, MSTP **18-22**

maximum-paths command **34-47, 34-62**

membership mode, VLAN port **12-3**

member switch  
 defined **5-2**  
 managing **5-4**  
 recovering from lost connectivity **39-13**  
 requirements **5-3**  
 See also candidate switch, cluster standby group, and standby command switch

messages  
 logging ACL violations **31-17**  
 to users through banners **6-18**

messages, to users through banners **6-18**

metrics, in BGP **34-48**

metric translations, between routing protocols **34-67**

metro tags **16-2**

MHSRP **35-3**

MIBs  
 accessing files with FTP **A-3**  
 location of files **A-3**  
 overview **30-1**  
 SNMP interaction with **30-4**  
 supported **A-1**

mini-point-of-presence  
 See POP

mirroring traffic for analysis **27-1**

mismatches, autonegotiation **39-13**

module number **10-10**

monitoring  
 802.1Q tunneling **16-18**  
 access groups **31-41**  
 ACL configuration **31-41**  
 BGP **34-59**  
 cables for unidirectional links **26-1**  
 CDP **25-5**

monitoring (continued)  
 CEF **34-61**  
 EIGRP **34-39**  
 fallback bridging **38-11**  
 features **1-10**  
 Flex Links **20-3**  
 HSRP **35-11**  
 IGMP  
 filters **23-24**  
 snooping **23-11**  
 interfaces **10-26**

IP  
 address tables **34-18**  
 multicast routing **36-50**  
 routes **34-74**  
 Layer 2 protocol tunneling **16-18**  
 MSDP peers **37-19**  
 multicast router interfaces **23-12**  
 MVR **23-19**  
 network traffic for analysis with probe **27-2**  
 OSPF **34-33**

port  
 blocking **24-16**  
 protection **24-16**  
 private VLANs **14-15**  
 RP mapping information **36-23**  
 SFP status **1-11, 10-27, 39-15**  
 source-active messages **37-19**  
 speed and duplex mode **10-19**  
 traffic flowing among switches **28-1**  
 traffic suppression **24-16**  
 tunneling **16-18**

VLAN  
 filters **31-42**  
 maps **31-42**  
 VLANs **12-15**  
 VMPS **12-32**  
 VTP **13-15, 13-16**

- MSDP
- benefits of **37-3**
  - clearing MSDP connections and statistics **37-19**
  - controlling source information
    - forwarded by switch **37-12**
    - originated by switch **37-9**
    - received by switch **37-14**
  - default configuration **37-4**
  - dense-mode regions
    - sending SA messages to **37-17**
    - specifying the originating address **37-18**
  - filtering
    - incoming SA messages **37-14**
    - SA messages to a peer **37-12**
    - SA requests from a peer **37-11**
  - join latency, defined **37-6**
  - meshed groups
    - configuring **37-16**
    - defined **37-16**
  - originating address, changing **37-18**
  - overview **37-1**
  - peer-RPF flooding **37-2**
  - peers
    - configuring a default **37-4**
    - monitoring **37-19**
    - peering relationship, overview **37-1**
    - requesting source information from **37-8**
    - shutting down **37-16**
  - source-active messages
    - caching **37-6**
    - clearing cache entries **37-19**
    - defined **37-2**
    - filtering from a peer **37-11**
    - filtering incoming **37-14**
    - filtering to a peer **37-12**
    - limiting data with TTL **37-14**
    - monitoring **37-19**
    - restricting advertised sources **37-9**
    - support for **1-10**
- MSTP
- boundary ports
  - configuration guidelines **18-14**
  - described **18-5**
  - BPDU filtering
    - described **19-3**
    - enabling **19-14**
  - BPDU guard
    - described **19-3**
    - enabling **19-13**
  - CIST, described **18-3**
  - configuration guidelines **18-13, 19-12**
  - configuring
    - forward-delay time **18-21**
    - hello time **18-20**
    - link type for rapid convergence **18-23**
    - maximum aging time **18-22**
    - maximum hop count **18-22**
    - MST region **18-14**
    - path cost **18-19**
    - port priority **18-18**
    - root switch **18-15**
    - secondary root switch **18-17**
    - switch priority **18-20**
  - CST
    - defined **18-3**
    - operations between regions **18-4**
  - default configuration **18-13**
  - default optional feature configuration **19-12**
  - displaying status **18-24**
  - enabling the mode **18-14**
  - EtherChannel guard
    - described **19-10**
    - enabling **19-17**
  - extended system ID
    - effects on root switch **18-15**
    - effects on secondary root switch **18-17**
    - unexpected behavior **18-16**
  - instances supported **17-10**

- MSTP (continued)
- interface state, blocking to forwarding **19-2**
  - interoperability and compatibility among modes **17-11**
  - interoperability with 802.1D
    - described **18-6**
    - restarting migration process **18-23**
  - IST
    - defined **18-3**
    - master **18-3**
    - operations within a region **18-3**
  - loop guard
    - described **19-11**
    - enabling **19-18**
  - mapping VLANs to MST instance **18-14**
  - MST region
    - CIST **18-3**
    - configuring **18-14**
    - described **18-2**
    - hop-count mechanism **18-5**
    - IST **18-3**
    - supported spanning-tree instances **18-2**
  - optional features supported **1-6**
  - overview **18-2**
  - Port Fast
    - described **19-2**
    - enabling **19-12**
  - preventing root switch selection **19-10**
  - root guard
    - described **19-10**
    - enabling **19-17**
  - root switch
    - configuring **18-16**
    - effects of extended system ID **18-15**
    - unexpected behavior **18-16**
  - shutdown Port Fast-enabled port **19-3**
  - stack changes, effects of **18-6**
  - status, displaying **18-24**
  - multicast groups
    - Immediate Leave **23-5**
    - joining **23-3**
    - leaving **23-5**
    - static joins **23-9**
  - multicast packets
    - ACLs on **31-41**
    - blocking **24-7**
    - multicast router interfaces, monitoring **23-12**
    - multicast router ports, adding **23-8**
  - Multicast Source Discovery Protocol
    - See MSDP
  - multicast storm **24-1**
  - multicast storm-control command **24-4**
  - Multicast VLAN Registration
    - See MVR
  - Multiple HSRP
    - See MHSRP
  - MVR
    - and address aliasing **23-16**
    - configuring interfaces **23-17**
    - default configuration **23-15**
    - described **23-12**
    - in the switch stack **23-15**
    - modes **23-17**
    - monitoring **23-19**
    - setting global parameters **23-16**
    - support for **1-4**
- 
- N**
- named IP ACLs **31-16**
  - native VLAN
    - and 802.1Q tunneling **16-4**
    - configuring **12-23**
    - default **12-23**
  - neighbor discovery/recovery, EIGRP **34-34**
  - neighbors, BGP **34-54**

- Network Assistant
- benefits **1-2**
  - described **1-4**
  - downloading image files **1-2**
  - guide mode **1-2**
  - management options **1-2**
  - managing switch stacks **4-2, 4-16**
  - requirements **xxxviii**
  - upgrading a switch **B-19**
  - wizards **1-2**
- network configuration examples
- cost-effective wiring closet **1-15**
  - high-performance wiring closet **1-16**
  - increasing network performance **1-14**
  - large network **1-20**
  - long-distance, high-bandwidth transport **1-24**
  - multidwelling network **1-23**
  - providing network services **1-15**
  - redundant Gigabit backbone **1-17**
  - server aggregation and Linux server cluster **1-17**
  - small to medium-sized network **1-19**
- network design
- performance **1-14**
  - services **1-15**
- network management
- CDP **25-1**
  - RMON **28-1**
  - SNMP **30-1**
- Network Time Protocol
- See NTP
- no commands **2-4**
- nonhierarchical policy maps
- configuration guidelines **32-33**
  - configuring **32-48**
  - described **32-9**
- non-IP traffic filtering **31-28**
- nontrunking mode **12-18**
- normal-range VLANs
- configuration modes **12-7**
  - defined **12-1**
- no switchport command **10-4**
- note, described **xxxviii**
- not-so-stubby areas
- See NSSA
- NSSA, OSPF **34-29**
- NTP
- associations
  - authenticating **6-5**
  - defined **6-2**
  - enabling broadcast messages **6-7**
  - peer **6-6**
  - server **6-6**
  - default configuration **6-4**
  - displaying the configuration **6-11**
  - overview **6-2**
  - restricting access
    - creating an access group **6-9**
    - disabling NTP services per interface **6-10**
  - source IP address, configuring **6-10**
  - stratum **6-2**
  - support for **1-5**
  - synchronizing devices **6-6**
  - time
    - services **6-2**
    - synchronizing **6-2**
- 
- O**
- offline configuration for switch stacks **4-7**
- Open Shortest Path First
- See OSPF
- optimizing system resources **7-1**
- options, management **1-4**

- OSPF
- area parameters, configuring **34-29**
  - configuring **34-27**
  - default configuration
    - metrics **34-31**
    - route **34-31**
    - settings **34-26**
  - described **34-25**
  - interface parameters, configuring **34-28**
  - LSA group pacing **34-32**
  - monitoring **34-33**
  - router IDs **34-32**
  - route summarization **34-30**
  - support for **1-9**
  - virtual links **34-30**
- out-of-profile markdown **1-9**
- 
- P**
- packet modification, with QoS **32-19**
- PAgP
- Layer 2 protocol tunneling **16-9**
  - See EtherChannel
- parallel paths, in routing tables **34-62**
- passive interfaces
- configuring **34-70**
  - OSPF **34-31**
- passwords
- default configuration **8-2**
  - disabling recovery of **8-5**
  - encrypting **8-4**
  - for security **1-7**
  - overview **8-1**
  - recovery of **39-3**
- passwords (continued)
- setting
  - enable **8-3**
  - enable secret **8-4**
  - Telnet **8-6**
  - with usernames **8-7**
- VTP domain **13-8**
- path cost
- MSTP **18-19**
  - STP **17-20**
- PBR
- defined **34-67**
  - enabling **34-69**
  - fast-switched policy-based routing **34-70**
  - local policy-based routing **34-70**
- peers, BGP **34-54**
- performance, network design **1-14**
- performance features **1-3**
- persistent self-signed certificate **8-43**
- per-VLAN spanning-tree plus
- See PVST+
- physical ports **10-2**
- PIM
- default configuration **36-8**
  - dense mode
    - overview **36-4**
    - rendezvous point (RP), described **36-4**
    - RPF lookups **36-7**
  - displaying neighbors **36-51**
  - enabling a mode **36-11**
  - overview **36-3**
  - router-query message interval, modifying **36-26**
  - shared tree and source tree, overview **36-23**
  - shortest path tree, delaying the use of **36-25**

- PIM (continued)
  - sparse mode
    - join messages and shared tree **36-4**
    - overview **36-4**
    - prune messages **36-5**
    - RPF lookups **36-7**
    - support for **1-10**
    - versions
      - interoperability **36-9**
      - troubleshooting interoperability problems **36-23**
      - v2 improvements **36-4**
  - PIM-DVMRP, as snooping method **23-8**
  - ping
    - character output description **39-16**
    - executing **39-15**
    - overview **39-15**
  - PoE
    - auto mode **10-8**
    - CDP with power consumption, described **10-6**
    - CDP with power negotiation, described **10-6**
    - Cisco intelligent power management **10-6**
    - configuring **10-21**
    - devices supported **10-6**
    - high-power devices operating in low-power mode **10-6**
    - IEEE power classification levels **10-7**
    - powered-device detection and initial power allocation **10-7**
    - power management modes **10-8**
    - power negotiation extensions to CDP **10-6**
    - standards supported **10-6**
    - static mode **10-8**
    - supported watts per port **10-6**
    - troubleshooting **39-13**
    - policed-DSCP map for QoS **32-61**
  - policers
    - configuring
      - for each matched traffic class **32-48**
      - for more than one traffic class **32-57**
    - described **32-4**
    - displaying **32-77**
    - number of **32-33**
    - types of **32-9**
  - policing
    - described **32-4**
  - hierarchical
    - See hierarchical policy maps
    - token-bucket algorithm **32-9**
  - policy-based routing
    - See PBR
  - policy maps
    - hierarchical **32-8**
    - policy maps for QoS
      - characteristics of **32-48**
      - described **32-7**
      - displaying **32-78**
      - hierarchical on SVIs
        - configuration guidelines **32-33**
        - configuring **32-51**
        - described **32-10**
      - nonhierarchical on physical ports
        - configuration guidelines **32-33**
        - configuring **32-48**
        - described **32-9**
    - POP **1-23**
    - port ACLs
      - defined **31-2**
      - types of **31-3**
    - Port Aggregation Protocol
      - See EtherChannel

port-based authentication  
 accounting **9-5**  
 authentication server  
   defined **9-2**  
   RADIUS server **9-2**  
 client, defined **9-2**  
 configuration guidelines **9-12**  
 configuring  
   802.1x authentication **9-14**  
   guest VLAN **9-20**  
   host mode **9-19**  
   manual re-authentication of a client **9-17**  
   periodic re-authentication **9-16**  
   quiet period **9-17**  
   RADIUS server **9-16**  
   RADIUS server parameters on the switch **9-15**  
   switch-to-client frame-retransmission number **9-18,**  
**9-19**  
   switch-to-client retransmission time **9-17**  
 default configuration **9-11**  
 described **9-1**  
 device roles **9-2**  
 displaying statistics **9-23**  
 EAPOL-start frame **9-3**  
 EAP-request/identity frame **9-3**  
 EAP-response/identity frame **9-3**  
 encapsulation **9-3**  
 guest VLAN  
   configuration guidelines **9-9**  
   described **9-8**  
 host mode **9-5**  
 initiation and message exchange **9-3**  
 method lists **9-14**  
 multiple-hosts mode, described **9-5**  
 per-user ACLs  
   AAA authorization **9-14**  
   configuration tasks **9-10**  
   described **9-9**  
 RADIUS server attributes **9-9**

ports  
   authorization state and dot1x port-control command **9-4**  
   authorized and unauthorized **9-4**  
   voice VLAN **9-7**  
 port security  
   and voice VLAN **9-6**  
   described **9-6**  
   interactions **9-6**  
   multiple-hosts mode **9-5**  
   resetting to default values **9-22**  
   stack changes, effects of **9-10**  
   statistics, displaying **9-23**  
 switch  
   as proxy **9-2**  
   RADIUS client **9-2**  
 upgrading from a previous release **9-13, 32-26**  
 VLAN assignment  
   AAA authorization **9-14**  
   characteristics **9-8**  
   configuration tasks **9-8**  
   described **9-7**  
   voice VLAN  
    described **9-7**  
    PVID **9-7**  
    VVID **9-7**  
   port blocking **1-4, 24-6**  
 port-channel  
   See EtherChannel  
 Port Fast  
   described **19-2**  
   enabling **19-12**  
   mode, spanning tree **12-29**  
   support for **1-6**  
 port membership modes, VLAN **12-3**  
 port priority  
   MSTP **18-18**  
   STP **17-18**

- ports
  - 10-Gigabit Ethernet module **10-6**
  - 802.1Q tunnel **12-4**
  - access **10-3**
  - blocking **24-6**
  - dynamic access **12-4**
  - protected **24-5**
  - routed **10-4**
  - secure **24-7**
  - static-access **12-3, 12-11**
  - switch **10-2**
  - trunks **12-3, 12-16**
  - VLAN assignments **12-11**
- port security
  - aging **24-15**
  - and QoS trusted boundary **32-38**
  - and stacking **24-16**
  - configuring **24-12**
  - default configuration **24-10**
  - described **24-7**
  - displaying **24-16**
  - on trunk ports **24-13**
  - sticky learning **24-8**
  - violations **24-9**
  - with other features **24-10**
- port-shutdown response, VMPS **12-28**
- Power over Ethernet
  - See PoE
- preferential treatment of traffic
  - See QoS
- prefix lists, BGP **34-51**
- preventing unauthorized access **8-1**
- primary links **20-1**
- primary VLANs **14-1, 14-3**
- priority
  - HSRP **35-7**
  - overriding CoS **15-6**
  - trusting CoS **15-6**
- private VLAN edge ports
  - See protected ports
- private VLANs
  - across multiple switches **14-4**
  - and SDM template **14-4**
  - and SVIs **14-5**
  - and switch stacks **14-6**
  - benefits of **14-1**
  - community ports **14-2**
  - community VLANs **14-2, 14-3**
  - configuration guidelines **14-7, 14-9**
  - configuration tasks **14-6**
  - configuring **14-10**
  - default configuration **14-7**
  - end station access to **14-3**
  - IP addressing **14-3**
  - isolated port **14-2**
  - isolated VLANs **14-2, 14-3**
  - mapping **14-14**
  - monitoring **14-15**
  - ports
    - community **14-2**
    - configuration guidelines **14-9**
    - configuring host ports **14-12**
    - configuring promiscuous ports **14-13**
    - described **12-4**
    - isolated **14-2**
    - promiscuous **14-2**
  - primary VLANs **14-1, 14-3**
  - promiscuous ports **14-2**
  - secondary VLANs **14-2**
  - subdomains **14-1**
  - traffic in **14-5**
  - privileged EXEC mode **2-2**
  - privilege levels
    - changing the default for lines **8-9**
    - command switch **5-4**
    - exiting **8-10**
    - logging into **8-10**

privilege levels (continued)

- mapping on member switches **5-4**
- overview **8-2, 8-8**
- setting a command with **8-8**

promiscuous ports

- configuring **14-13**
- defined **14-2**

protected ports **1-7, 24-5**

protocol-dependent modules, EIGRP **34-35**

Protocol-Independent Multicast Protocol

- See PIM

provisioning new members for a switch stack **4-7**

proxy ARP

- configuring **34-11**
- definition **34-9**
- with IP routing disabled **34-12**

pruning, VTP

- disabling
  - in VTP domain **13-14**
  - on a port **12-23**
- enabling
  - in VTP domain **13-14**
  - on a port **12-22**
- examples **13-5**
- overview **13-4**

pruning-eligible list

- changing **12-22**
- for VTP pruning **13-5**
- VLANs **13-14**

PVST+

- 802.1Q trunking interoperability **17-11**
- described **17-10**
- instances supported **17-10**

**Q**

QoS

- and MQC commands **32-1**
- auto-QoS
  - categorizing traffic **32-20**
  - configuration and defaults display **32-30**
  - configuration guidelines **32-25**
  - described **32-20**
  - disabling **32-27**
  - displaying generated commands **32-27**
  - displaying the initial configuration **32-30**
  - effects on running configuration **32-25**
  - egress queue defaults **32-21**
  - enabling for VoIP **32-27**
  - example configuration **32-28**
  - ingress queue defaults **32-21**
  - list of generated commands **32-22**
  - basic model **32-4**
- classification
  - class maps, described **32-7**
  - defined **32-4**
  - DSCP transparency, described **32-39**
  - flowchart **32-6**
  - forwarding treatment **32-3**
  - in frames and packets **32-3**
  - IP ACLs, described **32-5, 32-7**
  - MAC ACLs, described **32-5, 32-7**
  - options for IP traffic **32-5**
  - options for non-IP traffic **32-5**
  - policy maps, described **32-7**
  - trust DSCP, described **32-5**
  - trusted CoS, described **32-5**
  - trust IP precedence, described **32-5**
- class maps
  - configuring **32-46**
  - displaying **32-77**

- QoS (continued)
- configuration guidelines
    - auto-QoS [32-25](#)
    - standard QoS [32-33](#)
  - configuring
    - aggregate policers [32-57](#)
    - auto-QoS [32-20](#)
    - default port CoS value [32-37](#)
    - DSCP maps [32-59](#)
    - DSCP transparency [32-39](#)
    - DSCP trust states bordering another domain [32-40](#)
    - egress queue characteristics [32-70](#)
    - ingress queue characteristics [32-65](#)
    - IP extended ACLs [32-44](#)
    - IP standard ACLs [32-42](#)
    - MAC ACLs [32-45](#)
    - policy maps, hierarchical [32-51](#)
    - policy maps on physical ports [32-48](#)
    - port trust states within the domain [32-35](#)
    - trusted boundary [32-38](#)
    - default auto configuration [32-20](#)
    - default standard configuration [32-31](#)
    - displaying statistics [32-77](#)
    - DSCP transparency [32-39](#)
    - egress queues
      - allocating buffer space [32-70](#)
      - buffer allocation scheme, described [32-18](#)
      - configuring shaped weights for SRR [32-74](#)
      - configuring shared weights for SRR [32-75](#)
      - described [32-4](#)
      - displaying the threshold map [32-73](#)
      - flowchart [32-17](#)
      - mapping DSCP or CoS values [32-72](#)
      - scheduling, described [32-4](#)
      - setting WTD thresholds [32-70](#)
      - WTD, described [32-19](#)
      - enabling globally [32-34](#)
  - QoS (continued)
    - flowcharts
      - classification [32-6](#)
      - egress queueing and scheduling [32-17](#)
      - ingress queueing and scheduling [32-15](#)
      - policing and marking [32-11](#)
    - implicit deny [32-7](#)
    - ingress queues
      - allocating bandwidth [32-68](#)
      - allocating buffer space [32-67](#)
      - buffer and bandwidth allocation, described [32-16](#)
      - configuring shared weights for SRR [32-68](#)
      - configuring the priority queue [32-69](#)
      - described [32-4](#)
      - displaying the threshold map [32-66](#)
      - flowchart [32-15](#)
      - mapping DSCP or CoS values [32-66](#)
      - priority queue, described [32-16](#)
      - scheduling, described [32-4](#)
      - setting WTD thresholds [32-66](#)
      - WTD, described [32-16](#)
    - IP phones
      - automatic classification and queueing [32-20](#)
      - detection and trusted settings [32-20, 32-38](#)
      - limiting bandwidth on egress interface [32-76](#)
    - mapping tables
      - CoS-to-DSCP [32-59](#)
      - displaying [32-77](#)
      - DSCP-to-CoS [32-62](#)
      - DSCP-to-DSCP-mutation [32-63](#)
      - IP-precedence-to-DSCP [32-60](#)
      - policed-DSCP [32-61](#)
      - types of [32-12](#)
    - marked-down actions [32-50, 32-54](#)
    - marking, described [32-4, 32-8](#)
    - overview [32-2](#)
    - packet modification [32-19](#)

- 
- QoS (continued)
- policers
    - configuring **32-50, 32-54, 32-57**
    - described **32-8**
    - displaying **32-77**
    - number of **32-33**
    - types of **32-9**
  - policies, attaching to an interface **32-8**
  - policing
    - described **32-4, 32-8**
    - token bucket algorithm **32-9**
  - policy maps
    - characteristics of **32-48**
    - displaying **32-78**
    - hierarchical **32-8**
    - hierarchical on SVIs **32-51**
    - nonhierarchical on physical ports **32-48**
  - QoS label, defined **32-4**
  - queues
    - configuring egress characteristics **32-70**
    - configuring ingress characteristics **32-65**
    - high priority (expedite) **32-19, 32-76**
    - location of **32-13**
    - SRR, described **32-14**
    - WTD, described **32-13**
  - rewrites **32-19**
  - support for **1-8**
  - trust states
    - bordering another domain **32-40**
    - described **32-5**
    - trusted device **32-38**
    - within the domain **32-35**
  - quality of service
    - See QoS
  - queries, IGMP **23-4**
- 
- R**
- RADIUS
- attributes
    - vendor-proprietary **8-31**
    - vendor-specific **8-29**
  - configuring
    - accounting **8-28**
    - authentication **8-23**
    - authorization **8-27**
    - communication, global **8-21, 8-29**
    - communication, per-server **8-21**
    - multiple UDP ports **8-21**
  - default configuration **8-20**
  - defining AAA server groups **8-25**
  - displaying the configuration **8-31**
  - identifying the server **8-21**
  - limiting the services to the user **8-27**
  - method list, defined **8-20**
  - operation of **8-19**
  - overview **8-18**
  - suggested network environments **8-18**
  - support for **1-8**
  - tracking services accessed by user **8-28**
- range
- macro **10-13**
  - of interfaces **10-12**
- rapid convergence **18-8**
- rapid per-VLAN spanning-tree plus
- See rapid PVST+
- rapid PVST+
- 802.1Q trunking interoperability **17-11**
  - described **17-10**
  - instances supported **17-10**
- Rapid Spanning Tree Protocol
- See RSTP
- RARP **34-9**
- rcommand command **5-4**

- RCP
- configuration files
    - downloading **B-17**
    - overview **B-15**
    - preparing the server **B-16**
    - uploading **B-18**
  - image files
    - deleting old image **B-32**
    - downloading **B-31**
    - preparing the server **B-29**
    - uploading **B-33**
  - reconfirmation interval, VMPS, changing **12-31**
  - recovery procedures **39-1**
  - redundancy
    - EtherChannel **33-2**
    - HSRP **35-1**
    - STP
      - backbone **17-9**
      - multidrop backbone **19-5**
      - path cost **12-26**
      - port priority **12-24**
    - redundant links and UplinkFast **19-15**
    - reliable transport protocol, EIGRP **34-34**
    - reloading software **3-16**
  - Remote Authentication Dial-In User Service
    - See RADIUS
  - Remote Copy Protocol
    - See RCP
  - Remote Network Monitoring
    - See RMON
  - Remote SPAN
    - See RSPAN
  - report suppression, IGMP
    - described **23-5**
    - disabling **23-10**
  - requirements
    - cluster **xxxix**
    - device manager **xxxviii**
    - Network Assistant **xxxviii**
  - resequencing ACL entries **31-16**
  - resets, in BGP **34-46**
  - resetting a UDLD-shutdown interface **26-6**
  - restricting access
    - NTP services **6-8**
    - overview **8-1**
    - passwords and privilege levels **8-2**
    - RADIUS **8-17**
    - TACACS+ **8-10**
  - retry count, VMPS, changing **12-32**
  - reverse address resolution **34-9**
  - Reverse Address Resolution Protocol
    - See RARP
  - RFC
    - 1058, RIP **34-20**
    - 1112, IP multicast and IGMP **23-2**
    - 1157, SNMPv1 **30-2**
    - 1163, BGP **34-40**
    - 1166, IP addresses **34-6**
    - 1253, OSPF **34-25**
    - 1267, BGP **34-40**
    - 1305, NTP **6-2**
    - 1587, NSSAs **34-25**
    - 1757, RMON **28-2**
    - 1771, BGP **34-40**
    - 1901, SNMPv2C **30-2**
    - 1902 to 1907, SNMPv2 **30-2**
    - 2236, IP multicast and IGMP **23-2**
    - 2273-2275, SNMPv3 **30-2**
  - RIP
    - advertisements **34-20**
    - authentication **34-23**
    - configuring **34-21**
    - default configuration **34-20**
    - described **34-20**
    - hop counts **34-20**
    - split horizon **34-23**
    - summary addresses **34-23**
    - support for **1-9**

RMON  
 default configuration **28-3**  
 displaying status **28-6**  
 enabling alarms and events **28-3**  
 groups supported **28-2**  
 overview **28-1**  
 statistics  
   collecting group Ethernet **28-6**  
   collecting group history **28-5**  
 support for **1-10**

root guard  
 described **19-10**  
 enabling **19-17**  
 support for **1-6**

root switch  
 MSTP **18-15**  
 STP **17-16**

route calculation timers, OSPF **34-31**

route dampening, BGP **34-58**

routed packets, ACLs on **31-40**

routed ports  
 configuring **34-4**  
 defined **10-4**  
 IP addresses on **10-24, 34-5**

route-map command **34-69**

route maps  
 BGP **34-49**  
 policy-based routing **34-68**

router ACLs  
 defined **31-2**  
 types of **31-4**

route reflectors, BGP **34-57**

router ID, OSPF **34-32**

route selection, BGP **34-47**

route summarization, OSPF **34-30**

routing  
 default **34-2**  
 dynamic **34-3**  
 redistribution of information **34-64**  
 static **34-2**  
 routing domain confederation, BGP **34-56**

Routing Information Protocol  
 See RIP

routing protocol administrative distances **34-63**

RSPAN  
 and stack changes **27-10**  
 characteristics **27-9**  
 configuration guidelines **27-17**  
 default configuration **27-11**  
 destination ports **27-7**  
 displaying status **27-24**  
 in a switch stack **27-2**  
 interaction with other features **27-9**  
 monitored ports **27-6**  
 monitoring ports **27-7**  
 overview **1-10, 27-1**  
 received traffic **27-5**  
 session limits **27-11**  
 sessions  
   creating **27-18**  
   defined **27-4**  
   limiting source traffic to specific VLANs **27-23**  
   specifying monitored ports **27-18**  
   with ingress traffic enabled **27-21**  
 source ports **27-6**  
 transmitted traffic **27-6**  
 VLAN-based **27-7**

RSTP  
 active topology **18-7**

BPDU  
 format **18-10**  
 processing **18-11**

RSTP (continued)  
 designated port, defined **18-7**  
 designated switch, defined **18-7**  
 interoperability with 802.1D  
 described **18-6**  
 restarting migration process **18-23**  
 topology changes **18-11**  
 overview **18-6**  
 port roles  
 described **18-7**  
 synchronized **18-9**  
 proposal-agreement handshake process **18-8**  
 rapid convergence  
 cross-stack rapid convergence **18-8**  
 described **18-8**  
 edge ports and Port Fast **18-8**  
 point-to-point links **18-8, 18-23**  
 root ports **18-8**  
 root port, defined **18-7**  
 See also MSTP  
 running configuration, saving **3-10**

**S**

scheduled reloads **3-16**  
 SDM  
 described **7-1**  
 switch stack consideration **4-10**  
 templates  
 configuring **7-4**  
 number of **7-1**  
 SDM mismatch mode **4-10, 7-2**  
 SDM template  
 aggregator **7-1**  
 configuring **7-3**  
 desktop **7-1**  
 types of **7-1**  
 secondary VLANs **14-2**

secure HTTP client  
 configuring **8-47**  
 displaying **8-48**  
 secure HTTP server  
 configuring **8-46**  
 displaying **8-48**  
 secure MAC addresses  
 and switch stacks **24-16**  
 deleting **24-14**  
 maximum number of **24-8**  
 types of **24-8**  
 secure ports  
 and switch stacks **24-16**  
 configuring **24-7**  
 secure remote connections **8-38**  
 Secure Shell  
 See SSH  
 Secure Socket Layer  
 See SSL  
 security, port **24-7**  
 security features **1-7**  
 sequence numbers in log messages **29-8**  
 server mode, VTP **13-3**  
 service-provider network, MSTP and RSTP **18-1**  
 service-provider networks  
 and 802.1Q tunneling **16-1**  
 and customer VLANs **16-2**  
 Layer 2 protocols across **16-8**  
 Layer 2 protocol tunneling for EtherChannels **16-9**  
 set-request operation **30-4**  
 setup program  
 failed command switch replacement **39-11**  
 replacing failed command switch **39-10**  
 severity levels, defining in system messages **29-9**  
 SFPs  
 monitoring status of **1-11, 10-27, 39-15**  
 numbering of **10-10**  
 security and identification **39-14**  
 status, displaying **1-11**

- shaped round robin  
See SRR
- show access-lists hw-summary command **31-23**
- show and more command output, filtering **2-8**
- show cdp traffic command **25-5**
- show cluster members command **5-4**
- show configuration command **10-23**
- show forward command **39-23**
- show interfaces command **10-19, 10-23**
- show l2protocol command **16-13, 16-15, 16-16**
- show platform forward command **39-23**
- show running-config command  
  displaying ACLs **31-21, 31-22, 31-33, 31-35**  
  interface description in **10-23**
- shutdown command on interfaces **10-28**
- shutdown threshold for Layer 2 protocol packets **16-11**
- Simple Network Management Protocol  
See SNMP
- small form-factor pluggable modules  
See SFPs
- Smartports macros  
  applying Cisco-default macros **11-6**  
  applying global parameter values **11-5, 11-6**  
  applying macros **11-5**  
  applying parameter values **11-5, 11-7**  
  configuration guidelines **11-3**  
  creating **11-4**  
  default configuration **11-2**  
  defined **11-1**  
  displaying **11-8**  
  tracing **11-3**  
  website **11-2**
- SNAP **25-1**
- SNMP  
  accessing MIB variables with **30-4**  
  agent  
    described **30-4**  
    disabling **30-8**  
  authentication level **30-10**  
  SNMP (continued)  
    community strings  
    configuring **30-8**  
    for cluster switches **30-4**  
    overview **30-4**  
    configuration examples **30-16**  
    default configuration **30-6**  
    engine ID **30-7**  
    groups **30-7, 30-9**  
    host **30-7**  
    ifIndex values **30-5**  
    in-band management **1-5**  
    informs  
      and trap keyword **30-11**  
      described **30-5**  
      differences from traps **30-5**  
      disabling **30-14**  
      enabling **30-14**  
    limiting access by TFTP servers **30-15**  
    limiting system log messages to NMS **29-10**  
    manager functions **1-4, 30-3**  
    managing clusters with **5-5**  
    MIBs  
      location of **A-3**  
      supported **A-1**  
      notifications **30-5**  
      overview **30-1, 30-4**  
      security levels **30-3**  
      status, displaying **30-17**  
      system contact and location **30-15**  
      trap manager, configuring **30-13**  
      traps  
        described **30-3, 30-5**  
        differences from informs **30-5**  
        disabling **30-14**  
        enabling **30-11**  
        enabling MAC address notification **6-23**  
        overview **30-1, 30-4**  
        types of **30-11**

- SNMP (continued)
- users **30-7, 30-9**
  - versions supported **30-2**
- SNMPv1 **30-2**
- SNMPv2C **30-2**
- SNMPv3 **30-2**
- snooping, IGMP **23-1**
- software compatibility
- See stacks, switch
- software images
- location in flash **B-20**
  - recovery procedures **39-2**
  - scheduling reloads **3-16**
  - tar file format, described **B-20**
  - See also downloading and uploading
- source addresses, in ACLs **31-13**
- source-and-destination-IP address based forwarding, EtherChannel **33-8**
- source-and-destination MAC address forwarding, EtherChannel **33-8**
- source-IP address based forwarding, EtherChannel **33-8**
- source-MAC address forwarding, EtherChannel **33-7**
- SPAN
- and stack changes **27-10**
  - configuration guidelines **27-11**
  - default configuration **27-11**
  - destination ports **27-7**
  - displaying status **27-24**
  - interaction with other features **27-9**
  - monitored ports **27-6**
  - monitoring ports **27-7**
  - overview **1-10, 27-1**
  - ports, restrictions **24-11**
  - received traffic **27-5**
  - session limits **27-11**
- SPAN (continued)
- sessions
  - configuring ingress forwarding **27-16, 27-22**
  - creating **27-12**
  - defined **27-4**
  - limiting source traffic to specific VLANs **27-16**
  - removing destination (monitoring) ports **27-14**
  - specifying monitored ports **27-12**
  - with ingress traffic enabled **27-15**
  - source ports **27-6**
  - transmitted traffic **27-6**
  - VLAN-based **27-7**
- spanning tree and native VLANs **12-19**
- Spanning Tree Protocol
- See STP
- SPAN traffic **27-5**
- speed, configuring on interfaces **10-16**
- split horizon, RIP **34-23**
- SRR
- configuring
  - shaped weights on egress queues **32-74**
  - shared weights on egress queues **32-75**
  - shared weights on ingress queues **32-68**
  - described **32-14**
  - shaped mode **32-14**
  - shared mode **32-14**
  - support for **1-9**
- SSH
- configuring **8-39**
  - cryptographic software image **8-37**
  - described **1-5, 8-38**
  - encryption methods **8-38**
  - switch stack considerations **4-17, 8-38**
  - user authentication methods, supported **8-38**

- SSL
- configuration guidelines [8-44](#)
  - configuring a secure HTTP client [8-47](#)
  - configuring a secure HTTP server [8-45](#)
  - cryptographic software image [8-42](#)
  - described [8-41](#)
  - monitoring [8-48](#)
- stack changes, effects on
- 802.1x port-based authentication [9-10](#)
  - ACL configuration [31-7](#)
  - CDP [25-2](#)
  - cross-stack EtherChannel [33-12](#)
  - EtherChannel [33-9](#)
  - fallback bridging [38-3](#)
  - HSRP [35-4](#)
  - IGMP snooping [23-6](#)
  - IP routing [34-3](#)
  - MAC address tables [6-22](#)
  - MSTP [18-6](#)
  - multicast routing [36-8](#)
  - MVR [23-13](#)
  - port security [24-16](#)
  - SDM template selection [7-2](#)
  - SNMP [30-1](#)
  - SPAN and RSPAN [27-10](#)
  - STP [17-12](#)
  - system message log [29-2](#)
  - VLANs [12-7](#)
  - VTP [13-6](#)
- stack master
- bridge ID (MAC address) [4-5](#)
  - defined [4-1](#)
  - election [4-4](#)
  - re-election [4-4](#)
- See also stacks, switch
- stack member
- accessing CLI of specific member [4-22](#)
  - configuring
    - member number [4-20](#)
    - priority value [4-21](#)
    - defined [4-1](#)
    - displaying information of [4-22](#)
    - number [4-6](#)
    - priority value [4-7](#)
    - provisioning a new member [4-21](#)
    - replacing [4-15](#)
- See also stacks, switch
- stack member number [10-10](#)
- stack protocol version [4-11](#)
- stacks, switch
- accessing CLI of specific member [4-22](#)
  - assigning information
    - member number [4-20](#)
    - priority value [4-21](#)
    - provisioning a new member [4-21](#)  - auto-advise [4-12](#)
  - auto-copy [4-12](#)
  - auto-upgrade [4-12](#)
  - benefits [1-2](#)
  - bridge ID [4-5](#)
  - CDP considerations [25-2](#)
  - compatibility, software [4-10](#)
  - configuration file [4-15](#)
  - configuration scenarios [4-17](#)
  - copying an image file from one member to another [B-34](#)
  - default configuration [4-20](#)
  - description of [4-1](#)
  - displaying information of [4-22](#)
  - hardware compatibility and SDM mismatch mode [4-10](#)
  - HSRP considerations [35-4](#)

- stacks, switch (continued)
- incompatible software and image upgrades **4-15, B-34**
  - MAC address considerations **6-22**
  - management connectivity **4-16**
  - managing **4-1**
  - membership **4-3**
  - merged **4-3**
  - MSTP instances supported **17-10**
  - multicast routing, stack master and member roles **36-8**
  - offline configuration
    - described **4-7**
    - effects of adding a provisioned switch **4-8**
    - effects of removing a provisioned switch **4-10**
    - effects of replacing a provisioned switch **4-10**
  - provisioned configuration, defined **4-7**
  - provisioned switch, defined **4-7**
  - provisioning a new member **4-21**
  - partitioned **4-3, 39-9**
  - provisioned switch
    - adding **4-8**
    - removing **4-10**
    - replacing **4-10**
  - replacing a failed member **4-15**
  - See also stack master and stack member
  - software compatibility **4-10**
  - software image version **4-10**
  - stack protocol version **4-11**
  - STP
    - bridge ID **17-3**
    - instances supported **17-10**
    - root port selection **17-3**
    - stack root switch election **17-3**
  - system messages
    - hostnames in the display **29-1**
    - remotely monitoring **29-2**
  - system prompt consideration **6-14**
  - system-wide configuration considerations **4-16**
  - upgrading **B-34**
- stacks, switch (continued)
- version-mismatch (VM) mode
    - automatic upgrades with auto-upgrade **4-12**
    - described **4-12**
    - examples **4-13**
    - manual upgrades with auto-advise **4-12**
  - StackWise technology, Cisco **1-3**
    - See also stacks, switch
  - standby command switch, requirements **5-2**
  - standby ip command **35-5**
  - standby links **20-1**
  - standby router **35-1**
  - standby timers, HSRP **35-9**
  - startup configuration
    - booting
      - manually **3-13**
      - specific image **3-13**
    - clearing **B-19**
    - configuration file
      - automatically downloading **3-12**
      - specifying the filename **3-12**
      - default boot configuration **3-12**
  - static access ports
    - assigning to VLAN **12-11**
    - defined **10-3, 12-3**
  - static addresses
    - See addresses
  - static IP routing **1-9**
  - static MAC addressing **1-7**
  - static routes, configuring **34-62**
  - static routing **34-2**
  - static VLAN membership **12-2**
  - statistics
    - 802.1x **9-23**
    - CDP **25-5**
    - interface **10-26**
    - IP multicast routing **36-51**
    - OSPF **34-33**

- statistics (continued)
- QoS ingress and egress **32-77**
  - RMON group Ethernet **28-6**
  - RMON group history **28-5**
  - SNMP input and output **30-17**
  - VTP **13-15**
  - sticky learning **24-8**
  - storm control
    - configuring **24-3**
    - described **24-1**
    - disabling **24-5**
    - displaying **24-16**
    - support for **1-4**
    - thresholds **24-1**
  - STP
    - 802.1D and bridge ID **17-4**
    - 802.1D and multicast addresses **17-9**
    - 802.1t and VLAN identifier **17-4**
    - accelerating root port selection **19-4**
    - BackboneFast
      - described **19-7**
      - disabling **19-17**
      - enabling **19-16**
    - BPDU filtering
      - described **19-3**
      - disabling **19-15**
      - enabling **19-14**
    - BPDU guard
      - described **19-3**
      - disabling **19-14**
      - enabling **19-13**
    - BPDU message exchange **17-3**
    - configuration guidelines **17-13, 19-12**
    - STP (continued)
      - configuring
      - forward-delay time **17-23**
      - hello time **17-22**
      - maximum aging time **17-23**
      - path cost **17-20**
      - port priority **17-18**
      - root switch **17-16**
      - secondary root switch **17-18**
      - spanning-tree mode **17-15**
      - switch priority **17-21**
      - counters, clearing **17-24**
      - cross-stack UplinkFast
        - described **19-5**
        - enabling **19-16**
      - default configuration **17-13**
      - default optional feature configuration **19-12**
      - designated port, defined **17-4**
      - designated switch, defined **17-4**
      - detecting indirect link failures **19-8**
      - disabling **17-16**
      - displaying status **17-24**
      - EtherChannel guard
        - described **19-10**
        - disabling **19-17**
        - enabling **19-17**
      - extended system ID
        - effects on root switch **17-16**
        - effects on the secondary root switch **17-18**
        - overview **17-4**
        - unexpected behavior **17-16**
      - features supported **1-6**
      - inferior BPDU **17-3**
      - instances supported **17-10**
      - interface state, blocking to forwarding **19-2**

- STP (continued)
- interface states
    - blocking **17-7**
    - disabled **17-8**
    - forwarding **17-6, 17-7**
    - learning **17-7**
    - listening **17-7**
    - overview **17-5**
  - interoperability and compatibility among modes **17-11**
  - keepalive messages **17-2**
  - Layer 2 protocol tunneling **16-8**
  - limitations with 802.1Q trunks **17-11**
  - load sharing
    - overview **12-24**
    - using path costs **12-26**
    - using port priorities **12-24**
  - loop guard
    - described **19-11**
    - enabling **19-18**
  - modes supported **17-10**
  - multicast addresses, effect of **17-9**
  - optional features supported **1-6**
  - overview **17-2**
  - path costs **12-26, 12-27**
  - Port Fast
    - described **19-2**
    - enabling **19-12**
  - port priorities **12-25**
  - preventing root switch selection **19-10**
  - protocols supported **17-10**
  - redundant connectivity **17-9**
  - root guard
    - described **19-10**
    - enabling **19-17**
  - root port, defined **17-3**
  - root port selection on a switch stack **17-3**
- STP (continued)
- root switch
    - configuring **17-16**
    - effects of extended system ID **17-4, 17-16**
    - election **17-3**
    - unexpected behavior **17-16**
  - shutdown Port Fast-enabled port **19-3**
  - stack changes, effects of **17-12**
  - status, displaying **17-24**
  - superior BPDU **17-3**
  - timers, described **17-22**
  - UplinkFast
    - described **19-4**
    - enabling **19-15**
  - VLAN-bridge **17-12**
  - stratum, NTP **6-2**
  - stub areas, OSPF **34-29**
  - subdomains, private VLAN **14-1**
  - subnet mask **34-6**
  - subnet zero **34-7**
  - success response, VMPS **12-28**
  - summer time **6-13**
  - SunNet Manager **1-4**
  - supernet **34-7**
  - SVIs
    - and IP unicast routing **34-4**
    - and router ACLs **31-4**
    - connecting VLANs **10-9**
    - defined **10-5**
    - routing between VLANs **12-2**
  - switch clustering technology **5-1**
    - See also clusters, switch
  - switch console port **1-5**
  - Switch Database Management
    - See SDM
  - switched packets, ACLs on **31-39**
  - Switched Port Analyzer
    - See SPAN
  - switched ports **10-2**

- switchport block multicast command **24-7**  
 switchport block unicast command **24-7**  
 switchport command **10-15**  
 switchport mode dot1q-tunnel command **16-6**  
 switchport protected command **24-6**  
 switch priority  
   MSTP **18-20**  
   STP **17-21**  
 switch software features **1-1**  
 switch virtual interface  
   See SVI  
 synchronization, BGP **34-44**  
 syslog  
   See system message logging  
 system clock  
   configuring  
     daylight saving time **6-13**  
     manually **6-11**  
     summer time **6-13**  
     time zones **6-12**  
   displaying the time and date **6-12**  
   overview **6-2**  
   See also NTP  
 system message logging  
   default configuration **29-4**  
   defining error message severity levels **29-9**  
   disabling **29-4**  
   displaying the configuration **29-13**  
   enabling **29-5**  
   facility keywords, described **29-13**  
   level keywords, described **29-10**  
   limiting messages **29-10**  
   message format **29-2**  
   overview **29-1**  
   sequence numbers, enabling and disabling **29-8**  
   setting the display destination device **29-5**  
   stack changes, effects of **29-2**  
   synchronizing log messages **29-6**  
   syslog facility **1-10**  
   system message logging (continued)  
     time stamps, enabling and disabling **29-8**  
   UNIX syslog servers  
     configuring the daemon **29-11**  
     configuring the logging facility **29-12**  
     facilities supported **29-13**  
   system MTU and 802.1Q tunneling **16-5**  
 system name  
   default configuration **6-15**  
   default setting **6-15**  
   manual configuration **6-15**  
   See also DNS  
 system prompt  
   default setting **6-14 to 6-15**  
   manual configuration **6-16**  
 system resources, optimizing **7-1**
- 
- T**
- TACACS+  
   accounting, defined **8-11**  
   authentication, defined **8-11**  
   authorization, defined **8-11**  
   configuring  
     accounting **8-17**  
     authentication key **8-13**  
     authorization **8-16**  
     login authentication **8-14**  
     default configuration **8-13**  
     displaying the configuration **8-17**  
     identifying the server **8-13**  
     limiting the services to the user **8-16**  
     operation of **8-12**  
     overview **8-10**  
     support for **1-8**  
     tracking services accessed by user **8-17**

- tagged packets
- 802.1Q [16-3](#)
- Layer 2 protocol [16-8](#)
- tar files
  - creating [B-6](#)
  - displaying the contents of [B-7](#)
  - extracting [B-7](#)
  - image file format [B-20](#)
- TDR [1-11](#)
- Telnet
  - accessing management interfaces [2-9](#)
  - number of connections [1-5](#)
  - setting a password [8-6](#)
- templates, SDM [7-1](#)
- temporary self-signed certificate [8-43](#)
- Terminal Access Controller Access Control System Plus
  - See TACACS+
- terminal lines, setting a password [8-6](#)
- TFTP
  - configuration files
    - downloading [B-11](#)
    - preparing the server [B-10](#)
    - uploading [B-12](#)
  - configuration files in base directory [3-6](#)
  - configuring for autoconfiguration [3-5](#)
  - image files
    - deleting [B-23](#)
    - downloading [B-22](#)
    - preparing the server [B-21](#)
    - uploading [B-24](#)
  - limiting access by servers [30-15](#)
- TFTP server [1-5](#)
- threshold, traffic level [24-2](#)
- time
  - See NTP and system clock
- Time Domain Reflector
  - See TDR
- time-range command [31-18](#)
- time ranges in ACLs [31-18](#)
- time stamps in log messages [29-8](#)
- time zones [6-12](#)
- Token Ring VLANs
  - support for [12-6](#)
  - VTP support [13-4](#)
- ToS [1-8](#)
- traceroute, Layer 2
  - and ARP [39-17](#)
  - and CDP [39-17](#)
  - broadcast traffic [39-17](#)
  - described [39-17](#)
  - IP addresses and subnets [39-17](#)
  - MAC addresses and VLANs [39-17](#)
  - multicast traffic [39-17](#)
  - multiple devices on a port [39-18](#)
  - unicast traffic [39-17](#)
  - usage guidelines [39-17](#)
- traceroute command [39-19](#)
  - See also IP traceroute
- traffic
  - blocking flooded [24-6](#)
  - fragmented [31-6](#)
  - unfragmented [31-6](#)
- traffic policing [1-9](#)
- traffic suppression [24-1](#)
- transparent mode, VTP [13-3, 13-12](#)
- trap-door mechanism [3-2](#)
- traps
  - configuring MAC address notification [6-23](#)
  - configuring managers [30-11](#)
  - defined [30-3](#)
  - enabling [6-23, 30-11](#)
  - notification types [30-11](#)
  - overview [30-1, 30-4](#)
- troubleshooting
  - connectivity problems [39-15, 39-16, 39-18](#)
  - detecting unidirectional links [26-1](#)
  - displaying crash information [39-25](#)
  - PIMv1 and PIMv2 interoperability problems [36-23](#)

- troubleshooting (continued)
- setting packet forwarding **39-23**
  - SFP security and identification **39-14**
  - show forward command **39-23**
  - with CiscoWorks **30-4**
  - with debug commands **39-21**
  - with ping **39-15**
  - with system message logging **29-1**
  - with traceroute **39-18**
- trunking encapsulation **1-6**
- trunk ports
- configuring **12-20**
  - defined **10-3, 12-3**
  - encapsulation **12-20, 12-25, 12-27**
  - secure MAC addresses on **24-12**
- trunks
- allowed-VLAN list **12-21**
  - configuring **12-20, 12-25, 12-27**
  - ISL **12-16**
  - load sharing
    - setting STP path costs **12-26**
    - using STP port priorities **12-24, 12-25**
  - native VLAN for untagged traffic **12-23**
  - parallel **12-26**
  - pruning-eligible list **12-22**
  - to non-DTP device **12-17**
  - understanding **12-17**
- trusted boundary for QoS **32-38**
- trusted port states
- between QoS domains **32-40**
  - classification options **32-5**
  - ensuring port security for IP phones **32-38**
  - support for **1-8**
  - within a QoS domain **32-35**
- trustpoints, CA **8-42**
- tunneling
- 802.1Q **16-1**
  - defined **16-1**
  - Layer 2 protocol **16-8**
  - tunnel ports
    - 802.1Q, configuring **16-6**
    - defined **12-4**
    - described **10-4, 16-1**
    - incompatibilities with other features **16-6**
    - twisted-pair Ethernet, detecting unidirectional links **26-1**
  - type of service
    - See ToS
- 
- U**
- UDLD
- default configuration **26-4**
  - disabling
    - fiber-optic interfaces **26-5**
    - globally **26-5**
    - per interface **26-5**
  - echoing detection mechanism **26-3**
  - enabling
    - globally **26-4**
    - per interface **26-5**
  - Layer 2 protocol tunneling **16-10**
  - link-detection mechanism **26-1**
  - neighbor database **26-2**
  - overview **26-1**
  - resetting an interface **26-6**
  - status, displaying **26-6**
  - support for **1-6**
- UDP, configuring **34-16**
- unauthorized ports with 802.1x **9-4**
- unicast MAC address filtering **1-5**
- and adding static addresses **6-27**
  - and broadcast MAC addresses **6-26**
  - and CPU packets **6-26**
  - and multicast addresses **6-26**
  - and router MAC addresses **6-26**
  - configuration guidelines **6-26**
  - described **6-26**
  - unicast storm **24-1**

- 
- unicast storm control command **24-4**  
 unicast traffic, blocking **24-7**  
 UniDirectional Link Detection protocol  
   See UDLD  
 UNIX syslog servers  
   daemon configuration **29-11**  
   facilities supported **29-13**  
   message logging configuration **29-12**  
 unrecognized Type-Length-Value (TLV) support **13-4**  
 upgrading information  
   See release notes  
 upgrading software images  
   See downloading  
 UplinkFast  
   described **19-4**  
   disabling **19-16**  
   enabling **19-15**  
   support for **1-6**  
 uploading  
   configuration files  
     preparing **B-10, B-13, B-16**  
     reasons for **B-8**  
     using FTP **B-14**  
     using RCP **B-18**  
     using TFTP **B-12**  
   image files  
     preparing **B-21, B-25, B-29**  
     reasons for **B-19**  
     using FTP **B-28**  
     using RCP **B-33**  
     using TFTP **B-24**  
 User Datagram Protocol  
   See UDP  
 user EXEC mode **2-2**  
 username-based authentication **8-7**
- 
- V**
- version-dependent transparent mode **13-4**  
 version-mismatch (VM) mode  
   automatic upgrades with auto-upgrade **4-12**  
   described **4-12**  
   displaying **4-12**  
   manual upgrades with auto-advise **4-12**  
 virtual router **35-1, 35-2**  
 vlan.dat file **12-5**  
 VLAN 1, disabling on a trunk port **12-22**  
 VLAN 1 minimization **12-21**  
 VLAN ACLs  
   See VLAN maps  
 vlan-assignment response, VMPS **12-28**  
 VLAN configuration  
   at bootup **12-8**  
   saving **12-8**  
 VLAN configuration mode **2-2, 12-7**  
 VLAN database  
   and startup configuration file **12-8**  
   and VTP **13-1**  
   VLAN configuration saved in **12-7**  
   VLANs saved in **12-4**  
 vlan database command **12-7**  
 vlan dot1q tag native command **16-5**  
 VLAN filtering and SPAN **27-7**  
 vlan global configuration command **12-7**  
 VLAN ID, discovering **6-28**  
 VLAN management domain **13-2**  
 VLAN Management Policy Server  
   See VMPS  
 VLAN map entries, order of **31-31**  
 VLAN maps  
   applying **31-35**  
   common uses for **31-35**  
   configuration example **31-36**

- VLAN maps (continued)
- configuration guidelines **31-31**
  - configuring **31-31**
  - creating **31-32**
  - defined **31-2**
  - denying access example **31-37**
  - denying and permitting packets **31-33**
  - displaying **31-42**
  - examples **31-37**
  - removing **31-35**
  - support for **1-7**
  - with router ACLs **31-41**
- VLAN membership
- confirming **12-31**
  - modes **12-3**
- VLAN Query Protocol
- See VQP
- VLANS
- adding **12-9**
  - adding to VLAN database **12-9**
  - aging dynamic addresses **17-10**
  - allowed on trunk **12-21**
  - and spanning-tree instances **12-3, 12-6, 12-13**
  - configuration guidelines, extended-range VLANs **12-13**
  - configuration guidelines, normal-range VLANs **12-6**
  - configuration options **12-7**
  - configuring **12-1**
  - configuring IDs 1006 to 4094 **12-13**
  - connecting through SVIs **10-9**
  - creating in config-vlan mode **12-9**
  - creating in VLAN configuration mode **12-10**
  - customer numbering in service-provider networks **16-3**
  - default configuration **12-8**
  - deleting **12-10**
  - described **10-2, 12-1**
  - displaying **12-15**
  - extended-range **12-1, 12-12**
  - features **1-6**
  - illustrated **12-2**
- VLANs (continued)
- internal **12-13**
  - in the switch stack **12-7**
  - limiting source traffic with RSPAN **27-23**
  - limiting source traffic with SPAN **27-16**
  - modifying **12-9**
  - native, configuring **12-23**
  - normal-range **12-1, 12-4**
  - number supported **1-6**
  - parameters **12-5**
  - port membership modes **12-3**
  - static-access ports **12-11**
  - STP and 802.1Q trunks **17-11**
  - supported **12-3**
  - Token Ring **12-6**
  - traffic between **12-2**
  - VLAN-bridge STP **17-12, 38-2**
  - VTP modes **13-3**
- VLAN Trunking Protocol
- See VTP
- VLAN trunks **12-16, 12-17**
- VMPS
- administering **12-32**
  - configuration example **12-33**
  - configuration guidelines **12-29**
  - default configuration **12-29**
  - description **12-27**
  - dynamic port membership
  - described **12-28**
  - reconfirming **12-31**
  - troubleshooting **12-33**
  - entering server address **12-30**
  - mapping MAC addresses to VLANs **12-28**
  - monitoring **12-32**
  - reconfirmation interval, changing **12-31**
  - reconfirming membership **12-31**
  - retry count, changing **12-32**
  - voice-over-IP **15-1**

- voice VLAN
- Cisco 7960 phone, port connections **15-1**
  - configuration guidelines **7.4, 15-3**
  - configuring IP phones for data traffic
    - override CoS of incoming frame **15-6**
    - trust CoS priority of incoming frame **15-6**
  - configuring ports for voice traffic in
    - 802.1p priority tagged frames **15-5**
    - 802.1Q frames **15-5**
  - connecting to an IP phone **15-4**
  - default configuration **15-3**
  - described **15-1**
  - displaying **15-6**
  - VQP **1-6, 12-27**
  - VTP
    - adding a client to a domain **13-14**
    - advertisements **12-19, 13-3**
    - and extended-range VLANs **13-2**
    - and normal-range VLANs **13-2**
    - client mode, configuring **13-11**
    - configuration
      - global configuration mode **13-7**
      - guidelines **13-8**
      - privileged EXEC mode **13-7**
      - requirements **13-9**
      - saving **13-7**
      - VLAN configuration mode **13-8**
    - configuration mode options **13-7**
    - configuration requirements **13-9**
    - configuration revision number
      - guideline **13-14**
      - resetting **13-15**
    - configuring
      - client mode **13-11**
      - server mode **13-9**
      - transparent mode **13-12**
    - consistency checks **13-4**
    - default configuration **13-7**
    - described **13-1**
    - VTP (continued)
      - disabling **13-12**
      - domain names **13-8**
      - domains **13-2**
      - Layer 2 protocol tunneling **16-8**
      - modes
        - client **13-3, 13-11**
        - server **13-3, 13-9**
        - transitions **13-3**
        - transparent **13-3, 13-12**
      - monitoring **13-15**
      - passwords **13-8**
      - pruning
        - disabling **13-14**
        - enabling **13-14**
        - examples **13-5**
        - overview **13-4**
        - support for **1-7**
      - pruning-eligible list, changing **12-22**
      - server mode, configuring **13-9**
      - statistics **13-15**
      - support for **1-7**
      - Token Ring support **13-4**
      - transparent mode, configuring **13-12**
      - using **13-1**
      - version, guidelines **13-9**
      - Version 1 **13-4**
      - Version 2
        - configuration guidelines **13-9**
        - disabling **13-13**
        - enabling **13-13**
        - overview **13-4**

---

**W**

weighted tail drop

See WTD

wizards **1-2**

**WTD**

described [32-13](#)

setting thresholds

  egress queue-sets [32-70](#)

  ingress queues [32-66](#)

support for [1-9](#)

---

**X**

Xmodem protocol [39-2](#)

