



---

## Numerics

### 10-Gigabit Ethernet interfaces

configuration guidelines [11-16](#)

defined [11-6](#)

### 802.1D

See STP

### 802.1Q

and trunk ports [11-3](#)

configuration limitations [13-19](#)

encapsulation [13-16](#)

native VLAN for untagged traffic [13-23](#)

### tunneling

compatibility with other features [17-6](#)

defaults [17-4](#)

described [17-1](#)

tunnel ports with other features [17-6](#)

### 802.1s

See MSTP

### 802.1w

See RSTP

### 802.1x

See port-based authentication

### 802.3ad

See EtherChannel

### 802.3af

See PoE

### 802.3z flow control [11-19](#)

---

## A

abbreviating commands [2-3](#)

ABRs [35-25](#)

access-class command [32-20](#)

access control entries

See ACEs

access-denied response, VMPS [13-28](#)

access groups

applying ACLs to interfaces [32-21](#)

IP [32-21](#)

Layer 2 [32-21](#)

Layer 3 [32-21](#)

accessing stack members [5-23](#)

access lists

See ACLs

access ports

and Layer 2 protocol tunneling [17-11](#)

defined [11-3](#)

accounting

with 802.1x [10-5, 10-22](#)

with RADIUS [9-28](#)

with TACACS+ [9-11, 9-17](#)

ACEs

and QoS [33-7](#)

defined [32-2](#)

Ethernet [32-2](#)

IP [32-2](#)

ACLs

ACEs [32-2](#)

any keyword [32-13](#)

applying

on bridged packets [32-39](#)

on multicast packets [32-40](#)

on routed packets [32-39](#)

on switched packets [32-38](#)

time ranges to [32-17](#)

## ACLs (continued)

## applying (continued)

to an interface [32-20](#)to QoS [33-7](#)classifying traffic for QoS [33-43](#)comments in [32-19](#)compiling [32-22](#)configuring with VLAN maps [32-37](#)defined [32-1, 32-8](#)examples of [32-22, 33-43](#)

## extended IP

configuring for QoS classification [33-45](#)creating [32-10](#)matching criteria [32-8](#)hardware and software handling [32-22](#)host keyword [32-13](#)

## IP

applying to interfaces [32-20](#)creating [32-8](#)fragments and QoS guidelines [33-34](#)implicit deny [32-10, 32-14, 32-16](#)implicit masks [32-10](#)matching criteria [32-8](#)named [32-15](#)terminal lines, setting on [32-19](#)undefined [32-21](#)violations, logging [32-16](#)limiting actions [32-38](#)logging messages [32-10](#)log keyword [32-16](#)MAC extended [32-27, 33-46](#)matching [32-8, 32-21](#)monitoring [32-41](#)named [32-15](#)number per QoS class map [33-34](#)numbers [32-8](#)port [32-2](#)precedence of [32-2](#)QoS [33-7, 33-43](#)

## ACLs (continued)

resequencing entries [32-15](#)router [32-2](#)

## standard IP

configuring for QoS classification [33-44](#)creating [32-9](#)matching criteria [32-8](#)supported features [32-22](#)support for [1-7](#)time ranges [32-17](#)unsupported features [32-7](#)using router ACLs with VLAN maps [32-37](#)

## VLAN maps

configuration guidelines [32-31](#)configuring [32-30](#)active links [21-1](#)active router [37-1](#)address aliasing [24-2](#)

## addresses

displaying the MAC address table [7-27](#)

## dynamic

accelerated aging [18-9](#)changing the aging time [7-22](#)default aging [18-9](#)defined [7-20](#)learning [7-21](#)removing [7-23](#)MAC, discovering [7-27](#)

## multicast

group address range [38-3](#)STP address management [18-9](#)

## static

adding and removing [7-25](#)defined [7-20](#)address resolution [7-27, 35-9](#)

## Address Resolution Protocol

See ARP

adjacency tables, with CEF [35-61](#)

- administrative distances
  - defined 35-72
  - OSPF 35-31
  - routing protocol defaults 35-63
- advanced IP services image 1-1, 36-1
- advertisements
  - CDP 26-1
  - RIP 35-20
  - VTP 13-19, 14-3
- aggregatable global unicast addresses 36-3
- aggregate addresses, BGP 35-55
- aggregated ports
  - See EtherChannel
- aggregate policers 33-59
- aggregate policing 1-8
- aggregator template 5-10, 8-1
- aging, accelerating 18-9
- aging time
  - accelerated
    - for MSTP 19-21
    - for STP 18-9, 18-23
  - MAC address table 7-22
  - maximum
    - for MSTP 19-22
    - for STP 18-23
- alarms, RMON 29-3
- allowed-VLAN list 13-21
- area border routers
  - See ABRs
- ARP
  - configuring 35-10
  - defined 1-5, 7-27, 35-10
  - encapsulation 35-11
  - static cache configuration 35-10
  - table
    - address resolution 7-27
    - managing 7-27
- ASBRs 35-25
- AS-path filters, BGP 35-50
- asymmetrical links, and 802.1Q tunneling 17-4
- attributes, RADIUS
  - vendor-proprietary 9-31
  - vendor-specific 9-29
- audience xxix
- authentication
  - EIGRP 35-38
  - HSRP 37-9
  - local mode with AAA 9-36
  - NTP associations 7-5
  - RADIUS
    - key 9-21
    - login 9-23
  - TACACS+
    - defined 9-11
    - key 9-13
    - login 9-14
  - See also port-based authentication
- authentication keys, and routing protocols 35-73
- authoritative time source, described 7-2
- authorization
  - with RADIUS 9-27
  - with TACACS+ 9-11, 9-16
- authorized ports with 802.1x 10-4
- autoconfiguration 3-3
- automatic advise (auto-advise) in switch stacks 5-12
- automatic copy (auto-copy) in switch stacks 5-12
- automatic QoS
  - See QoS
- automatic upgrades (auto-upgrade) in switch stacks 5-12
- autonegotiation
  - duplex mode 1-3
  - interface configuration guidelines 11-17
  - mismatches 41-12
- autonomous system boundary routers
  - See ASBRs
- autonomous systems, in BGP 35-44
- Auto-RP, described 38-5
- autosensing, port speed 1-3

auxiliary VLAN

See voice VLAN

availability, features 1-5

## B

BackboneFast

described 20-7

disabling 20-17

enabling 20-16

support for 1-6

backup interfaces

See Flex Links

backup links 21-1

banners

configuring

login 7-19

message-of-the-day login 7-18

default configuration 7-18

when displayed 7-18

BGP

aggregate addresses 35-55

aggregate routes, configuring 35-55

CIDR 35-55

clear commands 35-59

community filtering 35-52

configuring neighbors 35-54

default configuration 35-42

described 35-41

enabling 35-44

monitoring 35-59

multipath support 35-47

neighbors, types of 35-44

path selection 35-47

peers, configuring 35-54

prefix filtering 35-51

resetting sessions 35-46

route dampening 35-58

route maps 35-49

BGP (continued)

route reflectors 35-57

routing domain confederation 35-56

show commands 35-59

supernets 35-55

support for 1-9

Version 4 35-41

binding cluster group and HSRP group 37-11

binding database

address, DHCP server

See DHCP, Cisco IOS server database

DHCP snooping

See DHCP snooping binding database

bindings

address, Cisco IOS DHCP server 22-5

DHCP snooping database 22-6

IP source guard 22-15

binding table, DHCP snooping

See DHCP snooping binding database

blocking packets 25-6

booting

boot loader, function of 3-2

boot process 3-2

manually 3-13

specific image 3-13

boot loader

accessing 3-14

described 3-2

environment variables 3-14

prompt 3-14

trap-door mechanism 3-2

bootstrap router (BSR), described 38-5

Border Gateway Protocol

See BGP

BPDU

error-disabled state 20-3

filtering 20-3

RSTP format 19-10

- BPDU filtering
    - described 20-3
    - disabling 20-15
    - enabling 20-14
    - support for 1-6
  - BPDU guard
    - described 20-3
    - disabling 20-14
    - enabling 20-13
    - support for 1-6
  - bridged packets, ACLs on 32-39
  - bridge groups
    - See fallback bridging
  - bridge protocol data unit
    - See BPDU
  - broadcast flooding 35-17
  - broadcast packets
    - directed 35-14
    - flooded 35-14
  - broadcast storm-control command 25-4
  - broadcast storms 25-1, 35-14
- 
- C
- cables, monitoring for unidirectional links 27-1
  - candidate switch
    - defined 6-3
    - requirements 6-3
    - See also command switch, cluster standby group, and member switch
  - CA trustpoint
    - configuring 9-45
    - defined 9-42
  - caution, described xxx
  - CDP
    - and trusted boundary 33-40
    - configuring 26-2
    - default configuration 26-2
    - described 26-1
  - CDP (continued)
    - disabling for routing device 26-3 to 26-4
    - enabling and disabling
      - on an interface 26-4
      - on a switch 26-3
    - Layer 2 protocol tunneling 17-8
    - monitoring 26-5
    - overview 26-1
    - power negotiation extensions 11-6
    - support for 1-5
    - switch stack considerations 26-2
    - transmission timer and holdtime, setting 26-2
    - updates 26-2
  - CEF
    - defined 35-60
    - distributed 35-61
    - enabling 35-61
    - IPv6 36-15
  - CGMP
    - as IGMP snooping learning method 24-8
    - clearing cached group entries 38-50
    - enabling server support 38-33
    - joining multicast group 24-3
    - overview 38-7
    - server support only 38-7
    - switch support of 1-4
  - CIDR 35-55
  - CipherSuites 9-43
  - Cisco 7960 IP Phone 16-1
  - Cisco Discovery Protocol
    - See CDP
  - Cisco Express Forwarding
    - See CEF
  - Cisco Group Management Protocol
    - See CGMP
  - Cisco intelligent power management 11-6
  - Cisco IOS DHCP server
    - See DHCP, Cisco IOS DHCP server

- Cisco IOS File System
  - See IFS
- Cisco Network Assistant
  - See Network Assistant
- Cisco Networking Services
  - See IE2100
- Cisco StackWise technology [1-3](#)
  - See also stacks, switch
- CiscoWorks 2000 [1-4, 31-4](#)
- classless interdomain routing
  - See CIDR
- classless routing [35-8](#)
- class maps for QoS
  - configuring [33-47](#)
  - described [33-7](#)
  - displaying [33-79](#)
- class of service
  - See CoS
- clearing interfaces [11-27](#)
- CLI
  - abbreviating commands [2-3](#)
  - command modes [2-1](#)
  - described [1-4](#)
  - editing features
    - enabling and disabling [2-6](#)
    - keystroke editing [2-6](#)
    - wrapped lines [2-8](#)
  - error messages [2-4](#)
  - filtering command output [2-8](#)
  - getting help [2-3](#)
  - history
    - changing the buffer size [2-5](#)
    - described [2-4](#)
    - disabling [2-5](#)
    - recalling commands [2-5](#)
  - managing clusters [6-4](#)
  - no and default forms of commands [2-4](#)
- client mode, VTP [14-3](#)
- clock
  - See system clock
- cluster requirements [xxxix](#)
- clusters, switch
  - benefits [1-2](#)
  - described [6-1](#)
  - managing
    - through CLI [6-4](#)
    - through SNMP [6-5](#)
  - planning considerations
    - CLI [6-4](#)
    - SNMP [6-5](#)

See also Getting Started with Cisco Network Assistant
- cluster standby group
  - and HSRP group [37-11](#)
  - requirements [6-2](#)
- Coarse Wave Division Multiplexer
  - See CWDM SFPs
- command-line interface
  - See CLI
- command modes [2-1](#)
- commands
  - abbreviating [2-3](#)
  - no and default [2-4](#)
- commands, setting privilege levels [9-8](#)
- command switch
  - configuration conflicts [41-12](#)
  - defined [6-2](#)
  - password privilege levels [6-4](#)
  - recovery
    - from command-switch failure [41-8](#)
    - from lost member connectivity [41-12](#)
  - replacing
    - with another switch [41-11](#)
    - with cluster member [41-9](#)
  - requirements [6-2](#)

See also candidate switch, cluster standby group, member switch, and standby command switch
- community list, BGP [35-53](#)

- community ports [15-2](#)
- community strings
  - configuring [31-8](#)
  - for cluster switches [31-4](#)
  - overview [31-4](#)
- community VLANs [15-2, 15-3](#)
- compatibility, feature [25-11](#)
- compatibility, software
  - See stacks, switch
- config.text [3-12](#)
- configuration, initial
  - defaults [1-11](#)
  - Express Setup [1-2](#)
  - See also getting started guide and hardware installation guide
- configuration conflicts, recovering from lost member connectivity [41-12](#)
- configuration examples, network [1-13](#)
- configuration files
  - clearing the startup configuration [B-19](#)
  - creating using a text editor [B-10](#)
  - default name [3-12](#)
  - deleting a stored configuration [B-19](#)
  - described [B-8](#)
  - downloading
    - automatically [3-12](#)
    - preparing [B-10, B-13, B-16](#)
    - reasons for [B-8](#)
    - using FTP [B-13](#)
    - using RCP [B-17](#)
    - using TFTP [B-11](#)
  - guidelines for creating and using [B-9](#)
  - invalid combinations when copying [B-5](#)
  - limiting TFTP server access [31-15](#)
  - obtaining with DHCP [3-7](#)
  - password recovery disable considerations [9-5](#)
  - specifying the filename [3-12](#)
  - system contact and location information [31-15](#)
  - types and location [B-9](#)
- configuration files (continued)
  - uploading
    - preparing [B-10, B-13, B-16](#)
    - reasons for [B-8](#)
    - using FTP [B-14](#)
    - using RCP [B-18](#)
    - using TFTP [B-11](#)
- configuration settings, saving [3-10](#)
- configure terminal command [11-11](#)
- config-vlan mode [2-2, 13-7](#)
- conflicts, configuration [41-12](#)
- connections, secure remote [9-38](#)
- connectivity problems [41-14, 41-16, 41-17](#)
- consistency checks in VTP Version 2 [14-4](#)
- console port, connecting to [2-9](#)
- conventions
  - command [xxx](#)
  - for examples [xxx](#)
  - publication [xxx](#)
  - text [xxx](#)
- corrupted software, recovery steps with Xmodem [41-2](#)
- CoS
  - in Layer 2 frames [33-2](#)
  - override priority [16-6](#)
  - trust priority [16-6](#)
- CoS input queue threshold map for QoS [33-17](#)
- CoS output queue threshold map for QoS [33-20](#)
- CoS-to-DSCP map for QoS [33-61](#)
- counters, clearing interface [11-27](#)
- crashinfo file [41-24](#)
- cross-stack EtherChannel
  - configuration guidelines [34-12](#)
  - configuring
    - on Layer 2 interfaces [34-12](#)
    - on Layer 3 physical interfaces [34-16](#)
  - described [34-2](#)
  - illustration [34-3](#)
  - support for [1-5](#)

## cross-stack UplinkFast, STP

- described [20-5](#)
- disabling [20-16](#)
- enabling [20-16](#)
- fast-convergence events [20-7](#)
- Fast Uplink Transition Protocol [20-6](#)
- normal-convergence events [20-7](#)
- support for [1-6](#)

## cryptographic software image

- Kerberos [9-32](#)
- SSH [9-37](#)
- SSL [9-42](#)
- switch stack considerations [5-2, 5-17, 9-38](#)

CWDM SFPs [1-24](#)

---

**D**daylight saving time [7-13](#)

## dCEF

- in the switch stack [35-60](#)

## debugging

- enabling all system diagnostics [41-21](#)
- enabling for a specific feature [41-20](#)
- redirecting error message output [41-21](#)
- using commands [41-20](#)

default commands [2-4](#)

## default configuration

- 802.1Q tunneling [17-4](#)
- 802.1x [10-11](#)
- auto-QoS [33-21](#)
- banners [7-18](#)
- BGP [35-42](#)
- booting [3-12](#)
- CDP [26-2](#)
- DHCP [22-7](#)
- DHCP option 82 [22-7](#)
- DHCP snooping [22-7](#)
- DHCP snooping binding database [22-8](#)
- DNS [7-17](#)

## default configuration (continued)

- dynamic ARP inspection [23-5](#)
- EIGRP [35-35](#)
- EtherChannel [34-10](#)
- fallback bridging [40-4](#)
- Flex Links [21-2](#)
- HSRP [37-5](#)
- IGMP [38-27](#)
- IGMP filtering [24-21](#)
- IGMP snooping [24-7](#)
- IGMP throttling [24-21](#)
- initial switch information [3-3](#)
- IP addressing, IP routing [35-6](#)
- IP multicast routing [38-8](#)
- IP source guard [22-16](#)
- IPv6 [36-10](#)
- Layer 2 interfaces [11-15](#)
- Layer 2 protocol tunneling [17-11](#)
- MAC address table [7-22](#)
- MSDP [39-4](#)
- MSTP [19-13](#)
- MVR [24-16](#)
- NTP [7-4](#)
- optional spanning-tree configuration [20-12](#)
- OSPF [35-26](#)
- password and privilege level [9-2](#)
- PIM [38-8](#)
- private VLANs [15-7](#)
- RADIUS [9-20](#)
- RIP [35-21](#)
- RMON [29-3](#)
- RSPAN [28-11](#)
- SDM template [8-5](#)
- SNMP [31-6](#)
- SPAN [28-11](#)
- SSL [9-44](#)
- standard QoS [33-32](#)
- STP [18-13](#)
- switch stacks [5-20](#)



- default configuration (continued)
  - system message logging [30-4](#)
  - system name and prompt [7-15](#)
  - TACACS+ [9-13](#)
  - UDLD [27-4](#)
  - VLAN, Layer 2 Ethernet interfaces [13-19](#)
  - VLANs [13-8](#)
  - VMPS [13-29](#)
  - voice VLAN [16-3](#)
  - VTP [14-7](#)
- default gateway [3-10, 35-12](#)
- default networks [35-63](#)
- default routes [35-63](#)
- default routing [35-3](#)
- deleting VLANs [13-10](#)
- description command [11-22](#)
- designing your network, examples [1-13](#)
- desktop template [5-10, 8-1](#)
- destination addresses, in ACLs [32-12](#)
- destination-IP address-based forwarding, EtherChannel [34-8](#)
- destination-MAC address forwarding, EtherChannel [34-8](#)
- detecting indirect link failures, STP [20-8](#)
- device [B-19](#)
- device discovery protocol [26-1](#)
- device manager
  - benefits [1-2](#)
  - described [1-2, 1-4](#)
  - in-band management [1-5](#)
  - requirements [xxx](#)
  - upgrading a switch [B-19](#)
- DHCP
  - Cisco IOS server database
    - configuring [22-13](#)
    - default configuration [22-7](#)
    - described [22-5](#)
  - enabling
    - relay agent [22-9](#)
    - server [22-9](#)
  - DHCP-based autoconfiguration
    - client request message exchange [3-4](#)
    - configuring
      - client side [3-4](#)
      - DNS [3-6](#)
      - relay device [3-7](#)
      - server side [3-5](#)
      - server-side [22-9](#)
      - TFTP server [3-6](#)
    - example [3-8](#)
    - lease options
      - for IP address information [3-5](#)
      - for receiving the configuration file [3-5](#)
    - overview [3-3](#)
    - relationship to BOOTP [3-4](#)
    - relay support [1-5, 1-10](#)
    - support for [1-5](#)
  - DHCP binding database
    - See DHCP snooping binding database
  - DHCP binding table
    - See DHCP snooping binding database
  - DHCP option 82
    - circuit ID suboption [22-5](#)
    - configuration guidelines [22-8](#)
    - default configuration [22-7](#)
    - displaying [22-14](#)
    - forwarding address, specifying [22-10](#)
    - helper address [22-10](#)
    - overview [22-3](#)
    - packet format, suboption
      - circuit ID [22-5](#)
      - remote ID [22-5](#)
    - remote ID suboption [22-5](#)
  - DHCP snooping
    - accepting untrusted packets form edge switch [22-3, 22-11](#)
    - and private VLANs [22-12](#)
    - binding database
      - See DHCP snooping binding database

- DHCP snooping (continued)
  - configuration guidelines [22-8](#)
  - default configuration [22-7](#)
  - displaying binding tables [22-14](#)
  - message exchange process [22-4](#)
  - option 82 data insertion [22-3](#)
  - trusted interface [22-2](#)
  - untrusted interface [22-2](#)
  - untrusted messages [22-2](#)
- DHCP snooping binding database
  - adding bindings [22-13](#)
  - binding file
    - format [22-6](#)
    - location [22-6](#)
  - bindings [22-6](#)
  - clearing agent statistics [22-14](#)
  - configuration guidelines [22-9](#)
  - configuring [22-13](#)
  - default configuration [22-7, 22-8](#)
  - deleting
    - binding file [22-13](#)
    - bindings [22-14](#)
    - database agent [22-13](#)
  - described [22-5](#)
  - displaying [22-14](#)
    - binding entries [22-14](#)
    - status and statistics [22-14](#)
  - enabling [22-13](#)
  - entry [22-6](#)
  - renewing database [22-14](#)
  - resetting
    - delay value [22-13](#)
    - timeout value [22-13](#)
  - updating process [22-6](#)
- DHCP snooping binding table
  - See DHCP snooping binding database
- Differentiated Services architecture, QoS [33-2](#)
- Differentiated Services Code Point [33-2](#)
- Diffusing Update Algorithm (DUAL) [35-34](#)
- directed unicast requests [1-5](#)
- directories
  - changing [B-4](#)
  - creating and removing [B-4](#)
  - displaying the working [B-4](#)
- Distance Vector Multicast Routing Protocol
  - See DVMRP
- distance-vector protocols [35-3](#)
- distribute-list command [35-71](#)
- DNS
  - and DHCP-based autoconfiguration [3-6](#)
  - default configuration [7-17](#)
  - displaying the configuration [7-18](#)
  - in IPv6 [36-4](#)
  - overview [7-16](#)
  - setting up [7-17](#)
  - support for [1-5](#)
- documentation, related [xxx](#)
- document conventions [xxx](#)
- domain names
  - DNS [7-16](#)
  - VTP [14-8](#)
- Domain Name System
  - See DNS
- dot1q-tunnel switchport mode [13-18](#)
- double-tagged packets
  - 802.1Q tunneling [17-2](#)
  - Layer 2 protocol tunneling [17-10](#)
- downloading
  - configuration files
    - preparing [B-10, B-13, B-16](#)
    - reasons for [B-8](#)
    - using FTP [B-13](#)
    - using RCP [B-17](#)
    - using TFTP [B-11](#)

- downloading (continued)
  - image files
    - deleting old image [B-23](#)
    - preparing [B-22, B-25, B-29](#)
    - reasons for [B-19](#)
    - using CMS [1-2](#)
    - using FTP [B-26](#)
    - using HTTP [1-2, B-19](#)
    - using Network Assistant [1-2](#)
    - using RCP [B-31](#)
    - using TFTP [B-22](#)
    - using the device manager or Network Assistant [B-19](#)
  - drop threshold for Layer 2 protocol packets [17-11](#)
  - DSCP [1-8, 33-2](#)
  - DSCP input queue threshold map for QoS [33-17](#)
  - DSCP output queue threshold map for QoS [33-20](#)
  - DSCP-to-CoS map for QoS [33-64](#)
  - DSCP-to-DSCP-mutation map for QoS [33-65](#)
  - DSCP transparency [33-40](#)
  - DTP [1-6, 13-17](#)
  - DUAL finite state machine, EIGRP [35-34](#)
  - dual IPv4 and IPv6 templates [8-2, 36-9](#)
  - dual protocol stacks
    - configuring [36-13](#)
    - IPv4 and IPv6 [36-9](#)
    - SDM templates supporting [36-9](#)
  - duplex mode, configuring [11-17](#)
  - DVMRP
    - autosummarization
      - configuring a summary address [38-47](#)
      - disabling [38-49](#)
    - connecting PIM domain to DVMRP router [38-39](#)
    - enabling unicast routing [38-43](#)
    - interoperability
      - with Cisco devices [38-37](#)
      - with Cisco IOS software [38-7](#)
    - mrinfo requests, responding to [38-42](#)
  - DVRMP (continued)
    - neighbors
      - advertising the default route to [38-41](#)
      - discovery with Probe messages [38-37](#)
      - displaying information [38-42](#)
      - prevent peering with nonpruning [38-45](#)
      - rejecting nonpruning [38-43](#)
    - overview [38-7](#)
    - routes
      - adding a metric offset [38-49](#)
      - advertising all [38-49](#)
      - advertising the default route to neighbors [38-41](#)
      - caching DVMRP routes learned in report messages [38-43](#)
      - changing the threshold for syslog messages [38-46](#)
      - deleting [38-50](#)
      - displaying [38-51](#)
      - favoring one over another [38-49](#)
      - limiting the number injected into MBONE [38-46](#)
      - limiting unicast route advertisements [38-37](#)
    - routing table [38-7](#)
    - source distribution tree, building [38-7](#)
    - support for [1-10](#)
    - tunnels
      - configuring [38-39](#)
      - displaying neighbor information [38-42](#)
  - dynamic access ports
    - characteristics [13-3](#)
    - configuring [13-30](#)
    - defined [11-3](#)
  - dynamic addresses
    - See addresses
  - dynamic ARP inspection
    - ARP cache poisoning [23-1](#)
    - ARP requests, described [23-1](#)
    - ARP spoofing attack [23-1](#)

dynamic ARP inspection (continued)

- clearing
  - log buffer [23-15](#)
  - statistics [23-15](#)
- configuration guidelines [23-6](#)
- configuring
  - ACLs for non-DHCP environments [23-8](#)
  - in DHCP environments [23-7](#)
  - log buffer [23-12](#)
  - rate limit for incoming ARP packets [23-4, 23-10](#)
- default configuration [23-5](#)
- denial-of-service attacks, preventing [23-10](#)
- described [23-1](#)
- DHCP snooping binding database [23-2](#)
- displaying
  - ARP ACLs [23-14](#)
  - configuration and operating state [23-14](#)
  - log buffer [23-15](#)
  - statistics [23-15](#)
  - trust state and rate limit [23-14](#)
- error-disabled state for exceeding rate limit [23-4](#)
- function of [23-2](#)
- interface trust states [23-3](#)
- log buffer
  - clearing [23-15](#)
  - configuring [23-12](#)
  - displaying [23-15](#)
- logging of dropped packets, described [23-5](#)
- man-in-the middle attack, described [23-2](#)
- network security issues and interface trust states [23-3](#)
- priority of ARP ACLs and DHCP snooping entries [23-4](#)
- rate limiting of ARP packets
  - configuring [23-10](#)
  - described [23-4](#)
  - error-disabled state [23-4](#)
- statistics
  - clearing [23-15](#)
  - displaying [23-15](#)
- validation checks, performing [23-11](#)

- dynamic auto trunking mode [13-18](#)
- dynamic desirable trunking mode [13-18](#)
- Dynamic Host Configuration Protocol
  - See DHCP-based autoconfiguration
- dynamic port VLAN membership
  - described [13-28](#)
  - reconfirming [13-31](#)
  - troubleshooting [13-33](#)
  - types of connections [13-30](#)
- dynamic routing [35-3](#)
- Dynamic Trunking Protocol
  - See DTP

---

## E

- EBGP [35-40](#)
- editing features
  - enabling and disabling [2-6](#)
  - keystrokes used [2-6](#)
  - wrapped lines [2-8](#)
- EIGRP
  - authentication [35-38](#)
  - components [35-34](#)
  - configuring [35-36](#)
  - default configuration [35-35](#)
  - definition [35-34](#)
  - interface parameters, configuring [35-37](#)
  - monitoring [35-39](#)
  - support for [1-9](#)
- elections
  - See stack master
- EMI [1-1](#)
- enable password [9-4](#)
- enable secret password [9-4](#)
- encryption, CipherSuite [9-44](#)
- encryption for passwords [9-4](#)
- Enhanced IGRP
  - See EIGRP

enhanced multilayer image

See EMI

environment variables, function of 3-15

equal-cost routing 1-9, 35-62

error messages during command entry 2-4

EtherChannel

802.3ad, described 34-6

automatic creation of 34-5, 34-6

channel groups

binding physical and logical interfaces 34-4

numbering of 34-4

configuration guidelines 34-11

configuring

Layer 2 interfaces 34-12

Layer 3 physical interfaces 34-16

Layer 3 port-channel logical interfaces 34-15

default configuration 34-10

described 34-2

displaying status 34-23

forwarding methods 34-7, 34-18

interaction

with STP 34-11

with VLANs 34-12

LACP

described 34-6

displaying status 34-23

hot-standby ports 34-20

interaction with other features 34-7

modes 34-6

port priority 34-22

system priority 34-21

Layer 3 interface 35-5

load balancing 34-7, 34-18

logical interfaces, described 34-4

EtherChannel (continued)

PAGP

aggregate-port learners 34-19

compatibility with Catalyst 1900 34-19

described 34-5

displaying status 34-23

interaction with other features 34-6

learn method and priority configuration 34-19

modes 34-5

support for 1-4

port-channel interfaces

described 34-4

numbering of 34-4

port groups 11-5

stack changes, effects of 34-9

support for 1-4

EtherChannel guard

described 20-10

disabling 20-17

enabling 20-17

Ethernet VLANs

adding 13-9

defaults and ranges 13-8

modifying 13-9

EUI 36-3

events, RMON 29-3

examples

conventions for xxx

network configuration 1-13

expedite queue for QoS 33-78

Express Setup 1-2

See also getting started guide

extended-range VLANs

configuration guidelines 13-13

configuring 13-12

creating 13-14

defined 13-1

extended system ID

MSTP [19-15](#)

STP [18-4, 18-16](#)

extended universal identifier

See EUI

Extensible Authentication Protocol over LAN [10-1](#)

external BGP

See EBGp

external neighbors, BGP [35-44](#)

---

## F

failover support [1-5](#)

fallback bridging

and protected ports [40-4](#)

bridge groups

creating [40-4](#)

described [40-2](#)

displaying [40-11](#)

function of [40-2](#)

number supported [40-5](#)

removing [40-5](#)

bridge table

clearing [40-11](#)

displaying [40-11](#)

configuration guidelines [40-4](#)

connecting interfaces with [11-9](#)

default configuration [40-4](#)

described [40-1](#)

frame forwarding

flooding packets [40-2](#)

forwarding packets [40-2](#)

overview [40-1](#)

protocol, unsupported [40-4](#)

stack changes, effects of [40-3](#)

STP

disabling on an interface [40-11](#)

forward-delay interval [40-10](#)

hello BPDU interval [40-9](#)

fallback bridging (continued)

STP (continued)

interface priority [40-7](#)

keepalive messages [18-2](#)

maximum-idle interval [40-10](#)

path cost [40-8](#)

VLAN-bridge spanning-tree priority [40-7](#)

VLAN-bridge STP [40-2](#)

support for [1-9](#)

SVIs and routed ports [40-1](#)

unsupported protocols [40-4](#)

VLAN-bridge STP [18-12](#)

Fast Uplink Transition Protocol [20-6](#)

features, incompatible [25-11](#)

FIB [35-60](#)

fiber-optic, detecting unidirectional links [27-1](#)

files

copying [B-5](#)

crashinfo

description [41-24](#)

displaying the contents of [41-24](#)

location [41-24](#)

deleting [B-5](#)

displaying the contents of [B-8](#)

tar

creating [B-6](#)

displaying the contents of [B-6](#)

extracting [B-7](#)

image file format [B-20](#)

file system

displaying available file systems [B-2](#)

displaying file information [B-3](#)

local file system names [B-1](#)

network file system names [B-5](#)

setting the default [B-3](#)

filtering

in a VLAN [32-30](#)

non-IP traffic [32-27](#)

show and more command output [2-8](#)

filtering show and more command output [2-8](#)

filters, IP

See ACLs, IP

flash device, number of [B-1](#)

Flex Links

configuration guidelines [21-2](#)

configuring [21-3](#)

default configuration [21-2](#)

description [21-1](#)

monitoring [21-3](#)

flooded traffic, blocking [25-7](#)

flow-based packet classification [1-8](#)

flowcharts

QoS classification [33-6](#)

QoS egress queueing and scheduling [33-18](#)

QoS ingress queueing and scheduling [33-16](#)

QoS policing and marking [33-10](#)

flow control [1-3, 11-19](#)

forward-delay time

MSTP [19-21](#)

STP [18-23](#)

Forwarding Information Base

See FIB

forwarding nonroutable protocols [40-1](#)

FTP

accessing MIB files [A-3](#)

configuration files

downloading [B-13](#)

overview [B-12](#)

preparing the server [B-13](#)

uploading [B-14](#)

image files

deleting old image [B-28](#)

downloading [B-26](#)

preparing the server [B-25](#)

uploading [B-28](#)

---

## G

get-bulk-request operation [31-3](#)

get-next-request operation [31-3, 31-4](#)

get-request operation [31-3, 31-4](#)

get-response operation [31-3](#)

Gigabit modules

See SFPs

global configuration mode [2-2](#)

guest VLAN and 802.1x [10-8](#)

guide

audience [xxix](#)

purpose of [xxix](#)

guide mode [1-2](#)

GUIs

See device manager and Network Assistant [1-4](#)

---

## H

hardware limitations and Layer 3 interfaces [11-24](#)

hello time

MSTP [19-20](#)

STP [18-22](#)

help, for the command line [2-3](#)

hierarchical policy maps [33-8](#)

configuration guidelines [33-34](#)

configuring [33-52](#)

described [33-11](#)

history

changing the buffer size [2-5](#)

described [2-4](#)

disabling [2-5](#)

recalling commands [2-5](#)

history table, level and number of syslog messages [30-10](#)

host ports

configuring [15-12](#)

kinds of [15-2](#)

hosts, limit on dynamic ports [13-33](#)

## Hot Standby Router Protocol

See HSRP

## HP OpenView 1-4

## HSRP

- authentication string 37-9
- binding to cluster group 37-11
- command-switch redundancy 1-1, 1-5
- configuring 37-4
- default configuration 37-5
- definition 37-1
- guidelines 37-5
- monitoring 37-11
- overview 37-1
- priority 37-7
- routing redundancy 1-9
- support for ICMP redirect messages 37-11
- switch stack considerations 37-4
- timers 37-9
- tracking 37-7

## HTTP over SSL

see HTTPS

## HTTPS 9-42

- configuring 9-45
- self-signed certificate 9-43

## HTTP secure server 9-42

## IBPG 35-40

## ICMP

- IPv6 36-4
- redirect messages 35-12
- support for 1-9
- time-exceeded messages 41-18
- traceroute and 41-18
- unreachable messages 32-20
- unreachables and ACLs 32-22

## ICMP ping

- executing 41-15
- overview 41-14

## ICMP Router Discovery Protocol

See IRDP

## ICMPv6 36-4

## IDS appliances

- and ingress RSPAN 28-22
- and ingress SPAN 28-15

## IE2100

## CNS embedded agents

- described 4-5
- enabling automated configuration 4-6
- enabling configuration agent 4-9
- enabling event agent 4-8

## Configuration Registrar

- configID, deviceID, hostname 4-3
- configuration service 4-2
- described 4-1
- event service 4-3

## IEEE 802.1p 16-1

## ifIndex values, SNMP 31-5

## IFS 1-5

## IGMP

- configuring the switch
  - as a member of a group 38-27
  - statically connected member 38-32
- controlling access to groups 38-28
- default configuration 38-27
- deleting cache entries 38-51
- displaying groups 38-51
- fast switching 38-32
- host-query interval, modifying 38-30
- joining multicast group 24-3
- join messages 24-3
- leave processing, enabling 24-10
- leaving multicast group 24-5
- multicast reachability 38-27
- overview 38-2



- IGMP (continued)
  - queries [24-4](#)
  - report suppression
    - described [24-5](#)
    - disabling [24-12](#)
  - support for [1-4](#)
  - Version 1
    - changing to Version 2 [38-29](#)
    - described [38-3](#)
  - Version 2
    - changing to Version 1 [38-29](#)
    - described [38-3](#)
    - maximum query response time value [38-31](#)
    - pruning groups [38-31](#)
    - query timeout value [38-31](#)
- IGMP filtering
  - configuring [24-21](#)
  - default configuration [24-21](#)
  - described [24-20](#)
  - monitoring [24-25](#)
  - support for [1-4](#)
- IGMP groups
  - configuring filtering [24-24](#)
  - setting the maximum number [24-23](#)
- IGMP profile
  - applying [24-22](#)
  - configuration mode [24-21](#)
  - configuring [24-22](#)
- IGMP snooping
  - and address aliasing [24-2](#)
  - and stack changes [24-6](#)
  - configuring [24-6](#)
  - default configuration [24-7](#)
  - definition [24-1](#)
  - enabling and disabling [24-7](#)
  - global configuration [24-7](#)
  - Immediate Leave [24-5](#)
  - in the switch stack [24-6](#)
  - method [24-8](#)
- IGMP snooping (continued)
  - monitoring [24-13](#)
  - querier
    - configuring [24-11](#)
    - guidelines and restrictions [24-6](#)
  - support for [1-4](#)
  - VLAN configuration [24-8](#)
- IGMP throttling
  - configuring [24-24](#)
  - default configuration [24-21](#)
  - described [24-21](#)
  - displaying action [24-25](#)
- IGP [35-25](#)
- Immediate Leave, IGMP
  - described [24-5](#)
  - enabling [24-10](#)
- initial configuration
  - defaults [1-11](#)
  - Express Setup [1-2](#)
  - See also getting started guide and hardware installation guide
- Intelligence Engine 2100 Series CNS Agents
  - See IE2100
- interface
  - number [11-10](#)
  - range macros [11-13](#)
- interface command [11-10 to 11-11](#)
- interface configuration mode [2-2](#)
- interfaces
  - configuration guidelines
    - 10-Gigabit Ethernet [11-16](#)
    - duplex and speed [11-17](#)
  - configuring
    - duplex mode [11-17](#)
    - procedure [11-11](#)
    - speed [11-17](#)
  - configuring for IPv4 and IPv6 [36-13](#)
  - counters, clearing [11-27](#)
  - described [11-22](#)

## interfaces (continued)

- descriptive name, adding [11-22](#)
  - displaying information about [11-26](#)
  - flow control [11-19](#)
  - management [1-4](#)
  - monitoring [11-26](#)
  - naming [11-22](#)
  - physical, identifying [11-10](#)
  - range of [11-11](#)
  - restarting [11-27, 11-28](#)
  - shutting down [11-27](#)
  - status [11-26](#)
  - supported [11-10](#)
  - types of [11-1](#)
- interfaces range macro command [11-13](#)
- interface types [11-10](#)

## Interior Gateway Protocol

See IGP

## internal BGP

See IBGP

internal neighbors, BGP [35-44](#)

## Internet Control Message Protocol

See ICMP

## Internet Group Management Protocol

See IGMP

## Internet Protocol version 6

See IPv6

## Inter-Switch Link

See ISL

inter-VLAN routing [1-9, 35-2](#)

## Intrusion Detection System

See IDS appliances

ip access group command [32-21](#)

## IP ACLs

- extended, creating [32-10](#)
- for QoS classification [33-7](#)
- implicit deny [32-10, 32-14, 32-16](#)
- implicit masks [32-10](#)
- logging [32-16](#)

## IP ACLs (continued)

- named [32-15](#)
- standard, creating [32-9](#)
- undefined [32-21](#)
- virtual terminal lines, setting on [32-19](#)

## IP addresses

- 128-bit [36-2](#)
- candidate or member [6-3](#)
- classes of [35-6](#)
- command switch [6-2](#)
- default configuration [35-6](#)
- discovering [7-27](#)
- for IP routing [35-5](#)
- IPv6 [36-2](#)
- MAC address association [35-9](#)
- monitoring [35-18](#)

See also IP information

IP broadcast address [35-17](#)ip cef distributed command [35-61](#)IP directed broadcasts [35-15](#)ip igmp profile command [24-21](#)

## IP information

- assigned
  - manually [3-10](#)
  - through DHCP-based autoconfiguration [3-3](#)
- default configuration [3-3](#)

## IP multicast routing

- addresses
  - all-hosts [38-3](#)
  - all-multicast-routers [38-3](#)
  - host group address range [38-3](#)

administratively-scoped boundaries, described [38-35](#)

and IGMP snooping [24-1](#)

## Auto-RP

- adding to an existing sparse-mode cloud [38-14](#)
- benefits of [38-14](#)
- clearing the cache [38-51](#)
- configuration guidelines [38-10](#)
- filtering incoming RP announcement messages [38-17](#)

- IP multicast routing (continued)
  - Auto\_RP (continued)
    - overview [38-5](#)
    - preventing candidate RP spoofing [38-17](#)
    - preventing join messages to false RPs [38-16](#)
    - setting up in a new internetwork [38-14](#)
    - using with BSR [38-22](#)
  - bootstrap router
    - configuration guidelines [38-10](#)
    - configuring candidate BSRs [38-20](#)
    - configuring candidate RPs [38-21](#)
    - defining the IP multicast boundary [38-19](#)
    - defining the PIM domain border [38-18](#)
    - overview [38-5](#)
    - using with Auto-RP [38-22](#)
  - Cisco implementation [38-2](#)
  - configuring
    - basic multicast routing [38-10](#)
    - IP multicast boundary [38-35](#)
  - default configuration [38-8](#)
  - enabling
    - multicast forwarding [38-11](#)
    - PIM mode [38-11](#)
  - group-to-RP mappings
    - Auto-RP [38-5](#)
    - BSR [38-5](#)
  - MBONE
    - deleting sdr cache entries [38-51](#)
    - described [38-34](#)
    - displaying sdr cache [38-52](#)
    - enabling sdr listener support [38-34](#)
    - limiting DVMRP routes advertised [38-46](#)
    - limiting sdr cache entry lifetime [38-35](#)
    - SAP packets for conference session announcement [38-34](#)
    - Session Directory (sdr) tool, described [38-34](#)
- IP multicast routing (continued)
  - monitoring
    - packet rate loss [38-52](#)
    - peering devices [38-52](#)
    - tracing a path [38-52](#)
  - multicast forwarding, described [38-6](#)
  - PIMv1 and PIMv2 interoperability [38-9](#)
  - protocol interaction [38-2](#)
  - reverse path check (RPF) [38-6](#)
  - routing table
    - deleting [38-51](#)
    - displaying [38-51](#)
  - RP
    - assigning manually [38-12](#)
    - configuring Auto-RP [38-14](#)
    - configuring PIMv2 BSR [38-18](#)
    - monitoring mapping information [38-23](#)
    - using Auto-RP and BSR [38-22](#)
  - stacking
    - stack master functions [38-8](#)
    - stack member functions [38-8](#)
  - statistics, displaying system and network [38-51](#)
  - See also CGMP
  - See also DVMRP
  - See also IGMP
  - See also PIM
- IP phones
  - and QoS [16-1](#)
  - automatic classification and queueing [33-21](#)
  - configuring [16-4](#)
  - ensuring port security with QoS [33-39](#)
  - trusted boundary for QoS [33-39](#)
- IP precedence [33-2](#)
- IP-precedence-to-DSCP map for QoS [33-62](#)
- IP protocols
  - in ACLs [32-12](#)
  - routing [1-9](#)

- IP routes, monitoring [35-74](#)
- IP routing
  - connecting interfaces with [11-9](#)
  - disabling [35-19](#)
  - enabling [35-19](#)
- IP source guard
  - and 802.1x [22-16](#)
  - and DHCP snooping [22-15](#)
  - and EtherChannels [22-16](#)
  - and port security [22-16](#)
  - and private VLANs [22-16](#)
  - and routed ports [22-16](#)
  - and TCAM entries [22-16](#)
  - and trunk interfaces [22-16](#)
  - and VRF [22-16](#)
  - binding configuration
    - automatic [22-15](#)
    - manual [22-15](#)
  - binding table [22-15](#)
  - configuration guidelines [22-16](#)
  - default configuration [22-16](#)
  - described [22-14](#)
  - disabling [22-17](#)
  - displaying
    - bindings [22-17](#)
    - configuration [22-17](#)
  - enabling [22-16](#)
  - filtering
    - source IP address [22-15](#)
    - source IP and MAC address [22-15](#)
  - source IP address filtering [22-15](#)
  - source IP and MAC address filtering [22-15](#)
  - static bindings
    - adding [22-16](#)
    - deleting [22-17](#)
- IP traceroute
  - executing [41-18](#)
  - overview [41-17](#)
- IP unicast routing
  - address resolution [35-9](#)
  - administrative distances [35-63, 35-72](#)
  - ARP [35-10](#)
  - assigning IP addresses to Layer 3 interfaces [35-7](#)
  - authentication keys [35-73](#)
  - broadcast
    - address [35-17](#)
    - flooding [35-17](#)
    - packets [35-14](#)
    - storms [35-14](#)
  - classless routing [35-8](#)
  - configuring static routes [35-62](#)
  - default
    - addressing configuration [35-6](#)
    - gateways [35-12](#)
    - networks [35-63](#)
    - routes [35-63](#)
    - routing [35-3](#)
  - directed broadcasts [35-15](#)
  - disabling [35-19](#)
  - dynamic routing [35-3](#)
  - enabling [35-19](#)
  - EtherChannel Layer 3 interface [35-5](#)
  - IGP [35-25](#)
  - inter-VLAN [35-2](#)
  - IP addressing
    - classes [35-6](#)
    - configuring [35-5](#)
  - IPv6 [36-3](#)
  - IRDP [35-13](#)
  - Layer 3 interfaces [35-9](#)
  - MAC address and IP address [35-9](#)
  - passive interfaces [35-70](#)
  - protocols
    - distance-vector [35-3](#)
    - dynamic [35-3](#)
    - link-state [35-3](#)
  - proxy ARP [35-10](#)

## IP unicast routing (continued)

- redistribution [35-64](#)
- reverse address resolution [35-9](#)
- routed ports [35-5](#)
- static routing [35-3](#)
- steps to configure [35-5](#)
- subnet mask [35-7](#)
- subnet zero [35-7](#)
- supernet [35-8](#)
- UDP [35-16](#)
- with SVIs [35-5](#)
- See also BGP
- See also EIGRP
- See also OSPF
- See also RIP

## IPv4 and IPv6

- configuring on an interface [36-13](#)
- differences [36-1](#)
- dual protocol stacks [36-5](#)

## IPv6

- addresses [36-2](#)
- address formats [36-2](#)
- advantages [36-2](#)
- and switch stacks [36-7](#)
- applications [36-5](#)
- assigning address [36-11](#)
- autoconfiguration [36-4](#)
- CEFv6 [36-15](#)
- configuring static routes [36-16](#)
- default configuration [36-10](#)
- defined [36-1](#)
- enabling [36-11](#)
- feature limitations [36-7](#)
- features not supported [36-6](#)
- ICMP [36-4](#)
- ICMP rate limiting [36-14](#)
- monitoring [36-22](#)
- OSPF [36-20](#)
- path MTU discovery [36-4](#)

## IPv6 (continued)

- reasons for [36-1](#)
- RIP [36-18](#)
- SDM templates [8-2, 36-8](#)
- stack master functions [36-8](#)
- supported features [36-3](#)
- switch limitations [36-6](#)

## IRDP

- configuring [35-13](#)
- definition [35-13](#)
- support for [1-9](#)

## ISL

- and IPv6 [36-3](#)
- and trunk ports [11-3](#)
- encapsulation [1-6, 13-16](#)
- trunking with 802.1 tunneling [17-5](#)

isolated port [15-2](#)

isolated VLANs [15-2, 15-3](#)

---

**J**

join messages, IGMP [24-3](#)

---

**K**

## KDC

- described [9-32](#)
- See also Kerberos

keepalive messages [18-2](#)

## Kerberos

- authenticating to
  - boundary switch [9-35](#)
  - KDC [9-35](#)
  - network services [9-35](#)
- configuration examples [9-32](#)
- configuring [9-36](#)
- credentials [9-32](#)
- cryptographic software image [9-32](#)

## Kerberos (continued)

- described [9-32](#)
- KDC [9-32](#)
- operation [9-34](#)
- realm [9-33](#)
- server [9-33](#)
- support for [1-8](#)
- switch as trusted third party [9-32](#)
- terms [9-33](#)
- TGT [9-34](#)
- tickets [9-32](#)

## key distribution center

- See KDC

## L

l2protocol-tunnel command [17-13](#)

## LACP

- Layer 2 protocol tunneling [17-9](#)
- See EtherChannel

Layer 2 frames, classification with CoS [33-2](#)Layer 2 interfaces, default configuration [11-15](#)

## Layer 2 protocol tunneling

- configuring [17-10](#)
- configuring for EtherChannels [17-14](#)
- default configuration [17-11](#)
- defined [17-8](#)
- guidelines [17-11](#)

## Layer 2 traceroute

- and ARP [41-17](#)
- and CDP [41-16](#)
- broadcast traffic [41-16](#)
- described [41-16](#)
- IP addresses and subnets [41-17](#)
- MAC addresses and VLANs [41-16](#)
- multicast traffic [41-16](#)
- multiple devices on a port [41-17](#)
- unicast traffic [41-16](#)
- usage guidelines [41-16](#)

Layer 2 trunks [13-17](#)Layer 3 features [1-9](#)

## Layer 3 interfaces

- assigning IP addresses to [35-7](#)
- assigning IPv4 and IPv6 addresses to [36-13](#)
- assigning IPv6 addresses to [36-11](#)
- changing from Layer 2 mode [35-7](#)
- types of [35-5](#)

Layer 3 packets, classification methods [33-2](#)LDAP [4-2](#)

## LEDs, switch

- See hardware installation guide

## lightweight directory access protocol

- See LDAP

line configuration mode [2-2](#)

## Link Aggregation Control Protocol

- See EtherChannel

link local unicast addresses [36-3](#)

## link redundancy

- See Flex Links

links, unidirectional [27-1](#)link state advertisements (LSAs) [35-29](#)link-state protocols [35-3](#)load balancing [37-3](#)logging messages, ACL [32-10](#)

## login authentication

- with RADIUS [9-23](#)
- with TACACS+ [9-14](#)

login banners [7-18](#)

## log messages

- See system message logging

Long-Reach Ethernet (LRE) technology [1-15, 1-23](#)

## loop guard

- described [20-11](#)
- enabling [20-18](#)
- support for [1-6](#)

## M

## MAC addresses

- aging time [7-22](#)
- and VLAN association [7-21](#)
- building the address table [7-21](#)
- default configuration [7-22](#)
- discovering [7-27](#)
- displaying [7-27](#)
- displaying in the IP source binding table [22-17](#)
- dynamic
  - learning [7-21](#)
  - removing [7-23](#)
- in ACLs [32-27](#)
- IP address association [35-9](#)
- static
  - adding [7-25](#)
  - allowing [7-27](#)
  - characteristics of [7-25](#)
  - dropping [7-26](#)
  - removing [7-25](#)

MAC address notification, support for [1-10](#)MAC address-to-VLAN mapping [13-28](#)

## MAC extended access lists

- applying to Layer 2 interfaces [32-29](#)
- configuring for QoS [33-46](#)
- creating [32-27](#)
- defined [32-27](#)
- for QoS classification [33-5](#)

## macros

See Smartports macros

manageability features [1-5](#)

## management access

## in-band

- browser session [1-5](#)
- CLI session [1-5](#)
- device manager [1-5](#)
- SNMP [1-5](#)

out-of-band console port connection [1-5](#)

## management options

- CLI [2-1](#)
- clustering [1-3](#)
- CNS [4-1](#)
- Network Assistant [1-2](#)
- overview [1-4](#)
- switch stacks [1-3](#)

## mapping tables for QoS

## configuring

- CoS-to-DSCP [33-61](#)
- DSCP [33-61](#)
- DSCP-to-CoS [33-64](#)
- DSCP-to-DSCP-mutation [33-65](#)
- IP-precedence-to-DSCP [33-62](#)
- policed-DSCP [33-63](#)

described [33-13](#)

## marking

- action in policy map [33-49](#)
- action with aggregate policers [33-59](#)
- described [33-4](#), [33-8](#)

matching, ACLs [32-8](#)

## maximum aging time

- MSTP [19-22](#)
- STP [18-23](#)

maximum hop count, MSTP [19-22](#)maximum-paths command [35-47](#), [35-62](#)membership mode, VLAN port [13-3](#)

## member switch

- defined [6-2](#)
- managing [6-4](#)
- recovering from lost connectivity [41-12](#)
- requirements [6-3](#)

See also candidate switch, cluster standby group, and standby command switch

## messages

- logging ACL violations [32-16](#)
- to users through banners [7-18](#)

messages, to users through banners [7-18](#)metrics, in BGP [35-48](#)

- metric translations, between routing protocols [35-67](#)
- metro tags [17-2](#)
- MHSRP [37-3](#)
- MIBs
  - accessing files with FTP [A-3](#)
  - location of files [A-3](#)
  - overview [31-1](#)
  - SNMP interaction with [31-4](#)
  - supported [A-1](#)
- mini-point-of-presence
  - See POP
- mirroring traffic for analysis [28-1](#)
- mismatches, autonegotiation [41-12](#)
- module number [11-10](#)
- monitoring
  - 802.1Q tunneling [17-18](#)
  - access groups [32-41](#)
  - ACL configuration [32-41](#)
  - BGP [35-59](#)
  - cables for unidirectional links [27-1](#)
  - CDP [26-5](#)
  - CEF [35-61](#)
  - EIGRP [35-39](#)
  - fallback bridging [40-11](#)
  - features [1-10](#)
  - Flex Links [21-3](#)
  - HSRP [37-11](#)
  - IGMP
    - filters [24-25](#)
    - snooping [24-13](#)
  - interfaces [11-26](#)
  - IP
    - address tables [35-18](#)
    - multicast routing [38-50](#)
    - routes [35-74](#)
  - IPv6 [36-22](#)
  - Layer 2 protocol tunneling [17-18](#)
  - MSDP peers [39-19](#)
  - multicast router interfaces [24-13](#)
  - monitoring (continued)
    - MVR [24-20](#)
    - network traffic for analysis with probe [28-2](#)
    - OSPF [35-33](#)
    - port
      - blocking [25-16](#)
      - protection [25-16](#)
    - private VLANs [15-15](#)
    - RP mapping information [38-23](#)
    - SFP status [1-10, 11-27, 41-14](#)
    - source-active messages [39-19](#)
    - speed and duplex mode [11-19](#)
    - traffic flowing among switches [29-1](#)
    - traffic suppression [25-16](#)
    - tunneling [17-18](#)
    - VLAN
      - filters [32-41](#)
      - maps [32-41](#)
    - VLANs [13-16](#)
    - VMPS [13-32](#)
    - VTP [14-16](#)
- MSDP
  - benefits of [39-3](#)
  - clearing MSDP connections and statistics [39-19](#)
  - controlling source information
    - forwarded by switch [39-12](#)
    - originated by switch [39-9](#)
    - received by switch [39-14](#)
  - default configuration [39-4](#)
  - dense-mode regions
    - sending SA messages to [39-17](#)
    - specifying the originating address [39-18](#)
  - filtering
    - incoming SA messages [39-14](#)
    - SA messages to a peer [39-12](#)
    - SA requests from a peer [39-11](#)
  - join latency, defined [39-6](#)



## MDSP (continued)

- meshed groups
  - configuring 39-16
  - defined 39-16
- originating address, changing 39-18
- overview 39-1
- peer-RPF flooding 39-2
- peers
  - configuring a default 39-4
  - monitoring 39-19
  - peering relationship, overview 39-1
  - requesting source information from 39-8
  - shutting down 39-16
- source-active messages
  - caching 39-6
  - clearing cache entries 39-19
  - defined 39-2
  - filtering from a peer 39-11
  - filtering incoming 39-14
  - filtering to a peer 39-12
  - limiting data with TTL 39-14
  - monitoring 39-19
  - restricting advertised sources 39-9
- support for 1-9

## MSTP

- boundary ports
  - configuration guidelines 19-14
  - described 19-5
- BPDU filtering
  - described 20-3
  - enabling 20-14
- BPDU guard
  - described 20-3
  - enabling 20-13
- CIST, described 19-3
- configuration guidelines 19-13, 20-12

## MSTP (continued)

- configuring
  - forward-delay time 19-21
  - hello time 19-20
  - link type for rapid convergence 19-23
  - maximum aging time 19-22
  - maximum hop count 19-22
  - MST region 19-14
  - path cost 19-19
  - port priority 19-18
  - root switch 19-15
  - secondary root switch 19-17
  - switch priority 19-20
- CST
  - defined 19-3
  - operations between regions 19-4
- default configuration 19-13
- default optional feature configuration 20-12
- displaying status 19-24
- enabling the mode 19-14
- EtherChannel guard
  - described 20-10
  - enabling 20-17
- extended system ID
  - effects on root switch 19-15
  - effects on secondary root switch 19-17
  - unexpected behavior 19-16
- instances supported 18-10
- interface state, blocking to forwarding 20-2
- interoperability and compatibility among modes 18-11
- interoperability with 802.1D
  - described 19-6
  - restarting migration process 19-23
- IST
  - defined 19-3
  - master 19-3
  - operations within a region 19-3

## MSTP (continued)

## loop guard

described [20-11](#)enabling [20-18](#)mapping VLANs to MST instance [19-14](#)

## MST region

CIST [19-3](#)configuring [19-14](#)described [19-2](#)hop-count mechanism [19-5](#)IST [19-3](#)supported spanning-tree instances [19-2](#)optional features supported [1-6](#)overview [19-2](#)

## Port Fast

described [20-2](#)enabling [20-12](#)preventing root switch selection [20-10](#)

## root guard

described [20-10](#)enabling [20-17](#)

## root switch

configuring [19-16](#)effects of extended system ID [19-15](#)unexpected behavior [19-16](#)shutdown Port Fast-enabled port [20-3](#)stack changes, effects of [19-6](#)status, displaying [19-24](#)

## multicast groups

Immediate Leave [24-5](#)joining [24-3](#)leaving [24-5](#)static joins [24-10](#)

## multicast packets

ACLs on [32-40](#)blocking [25-7](#)multicast router interfaces, monitoring [24-13](#)multicast router ports, adding [24-9](#)

## Multicast Source Discovery Protocol

See MSDP

multicast storm [25-1](#)multicast storm-control command [25-4](#)

## Multicast VLAN Registration

See MVR

## Multiple HSRP

See MHSRP

## MVR

and address aliasing [24-17](#)configuring interfaces [24-18](#)default configuration [24-16](#)described [24-14](#)in the switch stack [24-16](#)modes [24-18](#)monitoring [24-20](#)setting global parameters [24-17](#)support for [1-4](#)

## N

named IP ACLs [32-15](#)

## NameSpace Mapper

See NSM

## native VLAN

and 802.1Q tunneling [17-4](#)configuring [13-23](#)default [13-23](#)neighbor discovery/recovery, EIGRP [35-34](#)neighbors, BGP [35-54](#)

## Network Assistant

benefits [1-2](#)described [1-4](#)downloading image files [1-2](#)guide mode [1-2](#)management options [1-2](#)managing switch stacks [5-2, 5-16](#)requirements [xxx](#)

- Network Assistant (continued)
    - upgrading a switch [B-19](#)
    - wizards [1-2](#)
  - network configuration examples
    - cost-effective wiring closet [1-15](#)
    - high-performance wiring closet [1-16](#)
    - increasing network performance [1-14](#)
    - large network [1-21](#)
    - long-distance, high-bandwidth transport [1-24](#)
    - multidwelling network [1-23](#)
    - providing network services [1-15](#)
    - redundant Gigabit backbone [1-17](#)
    - server aggregation and Linux server cluster [1-17](#)
    - small to medium-sized network [1-19](#)
  - network design
    - performance [1-14](#)
    - services [1-15](#)
  - network management
    - CDP [26-1](#)
    - RMON [29-1](#)
    - SNMP [31-1](#)
  - Network Time Protocol
    - See NTP
  - no commands [2-4](#)
  - nonhierarchical policy maps
    - configuration guidelines [33-34](#)
    - configuring [33-49](#)
    - described [33-9](#)
  - non-IP traffic filtering [32-27](#)
  - nontrunking mode [13-18](#)
  - normal-range VLANs
    - configuration modes [13-7](#)
    - defined [13-1](#)
  - no switchport command [11-4](#)
  - note, described [xxx](#)
  - not-so-stubby areas
    - See NSSA
  - NSM [4-3](#)
  - NSSA, OSPF [35-29](#)
  - NTP
    - associations
      - authenticating [7-5](#)
      - defined [7-2](#)
      - enabling broadcast messages [7-7](#)
      - peer [7-6](#)
      - server [7-6](#)
    - default configuration [7-4](#)
    - displaying the configuration [7-11](#)
    - overview [7-2](#)
    - restricting access
      - creating an access group [7-9](#)
      - disabling NTP services per interface [7-10](#)
    - source IP address, configuring [7-10](#)
    - stratum [7-2](#)
    - support for [1-5](#)
    - synchronizing devices [7-6](#)
    - time
      - services [7-2](#)
      - synchronizing [7-2](#)
- 
- O
    - offline configuration for switch stacks [5-7](#)
    - Open Shortest Path First
      - See OSPF
    - optimizing system resources [8-1](#)
    - options, management [1-4](#)
    - OSPF
      - area parameters, configuring [35-29](#)
      - configuring [35-27](#)
      - default configuration
        - metrics [35-31](#)
        - route [35-31](#)
        - settings [35-26](#)
      - described [35-25](#)
      - for IPv6 [36-20](#)
      - interface parameters, configuring [35-28](#)
      - LSA group pacing [35-32](#)

## OSPF (continued)

- monitoring [35-33](#)
  - router IDs [35-32](#)
  - route summarization [35-30](#)
  - support for [1-9](#)
  - virtual links [35-30](#)
- out-of-profile markdown [1-8](#)

## P

- packet modification, with QoS [33-20](#)

## PAgP

- Layer 2 protocol tunneling [17-9](#)
- See EtherChannel
- parallel paths, in routing tables [35-62](#)

## passive interfaces

- configuring [35-70](#)
- OSPF [35-31](#)

## passwords

- default configuration [9-2](#)
- disabling recovery of [9-5](#)
- encrypting [9-4](#)
- for security [1-7](#)
- overview [9-1](#)
- recovery of [41-3](#)
- setting
  - enable [9-3](#)
  - enable secret [9-4](#)
  - Telnet [9-6](#)
  - with usernames [9-7](#)
- VTP domain [14-8](#)

## path cost

- MSTP [19-19](#)
- STP [18-20](#)

- path MTU discovery [36-4](#)

## PBR

- defined [35-67](#)
- enabling [35-69](#)
- fast-switched policy-based routing [35-70](#)
- local policy-based routing [35-70](#)

- peers, BGP [35-54](#)

- performance, network design [1-14](#)

- performance features [1-3](#)

- persistent self-signed certificate [9-43](#)

## per-VLAN spanning-tree plus

- See PVST+

- physical ports [11-2](#)

## PIM

- default configuration [38-8](#)
- dense mode
  - overview [38-4](#)
  - rendezvous point (RP), described [38-4](#)
  - RPF lookups [38-7](#)
- displaying neighbors [38-51](#)
- enabling a mode [38-11](#)
- overview [38-3](#)
- router-query message interval, modifying [38-26](#)
- shared tree and source tree, overview [38-23](#)
- shortest path tree, delaying the use of [38-25](#)
- sparse mode
  - join messages and shared tree [38-4](#)
  - overview [38-4](#)
  - prune messages [38-5](#)
  - RPF lookups [38-7](#)
- support for [1-9](#)
- versions
  - interoperability [38-9](#)
  - troubleshooting interoperability problems [38-23](#)
  - v2 improvements [38-4](#)
- PIM-DVMRP, as snooping method [24-8](#)
- ping
  - character output description [41-15](#)
  - executing [41-15](#)
  - overview [41-14](#)

- PoE
  - auto mode [11-8](#)
  - CDP with power consumption, described [11-6](#)
  - CDP with power negotiation, described [11-6](#)
  - Cisco intelligent power management [11-6](#)
  - configuring [11-21](#)
  - devices supported [11-6](#)
  - high-power devices operating in low-power mode [11-6](#)
  - IEEE power classification levels [11-7](#)
  - powered-device detection and initial power allocation [11-7](#)
  - power management modes [11-8](#)
  - power negotiation extensions to CDP [11-6](#)
  - standards supported [11-6](#)
  - static mode [11-8](#)
  - supported watts per port [11-6](#)
  - troubleshooting [41-13](#)
- policed-DSCP map for QoS [33-63](#)
- policers
  - configuring
    - for each matched traffic class [33-49](#)
    - for more than one traffic class [33-59](#)
  - described [33-4](#)
  - displaying [33-79](#)
  - number of [33-34](#)
  - types of [33-9](#)
- policing
  - described [33-4](#)
  - hierarchical
    - See hierarchical policy maps
  - token-bucket algorithm [33-9](#)
- policy-based routing
  - See PBR
- policy maps
  - hierarchical [33-8](#)
- policy maps for QoS
  - characteristics of [33-49](#)
  - described [33-7](#)
  - displaying [33-80](#)
  - hierarchical on SVIs
    - configuration guidelines [33-34](#)
    - configuring [33-52](#)
    - described [33-11](#)
  - nonhierarchical on physical ports
    - configuration guidelines [33-34](#)
    - configuring [33-49](#)
    - described [33-9](#)
- POP [1-23](#)
- port ACLs
  - defined [32-2](#)
  - types of [32-3](#)
- Port Aggregation Protocol
  - See EtherChannel
- port-based authentication
  - accounting [10-5](#)
  - authentication server
    - defined [10-2](#)
    - RADIUS server [10-2](#)
  - client, defined [10-2](#)
  - configuration guidelines [10-12](#)
  - configuring
    - 802.1x authentication [10-14](#)
    - guest VLAN [10-20](#)
    - host mode [10-19](#)
    - manual re-authentication of a client [10-17](#)
    - periodic re-authentication [10-16](#)
    - quiet period [10-17](#)
    - RADIUS server [10-16](#)
    - RADIUS server parameters on the switch [10-15](#)
    - switch-to-client frame-retransmission number [10-18](#), [10-19](#)
    - switch-to-client retransmission time [10-17](#)

## port-based authentication (continued)

- default configuration [10-11](#)
- described [10-1](#)
- device roles [10-2](#)
- displaying statistics [10-23](#)
- EAPOL-start frame [10-3](#)
- EAP-request/identity frame [10-3](#)
- EAP-response/identity frame [10-3](#)
- encapsulation [10-3](#)
- guest VLAN
  - configuration guidelines [10-9](#)
  - described [10-8](#)
- host mode [10-5](#)
- initiation and message exchange [10-3](#)
- method lists [10-14](#)
- multiple-hosts mode, described [10-5](#)
- per-user ACLs
  - AAA authorization [10-14](#)
  - configuration tasks [10-10](#)
  - described [10-9](#)
  - RADIUS server attributes [10-9](#)
- ports
  - authorization state and dot1x port-control command [10-4](#)
  - authorized and unauthorized [10-4](#)
  - voice VLAN [10-7](#)
- port security
  - and voice VLAN [10-6](#)
  - described [10-6](#)
  - interactions [10-6](#)
  - multiple-hosts mode [10-5](#)
- resetting to default values [10-22](#)
- stack changes, effects of [10-10](#)
- statistics, displaying [10-23](#)
- switch
  - as proxy [10-2](#)
  - RADIUS client [10-2](#)
- upgrading from a previous release [10-13, 33-27](#)

## port-based authentication (continued)

- VLAN assignment
  - AAA authorization [10-14](#)
  - characteristics [10-8](#)
  - configuration tasks [10-8](#)
  - described [10-7](#)
- voice VLAN
  - described [10-7](#)
  - PVID [10-7](#)
  - VVID [10-7](#)
- port blocking [1-4, 25-6](#)
- port-channel
  - See EtherChannel
- Port Fast
  - described [20-2](#)
  - enabling [20-12](#)
  - mode, spanning tree [13-29](#)
  - support for [1-6](#)
- port membership modes, VLAN [13-3](#)
- port priority
  - MSTP [19-18](#)
  - STP [18-18](#)
- ports
  - 10-Gigabit Ethernet module [11-6](#)
  - 802.1Q tunnel [13-4](#)
  - access [11-3](#)
  - blocking [25-6](#)
  - dynamic access [13-3](#)
  - protected [25-5](#)
  - routed [11-4](#)
  - secure [25-7](#)
  - static-access [13-3, 13-11](#)
  - switch [11-2](#)
  - trunks [13-3, 13-16](#)
  - VLAN assignments [13-11](#)

- port security
  - aging 25-15
  - and QoS trusted boundary 33-39
  - and stacking 25-16
  - configuring 25-12
  - default configuration 25-10
  - described 25-7
  - displaying 25-16
  - on trunk ports 25-13
  - sticky learning 25-8
  - violations 25-9
  - with other features 25-10
- port-shutdown response, VMPS 13-28
- Power over Ethernet
  - See PoE
- preferential treatment of traffic
  - See QoS
- prefix lists, BGP 35-51
- preventing unauthorized access 9-1
- primary links 21-1
- primary VLANs 15-1, 15-3
- priority
  - HSRP 37-7
  - overriding CoS 16-6
  - trusting CoS 16-6
- private VLAN edge ports
  - See protected ports
- private VLANs
  - across multiple switches 15-4
  - and SDM template 15-4
  - and SVIs 15-5
  - and switch stacks 15-6
  - benefits of 15-1
  - community ports 15-2
  - community VLANs 15-2, 15-3
  - configuration guidelines 15-7, 15-9
  - configuration tasks 15-6
  - configuring 15-10
  - default configuration 15-7
  - private VLANs (continued)
    - end station access to 15-3
    - IP addressing 15-3
    - isolated port 15-2
    - isolated VLANs 15-2, 15-3
    - mapping 15-14
    - monitoring 15-15
    - ports
      - community 15-2
      - configuration guidelines 15-9
      - configuring host ports 15-12
      - configuring promiscuous ports 15-13
      - described 13-4
      - isolated 15-2
      - promiscuous 15-2
    - primary VLANs 15-1, 15-3
    - promiscuous ports 15-2
    - secondary VLANs 15-2
    - subdomains 15-1
    - traffic in 15-5
  - privileged EXEC mode 2-2
  - privilege levels
    - changing the default for lines 9-9
    - command switch 6-4
    - exiting 9-10
    - logging into 9-10
    - mapping on member switches 6-4
    - overview 9-2, 9-8
    - setting a command with 9-8
  - promiscuous ports
    - configuring 15-13
    - defined 15-2
  - protected ports 1-7, 25-5
  - protocol-dependent modules, EIGRP 35-35
  - Protocol-Independent Multicast Protocol
    - See PIM
  - provisioning new members for a switch stack 5-7

proxy ARP  
 configuring 35-12  
 definition 35-10  
 with IP routing disabled 35-12

pruning, VTP  
 disabling  
 in VTP domain 14-14  
 on a port 13-23  
 enabling  
 in VTP domain 14-14  
 on a port 13-22  
 examples 14-5  
 overview 14-4

pruning-eligible list  
 changing 13-22  
 for VTP pruning 14-5  
 VLANs 14-14

PVST+  
 802.1Q trunking interoperability 18-11  
 described 18-10  
 instances supported 18-10

---

## Q

QoS  
 and MQC commands 33-1  
 auto-QoS  
 categorizing traffic 33-21  
 configuration and defaults display 33-31  
 configuration guidelines 33-26  
 described 33-21  
 disabling 33-28  
 displaying generated commands 33-28  
 displaying the initial configuration 33-31  
 effects on running configuration 33-26  
 egress queue defaults 33-22  
 enabling for VoIP 33-28  
 example configuration 33-29

QoS (continued)  
 auto-QoS (continued)  
 ingress queue defaults 33-22  
 list of generated commands 33-23  
 basic model 33-4  
 classification  
 class maps, described 33-7  
 defined 33-4  
 DSCP transparency, described 33-40  
 flowchart 33-6  
 forwarding treatment 33-3  
 in frames and packets 33-3  
 IP ACLs, described 33-5, 33-7  
 MAC ACLs, described 33-5, 33-7  
 options for IP traffic 33-5  
 options for non-IP traffic 33-5  
 policy maps, described 33-7  
 trust DSCP, described 33-5  
 trusted CoS, described 33-5  
 trust IP precedence, described 33-5  
 class maps  
 configuring 33-47  
 displaying 33-79  
 configuration guidelines  
 auto-QoS 33-26  
 standard QoS 33-34  
 configuring  
 aggregate policers 33-59  
 auto-QoS 33-21  
 default port CoS value 33-38  
 DSCP maps 33-61  
 DSCP transparency 33-40  
 DSCP trust states bordering another domain 33-41  
 egress queue characteristics 33-72  
 ingress queue characteristics 33-67  
 IP extended ACLs 33-45  
 IP standard ACLs 33-43  
 MAC ACLs 33-46



## QoS (continued)

## configuring (continued)

- policy maps, hierarchical [33-52](#)
- policy maps on physical ports [33-49](#)
- port trust states within the domain [33-36](#)
- trusted boundary [33-39](#)

default auto configuration [33-21](#)default standard configuration [33-32](#)displaying statistics [33-79](#)DSCP transparency [33-40](#)

## egress queues

- allocating buffer space [33-72](#)
- buffer allocation scheme, described [33-19](#)
- configuring shaped weights for SRR [33-76](#)
- configuring shared weights for SRR [33-77](#)
- described [33-4](#)
- displaying the threshold map [33-75](#)
- flowchart [33-18](#)
- mapping DSCP or CoS values [33-74](#)
- scheduling, described [33-4](#)
- setting WTD thresholds [33-72](#)
- WTD, described [33-20](#)

enabling globally [33-35](#)

## flowcharts

- classification [33-6](#)
- egress queueing and scheduling [33-18](#)
- ingress queueing and scheduling [33-16](#)
- policing and marking [33-10](#)

implicit deny [33-7](#)

## ingress queues

- allocating bandwidth [33-70](#)
- allocating buffer space [33-69](#)
- buffer and bandwidth allocation, described [33-17](#)
- configuring shared weights for SRR [33-70](#)
- configuring the priority queue [33-71](#)
- described [33-4](#)
- displaying the threshold map [33-68](#)
- flowchart [33-16](#)
- mapping DSCP or CoS values [33-68](#)

## QoS (continued)

## ingress queues (continued)

- priority queue, described [33-17](#)
- scheduling, described [33-4](#)
- setting WTD thresholds [33-68](#)
- WTD, described [33-17](#)

## IP phones

- automatic classification and queueing [33-21](#)
- detection and trusted settings [33-21, 33-39](#)

limiting bandwidth on egress interface [33-78](#)

## mapping tables

- CoS-to-DSCP [33-61](#)
- displaying [33-79](#)
- DSCP-to-CoS [33-64](#)
- DSCP-to-DSCP-mutation [33-65](#)
- IP-precedence-to-DSCP [33-62](#)
- policed-DSCP [33-63](#)
- types of [33-13](#)

marked-down actions [33-51, 33-56](#)marking, described [33-4, 33-8](#)overview [33-2](#)packet modification [33-20](#)

## policers

- configuring [33-51, 33-56, 33-59](#)
- described [33-8](#)
- displaying [33-79](#)
- number of [33-34](#)
- types of [33-9](#)

policies, attaching to an interface [33-8](#)

## policing

- described [33-4, 33-8](#)
- token bucket algorithm [33-9](#)

## policy maps

- characteristics of [33-49](#)
- displaying [33-80](#)
- hierarchical [33-8](#)
- hierarchical on SVIs [33-52](#)
- nonhierarchical on physical ports [33-49](#)

QoS label, defined [33-4](#)

## QoS (continued)

## queues

- configuring egress characteristics [33-72](#)
- configuring ingress characteristics [33-67](#)
- high priority (expedite) [33-20, 33-78](#)
- location of [33-14](#)
- SRR, described [33-15](#)
- WTD, described [33-14](#)

rewrites [33-20](#)support for [1-8](#)

## trust states

- bordering another domain [33-41](#)
- described [33-5](#)
- trusted device [33-39](#)
- within the domain [33-36](#)

## quality of service

See QoS

queries, IGMP [24-4](#)

## R

## RADIUS

## attributes

- vendor-proprietary [9-31](#)
- vendor-specific [9-29](#)

## configuring

- accounting [9-28](#)
- authentication [9-23](#)
- authorization [9-27](#)
- communication, global [9-21, 9-29](#)
- communication, per-server [9-20, 9-21](#)
- multiple UDP ports [9-21](#)

default configuration [9-20](#)defining AAA server groups [9-25](#)displaying the configuration [9-31](#)identifying the server [9-20](#)limiting the services to the user [9-27](#)method list, defined [9-20](#)operation of [9-19](#)

## RADIUS (continued)

- overview [9-18](#)
- suggested network environments [9-18](#)
- support for [1-8](#)
- tracking services accessed by user [9-28](#)

## range

- macro [11-13](#)
- of interfaces [11-12](#)

rapid convergence [19-8](#)

## rapid per-VLAN spanning-tree plus

See rapid PVST+

## rapid PVST+

- 802.1Q trunking interoperability [18-11](#)
- described [18-10](#)
- instances supported [18-10](#)

## Rapid Spanning Tree Protocol

See RSTP

RARP [35-10](#)rcommand command [6-4](#)

## RCP

## configuration files

- downloading [B-17](#)
- overview [B-15](#)
- preparing the server [B-16](#)
- uploading [B-18](#)

## image files

- deleting old image [B-32](#)
- downloading [B-31](#)
- preparing the server [B-29](#)
- uploading [B-33](#)

reconfirmation interval, VMPS, changing [13-31](#)recovery procedures [41-1](#)

## redundancy

- EtherChannel [34-2](#)
- HSRP [37-1](#)

- redundancy (continued)
  - STP
    - backbone [18-9](#)
    - multidrop backbone [20-5](#)
    - path cost [13-26](#)
    - port priority [13-24](#)
- redundant links and UplinkFast [20-15](#)
- reliable transport protocol, EIGRP [35-34](#)
- reloading software [3-16](#)
- Remote Authentication Dial-In User Service
  - See RADIUS
- Remote Copy Protocol
  - See RCP
- Remote Network Monitoring
  - See RMON
- Remote SPAN
  - See RSPAN
- report suppression, IGMP
  - described [24-5](#)
  - disabling [24-12](#)
- requirements
  - cluster [xxxi](#)
  - device manager [xxx](#)
  - Network Assistant [xxx](#)
- resequencing ACL entries [32-15](#)
- resets, in BGP [35-46](#)
- resetting a UDLD-shutdown interface [27-6](#)
- restricting access
  - NTP services [7-8](#)
  - overview [9-1](#)
  - passwords and privilege levels [9-2](#)
  - RADIUS [9-17](#)
  - TACACS+ [9-10](#)
- retry count, VMPS, changing [13-32](#)
- reverse address resolution [35-9](#)
- Reverse Address Resolution Protocol
  - See RARP
- RFC
  - 1058, RIP [35-20](#)
  - 1112, IP multicast and IGMP [24-2](#)
  - 1157, SNMPv1 [31-2](#)
  - 1163, BGP [35-40](#)
  - 1166, IP addresses [35-6](#)
  - 1253, OSPF [35-25](#)
  - 1267, BGP [35-40](#)
  - 1305, NTP [7-2](#)
  - 1587, NSSAs [35-25](#)
  - 1757, RMON [29-2](#)
  - 1771, BGP [35-40](#)
  - 1901, SNMPv2C [31-2](#)
  - 1902 to 1907, SNMPv2 [31-2](#)
  - 2236, IP multicast and IGMP [24-2](#)
  - 2273-2275, SNMPv3 [31-2](#)
- RIP
  - advertisements [35-20](#)
  - authentication [35-23](#)
  - configuring [35-21](#)
  - default configuration [35-21](#)
  - described [35-20](#)
  - for IPv6 [36-18](#)
  - hop counts [35-20](#)
  - split horizon [35-23](#)
  - summary addresses [35-23](#)
  - support for [1-9](#)
- RMON
  - default configuration [29-3](#)
  - displaying status [29-6](#)
  - enabling alarms and events [29-3](#)
  - groups supported [29-2](#)
  - overview [29-1](#)
  - statistics
    - collecting group Ethernet [29-6](#)
    - collecting group history [29-5](#)
  - support for [1-10](#)

- root guard
  - described 20-10
  - enabling 20-17
  - support for 1-6
- root switch
  - MSTP 19-15
  - STP 18-16
- route calculation timers, OSPF 35-31
- route dampening, BGP 35-58
- routed packets, ACLs on 32-39
- routed ports
  - configuring 35-5
  - defined 11-4
  - IP addresses on 11-23, 35-5
- route-map command 35-69
- route maps
  - BGP 35-49
  - policy-based routing 35-68
- router ACLs
  - defined 32-2
  - types of 32-4
- route reflectors, BGP 35-57
- router ID, OSPF 35-32
- route selection, BGP 35-47
- route summarization, OSPF 35-30
- routing
  - default 35-3
  - dynamic 35-3
  - redistribution of information 35-64
  - static 35-3
- routing domain confederation, BGP 35-56
- Routing Information Protocol
  - See RIP
- routing protocol administrative distances 35-63
- RSPAN
  - and stack changes 28-10
  - characteristics 28-9
  - configuration guidelines 28-17
  - default configuration 28-11
  - destination ports 28-7
  - displaying status 28-25
  - in a switch stack 28-2
  - interaction with other features 28-9
  - monitored ports 28-6
  - monitoring ports 28-7
  - overview 1-10, 28-1
  - received traffic 28-5
  - session limits 28-11
  - sessions
    - creating 28-18
    - defined 28-4
    - limiting source traffic to specific VLANs 28-24
    - specifying monitored ports 28-18
    - with ingress traffic enabled 28-22
  - source ports 28-6
  - transmitted traffic 28-6
  - VLAN-based 28-7
- RSTP
  - active topology 19-7
  - BPDU
    - format 19-10
    - processing 19-11
  - designated port, defined 19-7
  - designated switch, defined 19-7
  - interoperability with 802.1D
    - described 19-6
    - restarting migration process 19-23
    - topology changes 19-11
  - overview 19-6

## RSTP (continued)

- port roles
  - described 19-7
  - synchronized 19-9
- proposal-agreement handshake process 19-8
- rapid convergence
  - cross-stack rapid convergence 19-8
  - described 19-8
  - edge ports and Port Fast 19-8
  - point-to-point links 19-8, 19-23
  - root ports 19-8
- root port, defined 19-7
- See also MSTP
- running configuration, saving 3-10

---

**S**

scheduled reloads 3-16

**SDM**

- described 8-1
- switch stack consideration 5-10
- templates
  - configuring 8-6
  - number of 8-1

SDM mismatch mode 5-10, 8-4

**SDM template**

- aggregator 8-1
- configuration guidelines 8-5
- configuring 8-5
- desktop 8-1
- dual IPv4 and IPv6 8-2
- types of 8-1

secondary VLANs 15-2

**secure HTTP client**

- configuring 9-47
- displaying 9-48

**secure HTTP server**

- configuring 9-46
- displaying 9-48

**secure MAC addresses**

- and switch stacks 25-16
- deleting 25-14
- maximum number of 25-8
- types of 25-8

**secure ports**

- and switch stacks 25-16
- configuring 25-7

secure remote connections 9-38

**Secure Shell**

See SSH

**Secure Socket Layer**

See SSL

security, port 25-7

security features 1-7

sequence numbers in log messages 30-8

server mode, VTP 14-3

service-provider network, MSTP and RSTP 19-1

**service-provider networks**

- and 802.1Q tunneling 17-1
- and customer VLANs 17-2
- Layer 2 protocols across 17-8
- Layer 2 protocol tunneling for EtherChannels 17-9

set-request operation 31-4

**setup program**

- failed command switch replacement 41-11
- replacing failed command switch 41-9

severity levels, defining in system messages 30-9

**SFPs**

- monitoring status of 1-10, 11-27, 41-14
- numbering of 11-11
- security and identification 41-13
- status, displaying 1-10

**shaped round robin**

See SRR

show access-lists hw-summary command 32-22

show and more command output, filtering 2-8

show cdp traffic command 26-5

show cluster members command 6-4

- show configuration command [11-22](#)
- show forward command [41-22](#)
- show interfaces command [11-19, 11-22](#)
- show l2protocol command [17-14, 17-16](#)
- show platform forward command [41-22](#)
- show running-config command
  - displaying ACLs [32-20, 32-21, 32-32, 32-34](#)
  - interface description in [11-22](#)
- shutdown command on interfaces [11-27](#)
- shutdown threshold for Layer 2 protocol packets [17-11](#)
- Simple Network Management Protocol
  - See SNMP
- small form-factor pluggable modules
  - See SFPs
- Smartports macros
  - applying Cisco-default macros [12-6](#)
  - applying global parameter values [12-5, 12-6](#)
  - applying macros [12-5](#)
  - applying parameter values [12-5, 12-7](#)
  - configuration guidelines [12-3](#)
  - creating [12-4](#)
  - default configuration [12-2](#)
  - defined [12-1](#)
  - displaying [12-8](#)
  - tracing [12-3](#)
  - website [12-2](#)
- SMI [1-1](#)
- SNAP [26-1](#)
- SNMP
  - accessing MIB variables with [31-4](#)
  - agent
    - described [31-4](#)
    - disabling [31-8](#)
  - authentication level [31-10](#)
- SNMP (continued)
  - community strings
    - configuring [31-8](#)
    - for cluster switches [31-4](#)
    - overview [31-4](#)
  - configuration examples [31-16](#)
  - default configuration [31-6](#)
  - engine ID [31-7](#)
  - groups [31-7, 31-9](#)
  - host [31-7](#)
  - ifIndex values [31-5](#)
  - in-band management [1-5](#)
  - informs
    - and trap keyword [31-11](#)
    - described [31-5](#)
    - differences from traps [31-5](#)
    - disabling [31-14](#)
    - enabling [31-14](#)
  - limiting access by TFTP servers [31-15](#)
  - limiting system log messages to NMS [30-10](#)
  - manager functions [1-4, 31-3](#)
  - managing clusters with [6-5](#)
  - MIBs
    - location of [A-3](#)
    - supported [A-1](#)
  - notifications [31-5](#)
  - overview [31-1, 31-4](#)
  - security levels [31-3](#)
  - status, displaying [31-17](#)
  - system contact and location [31-15](#)
  - trap manager, configuring [31-13](#)
  - traps
    - described [31-3, 31-5](#)
    - differences from informs [31-5](#)
    - disabling [31-14](#)
    - enabling [31-11](#)

- SNMP (continued)
  - traps (continued)
    - enabling MAC address notification [7-23](#)
    - overview [31-1, 31-4](#)
    - types of [31-11](#)
  - users [31-7, 31-9](#)
  - versions supported [31-2](#)
- SNMPv1 [31-2](#)
- SNMPv2C [31-2](#)
- SNMPv3 [31-2](#)
- snooping, IGMP [24-1](#)
- software compatibility
  - See stacks, switch
- software images
  - location in flash [B-20](#)
  - recovery procedures [41-2](#)
  - scheduling reloads [3-16](#)
  - tar file format, described [B-20](#)
  - See also downloading and uploading
- source addresses, in ACLs [32-12](#)
- source-and-destination-IP address based forwarding, EtherChannel [34-8](#)
- source-and-destination MAC address forwarding, EtherChannel [34-8](#)
- source-IP address based forwarding, EtherChannel [34-8](#)
- source-MAC address forwarding, EtherChannel [34-7](#)
- SPAN
  - and stack changes [28-10](#)
  - configuration guidelines [28-11](#)
  - default configuration [28-11](#)
  - destination ports [28-7](#)
  - displaying status [28-25](#)
  - interaction with other features [28-9](#)
  - monitored ports [28-6](#)
  - monitoring ports [28-7](#)
  - overview [1-10, 28-1](#)
  - ports, restrictions [25-11](#)
  - received traffic [28-5](#)
- SPAN (continued)
  - session limits [28-11](#)
  - sessions
    - configuring ingress forwarding [28-16, 28-23](#)
    - creating [28-12](#)
    - defined [28-4](#)
    - limiting source traffic to specific VLANs [28-16](#)
    - removing destination (monitoring) ports [28-14](#)
    - specifying monitored ports [28-12](#)
    - with ingress traffic enabled [28-15](#)
  - source ports [28-6](#)
  - transmitted traffic [28-6](#)
  - VLAN-based [28-7](#)
- spanning tree and native VLANs [13-19](#)
- Spanning Tree Protocol
  - See STP
- SPAN traffic [28-5](#)
- speed, configuring on interfaces [11-17](#)
- split horizon, RIP [35-23](#)
- SRR
  - configuring
    - shaped weights on egress queues [33-76](#)
    - shared weights on egress queues [33-77](#)
    - shared weights on ingress queues [33-70](#)
  - described [33-15](#)
  - shaped mode [33-15](#)
  - shared mode [33-15](#)
  - support for [1-9](#)
- SSH
  - configuring [9-39](#)
  - cryptographic software image [9-37](#)
  - described [1-5, 9-38](#)
  - encryption methods [9-38](#)
  - switch stack considerations [5-17, 9-38](#)
  - user authentication methods, supported [9-38](#)
- SSL
  - configuration guidelines [9-44](#)
  - configuring a secure HTTP client [9-47](#)
  - configuring a secure HTTP server [9-45](#)

- SSL (continued)
  - cryptographic software image [9-42](#)
  - described [9-41](#)
  - monitoring [9-48](#)
- stack changes
  - effects on
    - IPv6 routing [36-7](#)
- stack changes, effects on
  - 802.1x port-based authentication [10-10](#)
  - ACL configuration [32-7](#)
  - CDP [26-2](#)
  - cross-stack EtherChannel [34-12](#)
  - EtherChannel [34-9](#)
  - fallback bridging [40-3](#)
  - HSRP [37-4](#)
  - IGMP snooping [24-6](#)
  - IP routing [35-4](#)
  - MAC address tables [7-21](#)
  - MSTP [19-6](#)
  - multicast routing [38-8](#)
  - MVR [24-14](#)
  - port security [25-16](#)
  - SDM template selection [8-4](#)
  - SNMP [31-1](#)
  - SPAN and RSPAN [28-10](#)
  - STP [18-12](#)
  - system message log [30-2](#)
  - VLANs [13-6](#)
  - VTP [14-6](#)
- stack master
  - bridge ID (MAC address) [5-5](#)
  - defined [5-1](#)
  - election [5-4](#)
  - IPv6 [36-8](#)
  - re-election [5-4](#)
  - See also stacks, switch
- stack member
  - accessing CLI of specific member [5-23](#)
  - configuring
    - member number [5-21](#)
    - priority value [5-22](#)
  - defined [5-1](#)
  - displaying information of [5-23](#)
  - IPv6 [36-8](#)
  - number [5-6](#)
  - priority value [5-7](#)
  - provisioning a new member [5-22](#)
  - replacing [5-15](#)
  - See also stacks, switch
- stack member number [11-10](#)
- stack protocol version [5-11](#)
- stacks, switch
  - accessing CLI of specific member [5-23](#)
  - assigning information
    - member number [5-21](#)
    - priority value [5-22](#)
    - provisioning a new member [5-22](#)
  - auto-advise [5-12](#)
  - auto-copy [5-12](#)
  - auto-upgrade [5-12](#)
  - benefits [1-2](#)
  - bridge ID [5-5](#)
  - CDP considerations [26-2](#)
  - compatibility, software [5-10](#)
  - configuration file [5-15](#)
  - configuration scenarios [5-17](#)
  - copying an image file from one member to another [B-34](#)
  - default configuration [5-20](#)
  - description of [5-1](#)
  - displaying information of [5-23](#)
  - hardware compatibility and SDM mismatch mode [5-10](#)
  - HSRP considerations [37-4](#)
  - incompatible software and image upgrades [5-15, B-34](#)
  - IPv6 on [36-7](#)
  - MAC address considerations [7-21](#)



- stacks, switch (continued)
    - management connectivity [5-16](#)
    - managing [5-1](#)
    - membership [5-3](#)
    - merged [5-3](#)
    - MSTP instances supported [18-10](#)
    - multicast routing, stack master and member roles [38-8](#)
    - offline configuration
      - described [5-7](#)
      - effects of adding a provisioned switch [5-8](#)
      - effects of removing a provisioned switch [5-10](#)
      - effects of replacing a provisioned switch [5-10](#)
      - provisioned configuration, defined [5-7](#)
      - provisioned switch, defined [5-7](#)
      - provisioning a new member [5-22](#)
    - partitioned [5-3, 41-8](#)
    - provisioned switch
      - adding [5-8](#)
      - removing [5-10](#)
      - replacing [5-10](#)
    - replacing a failed member [5-15](#)
    - software compatibility [5-10](#)
    - software image version [5-10](#)
    - stack protocol version [5-11](#)
  - STP
    - bridge ID [18-3](#)
    - instances supported [18-10](#)
    - root port selection [18-3](#)
    - stack root switch election [18-3](#)
  - system messages
    - hostnames in the display [30-1](#)
    - remotely monitoring [30-2](#)
  - system prompt consideration [7-14](#)
  - system-wide configuration considerations [5-16](#)
  - upgrading [B-34](#)
- stacks, switch (continued)
    - version-mismatch (VM) mode
      - automatic upgrades with auto-upgrade [5-12](#)
      - described [5-12](#)
      - examples [5-13](#)
      - manual upgrades with auto-advise [5-12](#)
    - See also stack master and stack member
  - StackWise technology, Cisco [1-3](#)
    - See also stacks, switch
  - standard multilayer image
    - See SMI
  - standby command switch, requirements [6-2](#)
  - standby ip command [37-5](#)
  - standby links [21-1](#)
  - standby router [37-1](#)
  - standby timers, HSRP [37-9](#)
  - startup configuration
    - booting
      - manually [3-13](#)
      - specific image [3-13](#)
    - clearing [B-19](#)
    - configuration file
      - automatically downloading [3-12](#)
      - specifying the filename [3-12](#)
    - default boot configuration [3-12](#)
  - stateless autoconfiguration [36-4](#)
  - static access ports
    - assigning to VLAN [13-11](#)
    - defined [11-3, 13-3](#)
  - static addresses
    - See addresses
  - static IP routing [1-9](#)
  - static MAC addressing [1-7](#)
  - static routes
    - configuring [35-62](#)
    - configuring for IPv6 [36-16](#)
  - static routing [35-3](#)
  - static VLAN membership [13-2](#)

## statistics

- 802.1x [10-23](#)
- CDP [26-5](#)
- interface [11-26](#)
- IP multicast routing [38-51](#)
- OSPF [35-33](#)
- QoS ingress and egress [33-79](#)
- RMON group Ethernet [29-6](#)
- RMON group history [29-5](#)
- SNMP input and output [31-17](#)
- VTP [14-16](#)

sticky learning [25-8](#)

## storm control

- configuring [25-3](#)
- described [25-1](#)
- disabling [25-5](#)
- displaying [25-16](#)
- support for [1-4](#)
- thresholds [25-1](#)

## STP

- 802.1D and bridge ID [18-4](#)
- 802.1D and multicast addresses [18-9](#)
- 802.1t and VLAN identifier [18-4](#)
- accelerating root port selection [20-4](#)
- BackboneFast
  - described [20-7](#)
  - disabling [20-17](#)
  - enabling [20-16](#)
- BPDUs filtering
  - described [20-3](#)
  - disabling [20-15](#)
  - enabling [20-14](#)

## STP (continued)

- BPDUs guard
  - described [20-3](#)
  - disabling [20-14](#)
  - enabling [20-13](#)
- BPDUs message exchange [18-3](#)
- configuration guidelines [18-13, 20-12](#)
- configuring
  - forward-delay time [18-23](#)
  - hello time [18-22](#)
  - maximum aging time [18-23](#)
  - path cost [18-20](#)
  - port priority [18-18](#)
  - root switch [18-16](#)
  - secondary root switch [18-18](#)
  - spanning-tree mode [18-15](#)
  - switch priority [18-21](#)
- counters, clearing [18-24](#)
- cross-stack UplinkFast
  - described [20-5](#)
  - enabling [20-16](#)
- default configuration [18-13](#)
- default optional feature configuration [20-12](#)
- designated port, defined [18-4](#)
- designated switch, defined [18-4](#)
- detecting indirect link failures [20-8](#)
- disabling [18-16](#)
- displaying status [18-24](#)
- EtherChannel guard
  - described [20-10](#)
  - disabling [20-17](#)
  - enabling [20-17](#)
- extended system ID
  - effects on root switch [18-16](#)
  - effects on the secondary root switch [18-18](#)
  - overview [18-4](#)
  - unexpected behavior [18-16](#)

## STP (continued)

- features supported 1-6
- inferior BPDU 18-3
- instances supported 18-10
- interface state, blocking to forwarding 20-2
- interface states
  - blocking 18-7
  - disabled 18-8
  - forwarding 18-6, 18-7
  - learning 18-7
  - listening 18-7
  - overview 18-5
- interoperability and compatibility among modes 18-11
- keepalive messages 18-2
- Layer 2 protocol tunneling 17-8
- limitations with 802.1Q trunks 18-11
- load sharing
  - overview 13-24
  - using path costs 13-26
  - using port priorities 13-24
- loop guard
  - described 20-11
  - enabling 20-18
- modes supported 18-10
- multicast addresses, effect of 18-9
- optional features supported 1-6
- overview 18-2
- path costs 13-26, 13-27
- Port Fast
  - described 20-2
  - enabling 20-12
- port priorities 13-25
- preventing root switch selection 20-10
- protocols supported 18-10
- redundant connectivity 18-9
- root guard
  - described 20-10
  - enabling 20-17
- root port, defined 18-3

## STP (continued)

- root port selection on a switch stack 18-3
- root switch
  - configuring 18-16
  - effects of extended system ID 18-4, 18-16
  - election 18-3
  - unexpected behavior 18-16
- shutdown Port Fast-enabled port 20-3
- stack changes, effects of 18-12
- status, displaying 18-24
- superior BPDU 18-3
- timers, described 18-22
- UplinkFast
  - described 20-4
  - enabling 20-15
  - VLAN-bridge 18-12
- stratum, NTP 7-2
- stub areas, OSPF 35-29
- subdomains, private VLAN 15-1
- subnet mask 35-7
- subnet zero 35-7
- success response, VMPS 13-28
- summer time 7-13
- SunNet Manager 1-4
- supernet 35-8
- SVIs
  - and IP unicast routing 35-5
  - and router ACLs 32-4
  - connecting VLANs 11-9
  - defined 11-5
  - routing between VLANs 13-2
- switch clustering technology 6-1
  - See also clusters, switch
- switch console port 1-5
- Switch Database Management
  - See SDM
- switched packets, ACLs on 32-38
- Switched Port Analyzer
  - See SPAN

- switched ports [11-2](#)
  - switchport block multicast command [25-7](#)
  - switchport block unicast command [25-7](#)
  - switchport command [11-15](#)
  - switchport mode dot1q-tunnel command [17-6](#)
  - switchport protected command [25-6](#)
  - switch priority
    - MSTP [19-20](#)
    - STP [18-21](#)
  - switch software features [1-1](#)
  - switch virtual interface
    - See SVI
  - synchronization, BGP [35-44](#)
  - syslog
    - See system message logging
  - system clock
    - configuring
      - daylight saving time [7-13](#)
      - manually [7-11](#)
      - summer time [7-13](#)
      - time zones [7-12](#)
    - displaying the time and date [7-12](#)
    - overview [7-2](#)
    - See also NTP
  - system message logging
    - default configuration [30-4](#)
    - defining error message severity levels [30-9](#)
    - disabling [30-4](#)
    - displaying the configuration [30-13](#)
    - enabling [30-5](#)
    - facility keywords, described [30-13](#)
    - level keywords, described [30-10](#)
    - limiting messages [30-10](#)
    - message format [30-2](#)
    - overview [30-1](#)
    - sequence numbers, enabling and disabling [30-8](#)
    - setting the display destination device [30-5](#)
    - stack changes, effects of [30-2](#)
    - synchronizing log messages [30-6](#)
    - system message logging (continued)
      - syslog facility [1-10](#)
      - time stamps, enabling and disabling [30-8](#)
      - UNIX syslog servers
        - configuring the daemon [30-12](#)
        - configuring the logging facility [30-12](#)
        - facilities supported [30-13](#)
    - system MTU and 802.1Q tunneling [17-5](#)
    - system name
      - default configuration [7-15](#)
      - default setting [7-15](#)
      - manual configuration [7-15](#)
      - See also DNS
    - system prompt
      - default setting [7-14 to 7-15](#)
      - manual configuration [7-16](#)
    - system resources, optimizing [8-1](#)
- 
- T
- TACACS+
    - accounting, defined [9-11](#)
    - authentication, defined [9-11](#)
    - authorization, defined [9-11](#)
    - configuring
      - accounting [9-17](#)
      - authentication key [9-13](#)
      - authorization [9-16](#)
      - login authentication [9-14](#)
    - default configuration [9-13](#)
    - displaying the configuration [9-17](#)
    - identifying the server [9-13](#)
    - limiting the services to the user [9-16](#)
    - operation of [9-12](#)
    - overview [9-10](#)
    - support for [1-8](#)
    - tracking services accessed by user [9-17](#)

- tagged packets
  - 802.1Q [17-3](#)
  - Layer 2 protocol [17-8](#)
- tar files
  - creating [B-6](#)
  - displaying the contents of [B-6](#)
  - extracting [B-7](#)
  - image file format [B-20](#)
- TDR [1-10](#)
- Telnet
  - accessing management interfaces [2-9](#)
  - number of connections [1-5](#)
  - setting a password [9-6](#)
- templates, SDM [8-1](#)
- temporary self-signed certificate [9-43](#)
- Terminal Access Controller Access Control System Plus
  - See TACACS+
- terminal lines, setting a password [9-6](#)
- TFTP
  - configuration files
    - downloading [B-11](#)
    - preparing the server [B-10](#)
    - uploading [B-11](#)
  - configuration files in base directory [3-6](#)
  - configuring for autoconfiguration [3-6](#)
  - image files
    - deleting [B-23](#)
    - downloading [B-22](#)
    - preparing the server [B-22](#)
    - uploading [B-24](#)
  - limiting access by servers [31-15](#)
- TFTP server [1-5](#)
- threshold, traffic level [25-2](#)
- time
  - See NTP and system clock
- Time Domain Reflector
  - See TDR
- time-range command [32-17](#)
- time ranges in ACLs [32-17](#)
- time stamps in log messages [30-8](#)
- time zones [7-12](#)
- Token Ring VLANs
  - support for [13-6](#)
  - VTP support [14-4](#)
- ToS [1-8](#)
- traceroute, Layer 2
  - and ARP [41-17](#)
  - and CDP [41-16](#)
  - broadcast traffic [41-16](#)
  - described [41-16](#)
  - IP addresses and subnets [41-17](#)
  - MAC addresses and VLANs [41-16](#)
  - multicast traffic [41-16](#)
  - multiple devices on a port [41-17](#)
  - unicast traffic [41-16](#)
  - usage guidelines [41-16](#)
- traceroute command [41-18](#)
  - See also IP traceroute
- traffic
  - blocking flooded [25-6](#)
  - fragmented [32-5](#)
  - unfragmented [32-5](#)
- traffic policing [1-8](#)
- traffic suppression [25-1](#)
- transparent mode, VTP [14-3, 14-12](#)
- trap-door mechanism [3-2](#)
- traps
  - configuring MAC address notification [7-23](#)
  - configuring managers [31-11](#)
  - defined [31-3](#)
  - enabling [7-23, 31-11](#)
  - notification types [31-11](#)
  - overview [31-1, 31-4](#)
- troubleshooting
  - connectivity problems [41-14, 41-16, 41-17](#)
  - detecting unidirectional links [27-1](#)
  - displaying crash information [41-24](#)
  - PIMv1 and PIMv2 interoperability problems [38-23](#)

- troubleshooting (continued)
    - setting packet forwarding [41-22](#)
    - SFP security and identification [41-13](#)
    - show forward command [41-22](#)
    - with CiscoWorks [31-4](#)
    - with debug commands [41-20](#)
    - with ping [41-14](#)
    - with system message logging [30-1](#)
    - with traceroute [41-17](#)
  - trunking encapsulation [1-6](#)
  - trunk ports
    - configuring [13-20](#)
    - defined [11-3, 13-3](#)
    - encapsulation [13-20, 13-25, 13-27](#)
    - secure MAC addresses on [25-12](#)
  - trunks
    - allowed-VLAN list [13-21](#)
    - configuring [13-20, 13-25, 13-27](#)
    - ISL [13-16](#)
    - load sharing
      - setting STP path costs [13-26](#)
      - using STP port priorities [13-24, 13-25](#)
    - native VLAN for untagged traffic [13-23](#)
    - parallel [13-26](#)
    - pruning-eligible list [13-22](#)
    - to non-DTP device [13-17](#)
    - understanding [13-17](#)
  - trusted boundary for QoS [33-39](#)
  - trusted port states
    - between QoS domains [33-41](#)
    - classification options [33-5](#)
    - ensuring port security for IP phones [33-39](#)
    - support for [1-8](#)
    - within a QoS domain [33-36](#)
  - trustpoints, CA [9-42](#)
  - tunneling
    - 802.1Q [17-1](#)
    - defined [17-1](#)
    - Layer 2 protocol [17-8](#)
  - tunnel ports
    - 802.1Q, configuring [17-6](#)
    - defined [13-4](#)
    - described [11-4, 17-1](#)
    - incompatibilities with other features [17-6](#)
  - twisted-pair Ethernet, detecting unidirectional links [27-1](#)
  - type of service
    - See ToS
- 
- ## U
- UDLD
    - default configuration [27-4](#)
    - disabling
      - fiber-optic interfaces [27-5](#)
      - globally [27-5](#)
      - per interface [27-6](#)
    - echoing detection mechanism [27-3](#)
    - enabling
      - globally [27-5](#)
      - per interface [27-6](#)
    - Layer 2 protocol tunneling [17-10](#)
    - link-detection mechanism [27-1](#)
    - neighbor database [27-2](#)
    - overview [27-1](#)
    - resetting an interface [27-6](#)
    - status, displaying [27-7](#)
    - support for [1-6](#)
  - UDP, configuring [35-16](#)
  - unauthorized ports with 802.1x [10-4](#)
  - unicast MAC address filtering [1-5](#)
    - and adding static addresses [7-26](#)
    - and broadcast MAC addresses [7-26](#)
    - and CPU packets [7-26](#)
    - and multicast addresses [7-26](#)
    - and router MAC addresses [7-26](#)
    - configuration guidelines [7-26](#)
    - described [7-26](#)
  - unicast storm [25-1](#)

unicast storm control command [25-4](#)

unicast traffic, blocking [25-7](#)

UniDirectional Link Detection protocol  
See UDLD

UNIX syslog servers  
daemon configuration [30-12](#)  
facilities supported [30-13](#)  
message logging configuration [30-12](#)

unrecognized Type-Length-Value (TLV) support [14-4](#)

upgrading information  
See release notes

upgrading software images  
See downloading

UplinkFast  
described [20-4](#)  
disabling [20-16](#)  
enabling [20-15](#)  
support for [1-6](#)

uploading  
configuration files  
preparing [B-10, B-13, B-16](#)  
reasons for [B-8](#)  
using FTP [B-14](#)  
using RCP [B-18](#)  
using TFTP [B-11](#)

image files  
preparing [B-22, B-25, B-29](#)  
reasons for [B-19](#)  
using FTP [B-28](#)  
using RCP [B-33](#)  
using TFTP [B-24](#)

User Datagram Protocol  
See UDP

user EXEC mode [2-2](#)

username-based authentication [9-7](#)

---

V

version-dependent transparent mode [14-4](#)

version-mismatch (VM) mode  
automatic upgrades with auto-upgrade [5-12](#)  
described [5-12](#)  
displaying [5-12](#)  
manual upgrades with auto-advise [5-12](#)

virtual router [37-1, 37-2](#)

vlan.dat file [13-5](#)

VLAN 1, disabling on a trunk port [13-22](#)

VLAN 1 minimization [13-21](#)

VLAN ACLs  
See VLAN maps

vlan-assignment response, VMPS [13-28](#)

VLAN configuration  
at bootup [13-8](#)  
saving [13-8](#)

VLAN configuration mode [2-2, 13-7](#)

VLAN database  
and startup configuration file [13-8](#)  
and VTP [14-1](#)  
VLAN configuration saved in [13-7](#)  
VLANs saved in [13-4](#)

vlan database command [13-7](#)

vlan dot1q tag native command [17-5](#)

VLAN filtering and SPAN [28-7](#)

vlan global configuration command [13-7](#)

VLAN ID, discovering [7-27](#)

VLAN management domain [14-2](#)

VLAN Management Policy Server  
See VMPS

VLAN map entries, order of [32-31](#)

VLAN maps  
applying [32-34](#)  
common uses for [32-35](#)

## VLAN maps (continued)

- configuration example [32-35](#)
- configuration guidelines [32-31](#)
- configuring [32-30](#)
- creating [32-32](#)
- defined [32-2](#)
- denying access example [32-36](#)
- denying and permitting packets [32-32](#)
- displaying [32-41](#)
- examples [32-36](#)
- removing [32-34](#)
- support for [1-7](#)
- with router ACLs [32-41](#)

## VLAN membership

- confirming [13-31](#)
- modes [13-3](#)

## VLAN Query Protocol

See VQP

## VLANs

- adding [13-9](#)
- adding to VLAN database [13-9](#)
- aging dynamic addresses [18-10](#)
- allowed on trunk [13-21](#)
- and spanning-tree instances [13-3, 13-6, 13-13](#)
- configuration guidelines, extended-range VLANs [13-13](#)
- configuration guidelines, normal-range VLANs [13-6](#)
- configuration options [13-7](#)
- configuring [13-1](#)
- configuring IDs 1006 to 4094 [13-13](#)
- connecting through SVIs [11-9](#)
- creating in config-vlan mode [13-9](#)
- creating in VLAN configuration mode [13-10](#)
- customer numbering in service-provider networks [17-3](#)
- default configuration [13-8](#)
- deleting [13-10](#)
- described [11-2, 13-1](#)
- displaying [13-16](#)
- extended-range [13-1, 13-12](#)
- features [1-6](#)

## VLANs (continued)

- illustrated [13-2](#)
- internal [13-13](#)
- in the switch stack [13-6](#)
- limiting source traffic with RSPAN [28-24](#)
- limiting source traffic with SPAN [28-16](#)
- modifying [13-9](#)
- native, configuring [13-23](#)
- normal-range [13-1, 13-4](#)
- number supported [1-6](#)
- parameters [13-5](#)
- port membership modes [13-3](#)
- static-access ports [13-11](#)
- STP and 802.1Q trunks [18-11](#)
- supported [13-2](#)
- Token Ring [13-6](#)
- traffic between [13-2](#)
- VLAN-bridge STP [18-12, 40-2](#)
- VTP modes [14-3](#)

## VLAN Trunking Protocol

See VTP

VLAN trunks [13-16, 13-17](#)

## VMPS

- administering [13-32](#)
- configuration example [13-33](#)
- configuration guidelines [13-29](#)
- default configuration [13-29](#)
- description [13-27](#)
- dynamic port membership
  - described [13-28](#)
  - reconfirming [13-31](#)
  - troubleshooting [13-33](#)
- entering server address [13-30](#)
- mapping MAC addresses to VLANs [13-28](#)
- monitoring [13-32](#)
- reconfirmation interval, changing [13-31](#)
- reconfirming membership [13-31](#)
- retry count, changing [13-32](#)
- voice-over-IP [16-1](#)



## voice VLAN

- Cisco 7960 phone, port connections [16-1](#)
- configuration guidelines [16-3](#)
- configuring IP phones for data traffic
  - override CoS of incoming frame [16-6](#)
  - trust CoS priority of incoming frame [16-6](#)
- configuring ports for voice traffic in
  - 802.1p priority tagged frames [16-5](#)
  - 802.1Q frames [16-5](#)
- connecting to an IP phone [16-4](#)
- default configuration [16-3](#)
- described [16-1](#)
- displaying [16-6](#)

VQP [1-6, 13-27](#)

## VTP

- adding a client to a domain [14-14](#)
- advertisements [13-19, 14-3](#)
- and extended-range VLANs [14-2](#)
- and normal-range VLANs [14-2](#)
- client mode, configuring [14-11](#)
- configuration
  - global configuration mode [14-7](#)
  - guidelines [14-8](#)
  - privileged EXEC mode [14-7](#)
  - requirements [14-9](#)
  - saving [14-7](#)
  - VLAN configuration mode [14-8](#)
- configuration mode options [14-7](#)
- configuration requirements [14-9](#)
- configuration revision number
  - guideline [14-14](#)
  - resetting [14-15](#)
- configuring
  - client mode [14-11](#)
  - server mode [14-9](#)
  - transparent mode [14-12](#)
- consistency checks [14-4](#)

## VTP (continued)

- default configuration [14-7](#)
- described [14-1](#)
- disabling [14-12](#)
- domain names [14-8](#)
- domains [14-2](#)
- Layer 2 protocol tunneling [17-8](#)
- modes
  - client [14-3, 14-11](#)
  - server [14-3, 14-9](#)
  - transitions [14-3](#)
  - transparent [14-3, 14-12](#)
- monitoring [14-16](#)
- passwords [14-8](#)
- pruning
  - disabling [14-14](#)
  - enabling [14-14](#)
  - examples [14-5](#)
  - overview [14-4](#)
  - support for [1-7](#)
- pruning-eligible list, changing [13-22](#)
- server mode, configuring [14-9](#)
- statistics [14-16](#)
- support for [1-7](#)
- Token Ring support [14-4](#)
- transparent mode, configuring [14-12](#)
- using [14-1](#)
- version, guidelines [14-9](#)
- Version 1 [14-4](#)
- Version 2
  - configuration guidelines [14-9](#)
  - disabling [14-13](#)
  - enabling [14-13](#)
  - overview [14-4](#)

---

## W

weighted tail drop

See WTD

wizards [1-2](#)

### WTD

described [33-14](#)

setting thresholds

egress queue-sets [33-72](#)

ingress queues [33-68](#)

support for [1-9](#)

---

## X

Xmodem protocol [41-2](#)