



A

aaa accounting dot1x command [2-1](#)
aaa authentication dot1x command [2-3](#)
AAA methods [2-3](#)
abort command [2-710](#)
access control entries
 See ACEs
access control lists
 See ACLs
access groups
 IP [2-130](#)
 MAC, displaying [2-474](#)
access list, IPv6 [2-188](#)
access map configuration mode [2-239](#)
access mode [2-653](#)
access ports [2-653](#)
ACEs [2-87](#), [2-307](#)
ACLs
 deny [2-85](#)
 displaying [2-357](#)
 for non-IP protocols [2-219](#)
 IP [2-130](#)
 matching [2-239](#)
 on Layer 2 interfaces [2-130](#)
 permit [2-305](#)
action command [2-5](#)
address aliasing [2-288](#)
aggregate-port learner [2-293](#)
allowed VLANs [2-673](#)
apply command [2-710](#)
archive copy-sw command [2-7](#)
archive download-sw command [2-10](#)

archive tar command [2-15](#)
archive upload-sw command [2-18](#)
arp access-list command [2-20](#)
audience [xix](#)
authentication failed VLAN
 See dot1x auth-fail vlan
auth-fail max-attempts
 See dot1x auth-fail max-attempts
auth-fail vlan
 See dot1x auth-fail vlan
authorization state of controlled port [2-107](#)
autonegotiation of duplex mode [2-115](#)
auto qos voip command [2-22](#)

B

BackboneFast, for STP [2-581](#)
backup interfaces
 configuring [2-649](#)
 displaying [2-417](#)
boot (boot loader) command [A-2](#)
boot auto-copy-sw command [2-27](#)
boot boothlpr command [2-28](#)
boot config-file command [2-29](#)
boot enable-break command [2-30](#)
boot helper command [2-31](#)
boot helper-config file command [2-32](#)
booting
 Cisco IOS image [2-35](#)
 displaying environment variables [2-366](#)
 interrupting [2-30](#)
 manually [2-33](#)

boot loader

- accessing [A-1](#)
- booting
 - Cisco IOS image [A-2](#)
 - helper image [2-31](#)
- directories
 - creating [A-16](#)
 - displaying a list of [A-7](#)
 - removing [A-20](#)
- displaying
 - available commands [A-12](#)
 - memory heap utilization [A-14](#)
 - version [A-27](#)
- environment variables
 - described [A-21](#)
 - displaying settings [A-21](#)
 - location of [A-22](#)
 - setting [A-21](#)
 - unsetting [A-25](#)
- files
 - copying [A-5](#)
 - deleting [A-6](#)
 - displaying a list of [A-7](#)
 - displaying the contents of [A-4, A-17, A-24](#)
 - renaming [A-18](#)
- file system
 - formatting [A-10](#)
 - initializing flash [A-9](#)
 - running a consistency check [A-11](#)
- loading helper images [A-13](#)
- prompt [A-1](#)
- resetting the system [A-19](#)

boot manual command [2-33](#)

boot private-config-file command [2-34](#)

boot system command [2-35](#)

BPDU filtering, for spanning tree [2-582, 2-617](#)

BPDU guard, for spanning tree [2-584, 2-617](#)

broadcast storm control [2-637](#)

C

candidate switches

- See clusters

cat (boot loader) command [A-4](#)

caution, description [xx](#)

CDP, enabling protocol tunneling for [2-206](#)

channel-group command [2-37](#)

channel-protocol command [2-41](#)

Cisco Network Assistant

- See Network Assistant [xx](#)

Cisco SoftPhone

- auto-QoS configuration [2-22](#)
- trusting packets sent from [2-279](#)

class command [2-42](#)

class-map command [2-44](#)

class maps

- creating [2-44](#)
- defining the match criteria [2-241](#)
- displaying [2-370](#)

class of service

- See CoS

clear ip arp inspection log command [2-46](#)

clear ip arp inspection statistics command [2-47](#)

clear ipc command [2-49](#)

clear ip dhcp snooping database command [2-48](#)

clear l2protocol-tunnel counters command [2-50](#)

clear lacp command [2-51](#)

clear mac address-table command [2-52, 2-54](#)

clear pagp command [2-55](#)

clear port-security command [2-56](#)

clear spanning-tree counters command [2-58](#)

clear spanning-tree detected-protocols command [2-59](#)

clear vmps statistics command [2-60](#)

clear vtp counters command [2-61](#)

cluster commander-address command [2-62](#)

cluster discovery hop-count command [2-64](#)

cluster enable command [2-65](#)

cluster holdtime command [2-67](#)

- cluster member command [2-68](#)
- cluster outside-interface command [2-70](#)
- cluster requirements [xxi](#)
- cluster run command [2-71](#)
- clusters
 - adding candidates [2-68](#)
 - binding to HSRP group [2-72](#)
 - building manually [2-68](#)
 - communicating with
 - devices outside the cluster [2-70](#)
 - members by using Telnet [2-330](#)
 - debug messages, display [B-5](#)
 - displaying
 - candidate switches [2-373](#)
 - debug messages [B-5](#)
 - member switches [2-375](#)
 - status [2-371](#)
 - hop-count limit for extended discovery [2-64](#)
 - HSRP standby groups [2-72](#)
 - redundancy [2-72](#)
 - SNMP trap [2-571](#)
- cluster standby-group command [2-72](#)
- cluster timer command [2-74](#)
- command modes defined [1-2](#)
- commands changed in Cisco IOS Release 12.2(18)SE [1-6](#)
- command switch
 - See clusters
- configuration, initial
 - See getting started guide and hardware installation guide
- configuration files
 - password recovery disable considerations [A-1](#)
 - specifying the name [2-29, 2-34](#)
- configuring multiple interfaces [2-126](#)
- config-vlan mode
 - commands [2-696](#)
 - description [1-4](#)
 - entering [2-695](#)
 - summary [1-2](#)

- conventions
 - command [xx](#)
 - for examples [xx](#)
 - publication [xx](#)
 - text [xx](#)
- copy (boot loader) command [A-5](#)
- CoS
 - assigning default value to incoming packets [2-249](#)
 - assigning to Layer 2 protocol packets [2-209](#)
 - overriding the incoming value [2-249](#)
- CoS-to-DSCP map [2-253](#)
- CPU ASIC statistics, displaying [2-377](#)
- crashinfo files [2-121](#)

D

- debug auto qos command [B-2](#)
- debug backup command [B-4](#)
- debug cluster command [B-5](#)
- debug dot1x command [B-7](#)
- debug dtp command [B-9](#)
- debug etherchannel command [B-10](#)
- debug ilpower command [B-12](#)
- debug interface command [B-15](#)
- debug ip dhcp snooping command [B-13](#)
- debug ip igmp filter command [B-17](#)
- debug ip igmp max-groups command [B-18](#)
- debug ip igmp snooping command [B-19](#)
- debug ip verify source packet command [B-14](#)
- debug lacp command [B-20](#)
- debug mac-notification command [B-21](#)
- debug matm command [B-22](#)
- debug matm move update command [B-23](#)
- debug monitor command [B-24](#)
- debug mvrdbg command [B-26](#)
- debug nvram command [B-27](#)
- debug pagp command [B-28](#)
- debug platform acl command [B-29](#)
- debug platform backup interface command [B-30](#)

- debug platform cli-redirect main command [B-31](#)
- debug platform configuration command [B-32](#), [B-40](#)
- debug platform cpu-queues command [B-33](#)
- debug platform device-manager command [B-35](#)
- debug platform dot1x command [B-36](#)
- debug platform etherchannel command [B-37](#)
- debug platform fallback-bridging command [B-38](#)
- debug platform forw-tcam command [B-39](#)
- debug platform ip arp inspection command [B-42](#)
- debug platform ipc command [B-50](#)
- debug platform ip dhcp command [B-43](#)
- debug platform ip igmp snooping command [B-44](#)
- debug platform ip multicast command [B-46](#)
- debug platform ip unicast command [B-48](#)
- debug platform led command [B-51](#)
- debug platform matm command [B-52](#)
- debug platform messaging application command [B-54](#)
- debug platform phy command [B-56](#)
- debug platform pm command [B-58](#)
- debug platform port-asic command [B-60](#)
- debug platform port-security command [B-61](#)
- debug platform qos-acl-tcam command [B-62](#)
- debug platform remote-commands command [B-63](#)
- debug platform resource-manager command [B-64](#)
- debug platform snmp command [B-65](#)
- debug platform span command [B-66](#)
- debug platform stack-manager command [B-67](#)
- debug platform supervisor-asic command [B-68](#)
- debug platform sw-bridge command [B-69](#)
- debug platform tcam command [B-70](#)
- debug platform udd command [B-73](#)
- debug platform vlan command [B-74](#)
- debug pm command [B-75](#)
- debug port-security command [B-77](#)
- debug qos-manager command [B-78](#)
- debug spanning-tree backbonefast command [B-81](#)
- debug spanning-tree bpdu command [B-82](#)
- debug spanning-tree bpdu-opt command [B-83](#)
- debug spanning-tree command [B-79](#)
- debug spanning-tree mstp command [B-84](#)
- debug spanning-tree switch command [B-86](#)
- debug spanning-tree uplinkfast command [B-88](#)
- debug sw-vlan command [B-89](#)
- debug sw-vlan ifs command [B-91](#)
- debug sw-vlan notification command [B-93](#)
- debug sw-vlan vtp command [B-95](#)
- debug udd command [B-97](#)
- debug vqpc command [B-99](#)
- define interface-range command [2-75](#)
- delete (boot loader) command [A-6](#)
- delete command [2-77](#)
- deny (ARP access-list configuration) command [2-78](#)
- deny (IPv6) command [2-80](#)
- deny command [2-85](#)
- detect mechanism, causes [2-116](#)
- device manager requirements [xx](#)
- DHCP snooping
 - accepting untrusted packets from edge switch [2-155](#)
 - enabling
 - on a VLAN [2-160](#)
 - option 82 [2-153](#), [2-155](#)
 - trust on an interface [2-158](#)
 - error recovery timer [2-118](#)
 - rate limiting [2-157](#)
- DHCP snooping binding database
 - binding file, configuring [2-151](#)
 - bindings
 - adding [2-149](#)
 - deleting [2-149](#)
 - displaying [2-435](#)
 - clearing database agent statistics [2-48](#)
 - database agent, configuring [2-151](#)
 - displaying
 - binding entries [2-435](#)
 - database agent status [2-437](#)
 - renewing [2-337](#)
- dir (boot loader) command [A-7](#)
- directories, deleting [2-77](#)

- documentation, related [xx](#)
- document conventions [xx](#)
- domain name, VTP [2-721](#), [2-725](#)
- dot1x auth-fail max-attempts [2-90](#)
- dot1x auth-fail vlan [2-92](#)
- dot1x command [2-88](#)
- dot1x control-direction command [2-94](#)
- dot1x critical command [2-96](#)
- dot1x default command [2-98](#)
- dot1x guest-vlan command [2-99](#)
- dot1x host-mode command [2-101](#)
- dot1x initialize command [2-103](#)
- dot1x max-req command [2-104](#), [2-105](#)
- dot1x multiple-hosts command [2-106](#)
- dot1x port-control command [2-107](#)
- dot1x re-authenticate command [2-109](#)
- dot1x re-authentication command [2-110](#)
- dot1x reauthentication command [2-111](#)
- dot1x timeout command [2-112](#)
- dropping packets, with ACL matches [2-5](#)
- drop threshold, Layer 2 protocol tunneling [2-206](#)
- DSCP-to-CoS map [2-253](#)
- DSCP-to-DSCP-mutation map [2-253](#)
- DTP [2-654](#)
- DTP flap
 - error detection for [2-116](#)
 - error recovery timer [2-118](#)
- DTP negotiation [2-658](#)
- dual IPv4 and IPv6 templates [2-299](#)
- duplex command [2-114](#)
- dynamic-access ports
 - configuring [2-647](#)
 - restrictions [2-648](#)
- dynamic ARP inspection
 - ARP ACLs
 - apply to a VLAN [2-135](#)
 - define [2-20](#)
 - deny packets [2-78](#)
 - display [2-361](#)
 - permit packets [2-297](#)
 - clear
 - log buffer [2-46](#)
 - statistics [2-47](#)
 - display
 - ARP ACLs [2-361](#)
 - configuration and operating state [2-431](#)
 - log buffer [2-431](#)
 - statistics [2-431](#)
 - trust state and rate limit [2-431](#)
 - enable per VLAN [2-145](#)
 - error detection for [2-116](#)
 - error recovery timer [2-118](#)
 - log buffer
 - clear [2-46](#)
 - configure [2-139](#)
 - display [2-431](#)
 - rate-limit incoming ARP packets [2-137](#)
 - statistics
 - clear [2-47](#)
 - display [2-431](#)
 - trusted interface state [2-141](#)
 - type of packet logged [2-146](#)
 - validation checks [2-143](#)
- dynamic auto VLAN membership mode [2-653](#)
- dynamic desirable VLAN membership mode [2-653](#)
- Dynamic Host Configuration Protocol (DHCP)
 - See DHCP snooping
- Dynamic Trunking Protocol
 - See DTP

E

EAP-request/identity frame

- maximum number to send [2-105](#)
- response time before retransmitting [2-112](#)

encapsulation methods [2-673](#)environment variables, displaying [2-366](#)errdisable detect cause command [2-116](#)errdisable recovery command [2-118](#)error conditions, displaying [2-405](#)error disable detection [2-116](#)error-disabled interfaces, displaying [2-417](#)

EtherChannel

- assigning Ethernet interface to channel group [2-37](#)
- creating port-channel logical interface [2-124](#)
- debug EtherChannel/PAGP, display [B-10](#)
- debug platform-specific events, display [B-37](#)
- displaying [2-409](#)
- enabling Layer 2 protocol tunneling for
 - LACP [2-207](#)
 - PAGP [2-207](#)
 - UDLD [2-207](#)

interface information, displaying [2-417](#)

LACP

- clearing channel-group information [2-51](#)
- debug messages, display [B-20](#)
- displaying [2-470](#)
- modes [2-37](#)
- port priority for hot-standby ports [2-210](#)
- restricting a protocol [2-41](#)
- system priority [2-212](#)

load-distribution methods [2-315](#)

EtherChannel (continued)

PAGP

- aggregate-port learner [2-293](#)
- clearing channel-group information [2-55](#)
- debug messages, display [B-28](#)
- displaying [2-519](#)
- error detection for [2-116](#)
- error recovery timer [2-118](#)
- learn method [2-293](#)
- modes [2-37](#)
- physical-port learner [2-293](#)
- priority of interface for transmitted traffic [2-295](#)

Ethernet controller, internal register display [2-379](#)Ethernet statistics, collecting [2-339](#)examples, conventions for [xx](#)exception crashinfo command [2-121](#)exit command [2-710](#)extended discovery of candidate switches [2-64](#)

extended-range VLANs

- and allowed VLAN list [2-673](#)
- and pruning-eligible list [2-673](#)
- configuring [2-695](#)

extended system ID for STP [2-590](#)**F**fan information, displaying [2-400](#)file name, VTP [2-721](#)files, deleting [2-77](#)flash_init (boot loader) command [A-9](#)

Flex Links

- configuring [2-649](#)
- displaying [2-417](#)

flowcontrol command [2-122](#)format (boot loader) command [A-10](#)forwarding packets, with ACL matches [2-5](#)forwarding results, display [C-6](#)frame forwarding information, displaying [C-6](#)

front-end controller
 counter and status information [C-8](#)
 fsck (boot loader) command [A-11](#)

G

global configuration mode [1-2, 1-4](#)

H

hardware ACL statistics [2-357](#)
 help (boot loader) command [A-12](#)
 hierarchical policy maps [2-313](#)
 hop-count limit for clusters [2-64](#)
 host connection, port configuration [2-652](#)
 host ports, private VLANs [2-656](#)
 Hot Standby Router Protocol
 See HSRP
 HSRP
 binding HSRP group to cluster [2-72](#)
 standby group [2-72](#)

I

IEEE 802.1Q trunk ports and native VLANs [2-712](#)
 IEEE 802.1Q tunnel ports
 configuring [2-653](#)
 displaying [2-393](#)
 limitations [2-654](#)
 IEEE 802.1x
 and switchport modes [2-654](#)
 violation error recovery [2-118](#)
 See also port-based authentication
 IEEE 802.1X Port Based Authentication
 enabling guest VLAN supplicant [2-91](#)
 IGMP filters
 applying [2-161](#)
 debug messages, display [B-17](#)

IGMP groups, setting maximum [2-162](#)
 IGMP maximum groups, debugging [B-18](#)
 IGMP profiles
 creating [2-164](#)
 displaying [2-439](#)
 IGMP snooping
 adding ports as a static member of a group [2-180](#)
 displaying [2-440, 2-445, 2-447](#)
 enabling [2-166](#)
 enabling the configurable-leave timer [2-168](#)
 enabling the Immediate-Leave feature [2-177](#)
 flooding query count [2-174](#)
 interface topology change notification behavior [2-176](#)
 multicast table [1-6, 2-443](#)
 querier [2-170](#)
 query solicitation [2-174](#)
 report suppression [2-172](#)
 switch topology change notification behavior [2-174](#)
 images
 See software images
 Immediate-Leave feature, MVR [2-290](#)
 Immediate-Leave processing
 IPv6 [2-202](#)
 immediate-leave processing [2-177](#)
 initial configuration
 See getting started guide and hardware installation guide
 interface configuration mode [1-2, 1-4](#)
 interface port-channel command [2-124](#)
 interface range command [2-126](#)
 interface-range macros [2-75](#)
 interfaces
 assigning Ethernet interface to channel group [2-37](#)
 configuring [2-114](#)
 configuring multiple [2-126](#)
 creating port-channel logical [2-124](#)
 debug messages, display [B-15](#)
 disabling [2-569](#)
 displaying the MAC address table [2-486](#)
 restarting [2-569](#)

- interface speed, configuring [2-627](#)
- interface vlan command [2-128](#)
- internal registers, displaying [2-379, 2-389](#)
- Internet Group Management Protocol
 - See IGMP
- invalid GBIC
 - error detection for [2-116](#)
 - error recovery timer [2-118](#)
- ip access-group command [2-130](#)
- ip address command [2-133](#)
- IP addresses, setting [2-133](#)
- IP address matching [2-239](#)
- ip arp inspection filter vlan command [2-135](#)
- ip arp inspection limit command [2-137](#)
- ip arp inspection log-buffer command [2-139](#)
- ip arp inspection trust command [2-141](#)
- ip arp inspection validate command [2-143](#)
- ip arp inspection vlan command [2-145](#)
- ip arp inspection vlan logging command [2-146](#)
- IP DHCP snooping
 - See DHCP snooping
- ip dhcp snooping binding command [2-149](#)
- ip dhcp snooping command [2-148](#)
- ip dhcp snooping database command [2-151](#)
- ip dhcp snooping information option allow-untrusted command [2-155](#)
- ip dhcp snooping information option command [2-153](#)
- ip dhcp snooping limit rate command [2-157](#)
- ip dhcp snooping trust command [2-158](#)
- ip dhcp snooping verify command [2-159](#)
- ip dhcp snooping vlan command [2-160](#)
- ip igmp filter command [2-161](#)
- ip igmp max-groups command [2-162](#)
- ip igmp profile command [2-164](#)
- ip igmp snooping command [2-166](#)
- ip igmp snooping last-member-query-interval command [2-168](#)
- ip igmp snooping querier command [2-170](#)
- ip igmp snooping report-suppression command [2-172](#)
- ip igmp snooping tcn command [2-174](#)
- ip igmp snooping tcn flood command [2-176](#)
- ip igmp snooping vlan immediate-leave command [2-177](#)
- ip igmp snooping vlan mrouter command [2-178](#)
- ip igmp snooping vlan static command [2-180](#)
- IP multicast addresses [2-287](#)
- IP phones
 - auto-QoS configuration [2-22](#)
 - trusting packets sent from [2-279](#)
- IP-precedence-to-DSCP map [2-253](#)
- ip snap forwarding command [2-182](#)
- ip source binding command [2-183](#)
- IP source guard
 - disabling [2-187](#)
 - displaying
 - binding entries [2-449](#)
 - configuration [2-451](#)
 - dynamic binding entries only [2-435](#)
 - enabling [2-187](#)
 - static IP source bindings [2-183](#)
- ip ssh command [2-185](#)
- IPv6 access list
 - deny conditions [2-80](#)
- ipv6 access-list command [2-188](#)
- ipv6 mld snooping command [2-190](#)
- ipv6 mld snooping last-listener-query count command [2-192](#)
- ipv6 mld snooping last-listener-query-interval command [2-194](#)
- ipv6 mld snooping listener-message-suppression command [2-196](#)
- ipv6 mld snooping robustness-variable command [2-198](#)
- ipv6 mld snooping tcn command [2-200](#)
- ipv6 mld snooping vlan command [2-202](#)
- IPv6 SDM template [2-340](#)
- ipv6 traffic-filter command [2-204](#)
- ip verify source command [2-187](#)

J

jumbo frames

See MTU

L

l2protocol-tunnel command [2-206](#)

l2protocol-tunnel cos command [2-209](#)

LACP

See EtherChannel

lacp port-priority command [2-210](#)

lacp system-priority command [2-212](#)

Layer 2 mode, enabling [2-645](#)

Layer 2 protocol ports, displaying [2-467](#)

Layer 2 protocol-tunnel

error detection for [2-116](#)

error recovery timer [2-118](#)

Layer 2 protocol tunnel counters [2-50](#)

Layer 2 protocol tunneling error recovery [2-207](#)

Layer 2 traceroute

IP addresses [2-686](#)

MAC addresses [2-683](#)

Layer 3 mode, enabling [2-645](#)

line configuration mode [1-3, 1-5](#)

Link Aggregation Control Protocol

See EtherChannel

link flap

error detection for [2-116](#)

error recovery timer [2-118](#)

load_helper (boot loader) command [A-13](#)

load-distribution methods for EtherChannel [2-315](#)

logging event power-inline-status command [2-214](#)

logging file command [2-215](#)

logical interface [2-124](#)

loopback error

detection for [2-116](#)

recovery timer [2-118](#)

loop guard, for spanning tree [2-592, 2-596](#)

M

mac access-group command [2-217](#)

MAC access-groups, displaying [2-474](#)

MAC access list configuration mode [2-219](#)

mac access-list extended command [2-219](#)

MAC access lists [2-85](#)

MAC addresses

displaying

aging time [2-480](#)

all [2-478](#)

dynamic [2-484](#)

MAC address-table move updates [2-488](#)

notification settings [2-490](#)

number of addresses in a VLAN [2-482](#)

per interface [2-486](#)

per VLAN [2-494](#)

static [2-492](#)

static and dynamic entries [2-476](#)

dynamic

aging time [2-221](#)

deleting [2-52](#)

displaying [2-484](#)

enabling MAC address notification [2-224](#)

enabling MAC address-table move update [2-222](#)

matching [2-239](#)

persistent stack [2-635](#)

static

adding and removing [2-226](#)

displaying [2-492](#)

dropping on an interface [2-227](#)

tables [2-478](#)

MAC address notification, debugging [B-21](#)

mac address-table aging-time [2-217, 2-239](#)

mac address-table aging-time command [2-221](#)

mac address-table move update command [2-222](#)

mac address-table notification command [2-224](#)

mac address-table static command [2-226](#)

mac address-table static drop command [2-227](#)

- macro apply command [2-229](#)
- macro description command [2-232](#)
- macro global command [2-233](#)
- macro global description command [2-236](#)
- macro name command [2-237](#)
- macros
 - adding a description [2-232](#)
 - adding a global description [2-236](#)
 - applying [2-233](#)
 - creating [2-237](#)
 - displaying [2-521](#)
 - interface range [2-75, 2-126](#)
 - specifying parameter values [2-233](#)
 - tracing [2-233](#)
- manual
 - audience [xix](#)
 - purpose of [xix](#)
- maps
 - QoS
 - defining [2-253](#)
 - displaying [2-504](#)
 - VLAN
 - creating [2-707](#)
 - defining [2-239](#)
 - displaying [2-559](#)
- match (access-map configuration) command [2-239](#)
- match (class-map configuration) command [2-241](#)
- maximum transmission unit
 - See MTU
- mdix auto command [2-243](#)
- MDL snooping
 - displaying [2-461](#)
- member switches
 - See clusters
- memory (boot loader) command [A-14](#)
- mkdir (boot loader) command [A-16](#)
- MLD snooping
 - configuring [2-196, 2-198](#)
 - configuring queries [2-192, 2-194](#)
 - configuring topology change notification [2-200](#)
 - displaying [2-459, 2-463, 2-465](#)
 - enabling [2-190](#)
- MLD snooping on a VLAN
 - enabling [2-202](#)
- mls qos aggregate-policer command [2-247](#)
- mls qos command [2-245](#)
- mls qos cos command [2-249](#)
- mls qos dscp-mutation command [2-251](#)
- mls qos map command [2-253](#)
- mls qos queue-set output buffers command [2-257](#)
- mls qos queue-set output threshold command [2-259](#)
- mls qos rewrite ip dscp command [2-261](#)
- mls qos srr-queue input bandwidth command [2-263](#)
- mls qos srr-queue input buffers command [2-265](#)
- mls qos srr-queue input cos-map command [2-267](#)
- mls qos srr-queue input dscp-map command [2-269](#)
- mls qos srr-queue input priority-queue command [2-271](#)
- mls qos srr-queue input threshold command [2-273](#)
- mls qos srr-queue output cos-map command [2-275](#)
- mls qos srr-queue output dscp-map command [2-277](#)
- mls qos trust command [2-279](#)
- mls qos vlan-based command [2-281](#)
- mode, MVR [2-287](#)
- Mode button, and password recovery [2-344](#)
- modes, commands [1-2](#)
- monitor session command [2-282](#)
- more (boot loader) command [A-17](#)
- MSTP
 - displaying [2-538](#)
 - interoperability [2-59](#)
 - link type [2-594](#)

MSTP (continued)

MST region

- aborting changes [2-600](#)
- applying changes [2-600](#)
- configuration name [2-600](#)
- configuration revision number [2-600](#)
- current or pending display [2-600](#)
- displaying [2-538](#)
- MST configuration mode [2-600](#)
- VLANs-to-instance mapping [2-600](#)

path cost [2-602](#)protocol mode [2-598](#)restart protocol migration process [2-59](#)

root port

- loop guard [2-592](#)
- preventing from becoming designated [2-592](#)
- restricting which can be root [2-592](#)
- root guard [2-592](#)

root switch

- affects of extended system ID [2-590](#)
- hello-time [2-605, 2-613](#)
- interval between BPDU messages [2-606](#)
- interval between hello BPDU messages [2-605, 2-613](#)
- max-age [2-606](#)
- maximum hop count before discarding BPDU [2-607](#)
- port priority for selection of [2-609](#)
- primary or secondary [2-613](#)
- switch priority [2-612](#)

state changes

- blocking to forwarding state [2-619](#)
- enabling BPDU filtering [2-582, 2-617](#)
- enabling BPDU guard [2-584, 2-617](#)
- enabling Port Fast [2-617, 2-619](#)
- forward-delay time [2-604](#)
- length of listening and learning states [2-604](#)
- rapid transition to forwarding [2-594](#)
- shutting down Port Fast-enabled ports [2-617](#)

state information display [2-537](#)

MTU

- configuring size [2-680](#)
- displaying global setting [2-548](#)

Multicast Listener Discovery

See MLD

multicast group address, MVR [2-290](#)multicast groups, MVR [2-288](#)

Multicast Listener Discovery

See MLD

multicast router learning method [2-178](#)

multicast router ports

IPv6 [2-202](#)multicast router ports, configuring [2-178](#)multicast storm control [2-637](#)multicast VLAN, MVR [2-287](#)

multicast VLAN registration

See MVR

multiple hosts on authorized port [2-101](#)

Multiple Spanning Tree Protocol

See MSTP

MVR

- and address aliasing [2-288](#)
- configuring [2-287](#)
- configuring interfaces [2-290](#)
- debug messages, display [B-26](#)
- displaying [2-513](#)
- displaying interface information [2-515](#)
- members, displaying [2-517](#)

mvr (global configuration) command [2-287](#)mvr (interface configuration) command [2-290](#)mvr vlan group command [2-291](#)

N

native VLANs [2-673](#)
 native VLAN tagging [2-712](#)
 Network Assistant requirements **xx**
 nonegotiate
 DTP messaging [2-658](#)
 nonegotiate, speed [2-627](#)
 non-IP protocols
 denying [2-85](#)
 forwarding [2-305](#)
 non-IP traffic access lists [2-219](#)
 non-IP traffic forwarding
 denying [2-85](#)
 permitting [2-305](#)
 normal-range VLANs [2-695, 2-701](#)
 note, description **xx**
 no vlan command [2-695, 2-705](#)

P

PAgP
 See EtherChannel
 pagp learn-method command [2-293](#)
 pagp port-priority command [2-295](#)
 password, VTP [2-721, 2-725](#)
 password-recovery mechanism, enabling and
 disabling [2-344](#)
 permit (ARP access-list configuration) command [2-297](#)
 permit (IPv6) command [2-299](#)
 permit (MAC access-list configuration) command [2-305](#)
 per-VLAN spanning-tree plus
 See STP
 physical-port learner [2-293](#)
 PID, displaying [2-430](#)
 PIM-DVMRP, as multicast router learning method [2-178](#)

PoE

 configuring the power budget [2-320](#)
 configuring the power management mode [2-317](#)
 displaying controller register values [2-387](#)
 displaying power management information [2-529](#)
 logging of status [2-214](#)
 police aggregate command [2-310](#)
 police command [2-308](#)
 policed-DSCP map [2-253](#)
 policy-map command [2-312](#)
 policy maps
 applying to an interface [2-346, 2-352](#)
 creating [2-312](#)
 displaying [2-524](#)
 hierarchical [2-313](#)
 policers
 displaying [2-497](#)
 for a single class [2-308](#)
 for multiple classes [2-247, 2-310](#)
 policed-DSCP map [2-253](#)
 traffic classification
 defining the class [2-42](#)
 defining trust states [2-688](#)
 setting DSCP or IP precedence values [2-350](#)

Port Aggregation Protocol
 See EtherChannel
 port-based authentication
 AAA method list [2-3](#)
 debug messages, display [B-7](#)
 enabling IEEE 802.1x
 globally [2-88](#)
 per interface [2-107](#)
 guest VLAN [2-99](#)
 host modes [2-101](#)
 IEEE 802.1x AAA accounting methods [2-1](#)
 initialize an interface [2-103](#)
 manual control of authorization state [2-107](#)

- port-based authentication (continued)
 - multiple hosts on authorized port [2-101](#)
 - periodic re-authentication
 - enabling [2-111](#)
 - time between attempts [2-112](#)
 - quiet period between failed authentication exchanges [2-112](#)
 - re-authenticating IEEE 802.1x-enabled ports [2-109](#)
 - resetting configurable IEEE 802.1x parameters [2-98](#)
 - switch-to-authentication server retransmission time [2-112](#)
 - switch-to-client frame-retransmission number [2-104 to 2-105](#)
 - switch-to-client retransmission time [2-112](#)
 - port-channel load-balance command [2-315](#)
 - Port Fast, for spanning tree [2-619](#)
 - port ranges, defining [2-75](#)
 - ports, debugging [B-75](#)
 - ports, protected [2-671](#)
 - port security
 - aging [2-665](#)
 - debug messages, display [B-77](#)
 - enabling [2-660](#)
 - violation error recovery [2-118](#)
 - port trust states for QoS [2-279](#)
 - port types, MVR [2-290](#)
 - power information, displaying [2-400](#)
 - power inline command [2-317](#)
 - power inline consumption command [2-320](#)
 - Power over Ethernet
 - See PoE
 - priority-queue command [2-322](#)
 - priority value, stack member [2-545, 2-640](#)
 - private-vlan command [2-324](#)
 - private-vlan mapping command [2-327](#)
 - private VLANs
 - association [2-669](#)
 - configuring [2-324](#)
 - configuring ports [2-656](#)
 - displaying [2-554](#)
 - host ports [2-656](#)
 - mapping
 - configuring [2-669](#)
 - displaying [2-417](#)
 - promiscuous ports [2-656](#)
 - privileged EXEC mode [1-2, 1-3](#)
 - product identification information, displaying [2-430](#)
 - promiscuous ports, private VLANs [2-656](#)
 - protected ports, displaying [2-423](#)
 - pruning
 - VLANs [2-673](#)
 - VTP
 - displaying interface information [2-417](#)
 - enabling [2-721, 2-725](#)
 - pruning-eligible VLAN list [2-675](#)
 - PVST+
 - See STP
-
- ## Q
- QoS
 - auto-QoS
 - configuring [2-22](#)
 - debug messages, display [1-6, B-2](#)
 - displaying [2-362](#)
 - class maps
 - creating [2-44](#)
 - defining the match criteria [2-241](#)
 - displaying [2-370](#)
 - defining the CoS value for an incoming packet [2-249](#)
 - displaying configuration information [2-362, 2-496](#)

QoS (continued)

- DSCP transparency [2-261](#)
- DSCP trusted ports
 - applying DSCP-to-DSCP-mutation map to [2-251](#)
 - defining DSCP-to-DSCP-mutation map [2-253](#)
- egress queues
 - allocating buffers [2-257](#)
 - defining the CoS output queue threshold map [2-275](#)
 - defining the DSCP output queue threshold map [2-277](#)
 - displaying buffer allocations [2-500](#)
 - displaying CoS output queue threshold map [2-504](#)
 - displaying DSCP output queue threshold map [2-504](#)
 - displaying queueing strategy [2-500](#)
 - displaying queue-set settings [2-507](#)
 - enabling bandwidth shaping and scheduling [2-631](#)
 - enabling bandwidth sharing and scheduling [2-633](#)
 - limiting the maximum output on a port [2-629](#)
 - mapping a port to a queue-set [2-329](#)
 - mapping CoS values to a queue and threshold [2-275](#)
 - mapping DSCP values to a queue and threshold [2-277](#)
 - setting maximum and reserved memory allocations [2-259](#)
 - setting WTD thresholds [2-259](#)
- enabling [2-245](#)
- ingress queues
 - allocating buffers [2-265](#)
 - assigning SRR scheduling weights [2-263](#)
 - defining the CoS input queue threshold map [2-267](#)
 - defining the DSCP input queue threshold map [2-269](#)
 - displaying buffer allocations [2-500](#)
 - displaying CoS input queue threshold map [2-504](#)
 - displaying DSCP input queue threshold map [2-504](#)
 - displaying queueing strategy [2-500](#)
 - displaying settings for [2-498](#)
 - enabling the priority queue [2-271](#)
 - mapping CoS values to a queue and threshold [2-267](#)
 - mapping DSCP values to a queue and threshold [2-269](#)
 - setting WTD thresholds [2-273](#)

QoS (continued)

- maps
 - defining [2-253, 2-267, 2-269, 2-275, 2-277](#)
 - displaying [2-504](#)
- policy maps
 - applying an aggregate policer [2-310](#)
 - applying to an interface [2-346, 2-352](#)
 - creating [2-312](#)
 - defining policers [2-247, 2-308](#)
 - displaying policers [2-497](#)
 - displaying policy maps [2-524](#)
 - hierarchical [2-313](#)
 - policed-DSCP map [2-253](#)
 - setting DSCP or IP precedence values [2-350](#)
 - traffic classifications [2-42](#)
 - trust states [2-688](#)
- port trust states [2-279](#)
- queues, enabling the expedite [2-322](#)
- statistics
 - in-profile and out-of-profile packets [2-500](#)
 - packets enqueued or dropped [2-500](#)
 - sent and received CoS values [2-500](#)
 - sent and received DSCP values [2-500](#)
- trusted boundary for IP phones [2-279](#)
- VLAN-based [2-281](#)
- quality of service
 - See QoS
- querytime, MVR [2-287](#)
- queue-set command [2-329](#)

R

rapid per-VLAN spanning-tree plus
 See STP

rapid PVST+
 See STP

rcommand command [2-330](#)

re-authenticating IEEE 802.1x-enabled ports [2-109](#)

re-authentication
 periodic [2-111](#)
 time between attempts [2-112](#)

receiver ports, MVR [2-290](#)

receiving flow-control packets [2-122](#)

recovery mechanism
 causes [2-118](#)
 display [2-368, 2-403, 2-407](#)
 timer interval [2-119](#)

redundancy for cluster switches [2-72](#)

reload command [2-332](#)

remote command [2-334](#)

remote-span command [2-335](#)

Remote Switched Port Analyzer
 See RSPAN

rename (boot loader) command [A-18](#)

renew ip dhcp snooping database command [2-337](#)

requirements
 cluster [xxi](#)
 device manager [xx](#)
 Network Assistant [xx](#)

reset (boot loader) command [A-19](#)

reset command [2-710](#)

resource templates, displaying [2-532](#)

restricted VLAN
 See dot1x auth-fail vlan

rmdir (boot loader) command [A-20](#)

rmon collection stats command [2-339](#)

root guard, for spanning tree [2-592](#)

routed ports
 IP addresses on [2-134](#)
 number supported [2-134](#)

RSPAN
 configuring [2-282](#)
 displaying [2-510](#)
 filter RSPAN traffic [2-282](#)
 remote-span command [2-335](#)
 sessions
 add interfaces to [2-282](#)
 displaying [2-510](#)
 start new [2-282](#)

S

SDM mismatch mode [2-341, 2-546](#)

sdm prefer command [2-340](#)

SDM templates
 allowed resources [2-341](#)
 and stacking [2-341](#)
 displaying [2-532](#)
 dual IPv4 and IPv6 [2-340](#)

secure ports, limitations [2-662](#)

sending flow-control packets [2-122](#)

service password-recovery command [2-344](#)

service-policy command [2-346](#)

session command [2-349](#)

set (boot loader) command [A-21](#)

set command [2-350](#)

setup command [2-352](#)

setup express command [2-355](#)

show access-lists command [2-357](#)

show archive status command [2-360](#)

show arp access-list command [2-361](#)

show auto qos command [2-362](#)

show boot command [2-366](#)

show cable-diagnostics tdr command [2-368](#)

show changes command [2-710](#)

show class-map command [2-370](#)

- show cluster candidates command [2-373](#)
- show cluster command [2-371](#)
- show cluster members command [2-375](#)
- show controllers cpu-interface command [2-377](#)
- show controllers ethernet-controller command [2-379](#)
- show controllers power inline command [2-387](#)
- show controllers team command [2-389](#)
- show controller utilization command [2-391](#)
- show current command [2-710](#)
- show dot1q-tunnel command [2-393](#)
- show dot1x command [2-394](#)
- show dtp [2-398](#)
- show env command [2-400](#)
- show errdisable detect command [2-403](#)
- show errdisable flap-values command [2-405](#)
- show errdisable recovery command [2-407](#)
- show etherchannel command [2-409](#)
- show flowcontrol command [2-412](#)
- show idprom command [2-414](#)
- show interfaces command [2-417](#)
- show interfaces counters command [2-427](#)
- show inventory command [2-430](#)
- show ip arp inspection command [2-431](#)
- show ipc command [2-453](#)
- show ip dhcp snooping binding command [2-435](#)
- show ip dhcp snooping command [2-434](#)
- show ip dhcp snooping database command [2-437](#)
- show ip igmp profile command [2-439](#)
- show ip igmp snooping address command [2-461](#)
- show ip igmp snooping command [2-440, 2-459](#)
- show ip igmp snooping groups command [2-443](#)
- show ip igmp snooping mrouter command [2-445, 2-463](#)
- show ip igmp snooping querier command [2-447, 2-465](#)
- show ip source binding command [2-449](#)
- show ipv6 access-list command [2-457](#)
- show ip verify source command [2-451](#)
- show l2protocol-tunnel command [2-467](#)
- show lacp command [2-470](#)
- show mac access-group command [2-474](#)
- show mac address-table address command [2-478](#)
- show mac address-table aging time command [2-480](#)
- show mac address-table command [2-476](#)
- show mac address-table count command [2-482](#)
- show mac address-table dynamic command [2-484](#)
- show mac address-table interface command [2-486](#)
- show mac address-table move update command [2-488](#)
- show mac address-table notification command [2-54, 2-490, B-23](#)
- show mac address-table static command [2-492](#)
- show mac address-table vlan command [2-494](#)
- show mls qos aggregate-policer command [2-497](#)
- show mls qos command [2-496](#)
- show mls qos input-queue command [2-498](#)
- show mls qos interface command [2-500](#)
- show mls qos maps command [2-504](#)
- show mls qos queue-set command [2-507](#)
- show mls qos vlan command [2-509](#)
- show monitor command [2-510](#)
- show mvr command [2-513](#)
- show mvr interface command [2-515](#)
- show mvr members command [2-517](#)
- show pagp command [2-519](#)
- show parser macro command [2-521](#)
- show platform acl command [C-2](#)
- show platform backup interface command [C-3](#)
- show platform configuration command [C-4](#)
- show platform etherchannel command [C-5](#)
- show platform forward command [C-6](#)
- show platform frontend-controller command [C-8](#)
- show platform igmp snooping command [C-9](#)
- show platform ipc trace command [C-16](#)
- show platform ip multicast command [C-11](#)
- show platform ip unicast command [C-12](#)
- show platform ipv6 unicast command [C-17](#)
- show platform layer4op command [C-19](#)
- show platform mac-address-table command [C-20](#)
- show platform messaging command [C-21](#)
- show platform monitor command [C-22](#)

- show platform mvr table command [C-23](#)
- show platform pm command [C-24](#)
- show platform port-asic command [C-25](#)
- show platform port-security command [C-31](#)
- show platform qos command [C-32](#)
- show platform resource-manager command [C-33](#)
- show platform snmp counters command [C-35](#)
- show platform spanning-tree command [C-36](#)
- show platform stack-manager command [C-38](#)
- show platform stp-instance command [C-37](#)
- show platform tb command [C-40](#)
- show platform team command [C-42](#)
- show platform vlan command [C-45](#)
- show policy-map command [2-524](#)
- show port security command [2-526](#)
- show power inline command [2-529](#)
- show proposed command [2-710](#)
- show sdm prefer command [2-532](#)
- show setup express command [2-536](#)
- show spanning-tree command [2-537](#)
- show storm-control command [2-543](#)
- show switch command [2-545](#)
- show system mtu command [2-548](#)
- show trust command [2-688](#)
- show udd command [2-549](#)
- show version command [2-552](#)
- show vlan access-map command [2-559](#)
- show vlan command [2-554](#)
- show vlan command, fields [2-556](#)
- show vlan filter command [2-560](#)
- show vmps command [2-561](#)
- show vtp command [2-564](#)
- shutdown command [2-569](#)
- shutdown threshold, Layer 2 protocol tunneling [2-206](#)
- shutdown vlan command [2-570](#)
- Smartports macros
 - See macros
- SNMP host, specifying [2-575](#)
- SNMP informs, enabling the sending of [2-571](#)
- snmp-server enable traps command [2-571](#)
- snmp-server host command [2-575](#)
- snmp trap mac-notification command [2-579](#)
- SNMP traps
 - enabling MAC address notification trap [2-579](#)
 - enabling the MAC address notification feature [2-224](#)
 - enabling the sending of [2-571](#)
- SoftPhone
 - See Cisco SoftPhone
- software images
 - copying [2-7](#)
 - deleting [2-77](#)
 - downloading [2-10](#)
 - upgrading [2-7, 2-10](#)
 - uploading [2-18](#)
- software version, displaying [2-552](#)
- source ports, MVR [2-290](#)
- SPAN
 - configuring [2-282](#)
 - debug messages, display [B-24](#)
 - displaying [2-510](#)
 - filter SPAN traffic [2-282](#)
 - sessions
 - add interfaces to [2-282](#)
 - displaying [2-510](#)
 - start new [2-282](#)
- spanning [2-621](#)
- spanning-tree backbonefast command [2-581](#)
- spanning-tree bpdudfilter command [2-582](#)
- spanning-tree bpduguard command [2-584](#)
- spanning-tree cost command [2-586](#)
- spanning-tree etherchannel command [2-588](#)
- spanning-tree extend system-id command [2-590](#)
- spanning-tree guard command [2-592](#)
- spanning-tree link-type command [2-594](#)
- spanning-tree loopguard default command [2-596](#)
- spanning-tree mode command [2-598](#)
- spanning-tree mst configuration command [2-600](#)
- spanning-tree mst cost command [2-602](#)

- spanning-tree mst forward-time command [2-604](#)
- spanning-tree mst hello-time command [2-605](#)
- spanning-tree mst max-age command [2-606](#)
- spanning-tree mst max-hops command [2-607](#)
- spanning-tree mst port-priority command [2-609](#)
- spanning-tree mst pre-standard command [2-611](#)
- spanning-tree mst priority command [2-612](#)
- spanning-tree mst root command [2-613](#)
- spanning-tree portfast (global configuration) command [2-617](#)
- spanning-tree portfast (interface configuration) command [2-619](#)
- spanning-tree port-priority command [2-615](#)
- Spanning Tree Protocol
 - See STP
- spanning-tree transmit hold-count command [2-621](#)
- spanning-tree uplinkfast command [2-622](#)
- spanning-tree vlan command [2-624](#)
- speed command [2-627](#)
- srr-queue bandwidth limit command [2-629](#)
- srr-queue bandwidth shape command [2-631](#)
- srr-queue bandwidth share command [2-633](#)
- SSH, configuring version [2-185](#)
- stack-mac persistent timer command [2-635](#)
- stack member
 - access [2-349](#)
 - number [2-545, 2-643](#)
 - priority value [2-640](#)
 - provisioning [2-641](#)
 - reloading [2-332](#)
- stacks, switch
 - MAC address [2-635](#)
 - provisioning a new member [2-641](#)
 - reloading [2-332](#)
 - stack member access [2-349](#)
 - stack member number [2-545, 2-643](#)
 - stack member priority value [2-545, 2-640](#)
- static-access ports, configuring [2-647](#)
- statistics, Ethernet group [2-339](#)
- sticky learning, enabling [2-660](#)
- storm-control command [2-637](#)
- STP
 - BackboneFast [2-581](#)
 - counters, clearing [2-58](#)
 - debug messages, display
 - BackboneFast events [B-81](#)
 - MSTP [B-84](#)
 - optimized BPDUs handling [B-83](#)
 - spanning-tree activity [B-79](#)
 - switch shim [B-86](#)
 - transmitted and received BPDUs [B-82](#)
 - UplinkFast [B-88](#)
 - detection of indirect link failures [2-581](#)
 - enabling protocol tunneling for [2-206](#)
 - EtherChannel misconfiguration [2-588](#)
 - extended system ID [2-590](#)
 - path cost [2-586](#)
 - protocol modes [2-598](#)
 - root port
 - accelerating choice of new [2-622](#)
 - loop guard [2-592](#)
 - preventing from becoming designated [2-592](#)
 - restricting which can be root [2-592](#)
 - root guard [2-592](#)
 - UplinkFast [2-622](#)
- root switch
 - affects of extended system ID [2-590, 2-625](#)
 - hello-time [2-624](#)
 - interval between BPDU messages [2-624](#)
 - interval between hello BPDU messages [2-624](#)
 - max-age [2-624](#)
 - port priority for selection of [2-615](#)
 - primary or secondary [2-624](#)
 - switch priority [2-624](#)

- STP (continued)
 - state changes
 - blocking to forwarding state [2-619](#)
 - enabling BPDU filtering [2-582, 2-617](#)
 - enabling BPDU guard [2-584, 2-617](#)
 - enabling Port Fast [2-617, 2-619](#)
 - enabling timer to recover from error state [2-118](#)
 - forward-delay time [2-624](#)
 - length of listening and learning states [2-624](#)
 - shutting down Port Fast-enabled ports [2-617](#)
 - state information display [2-537](#)
 - VLAN options [2-612, 2-624](#)
 - SVIs, creating [2-128](#)
 - Switched Port Analyzer
 - See SPAN
 - switching characteristics
 - modifying [2-645](#)
 - returning to interfaces [2-645](#)
 - switchport access command [2-647](#)
 - switchport backup interface command [2-649](#)
 - switchport block command [2-651](#)
 - switchport command [2-645](#)
 - switchport host command [2-652](#)
 - switchport mode command [2-653](#)
 - switchport mode private-vlan command [2-656](#)
 - switchport nonegotiate command [2-658](#)
 - switchport port-security aging command [2-665](#)
 - switchport port-security command [2-660](#)
 - switchport priority extend command [2-667](#)
 - switchport private-vlan command [2-669](#)
 - switchport protected command [2-671](#)
 - switchports, displaying [2-417](#)
 - switchport trunk command [2-673](#)
 - switchport voice vlan command [2-676](#)
 - switch priority command [2-640](#)
 - switch provision command [2-641](#)
 - switch renumber command [2-643](#)
 - system env temperature threshold yellow command [2-678](#)
 - system message logging [2-214](#)
 - system message logging, save message to flash [2-215](#)
 - system mtu command [2-680](#)
 - system resource templates [2-340](#)
-
- ## T
- tar files, creating, listing, and extracting [2-15](#)
 - TDR, running [2-682](#)
 - Telnet, using to communicate to cluster switches [2-330](#)
 - temperature information, displaying [2-400](#)
 - templates, system resources [2-340](#)
 - test cable-diagnostics tdr command [2-682](#)
 - traceroute mac command [2-683](#)
 - traceroute mac ip command [2-686](#)
 - trunking, VLAN mode [2-653](#)
 - trunk mode [2-653](#)
 - trunk ports [2-653](#)
 - trunks, to non-DTP device [2-654](#)
 - trusted boundary for QoS [2-279](#)
 - trusted port states for QoS [2-279](#)
 - tunnel ports, Layer 2 protocol, displaying [2-467](#)
 - type (boot loader) command [A-24](#)
-
- ## U
- UDLD
 - aggressive mode [2-690, 2-692](#)
 - debug messages, display [B-97](#)
 - enable globally [2-690](#)
 - enable per interface [2-692](#)
 - error recovery timer [2-118](#)
 - message timer [2-690](#)
 - normal mode [2-690, 2-692](#)
 - reset a shutdown interface [2-694](#)
 - status [2-549](#)
 - udld command [2-690](#)
 - udld port command [2-692](#)
 - udld reset command [2-694](#)

unicast storm control [2-637](#)

UniDirectional Link Detection

See UDLD

unknown multicast traffic, preventing [2-651](#)

unknown unicast traffic, preventing [2-651](#)

unset (boot loader) command [A-25](#)

upgrading

software images [2-7, 2-10](#)

monitoring status of [2-360](#)

upgrading information

See release notes

UplinkFast, for STP [2-622](#)

user EXEC mode [1-2, 1-3](#)

V

version (boot loader) command [A-27](#)

version mismatch mode [2-546](#)

VLAN

enabling guest VLAN supplicant [2-91](#)

vlan (global configuration) command [2-695](#)

vlan (VLAN configuration) command [2-701](#)

vlan access-map command [2-707](#)

VLAN access map configuration mode [2-707](#)

VLAN access maps

actions [2-5](#)

displaying [2-559](#)

VLAN-based QoS [2-281](#)

VLAN configuration

rules [2-698, 2-703](#)

saving [2-695, 2-705](#)

VLAN configuration mode

commands

VLAN [2-701](#)

VTP [2-725](#)

description [1-5](#)

entering [2-709](#)

summary [1-3](#)

vlan database command [2-709](#)

vlan dot1q tag native command [2-712](#)

vlan filter command [2-714](#)

VLAN filters, displaying [2-560](#)

VLAN ID range [2-695, 2-701](#)

VLAN maps

applying [2-714](#)

creating [2-707](#)

defining [2-239](#)

displaying [2-559](#)

VLAN Query Protocol

See VQP

VLANs

adding [2-695](#)

configuring [2-695, 2-701](#)

debug messages, display

ISL [B-93](#)

VLAN IOS file system error tests [B-91](#)

VLAN manager activity [B-89](#)

VTP [B-95](#)

displaying configurations [2-554](#)

extended-range [2-695](#)

MAC addresses

displaying [2-494](#)

number of [2-482](#)

media types [2-698, 2-703](#)

normal-range [2-695, 2-701](#)

private [2-656](#)

configuring [2-324](#)

displaying [2-554](#)

See also private VLANs

restarting [2-570](#)

saving the configuration [2-695](#)

shutting down [2-570](#)

SNMP traps for VTP [2-573, 2-576](#)

suspending [2-570](#)

variables [2-701](#)

VLAN Trunking Protocol

See VTP

VM mode [2-546](#)

VMPS

- configuring servers [2-719](#)
- displaying [2-561](#)
- error recovery timer [2-119](#)
- reconfirming dynamic VLAN assignments [2-716](#)
- vmmps reconfirm (global configuration) command [2-717](#)
- vmmps reconfirm (privileged EXEC) command [2-716](#)
- vmmps retry command [2-718](#)
- vmmps server command [2-719](#)
- voice VLAN
 - configuring [2-676](#)
 - setting port priority [2-667](#)

VQP

- and dynamic-access ports [2-648](#)
- clearing client statistics [2-60](#)
- displaying information [2-561](#)
- per-server retry count [2-718](#)
- reconfirmation interval [2-717](#)
- reconfirming dynamic VLAN assignments [2-716](#)

VTP

- changing characteristics [2-721](#)
- clearing pruning counters [2-61](#)
- configuring
 - domain name [2-721, 2-725](#)
 - file name [2-721](#)
 - mode [2-721, 2-725](#)
 - password [2-721, 2-725](#)
- counters display fields [2-565](#)
- displaying information [2-564](#)
- enabling
 - pruning [2-721, 2-725](#)
 - tunneling for [2-206](#)
 - Version 2 [2-721, 2-725](#)
- mode [2-721, 2-725](#)
- pruning [2-721, 2-725](#)
- saving the configuration [2-695, 2-705](#)
- statistics [2-564](#)
- status [2-564](#)
- status display fields [2-567](#)

- vtp (global configuration) command [2-721](#)
- vtp (VLAN configuration) command [2-725](#)

X

- XENPAK module serial EERPOM information [2-383, 2-414](#)

