



## INDEX

### A

abbreviating commands **2-4**

AC (command switch) **7-9**

access-class command **34-16**

access control entries

    See ACEs

access-denied response, VMPS **15-24**

access groups, applying IPv4 ACLs to interfaces **34-17**

accessing

    clusters, switch **7-12**

    command switches **7-10**

    member switches **7-12**

    switch clusters **7-12**

access lists

    See ACLs

access ports

    in switch clusters **7-8**

access ports, defined **13-2**

accounting

    with 802.1x **12-41**

    with IEEE 802.1x **12-12**

    with RADIUS **11-28**

    with TACACS+ **11-11, 11-17**

ACEs

    and QoS **36-7**

    defined **34-2**

    Ethernet **34-2**

    IP **34-2**

ACLs

    ACEs **34-2**

    any keyword **34-9**

    applying

        time ranges to **34-14**

        to an interface **34-16**

        to QoS **36-7**

    classifying traffic for QoS **36-39**

    comments in **34-15**

    compiling **34-18**

    defined **34-1, 34-5**

    examples of **34-18, 36-39**

    extended IP, configuring for QoS classification **36-40**

    extended IPv4

        creating **34-8**

        matching criteria **34-5**

    hardware and software handling **34-17**

    host keyword **34-10**

    IP

        creating **34-5**

        fragments and QoS guidelines **36-31**

        implicit deny **34-7, 34-11, 34-13**

        implicit masks **34-7**

        matching criteria **34-5**

        undefined **34-17**

    IPv4

        applying to interfaces **34-16**

        creating **34-5**

        matching criteria **34-5**

        named **34-12**

        numbers **34-6**

        terminal lines, setting on **34-16**

        unsupported features **34-4**

- ACLs (continued)
  - MAC extended **34-20, 36-41**
  - matching **34-5, 34-17**
  - monitoring **34-23**
  - named, IPv4 **34-12**
  - number per QoS class map **36-31**
  - QoS **36-7, 36-39**
  - resequencing entries **34-12**
  - standard IP, configuring for QoS classification **36-39**
  - standard IPv4
    - creating **34-7**
    - matching criteria **34-5**
  - support for **1-8**
  - support in hardware **34-17**
  - time ranges **34-14**
  - unsupported features, IPv4 **34-4**
- active link **22-4, 22-5, 22-6**
- active links **22-2**
- active traffic monitoring, IP SLAs **35-1**
- address aliasing **25-2**
- addresses
  - displaying the MAC address table **8-27**
  - dynamic
    - accelerated aging **18-8**
    - changing the aging time **8-21**
    - default aging **18-8**
    - defined **8-19**
    - learning **8-20**
    - removing **8-21**
  - IPv6 **37-2**
  - MAC, discovering **8-27**
  - multicast, STP address management **18-8**
  - static
    - adding and removing **8-23**
    - defined **8-19**
- address resolution **8-27**
- Address Resolution Protocol
  - See ARP
- administrative VLAN
  - REP, configuring **21-8**
  - administrative VLAN, REP **21-8**
  - advertisements
    - CDP **28-1**
    - LLDP **27-1, 27-2**
    - VTP **15-16, 16-3**
  - age timer, REP **21-8**
  - aggregatable global unicast addresses **37-3**
  - aggregated ports
    - See EtherChannel
  - aggregate policers **36-48**
  - aggregate policing **1-10**
  - aging, accelerating **18-8**
  - aging time
    - accelerated
      - for MSTP **19-23**
      - for STP **18-8, 18-21**
    - MAC address table **8-21**
    - maximum
      - for MSTP **19-23, 19-24**
      - for STP **18-21, 18-22**
  - alarm profiles
    - configuring **3-11**
    - creating or modifying **3-10**
  - alarms
    - default configuration **3-4**
    - displaying **3-12**
    - power supply **3-2**
    - temperature **3-2**
  - alarms, RMON **31-3**
  - allowed-VLAN list **15-18**
  - ARP
    - defined **1-5, 8-27**
    - table
      - address resolution **8-27**
      - managing **8-27**
    - associating the temperature alarms to a relay **3-7**
    - attaching an alarm profile to a port **3-11**

attributes, RADIUS  
 vendor-proprietary **11-31**  
 vendor-specific **11-29**

attribute-value pairs **12-11, 12-13, 12-16, 12-25**

authentication  
 local mode with AAA **11-32**  
 NTP associations **8-4**  
 open1x **12-24**  
 RADIUS  
 key **11-21**  
 login **11-23**

TACACS+  
 defined **11-11**  
 key **11-13**  
 login **11-14**  
 See also port-based authentication

authentication compatibility with Catalyst 6000 switches **12-8**

authentication failed VLAN  
 See restricted VLAN

authentication manager  
 CLI commands **12-8**  
 compatibility with older 802.1x CLI commands **12-8 to 12-9**  
 overview **12-7**

authoritative time source, described **8-2**

authorization  
 with RADIUS **11-27**  
 with TACACS+ **11-11, 11-16**

authorized ports with IEEE 802.1x **12-9**

autoconfiguration **4-3**

auto enablement **12-24**

automatic discovery  
 considerations  
 beyond a noncandidate device **7-7**  
 brand new switches **7-8**  
 connectivity **7-4**  
 different VLANs **7-6**  
 management VLANs **7-7**

automatic discovery (continued)  
 non-CDP-capable devices **7-6**  
 noncluster-capable devices **7-6**  
 in switch clusters **7-4**  
 See also CDP

automatic QoS  
 See QoS

automatic recovery, clusters **7-9**  
 See also HSRP

auto-MDIX  
 configuring **13-16**  
 described **13-16**

autonegotiation  
 duplex mode **1-3**  
 interface configuration guidelines **13-13**  
 mismatches **39-7**

autosensing, port speed **1-3**

Auto Smartports macros  
 displaying **14-5**

auxiliary VLAN  
 See voice VLAN

availability, features **1-6**

---

**B**

BackboneFast  
 described **20-5**  
 disabling **20-14**  
 enabling **20-13**  
 support for **1-6**

backup interfaces  
 See Flex Links

backup links **22-2**

banners  
 configuring  
 login **8-18**  
 message-of-the-day login **8-18**

default configuration **8-17**

when displayed **8-17**

Berkeley r-tools replacement **11-44**  
 binding database  
   DHCP snooping  
 See DHCP snooping binding database  
 bindings  
   DHCP snooping database **23-5**  
   IP source guard **23-12**  
 binding table, DHCP snooping  
   See DHCP snooping binding database  
 blocking packets **26-7**  
 booting  
   boot loader, function of **4-2**  
   boot process **4-1**  
   manually **4-17**  
   specific image **4-18**  
 boot loader  
   accessing **4-18**  
   described **4-2**  
   environment variables **4-18**  
   prompt **4-18**  
   trap-door mechanism **4-2**  
 BPDU  
   error-disabled state **20-2**  
   filtering **20-3**  
   RSTP format **19-12**  
 BPDU filtering  
   described **20-3**  
   disabling **20-12**  
   enabling **20-12**  
   support for **1-7**  
 BPDU guard  
   described **20-2**  
   disabling **20-12**  
   enabling **20-11**  
   support for **1-7**  
 bridge protocol data unit  
   See BPDU  
 broadcast storm-control command **26-4**  
 broadcast storms **26-1**

**C**

cables, monitoring for unidirectional links **29-1**  
 candidate switch  
   automatic discovery **7-4**  
   defined **7-3**  
   requirements **7-3**  
   See also command switch, cluster standby group, and member switch  
 Catalyst 6000 switches  
   authentication compatibility **12-8**  
 CA trustpoint  
   configuring **11-40**  
   defined **11-38**  
 CDP  
   and trusted boundary **36-35**  
   automatic discovery in switch clusters **7-4**  
   configuring **28-2**  
   default configuration **28-2**  
   defined with LLDP **27-1**  
   described **28-1**  
   disabling for routing device **28-3 to 28-4**  
   enabling and disabling  
    on an interface **28-4**  
    on a switch **28-3**  
   monitoring **28-5**  
   overview **28-1**  
   support for **1-5**  
   transmission timer and holdtime, setting **28-2**  
   updates **28-2**  
 CGMP  
   as IGMP snooping learning method **25-8**  
   joining multicast group **25-3**  
 CipherSuites **11-39**  
 Cisco 7960 IP Phone **17-1**  
 Cisco Discovery Protocol  
   See CDP  
 Cisco IOS File System  
   See IFS

- Cisco IOS IP Service Level Agreements (SLAs)  
responder **1-4**
- Cisco IOS IP SLAs **35-1**
- Cisco Secure ACS  
attribute-value pairs for downloadable ACLs **12-16**  
attribute-value pairs for redirect URL **12-16**
- Cisco Secure ACS configuration guide **12-52**
- CiscoWorks 2000 **1-4, 33-4**
- CISP **12-24**
- CIST regional root  
See MSTP
- CIST root  
See MSTP
- civic location **27-3**
- class maps for QoS  
configuring **36-42**  
described **36-7**  
displaying **36-68**
- class of service  
See CoS
- clearing interfaces **13-19**
- CLI  
abbreviating commands **2-4**  
command modes **2-1**  
configuration logging **2-5**  
described **1-4**  
editing features  
enabling and disabling **2-7**  
keystroke editing **2-7**  
wrapped lines **2-9**  
error messages **2-5**  
filtering command output **2-10**  
getting help **2-3**  
history  
changing the buffer size **2-6**  
described **2-6**  
disabling **2-7**  
recalling commands **2-6**
- CLI (continued)  
managing clusters **7-14**  
no and default forms of commands **2-4**
- Client Information Signalling Protocol  
See CISP
- client mode, VTP **16-3**
- clock  
See system clock
- clusters, switch  
accessing **7-12**  
automatic discovery **7-4**  
automatic recovery **7-9**  
benefits **1-2**  
compatibility **7-4**  
described **7-1**  
LRE profile considerations **7-13**  
managing  
through CLI **7-14**  
through SNMP **7-14**
- planning **7-4**  
planning considerations  
automatic discovery **7-4**  
automatic recovery **7-9**  
CLI **7-14**  
host names **7-12**  
IP addresses **7-12**  
LRE profiles **7-13**  
passwords **7-12**  
RADIUS **7-13**  
SNMP **7-13, 7-14**  
TACACS+ **7-13**
- See also candidate switch, command switch, cluster standby group, member switch, and standby command switch
- cluster standby group  
automatic recovery **7-11**  
considerations **7-10**  
defined **7-2**  
requirements **7-3**

- cluster standby group (continued)
- virtual IP address **7-10**
  - See also HSRP
- CNS **1-5**
- Configuration Engine
    - configID, deviceID, hostname **6-3**
    - configuration service **6-2**
    - described **6-1**
    - event service **6-3**
  - embedded agents
    - described **6-5**
    - enabling automated configuration **6-6**
    - enabling configuration agent **6-9**
    - enabling event agent **6-7**
  - management functions **1-4**
- command-line interface
- See CLI
- command modes **2-1**
- commands
- abbreviating **2-4**
  - no and default **2-4**
- commands, setting privilege levels **11-8**
- command switch
- accessing **7-10**
  - active (AC) **7-9**
  - configuration conflicts **39-7**
  - defined **7-2**
  - passive (PC) **7-9**
  - password privilege levels **7-14**
  - priority **7-9**
  - recovery
    - from command-switch failure **7-9, 39-4**
    - from lost member connectivity **39-7**
  - redundant **7-9**
  - replacing
    - with another switch **39-6**
    - with cluster member **39-4**
  - requirements **7-3**
  - standby (SC) **7-9**
- command switch (continued)
- See also candidate switch, cluster standby group, member switch, and standby command switch
- community strings
- configuring **7-13, 33-8**
  - for cluster switches **33-4**
  - in clusters **7-13**
  - overview **33-4**
  - SNMP **7-13**
- compatibility, feature **26-12**
- config.text **4-16**
- configurable leave timer, IGMP **25-5**
- configuration, initial
- defaults **1-11**
  - Express Setup **1-2**
- configuration changes, logging **32-10**
- configuration conflicts, recovering from lost member connectivity **39-7**
- configuration examples, network **1-13**
- configuration files
- archiving **B-19**
  - clearing the startup configuration **B-19**
  - creating using a text editor **B-10**
  - default name **4-16**
  - deleting a stored configuration **B-19**
  - described **B-8**
  - downloading
    - automatically **4-16**
    - preparing **B-10, B-13, B-16**
    - reasons for **B-8**
    - using FTP **B-13**
    - using RCP **B-17**
    - using TFTP **B-11**
  - guidelines for creating and using **B-9**
  - guidelines for replacing and rolling back **B-21**
  - invalid combinations when copying **B-5**
  - limiting TFTP server access **33-16**
  - obtaining with DHCP **4-8**
  - password recovery disable considerations **11-5**

- configuration files (continued)
- replacing a running configuration **B-19, B-20**
  - rolling back a running configuration **B-19, B-20**
  - specifying the filename **4-16**
  - system contact and location information **33-16**
  - types and location **B-9**
  - uploading
    - preparing **B-10, B-13, B-16**
    - reasons for **B-8**
    - using FTP **B-14**
    - using RCP **B-18**
    - using TFTP **B-11**
- configuration guidelines
- REP **21-7**
- configuration logger **32-10**
- configuration logging **2-5**
- configuration replacement **B-19**
- configuration rollback **B-19**
- configuration settings, saving **4-14**
- configure terminal command **13-6**
- configuring port-based authentication violation modes **12-32**
- configuring small-frame arrival rate **26-5**
- config-vlan mode **2-2, 15-6**
- conflicts, configuration **39-7**
- connections, secure remote **11-33**
- connectivity problems **39-8, 39-10, 39-11**
- consistency checks in VTP Version 2 **16-4**
- console port, connecting to **2-10**
- control protocol, IP SLAs **35-3**
- convergence
- REP **21-4**
- corrupted software, recovery steps with Xmodem **39-2**
- CoS
- in Layer 2 frames **36-2**
  - override priority **17-6**
  - trust priority **17-6**
- CoS input queue threshold map for QoS **36-14**
- CoS output queue threshold map for QoS **36-17**
- CoS-to-DSCP map for QoS **36-51**
- counters, clearing interface **13-19**
- CPU utilization, troubleshooting **39-18**
- crashinfo file **39-17**
- critical authentication, IEEE 802.1x **12-45**
- cryptographic software image
- SSH **11-33**
  - SSL **11-37**
- 
- D**
- DACL
- See downloadable ACL
- daylight saving time **8-13**
- debugging
- enabling all system diagnostics **39-15**
  - enabling for a specific feature **39-14**
  - redirecting error message output **39-15**
  - using commands **39-14**
- default alarm configuration **3-4**
- default commands **2-4**
- default configuration
- 802.1x **12-27**
  - auto-QoS **36-19**
  - banners **8-17**
  - booting **4-16**
  - CDP **28-2**
  - DHCP **23-6**
  - DHCP option 82 **23-7**
  - DHCP snooping **23-7**
  - DHCP snooping binding database **23-7**
  - DNS **8-16**
  - dynamic ARP inspection **24-5**
  - EtherChannel **38-9**
  - Ethernet interfaces **13-10**
  - Flex Links **22-8**
  - IGMP filtering **25-24**
  - IGMP snooping **25-6**
  - IGMP throttling **25-24**

- default configuration (continued)
- initial switch information **4-3**
  - IP SLAs **35-5**
  - IP source guard **23-13**
  - IPv6 **37-6**
  - Layer 2 interfaces **13-10**
  - LLDP **27-4**
  - MAC address table **8-20**
  - MAC address-table move update **22-8**
  - MSTP **19-14**
  - MVR **25-19**
  - NTP **8-4**
  - optional spanning-tree configuration **20-9**
  - password and privilege level **11-2**
  - PTP **9-2**
  - RADIUS **11-20**
  - REP **21-7**
  - RMON **31-3**
  - RSPAN **30-9**
  - SDM template **10-2**
  - SNMP **33-6**
  - SPAN **30-9**
  - SSL **11-40**
  - standard QoS **36-28**
  - STP **18-11**
  - system message logging **32-3**
  - system name and prompt **8-15**
  - TACACS+ **11-13**
  - UDLD **29-4**
  - VLAN, Layer 2 Ethernet interfaces **15-16**
  - VLANs **15-7**
  - VMPS **15-25**
  - voice VLAN **17-3**
  - VTP **16-6**
  - default gateway **4-14**
  - deleting VLANs **15-9**
  - denial-of-service attack **26-1**
  - description command **13-17**
  - designing your network, examples **1-13**
- destination addresses
- in IPv4 ACLs **34-9**
- destination-IP address-based forwarding, EtherChannel **38-7**
- destination-MAC address forwarding, EtherChannel **38-7**
- detecting indirect link failures, STP **20-5**
- device **B-23**
- device discovery protocol **27-1, 28-1**
- device manager
- benefits **1-2**
  - described **1-2, 1-4**
  - in-band management **1-5**
  - upgrading a switch **B-23**
- DHCP
- Cisco IOS server database
  - configuring **23-10**
  - enabling
  - relay agent **23-8**
- DHCP-based autoconfiguration
- client request message exchange **4-4**
  - configuring
  - client side **4-3**
  - DNS **4-7**
  - relay device **4-8**
  - server side **4-6**
  - TFTP server **4-7**
  - example **4-9**
  - lease options
  - for IP address information **4-6**
  - for receiving the configuration file **4-6**
  - overview **4-3**
  - relationship to BOOTP **4-4**
  - relay support **1-5**
  - support for **1-5**
- DHCP-based autoconfiguration and image update
- configuring **4-11 to 4-13**
  - understanding **4-5**
- DHCP binding database
- See DHCP snooping binding database

- DHCP binding table  
See DHCP snooping binding database
- DHCP option 82  
circuit ID suboption **23-5**  
configuration guidelines **23-7**  
default configuration **23-6**  
displaying **23-12**  
overview **23-3**  
packet format, suboption  
  circuit ID **23-5**  
  remote ID **23-5**  
remote ID suboption **23-5**
- DHCP server port-based address allocation  
configuration guidelines **23-16**  
default configuration **23-16**  
described **23-16**  
displaying **23-19**  
enabling **23-17**
- DHCP server port-based address assignment  
support for **1-5**
- DHCP snooping  
accepting untrusted packets from edge switch **23-3, 23-9**  
binding database  
  See DHCP snooping binding database  
configuration guidelines **23-7**  
default configuration **23-6**  
displaying binding tables **23-12**  
message exchange process **23-4**  
option 82 data insertion **23-3**  
trusted interface **23-2**  
untrusted interface **23-2**  
untrusted messages **23-2**
- DHCP snooping binding database  
adding bindings **23-11**  
binding entries, displaying **23-12**  
binding file  
  format **23-6**  
  location **23-5**
- DHCP snooping binding database (continued)  
bindings **23-5**  
clearing agent statistics **23-11**  
configuration guidelines **23-8**  
configuring **23-11**  
default configuration **23-6, 23-7**  
deleting  
  binding file **23-11**  
  bindings **23-11**  
  database agent **23-11**  
described **23-5**  
displaying **23-12**  
displaying status and statistics **23-12**  
enabling **23-11**  
entry **23-5**  
renewing database **23-11**  
resetting  
  delay value **23-11**  
  timeout value **23-11**
- DHCP snooping binding table  
See DHCP snooping binding database
- Differentiated Services architecture, QoS **36-2**
- Differentiated Services Code Point **36-2**
- directed unicast requests **1-5**
- directories  
  changing **B-4**  
  creating and removing **B-4**  
  displaying the working **B-4**
- discovery, clusters  
  See automatic discovery
- displaying switch alarms **3-12**
- DNS  
  and DHCP-based autoconfiguration **4-7**  
  default configuration **8-16**  
  displaying the configuration **8-17**  
  in IPv6 **37-3**  
  overview **8-15**  
  setting up **8-16**  
  support for **1-5**

- domain names
  - DNS **8-15**
  - VTP **16-7**
- Domain Name System
  - See DNS
- downloadable ACL **12-15, 12-16, 12-52**
- downloading
  - configuration files
    - preparing **B-10, B-13, B-16**
    - reasons for **B-8**
    - using FTP **B-13**
    - using RCP **B-17**
    - using TFTP **B-11**
  - image files
    - deleting old image **B-27**
    - preparing **B-25, B-29, B-33**
    - reasons for **B-23**
    - using CMS **1-2**
    - using FTP **B-30**
    - using HTTP **1-2, B-23**
    - using RCP **B-34**
    - using TFTP **B-26**
    - using the device manager or Network Assistant **B-23**
- DSCL **1-9, 36-2**
- DSCL input queue threshold map for QoS **36-14**
- DSCL output queue threshold map for QoS **36-17**
- DSCL-to-CoS map for QoS **36-54**
- DSCL-to-DSCL-mutation map for QoS **36-55**
- DSCL transparency **36-36**
- DTP **1-7, 15-14**
- dual-action detection **38-5**
- dual IPv4 and IPv6 templates **37-4, 37-5**
- dual protocol stacks
  - IPv4 and IPv6 **37-5**
  - SDM templates supporting **37-5**
- dual-purpose uplinks
  - defined **13-4**
  - LEDs **13-4**
  - link selection **13-4, 13-11**
  - setting the type **13-11**
- dynamic access ports
  - characteristics **15-3**
  - configuring **15-26**
  - defined **13-3**
- dynamic addresses
  - See addresses
- dynamic ARP inspection
  - ARP cache poisoning **24-1**
  - ARP requests, described **24-1**
  - ARP spoofing attack **24-1**
  - clearing
    - log buffer **24-15**
    - statistics **24-14**
  - configuration guidelines **24-6**
  - configuring
    - ACLs for non-DHCP environments **24-8**
    - in DHCP environments **24-7**
    - log buffer **24-13**
    - rate limit for incoming ARP packets **24-4, 24-10**
  - default configuration **24-5**
  - denial-of-service attacks, preventing **24-10**
  - described **24-1**
  - DHCP snooping binding database **24-2**
  - displaying
    - ARP ACLs **24-14**
    - configuration and operating state **24-14**
    - log buffer **24-15**
    - statistics **24-14**
    - trust state and rate limit **24-14**
  - error-disabled state for exceeding rate limit **24-4**
  - function of **24-2**
  - interface trust states **24-3**

- dynamic ARP inspection (continued)
- log buffer
    - clearing **24-15**
    - configuring **24-13**
    - displaying **24-15**
  - logging of dropped packets, described **24-4**
  - man-in-the middle attack, described **24-2**
  - network security issues and interface trust states **24-3**
  - priority of ARP ACLs and DHCP snooping entries **24-4**
  - rate limiting of ARP packets
    - configuring **24-10**
    - described **24-4**
    - error-disabled state **24-4**
  - statistics
    - clearing **24-14**
    - displaying **24-14**
  - validation checks, performing **24-12**
- dynamic auto trunking mode **15-15**
- dynamic desirable trunking mode **15-15**
- Dynamic Host Configuration Protocol
- See DHCP-based autoconfiguration
- dynamic port VLAN membership
- described **15-24**
  - reconfirming **15-27**
  - troubleshooting **15-29**
  - types of connections **15-26**
- Dynamic Trunking Protocol
- See DTP
- 
- E**
- editing features
- enabling and disabling **2-7**
  - keystrokes used **2-7**
  - wrapped lines **2-9**
- ELIN location **27-3**
- enable password **11-3**
- enable secret password **11-3**
- enabling SNMP traps **3-11**
- encryption, CipherSuite **11-39**
- encryption for passwords **11-3**
- environment variables, function of **4-19**
- error-disabled state, BPDU **20-2**
- error messages during command entry **2-5**
- EtherChannel
- automatic creation of **38-4, 38-5**
  - channel groups
    - binding physical and logical interfaces **38-3**
    - numbering of **38-3**
  - configuration guidelines **38-9**
  - configuring Layer 2 interfaces **38-10**
  - default configuration **38-9**
  - described **38-2**
  - displaying status **38-17**
  - forwarding methods **38-7, 38-13**
  - IEEE 802.3ad, described **38-5**
  - interaction
    - with STP **38-10**
    - with VLANs **38-10**
- LACP
- described **38-5**
  - displaying status **38-17**
  - hot-standby ports **38-15**
  - interaction with other features **38-6**
  - modes **38-6**
  - port priority **38-16**
  - system priority **38-16**
  - load balancing **38-7, 38-13**
- PAgP
- aggregate-port learners **38-14**
  - compatibility with Catalyst 1900 **38-14**
  - described **38-4**
  - displaying status **38-17**
  - interaction with other features **38-5**
  - interaction with virtual switches **38-5**
  - learn method and priority configuration **38-14**
  - modes **38-4**

EtherChannel (continued)

- support for **1-3**
- with dual-action detection **38-5**

port-channel interfaces

- described **38-3**
- numbering of **38-3**

port groups **13-3**

support for **1-3**

EtherChannel guard

- described **20-7**
- disabling **20-14**
- enabling **20-14**

Ethernet VLANs

- adding **15-8**
- defaults and ranges **15-7**
- modifying **15-8**

EUI **37-3**

events, RMON **31-3**

examples

- network configuration **1-13**

expedite queue for QoS **36-67**

Express Setup **1-2**

- See also getting started guide

extended crashinfo file **39-17**

extended-range VLANs

- configuration guidelines **15-12**

- configuring **15-11**

- creating **15-12**

- defined **15-1**

extended system ID

- MSTP **19-17**

- STP **18-4, 18-14**

extended universal identifier

- See EUI

Extensible Authentication Protocol over LAN **12-1**

## F

fa0 interface **1-6**

Fast Convergence **22-3**

FCS bit error rate alarm

- configuring **3-8, 3-9**

- defined **3-3**

FCS error hysteresis threshold **3-2**

features, incompatible **26-12**

fiber-optic, detecting unidirectional links **29-1**

files

- basic crashinfo

- description **39-17**

- location **39-17**

- copying **B-5**

- crashinfo, description **39-17**

- deleting **B-5**

- displaying the contents of **B-8**

- extended crashinfo

- description **39-18**

- location **39-18**

tar

- creating **B-6**

- displaying the contents of **B-6**

- extracting **B-7**

- image file format **B-24**

file system

- displaying available file systems **B-2**

- displaying file information **B-3**

- local file system names **B-1**

- network file system names **B-5**

- setting the default **B-2**

filtering

- non-IP traffic **34-20**

- show and more command output **2-10**

filtering show and more command output **2-10**

filters, IP

- See ACLs, IP

flash device, number of **B-1**

flexible authentication ordering  
     configuring [12-54](#)  
     overview [12-23](#)

Flex Link Multicast Fast Convergence [22-3](#)

Flex Links  
     configuration guidelines [22-8](#)  
     configuring [22-9](#)  
     configuring preferred VLAN [22-12](#)  
     configuring VLAN load balancing [22-11](#)  
     default configuration [22-8](#)  
     description [22-1](#)  
     link load balancing [22-2](#)  
     monitoring [22-14](#)  
     VLANs [22-2](#)

flooded traffic, blocking [26-8](#)

flow-based packet classification [1-9](#)

flowcharts  
     QoS classification [36-6](#)  
     QoS egress queueing and scheduling [36-16](#)  
     QoS ingress queueing and scheduling [36-13](#)  
     QoS policing and marking [36-10](#)

flowcontrol  
     configuring [13-15](#)  
     described [13-15](#)

forward-delay time  
     MSTP [19-23](#)  
     STP [18-21](#)

FTP  
     accessing MIB files [A-3](#)  
     configuration files  
         downloading [B-13](#)  
         overview [B-12](#)  
         preparing the server [B-13](#)  
         uploading [B-14](#)  
     image files  
         deleting old image [B-31](#)  
         downloading [B-30](#)  
         preparing the server [B-29](#)  
         uploading [B-31](#)

**G**

general query [22-5](#)  
     Generating IGMP Reports [22-3](#)  
     get-bulk-request operation [33-3](#)  
     get-next-request operation [33-3, 33-4](#)  
     get-request operation [33-3, 33-4](#)  
     get-response operation [33-3](#)  
     global configuration mode [2-2](#)  
     global leave, IGMP [25-12](#)  
     global status monitoring alarms [3-2](#)  
     guest VLAN and 802.1x [12-17](#)  
     guide mode [1-2](#)  
     GUIs  
         See device manager and Network Assistant

**H**

hello time  
     MSTP [19-22](#)  
     STP [18-20](#)

help, for the command line [2-3](#)

history  
     changing the buffer size [2-6](#)  
     described [2-6](#)  
     disabling [2-7](#)  
     recalling commands [2-6](#)

history table, level and number of syslog messages [32-10](#)

host names, in clusters [7-12](#)

hosts, limit on dynamic ports [15-29](#)

HP OpenView [1-4](#)

HSRP  
     automatic cluster recovery [7-11](#)  
     cluster standby group considerations [7-10](#)  
     See also clusters, cluster standby group, and standby command switch

HTTP over SSL  
     see HTTPS

**HTTPS** **11-38**

- configuring **11-41**
- self-signed certificate **11-38**

**HTTP secure server** **11-38**

---

**ICMP**

- IPv6** **37-3**
- time-exceeded messages **39-12**
- traceroute and **39-12**

**ICMP ping**

- executing **39-9**
- overview **39-9**

**ICMPv6** **37-3**

**IDS appliances**

- and ingress RSPAN **30-20**
- and ingress SPAN **30-13**

**IEEE 1588 standard** **9-1**

**IEEE 802.1D**

See **STP**

**IEEE 802.1p** **17-1**

**IEEE 802.1Q**

- and trunk ports **13-3**
- configuration limitations **15-15**
- encapsulation **15-14**
- native VLAN for untagged traffic **15-19**

**IEEE 802.1s**

See **MSTP**

**IEEE 802.1w**

See **RSTP**

**IEEE 802.1x**

See port-based authentication

**IEEE 802.3ad**

See **EtherChannel**

**IEEE 802.3x flow control** **13-15**

**ifIndex values, SNMP** **33-5**

**IFS** **1-5**

**IGMP**

- configurable leave timer
- described **25-5**
- enabling **25-10**
- flooded multicast traffic
- controlling the length of time **25-11**
- disabling on an interface **25-13**
- global leave **25-12**
- query solicitation **25-12**
- recovering from flood mode **25-12**
- joining multicast group **25-3**
- join messages **25-3**
- leave processing, enabling **25-10**
- leaving multicast group **25-5**
- queries **25-4**
- report suppression
- described **25-6**
- disabling **25-15**
- supported versions **25-2**
- support for **1-3**

**IGMP filtering**

- configuring **25-24**
- default configuration **25-24**
- described **25-23**
- monitoring **25-28**
- support for **1-3**

**IGMP groups**

- configuring filtering **25-27**
- setting the maximum number **25-26**

**IGMP Immediate Leave**

- configuration guidelines **25-10**
- described **25-5**
- enabling **25-10**

**IGMP profile**

- applying **25-25**
- configuration mode **25-24**
- configuring **25-25**

- IGMP snooping  
 and address aliasing **25-2**  
 configuring **25-6**  
 default configuration **25-6**  
 definition **25-1**  
 enabling and disabling **25-7**  
 global configuration **25-7**  
 Immediate Leave **25-5**  
 method **25-8**  
 monitoring **25-15**  
 querier  
   configuration guidelines **25-13**  
   configuring **25-13**  
 supported versions **25-2**  
 support for **1-3**  
 VLAN configuration **25-7**
- IGMP throttling  
 configuring **25-27**  
 default configuration **25-24**  
 described **25-24**  
 displaying action **25-28**
- Immediate Leave, IGMP **25-5**
- inaccessible authentication bypass **12-19**
- initial configuration  
 defaults **1-11**  
 Express Setup **1-2**
- interface  
 range macros **13-8**
- interface command **13-5 to 13-6**
- interface configuration  
 REP **21-9**
- interface configuration mode **2-3**
- interfaces  
 auto-MDIX, configuring **13-16**  
 configuration guidelines  
   duplex and speed **13-13**  
 configuring  
   procedure **13-6**  
 counters, clearing **13-19**
- interfaces (continued)  
 default configuration **13-10**  
 described **13-17**  
 descriptive name, adding **13-17**  
 displaying information about **13-19**  
 flow control **13-15**  
 management **1-4**  
 monitoring **13-18**  
 naming **13-17**  
 physical, identifying **13-5**  
 range of **13-6**  
 restarting **13-20**  
 shutting down **13-20**  
 speed and duplex, configuring **13-14**  
 status **13-18**  
 supported **13-4**  
 types of **13-1**  
 interfaces range macro command **13-8**  
 interface types **13-5**  
 Internet Protocol version 6  
   See IPv6
- Intrusion Detection System  
   See IDS appliances
- inventory management TLV **27-2, 27-6**
- IP ACLs  
 for QoS classification **36-7**  
 implicit deny **34-7, 34-11**  
 implicit masks **34-7**  
 named **34-12**  
 undefined **34-17**
- IP addresses  
 128-bit **37-2**  
 candidate or member **7-3, 7-12**  
 cluster access **7-2**  
 command switch **7-3, 7-10, 7-12**  
 discovering **8-27**  
 IPv6 **37-2**  
 redundant clusters **7-10**  
 standby command switch **7-10, 7-12**

- IP addresses (continued)
  - See also IP information
- ip igmp profile command **25-24**
- IP information
  - assigned
    - manually **4-14**
    - through DHCP-based autoconfiguration **4-3**
  - default configuration **4-3**
- IP phones
  - and QoS **17-1**
  - automatic classification and queueing **36-19**
  - configuring **17-4**
  - ensuring port security with QoS **36-35**
  - trusted boundary for QoS **36-35**
- IP precedence **36-2**
- IP-precedence-to-DSCP map for QoS **36-52**
- IP protocols in ACLs **34-9**
- IP Service Level Agreements
  - See IP SLAs
- IP service levels, analyzing **35-1**
- IP SLAs
  - benefits **35-2**
  - configuration guidelines **35-5**
  - Control Protocol **35-3**
  - default configuration **35-5**
  - definition **35-1**
  - measuring network performance **35-2**
  - monitoring **35-6**
  - operation **35-3**
  - responder
    - described **35-3**
    - enabling **35-6**
  - response time **35-4**
  - SNMP support **35-2**
  - supported metrics **35-2**
- IP source guard
  - and 802.1x **23-14**
  - and DHCP snooping **23-12**
  - and EtherChannels **23-14**
- IP source guard (continued)
  - and port security **23-14**
  - and private VLANs **23-14**
  - and routed ports **23-13**
  - and TCAM entries **23-14**
  - and trunk interfaces **23-14**
  - and VRF **23-14**
  - binding configuration
    - automatic **23-12**
    - manual **23-12**
  - binding table **23-12**
  - configuration guidelines **23-13**
  - default configuration **23-13**
  - described **23-12**
  - disabling **23-15**
  - displaying
    - bindings **23-15**
    - configuration **23-15**
  - enabling **23-14**
  - filtering
    - source IP address **23-13**
    - source IP and MAC address **23-13**
  - source IP address filtering **23-13**
  - source IP and MAC address filtering **23-13**
  - static bindings
    - adding **23-14**
    - deleting **23-15**
- IP traceroute
  - executing **39-12**
  - overview **39-11**
- IPv4 ACLs
  - applying to interfaces **34-16**
  - extended, creating **34-8**
  - named **34-12**
  - standard, creating **34-7**
- IPv4 and IPv6
  - dual protocol stacks **37-4**

**I**

- IPv6  
 addresses **37-2**  
 address formats **37-2**  
 applications **37-4**  
 assigning address **37-6**  
 autoconfiguration **37-4**  
 configuring static routes **37-9**  
 default configuration **37-6**  
 defined **37-1**  
 forwarding **37-6**  
 ICMP **37-3**  
 monitoring **37-10**  
 neighbor discovery **37-3**  
 Stateless Autoconfiguration **37-4**  
 supported features **37-2**  
 understanding static routes **37-5**
- 
- J**
- join messages, IGMP **25-3**
- 
- L**

**LACP**

See EtherChannel

- Layer 2 frames, classification with CoS **36-2**  
 Layer 2 interfaces, default configuration **13-10**

**Layer 2 traceroute**

and ARP **39-11**

and CDP **39-10**

broadcast traffic **39-10**

described **39-10**

IP addresses and subnets **39-11**

MAC addresses and VLANs **39-11**

multicast traffic **39-11**

multiple devices on a port **39-11**

unicast traffic **39-10**

usage guidelines **39-10**

- Layer 3 interfaces  
 assigning IPv6 addresses to **37-7**  
 Layer 3 packets, classification methods **36-2**  
 LDAP **6-2**  
 Leaking IGMP Reports **22-4**  
 LEDs, switch  
 See hardware installation guide  
 lightweight directory access protocol  
 See LDAP  
 line configuration mode **2-3**  
 Link Aggregation Control Protocol  
 See EtherChannel  
 link failure, detecting unidirectional **19-7**  
 link fault alarm **3-3**  
 link integrity, verifying with REP **21-3**  
 Link Layer Discovery Protocol

See CDP

link local unicast addresses **37-3**

**link redundancy**

See Flex Links

links, unidirectional **29-1**

**link-state tracking**

configuring **38-20**

described **38-18**

**LLDP**

configuring **27-4**

characteristics **27-5**

default configuration **27-4**

enabling **27-5**

monitoring and maintaining **27-10**

overview **27-1**

supported TLVs **27-2**

switch stack considerations **27-2**

transmission timer and holdtime, setting **27-5**

**LLDP-MED**

configuring

procedures **27-4**

TLVs **27-6**

- LLDP-MED (continued)
- monitoring and maintaining **27-10**
  - overview **27-1, 27-2**
  - supported TLVs **27-2**
- LLDP Media Endpoint Discovery
- See LLDP-MED
- local SPAN **30-2**
- location TLV **27-3, 27-6**
- login authentication
- with RADIUS **11-23**
  - with TACACS+ **11-14**
- login banners **8-17**
- log messages
- See system message logging
- Long-Reach Ethernet (LRE) technology **1-14**
- loop guard
- described **20-9**
  - enabling **20-15**
  - support for **1-7**
- LRE profiles, considerations in switch clusters **7-13**
- 
- M**
- MAB
- See MAC authentication bypass
- MAB inactivity timer
- default setting **12-28**
  - range **12-30**
- MAC/PHY configuration status TLV **27-2**
- MAC addresses
- aging time **8-21**
  - and VLAN association **8-20**
  - building the address table **8-20**
  - default configuration **8-20**
  - disabling learning on a VLAN **8-26**
  - discovering **8-27**
  - displaying **8-27**
  - displaying in the IP source binding table **23-15**
- MAC addresses (continued)
- dynamic
  - learning **8-20**
  - removing **8-21**
  - in ACLs **34-20**
  - static
  - adding **8-24**
  - allowing **8-25, 8-26**
  - characteristics of **8-23**
  - dropping **8-25**
  - removing **8-24**
- MAC address learning **1-5**
- MAC address learning, disabling on a VLAN **8-26**
- MAC address notification, support for **1-10**
- MAC address-table move update
- configuration guidelines **22-8**
  - configuring **22-12**
  - default configuration **22-8**
  - description **22-6**
  - monitoring **22-14**
- MAC address-to-VLAN mapping **15-24**
- MAC authentication bypass **12-30**
- configuring **12-48**
  - overview **12-14**
- MAC extended access lists
- applying to Layer 2 interfaces **34-22**
  - configuring for QoS **36-41**
  - creating **34-20**
  - defined **34-20**
  - for QoS classification **36-5**
- magic packet **12-21**
- manageability features **1-5**
- management access
- in-band
  - browser session **1-5**
  - CLI session **1-6**
  - device manager **1-5**
  - SNMP **1-6**
  - out-of-band console port connection **1-6**

- management address TLV **27-2**
- management options
- CLI **2-1**
  - clustering **1-2**
  - CNS **6-1**
  - Network Assistant **1-2**
  - overview **1-4**
- management VLAN
- considerations in switch clusters **7-7**
  - discovery through different management VLANs **7-7**
- manual preemption, REP, configuring **21-12**
- mapping tables for QoS
- configuring
  - CoS-to-DSCP **36-51**
  - DSCP **36-50**
  - DSCP-to-CoS **36-54**
  - DSCP-to-DSCP-mutation **36-55**
  - IP-precedence-to-DSCP **36-52**
  - policed-DSCP **36-53**
  - described **36-10**
- marking
- action with aggregate policers **36-48**
  - described **36-4, 36-8**
- matching, IPv4 ACLs **34-5**
- maximum aging time
- MSTP **19-23**
  - STP **18-21**
- maximum hop count, MSTP **19-24**
- maximum number of allowed devices, port-based authentication **12-30**
- MDA
- configuration guidelines **12-11 to 12-12**
  - described **1-8, 12-11**
  - exceptions with authentication process **12-5**
- membership mode, VLAN port **15-3**
- member switch
- automatic discovery **7-4**
  - defined **7-2**
  - managing **7-14**
- member switch (continued)
- passwords **7-12**
  - recovering from lost connectivity **39-7**
  - requirements **7-3**
  - See also candidate switch, cluster standby group, and standby command switch
  - messages, to users through banners **8-17**
- MIBs
- accessing files with FTP **A-3**
  - location of files **A-3**
  - overview **33-1**
  - SNMP interaction with **33-4**
  - supported **A-1**
  - mirroring traffic for analysis **30-1**
  - mismatches, autonegotiation **39-7**
  - module number **13-5**
  - monitoring
  - access groups **34-23**
  - alarms **3-12**
  - cables for unidirectional links **29-1**
  - CDP **28-5**
  - features **1-10**
  - Flex Links **22-14**
  - IGMP
  - filters **25-28**
  - snooping **25-15**
  - interfaces **13-18**
  - IP SLAs operations **35-6**
  - IPv4 ACL configuration **34-23**
  - IPv6 **37-10**
  - MAC address-table move update **22-14**
  - multicast router interfaces **25-16**
  - MVR **25-23**
  - network traffic for analysis with probe **30-2**
  - port
  - blocking **26-19**
  - protection **26-19**
  - PTP **9-4**
  - REP **21-13**

- monitoring (continued)
- SFP status **13-19, 39-8**
  - speed and duplex mode **13-14**
  - traffic flowing among switches **31-1**
  - traffic suppression **26-19**
  - VLANs **15-13**
  - VMPS **15-28**
  - VTP **16-16**
  - mrouter Port **22-3**
  - mrouter port **22-5**
  - MSTP
    - boundary ports
      - configuration guidelines **19-15**
      - described **19-6**
    - BPDU filtering
      - described **20-3**
      - enabling **20-12**
    - BPDU guard
      - described **20-2**
      - enabling **20-11**
    - CIST, described **19-3**
    - CIST regional root **19-3**
    - CIST root **19-5**
    - configuration guidelines **19-14, 20-10**
    - configuring
      - forward-delay time **19-23**
      - hello time **19-22**
      - link type for rapid convergence **19-24**
      - maximum aging time **19-23**
      - maximum hop count **19-24**
      - MST region **19-15**
      - neighbor type **19-25**
      - path cost **19-20**
      - port priority **19-19**
      - root switch **19-17**
      - secondary root switch **19-18**
      - switch priority **19-21**  - MSTP (continued)
    - CST
      - defined **19-3**
      - operations between regions **19-3**
    - default configuration **19-14**
    - default optional feature configuration **20-9**
    - displaying status **19-26**
    - enabling the mode **19-15**
    - EtherChannel guard
      - described **20-7**
      - enabling **20-14**
    - extended system ID
      - effects on root switch **19-17**
      - effects on secondary root switch **19-18**
      - unexpected behavior **19-17**
    - IEEE 802.1s
      - implementation **19-6**
      - port role naming change **19-6**
      - terminology **19-5**
    - instances supported **18-9**
    - interface state, blocking to forwarding **20-2**
    - interoperability and compatibility among modes **18-10**
    - interoperability with IEEE 802.1D
      - described **19-8**
      - restarting migration process **19-25**
    - IST
      - defined **19-2**
      - master **19-3**
      - operations within a region **19-3**
    - loop guard
      - described **20-9**
      - enabling **20-15**
    - mapping VLANs to MST instance **19-16**

- MSTP (continued)
- MST region
    - CIST **19-3**
    - configuring **19-15**
    - described **19-2**
    - hop-count mechanism **19-5**
    - IST **19-2**
    - supported spanning-tree instances **19-2**
  - optional features supported **1-7**
  - overview **19-2**
- Port Fast
- described **20-2**
  - enabling **20-10**
  - preventing root switch selection **20-8**
- root guard
- described **20-8**
  - enabling **20-15**
- root switch
- configuring **19-17**
  - effects of extended system ID **19-17**
  - unexpected behavior **19-17**
- shutdown Port Fast-enabled port **20-2**
- status, displaying **19-26**
- multiauth mode
- See multiple-authentication mode
- multicast groups
- Immediate Leave **25-5**
  - joining **25-3**
  - leaving **25-5**
  - static joins **25-9**
- multicast router interfaces, monitoring **25-16**
- multicast router ports, adding **25-9**
- multicast storm **26-1**
- multicast storm-control command **26-4**
- multicast television application **25-17**
- multicast VLAN **25-16**
- Multicast VLAN Registration
- See MVR
- multidomain authentication
- See MDA
- multiple authentication **12-12**
- multiple authentication mode
- configuring **12-35**
- MVR
- and address aliasing **25-20**
  - and IGMPv3 **25-20**
  - configuration guidelines **25-19**
  - configuring interfaces **25-21**
  - default configuration **25-19**
  - described **25-16**
  - example application **25-17**
  - modes **25-20**
  - monitoring **25-23**
  - multicast television application **25-17**
  - setting global parameters **25-20**
  - support for **1-3**
- 
- N**
- NAC
- critical authentication **12-19, 12-45**
  - IEEE 802.1x authentication using a RADIUS server **12-49**
  - IEEE 802.1x validation using RADIUS server **12-49**
  - inaccessible authentication bypass **12-45**
  - Layer 2 IEEE 802.1x validation **1-9, 12-23, 12-49**
- named IPv4 ACLs **34-12**
- NameSpace Mapper
- See NSM
- native VLAN
- configuring **15-19**
  - default **15-19**
- NEAT
- configuring **12-50**
  - overview **12-24**
- neighbor discovery, IPv6 **37-3**
- neighbor offset numbers, REP **21-4**

Network Admission Control

See NAC

Network Admission Control Software Configuration Guide **12-57, 12-58**

Network Assistant

benefits **1-2**

described **1-4**

downloading image files **1-2**

guide mode **1-2**

management options **1-2**

upgrading a switch **B-23**

wizards **1-2**

network configuration examples

increasing network performance **1-13**

providing network services **1-14**

network design

performance **1-13**

services **1-14**

Network Edge Access Topology

See NEAT

network management

CDP **28-1**

RMON **31-1**

SNMP **33-1**

network performance, measuring with IP SLAs **35-2**

network policy TLV **27-2, 27-7**

Network Time Protocol

See NTP

no commands **2-4**

nonhierarchical policy maps

described **36-8**

non-IP traffic filtering **34-20**

nontrunking mode **15-15**

normal-range VLANs **15-4**

configuration guidelines **15-5**

configuration modes **15-6**

configuring **15-4**

defined **15-1**

NSM **6-3**

NTP

associations

authenticating **8-4**

defined **8-2**

enabling broadcast messages **8-6**

peer **8-5**

server **8-5**

default configuration **8-4**

displaying the configuration **8-11**

overview **8-2**

restricting access

creating an access group **8-8**

disabling NTP services per interface **8-10**

source IP address, configuring **8-10**

stratum **8-2**

support for **1-5**

synchronizing devices **8-5**

time

services **8-2**

synchronizing **8-2**

---

## O

open1x

configuring **12-55**

open1x authentication

overview **12-24**

optimizing system resources **10-1**

options, management **1-4**

out-of-profile markdown **1-10**

---

## P

packet modification, with QoS **36-18**

PAgP

See EtherChannel

- passwords
- default configuration **11-2**
  - disabling recovery of **11-5**
  - encrypting **11-3**
  - for security **1-8**
  - in clusters **7-12**
  - overview **11-1**
  - recovery of **39-3**
  - setting
    - enable **11-3**
    - enable secret **11-3**
    - Telnet **11-6**
    - with usernames **11-6**
  - VTP domain **16-8**
- path cost
- MSTP **19-20**
  - STP **18-18**
- PC (passive command switch) **7-9**
- performance, network design **1-13**
- performance features **1-3**
- persistent self-signed certificate **11-38**
- per-user ACLs and Filter-Ids **12-8**
- per-VLAN spanning-tree plus
- See PVST+
- physical ports **13-2**
- PIM-DVMRP, as snooping method **25-8**
- ping
- character output description **39-9**
  - executing **39-9**
  - overview **39-9**
- policed-DSCP map for QoS **36-53**
- policers
- configuring
    - for each matched traffic class **36-44**
    - for more than one traffic class **36-48**
  - described **36-4**
  - displaying **36-68**
  - number of **36-31**
  - types of **36-8**
- policing
- described **36-4**
  - token-bucket algorithm **36-9**
- policy maps for QoS
- characteristics of **36-44**
  - described **36-7**
  - displaying **36-69**
  - nonhierarchical on physical ports
    - described **36-8**
  - port ACLs, described **34-2**
- Port Aggregation Protocol
- See EtherChannel
- port-based authentication
- accounting **12-12**
  - authentication server
    - defined **12-2**
    - RADIUS server **12-3**
  - client, defined **12-2**
  - configuration guidelines **12-28**
  - configuring
    - 802.1x authentication **12-32**
    - guest VLAN **12-42**
    - host mode **12-35**
    - inaccessible authentication bypass **12-45**
    - manual re-authentication of a client **12-38**
    - periodic re-authentication **12-37**
    - quiet period **12-38**
    - RADIUS server **12-35**
    - RADIUS server parameters on the switch **12-34**
    - restricted VLAN **12-43**
    - switch-to-client frame-retransmission number **12-39, 12-40**
    - switch-to-client retransmission time **12-39**
    - violation modes **12-32**
  - default configuration **12-27**
  - described **12-1**
  - device roles **12-2**
  - displaying statistics **12-59**

- port-based authentication (continued)
  - downloadable ACLs and redirect URLs
    - configuring **12-52 to 12-54**
    - overview **12-15 to 12-16**
  - EAPOL-start frame **12-5**
  - EAP-request/identity frame **12-5**
  - EAP-response/identity frame **12-5**
  - encapsulation **12-3**
  - flexible authentication ordering
    - configuring **12-54**
    - overview **12-23**
  - guest VLAN
    - configuration guidelines **12-17, 12-18**
    - described **12-17**
  - host mode **12-10**
  - inaccessible authentication bypass
    - configuring **12-45**
    - described **12-19**
    - guidelines **12-30**
  - initiation and message exchange **12-5**
  - magic packet **12-21**
  - maximum number of allowed devices per port **12-30**
  - method lists **12-32**
  - multiple authentication **12-12**
  - ports
    - authorization state and dot1x port-control command **12-9**
    - authorized and unauthorized **12-9**
    - critical **12-19**
    - voice VLAN **12-20**
  - port security
    - and voice VLAN **12-21**
    - described **12-20**
    - interactions **12-20**
    - multiple-hosts mode **12-10**
  - readiness check
    - configuring **12-31**
    - described **12-14, 12-31**
  - resetting to default values **12-59**
- port-based authentication (continued)
  - statistics, displaying **12-59**
  - switch
    - as proxy **12-3**
    - RADIUS client **12-3**
  - switch supplicant
    - configuring **12-50**
    - overview **12-24**
  - VLAN assignment
    - AAA authorization **12-32**
    - characteristics **12-14**
    - configuration tasks **12-15**
    - described **12-14**
  - voice VLAN
    - described **12-20**
    - PVID **12-20**
    - VVID **12-20**
  - wake-on-LAN, described **12-21**
  - with ACLs and RADIUS Filter-Id attribute **12-26**
- port-based authentication methods, supported **12-7**
- port blocking **1-3, 26-7**
- port-channel
  - See EtherChannel
- port description TLV **27-2**
- Port Fast
  - described **20-2**
  - enabling **20-10**
  - mode, spanning tree **15-25**
  - support for **1-7**
- port membership modes, VLAN **15-3**
- port not forwarding alarm **3-3**
- port not operating alarm **3-3**
- port priority
  - MSTP **19-19**
  - STP **18-16**
- ports
  - access **13-2**
  - blocking **26-7**
  - dual-purpose uplink **13-4**

- ports (continued)
- dynamic access **15-3**
  - protected **26-6**
  - REP **21-6**
  - secure **26-8**
  - static-access **15-3, 15-10**
  - switch **13-2**
  - trunks **15-3, 15-14**
  - VLAN assignments **15-10**
- port security
- aging **26-17**
  - and QoS trusted boundary **36-35**
  - configuring **26-12**
  - default configuration **26-11**
  - described **26-8**
  - displaying **26-19**
  - on trunk ports **26-14**
  - sticky learning **26-9**
  - violations **26-10**
  - with other features **26-11**
- port-shutdown response, VMPS **15-24**
- port status monitoring alarms
- FCS bit error rate alarm **3-3**
  - link fault alarm **3-3**
  - port not forwarding alarm **3-3**
  - port not operating alarm **3-3**
- port VLAN ID TLV **27-2**
- power management TLV **27-2, 27-7**
- power supply alarm, configuring **3-5**
- Precision Time Protocol
- See PTP
- preempt delay time, REP **21-5**
- preemption, default configuration **22-8**
- preemption delay, default configuration **22-8**
- preferential treatment of traffic
- See QoS
- preventing unauthorized access **11-1**
- primary edge port, REP **21-4**
- primary links **22-2**
- priority
- overriding CoS **17-6**
  - trusting CoS **17-6**
- private VLAN edge ports
- See protected ports
- privileged EXEC mode **2-2**
- privilege levels
- changing the default for lines **11-9**
  - command switch **7-14**
  - exiting **11-9**
  - logging into **11-9**
  - mapping on member switches **7-14**
  - overview **11-2, 11-7**
  - setting a command with **11-8**
- protected ports **1-8, 26-6**
- proxy reports **22-3**
- pruning, VTP
- disabling
    - in VTP domain **16-14**
    - on a port **15-19**
  - enabling
    - in VTP domain **16-14**
    - on a port **15-19**
  - examples **16-5**
  - overview **16-4**
- pruning-eligible list
- changing **15-19**
  - for VTP pruning **16-4**
  - VLANs **16-14**
- PTP **9-1**
- configuring **9-3**
  - default configuration **9-2**
  - displaying configuration **9-4**
- PVST+
- described **18-9**
  - IEEE 802.1Q trunking interoperability **18-10**
  - instances supported **18-9**

**Q****QoS**

and MQC commands **36-1**

auto-QoS

  categorizing traffic **36-19**

  configuration and defaults display **36-27**

  configuration guidelines **36-24**

  described **36-19**

  disabling **36-25**

  displaying generated commands **36-25**

  displaying the initial configuration **36-27**

  effects on running configuration **36-24**

  egress queue defaults **36-20**

  enabling for VoIP **36-25**

  example configuration **36-26**

  ingress queue defaults **36-20**

  list of generated commands **36-21**

basic model **36-4**

classification

  class maps, described **36-7**

  defined **36-4**

  DSCP transparency, described **36-36**

  flowchart **36-6**

  forwarding treatment **36-3**

  in frames and packets **36-3**

  IP ACLs, described **36-5, 36-7**

  MAC ACLs, described **36-5, 36-7**

  options for IP traffic **36-5**

  options for non-IP traffic **36-5**

  policy maps, described **36-7**

  trust DSCP, described **36-5**

  trusted CoS, described **36-5**

  trust IP precedence, described **36-5**

class maps

  configuring **36-42**

  displaying **36-68**

QoS (continued)

  configuration guidelines

    auto-QoS **36-24**

    standard QoS **36-31**

  configuring

    aggregate policers **36-48**

    auto-QoS **36-19**

    default port CoS value **36-34**

    DSCP maps **36-50**

    DSCP transparency **36-36**

    DSCP trust states bordering another domain **36-37**

    egress queue characteristics **36-61**

    ingress queue characteristics **36-56**

    IP extended ACLs **36-40**

    IP standard ACLs **36-39**

    MAC ACLs **36-41**

    port trust states within the domain **36-33**

    trusted boundary **36-35**

    default auto configuration **36-19**

    default standard configuration **36-28**

    displaying statistics **36-68**

    DSCP transparency **36-36**

    egress queues

      allocating buffer space **36-61**

      buffer allocation scheme, described **36-16**

      configuring shaped weights for SRR **36-65**

      configuring shared weights for SRR **36-66**

      described **36-4**

      displaying the threshold map **36-64**

      flowchart **36-16**

      mapping DSCP or CoS values **36-64**

      scheduling, described **36-4**

      setting WTD thresholds **36-61**

      WTD, described **36-17**

    enabling globally **36-32**

- QoS (continued)
- flowcharts
    - classification **36-6**
    - egress queueing and scheduling **36-16**
    - ingress queueing and scheduling **36-13**
    - policing and marking **36-10**
  - implicit deny **36-7**
  - ingress queues
    - allocating bandwidth **36-59**
    - allocating buffer space **36-58**
    - buffer and bandwidth allocation, described **36-14**
    - configuring shared weights for SRR **36-59**
    - configuring the priority queue **36-60**
    - described **36-4**
    - displaying the threshold map **36-58**
    - flowchart **36-13**
    - mapping DSCP or CoS values **36-57**
    - priority queue, described **36-14**
    - scheduling, described **36-4**
    - setting WTD thresholds **36-57**
    - WTD, described **36-14**
  - IP phones
    - automatic classification and queueing **36-19**
    - detection and trusted settings **36-19, 36-35**
  - limiting bandwidth on egress interface **36-67**
  - mapping tables
    - CoS-to-DSCP **36-51**
    - displaying **36-68**
    - DSCP-to-CoS **36-54**
    - DSCP-to-DSCP-mutation **36-55**
    - IP-precedence-to-DSCP **36-52**
    - policed-DSCP **36-53**
    - types of **36-10**
  - marked-down actions **36-47**
  - marking, described **36-4, 36-8**
  - overview **36-1**
  - packet modification **36-18**
- QoS (continued)
- policers
    - configuring **36-47, 36-49**
    - described **36-8**
    - displaying **36-68**
    - number of **36-31**
    - types of **36-8**
  - policies, attaching to an interface **36-8**
  - policing
    - described **36-4, 36-8**
    - token bucket algorithm **36-9**
  - policy maps
    - characteristics of **36-44**
    - displaying **36-69**
    - nonhierarchical on physical ports **36-44**
  - QoS label, defined **36-4**
  - queues
    - configuring egress characteristics **36-61**
    - configuring ingress characteristics **36-56**
    - high priority (expedite) **36-18, 36-67**
    - location of **36-11**
    - SRR, described **36-12**
    - WTD, described **36-11**
  - rewrites **36-18**
  - support for **1-9**
  - trust states
    - bordering another domain **36-37**
    - described **36-5**
    - trusted device **36-35**
    - within the domain **36-33**
  - quality of service
    - See QoS
  - queries, IGMP **25-4**
  - query solicitation, IGMP **25-12**

**R****RADIUS**

attributes

  vendor-proprietary **11-31**  vendor-specific **11-29**

configuring

  accounting **11-28**  authentication **11-23**  authorization **11-27**  communication, global **11-21, 11-29**  communication, per-server **11-20, 11-21**  multiple UDP ports **11-20**  default configuration **11-20**  defining AAA server groups **11-25**  displaying the configuration **11-32**  identifying the server **11-20**  in clusters **7-13**  limiting the services to the user **11-27**  method list, defined **11-19**  operation of **11-19**  overview **11-18**  server load balancing **11-31**  suggested network environments **11-18**  support for **1-9**  tracking services accessed by user **11-28****range**macro **13-8**of interfaces **13-7****rapid convergence** **19-9****rapid per-VLAN spanning-tree plus**

See rapid PVST+

**rapid PVST+**described **18-9**IEEE 802.1Q trunking interoperability **18-10**instances supported **18-9****Rapid Spanning Tree Protocol**

See RSTP

**rcommand command** **7-14****RCP**

configuration files

  downloading **B-17**  overview **B-15**  preparing the server **B-16**  uploading **B-18**

image files

  deleting old image **B-36**  downloading **B-34**  preparing the server **B-33**  uploading **B-36****readiness check**

port-based authentication

  configuring **12-31**  described **12-14, 12-31****real-time clock synchronization** **9-1**reconfirmation interval, VMPS, changing **15-27**reconfirming dynamic VLAN membership **15-27**recovery procedures **39-1**redirect URL **12-15, 12-16, 12-52****redundancy**  EtherChannel **38-2**

STP

    backbone **18-8**    path cost **15-22**    port priority **15-20**  redundant links and UplinkFast **20-13**  reloading software **4-20****Remote Authentication Dial-In User Service**

See RADIUS

**Remote Copy Protocol**

See RCP

**Remote Network Monitoring**

See RMON

**Remote SPAN**

See RSPAN

**remote SPAN** **30-2**

- REP
- administrative VLAN **21-8**
  - administrative VLAN, configuring **21-8**
  - age timer **21-8**
  - and STP **21-6**
  - configuration guidelines **21-7**
  - configuring interfaces **21-9**
  - convergence **21-4**
  - default configuration **21-7**
  - manual preemption, configuring **21-12**
  - monitoring **21-13**
  - neighbor offset numbers **21-4**
  - open segment **21-2**
  - ports **21-6**
  - preempt delay time **21-5**
  - primary edge port **21-4**
  - ring segment **21-2**
  - secondary edge port **21-4**
  - segments **21-1**
    - characteristics **21-2**
  - SNMP traps, configuring **21-13**
  - supported interfaces **21-1**
  - triggering VLAN load balancing **21-5**
  - verifying link integrity **21-3**
  - VLAN blocking **21-12**
  - VLAN load balancing **21-4**
- report suppression, IGMP
- described **25-6**
  - disabling **25-15**
- resequencing ACL entries **34-12**
- resetting a UDLD-shutdown interface **29-6**
- Resilient Ethernet Protocol
- See REP
- responder, IP SLAs
- described **35-3**
  - enabling **35-6**
- response time, measuring with IP SLAs **35-4**
- restricted VLAN
- configuring **12-43**
  - described **12-18**
  - using with IEEE 802.1x **12-18**
- restricting access
- NTP services **8-8**
  - overview **11-1**
  - passwords and privilege levels **11-2**
  - RADIUS **11-17**
  - TACACS+ **11-10**
- retry count, VMPS, changing **15-28**
- RFC
- 1112, IP multicast and IGMP **25-2**
  - 1157, SNMPv1 **33-2**
  - 1305, NTP **8-2**
  - 1757, RMON **31-2**
  - 1901, SNMPv2C **33-2**
  - 1902 to 1907, SNMPv2 **33-2**
  - 2236, IP multicast and IGMP **25-2**
  - 2273-2275, SNMPv3 **33-2**
- RMON
- default configuration **31-3**
  - displaying status **31-6**
  - enabling alarms and events **31-3**
  - groups supported **31-2**
  - overview **31-1**
  - statistics
    - collecting group Ethernet **31-5**
    - collecting group history **31-5**
  - support for **1-10**
- root guard
- described **20-8**
  - enabling **20-15**
  - support for **1-7**
- root switch
- MSTP **19-17**
  - STP **18-14**

## RSPAN

- characteristics **30-7**
- configuration guidelines **30-16**
- default configuration **30-9**
- defined **30-2**
- destination ports **30-6**
- displaying status **30-23**
- interaction with other features **30-8**
- monitored ports **30-5**
- monitoring ports **30-6**
- overview **1-10, 30-1**
- received traffic **30-4**
- sessions
  - creating **30-17**
  - defined **30-3**
  - limiting source traffic to specific VLANs **30-22**
  - specifying monitored ports **30-17**
  - with ingress traffic enabled **30-20**
- source ports **30-5**
- transmitted traffic **30-5**
- VLAN-based **30-6**

## RSTP

- active topology **19-9**
- BPDUs
  - format **19-12**
  - processing **19-12**
- designated port, defined **19-9**
- designated switch, defined **19-9**
- interoperability with IEEE 802.1D
  - described **19-8**
  - restarting migration process **19-25**
  - topology changes **19-13**
- overview **19-8**
- port roles
  - described **19-9**
  - synchronized **19-11**
- proposal-agreement handshake process **19-10**

## RSTP (continued)

- rapid convergence
- described **19-9**
- edge ports and Port Fast **19-9**
- point-to-point links **19-10, 19-24**
- root ports **19-10**
- root port, defined **19-9**
- See also MSTP
- running configuration
  - replacing **B-19, B-20**
  - rolling back **B-19, B-20**
- running configuration, saving **4-14**

**S**

- SC (standby command switch) **7-9**
- scheduled reloads **4-20**
- SCP
  - and SSH **11-44**
  - configuring **11-44**
- SDM
  - described **10-1**
  - templates
    - configuring **10-3**
    - number of **10-1**
- SDM template
  - configuration guidelines **10-2**
  - configuring **10-2**
  - types of **10-1**
- secondary edge port, REP **21-4**
- Secure Copy Protocol
- secure HTTP client
  - configuring **11-43**
  - displaying **11-43**
- secure HTTP server
  - configuring **11-41**
  - displaying **11-43**

secure MAC addresses  
     deleting **26-16**  
     maximum number of **26-9**  
     types of **26-9**

secure ports, configuring **26-8**

secure remote connections **11-33**

Secure Shell  
     See SSH

Secure Socket Layer  
     See SSL

security, port **26-8**

security features **1-8**

See SCP

sequence numbers in log messages **32-8**

server mode, VTP **16-3**

service-provider network, MSTP and RSTP **19-1**

set-request operation **33-4**

setting a secondary temperature threshold **3-6, 3-7**

setting power supply alarm options **3-5**

setting the FCS error hysteresis threshold **3-9**

setting the FCS error threshold **3-8**

setup program  
     failed command switch replacement **39-6**  
     replacing failed command switch **39-4**

severity levels, defining in system messages **32-8**

SFPs  
     monitoring status of **13-19, 39-8**  
     security and identification **39-8**  
     status, displaying **39-8**

shaped round robin  
     See SRR

show access-lists hw-summary command **34-17**

show alarm commands **3-12**

show and more command output, filtering **2-10**

show cdp traffic command **28-5**

show cluster members command **7-14**

show configuration command **13-17**

show forward command **39-16**

show interfaces command **13-14, 13-17**

show interfaces switchport **22-4**

show lldp traffic command **27-11**

show platform forward command **39-16**

show running-config command  
     displaying ACLs **34-16, 34-17**  
     interface description in **13-17**

shutdown command on interfaces **13-20**

Simple Network Management Protocol  
     See SNMP

small-frame arrival rate, configuring **26-5**

Smartports macros  
     applying Cisco-default macros **14-3**  
     applying global parameter values **14-3**  
     configuration guidelines **14-2**  
     default configuration **14-1**  
     displaying **14-5**  
     tracing **14-2**

SNAP **28-1**

SNMP  
     accessing MIB variables with **33-4**  
     agent  
         described **33-3**  
         disabling **33-7**  
     and IP SLAs **35-2**  
     authentication level **33-10**  
     community strings  
         configuring **33-8**  
         for cluster switches **33-4**  
         overview **33-4**  
     configuration examples **33-17**  
     default configuration **33-6**  
     engine ID **33-7**  
     groups **33-6, 33-9**  
     host **33-6**  
     ifIndex values **33-5**  
     in-band management **1-6**  
     in clusters **7-13**

- SNMP (continued)
- informs
    - and trap keyword [33-11](#)
    - described [33-5](#)
    - differences from traps [33-5](#)
    - disabling [33-15](#)
    - enabling [33-15](#)
  - limiting access by TFTP servers [33-16](#)
  - limiting system log messages to NMS [32-10](#)
  - manager functions [1-4, 33-3](#)
  - managing clusters with [7-14](#)
  - MIBs
    - location of [A-3](#)
    - supported [A-1](#)
  - notifications [33-5](#)
  - overview [33-1, 33-4](#)
  - security levels [33-3](#)
  - setting CPU threshold notification [33-15](#)
  - status, displaying [33-18](#)
  - system contact and location [33-16](#)
  - trap manager, configuring [33-13](#)
  - traps
    - described [33-3, 33-5](#)
    - differences from informs [33-5](#)
    - disabling [33-15](#)
    - enabling [33-11](#)
    - enabling MAC address notification [8-21](#)
    - overview [33-1, 33-4](#)
    - types of [33-11](#)
  - users [33-6, 33-9](#)
  - versions supported [33-2](#)
- SNMP and Syslog Over IPv6 [37-5](#)
- SNMP traps
- REP [21-13](#)
  - SNMPv1 [33-2](#)
  - SNMPv2C [33-2](#)
  - SNMPv3 [33-2](#)
  - snooping, IGMP [25-1](#)
- software images
- location in flash [B-24](#)
  - recovery procedures [39-2](#)
  - scheduling reloads [4-20](#)
  - tar file format, described [B-24](#)
  - See also downloading and uploading
- source addresses
- in IPv4 ACLs [34-9](#)
- source-and-destination-IP address based forwarding, EtherChannel [38-7](#)
- source-and-destination MAC address forwarding, EtherChannel [38-7](#)
- source-IP address based forwarding, EtherChannel [38-7](#)
- source-MAC address forwarding, EtherChannel [38-7](#)
- SPAN
- configuration guidelines [30-10](#)
  - default configuration [30-9](#)
  - destination ports [30-6](#)
  - displaying status [30-23](#)
  - interaction with other features [30-8](#)
  - monitored ports [30-5](#)
  - monitoring ports [30-6](#)
  - overview [1-10, 30-1](#)
  - ports, restrictions [26-12](#)
  - received traffic [30-4](#)
  - sessions
    - configuring ingress forwarding [30-14, 30-21](#)
    - creating [30-10](#)
    - defined [30-3](#)
    - limiting source traffic to specific VLANs [30-15](#)
    - removing destination (monitoring) ports [30-12](#)
    - specifying monitored ports [30-10](#)
    - with ingress traffic enabled [30-13](#)
  - source ports [30-5](#)
  - transmitted traffic [30-5](#)
  - VLAN-based [30-6](#)
- spanning tree and native VLANs [15-15](#)
- Spanning Tree Protocol
- See STP

- SPAN traffic **30-4**
- SRR
- configuring
    - shaped weights on egress queues **36-65**
    - shared weights on egress queues **36-66**
    - shared weights on ingress queues **36-59**
  - described **36-12**
  - shaped mode **36-12**
  - shared mode **36-12**
  - support for **1-10**
- SSH
- configuring **11-34**
  - cryptographic software image **11-33**
  - described **1-6, 11-33**
  - encryption methods **11-34**
  - user authentication methods, supported **11-34**
- SSL
- configuration guidelines **11-40**
  - configuring a secure HTTP client **11-43**
  - configuring a secure HTTP server **11-41**
  - cryptographic software image **11-37**
  - described **11-37**
  - monitoring **11-43**
- standby command switch
- configuring
  - considerations **7-10**
  - defined **7-2**
  - priority **7-9**
  - requirements **7-3**
  - virtual IP address **7-10**
- See also cluster standby group and HSRP
- standby group, cluster
- See cluster standby group and HSRP
- standby links **22-2**
- startup configuration
- booting
    - manually **4-17**
    - specific image **4-18**
  - clearing **B-19**
- startup configuration (continued)
- configuration file
    - automatically downloading **4-16**
    - specifying the filename **4-16**
    - default boot configuration **4-16**
  - static access ports
    - assigning to VLAN **15-10**
    - defined **13-3, 15-3**
  - static addresses
    - See addresses
  - static MAC addressing **1-8**
  - static routes
    - configuring for IPv6 **37-9**
    - understanding **37-5**
  - static VLAN membership **15-2**
  - statistics
    - 802.1x **12-59**
    - CDP **28-5**
    - interface **13-19**
    - LLDP **27-10**
    - LLDP-MED **27-10**
    - NMSP **27-10**
    - QoS ingress and egress **36-68**
    - RMON group Ethernet **31-5**
    - RMON group history **31-5**
    - SNMP input and output **33-18**
    - VTP **16-16**
    - sticky learning **26-9**
  - storm control
    - configuring **26-3**
    - described **26-1**
    - disabling **26-5**
    - displaying **26-19**
    - support for **1-3**
    - thresholds **26-1**

- STP
- accelerating root port selection **20-4**
  - and REP **21-6**
  - BackboneFast
    - described **20-5**
    - disabling **20-14**
    - enabling **20-13**
  - BPDU filtering
    - described **20-3**
    - disabling **20-12**
    - enabling **20-12**
  - BPDU guard
    - described **20-2**
    - disabling **20-12**
    - enabling **20-11**
  - BPDU message exchange **18-3**
  - configuration guidelines **18-12, 20-10**
  - configuring
    - forward-delay time **18-21**
    - hello time **18-20**
    - maximum aging time **18-21**
    - path cost **18-18**
    - port priority **18-16**
    - root switch **18-14**
    - secondary root switch **18-16**
    - spanning-tree mode **18-13**
    - switch priority **18-19**
    - transmit hold-count **18-22**
  - counters, clearing **18-22**
  - default configuration **18-11**
  - default optional feature configuration **20-9**
  - designated port, defined **18-3**
  - designated switch, defined **18-3**
  - detecting indirect link failures **20-5**
  - disabling **18-14**
  - displaying status **18-22**
  - EtherChannel guard
    - described **20-7**
    - disabling **20-14**
    - enabling **20-14**
  - extended system ID
    - effects on root switch **18-14**
    - effects on the secondary root switch **18-16**
    - overview **18-4**
    - unexpected behavior **18-14**
  - features supported **1-6**
  - IEEE 802.1D and bridge ID **18-4**
  - IEEE 802.1D and multicast addresses **18-8**
  - IEEE 802.1t and VLAN identifier **18-4**
  - inferior BPDU **18-3**
  - instances supported **18-9**
  - interface state, blocking to forwarding **20-2**
  - interface states
    - blocking **18-5**
    - disabled **18-7**
    - forwarding **18-5, 18-6**
    - learning **18-6**
    - listening **18-6**
    - overview **18-4**
  - interoperability and compatibility among modes **18-10**
  - limitations with IEEE 802.1Q trunks **18-10**
  - load sharing
    - overview **15-20**
    - using path costs **15-22**
    - using port priorities **15-20**
  - loop guard
    - described **20-9**
    - enabling **20-15**
  - modes supported **18-9**
  - multicast addresses, effect of **18-8**
  - optional features supported **1-7**
  - overview **18-2**
  - path costs **15-22**

- STP (continued)
- Port Fast
    - described **20-2**
    - enabling **20-10**
  - port priorities **15-21**
  - preventing root switch selection **20-8**
  - protocols supported **18-9**
  - redundant connectivity **18-8**
  - root guard
    - described **20-8**
    - enabling **20-15**
  - root port, defined **18-3**
  - root switch
    - configuring **18-14**
    - effects of extended system ID **18-4, 18-14**
    - election **18-3**
    - unexpected behavior **18-14**
  - shutdown Port Fast-enabled port **20-2**
  - status, displaying **18-22**
  - superior BPDU **18-3**
  - timers, described **18-20**
  - UplinkFast
    - described **20-3**
    - enabling **20-13**
  - stratum, NTP **8-2**
  - success response, VMPS **15-24**
  - summer time **8-13**
  - SunNet Manager **1-4**
  - supported port-based authentication methods **12-7**
  - switch **37-2**
    - See also clusters, switch
  - switch clustering technology **7-1**
  - switch console port **1-6**
  - Switch Database Management
    - See SDM
  - Switched Port Analyzer
    - See SPAN
  - switched ports **13-2**
  - switchport backup interface **22-4, 22-5**
  - switchport block multicast command **26-8**
  - switchport block unicast command **26-8**
  - switchport protected command **26-7**
  - switch priority
    - MSTP **19-21**
    - STP **18-19**
  - switch software features **1-1**
  - synchronization, real-time clocks **9-1**
  - syslog
    - See system message logging
  - system capabilities TLV **27-2**
  - system clock
    - configuring
      - daylight saving time **8-13**
      - manually **8-11**
      - summer time **8-13**
      - time zones **8-12**
    - displaying the time and date **8-12**
    - overview **8-1**
    - See also NTP
  - system description TLV **27-2**
  - system message logging
    - default configuration **32-3**
    - defining error message severity levels **32-8**
    - disabling **32-4**
    - displaying the configuration **32-13**
    - enabling **32-4**
    - facility keywords, described **32-13**
    - level keywords, described **32-9**
    - limiting messages **32-10**
    - message format **32-2**
    - overview **32-1**
    - sequence numbers, enabling and disabling **32-8**
    - setting the display destination device **32-5**
    - synchronizing log messages **32-6**
    - syslog facility **1-10**
    - time stamps, enabling and disabling **32-7**

- system message logging (continued)
- UNIX syslog servers
    - configuring the daemon **32-12**
    - configuring the logging facility **32-12**
    - facilities supported **32-13**
- system name
- default configuration **8-15**
  - default setting **8-15**
  - manual configuration **8-15**
  - See also DNS
- system name TLV **27-2**
- system prompt, default setting **8-14, 8-15**
- system resources, optimizing **10-1**
- 
- T**
- TACACS+
- accounting, defined **11-11**
  - authentication, defined **11-11**
  - authorization, defined **11-11**
  - configuring
    - accounting **11-17**
    - authentication key **11-13**
    - authorization **11-16**
    - login authentication **11-14**
  - default configuration **11-13**
  - displaying the configuration **11-17**
  - identifying the server **11-13**
  - in clusters **7-13**
  - limiting the services to the user **11-16**
  - operation of **11-12**
  - overview **11-10**
  - support for **1-9**
  - tracking services accessed by user **11-17**
- tar files
- creating **B-6**
  - displaying the contents of **B-6**
  - extracting **B-7**
  - image file format **B-24**
- TDR **1-11**
- Telnet
- accessing management interfaces **2-10**
  - number of connections **1-6**
  - setting a password **11-6**
- temperature alarms, configuring **3-6, 3-7**
- templates, SDM **10-1**
- temporary self-signed certificate **11-38**
- Terminal Access Controller Access Control System Plus
- See TACACS+
- terminal lines, setting a password **11-6**
- TFTP
- configuration files
    - downloading **B-11**
    - preparing the server **B-10**
    - uploading **B-11**
  - configuration files in base directory **4-7**
  - configuring for autoconfiguration **4-7**
  - image files
    - deleting **B-27**
    - downloading **B-26**
    - preparing the server **B-25**
    - uploading **B-28**
  - limiting access by servers **33-16**
- TFTP server **1-5**
- threshold, traffic level **26-2**
- time
- See NTP and system clock
- Time Domain Reflector
- See TDR
- time-range command **34-14**
- time ranges in ACLs **34-14**
- time stamps in log messages **32-7**
- time zones **8-12**
- TLVs
- defined **27-1**
  - LLDP **27-2**
  - LLDP-MED **27-2**

- Token Ring VLANs
- support for **15-5**
  - VTP support **16-4**
- ToS **1-9**
- traceroute, Layer 2
- and ARP **39-11**
  - and CDP **39-10**
  - broadcast traffic **39-10**
  - described **39-10**
  - IP addresses and subnets **39-11**
  - MAC addresses and VLANs **39-11**
  - multicast traffic **39-11**
  - multiple devices on a port **39-11**
  - unicast traffic **39-10**
  - usage guidelines **39-10**
- traceroute command **39-12**
- See also IP traceroute
- traffic
- blocking flooded **26-8**
  - fragmented **34-3**
  - unfragmented **34-3**
- traffic policing **1-10**
- traffic suppression **26-1**
- transmit hold-count
- see STP
- transparent mode, VTP **16-3, 16-12**
- trap-door mechanism **4-2**
- traps
- configuring MAC address notification **8-21**
  - configuring managers **33-11**
  - defined **33-3**
  - enabling **8-21, 33-11**
  - notification types **33-11**
  - overview **33-1, 33-4**
- triggering alarm options
- configurable relays **3-3**
  - methods **3-3**
  - SNMP traps **3-4**
  - syslog messages **3-4**
- troubleshooting
- connectivity problems **39-8, 39-10, 39-11**
  - CPU utilization **39-18**
  - detecting unidirectional links **29-1**
  - displaying crash information **39-17**
  - setting packet forwarding **39-16**
  - SFP security and identification **39-8**
  - show forward command **39-16**
  - with CiscoWorks **33-4**
  - with debug commands **39-14**
  - with ping **39-9**
  - with system message logging **32-1**
  - with traceroute **39-11**
- trunk failover
- See link-state tracking
- trunking encapsulation **1-7**
- trunk ports
- configuring **15-17**
  - defined **13-3, 15-3**
- trunks
- allowed-VLAN list **15-18**
  - load sharing
    - setting STP path costs **15-22**
    - using STP port priorities **15-20, 15-21**
  - native VLAN for untagged traffic **15-19**
  - parallel **15-22**
  - pruning-eligible list **15-19**
  - to non-DTP device **15-14**
- trusted boundary for QoS **36-35**
- trusted port states
- between QoS domains **36-37**
  - classification options **36-5**
  - ensuring port security for IP phones **36-35**
  - support for **1-9**
  - within a QoS domain **36-33**
- trustpoints, CA **11-38**
- twisted-pair Ethernet, detecting unidirectional links **29-1**
- type of service
- See ToS

**U**

## UDLD

- configuration guidelines [29-4](#)
- default configuration [29-4](#)
- disabling
  - globally [29-5](#)
  - on fiber-optic interfaces [29-5](#)
  - per interface [29-5](#)
- echoing detection mechanism [29-2](#)
- enabling
  - globally [29-5](#)
  - per interface [29-5](#)
- link-detection mechanism [29-1](#)
- neighbor database [29-2](#)
- overview [29-1](#)
- resetting an interface [29-6](#)
- status, displaying [29-6](#)
- support for [1-6](#)
- unauthorized ports with IEEE 802.1x [12-9](#)
- unicast MAC address filtering [1-5](#)
  - and adding static addresses [8-25](#)
  - and broadcast MAC addresses [8-24](#)
  - and CPU packets [8-24](#)
  - and multicast addresses [8-24](#)
  - and router MAC addresses [8-24](#)
- configuration guidelines [8-24](#)
- described [8-24](#)
- unicast storm [26-1](#)
- unicast storm control command [26-4](#)
- unicast traffic, blocking [26-8](#)
- UniDirectional Link Detection protocol
  - See UDLD
- UNIX syslog servers
  - daemon configuration [32-12](#)
  - facilities supported [32-13](#)
  - message logging configuration [32-12](#)
- unrecognized Type-Length-Value (TLV) support [16-4](#)

upgrading software images

See downloading

## UplinkFast

- described [20-3](#)
- disabling [20-13](#)
- enabling [20-13](#)
- support for [1-6](#)

uploading

configuration files

- preparing [B-10, B-13, B-16](#)
- reasons for [B-8](#)
- using FTP [B-14](#)
- using RCP [B-18](#)
- using TFTP [B-11](#)

image files

- preparing [B-25, B-29, B-33](#)
- reasons for [B-23](#)
- using FTP [B-31](#)
- using RCP [B-36](#)
- using TFTP [B-28](#)

user EXEC mode [2-2](#)

username-based authentication [11-6](#)

**V**

version-dependent transparent mode [16-4](#)

virtual IP address

- cluster standby group [7-10](#)
- command switch [7-10](#)

virtual switches and PAgP [38-5](#)

vlan.dat file [15-4](#)

VLAN 1, disabling on a trunk port [15-18](#)

VLAN 1 minimization [15-18](#)

vlan-assignment response, VMPS [15-24](#)

VLAN blocking, REP [21-12](#)

VLAN configuration

- at bootup [15-7](#)
- saving [15-7](#)

VLAN configuration mode [2-2, 15-6](#)

- VLAN database
- and startup configuration file **15-7**
  - and VTP **16-1**
  - VLAN configuration saved in **15-6**
  - VLANs saved in **15-4**
  - vlan database command **15-6**
  - VLAN filtering and SPAN **30-6**
  - vlan global configuration command **15-6**
  - VLAN ID, discovering **8-27**
  - VLAN load balancing
    - REP **21-4**
  - VLAN load balancing, triggering **21-5**
  - VLAN load balancing on flex links **22-2**
    - configuration guidelines **22-8**
  - VLAN management domain **16-2**
  - VLAN Management Policy Server
    - See VMPS
  - VLAN membership
    - confirming **15-27**
    - modes **15-3**
  - VLAN Query Protocol
    - See VQP
  - VLANS
  - adding **15-8**
    - adding to VLAN database **15-8**
    - aging dynamic addresses **18-9**
    - allowed on trunk **15-18**
    - and spanning-tree instances **15-2, 15-6, 15-12**
    - configuration guidelines, extended-range VLANs **15-12**
    - configuration guidelines, normal-range VLANs **15-5**
    - configuration options **15-6**
    - configuring **15-1**
    - configuring IDs 1006 to 4094 **15-12**
    - creating in config-vlan mode **15-8**
    - creating in VLAN configuration mode **15-9**
    - default configuration **15-7**
    - deleting **15-9**
    - described **13-2, 15-1**
  - VLANs (continued)
    - displaying **15-13**
    - extended-range **15-1, 15-11**
    - features **1-7**
    - illustrated **15-2**
    - limiting source traffic with RSPAN **30-22**
    - limiting source traffic with SPAN **30-15**
    - modifying **15-8**
    - multicast **25-16**
    - native, configuring **15-19**
    - normal-range **15-1, 15-4**
    - number supported **1-7**
    - parameters **15-4**
    - port membership modes **15-3**
    - static-access ports **15-10**
    - STP and IEEE 802.1Q trunks **18-10**
    - supported **15-2**
    - Token Ring **15-5**
    - traffic between **15-2**
    - VTP modes **16-3**
  - VLAN Trunking Protocol
    - See VTP
  - VLAN trunks **15-14**
  - VMPS
    - administering **15-28**
    - configuration example **15-29**
    - configuration guidelines **15-25**
    - default configuration **15-25**
    - description **15-23**
    - dynamic port membership
      - described **15-24**
      - reconfirming **15-27**
      - troubleshooting **15-29**
    - entering server address **15-26**
    - mapping MAC addresses to VLANs **15-24**
    - monitoring **15-28**
    - reconfirmation interval, changing **15-27**
    - reconfirming membership **15-27**
    - retry count, changing **15-28**

- voice-over-IP **17-1**
- voice VLAN
- Cisco 7960 phone, port connections **17-1**
  - configuration guidelines **17-3**
  - configuring IP phones for data traffic
    - override CoS of incoming frame **17-6**
    - trust CoS priority of incoming frame **17-6**
  - configuring ports for voice traffic in
    - 802.1p priority tagged frames **17-5**
    - 802.1Q frames **17-4**
  - connecting to an IP phone **17-4**
  - default configuration **17-3**
  - described **17-1**
  - displaying **17-6**
  - IP phone data traffic, described **17-2**
  - IP phone voice traffic, described **17-2**
- VQP **1-7, 15-23**
- VTP
- adding a client to a domain **16-14**
  - advertisements **15-16, 16-3**
  - and extended-range VLANs **16-1**
  - and normal-range VLANs **16-1**
  - client mode, configuring **16-11**
  - configuration
    - global configuration mode **16-7**
    - guidelines **16-7**
    - privileged EXEC mode **16-7**
    - requirements **16-8**
    - saving **16-7**
    - VLAN configuration mode **16-7**
  - configuration mode options **16-7**
  - configuration requirements **16-8**
  - configuration revision number
    - guideline **16-14**
    - resetting **16-15**
  - configuring
    - client mode **16-11**
    - server mode **16-9**
    - transparent mode **16-12**
  - consistency checks **16-4**
  - default configuration **16-6**
  - described **16-1**
  - disabling **16-12**
  - domain names **16-7**
  - domains **16-2**
  - modes
    - client **16-3, 16-11**
    - server **16-3, 16-9**
    - transitions **16-3**
    - transparent **16-3, 16-12**
  - monitoring **16-16**
  - passwords **16-8**
  - pruning
    - disabling **16-14**
    - enabling **16-14**
    - examples **16-5**
    - overview **16-4**
    - support for **1-7**
  - pruning-eligible list, changing **15-19**
  - server mode, configuring **16-9**
  - statistics **16-16**
  - support for **1-7**
  - Token Ring support **16-4**
  - transparent mode, configuring **16-12**
  - using **16-1**
  - version, guidelines **16-8**
  - Version 1 **16-4**
  - Version 2
    - configuration guidelines **16-8**
    - disabling **16-13**
    - enabling **16-13**
    - overview **16-4**

**W**

web authentication [12-14](#)

    configuring [12-55 to 12-58](#)

    described [1-8, 12-25](#)

    fallback for IEEE 802.1x [12-57](#)

weighted tail drop

    See WTD

wired location service

    configuring [27-9](#)

    displaying [27-10](#)

    location TLV [27-3](#)

    understanding [27-3](#)

wizards [1-2](#)

**WTD**

    described [36-11](#)

    setting thresholds

        egress queue-sets [36-61](#)

        ingress queues [36-57](#)

    support for [1-10](#)

**X**

Xmodem protocol [39-2](#)

