



## INDEX

### A

- aaa accounting dot1x command [2-1](#)
- aaa authentication dot1x command [2-3](#)
- aaa authorization network command [2-5, 2-28, 2-34, 2-36, 2-38, 2-40, 2-42, 2-130, 2-293, 2-485, B-8, B-35](#)
- AAA methods [2-3](#)
- access control entries
  - See ACEs
- access control lists
  - See ACLs
- access groups
  - IP [2-180](#)
  - MAC, displaying [2-594](#)
- access list, IPv6 [2-250](#)
- access map configuration mode [2-319](#)
- access mode [2-778](#)
- access ports [2-778](#)
- ACEs [2-121, 2-395](#)
- ACLs
  - deny [2-119](#)
  - displaying [2-461](#)
  - for non-IP protocols [2-297](#)
  - IP [2-180](#)
  - matching [2-319](#)
  - on Layer 2 interfaces [2-180](#)
  - permit [2-393](#)
- action command [2-6](#)
- address aliasing [2-369](#)
- aggregate-port learner [2-381](#)
- alarm command [2-12](#)
- alarm facility fcs-hysteresis command [2-8](#)
- alarm facility power-supply command [2-9](#)
- alarm facility temperature command [2-10](#)
- alarm IDs [2-13, 2-464](#)
- alarm profile
  - attaching to a port [2-14](#)
  - creating [2-12](#)
  - displaying [2-465](#)
- alarm profile (global configuration) command [2-12](#)
- alarm profile (interface configuration) command [2-14](#)
- alarm profile configuration mode [2-12](#)
- allowed VLANs [2-798](#)
- archive download-sw command [2-16](#)
- archive tar command [2-19](#)
- archive upload-sw command [2-22](#)
- arp access-list command [2-24](#)
- authentication command bounce-port ignore [2-26](#)
- authentication command disable-port ignore [2-27](#)
- authentication control-direction command [2-28](#)
- authentication event command [2-30](#)
- authentication failed VLAN
  - See dot1x auth-fail vlan
- authentication fallback command [2-34](#)
- authentication host-mode command [2-36](#)
- authentication mac-move permit command [2-38](#)
- authentication open command [2-40](#)
- authentication order command [2-42](#)
- authentication periodic command [2-44](#)
- authentication port-control command [2-46](#)
- authentication priority command [2-48](#)
- authentication timer command [2-50](#)
- authentication violation command [2-52](#)
- auth-fail max-attempts
  - See dot1x auth-fail max-attempts
- auth-fail vlan

See dot1x auth-fail vlan

auth open command [2-40](#)

auth order command [2-42](#)

authorization state of controlled port [2-147](#)

auth timer command [2-50](#)

autonegotiation of duplex mode [2-158](#)

auto qos voip command [2-54](#)

---

## B

BackboneFast, for STP [2-708](#)

backup interfaces

- configuring [2-771](#)
- displaying [2-529](#)

boot (boot loader) command [A-2](#)

boot config-file command [2-58](#)

boot enable-break command [2-59](#)

boot helper command [2-60](#)

boot helper-config file command [2-61](#)

booting

- Cisco IOS image [2-64](#)
- displaying environment variables [2-478](#)
- interrupting [2-59](#)
- manually [2-62](#)

boot loader

- accessing [A-1](#)
- booting
  - Cisco IOS image [A-2](#)
  - helper image [2-60](#)
- directories
  - creating [A-15](#)
  - displaying a list of [A-8](#)
  - removing [A-19](#)
- displaying
  - available commands [A-13](#)
  - memory heap utilization [A-14](#)
  - version [A-27](#)
- environment variables
  - described [A-20](#)

- displaying settings [A-20](#)
- location of [A-21](#)
- setting [A-20](#)
- unsetting [A-25](#)

files

- copying [A-6](#)
- deleting [A-7](#)
- displaying a list of [A-8](#)
- displaying the contents of [A-4, A-16, A-23](#)
- renaming [A-17](#)

file system

- formatting [A-11](#)
- initializing flash [A-10](#)
- running a consistency check [A-12](#)
- resetting the system [A-18](#)

boot manual command [2-62](#)

boot private-config-file command [2-63](#)

boot system command [2-64](#)

BPDU filtering, for spanning tree [2-709, 2-744](#)

BPDU guard, for spanning tree [2-711, 2-744](#)

broadcast storm control [2-762](#)

---

## C

candidate switches

- See clusters

cat (boot loader) command [A-4](#)

CDP, enabling protocol tunneling for [2-275](#)

channel-group command [2-65](#)

channel-protocol command [2-68](#)

Cisco SoftPhone

- auto-QoS configuration [2-54](#)
- trusting packets sent from [2-360](#)

CISP

- See Client Information Signalling Protocol

cisp

- debug platform cisp command [B-35](#)

cisp enable command [2-71](#)

class command [2-72](#)

- class-map command [2-74](#)
  - class maps
    - creating [2-74](#)
    - defining the match criteria [2-321](#)
    - displaying [2-486](#)
  - class of service
    - See CoS
  - clear dot1x command [2-76](#)
  - clear eap sessions command [2-77](#)
  - clear errdisable interface [2-78](#)
  - clear ip arp inspection log command [2-79](#)
  - clear ip arp inspection statistics command [2-80](#)
  - clear ipc command [2-83](#)
  - clear ip dhcp snooping database command [2-81](#)
  - clear ipv6 dhcp conflict command [2-84](#)
  - clear l2protocol-tunnel counters command [2-85](#)
  - clear lacp command [2-86](#)
  - clear mac address-table command [2-87, 2-88](#)
  - clear nmsp statistics command [2-89](#)
  - clear pagp command [2-90, 2-94](#)
  - clear port-security command [2-91](#)
  - clear psp counter [2-93](#)
  - clear psp counter command [2-93](#)
  - clear spanning-tree counters command [2-95](#)
  - clear spanning-tree detected-protocols command [2-96](#)
  - clear vmps statistics command [2-97](#)
  - clear vtp counters command [2-98](#)
  - Client Information Signalling Protocol [2-71, 2-130, 2-485, B-8, B-35](#)
  - cluster commander-address command [2-99](#)
  - cluster discovery hop-count command [2-101](#)
  - cluster enable command [2-102](#)
  - cluster holdtime command [2-103](#)
  - cluster member command [2-104](#)
  - cluster outside-interface command [2-106](#)
  - cluster run command [2-107](#)
  - clusters
    - adding candidates [2-104](#)
    - binding to HSRP group [2-108](#)
    - building manually [2-104](#)
    - communicating with
      - devices outside the cluster [2-106](#)
      - members by using Telnet [2-425](#)
    - debug messages, display [B-9](#)
    - displaying
      - candidate switches [2-489](#)
      - debug messages [B-9](#)
      - member switches [2-491](#)
      - status [2-487](#)
    - hop-count limit for extended discovery [2-101](#)
    - HSRP standby groups [2-108](#)
    - redundancy [2-108](#)
    - SNMP trap [2-699](#)
  - cluster standby-group command [2-108](#)
  - cluster timer command [2-110](#)
  - command modes defined [1-1](#)
  - command switch
    - See clusters
  - configuration files
    - password recovery disable considerations [A-1](#)
    - specifying the name [2-58, 2-63](#)
  - configuring multiple interfaces [2-176](#)
  - config-vlan mode
    - commands [2-820](#)
  - copy (boot loader) command [A-6](#)
  - CoS
    - assigning default value to incoming packets [2-330](#)
    - assigning to Layer 2 protocol packets [2-278](#)
    - overriding the incoming value [2-330](#)
  - CoS-to-DSCP map [2-334](#)
  - CPU ASIC statistics, displaying [2-493](#)
  - crashinfo files [2-168](#)
  - critical VLAN [2-31](#)
- 
- ## D
- debug authentication [B-2](#)
  - debug auto qos command [B-4](#)

- debug backup command [B-6, B-7](#)
- debug cip [B-7](#)
- debug cisp command [B-8](#)
- debug cluster command [B-9](#)
- debug dot1x command [B-11](#)
- debug dtp command [B-12](#)
- debug eap command [B-13, B-88](#)
- debug etherchannel command [B-14](#)
- debug interface command [B-15](#)
- debug ip dhcp snooping command [B-16](#)
- debug ip igmp filter command [B-18](#)
- debug ip igmp max-groups command [B-19](#)
- debug ip igmp snooping command [B-20](#)
- debug ip verify source packet command [B-17](#)
- debug lacp command [B-21](#)
- debug lldp packets command [B-22](#)
- debug mac-notification command [B-23](#)
- debug matm command [B-24](#)
- debug matm move update command [B-25](#)
- debug monitor command [B-26](#)
- debug mvrdbg command [B-28](#)
- debug nmsp command [B-29](#)
- debug nvram command [B-30](#)
- debug pagp command [B-31](#)
- debug platform acl command [B-32](#)
- debug platform backup interface command [B-34](#)
- debug platform cisp command [B-35](#)
- debug platform cpu-queues command [B-36](#)
- debug platform dot1x command [B-38](#)
- debug platform etherchannel command [B-39](#)
- debug platform fallback-bridging command [B-40](#)
- debug platform forw-tcam command [B-41](#)
- debug platform ip arp inspection command [B-42](#)
- debug platform ip dhcp command [B-43](#)
- debug platform ip igmp snooping command [B-44](#)
- debug platform ip multicast command [B-46](#)
- debug platform ip source-guard command [B-48](#)
- debug platform ip unicast command [B-49](#)
- debug platform led command [B-51](#)
- debug platform matm command [B-52](#)
- debug platform messaging application command [B-53](#)
- debug platform phy command [B-54](#)
- debug platform pm command [B-56](#)
- debug platform port-asic command [B-58](#)
- debug platform port-security command [B-59](#)
- debug platform qos-acl-tcam command [B-60](#)
- debug platform resource-manager command [B-61](#)
- debug platform snmp command [B-62](#)
- debug platform span command [B-63](#)
- debug platform supervisor-asic command [B-64](#)
- debug platform sw-bridge command [B-65](#)
- debug platform tcam command [B-66](#)
- debug platform ulld command [B-69](#)
- debug platform vlan command [B-70](#)
- debug pm command [B-71](#)
- debug port-security command [B-73](#)
- debug profinet alarm [B-74](#)
- debug profinet cyclic [B-76](#)
- debug profinet error [B-78](#)
- debug profinet packet [B-80](#)
- debug profinet platform [B-82](#)
- debug profinet topology [B-84](#)
- debug profinet trace [B-86](#)
- debug qos-manager command [B-89](#)
- debug spanning-tree backbonefast command [B-92](#)
- debug spanning-tree bpdu command [B-93](#)
- debug spanning-tree bpdu-opt command [B-94](#)
- debug spanning-tree command [B-90](#)
- debug spanning-tree mstp command [B-95](#)
- debug spanning-tree switch command [B-97](#)
- debug spanning-tree uplinkfast command [B-99](#)
- debug sw-vlan command [B-100](#)
- debug sw-vlan ifs command [B-102](#)
- debug sw-vlan notification command [B-103](#)
- debug sw-vlan vtp command [B-105](#)
- debug ulld command [B-107](#)
- debug vqpc command [B-109](#)
- defaultPort profile [2-13, 2-14](#)

- define interface-range command [2-111](#)
- delete (boot loader) command [A-7](#)
- delete command [2-113](#)
- deny (ARP access-list configuration) command [2-114](#)
- deny (IPv6) command [2-116](#)
- deny command [2-119](#)
- detect mechanism, causes [2-159](#)
- DHCP snooping
  - accepting untrusted packets from edge switch [2-208](#)
  - enabling
    - on a VLAN [2-215](#)
    - option 82 [2-206, 2-208](#)
    - trust on an interface [2-213](#)
  - error recovery timer [2-165](#)
  - rate limiting [2-212](#)
- DHCP snooping binding database
  - binding file, configuring [2-204](#)
  - bindings
    - adding [2-202](#)
    - deleting [2-202](#)
    - displaying [2-548](#)
  - clearing database agent statistics [2-81](#)
  - database agent, configuring [2-204](#)
  - displaying
    - binding entries [2-548](#)
    - database agent status [2-551, 2-553](#)
  - renewing [2-429](#)
- dir (boot loader) command [A-8](#)
- directories, deleting [2-113](#)
- domain name, VTP [2-835](#)
- dot1x auth-fail max-attempts [2-124](#)
- dot1x auth-fail vlan [2-126](#)
- dot1x command [2-122](#)
- dot1x control-direction command [2-128](#)
- dot1x credentials (global configuration) command [2-130](#)
- dot1x critical global configuration command [2-131](#)
- dot1x critical interface configuration command [2-133](#)
- dot1x default command [2-135](#)
- dot1x fallback command [2-136](#)
- dot1x guest-vlan command [2-137](#)
- dot1x host-mode command [2-139](#)
- dot1x initialize command [2-141](#)
- dot1x mac-auth-bypass command [2-142](#)
- dot1x max-reauth-req command [2-144](#)
- dot1x max-req command [2-145](#)
- dot1x pae command [2-146](#)
- dot1x port-control command [2-147](#)
- dot1x re-authenticate command [2-149](#)
- dot1x reauthentication command [2-150](#)
- dot1x supplicant force-multicast command [2-151](#)
- dot1x test eapol-capable command [2-152](#)
- dot1x test timeout command [2-153](#)
- dot1x timeout command [2-154](#)
- dot1x violation-mode command [2-156](#)
- dropping packets, with ACL matches [2-6](#)
- drop threshold, Layer 2 protocol tunneling [2-275](#)
- DSCP-to-CoS map [2-334](#)
- DSCP-to-DSCP-mutation map [2-334](#)
- DTP [2-779](#)
- DTP flap
  - error detection for [2-159](#)
  - error recovery timer [2-165](#)
- DTP negotiation [2-783](#)
- dual-purpose uplink ports
  - selecting the type [2-324](#)
- duplex command [2-157](#)
- dynamic-access ports
  - configuring [2-767](#)
  - restrictions [2-768](#)
- dynamic ARP inspection
  - ARP ACLs
    - apply to a VLAN [2-188](#)
    - define [2-24](#)
    - deny packets [2-114](#)
    - display [2-469](#)
    - permit packets [2-385](#)
  - clear
    - log buffer [2-79](#)

- statistics [2-80](#)
- display
  - ARP ACLs [2-469](#)
  - configuration and operating state [2-543](#)
  - log buffer [2-543](#)
  - statistics [2-543](#)
  - trust state and rate limit [2-543](#)
- enable per VLAN [2-198](#)
- error detection for [2-159](#)
- log buffer
  - clear [2-79](#)
  - configure [2-192](#)
  - display [2-543](#)
- rate-limit incoming ARP packets [2-190](#)
- statistics
  - clear [2-80](#)
  - display [2-543](#)
- trusted interface state [2-194](#)
- type of packet logged [2-199](#)
- validation checks [2-196](#)
- dynamic auto VLAN membership mode [2-778](#)
- dynamic desirable VLAN membership mode [2-778](#)
- Dynamic Host Configuration Protocol (DHCP)
  - See DHCP snooping
- Dynamic Trunking Protocol
  - See DTP

---

## E

- EAP-request/identity frame
  - maximum number to send [2-145](#)
  - response time before retransmitting [2-154](#)
- environmental alarms, displaying [2-467](#)
- environment variables, displaying [2-478](#)
- errdisable detect cause command [2-159](#)
- errdisable detect cause small-frame comand [2-162](#)
- errdisable recovery cause small-frame [2-164](#)
- errdisable recovery command [2-165](#)
- error conditions, displaying [2-517](#)
- error disable detection [2-159](#)
- error-disabled interfaces, displaying [2-529](#)
- EtherChannel
  - assigning Ethernet interface to channel group [2-65](#)
  - creating port-channel logical interface [2-174](#)
  - debug EtherChannel/PAgP, display [B-14](#)
  - debug platform-specific events, display [B-39](#)
  - displaying [2-520](#)
  - enabling Layer 2 protocol tunneling for
    - LACP [2-276](#)
    - PAgP [2-276](#)
    - UDLD [2-276](#)
  - interface information, displaying [2-529](#)
- LACP
  - clearing channel-group information [2-86](#)
  - debug messages, display [B-21](#)
  - displaying [2-586](#)
  - modes [2-65](#)
  - port priority for hot-standby ports [2-279](#)
  - restricting a protocol [2-68](#)
  - system priority [2-281](#)
- load-distribution methods [2-403](#)
- PAgP
  - aggregate-port learner [2-381](#)
  - clearing channel-group information [2-90](#)
  - debug messages, display [B-31](#)
  - displaying [2-643](#)
  - error detection for [2-159](#)
  - error recovery timer [2-165](#)
  - learn method [2-381](#)
  - modes [2-65](#)
  - physical-port learner [2-381](#)
  - priority of interface for transmitted traffic [2-383](#)
- Ethernet controller, internal register display [2-495](#)
- Ethernet statistics, collecting [2-445](#)
- exception crashinfo command [2-168](#)
- extended discovery of candidate switches [2-101](#)
- extended-range VLANs
  - and allowed VLAN list [2-798](#)

- and pruning-eligible list [2-798](#)
- configuring [2-819](#)

extended system ID for STP [2-717](#)

---

## F

facility alarm relays, displaying [2-523](#)

facility alarm status, displaying [2-524](#)

fallback profile command [2-169](#)

fallback profiles, displaying [2-525](#)

FCS bit error rate

- displaying [2-526](#)
- fluctuation threshold [2-8](#)
- setting [2-171](#)

FCS hysteresis threshold [2-8](#)

fcs-threshold command [2-171](#)

file name, VTP [2-835](#)

files, deleting [2-113](#)

flash\_init (boot loader) command [A-10](#)

flexible authentication ordering [2-42](#)

Flex Links

- configuring [2-771](#)
- configuring preferred VLAN [2-773](#)
- displaying [2-529](#)

flowcontrol command [2-172](#)

format (boot loader) command [A-11](#)

forwarding packets, with ACL matches [2-6](#)

forwarding results, display [C-6](#)

frame check sequence

- See FCS

frame forwarding information, displaying [C-6](#)

fsck (boot loader) command [A-12](#)

---

## G

global configuration mode [1-2, 1-3](#)

---

## H

hardware ACL statistics [2-461](#)

help (boot loader) command [A-13](#)

hierarchical policy maps [2-401](#)

hop-count limit for clusters [2-101](#)

host connection, port configuration [2-777](#)

host ports, private VLANs [2-781](#)

Hot Standby Router Protocol

- See HSRP

HSRP

- binding HSRP group to cluster [2-108](#)
- standby group [2-108](#)

---

## I

IEEE 802.1Q trunk ports and native VLANs [2-826](#)

IEEE 802.1Q tunnel ports

- displaying [2-506](#)
- limitations [2-779](#)

IEEE 802.1x

- and switchport modes [2-779](#)
- violation error recovery [2-165](#)
- See also port-based authentication

IEEE 802.1X Port Based Authentication

- enabling guest VLAN supplicant [2-125, 2-136, 2-170](#)

IGMP filters

- applying [2-218](#)
- debug messages, display [B-18](#)

IGMP groups, setting maximum [2-220](#)

IGMP maximum groups, debugging [B-19](#)

IGMP profiles

- creating [2-222](#)
- displaying [2-556](#)

IGMP snooping

- adding ports as a static member of a group [2-238](#)
- displaying [2-557](#)
- enabling [2-224](#)
- enabling the configurable-leave timer [2-226](#)

- enabling the Immediate-Leave feature [2-235](#)
- flooding query count [2-232](#)
- interface topology change notification behavior [2-234](#)
- querier [2-228](#)
- query solicitation [2-232](#)
- report suppression [2-230](#)
- switch topology change notification behavior [2-232](#)
- images
  - See software images
- Immediate-Leave feature, MVR [2-371](#)
- immediate-leave processing [2-235](#)
- Immediate-Leave processing, IPv6 [2-271](#)
- interface configuration mode [1-2, 1-4](#)
- interface port-channel command [2-174](#)
- interface range command [2-176](#)
- interface-range macros [2-111](#)
- interfaces
  - assigning Ethernet interface to channel group [2-65](#)
  - configuring [2-157](#)
  - configuring multiple [2-176](#)
  - creating port-channel logical [2-174](#)
  - debug messages, display [B-15](#)
  - disabling [2-695](#)
  - displaying the MAC address table [2-605](#)
  - restarting [2-695](#)
- interface speed, configuring [2-754](#)
- interface vlan command [2-178](#)
- internal registers, displaying [2-495, 2-502](#)
- Internet Group Management Protocol
  - See IGMP
- invalid GBIC
  - error detection for [2-159](#)
  - error recovery timer [2-165](#)
- ip access-group command [2-180](#)
- ip address command [2-183](#)
- IP addresses, setting [2-183](#)
- IP address matching [2-319](#)
- ip admission command [2-185](#)
- ip admission name proxy http command [2-186](#)
- ip arp inspection filter vlan command [2-188](#)
- ip arp inspection limit command [2-190](#)
- ip arp inspection log-buffer command [2-192](#)
- ip arp inspection trust command [2-194](#)
- ip arp inspection validate command [2-196](#)
- ip arp inspection vlan command [2-198](#)
- ip arp inspection vlan logging command [2-199](#)
- IP DHCP snooping
  - See DHCP snooping
- ip dhcp snooping binding command [2-202](#)
- ip dhcp snooping command [2-201](#)
- ip dhcp snooping database command [2-204](#)
- ip dhcp snooping information option allow-untrusted command [2-208](#)
- ip dhcp snooping information option command [2-206](#)
- ip dhcp snooping information option format remote-id command [2-210](#)
- ip dhcp snooping limit rate command [2-212](#)
- ip dhcp snooping trust command [2-213](#)
- ip dhcp snooping verify command [2-214](#)
- ip dhcp snooping vlan command [2-215](#)
- ip dhcp snooping vlan information option format-type circuit-id string command [2-216](#)
- ip igmp filter command [2-218](#)
- ip igmp max-groups command [2-220, 2-244, 2-246](#)
- ip igmp profile command [2-222](#)
- ip igmp snooping command [2-224](#)
- ip igmp snooping last-member-query-interval command [2-226](#)
- ip igmp snooping querier command [2-228](#)
- ip igmp snooping report-suppression command [2-230](#)
- ip igmp snooping tcn command [2-232](#)
- ip igmp snooping tcn flood command [2-234](#)
- ip igmp snooping vlan immediate-leave command [2-235](#)
- ip igmp snooping vlan mrouter command [2-236](#)
- ip igmp snooping vlan static command [2-238](#)
- IP multicast addresses [2-368](#)
- IP phones
  - auto-QoS configuration [2-54](#)
  - trusting packets sent from [2-360](#)



IP-precedence-to-DSCP map [2-334](#)  
 ip source binding command [2-240](#)  
 IP source guard  
   disabling [2-248](#)  
   displaying  
     binding entries [2-564](#)  
     configuration [2-565](#)  
     dynamic binding entries only [2-548](#)  
   enabling [2-248](#)  
   static IP source bindings [2-240](#)  
 ip ssh command [2-242](#)  
 IPv6 access list, deny conditions [2-116](#)  
 ipv6 access-list command [2-250](#)  
 ipv6 address dhcp command [2-253](#)  
 ipv6 dhcp client request vendor command [2-254](#)  
 ipv6 dhcp ping packets command [2-255](#)  
 ipv6 dhcp pool command [2-256](#)  
 ipv6 dhcp server command [2-258](#)  
 ipv6 mld snooping command [2-260](#)  
 ipv6 mld snooping last-listener-query count  
 command [2-262](#)  
 ipv6 mld snooping last-listener-query-interval  
 command [2-264](#)  
 ipv6 mld snooping listener-message-suppression  
 command [2-266](#)  
 ipv6 mld snooping robustness-variable command [2-267](#)  
 ipv6 mld snooping tcn command [2-269](#)  
 ipv6 mld snooping vlan command [2-271](#)  
 IPv6 SDM template [2-446](#)  
 ipv6 traffic-filter command [2-273](#)  
 ip verify source command [2-248](#)

---

## J

jumbo frames  
   See MTU

---

## L

l2protocol-tunnel command [2-275](#)  
 l2protocol-tunnel cos command [2-278](#)  
 LACP  
   See EtherChannel  
 lacp port-priority command [2-279](#)  
 lacp system-priority command [2-281](#)  
 Layer 2 mode, enabling [2-765](#)  
 Layer 2 protocol ports, displaying [2-583](#)  
 Layer 2 protocol tunnel counters [2-85](#)  
 Layer 2 protocol tunneling error recovery [2-276](#)  
 Layer 2 traceroute  
   IP addresses [2-810](#)  
   MAC addresses [2-807](#)  
 Layer 3 mode, enabling [2-765](#)  
 line configuration mode [1-2, 1-4](#)  
 Link Aggregation Control Protocol  
   See EtherChannel  
 link flap  
   error detection for [2-159](#)  
   error recovery timer [2-165](#)  
 link state group command [2-287](#)  
 link state track command [2-289](#)  
 load-distribution methods for EtherChannel [2-403](#)  
 location (global configuration) command [2-283](#)  
 location (interface configuration) command [2-285](#)  
 logging event command [2-290](#)  
 logging file command [2-291](#)  
 logical interface [2-174](#)  
 loopback error  
   detection for [2-159](#)  
   recovery timer [2-165](#)  
 loop guard, for spanning tree [2-719, 2-723](#)

---

## M

mab request format attribute 32 command [2-293](#)  
 mac access-group command [2-295](#)

- MAC access list configuration mode [2-297](#)
- mac access-list extended command [2-297](#)
- MAC access lists [2-119](#)
- MAC addresses
  - disabling MAC address learning per VLAN [2-300](#)
  - displaying
    - aging time [2-599](#)
    - all [2-597](#)
    - dynamic [2-603](#)
    - MAC address-table move updates [2-608](#)
    - notification settings [2-607, 2-610](#)
    - number of addresses in a VLAN [2-601](#)
    - per interface [2-605](#)
    - per VLAN [2-614](#)
    - static [2-612](#)
    - static and dynamic entries [2-595](#)
  - dynamic
    - aging time [2-299](#)
    - deleting [2-87](#)
    - displaying [2-603](#)
  - enabling MAC address notification [2-304](#)
  - enabling MAC address-table move update [2-302](#)
  - matching [2-319](#)
  - static
    - adding and removing [2-306](#)
    - displaying [2-612](#)
    - dropping on an interface [2-307](#)
  - tables [2-597](#)
- MAC address notification, debugging [B-23](#)
- mac address-table aging-time [2-295](#)
- mac address-table aging-time command [2-299](#)
- mac address-table learning command [2-300](#)
- mac address-table move update command [2-302](#)
- mac address-table notification command [2-304](#)
- mac address-table static command [2-306](#)
- mac address-table static drop command [2-307](#)
- macro apply command [2-309](#)
- macro description command [2-312](#)
- macro global command [2-313](#)
- macro global description command [2-316](#)
- macro name command [2-317](#)
- macros
  - adding a description [2-312](#)
  - adding a global description [2-316](#)
  - applying [2-313](#)
  - creating [2-317](#)
  - displaying [2-645](#)
  - interface range [2-111, 2-176](#)
  - specifying parameter values [2-313](#)
  - tracing [2-313](#)
- maps
  - QoS
    - defining [2-334](#)
    - displaying [2-624](#)
  - VLAN
    - creating [2-824](#)
    - defining [2-319](#)
    - displaying [2-686](#)
- match (access-map configuration) command [2-319](#)
- match (class-map configuration) command [2-321](#)
- maximum transmission unit
  - See MTU
- mdix auto command [2-323](#)
- media-type command [2-324](#)
- member switches
  - See clusters
- memory (boot loader) command [A-14](#)
- mkdir (boot loader) command [A-15](#)
- MLD snooping
  - configuring [2-266, 2-267](#)
  - configuring queries [2-262, 2-264](#)
  - configuring topology change notification [2-269](#)
  - displaying [2-573, 2-575, 2-579](#)
  - enabling [2-260](#)
- MLD snooping on a VLAN, enabling [2-271](#)
- mls qos aggregate-policer command [2-328](#)
- mls qos command [2-326](#)
- mls qos cos command [2-330](#)

- mls qos dscp-mutation command [2-332](#)
- mls qos map command [2-334](#)
- mls qos queue-set output buffers command [2-338](#)
- mls qos queue-set output threshold command [2-340](#)
- mls qos rewrite ip dscp command [2-342](#)
- mls qos srr-queue input bandwidth command [2-344](#)
- mls qos srr-queue input buffers command [2-346](#)
- mls qos-srr-queue input cos-map command [2-348](#)
- mls qos srr-queue input dscp-map command [2-350](#)
- mls qos srr-queue input priority-queue command [2-352](#)
- mls qos srr-queue input threshold command [2-354](#)
- mls qos-srr-queue output cos-map command [2-356](#)
- mls qos srr-queue output dscp-map command [2-358](#)
- mls qos trust command [2-360](#)
- mls qos vlan-based command [2-362](#)
- mode, MVR [2-368](#)
- modes, commands [1-1](#)
- monitor session command [2-363](#)
- more (boot loader) command [A-16](#)
- MSTP
  - displaying [2-668](#)
  - interoperability [2-96](#)
  - link type [2-721](#)
  - MST region
    - aborting changes [2-727](#)
    - applying changes [2-727](#)
    - configuration name [2-727](#)
    - configuration revision number [2-727](#)
    - current or pending display [2-727](#)
    - displaying [2-668](#)
    - MST configuration mode [2-727](#)
    - VLANs-to-instance mapping [2-727](#)
  - path cost [2-729](#)
  - protocol mode [2-725](#)
  - restart protocol migration process [2-96](#)
  - root port
    - loop guard [2-719](#)
    - preventing from becoming designated [2-719](#)
    - restricting which can be root [2-719](#)
    - root guard [2-719](#)
  - root switch
    - affects of extended system ID [2-717](#)
    - hello-time [2-732, 2-740](#)
    - interval between BPDU messages [2-733](#)
    - interval between hello BPDU messages [2-732, 2-740](#)
    - max-age [2-733](#)
    - maximum hop count before discarding BPDU [2-734](#)
    - port priority for selection of [2-736](#)
    - primary or secondary [2-740](#)
    - switch priority [2-739](#)
  - state changes
    - blocking to forwarding state [2-746](#)
    - enabling BPDU filtering [2-709, 2-744](#)
    - enabling BPDU guard [2-711, 2-744](#)
    - enabling Port Fast [2-744, 2-746](#)
    - forward-delay time [2-731](#)
    - length of listening and learning states [2-731](#)
    - rapid transition to forwarding [2-721](#)
    - shutting down Port Fast-enabled ports [2-744](#)
  - state information display [2-667](#)
- MTU
  - configuring size [2-803](#)
  - displaying global setting [2-675](#)
- Multicast Listener Discovery
  - See MLD
- multicast group address, MVR [2-371](#)
- multicast groups, MVR [2-369](#)
- Multicast Listener Discovery
  - See MLD
- multicast router learning method [2-236](#)
- multicast router ports, configuring [2-236](#)
- multicast router ports, IPv6 [2-271](#)
- multicast storm control [2-762](#)
- multicast VLAN, MVR [2-368](#)
- multicast VLAN registration
  - See MVR

## Multiple Spanning Tree Protocol

See MSTP

## MVR

and address aliasing [2-369](#)configuring [2-368](#)configuring interfaces [2-371](#)debug messages, display [B-28](#)displaying [2-632](#)displaying interface information [2-634](#)members, displaying [2-636](#)mvr (global configuration) command [2-368](#)mvr (interface configuration) command [2-371](#)mvr vlan group command [2-372](#)**N**native VLANs [2-798](#)native VLAN tagging [2-826](#)network-policy (global configuration) command [2-375](#)network-policy command [2-374](#)network-policy profile (network-policy configuration) command [2-377](#)nmsp attachment suppress command [2-380](#)nmsp command [2-379](#)nonegotiate, speed [2-754](#)nonegotiating DTP messaging [2-783](#)

## non-IP protocols

denying [2-119](#)forwarding [2-393](#)non-IP traffic access lists [2-297](#)

## non-IP traffic forwarding

denying [2-119](#)permitting [2-393](#)normal-range VLANs [2-819](#)notifies command [2-12](#)no vlan command [2-819](#)**O**

## online diagnostics

## displaying

configured boot-up coverage level [2-506](#)current scheduled tasks [2-506](#)event logs [2-506](#)supported test suites [2-506](#)test ID [2-506](#)test results [2-506](#)test statistics [2-506](#)

## global configuration mode

clearing health monitoring diagnostic test schedule [2-79](#)setting health monitoring diagnostic testing [2-79](#)setting up health monitoring diagnostic test schedule [2-79](#)**P**

## PAgP

See EtherChannel

pagp learn-method command [2-381](#)pagp port-priority command [2-383](#)password, VTP [2-836](#)permit (ARP access-list configuration) command [2-385](#)permit (IPv6) command [2-387](#)permit (MAC access-list configuration) command [2-393](#)

## per-VLAN spanning-tree plus

See STP

physical-port learner [2-381](#)PID, displaying [2-542](#)PIM-DVMRP, as multicast router learning method [2-236](#)police aggregate command [2-398](#)police command [2-396](#)policed-DSCP map [2-334](#)policy-map command [2-400](#)

## policy maps

applying to an interface [2-451, 2-456](#)

- creating [2-400](#)
- displaying [2-648](#)
- hierarchical [2-401](#)
- policers
  - displaying [2-617](#)
  - for a single class [2-396](#)
  - for multiple classes [2-328, 2-398](#)
  - policed-DSCP map [2-334](#)
- traffic classification
  - defining the class [2-72](#)
  - defining trust states [2-812](#)
  - setting DSCP or IP precedence values [2-454](#)
- Port Aggregation Protocol
  - See EtherChannel
- port-based authentication
  - AAA method list [2-3](#)
  - configuring violation modes [2-156](#)
  - debug messages, display [B-11](#)
  - enabling IEEE 802.1x
    - globally [2-122](#)
    - per interface [2-147](#)
  - guest VLAN [2-137](#)
  - host modes [2-139](#)
  - IEEE 802.1x AAA accounting methods [2-1](#)
  - initialize an interface [2-141, 2-153](#)
  - MAC authentication bypass [2-142](#)
  - manual control of authorization state [2-147](#)
  - PAE as authenticator [2-146](#)
  - periodic re-authentication
    - enabling [2-150](#)
    - time between attempts [2-154](#)
  - quiet period between failed authentication exchanges [2-154](#)
  - re-authenticating IEEE 802.1x-enabled ports [2-149](#)
  - resetting configurable IEEE 802.1x parameters [2-135](#)
  - switch-to-authentication server retransmission time [2-154](#)
  - switch-to-client frame-retransmission number [2-144 to 2-145](#)
  - switch-to-client retransmission time [2-154](#)
  - test for IEEE 802.1x readiness [2-152](#)
  - port-channel load-balance command [2-403](#)
  - Port Fast, for spanning tree [2-746](#)
  - port ranges, defining [2-111](#)
  - ports, debugging [B-71](#)
  - ports, protected [2-796](#)
  - port security
    - aging [2-790](#)
    - debug messages, display [B-73](#)
    - enabling [2-785](#)
    - violation error recovery [2-165](#)
  - port trust states for QoS [2-360](#)
  - port types, MVR [2-371](#)
  - power supply alarms, setting [2-9](#)
  - power-supply dual command [2-405](#)
  - power-supply mode [2-405](#)
  - Precision Time Protocol
  - primary temperature alarm [2-10](#)
  - priority-queue command [2-406](#)
  - private-vlan command [2-408](#)
  - private-vlan mapping command [2-411](#)
  - private VLANs
    - association [2-794](#)
    - configuring [2-408](#)
    - configuring ports [2-781](#)
    - host ports [2-781](#)
    - mapping
      - configuring [2-794](#)
    - promiscuous ports [2-781](#)
  - privileged EXEC mode [1-2, 1-3](#)
  - product identification information, displaying [2-542](#)
  - profinet [2-413](#)
  - promiscuous ports, private VLANs [2-781](#)
  - protected ports, displaying [2-534](#)
  - pruning
    - VLANs [2-798](#)
    - VTP
      - displaying interface information [2-529](#)
      - enabling [2-836](#)

pruning-eligible VLAN list [2-799](#)

psp [2-415](#)

psp command [2-415](#)

ptp (global configuration) command [2-416](#)

ptp interface configuration command [2-418](#)

PTP settings [2-418](#)

PVST+

See STP

## Q

QoS

auto-QoS

configuring [2-54](#)

debug messages, display [B-4](#)

displaying [2-474](#)

class maps

creating [2-74](#)

defining the match criteria [2-321](#)

displaying [2-486](#)

defining the CoS value for an incoming packet [2-330](#)

displaying configuration information [2-474, 2-616](#)

DSCP transparency [2-342](#)

DSCP trusted ports

applying DSCP-to-DSCP-mutation map to [2-332](#)

defining DSCP-to-DSCP-mutation map [2-334](#)

egress queues

allocating buffers [2-338](#)

defining the CoS output queue threshold map [2-356](#)

defining the DSCP output queue threshold map [2-358](#)

displaying buffer allocations [2-620](#)

displaying CoS output queue threshold map [2-624](#)

displaying DSCP output queue threshold map [2-624](#)

displaying queueing strategy [2-620](#)

displaying queue-set settings [2-627](#)

enabling bandwidth shaping and scheduling [2-758](#)

enabling bandwidth sharing and scheduling [2-760](#)

limiting the maximum output on a port [2-756](#)

mapping a port to a queue-set [2-420](#)

mapping CoS values to a queue and threshold [2-356](#)

mapping DSCP values to a queue and threshold [2-358](#)

setting maximum and reserved memory allocations [2-340](#)

setting WTD thresholds [2-340](#)

enabling [2-326](#)

ingress queues

allocating buffers [2-346](#)

assigning SRR scheduling weights [2-344](#)

defining the CoS input queue threshold map [2-348](#)

defining the DSCP input queue threshold map [2-350](#)

displaying buffer allocations [2-620](#)

displaying CoS input queue threshold map [2-624](#)

displaying DSCP input queue threshold map [2-624](#)

displaying queueing strategy [2-620](#)

displaying settings for [2-618](#)

enabling the priority queue [2-352](#)

mapping CoS values to a queue and threshold [2-348](#)

mapping DSCP values to a queue and threshold [2-350](#)

setting WTD thresholds [2-354](#)

maps

defining [2-334, 2-348, 2-350, 2-356, 2-358](#)

displaying [2-624](#)

policy maps

applying an aggregate policer [2-398](#)

applying to an interface [2-451, 2-456](#)

creating [2-400](#)

defining policers [2-328, 2-396](#)

displaying policers [2-617](#)

- displaying policy maps [2-648](#)
- hierarchical [2-401](#)
- policed-DSCP map [2-334](#)
- setting DSCP or IP precedence values [2-454](#)
- traffic classifications [2-72](#)
- trust states [2-812](#)
- port trust states [2-360](#)
- queues, enabling the expedite [2-406](#)
- statistics
  - in-profile and out-of-profile packets [2-620](#)
  - packets enqueued or dropped [2-620](#)
  - sent and received CoS values [2-620](#)
  - sent and received DSCP values [2-620](#)
- trusted boundary for IP phones [2-360](#)
- VLAN-based [2-362](#)
- quality of service
  - See QoS
- querytime, MVR [2-368](#)
- queue-set command [2-420](#)

---

## R

- radius-server dead-criteria command [2-421](#)
- radius-server host command [2-423](#)
- rapid per-VLAN spanning-tree plus
  - See STP
- rapid PVST+
  - See STP
- rcommand command [2-425](#)
- re-authenticating IEEE 802.1x-enabled ports [2-149](#)
- re-authentication
  - periodic [2-150](#)
  - time between attempts [2-154](#)
- receiver ports, MVR [2-371](#)
- receiving flow-control packets [2-172](#)
- recovery mechanism
  - causes [2-165](#)
  - display [2-78](#), [2-480](#), [2-516](#), [2-518](#)
  - timer interval [2-166](#)

- redundancy for cluster switches [2-108](#)
- relay-major command [2-12](#)
- relay-minor command [2-12](#)
- remote-span command [2-427](#)
- Remote Switched Port Analyzer
  - See RSPAN
- rename (boot loader) command [A-17](#)
- renew ip dhcp snooping database command [2-429](#)
- rep admin vlan command [2-431](#)
- rep block port command [2-432](#)
- rep lsl-age-timer command [2-435](#)
- rep preempt delay command [2-437](#)
- rep preempt segment command [2-439](#)
- rep segment command [2-440](#)
- rep stcn command [2-443](#)
- reset (boot loader) command [A-18](#)
- resource templates, displaying [2-663](#)
- restricted VLAN
  - See dot1x auth-fail vlan
- rmdir (boot loader) command [A-19](#)
- rmon collection stats command [2-445](#)
- root guard, for spanning tree [2-719](#)

- routed ports
  - IP addresses on [2-184](#)
  - number supported [2-184](#)

- RSPAN
  - configuring [2-363](#)
  - displaying [2-630](#)
  - filter RSPAN traffic [2-363](#)
  - remote-span command [2-427](#)
  - sessions
    - displaying [2-630](#)

---

## S

- sdm prefer command [2-446](#)
- SDM templates
  - displaying [2-663](#)
  - dual IPv4 and IPv6 [2-446](#)

- secondary temperature alarm [2-10](#)
- secure ports, limitations [2-787](#)
- see PTP
- sending flow-control packets [2-172](#)
- service password-recovery command [2-449](#)
- service-policy command [2-451](#)
- set (boot loader) command [A-20](#)
- set command [2-454](#)
- setup command [2-456](#)
- setup express command [2-459](#)
- show access-lists command [2-461](#)
- show alarm description port [2-464](#)
- show alarm description port command [2-464](#)
- show alarm profile command [2-465](#)
- show alarm settings command [2-467](#)
- show archive status command [2-468](#)
- show arp access-list command [2-469](#)
- show authentication command [2-470](#)
- show auto qos command [2-474](#)
- show boot command [2-478](#)
- show cable-diagnostics tdr command [2-480](#)
- show cisp command [2-485](#)
- show class-map command [2-486](#)
- show cluster candidates command [2-489](#)
- show cluster command [2-487](#)
- show cluster members command [2-491](#)
- show controllers cpu-interface command [2-493](#)
- show controllers ethernet-controller command [2-495](#)
- show controllers tcam command [2-502](#)
- show controller utilization command [2-504](#)
- show dot1q-tunnel command [2-506](#)
- show dot1x command [2-507](#)
- show dtp [2-511](#)
- show eap command [2-513](#)
- show env command [2-515](#)
- show errdisable detect command [2-516](#)
- show errdisable flap-values command [2-517](#)
- show errdisable recovery command [2-518](#)
- show etherchannel command [2-520](#)
- show facility-alarm relay command [2-523](#)
- show facility-alarm status [2-523](#)
- show facility-alarm status command [2-524](#)
- show fallback profile command [2-525](#)
- show fcs threshold command [2-526](#)
- show flowcontrol command [2-528](#)
- show interface rep command [2-540](#)
- show interfaces command [2-529](#)
- show interfaces counters command [2-538](#)
- show interfaces rep command [2-540](#)
- show inventory command [2-542](#)
- show ip arp inspection command [2-543](#)
- show ipc command [2-567](#)
- show ip dhcp snooping binding command [2-548](#)
- show ip dhcp snooping command [2-547](#)
- show ip dhcp snooping database command [2-551, 2-553](#)
- show ip igmp profile command [2-556](#)
- show ip igmp snooping address command [2-575](#)
- show ip igmp snooping command [2-557, 2-573](#)
- show ip igmp snooping groups command [2-559](#)
- show ip igmp snooping mrouter command [2-561, 2-577](#)
- show ip igmp snooping querier command [2-562, 2-579](#)
- show ip source binding command [2-564](#)
- show ipv6 access-list command [2-570](#)
- show ipv6 dhcp conflict command [2-572](#)
- show ipv6 route updated [2-581](#)
- show ip verify source command [2-565](#)
- show l2protocol-tunnel command [2-583](#)
- show lacp command [2-586](#)
- show link state group command [2-592](#)
- show location [2-590](#)
- show mac access-group command [2-594](#)
- show mac address-table address command [2-597](#)
- show mac address-table aging time command [2-599](#)
- show mac address-table command [2-595](#)
- show mac address-table count command [2-601](#)
- show mac address-table dynamic command [2-603](#)
- show mac address-table interface command [2-605](#)
- show mac address-table learning command [2-607](#)



- show mac address-table move update command [2-608](#)
- show mac address-table notification command [2-88, 2-610, B-25](#)
- show mac address-table static command [2-612](#)
- show mac address-table vlan command [2-614](#)
- show mls qos aggregate-policer command [2-617](#)
- show mls qos command [2-616](#)
- show mls qos input-queue command [2-618](#)
- show mls qos interface command [2-620](#)
- show mls qos maps command [2-624](#)
- show mls qos queue-set command [2-627](#)
- show mls qos vlan command [2-629](#)
- show monitor command [2-630](#)
- show mvr command [2-632](#)
- show mvr interface command [2-634](#)
- show mvr members command [2-636](#)
- show network-policy profile command [2-638](#)
- show nmsp command [2-640](#)
- show pagp command [2-643](#)
- show parser macro command [2-645](#)
- show platform acl command [C-2](#)
- show platform backup interface command [C-3](#)
- show platform configuration command [C-4](#)
- show platform etherchannel command [C-5](#)
- show platform forward command [C-6](#)
- show platform igmp snooping command [C-8](#)
- show platform ip multicast command [C-9](#)
- show platform ip unicast command [C-10](#)
- show platform ipv6 unicast command [C-14](#)
- show platform ip wccp command [C-13](#)
- show platform layer4op command [C-16](#)
- show platform mac-address-table command [C-17](#)
- show platform messaging command [C-18](#)
- show platform monitor command [C-19](#)
- show platform mvr table command [C-20](#)
- show platform pm command [C-21](#)
- show platform port-asic command [C-22](#)
- show platform port-security command [C-26](#)
- show platform qos command [C-27](#)
- show platform resource-manager command [C-28](#)
- show platform snmp counters command [C-30](#)
- show platform spanning-tree command [C-31](#)
- show platform stp-instance command [C-32](#)
- show platform team command [C-33](#)
- show platform vlan command [C-36](#)
- show policy-map command [2-648](#)
- show port security command [2-650](#)
- show profinet [2-653](#)
- show psp config [2-655](#)
- show psp config command [2-655](#)
- show psp statistics [2-656](#)
- show psp statistics command [2-656](#)
- show ptp command [2-657](#)
- show rep topology command [2-660](#)
- show sdm prefer command [2-663](#)
- show setup express command [2-666](#)
- show spanning-tree command [2-667](#)
- show storm-control command [2-673](#)
- show system mtu command [2-675](#)
- show trust command [2-812](#)
- show uddl command [2-676](#)
- show version command [2-679](#)
- show vlan access-map command [2-686](#)
- show vlan command [2-681](#)
- show vlan command, fields [2-683](#)
- show vlan filter command [2-687](#)
- show vmmps command [2-688](#)
- show vtp command [2-690](#)
- shutdown command [2-695](#)
- shutdown threshold, Layer 2 protocol tunneling [2-275](#)
- shutdown vlan command [2-696](#)
- small violation-rate command [2-697](#)
- Smartports macros
  - See macros
- SNMP host, specifying [2-703](#)
- SNMP informs, enabling the sending of [2-699](#)
- snmp-server enable traps command [2-699](#)
- snmp-server host command [2-703](#)

- snmp trap mac-notification change command [2-706](#)
- SNMP traps
  - enabling MAC address notification trap [2-706](#)
  - enabling the MAC address notification feature [2-304](#)
  - enabling the sending of [2-699](#)
- SoftPhone
  - See Cisco SoftPhone
- software images
  - deleting [2-113](#)
  - downloading [2-16](#)
  - upgrading [2-16](#)
  - uploading [2-22](#)
- software version, displaying [2-679](#)
- source ports, MVR [2-371](#)
- SPAN
  - configuring [2-363](#)
  - debug messages, display [B-26](#)
  - displaying [2-630](#)
  - filter SPAN traffic [2-363](#)
  - sessions
    - add interfaces to [2-363](#)
    - displaying [2-630](#)
    - start new [2-363](#)
- spanning-tree backbonefast command [2-708](#)
- spanning-tree bpdudfilter command [2-709](#)
- spanning-tree bpduguard command [2-711](#)
- spanning-tree cost command [2-713](#)
- spanning-tree etherchannel command [2-715](#)
- spanning-tree extend system-id command [2-717](#)
- spanning-tree guard command [2-719](#)
- spanning-tree link-type command [2-721](#)
- spanning-tree loopguard default command [2-723](#)
- spanning-tree mode command [2-725](#)
- spanning-tree mst configuration command [2-727](#)
- spanning-tree mst cost command [2-729](#)
- spanning-tree mst forward-time command [2-731](#)
- spanning-tree mst hello-time command [2-732](#)
- spanning-tree mst max-age command [2-733](#)
- spanning-tree mst max-hops command [2-734](#)
- spanning-tree mst port-priority command [2-736](#)
- spanning-tree mst pre-standard command [2-738](#)
- spanning-tree mst priority command [2-739](#)
- spanning-tree mst root command [2-740](#)
- spanning-tree portfast (global configuration) command [2-744](#)
- spanning-tree portfast (interface configuration) command [2-746](#)
- spanning-tree port-priority command [2-742](#)
- Spanning Tree Protocol
  - See STP
- spanning-tree transmit hold-count command [2-748](#)
- spanning-tree uplinkfast command [2-749](#)
- spanning-tree vlan command [2-751](#)
- speed command [2-754](#)
- srr-queue bandwidth limit command [2-756](#)
- srr-queue bandwidth share command [2-760](#)
- SSH, configuring version [2-242](#)
- static-access ports, configuring [2-767](#)
- statistics, Ethernet group [2-445](#)
- sticky learning, enabling [2-785](#)
- storm-control command [2-762](#)
- STP
  - BackboneFast [2-708](#)
  - counters, clearing [2-95](#)
  - debug messages, display
    - BackboneFast events [B-92](#)
    - MSTP [B-95](#)
    - optimized BPDUs handling [B-94](#)
    - spanning-tree activity [B-90](#)
    - switch shim [B-97](#)
    - transmitted and received BPDUs [B-93](#)
    - UplinkFast [B-99](#)
  - detection of indirect link failures [2-708](#)
  - enabling protocol tunneling for [2-275](#)
  - EtherChannel misconfiguration [2-715](#)
  - extended system ID [2-717](#)
  - path cost [2-713](#)
  - protocol modes [2-725](#)

- root port
    - accelerating choice of new [2-749](#)
    - loop guard [2-719](#)
    - preventing from becoming designated [2-719](#)
    - restricting which can be root [2-719](#)
    - root guard [2-719](#)
    - UplinkFast [2-749](#)
  - root switch
    - affects of extended system ID [2-717, 2-752](#)
    - hello-time [2-751](#)
    - interval between BPDU messages [2-751](#)
    - interval between hello BPDU messages [2-751](#)
    - max-age [2-751](#)
    - port priority for selection of [2-742](#)
    - primary or secondary [2-751](#)
    - switch priority [2-751](#)
  - state changes
    - blocking to forwarding state [2-746](#)
    - enabling BPDU filtering [2-709, 2-744](#)
    - enabling BPDU guard [2-711, 2-744](#)
    - enabling Port Fast [2-744, 2-746](#)
    - enabling timer to recover from error state [2-165](#)
    - forward-delay time [2-751](#)
    - length of listening and learning states [2-751](#)
    - shutting down Port Fast-enabled ports [2-744](#)
  - state information display [2-667](#)
  - VLAN options [2-739, 2-751](#)
  - SVIs, creating [2-178](#)
  - SVI status calculation [2-769](#)
  - Switched Port Analyzer
    - See SPAN
  - switching characteristics
    - modifying [2-765](#)
    - returning to interfaces [2-765](#)
  - switchport access command [2-767](#)
  - switchport autostate exclude command [2-769](#)
  - switchport backup interface command [2-771](#)
  - switchport block command [2-775](#)
  - switchport command [2-765](#)
  - switchport host command [2-777](#)
  - switchport mode command [2-778](#)
  - switchport mode private-vlan command [2-781](#)
  - switchport nonegotiate command [2-783](#)
  - switchport port-security aging command [2-790](#)
  - switchport port-security command [2-785](#)
  - switchport priority extend command [2-792](#)
  - switchport private-vlan command [2-794](#)
  - switchport protected command [2-796](#)
  - switchports, displaying [2-529](#)
  - switchport trunk command [2-798](#)
  - switchport voice vlan command [2-801](#)
  - syslog command [2-12](#)
  - system message logging, save message to flash [2-291](#)
  - system mtu command [2-803](#)
  - system resource templates [2-446](#)
- 
- ## T
- tar files, creating, listing, and extracting [2-19](#)
  - TDR, running [2-805](#)
  - Telnet, using to communicate to cluster switches [2-425](#)
  - temperature alarms, setting [2-10](#)
  - templates, system resources [2-446](#)
  - test cable-diagnostics tdr command [2-805](#)
  - test relay [2-806](#)
  - test relay command [2-806](#)
  - traceroute mac command [2-807](#)
  - traceroute mac ip command [2-810](#)
  - trunking, VLAN mode [2-778](#)
  - trunk mode [2-778](#)
  - trunk ports [2-778](#)
  - trunks, to non-DTP device [2-779](#)
  - trusted boundary for QoS [2-360](#)
  - trusted port states for QoS [2-360](#)
  - tunnel ports, Layer 2 protocol, displaying [2-583](#)
  - type (boot loader) command [A-23](#)

**U****UDLD**

- aggressive mode [2-814, 2-816](#)
- debug messages, display [B-107](#)
- enable globally [2-814](#)
- enable per interface [2-816](#)
- error recovery timer [2-165](#)
- message timer [2-814](#)
- normal mode [2-814, 2-816](#)
- reset a shutdown interface [2-818](#)
- status [2-676](#)

udld command [2-814](#)

udld port command [2-816](#)

udld reset command [2-818](#)

unicast storm control [2-762](#)

UniDirectional Link Detection

See UDLD

unknown multicast traffic, preventing [2-775](#)

unknown unicast traffic, preventing [2-775](#)

unset (boot loader) command [A-25](#)

upgrading

software images

downloading [2-16](#)

monitoring status of [2-468](#)

UplinkFast, for STP [2-749](#)

user EXEC mode [1-2](#)

**V**

version (boot loader) command [A-27](#)

vlan (global configuration) command [2-819](#)

vlan access-map command [2-824](#)

VLAN access map configuration mode [2-824](#)

VLAN access maps

actions [2-6](#)

displaying [2-686](#)

VLAN-based QoS [2-362](#)

VLAN configuration

rules [2-822](#)

saving [2-819](#)

VLAN configuration mode

description [1-4](#)

entering [2-819](#)

summary [1-2](#)

vlan dot1q tag native command [2-826](#)

vlan filter command [2-828](#)

VLAN filters, displaying [2-687](#)

VLAN ID range [2-819](#)

VLAN maps

applying [2-828](#)

creating [2-824](#)

defining [2-319](#)

displaying [2-686](#)

VLAN Query Protocol

See VQP

VLANs

adding [2-819](#)

configuring [2-819](#)

debug messages, display

ISL [B-103](#)

VLAN IOS file system error tests [B-102](#)

VLAN manager activity [B-100](#)

VTP [B-105](#)

displaying configurations [2-681](#)

enabling guest VLAN supplicant [2-125, 2-136, 2-170](#)

extended-range [2-819](#)

MAC addresses

displaying [2-614](#)

number of [2-601](#)

media types [2-822](#)

normal-range [2-819](#)

private [2-781](#)

configuring [2-408](#)

See also private VLANs

restarting [2-696](#)

saving the configuration [2-819](#)

shutting down [2-696](#)

- SNMP traps for VTP [2-701](#)
- suspending [2-696](#)
- VLAN Trunking Protocol
  - See VTP
- VMPS
  - configuring servers [2-833](#)
  - displaying [2-688](#)
  - error recovery timer [2-166](#)
  - reconfirming dynamic VLAN assignments [2-830](#)
- vmmps reconfirm (global configuration) command [2-831](#)
- vmmps reconfirm (privileged EXEC) command [2-830](#)
- vmmps retry command [2-832](#)
- vmmps server command [2-833](#)
- voice VLAN
  - configuring [2-801](#)
  - setting port priority [2-792](#)
- VQP
  - and dynamic-access ports [2-768](#)
  - clearing client statistics [2-97](#)
  - displaying information [2-688](#)
  - per-server retry count [2-832](#)
  - reconfirmation interval [2-831](#)
  - reconfirming dynamic VLAN assignments [2-830](#)
- VTP
  - changing characteristics [2-835](#)
  - clearing pruning counters [2-98](#)
  - configuring
    - domain name [2-835](#)
    - file name [2-835](#)
    - mode [2-835](#)
    - password [2-836](#)
  - counters display fields [2-691](#)
  - displaying information [2-690](#)
  - enabling
    - pruning [2-836](#)
    - tunneling for [2-275](#)
    - Version 2 [2-836](#)
  - enabling per port [2-840](#)
  - mode [2-835](#)
  - pruning [2-836](#)
  - saving the configuration [2-819](#)
  - statistics [2-690](#)
  - status [2-690](#)
  - status display fields [2-693](#)
  - vtp (global configuration) command [2-835](#)
  - vtp interface configuration) command [2-840](#)
  - vtp primary command [2-841](#)

