



INDEX

A

- aaa accounting dot1x command [2-1](#)
- aaa authentication dot1x command [2-3](#)
- aaa authorization network command [2-5, 2-28, 2-34, 2-36, 2-38, 2-40, 2-42, 2-131, 2-293, 2-493, B-8, B-35](#)
- AAA methods [2-3](#)
- access control entries
 - See ACEs
- access control lists
 - See ACLs
- access groups
 - IP [2-181](#)
 - MAC, displaying [2-606](#)
- access list, IPv6 [2-249](#)
- access map configuration mode [2-319](#)
- access mode [2-794](#)
- access ports [2-794](#)
- ACEs [2-122, 2-395](#)
- ACLs
 - deny [2-120](#)
 - displaying [2-469](#)
 - for non-IP protocols [2-297](#)
 - IP [2-181](#)
 - matching [2-319](#)
 - on Layer 2 interfaces [2-181](#)
 - permit [2-393](#)
- action command [2-6](#)
- address aliasing [2-369](#)
- aggregate-port learner [2-381](#)
- alarm command [2-12](#)
- alarm facility fcs-hysteresis command [2-8](#)
- alarm facility power-supply command [2-9](#)
- alarm facility temperature command [2-10](#)
- alarm IDs [2-13, 2-472](#)
- alarm profile
 - attaching to a port [2-14](#)
 - creating [2-12](#)
 - displaying [2-473](#)
- alarm profile (global configuration) command [2-12](#)
- alarm profile (interface configuration) command [2-14](#)
- alarm profile configuration mode [2-12](#)
- allowed VLANs [2-814](#)
- archive download-sw command [2-16](#)
- archive tar command [2-19](#)
- archive upload-sw command [2-22](#)
- arp access-list command [2-24](#)
- authentication command bounce-port ignore [2-26](#)
- authentication command disable-port ignore [2-27](#)
- authentication control-direction command [2-28](#)
- authentication event command [2-30](#)
- authentication failed VLAN
 - See dot1x auth-fail vlan
- authentication fallback command [2-34](#)
- authentication host-mode command [2-36](#)
- authentication mac-move permit command [2-38](#)
- authentication open command [2-40](#)
- authentication order command [2-42](#)
- authentication periodic command [2-44](#)
- authentication port-control command [2-46](#)
- authentication priority command [2-48](#)
- authentication timer command [2-50](#)
- authentication violation command [2-52](#)
- auth-fail max-attempts
 - See dot1x auth-fail max-attempts
- auth-fail vlan

See dot1x auth-fail vlan

auth open command [2-40](#)
 auth order command [2-42](#)
 authorization state of controlled port [2-148](#)
 auth timer command [2-50](#)
 autonegotiation of duplex mode [2-159](#)
 auto qos voip command [2-54](#)

B

BackboneFast, for STP [2-724](#)

backup interfaces

configuring [2-787](#)
 displaying [2-540](#)

boot (boot loader) command [A-2](#)

boot config-file command [2-58](#)

boot enable-break command [2-59](#)

boot fast command [2-60](#)

boot helper command [2-61](#)

boot helper-config file command [2-62](#)

booting

Cisco IOS image [2-65](#)
 displaying environment variables [2-486](#)
 interrupting [2-59](#)
 manually [2-63](#)

boot loader

accessing [A-1](#)

booting

Cisco IOS image [A-2](#)
 helper image [2-61](#)

directories

creating [A-15](#)
 displaying a list of [A-8](#)
 removing [A-19](#)

displaying

available commands [A-13](#)
 memory heap utilization [A-14](#)
 version [A-27](#)

environment variables

described [A-20](#)

displaying settings [A-20](#)

location of [A-21](#)

setting [A-20](#)

unsetting [A-25](#)

files

copying [A-6](#)

deleting [A-7](#)

displaying a list of [A-8](#)

displaying the contents of [A-4, A-16, A-23](#)

renaming [A-17](#)

file system

formatting [A-11](#)

initializing flash [A-10](#)

running a consistency check [A-12](#)

resetting the system [A-18](#)

boot manual command [2-63](#)

boot private-config-file command [2-64](#)

boot system command [2-65](#)

BPDU filtering, for spanning tree [2-725, 2-760](#)

BPDU guard, for spanning tree [2-727, 2-760](#)

broadcast storm control [2-778](#)

C

candidate switches

See clusters

cat (boot loader) command [A-4](#)

channel-group command [2-66](#)

channel-protocol command [2-69](#)

Cisco SoftPhone

auto-QoS configuration [2-54](#)

trusting packets sent from [2-360](#)

CISP

See Client Information Signalling Protocol

cisp

debug platform cisp command [B-35](#)

cisp enable command [2-72](#)

class command [2-73](#)

- class-map command [2-75](#)
 - class maps
 - creating [2-75](#)
 - defining the match criteria [2-321](#)
 - displaying [2-494](#)
 - class of service
 - See CoS
 - clear dot1x command [2-77](#)
 - clear eap sessions command [2-78](#)
 - clear errdisable interface [2-79](#)
 - clear ip arp inspection log command [2-80](#)
 - clear ip arp inspection statistics command [2-81](#)
 - clear ipc command [2-84](#)
 - clear ip dhcp snooping database command [2-82](#)
 - clear ipv6 dhcp conflict command [2-85](#)
 - clear l2protocol-tunnel counters command [2-86](#)
 - clear lacp command [2-87](#)
 - clear mac address-table command [2-88, 2-89](#)
 - clear nmsp statistics command [2-90](#)
 - clear pagp command [2-91, 2-95](#)
 - clear port-security command [2-92](#)
 - clear psp counter [2-94](#)
 - clear psp counter command [2-94](#)
 - clear spanning-tree counters command [2-96](#)
 - clear spanning-tree detected-protocols command [2-97](#)
 - clear vmps statistics command [2-98](#)
 - clear vtp counters command [2-99](#)
 - Client Information Signalling Protocol [2-72, 2-131, 2-493, B-8, B-35](#)
 - cluster commander-address command [2-100](#)
 - cluster discovery hop-count command [2-102](#)
 - cluster enable command [2-103](#)
 - cluster holdtime command [2-104](#)
 - cluster member command [2-105](#)
 - cluster outside-interface command [2-107](#)
 - cluster run command [2-108](#)
 - clusters
 - adding candidates [2-105](#)
 - binding to HSRP group [2-109](#)
 - building manually [2-105](#)
 - communicating with
 - devices outside the cluster [2-107](#)
 - members by using Telnet [2-432](#)
 - debug messages, display [B-9](#)
 - displaying
 - candidate switches [2-497](#)
 - debug messages [B-9](#)
 - member switches [2-499](#)
 - status [2-495](#)
 - hop-count limit for extended discovery [2-102](#)
 - HSRP standby groups [2-109](#)
 - redundancy [2-109](#)
 - SNMP trap [2-715](#)
 - cluster standby-group command [2-109](#)
 - cluster timer command [2-111](#)
 - command modes defined [1-1](#)
 - command switch
 - See clusters
 - configuration files
 - password recovery disable considerations [A-1](#)
 - specifying the name [2-58, 2-64](#)
 - configuring multiple interfaces [2-177](#)
 - config-vlan mode
 - commands [2-836](#)
 - copy (boot loader) command [A-6](#)
 - CoS
 - assigning default value to incoming packets [2-330](#)
 - assigning to Layer 2 protocol packets [2-277](#)
 - overriding the incoming value [2-330](#)
 - CoS-to-DSCP map [2-334](#)
 - CPU ASIC statistics, displaying [2-501](#)
 - crashinfo files [2-169](#)
 - critical VLAN [2-31](#)
-
- ## D
- debug authentication [B-2](#)
 - debug auto qos command [B-4](#)

- debug backup command [B-6, B-7](#)
- debug cip [B-7](#)
- debug cisp command [B-8](#)
- debug cluster command [B-9](#)
- debug dot1x command [B-11](#)
- debug dtp command [B-12](#)
- debug eap command [B-13, B-88](#)
- debug etherchannel command [B-14](#)
- debug interface command [B-15](#)
- debug ip dhcp snooping command [B-16](#)
- debug ip igmp filter command [B-18](#)
- debug ip igmp max-groups command [B-19](#)
- debug ip igmp snooping command [B-20](#)
- debug ip verify source packet command [B-17](#)
- debug lacp command [B-21](#)
- debug lldp packets command [B-22](#)
- debug mac-notification command [B-23](#)
- debug matm command [B-24](#)
- debug matm move update command [B-25](#)
- debug monitor command [B-26](#)
- debug mvrdbg command [B-28](#)
- debug nmsp command [B-29](#)
- debug nvram command [B-30](#)
- debug pagp command [B-31](#)
- debug platform acl command [B-32](#)
- debug platform backup interface command [B-34](#)
- debug platform cisp command [B-35](#)
- debug platform cpu-queues command [B-36](#)
- debug platform dot1x command [B-38](#)
- debug platform etherchannel command [B-39](#)
- debug platform fallback-bridging command [B-40](#)
- debug platform forw-tcam command [B-41](#)
- debug platform ip arp inspection command [B-42](#)
- debug platform ip dhcp command [B-43](#)
- debug platform ip igmp snooping command [B-44](#)
- debug platform ip multicast command [B-46](#)
- debug platform ip source-guard command [B-48](#)
- debug platform ip unicast command [B-49](#)
- debug platform led command [B-51](#)
- debug platform matm command [B-52](#)
- debug platform messaging application command [B-53](#)
- debug platform phy command [B-54](#)
- debug platform pm command [B-56](#)
- debug platform port-asic command [B-58](#)
- debug platform port-security command [B-59](#)
- debug platform qos-acl-tcam command [B-60](#)
- debug platform resource-manager command [B-61](#)
- debug platform snmp command [B-62](#)
- debug platform span command [B-63](#)
- debug platform supervisor-asic command [B-64](#)
- debug platform sw-bridge command [B-65](#)
- debug platform tcam command [B-66](#)
- debug platform ulld command [B-69](#)
- debug platform vlan command [B-70](#)
- debug pm command [B-71](#)
- debug port-security command [B-73](#)
- debug profinet alarm [B-74](#)
- debug profinet cyclic [B-76](#)
- debug profinet error [B-78](#)
- debug profinet packet [B-80](#)
- debug profinet platform [B-82](#)
- debug profinet topology [B-84](#)
- debug profinet trace [B-86](#)
- debug qos-manager command [B-89](#)
- debug spanning-tree backbonefast command [B-92](#)
- debug spanning-tree bpdu command [B-93](#)
- debug spanning-tree bpdu-opt command [B-94](#)
- debug spanning-tree command [B-90](#)
- debug spanning-tree mstp command [B-95](#)
- debug spanning-tree switch command [B-97](#)
- debug spanning-tree uplinkfast command [B-99](#)
- debug sw-vlan command [B-100](#)
- debug sw-vlan ifs command [B-102](#)
- debug sw-vlan notification command [B-103](#)
- debug sw-vlan vtp command [B-105](#)
- debug ulld command [B-107](#)
- debug vqpc command [B-109](#)
- defaultPort profile [2-13, 2-14](#)

- define interface-range command [2-112](#)
- delete (boot loader) command [A-7](#)
- delete command [2-114](#)
- deny (ARP access-list configuration) command [2-115](#)
- deny (IPv6) command [2-117](#)
- deny command [2-120](#)
- detect mechanism, causes [2-160](#)
- DHCP snooping
 - accepting untrusted packets from edge switch [2-209](#)
 - enabling
 - on a VLAN [2-216](#)
 - option 82 [2-207, 2-209](#)
 - trust on an interface [2-214](#)
 - error recovery timer [2-166](#)
 - rate limiting [2-213](#)
- DHCP snooping binding database
 - binding file, configuring [2-205](#)
 - bindings
 - adding [2-203](#)
 - deleting [2-203](#)
 - displaying [2-559](#)
 - clearing database agent statistics [2-82](#)
 - database agent, configuring [2-205](#)
 - displaying
 - binding entries [2-559](#)
 - database agent status [2-562, 2-564](#)
 - renewing [2-436](#)
- dir (boot loader) command [A-8](#)
- directories, deleting [2-114](#)
- domain name, VTP [2-851](#)
- dot1x auth-fail max-attempts [2-125](#)
- dot1x auth-fail vlan [2-127](#)
- dot1x command [2-123](#)
- dot1x control-direction command [2-129](#)
- dot1x credentials (global configuration) command [2-131](#)
- dot1x critical global configuration command [2-132](#)
- dot1x critical interface configuration command [2-134](#)
- dot1x default command [2-136](#)
- dot1x fallback command [2-137](#)
- dot1x guest-vlan command [2-138](#)
- dot1x host-mode command [2-140](#)
- dot1x initialize command [2-142](#)
- dot1x mac-auth-bypass command [2-143](#)
- dot1x max-reauth-req command [2-145](#)
- dot1x max-req command [2-146](#)
- dot1x pae command [2-147](#)
- dot1x port-control command [2-148](#)
- dot1x re-authenticate command [2-150](#)
- dot1x reauthentication command [2-151](#)
- dot1x supplicant force-multicast command [2-152](#)
- dot1x test eapol-capable command [2-153](#)
- dot1x test timeout command [2-154](#)
- dot1x timeout command [2-155](#)
- dot1x violation-mode command [2-157](#)
- dropping packets, with ACL matches [2-6](#)
- drop threshold, Layer 2 protocol tunneling [2-274](#)
- DSCP-to-CoS map [2-334](#)
- DSCP-to-DSCP-mutation map [2-334](#)
- DTP [2-795](#)
- DTP flap
 - error detection for [2-160](#)
 - error recovery timer [2-166](#)
- DTP negotiation [2-799](#)
- dual-purpose uplink ports
 - selecting the type [2-324](#)
- duplex command [2-158](#)
- dynamic-access ports
 - configuring [2-783](#)
 - restrictions [2-784](#)
- dynamic ARP inspection
 - ARP ACLs
 - apply to a VLAN [2-189](#)
 - define [2-24](#)
 - deny packets [2-115](#)
 - display [2-477](#)
 - permit packets [2-385](#)
 - clear
 - log buffer [2-80](#)

- statistics [2-81](#)
- display
 - ARP ACLs [2-477](#)
 - configuration and operating state [2-554](#)
 - log buffer [2-554](#)
 - statistics [2-554](#)
 - trust state and rate limit [2-554](#)
- enable per VLAN [2-199](#)
- error detection for [2-160](#)
- log buffer
 - clear [2-80](#)
 - configure [2-193](#)
 - display [2-554](#)
- rate-limit incoming ARP packets [2-191](#)
- statistics
 - clear [2-81](#)
 - display [2-554](#)
- trusted interface state [2-195](#)
- type of packet logged [2-200](#)
- validation checks [2-197](#)
- dynamic auto VLAN membership mode [2-794](#)
- dynamic desirable VLAN membership mode [2-794](#)
- Dynamic Host Configuration Protocol (DHCP)
 - See DHCP snooping
- Dynamic Trunking Protocol
 - See DTP

E

- EAP-request/identity frame
 - maximum number to send [2-146](#)
 - response time before retransmitting [2-155](#)
- environmental alarms, displaying [2-475](#)
- environment variables, displaying [2-486](#)
- errdisable detect cause command [2-160](#)
- errdisable detect cause small-frame comand [2-163](#)
- errdisable recovery cause small-frame [2-165](#)
- errdisable recovery command [2-166](#)
- error conditions, displaying [2-528](#)
- error disable detection [2-160](#)
- error-disabled interfaces, displaying [2-540](#)
- EtherChannel
 - assigning Ethernet interface to channel group [2-66](#)
 - creating port-channel logical interface [2-175](#)
 - debug EtherChannel/PAgP, display [B-14](#)
 - debug platform-specific events, display [B-39](#)
 - displaying [2-531](#)
 - enabling Layer 2 protocol tunneling for
 - LACP [2-275](#)
 - PAgP [2-275](#)
 - UDLD [2-275](#)
 - interface information, displaying [2-540](#)
- LACP
 - clearing channel-group information [2-87](#)
 - debug messages, display [B-21](#)
 - displaying [2-598](#)
 - modes [2-66](#)
 - port priority for hot-standby ports [2-278](#)
 - restricting a protocol [2-69](#)
 - system priority [2-280](#)
- load-distribution methods [2-403](#)
- PAgP
 - aggregate-port learner [2-381](#)
 - clearing channel-group information [2-91](#)
 - debug messages, display [B-31](#)
 - displaying [2-655](#)
 - error detection for [2-160](#)
 - error recovery timer [2-166](#)
 - learn method [2-381](#)
 - modes [2-66](#)
 - physical-port learner [2-381](#)
 - priority of interface for transmitted traffic [2-383](#)
- Ethernet controller, internal register display [2-503](#)
- Ethernet statistics, collecting [2-453](#)
- exception crashinfo command [2-169](#)
- extended discovery of candidate switches [2-102](#)
- extended-range VLANs
 - and allowed VLAN list [2-814](#)

- and pruning-eligible list [2-814](#)
- configuring [2-835](#)

extended system ID for STP [2-733](#)

F

- facility alarm relays, displaying [2-534](#)
- facility alarm status, displaying [2-535](#)
- fallback profile command [2-170](#)
- fallback profiles, displaying [2-536](#)
- FCS bit error rate
 - displaying [2-537](#)
 - fluctuation threshold [2-8](#)
 - setting [2-172](#)
- FCS hysteresis threshold [2-8](#)
- fcs-threshold command [2-172](#)
- file name, VTP [2-851](#)
- files, deleting [2-114](#)
- flash_init (boot loader) command [A-10](#)
- flexible authentication ordering [2-42](#)
- Flex Links
 - configuring [2-787](#)
 - configuring preferred VLAN [2-789](#)
 - displaying [2-540](#)
- flowcontrol command [2-173](#)
- format (boot loader) command [A-11](#)
- forwarding packets, with ACL matches [2-6](#)
- forwarding results, display [C-6](#)
- frame check sequence
 - See FCS
- frame forwarding information, displaying [C-6](#)
- fsck (boot loader) command [A-12](#)

G

- global configuration mode [1-2, 1-3](#)

H

- hardware ACL statistics [2-469](#)
- help (boot loader) command [A-13](#)
- hierarchical policy maps [2-400](#)
- hop-count limit for clusters [2-102](#)
- host connection, port configuration [2-793](#)
- host ports, private VLANs [2-797](#)
- Hot Standby Router Protocol
 - See HSRP
- HSRP
 - binding HSRP group to cluster [2-109](#)
 - standby group [2-109](#)

I

- IEEE 802.1Q trunk ports and native VLANs [2-842](#)
- IEEE 802.1Q tunnel ports
 - displaying [2-517](#)
 - limitations [2-795](#)
- IEEE 802.1x
 - and switchport modes [2-795](#)
 - violation error recovery [2-166](#)
 - See also port-based authentication
- IEEE 802.1X Port Based Authentication
 - enabling guest VLAN supplicant [2-126, 2-137, 2-171](#)
- IGMP filters
 - applying [2-219](#)
 - debug messages, display [B-18](#)
- IGMP groups, setting maximum [2-221](#)
- IGMP maximum groups, debugging [B-19](#)
- IGMP profiles
 - creating [2-223](#)
 - displaying [2-567](#)
- IGMP snooping
 - adding ports as a static member of a group [2-238](#)
 - displaying [2-568](#)
 - enabling [2-225](#)
 - enabling the configurable-leave timer [2-227](#)

- enabling the Immediate-Leave feature [2-235](#)
- flooding query count [2-232](#)
- interface topology change notification behavior [2-234](#)
- querier [2-229](#)
- query solicitation [2-232](#)
- report suppression [2-231](#)
- switch topology change notification behavior [2-232](#)
- images
 - See software images
- Immediate-Leave feature, MVR [2-371](#)
- immediate-leave processing [2-235](#)
- Immediate-Leave processing, IPv6 [2-270](#)
- interface configuration mode [1-2, 1-4](#)
- interface port-channel command [2-175](#)
- interface range command [2-177](#)
- interface-range macros [2-112](#)
- interfaces
 - assigning Ethernet interface to channel group [2-66](#)
 - configuring [2-158](#)
 - configuring multiple [2-177](#)
 - creating port-channel logical [2-175](#)
 - debug messages, display [B-15](#)
 - disabling [2-711](#)
 - displaying the MAC address table [2-617](#)
 - restarting [2-711](#)
- interface speed, configuring [2-770](#)
- interface vlan command [2-179](#)
- internal registers, displaying [2-503, 2-513](#)
- Internet Group Management Protocol
 - See IGMP
- invalid GBIC
 - error detection for [2-160](#)
 - error recovery timer [2-166](#)
- ip access-group command [2-181](#)
- ip address command [2-184](#)
- IP addresses, setting [2-184](#)
- IP address matching [2-319](#)
- ip admission command [2-186](#)
- ip admission name proxy http command [2-187](#)
- ip arp inspection filter vlan command [2-189](#)
- ip arp inspection limit command [2-191](#)
- ip arp inspection log-buffer command [2-193](#)
- ip arp inspection trust command [2-195](#)
- ip arp inspection validate command [2-197](#)
- ip arp inspection vlan command [2-199](#)
- ip arp inspection vlan logging command [2-200](#)
- IP DHCP snooping
 - See DHCP snooping
- ip dhcp snooping binding command [2-203](#)
- ip dhcp snooping command [2-202](#)
- ip dhcp snooping database command [2-205](#)
- ip dhcp snooping information option allow-untrusted command [2-209](#)
- ip dhcp snooping information option command [2-207](#)
- ip dhcp snooping information option format remote-id command [2-211](#)
- ip dhcp snooping limit rate command [2-213](#)
- ip dhcp snooping trust command [2-214](#)
- ip dhcp snooping verify command [2-215](#)
- ip dhcp snooping vlan command [2-216](#)
- ip dhcp snooping vlan information option format-type circuit-id string command [2-217](#)
- ip igmp filter command [2-219](#)
- ip igmp max-groups command [2-221, 2-244, 2-246](#)
- ip igmp profile command [2-223](#)
- ip igmp snooping command [2-225](#)
- ip igmp snooping last-member-query-interval command [2-227](#)
- ip igmp snooping querier command [2-229](#)
- ip igmp snooping report-suppression command [2-231](#)
- ip igmp snooping tcn command [2-232](#)
- ip igmp snooping tcn flood command [2-234](#)
- ip igmp snooping vlan immediate-leave command [2-235](#)
- ip igmp snooping vlan mrouter command [2-236](#)
- ip igmp snooping vlan static command [2-238](#)
- IP multicast addresses [2-368](#)
- IP phones
 - auto-QoS configuration [2-54](#)
 - trusting packets sent from [2-360](#)

IP-precedence-to-DSCP map [2-334](#)
 ip source binding command [2-240](#)
 IP source guard
 disabling [2-248](#)
 displaying
 binding entries [2-575](#)
 configuration [2-576](#)
 dynamic binding entries only [2-559](#)
 enabling [2-248](#)
 static IP source bindings [2-240](#)
 ip ssh command [2-242](#)
 IPv6 access list, deny conditions [2-117](#)
 ipv6 access-list command [2-249](#)
 ipv6 address dhcp command [2-252](#)
 ipv6 dhcp client request vendor command [2-253](#)
 ipv6 dhcp ping packets command [2-254](#)
 ipv6 dhcp pool command [2-256](#)
 ipv6 dhcp server command [2-258](#)
 ipv6 mld snooping command [2-260](#)
 ipv6 mld snooping last-listener-query count
 command [2-262](#)
 ipv6 mld snooping last-listener-query-count
 command [2-262](#)
 ipv6 mld snooping last-listener-query-interval
 command [2-264](#)
 ipv6 mld snooping listener-message-suppression
 command [2-266](#)
 ipv6 mld snooping robustness-variable command [2-267](#)
 ipv6 mld snooping tcn command [2-269](#)
 ipv6 mld snooping vlan command [2-270](#)
 IPv6 SDM template [2-454](#)
 ipv6 traffic-filter command [2-272](#)
 ip verify source command [2-248](#)

J

jumbo frames
 See MTU

L

l2protocol-tunnel command [2-274](#)
 l2protocol-tunnel cos command [2-277](#)
 LACP
 See EtherChannel
 lacp port-priority command [2-278](#)
 lacp system-priority command [2-280](#)
 Layer 2 mode, enabling [2-781](#)
 Layer 2 protocol ports, displaying [2-595](#)
 Layer 2 protocol tunnel counters [2-86](#)
 Layer 2 protocol tunneling error recovery [2-275](#)
 Layer 2 traceroute
 IP addresses [2-826](#)
 MAC addresses [2-823](#)
 Layer 3 mode, enabling [2-781](#)
 line configuration mode [1-2, 1-4](#)
 Link Aggregation Control Protocol
 See EtherChannel
 link flap
 error detection for [2-160](#)
 error recovery timer [2-166](#)
 link state group command [2-286](#)
 link state track command [2-288](#)
 load-distribution methods for EtherChannel [2-403](#)
 location (global configuration) command [2-282](#)
 location (interface configuration) command [2-284](#)
 logging event command [2-289](#)
 logging event power-inline-status command [2-290](#)
 logging file command [2-291](#)
 logical interface [2-175](#)
 loopback error
 detection for [2-160](#)
 recovery timer [2-166](#)
 loop guard, for spanning tree [2-735, 2-739](#)

M

mab request format attribute 32 command [2-293](#)

- mac access-group command [2-295](#)
- MAC access list configuration mode [2-297](#)
- mac access-list extended command [2-297](#)
- MAC access lists [2-120](#)
- MAC addresses
 - disabling MAC address learning per VLAN [2-300](#)
 - displaying
 - aging time [2-611](#)
 - all [2-609](#)
 - dynamic [2-615](#)
 - MAC address-table move updates [2-620](#)
 - notification settings [2-619, 2-622](#)
 - number of addresses in a VLAN [2-613](#)
 - per interface [2-617](#)
 - per VLAN [2-626](#)
 - static [2-624](#)
 - static and dynamic entries [2-607](#)
 - dynamic
 - aging time [2-299](#)
 - deleting [2-88](#)
 - displaying [2-615](#)
 - enabling MAC address notification [2-304](#)
 - enabling MAC address-table move update [2-302](#)
 - matching [2-319](#)
 - static
 - adding and removing [2-306](#)
 - displaying [2-624](#)
 - dropping on an interface [2-307](#)
 - tables [2-609](#)
- MAC address notification, debugging [B-23](#)
- mac address-table aging-time [2-295](#)
- mac address-table aging-time command [2-299](#)
- mac address-table learning command [2-300](#)
- mac address-table move update command [2-302](#)
- mac address-table notification command [2-304](#)
- mac address-table static command [2-306](#)
- mac address-table static drop command [2-307](#)
- macro apply command [2-309](#)
- macro description command [2-312](#)
- macro global command [2-313](#)
- macro global description command [2-316](#)
- macro name command [2-317](#)
- macros
 - adding a description [2-312](#)
 - adding a global description [2-316](#)
 - applying [2-313](#)
 - creating [2-317](#)
 - displaying [2-657](#)
 - interface range [2-112, 2-177](#)
 - specifying parameter values [2-313](#)
 - tracing [2-313](#)
- maps
 - QoS
 - defining [2-334](#)
 - displaying [2-636](#)
 - VLAN
 - creating [2-840](#)
 - defining [2-319](#)
 - displaying [2-700](#)
- match (access-map configuration) command [2-319](#)
- match (class-map configuration) command [2-321](#)
- maximum transmission unit
 - See MTU
- mdix auto command [2-323](#)
- media-type command [2-324](#)
- member switches
 - See clusters
- memory (boot loader) command [A-14](#)
- mkdir (boot loader) command [A-15](#)
- MLD snooping
 - configuring [2-266, 2-267](#)
 - configuring queries [2-262, 2-264](#)
 - configuring topology change notification [2-269](#)
 - displaying [2-585, 2-587, 2-591](#)
 - enabling [2-260](#)
- MLD snooping on a VLAN, enabling [2-270](#)
- mls qos aggregate-policer command [2-328](#)
- mls qos command [2-326](#)

- mls qos cos command [2-330](#)
- mls qos dscp-mutation command [2-332](#)
- mls qos map command [2-334](#)
- mls qos queue-set output buffers command [2-338](#)
- mls qos queue-set output threshold command [2-340](#)
- mls qos rewrite ip dscp command [2-342](#)
- mls qos srr-queue input bandwidth command [2-344](#)
- mls qos srr-queue input buffers command [2-346](#)
- mls qos-srr-queue input cos-map command [2-348](#)
- mls qos srr-queue input dscp-map command [2-350](#)
- mls qos srr-queue input priority-queue command [2-352](#)
- mls qos srr-queue input threshold command [2-354](#)
- mls qos-srr-queue output cos-map command [2-356](#)
- mls qos srr-queue output dscp-map command [2-358](#)
- mls qos trust command [2-360](#)
- mls qos vlan-based command [2-362](#)
- mode, MVR [2-368](#)
- modes, commands [1-1](#)
- monitor session command [2-363](#)
- more (boot loader) command [A-16](#)
- MSTP
 - displaying [2-682](#)
 - interoperability [2-97](#)
 - link type [2-737](#)
 - MST region
 - aborting changes [2-743](#)
 - applying changes [2-743](#)
 - configuration name [2-743](#)
 - configuration revision number [2-743](#)
 - current or pending display [2-743](#)
 - displaying [2-682](#)
 - MST configuration mode [2-743](#)
 - VLANs-to-instance mapping [2-743](#)
 - path cost [2-745](#)
 - protocol mode [2-741](#)
 - restart protocol migration process [2-97](#)
 - root port
 - loop guard [2-735](#)
 - preventing from becoming designated [2-735](#)
 - restricting which can be root [2-735](#)
 - root guard [2-735](#)
 - root switch
 - affects of extended system ID [2-733](#)
 - hello-time [2-748, 2-756](#)
 - interval between BPDU messages [2-749](#)
 - interval between hello BPDU messages [2-748, 2-756](#)
 - max-age [2-749](#)
 - maximum hop count before discarding BPDU [2-750](#)
 - port priority for selection of [2-752](#)
 - primary or secondary [2-756](#)
 - switch priority [2-755](#)
 - state changes
 - blocking to forwarding state [2-762](#)
 - enabling BPDU filtering [2-725, 2-760](#)
 - enabling BPDU guard [2-727, 2-760](#)
 - enabling Port Fast [2-760, 2-762](#)
 - forward-delay time [2-747](#)
 - length of listening and learning states [2-747](#)
 - rapid transition to forwarding [2-737](#)
 - shutting down Port Fast-enabled ports [2-760](#)
 - state information display [2-681](#)
- MTU
 - configuring size [2-819](#)
 - displaying global setting [2-689](#)
- Multicast Listener Discovery
 - See MLD
- multicast group address, MVR [2-371](#)
- multicast groups, MVR [2-369](#)
- Multicast Listener Discovery
 - See MLD
- multicast router learning method [2-236](#)
- multicast router ports, configuring [2-236](#)
- multicast router ports, IPv6 [2-270](#)
- multicast storm control [2-778](#)
- multicast VLAN, MVR [2-368](#)
- multicast VLAN registration

See MVR

Multiple Spanning Tree Protocol

See MSTP

MVR

and address aliasing [2-369](#)

configuring [2-368](#)

configuring interfaces [2-371](#)

debug messages, display [B-28](#)

displaying [2-644](#)

displaying interface information [2-646](#)

members, displaying [2-648](#)

mvr (global configuration) command [2-368](#)

mvr (interface configuration) command [2-371](#)

mvr vlan group command [2-372](#)

N

native VLANs [2-814](#)

native VLAN tagging [2-842](#)

network-policy (global configuration) command [2-375](#)

network-policy command [2-374](#)

network-policy profile (network-policy configuration) command [2-377](#)

nmsp attachment suppress command [2-380](#)

nmsp command [2-379](#)

nonegotiate, speed [2-770](#)

nonegotiating DTP messaging [2-799](#)

non-IP protocols

denying [2-120](#)

forwarding [2-393](#)

non-IP traffic access lists [2-297](#)

non-IP traffic forwarding

denying [2-120](#)

permitting [2-393](#)

normal-range VLANs [2-835](#)

notifies command [2-12](#)

no vlan command [2-835](#)

O

online diagnostics

displaying

configured boot-up coverage level [2-517](#)

current scheduled tasks [2-517](#)

event logs [2-517](#)

supported test suites [2-517](#)

test ID [2-517](#)

test results [2-517](#)

test statistics [2-517](#)

global configuration mode

clearing health monitoring diagnostic test schedule [2-80](#)

setting health monitoring diagnostic testing [2-80](#)

setting up health monitoring diagnostic test schedule [2-80](#)

P

PAgP

See EtherChannel

pagp learn-method command [2-381](#)

pagp port-priority command [2-383](#)

password, VTP [2-852](#)

permit (ARP access-list configuration) command [2-385](#)

permit (IPv6) command [2-387](#)

permit (MAC access-list configuration) command [2-393](#)

per-VLAN spanning-tree plus

See STP

physical-port learner [2-381](#)

PID, displaying [2-553](#)

PIM-DVMRP, as multicast router learning method [2-236](#)

PoE

configuring the power budget [2-408](#)

configuring the power management mode [2-405](#)

displaying controller register values [2-510](#)

displaying power management information [2-665](#)

logging of status [2-290](#)

- police aggregate command [2-398](#)
- police command [2-396](#)
- policed-DSCP map [2-334](#)
- policy-map command [2-400](#)
- policy maps
 - applying to an interface [2-459, 2-464](#)
 - creating [2-400](#)
 - displaying [2-660](#)
 - hierarchical [2-400](#)
 - policers
 - displaying [2-629](#)
 - for a single class [2-396](#)
 - for multiple classes [2-328, 2-398](#)
 - policed-DSCP map [2-334](#)
 - traffic classification
 - defining the class [2-73](#)
 - defining trust states [2-828](#)
 - setting DSCP or IP precedence values [2-462](#)
- Port Aggregation Protocol
 - See EtherChannel
- port-based authentication
 - AAA method list [2-3](#)
 - configuring violation modes [2-157](#)
 - debug messages, display [B-11](#)
 - enabling IEEE 802.1x
 - globally [2-123](#)
 - per interface [2-148](#)
 - guest VLAN [2-138](#)
 - host modes [2-140](#)
 - IEEE 802.1x AAA accounting methods [2-1](#)
 - initialize an interface [2-142, 2-154](#)
 - MAC authentication bypass [2-143](#)
 - manual control of authorization state [2-148](#)
 - PAE as authenticator [2-147](#)
 - periodic re-authentication
 - enabling [2-151](#)
 - time between attempts [2-155](#)
 - quiet period between failed authentication exchanges [2-155](#)
 - re-authenticating IEEE 802.1x-enabled ports [2-150](#)
 - resetting configurable IEEE 802.1x parameters [2-136](#)
 - switch-to-authentication server retransmission time [2-155](#)
 - switch-to-client frame-retransmission number [2-145 to 2-146](#)
 - switch-to-client retransmission time [2-155](#)
 - test for IEEE 802.1x readiness [2-153](#)
- port-channel load-balance command [2-403](#)
- Port Fast, for spanning tree [2-762](#)
- port ranges, defining [2-112](#)
- ports, debugging [B-71](#)
- ports, protected [2-812](#)
- port security
 - aging [2-806](#)
 - debug messages, display [B-73](#)
 - enabling [2-801](#)
 - violation error recovery [2-166](#)
- port trust states for QoS [2-360](#)
- port types, MVR [2-371](#)
- power inline consumption command [2-408](#)
- Power over Ethernet
 - See PoE
- power supply alarms, setting [2-9](#)
- power-supply dual command [2-412](#)
- power-supply mode [2-412](#)
- Precision Time Protocol
- primary temperature alarm [2-10](#)
- priority-queue command [2-413](#)
- private-vlan command [2-415](#)
- private-vlan mapping command [2-418](#)
- private VLANs
 - association [2-810](#)
 - configuring [2-415](#)
 - configuring ports [2-797](#)
 - host ports [2-797](#)
 - mapping
 - configuring [2-810](#)
 - promiscuous ports [2-797](#)

privileged EXEC mode [1-2, 1-3](#)
 product identification information, displaying [2-553](#)
 profinet [2-420](#)
 promiscuous ports, private VLANs [2-797](#)
 protected ports, displaying [2-545](#)
 pruning
 VLANs [2-814](#)
 VTP
 displaying interface information [2-540](#)
 enabling [2-852](#)
 pruning-eligible VLAN list [2-815](#)
 psp [2-422](#)
 psp command [2-422](#)
 ptp (global configuration) command [2-423](#)
 ptp interface configuration command [2-425](#)
 PTP settings [2-425](#)
 PVST+
 See STP

Q

QoS
 auto-QoS
 configuring [2-54](#)
 debug messages, display [B-4](#)
 displaying [2-482](#)
 class maps
 creating [2-75](#)
 defining the match criteria [2-321](#)
 displaying [2-494](#)
 defining the CoS value for an incoming packet [2-330](#)
 displaying configuration information [2-482, 2-628](#)
 DSCP transparency [2-342](#)
 DSCP trusted ports
 applying DSCP-to-DSCP-mutation map to [2-332](#)
 defining DSCP-to-DSCP-mutation map [2-334](#)
 egress queues
 allocating buffers [2-338](#)
 defining the CoS output queue threshold map [2-356](#)
 defining the DSCP output queue threshold map [2-358](#)
 displaying buffer allocations [2-632](#)
 displaying CoS output queue threshold map [2-636](#)
 displaying DSCP output queue threshold map [2-636](#)
 displaying queueing strategy [2-632](#)
 displaying queue-set settings [2-639](#)
 enabling bandwidth shaping and scheduling [2-774](#)
 enabling bandwidth sharing and scheduling [2-776](#)
 limiting the maximum output on a port [2-772](#)
 mapping a port to a queue-set [2-410, 2-427](#)
 mapping CoS values to a queue and threshold [2-356](#)
 mapping DSCP values to a queue and threshold [2-358](#)
 setting maximum and reserved memory allocations [2-340](#)
 setting WTD thresholds [2-340](#)
 enabling [2-326](#)
 ingress queues
 allocating buffers [2-346](#)
 assigning SRR scheduling weights [2-344](#)
 defining the CoS input queue threshold map [2-348](#)
 defining the DSCP input queue threshold map [2-350](#)
 displaying buffer allocations [2-632](#)
 displaying CoS input queue threshold map [2-636](#)
 displaying DSCP input queue threshold map [2-636](#)
 displaying queueing strategy [2-632](#)
 displaying settings for [2-630](#)
 enabling the priority queue [2-352](#)
 mapping CoS values to a queue and threshold [2-348](#)
 mapping DSCP values to a queue and threshold [2-350](#)

- setting WTD thresholds [2-354](#)
 - maps
 - defining [2-334, 2-348, 2-350, 2-356, 2-358](#)
 - displaying [2-636](#)
 - policy maps
 - applying an aggregate policer [2-398](#)
 - applying to an interface [2-459, 2-464](#)
 - creating [2-400](#)
 - defining policers [2-328, 2-396](#)
 - displaying policers [2-629](#)
 - displaying policy maps [2-660](#)
 - hierarchical [2-400](#)
 - policed-DSCP map [2-334](#)
 - setting DSCP or IP precedence values [2-462](#)
 - traffic classifications [2-73](#)
 - trust states [2-828](#)
 - port trust states [2-360](#)
 - queues, enabling the expedite [2-413](#)
 - statistics
 - in-profile and out-of-profile packets [2-632](#)
 - packets enqueued or dropped [2-632](#)
 - sent and received CoS values [2-632](#)
 - sent and received DSCP values [2-632](#)
 - trusted boundary for IP phones [2-360](#)
 - VLAN-based [2-362](#)
 - quality of service
 - See QoS
 - querytime, MVR [2-368](#)
 - queue-set command [2-410, 2-427](#)
-
- R**
- radius-server dead-criteria command [2-428](#)
 - radius-server host command [2-430](#)
 - rapid per-VLAN spanning-tree plus
 - See STP
 - rapid PVST+
 - See STP
 - rcommand command [2-432](#)
 - re-authenticating IEEE 802.1x-enabled ports [2-150](#)
 - re-authentication
 - periodic [2-151](#)
 - time between attempts [2-155](#)
 - receiver ports, MVR [2-371](#)
 - receiving flow-control packets [2-173](#)
 - recovery mechanism
 - causes [2-166](#)
 - display [2-79, 2-488, 2-527, 2-529](#)
 - timer interval [2-167](#)
 - redundancy for cluster switches [2-109](#)
 - relay-major command [2-12](#)
 - relay-minor command [2-12](#)
 - remote-span command [2-434](#)
 - Remote Switched Port Analyzer
 - See RSPAN
 - rename (boot loader) command [A-17](#)
 - renew ip dhcp snooping database command [2-436](#)
 - rep admin vlan command [2-438](#)
 - rep block port command [2-439](#)
 - rep lsl-age-timer command [2-442](#)
 - rep preempt delay command [2-444](#)
 - rep preempt segment command [2-446](#)
 - rep segment command [2-447](#)
 - rep stcn command [2-450](#)
 - reset (boot loader) command [A-18](#)
 - resource templates, displaying [2-677](#)
 - restricted VLAN
 - See dot1x auth-fail vlan
 - rmdir (boot loader) command [A-19](#)
 - rmon collection stats command [2-453](#)
 - root guard, for spanning tree [2-735](#)
 - routed ports
 - IP addresses on [2-185](#)
 - number supported [2-185](#)
 - RSPAN
 - configuring [2-363](#)
 - displaying [2-642](#)
 - filter RSPAN traffic [2-363](#)

remote-span command [2-434](#)

sessions

displaying [2-642](#)

S

sdm prefer command [2-454](#)

SDM templates

displaying [2-677](#)

dual IPv4 and IPv6 [2-454](#)

secondary temperature alarm [2-10](#)

secure ports, limitations [2-803](#)

see PTP

sending flow-control packets [2-173](#)

service password-recovery command [2-457](#)

service-policy command [2-459](#)

set (boot loader) command [A-20](#)

set command [2-462](#)

setup command [2-464](#)

setup express command [2-467](#)

show access-lists command [2-469](#)

show alarm description port [2-472](#)

show alarm description port command [2-472](#)

show alarm profile command [2-473](#)

show alarm settings command [2-475](#)

show archive status command [2-476](#)

show arp access-list command [2-477](#)

show authentication command [2-478](#)

show auto qos command [2-482](#)

show boot command [2-486](#)

show cable-diagnostics tdr command [2-488](#)

show cisp command [2-493](#)

show class-map command [2-494](#)

show cluster candidates command [2-497](#)

show cluster command [2-495](#)

show cluster members command [2-499](#)

show controllers cpu-interface command [2-501](#)

show controllers ethernet-controller command [2-503](#)

show controllers power inline command [2-510](#)

show controllers team command [2-513](#)

show controller utilization command [2-515](#)

show dot1q-tunnel command [2-517](#)

show dot1x command [2-518](#)

show dtp [2-522](#)

show eap command [2-524](#)

show env command [2-526](#)

show errdisable detect command [2-527](#)

show errdisable flap-values command [2-528](#)

show errdisable recovery command [2-529](#)

show etherchannel command [2-531](#)

show facility-alarm relay command [2-534](#)

show facility-alarm status [2-534](#)

show facility-alarm status command [2-535](#)

show fallback profile command [2-536](#)

show fcs threshold command [2-537](#)

show flowcontrol command [2-539](#)

show interface rep command [2-551](#)

show interfaces command [2-540](#)

show interfaces counters command [2-549](#)

show interfaces rep command [2-551](#)

show inventory command [2-553](#)

show ip arp inspection command [2-554](#)

show ipc command [2-578](#)

show ip dhcp snooping binding command [2-559](#)

show ip dhcp snooping command [2-558](#)

show ip dhcp snooping database command [2-562, 2-564](#)

show ip igmp profile command [2-567](#)

show ip igmp snooping address command [2-587](#)

show ip igmp snooping command [2-568, 2-585](#)

show ip igmp snooping groups command [2-570](#)

show ip igmp snooping mrouter command [2-572, 2-589](#)

show ip igmp snooping querier command [2-573, 2-591](#)

show ip source binding command [2-575](#)

show ipv6 access-list command [2-582](#)

show ipv6 dhcp conflict command [2-584](#)

show ipv6 route updated [2-593](#)

show ip verify source command [2-576](#)

show l2protocol-tunnel command [2-595](#)

- show lacp command [2-598](#)
- show link state group command [2-604](#)
- show location [2-602](#)
- show mac access-group command [2-606](#)
- show mac address-table address command [2-609](#)
- show mac address-table aging time command [2-611](#)
- show mac address-table command [2-607](#)
- show mac address-table count command [2-613](#)
- show mac address-table dynamic command [2-615](#)
- show mac address-table interface command [2-617](#)
- show mac address-table learning command [2-619](#)
- show mac address-table move update command [2-620](#)
- show mac address-table notification command [2-89, 2-622, B-25](#)
- show mac address-table static command [2-624](#)
- show mac address-table vlan command [2-626](#)
- show mls qos aggregate-policer command [2-629](#)
- show mls qos command [2-628](#)
- show mls qos input-queue command [2-630](#)
- show mls qos interface command [2-632](#)
- show mls qos maps command [2-636](#)
- show mls qos queue-set command [2-639](#)
- show mls qos vlan command [2-641](#)
- show monitor command [2-642](#)
- show mvr command [2-644](#)
- show mvr interface command [2-646](#)
- show mvr members command [2-648](#)
- show network-policy profile command [2-650](#)
- show nmsp command [2-652](#)
- show pagp command [2-655](#)
- show parser macro command [2-657](#)
- show platform acl command [C-2](#)
- show platform backup interface command [C-3](#)
- show platform configuration command [C-4](#)
- show platform etherchannel command [C-5](#)
- show platform forward command [C-6](#)
- show platform igmp snooping command [C-8](#)
- show platform ip multicast command [C-9](#)
- show platform ip unicast command [C-10](#)
- show platform ipv6 unicast command [C-14](#)
- show platform ip wccp command [C-13](#)
- show platform layer4op command [C-16](#)
- show platform mac-address-table command [C-17](#)
- show platform messaging command [C-18](#)
- show platform monitor command [C-19](#)
- show platform mvr table command [C-20](#)
- show platform pm command [C-21](#)
- show platform port-asic command [C-22](#)
- show platform port-security command [C-26](#)
- show platform qos command [C-27](#)
- show platform resource-manager command [C-28](#)
- show platform snmp counters command [C-30](#)
- show platform spanning-tree command [C-31](#)
- show platform stp-instance command [C-32](#)
- show platform team command [C-33](#)
- show platform vlan command [C-36](#)
- show policy-map command [2-660](#)
- show port security command [2-662](#)
- show power inline command [2-665](#)
- show profinet [2-665](#)
- show psp config [2-669](#)
- show psp config command [2-669](#)
- show psp statistics [2-670](#)
- show psp statistics command [2-670](#)
- show ptp command [2-671](#)
- show rep topology command [2-674](#)
- show sdm prefer command [2-677](#)
- show setup express command [2-680](#)
- show spanning-tree command [2-681](#)
- show storm-control command [2-687](#)
- show system mtu command [2-689](#)
- show trust command [2-828](#)
- show udld command [2-690](#)
- show version command [2-693](#)
- show vlan access-map command [2-700](#)
- show vlan command [2-695](#)
- show vlan command, fields [2-697](#)
- show vlan filter command [2-701](#)

- show vmps command [2-702](#)
- show vtp command [2-704](#)
- shutdown command [2-711](#)
- shutdown threshold, Layer 2 protocol tunneling [2-274](#)
- shutdown vlan command [2-712](#)
- small violation-rate command [2-713](#)
- Smartports macros
 - See macros
- SNMP host, specifying [2-719](#)
- SNMP informs, enabling the sending of [2-715](#)
- snmp-server enable traps command [2-715](#)
- snmp-server host command [2-719](#)
- snmp trap mac-notification change command [2-722](#)
- SNMP traps
 - enabling MAC address notification trap [2-722](#)
 - enabling the MAC address notification feature [2-304](#)
 - enabling the sending of [2-715](#)
- SoftPhone
 - See Cisco SoftPhone
- software images
 - deleting [2-114](#)
 - downloading [2-16](#)
 - upgrading [2-16](#)
 - uploading [2-22](#)
- software version, displaying [2-693](#)
- source ports, MVR [2-371](#)
- SPAN
 - configuring [2-363](#)
 - debug messages, display [B-26](#)
 - displaying [2-642](#)
 - filter SPAN traffic [2-363](#)
 - sessions
 - add interfaces to [2-363](#)
 - displaying [2-642](#)
 - start new [2-363](#)
- spanning-tree backbonefast command [2-724](#)
- spanning-tree bpduguard command [2-725](#)
- spanning-tree bpduguard command [2-727](#)
- spanning-tree cost command [2-729](#)
- spanning-tree etherchannel command [2-731](#)
- spanning-tree extend system-id command [2-733](#)
- spanning-tree guard command [2-735](#)
- spanning-tree link-type command [2-737](#)
- spanning-tree loopguard default command [2-739](#)
- spanning-tree mode command [2-741](#)
- spanning-tree mst configuration command [2-743](#)
- spanning-tree mst cost command [2-745](#)
- spanning-tree mst forward-time command [2-747](#)
- spanning-tree mst hello-time command [2-748](#)
- spanning-tree mst max-age command [2-749](#)
- spanning-tree mst max-hops command [2-750](#)
- spanning-tree mst port-priority command [2-752](#)
- spanning-tree mst pre-standard command [2-754](#)
- spanning-tree mst priority command [2-755](#)
- spanning-tree mst root command [2-756](#)
- spanning-tree portfast (global configuration) command [2-760](#)
- spanning-tree portfast (interface configuration) command [2-762](#)
- spanning-tree port-priority command [2-758](#)
- Spanning Tree Protocol
 - See STP
- spanning-tree transmit hold-count command [2-764](#)
- spanning-tree uplinkfast command [2-765](#)
- spanning-tree vlan command [2-767](#)
- speed command [2-770](#)
- srr-queue bandwidth limit command [2-772](#)
- srr-queue bandwidth share command [2-776](#)
- SSH, configuring version [2-242](#)
- static-access ports, configuring [2-783](#)
- statistics, Ethernet group [2-453](#)
- sticky learning, enabling [2-801](#)
- storm-control command [2-778](#)
- STP
 - BackboneFast [2-724](#)
 - counters, clearing [2-96](#)
 - debug messages, display
 - BackboneFast events [B-92](#)

- MSTP [B-95](#)
 - optimized BPDUs handling [B-94](#)
 - spanning-tree activity [B-90](#)
 - switch shim [B-97](#)
 - transmitted and received BPDUs [B-93](#)
 - UplinkFast [B-99](#)
 - detection of indirect link failures [2-724](#)
 - EtherChannel misconfiguration [2-731](#)
 - extended system ID [2-733](#)
 - path cost [2-729](#)
 - protocol modes [2-741](#)
 - root port
 - accelerating choice of new [2-765](#)
 - loop guard [2-735](#)
 - preventing from becoming designated [2-735](#)
 - restricting which can be root [2-735](#)
 - root guard [2-735](#)
 - UplinkFast [2-765](#)
 - root switch
 - affects of extended system ID [2-733, 2-768](#)
 - hello-time [2-767](#)
 - interval between BPDU messages [2-767](#)
 - interval between hello BPDU messages [2-767](#)
 - max-age [2-767](#)
 - port priority for selection of [2-758](#)
 - primary or secondary [2-767](#)
 - switch priority [2-767](#)
 - state changes
 - blocking to forwarding state [2-762](#)
 - enabling BPDU filtering [2-725, 2-760](#)
 - enabling BPDU guard [2-727, 2-760](#)
 - enabling Port Fast [2-760, 2-762](#)
 - enabling timer to recover from error state [2-166](#)
 - forward-delay time [2-767](#)
 - length of listening and learning states [2-767](#)
 - shutting down Port Fast-enabled ports [2-760](#)
 - state information display [2-681](#)
 - VLAN options [2-755, 2-767](#)
 - SVIs, creating [2-179](#)
 - SVI status calculation [2-785](#)
 - Switched Port Analyzer
 - See SPAN
 - switching characteristics
 - modifying [2-781](#)
 - returning to interfaces [2-781](#)
 - switchport access command [2-783](#)
 - switchport autostate exclude command [2-785](#)
 - switchport backup interface command [2-787](#)
 - switchport block command [2-791](#)
 - switchport command [2-781](#)
 - switchport host command [2-793](#)
 - switchport mode command [2-794](#)
 - switchport mode private-vlan command [2-797](#)
 - switchport nonnegotiate command [2-799](#)
 - switchport port-security aging command [2-806](#)
 - switchport port-security command [2-801](#)
 - switchport priority extend command [2-808](#)
 - switchport private-vlan command [2-810](#)
 - switchport protected command [2-812](#)
 - switchports, displaying [2-540](#)
 - switchport trunk command [2-814](#)
 - switchport voice vlan command [2-817](#)
 - syslog command [2-12](#)
 - system message logging [2-290](#)
 - system message logging, save message to flash [2-291](#)
 - system mtu command [2-819](#)
 - system resource templates [2-454](#)
-
- ## T
- tar files, creating, listing, and extracting [2-19](#)
 - TDR, running [2-821](#)
 - Telnet, using to communicate to cluster switches [2-432](#)
 - temperature alarms, setting [2-10](#)
 - templates, system resources [2-454](#)
 - test cable-diagnostics tdr command [2-821](#)
 - test relay [2-822](#)
 - test relay command [2-822](#)

tracertool mac command [2-823](#)
 tracertool mac ip command [2-826](#)
 trunking, VLAN mode [2-794](#)
 trunk mode [2-794](#)
 trunk ports [2-794](#)
 trunks, to non-DTP device [2-795](#)
 trusted boundary for QoS [2-360](#)
 trusted port states for QoS [2-360](#)
 tunnel ports, Layer 2 protocol, displaying [2-595](#)
 type (boot loader) command [A-23](#)

U

UDLD

aggressive mode [2-830, 2-832](#)
 debug messages, display [B-107](#)
 enable globally [2-830](#)
 enable per interface [2-832](#)
 error recovery timer [2-166](#)
 message timer [2-830](#)
 normal mode [2-830, 2-832](#)
 reset a shutdown interface [2-834](#)
 status [2-690](#)
 udld command [2-830](#)
 udld port command [2-832](#)
 udld reset command [2-834](#)
 unicast storm control [2-778](#)
 UniDirectional Link Detection
 See UDLD
 unknown multicast traffic, preventing [2-791](#)
 unknown unicast traffic, preventing [2-791](#)
 unset (boot loader) command [A-25](#)
 upgrading
 software images
 downloading [2-16](#)
 monitoring status of [2-476](#)
 UplinkFast, for STP [2-765](#)
 user EXEC mode [1-2](#)

V

version (boot loader) command [A-27](#)
 vlan (global configuration) command [2-835](#)
 vlan access-map command [2-840](#)
 VLAN access map configuration mode [2-840](#)
 VLAN access maps
 actions [2-6](#)
 displaying [2-700](#)
 VLAN-based QoS [2-362](#)
 VLAN configuration
 rules [2-838](#)
 saving [2-835](#)
 VLAN configuration mode
 description [1-4](#)
 entering [2-835](#)
 summary [1-2](#)
 vlan dot1q tag native command [2-842](#)
 vlan filter command [2-844](#)
 VLAN filters, displaying [2-701](#)
 VLAN ID range [2-835](#)
 VLAN maps
 applying [2-844](#)
 creating [2-840](#)
 defining [2-319](#)
 displaying [2-700](#)
 VLAN Query Protocol
 See VQP
 VLANs
 adding [2-835](#)
 configuring [2-835](#)
 debug messages, display
 ISL [B-103](#)
 VLAN IOS file system error tests [B-102](#)
 VLAN manager activity [B-100](#)
 VTP [B-105](#)
 displaying configurations [2-695](#)
 enabling guest VLAN supplicant [2-126, 2-137, 2-171](#)
 extended-range [2-835](#)

- MAC addresses
 - displaying [2-626](#)
 - number of [2-613](#)
- media types [2-838](#)
- normal-range [2-835](#)
- private [2-797](#)
 - configuring [2-415](#)
 - See also private VLANs
- restarting [2-712](#)
- saving the configuration [2-835](#)
- shutting down [2-712](#)
- SNMP traps for VTP [2-717](#)
- suspending [2-712](#)
- VLAN Trunking Protocol
 - See VTP
- VMPS
 - configuring servers [2-849](#)
 - displaying [2-702](#)
 - error recovery timer [2-167](#)
 - reconfirming dynamic VLAN assignments [2-846](#)
- vmpls reconfirm (global configuration) command [2-847](#)
- vmpls reconfirm (privileged EXEC) command [2-846](#)
- vmpls retry command [2-848](#)
- vmpls server command [2-849](#)
- voice VLAN
 - configuring [2-817](#)
 - setting port priority [2-808](#)
- VQP
 - and dynamic-access ports [2-784](#)
 - clearing client statistics [2-98](#)
 - displaying information [2-702](#)
 - per-server retry count [2-848](#)
 - reconfirmation interval [2-847](#)
 - reconfirming dynamic VLAN assignments [2-846](#)
- VTP
 - changing characteristics [2-851](#)
 - clearing pruning counters [2-99](#)
 - configuring
 - domain name [2-851](#)
 - file name [2-851](#)
 - mode [2-851](#)
 - password [2-852](#)
 - counters display fields [2-705](#)
 - displaying information [2-704](#)
 - enabling
 - pruning [2-852](#)
 - Version 2 [2-852](#)
 - enabling per port [2-856](#)
 - mode [2-851](#)
 - pruning [2-852](#)
 - saving the configuration [2-835](#)
 - statistics [2-704](#)
 - status [2-704](#)
 - status display fields [2-708](#)
 - vtp (global configuration) command [2-851](#)
 - vtp interface configuration) command [2-856](#)
 - vtp primary command [2-857](#)

