



## INDEX

---

### A

aaa accounting dot1x command [2-1](#)  
aaa authentication dot1x command [2-3](#)  
AAA methods [2-3](#)  
access control entries  
    See ACEs  
access control lists  
    See ACLs  
access groups  
    IP [2-147](#)  
    MAC, displaying [2-523](#)  
    matching for QoS classification [2-283](#)  
access list, IPv6 [2-216](#)  
access mode [2-682](#)  
access ports [2-682](#)  
ACEs [2-90](#), [2-322](#)  
ACLs  
    as match criteria for QoS classes [2-283](#)  
    deny [2-88](#)  
    displaying [2-398](#)  
    for non-IP protocols [2-261](#)  
    IP [2-147](#)  
    on Layer 2 interfaces [2-147](#)  
    permit [2-320](#)  
action command [2-5](#)  
address aliasing [2-303](#)  
aggregate policers  
    applying [2-332](#)  
    creating [2-328](#)  
    displaying [2-558](#)  
    QoS [2-330](#)  
aggregate-port learner [2-309](#)

alarm-contact command [2-7](#)  
alarm-contact status, displaying [2-431](#)  
allowed VLANs [2-698](#)  
archive download-sw command [2-9](#)  
archive tar command [2-12](#)  
archive upload-sw command [2-15](#)  
arp (boot loader) command [A-2](#)  
arp access-list command [2-17](#)  
attaching policy maps to interfaces [2-381](#)  
authorization state of controlled port [2-103](#)  
autonegotiation of duplex mode [2-115](#)

---

### B

backup interfaces  
    configuring [2-675](#)  
    displaying [2-453](#)  
bandwidth, configuring for QoS [2-19](#)  
bandwidth command [2-19](#)  
boot (boot loader) command [A-3](#)  
boot config-file command [2-22](#)  
boot enable-break command [2-23](#)  
boot helper command [2-24](#)  
boot helper-config file command [2-25](#)  
booting  
    Cisco IOS image [2-28](#)  
    displaying environment variables [2-403](#)  
    interrupting [2-23](#)  
    manually [2-26](#)

## boot loader

- accessing [A-1](#)

- booting

- Cisco IOS image [A-3](#)

- helper image [2-24](#)

- directories

- creating [A-18](#)

- displaying a list of [A-8](#)

- removing [A-22](#)

- displaying

- available commands [A-13](#)

- memory heap utilization [A-14](#)

- version [A-29](#)

- environment variables

- described [A-23](#)

- displaying settings [A-23](#)

- location of [A-24](#)

- setting [A-23](#)

- unsetting [A-27](#)

- files

- copying [A-6](#)

- deleting [A-7](#)

- displaying a list of [A-8](#)

- displaying the contents of [A-5, A-19, A-26](#)

- renaming [A-20](#)

- file system

- formatting [A-11](#)

- initializing flash [A-10](#)

- running a consistency check [A-12](#)

- prompt [A-1](#)

- resetting the system [A-21](#)

- boot manual command [2-26](#)

- boot private-config-file command [2-27](#)

- boot system command [2-28](#)

- BPDU filtering, for spanning tree [2-620, 2-658](#)

- BPDU guard, for spanning tree [2-622, 2-658](#)

- broadcast storm control [2-668](#)

- bundling characteristics, UNI [2-123](#)

- burst bytes, in QoS policers [2-324, 2-328](#)

---

**C**

- cat (boot loader) command [A-5](#)

- CBWFQ, configuring [2-19](#)

- CDP, enabling protocol tunneling for [2-241](#)

- CFM [2-308](#)

- CFM as OAM protocol [2-308](#)

- channel-group command [2-29](#)

- channel-protocol command [2-33](#)

- child policy maps [2-383](#)

- class-based traffic shaping [2-396](#)

- class-based weighted fair queuing

- See CBWFQ

- class command [2-35](#)

- class-map command [2-37](#)

- class-map configuration mode [2-37](#)

- class maps

- creating [2-37](#)

- defining the match criteria [2-284](#)

- displaying [2-407](#)

- matching in [2-37](#)

- class of service

- See CoS

- clear ip arp inspection log command [2-39](#)

- clear ip arp inspection statistics command [2-40](#)

- clear ipc command [2-43](#)

- clear ipv6 dhcp conflict command [2-44](#)

- clear l2protocol-tunnel counters command [2-45](#)

- clear lacp command [2-46](#)

- clear logging onboard command [2-47](#)

- clear mac address-table command [2-48, 2-49](#)

- clear pagp command [2-50, 2-54](#)

- clear policer cpu uni-eni counters command [2-51](#)

- clear port-security command [2-52](#)

- clear spanning-tree counters command [2-55](#)

- clear spanning-tree detected-protocols command [2-56](#)

- clear vmps statistics command [2-58](#)

- command modes defined [1-1](#)

- committed information rate in QoS policers [2-323, 2-328](#)

- configuration files
    - password recovery disable considerations [A-1](#)
    - specifying the name [2-22, 2-27](#)
  - configuring multiple interfaces [2-143](#)
  - conform-action command [2-59](#)
  - control-plane policer [2-51](#)
  - control-plane policer information, displaying [2-559](#)
  - control-plane security [2-334](#)
  - control plane statistics, clearing [2-51](#)
  - copy (boot loader) command [A-6](#)
  - copy logging onboard module command [2-61](#)
  - CoS
    - as match criteria for QoS groups [2-284](#)
    - for QoS classification [2-385](#)
    - setting value in policy maps [2-385](#)
  - CoS value, assigning to Layer 2 protocol packets [2-244](#)
  - CPU ASIC statistics, displaying [2-408](#)
  - CPU protection policers, displaying [C-26](#)
  - cpu traffic qos cos command [2-63](#)
  - cpu traffic qos dscp command [2-67](#)
  - cpu traffic qos precedence command [2-72](#)
  - cpu traffic qos qos-group command [2-75](#)
- 
- D**
- DC power supply [2-343](#)
  - debug backup command [B-2](#)
  - debug dot1x command [B-3](#)
  - debug etherchannel command [B-4](#)
  - debug interface command [B-7](#)
  - debug ip dhcp snooping command [B-8](#)
  - debug ip igmp filter command [B-9](#)
  - debug ip igmp max-groups command [B-10](#)
  - debug ip igmp snooping command [B-11](#)
  - debug ip sla error twamp connection command [B-12](#)
  - debug ip sla error twamp control reflector command [B-14](#)
  - debug ip sla error twamp control server command [B-16](#)
  - debug ip sla error twamp session command [B-18](#)
  - debug ip sla trace twamp connection command [B-20](#)
  - debug ip sla trace twamp control reflector command [B-22](#)
  - debug ip sla trace twamp control server command [B-24](#)
  - debug ip sla trace twamp session command [B-26](#)
  - debug ip verify source packet command [B-28](#)
  - debug lacp command [B-29](#)
  - debug mac-notification command [B-30](#)
  - debug matm command [B-31](#)
  - debug matm move update command [B-32](#)
  - debug monitor command [B-33](#)
  - debug mvrdbg command [B-34](#)
  - debug nvram command [B-35](#)
  - debug pagp command [B-36](#)
  - debug platform acl command [B-37](#)
  - debug platform backup interface command [B-39](#)
  - debug platform cfm command [B-38](#)
  - debug platform cpu-queues command [B-40](#)
  - debug platform dot1x command [B-42](#)
  - debug platform etherchannel command [B-43](#)
  - debug platform forw-tcam command [B-44](#)
  - debug platform ip arp inspection command [B-45](#)
  - debug platform ipc command [B-54](#)
  - debug platform ip dhcp command [B-46](#)
  - debug platform ip igmp snooping command [B-47](#)
  - debug platform ip multicast command [B-49](#)
  - debug platform ip source-guard command [B-51](#)
  - debug platform led command [B-55](#)
  - debug platform matm command [B-56](#)
  - debug platform messaging application command [B-57](#)
  - debug platform phy command [B-58](#)
  - debug platform pm command [B-60](#)
  - debug platform policer cpu uni-eni command [B-62](#)
  - debug platform port-asic command [B-63](#)
  - debug platform port-security command [B-64](#)
  - debug platform qos-acl-tcam command [B-65](#)
  - debug platform qos-manager command [B-66](#)
  - debug platform remote-commands command [B-67](#)
  - debug platform rep command [B-68](#)
  - debug platform resource-manager command [B-69](#)
  - debug platform snmp command [B-70](#)

- debug platform span command [B-71](#)
- debug platform supervisor-asic command [B-72](#)
- debug platform sw-bridge command [B-73](#)
- debug platform team command [B-74](#)
- debug platform udd command [B-76](#)
- debug platform vlan command [B-77](#)
- debug pm command [B-78](#)
- debug port-security command [B-80](#)
- debug qos-manager command [B-81](#)
- debug spanning-tree bpdu command [B-84](#)
- debug spanning-tree bpdu-opt command [B-85](#)
- debug spanning-tree command [B-82](#)
- debug spanning-tree mstp command [B-86](#)
- debug spanning-tree switch command [B-88](#)
- debug sw-vlan command [B-90](#)
- debug sw-vlan ifs command [B-91](#)
- debug sw-vlan notification command [B-92](#)
- debug udd command [B-94](#)
- debug vqpc command [B-96](#)
- default policer configuration
  - NNIs [C-29](#)
  - UNIs [C-27](#)
- define interface-range command [2-77](#)
- delete (boot loader) command [A-7](#)
- delete command [2-79](#)
- deny (ARP access-list configuration) command [2-80](#)
- deny (IPv6) command [2-82](#)
- deny command [2-88](#)
- detect mechanism, causes [2-116](#)
- DHCP snooping
  - accepting untrusted packets from edge switch [2-172](#)
  - enabling
    - on a VLAN [2-178](#)
    - option 82 [2-170, 2-172](#)
    - trust on an interface [2-176](#)
  - error recovery timer [2-118](#)
  - rate limiting [2-175](#)
- DHCP snooping binding database
  - binding file, configuring [2-168](#)
  - bindings
    - adding [2-166](#)
    - deleting [2-166](#)
    - displaying [2-475](#)
  - clearing database agent statistics [2-41](#)
  - database agent, configuring [2-168](#)
  - displaying
    - binding entries [2-475](#)
    - database agent status [2-477, 2-479](#)
    - renewing [2-358](#)
- diagnostic monitor command [2-91](#)
- diagnostic schedule test command [2-93](#)
- diagnostic start test command [2-95](#)
- differentiated service code point
  - See DSCP
- Digital Optical Monitoring
  - see DoM
- dir (boot loader) command [A-8](#)
- directories, deleting [2-79](#)
- DoM
  - displaying supported transceivers [2-465, 2-610, 2-611](#)
- domains, CFM [2-308](#)
- dot1x default command [2-97](#)
- dot1x host-mode command [2-98](#)
- dot1x initialize command [2-100](#)
- dot1x max-req command [2-101, 2-102](#)
- dot1x port-control command [2-103](#)
- dot1x re-authenticate command [2-105](#)
- dot1x reauthentication command [2-106](#)
- dot1x supplicant force-multicast command [2-107](#)
- dot1x system-auth-control command [2-108](#)
- dot1x test eapol-capable command [2-109](#)
- dot1x test timeout command [2-110](#)
- dot1x timeout command [2-111](#)
- dot1x violation-mode command [2-113](#)
- dropping packets, with ACL matches [2-5](#)
- drop threshold, Layer 2 protocol tunneling [2-241](#)

## DSCP

- as match criteria for QoS groups [2-285, 2-291](#)
- for QoS traffic marking [2-387](#)
- setting in policy maps [2-387](#)

dual IPv4 and IPv6 templates [2-315](#)dual-purpose uplink ports, selecting the type [2-296](#)duplex command [2-114](#)

## dynamic-access ports

- configuring [2-673](#)
- restrictions [2-674](#)

## dynamic ARP inspection

## ARP ACLs

- apply to a VLAN [2-152](#)
- define [2-17](#)
- deny packets [2-80](#)
- display [2-402](#)
- permit packets [2-313](#)

## clear

- log buffer [2-39](#)
- statistics [2-40](#)

## display

- ARP ACLs [2-402](#)
- configuration and operating state [2-470](#)
- log buffer [2-470](#)
- statistics [2-470](#)
- trust state and rate limit [2-470](#)

enable per VLAN [2-161](#)error detection for [2-116](#)error recovery timer [2-118](#)

## log buffer

- clear [2-39](#)
- configure [2-156](#)
- display [2-470](#)

rate-limit incoming ARP packets [2-154](#)

## statistics

- clear [2-40](#)
- display [2-470](#)

trusted interface state [2-158](#)type of packet logged [2-162](#)

## dynamic ARP inspection (continued)

- validation checks [2-159](#)

## Dynamic Host Configuration Protocol (DHCP)

- See DHCP snooping

---

**E**

## EAP-request/identity frame

- maximum number to send [2-102](#)
- response time before retransmitting [2-111](#)

## E-LMI

- enabling [2-121](#)
- mapping [2-123](#)

environment variables, displaying [2-403](#)errdisable detect cause command [2-116](#)errdisable recovery command [2-118](#)error conditions, displaying [2-435](#)error disable detection [2-116](#)error-disabled interfaces, displaying [2-453](#)

## EtherChannel

- assigning Ethernet interface to channel group [2-29](#)
- creating port-channel logical interface [2-141](#)
- debug EtherChannel/PAGP, display [B-4](#)
- debug platform-specific events, display [B-43](#)
- displaying [2-439](#)
- enabling Layer 2 protocol tunneling for
  - LACP [2-242](#)
  - PAGP [2-242](#)
  - UDLD [2-242](#)

interface information, displaying [2-453](#)

## LACP

- clearing channel-group information [2-46](#)
- debug messages, display [B-29](#)
- displaying [2-510](#)
- modes [2-29](#)
- port priority for hot-standby ports [2-245](#)
- restricting a protocol [2-33](#)
- system priority [2-247](#)

load-distribution methods [2-339](#)

## EtherChannel (continued)

## PAgP

- aggregate-port learner [2-309](#)
- clearing channel-group information [2-50](#)
- debug messages, display [B-36](#)
- displaying [2-554](#)
- error detection for [2-116](#)
- error recovery timer [2-118](#)
- learn method [2-309](#)
- modes [2-29](#)
- physical-port learner [2-309](#)
- priority of interface for transmitted traffic [2-311](#)

Ethernet controller, internal register display [2-410](#)

ethernet evc command [2-120](#)

ethernet lmi ce-vlan map command [2-121](#), [2-123](#)

ethernet lmi command [2-121](#)

ethernet lmi global command [2-121](#)

Ethernet Local Management Interface

See E-LMI

ethernet loopback interface configuration command [2-125](#)

ethernet loopback privileged EXEC command [2-128](#)

ethernet oam remote-failure command [2-130](#)

Ethernet service

debugging [B-5](#)

displaying [2-444](#)

Ethernet service instance [2-377](#)

Ethernet service interfaces [2-447](#)

Ethernet statistics, collecting [2-373](#)

Ethernet UNI configuration [2-132](#)

ethernet uni id command [2-134](#)

Ethernet virtual connections

See EVCs

EVC configuration mode [2-120](#)

EVCs [2-120](#)

and VLANs [2-132](#)

service instances [2-377](#)

UNI counts [2-720](#)

EVC service

point-to-multipoint [2-720](#)

point-to-point [2-720](#)

exceed-action command [2-135](#)

extended-range VLANs

and allowed VLAN list [2-698](#)

configuring [2-726](#)

extended system ID for STP [2-628](#)

external alarms, configuring [2-7](#)

---

## F

failure logging data

clearing [2-47](#)

copying [2-61](#)

fan information, displaying [2-431](#)

files, deleting [2-79](#)

flash\_init (boot loader) command [A-10](#)

Flex Links

configuring [2-675](#)

configuring preferred VLAN [2-677](#)

displaying [2-453](#)

flowcontrol command [2-137](#)

format (boot loader) command [A-11](#)

forwarding packets, with ACL matches [2-5](#)

forwarding results, display [C-8](#)

frame forwarding information, displaying [C-8](#)

front-end controller counter and status information [C-10](#)

fsck (boot loader) command [A-12](#)

---

## G

global configuration mode [1-2](#), [1-3](#)

---

## H

hardware ACL statistics [2-398](#)

health-monitoring diagnostic testing [2-91](#)

help (boot loader) command [A-13](#)  
 host connection, port configuration [2-681](#)  
 host ports, private VLANs [2-685](#)  
 hw-module module logging onboard command [2-139](#)

## I

IEEE 802.1ag Connectivity Fault Management  
 See CFM

IEEE 802.1Q trunk ports and native VLANs [2-731](#)

IEEE 802.1Q tunnel ports  
 configuring [2-682](#)  
 displaying [2-427](#)  
 limitations [2-683](#)

IEEE 802.1x  
 and switchport modes [2-683](#)  
 violation error recovery [2-118](#)  
 See also port-based authentication

IGMP filters  
 applying [2-181](#)  
 debug messages, display [B-9](#)

IGMP groups, setting maximum [2-183](#)

IGMP maximum groups, debugging [B-10](#)

IGMP profiles  
 creating [2-185](#)  
 displaying [2-482](#)

IGMP snooping  
 adding ports as a static member of a group [2-200](#)  
 displaying [2-483, 2-487, 2-489](#)  
 enabling [2-187](#)  
 enabling the configurable-leave timer [2-189](#)  
 enabling the Immediate-Leave feature [2-197](#)  
 flooding query count [2-195](#)  
 interface topology change notification behavior [2-196](#)  
 multicast table [2-485](#)  
 querier [2-191](#)  
 query solicitation [2-195](#)  
 report suppression [2-193](#)  
 switch topology change notification behavior [2-195](#)

images  
 See software images

Immediate-Leave feature, MVR [2-305](#)

immediate-leave processing [2-197](#)

Immediate-Leave processing, IPv6 [2-237](#)

input policy maps  
 and ACL classification [2-283](#)  
 and aggregate policers [2-330](#)  
 commands not supported in [2-337](#)  
 configuration guidelines [2-337](#)

interface command [2-145](#)

interface configuration mode [1-2, 1-4](#)

interface port-channel command [2-141](#)

interface range command [2-143](#)

interface-range macros [2-77](#)

interfaces  
 assigning Ethernet interface to channel group [2-29](#)  
 configuring [2-114](#)  
 configuring multiple [2-143](#)  
 creating port-channel logical [2-141](#)  
 debug messages, display [B-7](#)  
 disabling [2-605](#)  
 displaying the MAC address table [2-535](#)  
 restarting [2-605](#)

interface speed, configuring [2-666](#)

internal registers, displaying [2-410, 2-417](#)

Internet Group Management Protocol  
 See IGMP

invalid GBIC  
 error detection for [2-116](#)  
 error recovery timer [2-118](#)

ip address command [2-150](#)

IP addresses, setting [2-150](#)

IP address matching [2-281](#)

ip arp inspection filter vlan command [2-152](#)

ip arp inspection limit command [2-154](#)

ip arp inspection log-buffer command [2-156](#)

ip arp inspection trust command [2-158](#)

ip arp inspection validate command [2-159](#)

- ip arp inspection vlan command [2-161](#)
  - ip arp inspection vlan logging command [2-162](#)
  - IP DHCP snooping
    - See DHCP snooping
  - ip dhcp snooping binding command [2-166](#)
  - ip dhcp snooping command [2-165](#)
  - ip dhcp snooping database command [2-168](#)
  - ip dhcp snooping information option allow-untrusted command [2-172](#)
  - ip dhcp snooping information option command [2-170](#)
  - ip dhcp snooping information option format remote-id command [2-174](#)
  - ip dhcp snooping limit rate command [2-175](#)
  - ip dhcp snooping trust command [2-176](#)
  - ip dhcp snooping verify command [2-177](#)
  - ip dhcp snooping vlan command [2-178](#)
  - ip dhcp snooping vlan information option format-type circuit-id string command [2-179](#)
  - ip igmp filter command [2-181](#)
  - ip igmp max-groups command [2-183](#), [2-210](#), [2-212](#)
  - ip igmp profile command [2-185](#)
  - ip igmp snooping command [2-187](#)
  - ip igmp snooping last-member-query-interval command [2-189](#)
  - ip igmp snooping querier command [2-191](#)
  - ip igmp snooping report-suppression command [2-193](#)
  - ip igmp snooping tcn command [2-195](#)
  - ip igmp snooping tcn flood command [2-196](#)
  - ip igmp snooping vlan immediate-leave command [2-197](#)
  - ip igmp snooping vlan mrouter command [2-198](#)
  - ip igmp snooping vlan static command [2-200](#)
  - IP multicast addresses [2-302](#)
  - IP precedence, as match criteria for QoS groups [2-287](#)
  - ip sla responder twamp command [2-202](#)
  - ip sla server twamp command [2-204](#)
  - ip source binding command [2-206](#)
  - IP source guard
    - disabling [2-214](#)
    - displaying
      - binding entries [2-496](#)
      - configuration [2-497](#)
    - enabling [2-214](#)
    - static IP source bindings [2-206](#)
  - IP source guard, displaying dynamic binding entries [2-475](#)
  - ip ssh command [2-208](#)
  - IPv6 access list, deny conditions [2-82](#)
  - ipv6 access-list command [2-216](#)
  - ipv6 address dhcp command [2-218](#)
  - ipv6 dhcp client request vendor command [2-219](#)
  - ipv6 dhcp ping packets command [2-220](#)
  - ipv6 dhcp pool command [2-221](#)
  - ipv6 dhcp server command [2-224](#)
  - ipv6 mld snooping command [2-226](#)
  - ipv6 mld snooping last-listener-query count command [2-228](#)
  - ipv6 mld snooping last-listener-query-interval command [2-230](#)
  - ipv6 mld snooping listener-message-suppression command [2-232](#)
  - ipv6 mld snooping robustness-variable command [2-233](#)
  - ipv6 mld snooping tcn command [2-235](#)
  - ipv6 mld snooping vlan command [2-237](#)
  - IPv6 SDM template [2-374](#)
  - ipv6 traffic-filter command [2-239](#)
  - ip verify source command [2-214](#)
- 
- J**
- jumbo frames
    - See MTU
- 
- L**
- l2protocol-tunnel command [2-241](#)
  - l2protocol-tunnel cos command [2-244](#)



- LACP
  - See EtherChannel
- lacp port-priority command [2-245](#)
- lacp system-priority command [2-247](#)
- Layer 2 mode, enabling [2-671](#)
- Layer 2 protocol ports, displaying [2-508](#)
- Layer 2 protocol-tunnel
  - error detection for [2-116](#)
  - error recovery timer [2-118](#)
- Layer 2 protocol tunnel counters [2-45](#)
- Layer 2 protocol tunneling error recovery [2-242](#)
- Layer 2 traceroute
  - IP addresses [2-713](#)
  - MAC addresses [2-710](#)
- Layer 3 mode, enabling [2-671](#)
- line configuration mode [1-2, 1-4](#)
- Link Aggregation Control Protocol
  - See EtherChannel
- link flap
  - error detection for [2-116](#)
  - error recovery timer [2-118](#)
- link state group command [2-249](#)
- link state track command [2-251](#)
- load-distribution methods for EtherChannel [2-339](#)
- location (global configuration) command [2-252](#)
- location (interface configuration) command [2-254](#)
- logging event command [2-256](#)
- logging file command [2-257](#)
- logical interface [2-141](#)
- loopback error
  - detection for [2-116](#)
  - recovery timer [2-118](#)
- loop guard, for spanning tree [2-630, 2-634](#)
- mac access-list extended command [2-261](#)
- MAC access lists [2-88](#)
- MAC addresses
  - disabling MAC address learning per VLAN [2-264](#)
  - displaying
    - aging time [2-529](#)
    - all [2-527](#)
    - dynamic [2-533](#)
    - MAC address-table move updates [2-538](#)
    - notification settings [2-537, 2-540](#)
    - number of addresses in a VLAN [2-531](#)
    - per interface [2-535](#)
    - per VLAN [2-544](#)
    - static [2-542](#)
    - static and dynamic entries [2-525](#)
  - dynamic
    - aging time [2-263](#)
    - deleting [2-48](#)
    - displaying [2-533](#)
  - enabling MAC address notification [2-268](#)
  - enabling MAC address-table move update [2-266](#)
  - matching [2-281](#)
  - static
    - adding and removing [2-270](#)
    - displaying [2-542](#)
    - dropping on an interface [2-271](#)
  - tables [2-527](#)
- MAC address notification, debugging [B-30](#)
- mac address-table aging-time [2-259, 2-281](#)
- mac address-table aging-time command [2-263](#)
- mac address-table learning command [2-264](#)
- mac address-table move update command [2-266](#)
- mac address-table notification command [2-268](#)
- mac address-table static command [2-270](#)
- mac address-table static drop command [2-271](#)
- macro description command [2-275](#)
- macro global command [2-276](#)
- macro global description command [2-278](#)
- macro name command [2-279](#)

---

## M

- mac access-group command [2-259](#)
- MAC access-groups, displaying [2-523](#)
- MAC access list configuration mode [2-261](#)

## macros

- adding a description [2-275](#)
- adding a global description [2-278](#)
- applying [2-276](#)
- creating [2-279](#)
- displaying [2-556](#)
- interface range [2-77, 2-143](#)
- specifying parameter values [2-276](#)
- tracing [2-276](#)

maintenance end points [2-720](#)

mapping tables, QoS [2-706](#)

## maps

## class

- creating [2-37](#)

## VLAN

- creating [2-729](#)
- defining [2-281](#)
- displaying [2-599](#)

match access-group command [2-283](#)

match cos command [2-284](#)

match ip dscp command [2-285](#)

match ip precedence command [2-287](#)

match qos-group command [2-289](#)

match vlan command [2-291](#)

maximum transmission unit

See MTU

mdix auto command [2-294](#)

ME 3400EG-2CS switch policers [C-26](#)

ME 3400E-24TS switch policers [C-26, C-27](#)

ME 3400EG-12CS switch policers [C-26](#)

media-type command [2-296](#)

memory (boot loader) command [A-14](#)

mgmt\_clr (boot loader) command [A-15](#)

mgmt\_init (boot loader) command [A-16, A-17](#)

mkdir (boot loader) command [A-18](#)

## MLD snooping

- configuring [2-232, 2-233](#)
- configuring queries [2-228, 2-230](#)
- configuring topology change notification [2-235](#)
- enabling [2-226](#)

MLD snooping on a VLAN, enabling [2-237](#)

mode, MVR [2-302](#)

modes, commands [1-1](#)

monitor session command [2-298](#)

more (boot loader) command [A-19](#)

## MSTP

displaying [2-578, 2-579](#)

interoperability [2-56](#)

link type [2-632](#)

## MST region

- aborting changes [2-638](#)
- applying changes [2-638](#)
- configuration name [2-638](#)
- configuration revision number [2-639](#)
- current or pending display [2-639](#)
- displaying [2-578, 2-579](#)
- MST configuration mode [2-638](#)
- VLANs-to-instance mapping [2-638](#)

path cost [2-640](#)

protocol mode [2-636](#)

restart protocol migration process [2-56](#)

## root port

- loop guard [2-630](#)
- preventing from becoming designated [2-630](#)
- restricting which can be root [2-630](#)
- root guard [2-630](#)

## MSTP (continued)

## root switch

- affects of extended system ID [2-628](#)
- hello-time [2-643, 2-654](#)
- interval between BPDU messages [2-645](#)
- interval between hello BPDU messages [2-643, 2-654](#)
- max-age [2-645](#)
- maximum hop count before discarding BPDU [2-647](#)
- port priority for selection of [2-649](#)
- primary or secondary [2-654](#)
- switch priority [2-652](#)

## state changes

- blocking to forwarding state [2-661](#)
- enabling BPDU filtering [2-620, 2-658](#)
- enabling BPDU guard [2-622, 2-658](#)
- enabling Port Fast [2-658, 2-661](#)
- forward-delay time [2-642](#)
- length of listening and learning states [2-642](#)
- rapid transition to forwarding [2-632](#)
- shutting down Port Fast-enabled ports [2-658](#)

state information display [2-577](#)

## MTU

- configuring size [2-704](#)
- displaying global setting [2-586](#)

multicast group address, MVR [2-305](#)multicast groups, MVR [2-303](#)

## Multicast Listener Discovery

See MLD

- multicast router learning method [2-198](#)
- multicast router ports, configuring [2-198](#)
- multicast router ports, IPv6 [2-237](#)
- multicast storm control [2-668](#)
- multicast VLAN, MVR [2-303](#)
- multicast VLAN registration
  - See MVR
- multiple hosts on authorized port [2-98](#)

## Multiple Spanning Tree Protocol

See MSTP

multiplexing, UNI [2-132](#)

## MVR

- and address aliasing [2-303](#)
- configuring [2-302](#)
- configuring interfaces [2-305](#)
- debug messages, display [B-34](#)
- displaying [2-548](#)
- displaying interface information [2-550](#)
- members, displaying [2-552](#)

mvr (global configuration) command [2-302](#)mvr (interface configuration) command [2-305](#)mvr vlan group command [2-306](#)

---

**N**native VLANs [2-698](#)native VLAN tagging [2-731](#)network node interface [2-341](#)nonegotiate, speed [2-666, 2-667](#)

## non-IP protocols

- denying [2-88](#)
- forwarding [2-320](#)

non-IP traffic access lists [2-261](#)

## non-IP traffic forwarding

- denying [2-88](#)
- permitting [2-320](#)

normal-range VLANs [2-726](#)no vlan command [2-726](#)

---

**O**OAM PDUs [2-130](#)OAM protocol [2-308](#)oam protocol cfm svlan command [2-308](#)on-board failure logging, displaying [2-519](#)on-board failure logging, enabling [2-139](#)

online diagnostics

- enabling
  - scheduling [2-93](#)
- global configuration mode
  - clearing test-based testing schedule [2-93](#)
  - setting test-based testing [2-93](#)
  - setting up test-based testing [2-93](#)
- removing scheduling [2-93](#)
- scheduled switchover
  - disabling [2-93](#)
  - enabling [2-93](#)
- setting test interval [2-93](#)
- starting testing [2-95](#)

online diagnostic tests, displaying results [2-423](#)

online diagnostic tests, starting [2-95](#)

operation, administration, and maintenance protocol

- See OAM

output policy maps

- and QoS group classification [2-289](#)
- and traffic shaping [2-396](#)
- commands not supported in [2-337](#)
- configuration guidelines [2-337](#)
- priority in [2-346](#)
- queue limit in [2-353](#)

## P

PAGP

- See EtherChannel

pagp learn-method command [2-309](#)

pagp port-priority command [2-311](#)

parent policy maps [2-383](#)

password-recovery mechanism, enabling and disabling [2-379](#)

permit (ARP access-list configuration) command [2-313](#)

permit (IPv6) command [2-315](#)

permit command [2-320](#)

per-VLAN spanning-tree plus

- See STP

physical-port learner [2-309](#)

PID, displaying [2-469](#)

PIM-DVMRP, as multicast router learning method [2-198](#)

police

- multiple conform actions for a class [2-59](#)
- multiple exceed actions for a class [2-135](#)
- multiple violate actions for a class [2-724](#)
- with priority [2-323](#)

police aggregate command [2-332](#)

police command [2-323](#)

policer aggregate command [2-328](#)

policer configuration

- default for NNIs [C-29](#)
- default for UNIs [C-27](#)

policer cpu uni command [2-334](#)

policers

- aggregate [2-328, 2-332](#)
- for CPU protection [2-334](#)
- individual [2-323](#)

policy-map class, configuring multiple actions [2-59, 2-135, 2-724](#)

policy-map class configuration mode [2-35](#)

policy-map class police configuration mode [2-59, 2-326](#)

policy-map command [2-336](#)

policy-map configuration mode [2-336](#)

policy maps

- and CoS classification [2-284](#)
- and DSCP classification [2-285](#)
- and IP precedence classification [2-287](#)
- and policing [2-326](#)
- applying [2-381](#)
- applying to an interface [2-337, 2-381, 2-393](#)
- child [2-383](#)
- creating [2-336](#)
- displaying [2-562](#)
- hierarchical [2-383](#)
- parent [2-383](#)

- policy maps (continued)
  - policers
    - for a single class [2-323](#)
    - for multiple classes [2-328, 2-332, 2-334, 2-383](#)
  - setting priority [2-345](#)
  - setting QoS group identifier [2-391](#)
  - traffic classification, defining [2-35](#)
  - traffic marking
    - setting CoS values [2-385](#)
    - setting DSCP values [2-387](#)
    - setting IP precedence values [2-389](#)
- Port Aggregation Protocol
  - See EtherChannel
- port-based authentication
  - AAA method list [2-3](#)
  - configuring violation modes [2-113](#)
  - debug messages, display [B-3](#)
  - enabling 802.1x
    - globally [2-108](#)
    - per interface [2-103](#)
  - host modes [2-98](#)
  - IEEE 802.1x AAA accounting methods [2-1](#)
  - initialize an interface [2-100, 2-110](#)
  - manual control of authorization state [2-103](#)
  - multiple hosts on authorized port [2-98](#)
  - periodic re-authentication
    - enabling [2-106](#)
    - time between attempts [2-111](#)
  - quiet period between failed authentication exchanges [2-111](#)
  - re-authenticating 802.1x-enabled ports [2-105](#)
  - resetting configurable 802.1x parameters [2-97](#)
  - switch-to-authentication server retransmission time [2-111](#)
  - switch-to-client frame-retransmission number [2-101 to 2-102](#)
  - switch-to-client retransmission time [2-111](#)
  - test for IEEE 802.1x readiness [2-109](#)
- port-channel load-balance command [2-339](#)
- Port Fast, for spanning tree [2-661](#)
- port ranges, defining [2-47, 2-61, 2-77](#)
- ports, debugging [B-78](#)
- ports, protected [2-696](#)
- port security
  - aging [2-692](#)
  - debug messages, display [B-80](#)
  - enabling [2-688](#)
  - violation error recovery [2-118](#)
- port shaping [2-397](#)
- port-type command [2-341](#)
- port types, MVR [2-305](#)
- power information, displaying [2-431](#)
- power-supply alarm indications, configuring [2-343](#)
- power-supply dual command [2-343](#)
- power-supply status, displaying [2-431](#)
- precedence
  - for QoS traffic marking [2-389](#)
  - setting in policy maps [2-389](#)
- priority command [2-345](#)
- priority queuing, QoS [2-345](#)
- priority with police, QoS [2-345](#)
- private-vlan command [2-348](#)
- private-vlan mapping command [2-351](#)
- private VLANs
  - association [2-694](#)
  - configuring [2-348](#)
  - configuring ports [2-685](#)
  - displaying [2-594](#)
  - host ports [2-685](#)
  - mapping
    - configuring [2-694](#)
    - displaying [2-453](#)
  - promiscuous ports [2-685](#)
- privileged EXEC mode [1-2, 1-3](#)
- product identification information, displaying [2-469](#)
- promiscuous ports, private VLANs [2-685](#)
- PVST+
  - See STP

**Q**

## QoS

## aggregate policers

applying [2-332](#)creating [2-328](#)displaying [2-558](#)

## class maps

creating [2-37](#)defining the match criteria [2-284](#)displaying [2-407](#)conform actions, configuring [2-60](#)displaying statistics for [2-562](#), [C-35](#)exceed actions, configuring [2-136](#)

## policy maps

applying an aggregate policer [2-328](#), [2-332](#), [2-334](#), [2-383](#)applying to an interface [2-381](#), [2-393](#)creating [2-336](#)defining policers [2-323](#)displaying policy maps [2-562](#)setting CoS values [2-385](#)setting DSCP values [2-387](#)setting IP precedence values [2-389](#)setting QoS group identifier [2-391](#)traffic classifications [2-35](#)

## table maps

configuring [2-706](#)displaying [2-587](#)violate actions, configuring [2-725](#)

## QoS groups

as match criteria [2-289](#)for QoS traffic classification [2-391](#)setting in policy maps [2-391](#)

## QoS match criteria

ACLs [2-283](#)CoS value [2-284](#)DSCP value [2-285](#), [2-291](#)

## QoS match criteria (continued)

precedence value [2-287](#)QoS group number [2-289](#)

## quality of service

See QoS

querytime, MVR [2-302](#)queue-limit command [2-353](#)**R**

## rapid per-VLAN spanning-tree plus

See STP

## rapid PVST+

See STP

re-authenticating 802.1x-enabled ports [2-105](#)

## re-authentication

periodic [2-106](#)time between attempts [2-111](#)receiver ports, MVR [2-305](#)receiving flow-control packets [2-137](#)

## recovery mechanism

causes [2-118](#)display [2-405](#), [2-433](#), [2-437](#)timer interval [2-119](#)remote-span command [2-356](#)

## Remote Switched Port Analyzer

See RSPAN

rename (boot loader) command [A-20](#)renew ip dhcp snooping database command [2-358](#)rep admin vlan command [2-359](#)rep block port command [2-360](#)rep lsl-age-timer command [2-363](#)rep preempt delay command [2-365](#)rep preempt segment command [2-367](#)rep segment command [2-368](#)rep stcn command [2-371](#)reset (boot loader) command [A-21](#)resource templates, displaying [2-575](#)rmdir (boot loader) command [A-22](#)

rmon collection stats command [2-373](#)

root guard, for spanning tree [2-630](#)

routed ports

IP addresses on [2-151](#)

number supported [2-151](#)

RSPAN

configuring [2-298](#)

displaying [2-546](#)

filter RSPAN traffic [2-298](#)

remote-span command [2-356](#)

sessions

add interfaces to [2-298](#)

displaying [2-546](#)

start new [2-298](#)

## S

scheduled switchover

disabling [2-93](#)

enabling [2-93](#)

scheduling diagnostic tests [2-93](#)

sdm prefer command [2-374](#)

SDM templates

allowed resources [2-375](#)

displaying [2-575](#)

dual IPv4 and IPv6 [2-374](#)

secure ports, limitations [2-690](#)

sending flow-control packets [2-137](#)

service instance command [2-377](#)

service instances, displaying [2-445](#)

service password-recovery command [2-379](#)

service policy (policy-map class configuration) command [2-383](#)

service-policy interface configuration command [2-381](#)

service-policy policy-map class configuration command [2-383](#)

set (boot loader) command [A-23](#)

set cos command [2-385](#)

set dscp command [2-387](#)

set precedence command [2-389](#)

set qos-group command [2-391](#)

setup command [2-393](#)

SFPs, displaying information about [2-469](#)

shape average command [2-396](#)

show access-lists command [2-398](#)

show aggregate-policer command [2-587](#)

show archive status command [2-401](#)

show arp access-list command [2-402](#)

show boot command [2-403](#)

show class-map command [2-407](#)

show controllers cpu-interface command [2-408](#)

show controllers ethernet-controller command [2-410](#)

show controllers team command [2-417](#)

show controllers utilization command [2-419](#)

show controller utilization command [2-419](#)

show cpu traffic qos command [2-421](#)

show diagnostic command [2-423](#)

show dot1q-tunnel command [2-427](#)

show dot1x command [2-428](#)

show env command [2-431](#)

show errdisable detect command [2-433](#)

show errdisable flap-values command [2-435](#)

show errdisable recovery command [2-437](#)

show etherchannel command [2-439](#)

show ethernet loopback command [2-442](#)

show ethernet service evc command [2-444](#)

show ethernet service instance command [2-445](#)

show ethernet service interface command [2-447](#)

show flowcontrol command [2-449](#)

show idprom command [2-451](#)

show interface rep command [2-463](#)

show interfaces command [2-453](#)

show interfaces counters command [2-461](#)

show interfaces rep command [2-463](#)

show interface transceivers command [2-465](#)

show inventory command [2-469](#)

show ip arp inspection command [2-470](#)

show ipc command [2-499](#)

- show ip dhcp snooping binding command [2-475](#)
- show ip dhcp snooping command [2-474](#)
- show ip dhcp snooping database command [2-477, 2-479](#)
- show ip igmp profile command [2-482](#)
- show ip igmp snooping command [2-483](#)
- show ip igmp snooping command querier detail [2-489](#)
- show ip igmp snooping groups command [2-485](#)
- show ip igmp snooping mrouter command [2-487](#)
- show ip igmp snooping querier command [2-489](#)
- show ip igmp snooping querier detail command [2-489](#)
- show ip sla standards command [2-491](#)
- show ip sla twamp connection [2-421](#)
- show ip sla twamp connection command [2-492](#)
- show ip sla twamp session command [2-494](#)
- show ip source binding command [2-496](#)
- show ipv6 access-list command [2-503](#)
- show ipv6 dhcp conflict command [2-505](#)
- show ipv6 route updated command [2-506](#)
- show ip verify source command [2-497](#)
- show l2protocol-tunnel command [2-508](#)
- show lacp command [2-510](#)
- show link state group command [2-514](#)
- show location command [2-516](#)
- show logging onboard command [2-519](#)
- show mac access-group command [2-523](#)
- show mac address-table address command [2-527](#)
- show mac address-table aging time command [2-529](#)
- show mac address-table command [2-525](#)
- show mac address-table count command [2-531](#)
- show mac address-table dynamic command [2-533](#)
- show mac address-table interface command [2-535](#)
- show mac address-table learning command [2-537](#)
- show mac address-table move update command [2-538](#)
- show mac address-table notification command [2-49, 2-540, B-32](#)
- show mac address-table static command [2-542](#)
- show mac address-table vlan command [2-544](#)
- show monitor command [2-546](#)
- show mvr command [2-548](#)
- show mvr interface command [2-550](#)
- show mvr members command [2-552](#)
- show pagp command [2-554](#)
- show parser macro command [2-556](#)
- show platform acl command [C-2](#)
- show platform backup interface command [C-3](#)
- show platform cfm command [C-4](#)
- show platform configuration command [C-5](#)
- show platform dl command [C-6](#)
- show platform etherchannel command [C-7](#)
- show platform forward command [C-8](#)
- show platform frontend-controller command [C-10](#)
- show platform igmp snooping command [C-11](#)
- show platform ipc trace command [C-16](#)
- show platform ip multicast command [C-13](#)
- show platform ip unicast command [C-14](#)
- show platform ipv6 unicast command [C-17](#)
- show platform l2pt dm command [C-19](#)
- show platform layer4op command [C-20, C-42](#)
- show platform mac-address-table command [C-21](#)
- show platform messaging command [C-22](#)
- show platform monitor command [C-23](#)
- show platform mvr table command [C-24](#)
- show platform pm command [C-25](#)
- show platform policer cpu command [C-26](#)
- show platform port-asic command [C-30](#)
- show platform port-security command [C-34](#)
- show platform qos command [C-35](#)
- show platform resource-manager command [C-38](#)
- show platform snmp counters command [C-40](#)
- show platform spanning-tree synchronization command [C-41](#)
- show platform stp-instance command [C-43](#)
- show platform team command [C-44](#)
- show platform vlan command [C-47](#)
- show platform vlan mapping command [C-48](#)
- show policer aggregate command [2-558](#)
- show policer cpu uni-eni command [2-559](#)
- show policy-map command [2-562](#)



- show policy-map interface output fields [2-566](#)
- show port security command [2-567](#)
- show port-type command [2-570](#)
- show rep topology command [2-572](#)
- show sdm prefer command [2-575](#)
- show spanning-tree command [2-577](#)
- show storm-control command [2-584](#)
- show system mtu command [2-586](#)
- show udd command [2-589](#)
- show version command [2-592](#)
- show vlan access-map command [2-599](#)
- show vlan command [2-594](#)
- show vlan command, fields [2-596](#)
- show vlan filter command [2-600](#)
- show vlan mapping command [2-601](#)
- show vmps command [2-603](#)
- shutdown command [2-605](#)
- shutdown threshold, Layer 2 protocol tunneling [2-241](#)
- shutdown vlan command [2-606](#)
- SNMP host, specifying [2-612](#)
- SNMP informs, enabling the sending of [2-608](#)
- snmp mib rep trap-rate command [2-607](#)
- snmp-server enable traps command [2-608](#)
- snmp-server host command [2-612](#)
- snmp trap mac-notification change command [2-616](#)
- SNMP traps
  - enabling MAC address notification trap [2-616](#)
  - enabling the MAC address notification feature [2-268](#)
  - enabling the sending of [2-608](#)
- software images
  - deleting [2-79](#)
  - downloading [2-9](#)
  - upgrading [2-9](#)
  - uploading [2-15](#)
- software version, displaying [2-592](#)
- source ports, MVR [2-305](#)
- SPAN
  - configuring [2-298](#)
  - debug messages, display [B-33](#)
  - displaying [2-546](#)
  - filter SPAN traffic [2-298](#)
  - sessions
    - add interfaces to [2-298](#)
    - displaying [2-546](#)
    - start new [2-298](#)
  - spanning-tree bpdudfilter command [2-618, 2-620](#)
  - spanning-tree bpduguard command [2-622](#)
  - spanning-tree cost command [2-624](#)
  - spanning-tree etherchannel command [2-626](#)
  - spanning-tree extend system-id command [2-628](#)
  - spanning-tree guard command [2-630](#)
  - spanning-tree link-type command [2-632](#)
  - spanning-tree loopguard default command [2-634](#)
  - spanning-tree mode command [2-636](#)
  - spanning-tree mst configuration command [2-638](#)
  - spanning-tree mst cost command [2-640](#)
  - spanning-tree mst forward-time command [2-642](#)
  - spanning-tree mst hello-time command [2-643](#)
  - spanning-tree mst max-age command [2-645](#)
  - spanning-tree mst max-hops command [2-647](#)
  - spanning-tree mst port-priority command [2-649](#)
  - spanning-tree mst pre-standard command [2-651](#)
  - spanning-tree mst priority command [2-652](#)
  - spanning-tree mst root command [2-654](#)
  - spanning-tree portfast (global configuration) command [2-658](#)
  - spanning-tree portfast (interface configuration) command [2-661](#)
  - spanning-tree port-priority command [2-656](#)
  - Spanning Tree Protocol
    - See STP
  - spanning-tree vlan command [2-663](#)
  - speed command [2-666](#)
  - SSH, configuring version [2-208](#)
  - static-access ports, configuring [2-673](#)
  - statistics, Ethernet group [2-373](#)

- sticky learning, enabling [2-688](#)
  - storm-control command [2-668](#)
  - STP
    - counters, clearing [2-55](#)
    - debug messages, display
      - MSTP [B-86](#)
      - optimized BPDUs handling [B-85](#)
      - spanning-tree activity [B-82](#)
      - switch shim [B-88](#)
      - transmitted and received BPDUs [B-84](#)
    - enabling on ENIs [2-618](#)
    - enabling protocol tunneling for [2-241](#)
    - EtherChannel misconfiguration [2-626](#)
    - extended system ID [2-628](#)
    - path cost [2-624](#)
    - protocol modes [2-636](#)
    - root port
      - loop guard [2-630](#)
      - preventing from becoming designated [2-630](#)
      - restricting which can be root [2-630](#)
      - root guard [2-630](#)
    - root switch
      - affects of extended system ID [2-628, 2-664](#)
      - hello-time [2-663](#)
      - interval between BDPUs messages [2-663](#)
      - interval between hello BDPUs messages [2-663](#)
      - max-age [2-663](#)
      - port priority for selection of [2-656](#)
      - primary or secondary [2-663](#)
      - switch priority [2-663](#)
    - state changes
      - blocking to forwarding state [2-661](#)
      - enabling BDPUs filtering [2-620, 2-658](#)
      - enabling BDPUs guard [2-622, 2-658](#)
      - enabling Port Fast [2-658, 2-661](#)
      - enabling timer to recover from error state [2-118](#)
      - forward-delay time [2-663](#)
      - length of listening and learning states [2-663](#)
      - shutting down Port Fast-enabled ports [2-658](#)
  - STP (continued)
    - state information display [2-577](#)
    - VLAN options [2-652, 2-663](#)
  - SVIs, creating [2-145](#)
  - Switched Port Analyzer
    - See SPAN
  - switching characteristics
    - modifying [2-671](#)
    - returning to interfaces [2-671](#)
  - switchport access command [2-673](#)
  - switchport backup interface command [2-675](#)
  - switchport block command [2-679](#)
  - switchport command [2-671](#)
  - switchport host command [2-681](#)
  - switchport mode command [2-682](#)
  - switchport mode private-vlan command [2-685](#)
  - switchport port-security aging command [2-692](#)
  - switchport port-security command [2-688](#)
  - switchport private-vlan command [2-694](#)
  - switchport protected command [2-696](#)
  - switchports, displaying [2-453](#)
  - switchport trunk command [2-698](#)
  - switchport vlan mapping command [2-700](#)
  - system env temperature threshold yellow command [2-703](#)
  - system message logging, save message to flash [2-257](#)
  - system mtu command [2-704](#)
  - system resource templates [2-374](#)
- 
- T**
  - table-map command [2-706](#)
  - table-map configuration mode [2-706](#)
  - table maps
    - configuring [2-706](#)
    - displaying [2-587](#)
    - QoS [2-706](#)
  - tar files, creating, listing, and extracting [2-12](#)
  - TDR, running [2-708](#)
  - temperature information, displaying [2-431](#)

temperature status, displaying [2-431](#)  
 templates, system resources [2-374](#)  
 test cable-diagnostics tdr command [2-708](#)  
 traceroute mac command [2-710](#)  
 traceroute mac ip command [2-713](#)  
 traffic shaping, QoS [2-396](#)  
 trunking, VLAN mode [2-682](#)  
 trunk mode [2-682](#)  
 trunk ports [2-682](#)  
 tunnel ports, Layer 2 protocol, displaying [2-508](#)  
 type (boot loader) command [A-26](#)

## U

### UDLD

aggressive mode [2-715, 2-717](#)  
 debug messages, display [B-94](#)  
 enable globally [2-715](#)  
 enable per interface [2-717](#)  
 error recovery timer [2-118](#)  
 message timer [2-715](#)  
 normal mode [2-715, 2-717](#)  
 reset a shutdown interface [2-719](#)  
 status [2-589](#)

udld command [2-715](#)  
 udld port command [2-717](#)  
 udld reset command [2-719](#)

### UNI

bundling and multiplexing [2-132](#)  
 Ethernet [2-132](#)

unicast storm control [2-668](#)  
 uni count command [2-720](#)

### UniDirectional Link Detection

See UDLD

UNI ID, Ethernet [2-134](#)  
 uni-vlan command [2-722](#)  
 unknown multicast traffic, preventing [2-679](#)  
 unknown unicast traffic, preventing [2-679](#)  
 unset (boot loader) command [A-27](#)

upgrading  
     software images [2-9](#)  
         monitoring status of [2-401](#)  
 user EXEC mode [1-2](#)  
 user network interface [2-341](#)

## V

version (boot loader) command [A-29](#)  
 violate-action command [2-724](#)  
 vlan access-map command [2-729](#)  
 VLAN access map configuration mode [2-729](#)  
 VLAN access maps  
     actions [2-5](#)  
     displaying [2-599](#)  
 vlan command [2-726](#)  
 VLAN configuration mode  
     commands [2-726](#)  
     description [1-4](#)  
     entering [2-726](#)  
     summary [1-2](#)  
 vlan dot1q tag native command [2-731](#)  
 vlan filter command [2-733](#)  
 VLAN filters, displaying [2-600](#)  
 VLAN ID range [2-726](#)  
 VLAN ID translation  
     See VLAN mapping  
 VLAN mapping  
     configuring [2-700](#)  
     described [2-701](#)  
     displaying [2-601](#)  
 VLAN maps  
     applying [2-733](#)  
     creating [2-729](#)  
     defining [2-281](#)  
     displaying [2-599](#)  
 VLAN Query Protocol  
     See VQP

## VLANs

- adding [2-726](#)
- configuring [2-726](#)
- debug messages, display
  - activation of [B-92](#)
  - VLAN IOS file system error tests [B-91](#)
  - VLAN manager activity [B-90](#)
- displaying configurations [2-594](#)
- extended-range [2-726](#)
- MAC addresses
  - displaying [2-544](#)
  - number of [2-531](#)
- normal-range [2-726](#)
- private [2-685](#)
  - configuring [2-348](#)
  - displaying [2-594](#)
- See also private VLANs
- restarting [2-606](#)
- saving the configuration [2-726](#)
- shutting down [2-606](#)
- suspending [2-606](#)

## VMPS

- configuring servers [2-738](#)
- displaying [2-603](#)
- error recovery timer [2-119](#)
- reconfirming dynamic VLAN assignments [2-735](#)
- vmips reconfirm (global configuration) command [2-736](#)
- vmips reconfirm (privileged EXEC) command [2-735](#)
- vmips retry command [2-737](#)
- vmips server command [2-738](#)

## VQP

- and dynamic-access ports [2-674](#)
  - clearing client statistics [2-58](#)
  - displaying information [2-603](#)
  - per-server retry count [2-737](#)
  - reconfirmation interval [2-736](#)
  - reconfirming dynamic VLAN assignments [2-735](#)
- VTP, enabling tunneling for [2-241](#)

---

**W**

## Weighted Tail Drop

See WTD

WTD, queue-limit command [2-353](#)