

Send document comments to ucs-docfeedback@cisco.com



Cisco Driver Installer Utility, Release 2.0(1) User Guide

For Cisco UCS C-Series Servers January 14, 2011

Americas Headquarters

Cisco Systems, Inc. 170 West Tasman Drive San Jose, CA 95134-1706 USA

http://www.cisco.com Tel: 408 526-4000

800 553-NETS (6387)

Fax: 408 527-0883

Text Part Number: OL-24079-01

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

Cisco Driver Installer Utility User Guide
© 2011 Cisco Systems, Inc. All rights reserved.



Preface

This preface describes the organization and conventions of the Cisco Driver Installer Utility User Guide.

Organization

This guide is organized as follows:

Chapter Number	Chapter Title	Description
1	Introduction	Contains an overview of the Cisco Driver Installer Utility.
2	Using the Cisco Driver Installer Utility	Contains information on using the Cisco Driver Installer Utility.

Related Documentation

Documentation for Cisco UCS C-Series Rack-Mount Servers is available at the following URL:

http://www.cisco.com/go/unifiedcomputing/c-series-doc

Documentation for Cisco UCS Server Configuration Utility 2.0(1) is available at the following URL:

http://www.cisco.com/en/US/products/ps10493/products_user_guide_list.html

Obtaining Documentation and Submitting a Service Request

For information on obtaining documentation, submitting a service request, and gathering additional information, see the monthly *What's New in Cisco Product Documentation*, which also lists all new and revised Cisco technical documentation, at:

http://www.cisco.com/en/US/docs/general/whatsnew/whatsnew.html

Subscribe to the *What's New in Cisco Product Documentation* as a Really Simple Syndication (RSS) feed and set content to be delivered directly to your desktop using a reader application. The RSS feeds are a free service and Cisco currently supports RSS Version 2.0.



CONTENTS

Preface i

Organization i

Related Documentation i

Obtaining Documentation and Submitting a Service Request i

Introduction 1-1

Overview of the Cisco Driver Installer Utility 1-1

Supported Operating Systems and Versions 1-1

Supported Hardware Platforms 1-2

Using the Cisco Driver Installer Utility 2-1

Opening the Utility 2-1

Installing the Driver Updates 2-2

Contents



docfeedback@cisco.com

CHAPTER

Introduction

This chapter introduces you to the Cisco Driver Installer Utility. This chapter discusses the following topics:

- Overview of the Cisco Driver Installer Utility
- Supported Operating Systems and Versions
- Supported Hardware Platforms

Overview of the Cisco Driver Installer Utility

The Cisco Driver Installer utility enables you to install or update drivers for all Cisco supported devices. This utility is available on the Cisco UCS Server Configuration Utility (SCU) 2.0(1) release CD.

The Graphical User Interface (GUI) of the utility lists all the Cisco supported device drivers that are installed in the server. It lists the installed driver version and the most recent driver version that is available. The **Action** column lists the action that you can take on each device driver. The value displayed can be either Install, Update, or Force Update. The **Action** column displays the value Install when no driver is installed for a device. The **Action** column displays the value Update when a more recent version of a driver is available. The **Action** column displays the value Forced Update when the version of the driver that is installed and most recently available version is the same, or when the installed driver version is more recent than what is available. Based on the values displayed in the **Action** column, you can install the driver updates. You can install the updates individually on each driver, or you can select all the drivers and initiate an update.

By using this utility, you can install updates for the drivers either from a CD, from the network or from http://www.cisco.com. For a few device drivers, you might have to restart the server for the most recent changes to take effect. In such instances, you are prompted to decide whether or not you would like to restart the system immediately for the changes to take effect. Until you restart your system, the most recent driver updates will not be used.

Supported Operating Systems and Versions

The Cisco Driver Installer utility supports the following operating systems:

- Microsoft Windows 2003 x86 SP2
- Microsoft Windows 2003 x86 SP2 R2
- Microsoft Windows 2003 x64 SP2


Send document comments to ucs-docfeedback@cisco.com

- Microsoft Windows 2003 x64 SP2 R2
- Microsoft Windows 2008 x64
- Microsoft Windows 2008 R2 x64

Supported Hardware Platforms

The Cisco Driver Installer utility is supported on the following hardware platforms:

- Cisco UCS C200 Series
- Cisco UCS C210 Series
- Cisco UCS C250 Series
- Cisco UCS C460 Series (supported only with Microsoft Windows 2008)





Using the Cisco Driver Installer Utility

This chapter discusses the tasks that you can perform using the Cisco Driver Installer utility. This chapter discusses the following topics:

- Opening the Utility
- Installing the Driver Updates

Opening the Utility

The Cisco Driver Installer Utility is available on the Cisco UCS Server Configuration Utility (SCU) 2.0

To open the utility, follow these steps:

- Step 1 Ensure that your server and operating system supports this utility. For more information, see sections Supported Operating Systems and Versions and Supported Hardware Platforms.
- Step 2 Insert the Cisco UCS SCU 2.0 CD into the CD drive of the server.

The autorun of the CD is initiated.

Step 3 Click Launch Cisco Driver Installer Utility.

Optionally, you can run the following command at the command prompt:

%CDDRIVE%\DriverUpdate\DriverInstall.exe

The Cisco Driver Installer utility opens.

When you open the utility, a list of all device drivers that are currently installed in the server is displayed, along with the available updated versions. The Action column indicates either Install, Update, or Force Update based on the current device driver version. The **Reboot** column indicates whether a reboot is required after the update is installed. The **Remarks** column indicates whether the update installation was successful.

Send document comments to ucs-docfeedback@cisco.com

Installing the Driver Updates

After you open the Cisco Driver Installer utility GUI, you can either update the driver versions individually or you can select all the drivers and install the updates. Irrespective of what you choose to do, the procedure to install the updates is the same. Using this utility, you can install the driver updates from one of the following locations:

- SCU CD
- A location on the network
- www.cisco.com

To determine the most recent driver versions, see the *Hardware and Software Interoperability Matrix for C Series Servers* available at:

http://www.cisco.com/en/US/products/ps10477/prod_technical_reference_list.html

To install updates on a driver, follow these steps:

- **Step 1** Select the drivers on which you want to install the updates.
 - After you select a driver, the **Driver Description** field is populated with information about the driver.
- **Step 2** Click **Settings** to view the Driver Source page.
- **Step 3** On this page, specify the location of the updates that you want to install. You can select one of the following:
 - CD
 - Network
 - · Cisco.com
- **Step 4** If you selected CD, ensure that the SCU CD is present in the server or is mounted over VMedia.
- **Step 5** If you selected Network, you should have already downloaded the driver package that contains the updated driver versions to a location on the network. This driver package is a zipped file that contains several other zipped files that contain the updated driver versions. To install the driver updates using the Network option, follow these steps:
 - a. Click **Browse** to search for and select the zipped file that contains the updated driver version.
 - **b.** Click Open.
 - c. In the Driver Source dialog box, click OK.
- **Step 6** If you selected Cisco.com, you are prompted to enter your registered username and password to access the driver updates on http://www.cisco.com.

After you enter your credentials, the utility retrieves the driver packages from the website.

- **Step 7** Click **Install** to start installing the driver updates.
- Step 8 To confirm that you want to continue with the installation, click Yes in the confirmation dialog box.

A progress bar indicates the progress of the installation.

- **Step 9** After the driver updates are installed, the **Remarks** column indicates Success.
 - Some drivers might require a reboot for the new version to take effect. In such cases, you are prompted to determine if you would like to restart the server immediately or at a later time.
- **Step 10** Click **Refresh** to view the updated version information of all the drivers.



INDEX

ī

```
Installing
CD 2-2
cisco.com 2-2
driver updates 2-2
network 2-2
```

S

```
Supported
hardware 1-2
OS 1-1
```

U

```
Utility
overview 1-1
supported OS 1-1
```

Index