



# Configuring Port Profiles

---

This chapter includes the following sections:

- [Port Profiles, page 1](#)
- [Port Profile Clients, page 1](#)
- [Creating a Port Profile, page 2](#)
- [Deleting a Port Profile, page 3](#)
- [Adding a Named VLAN to a Port Profile, page 4](#)
- [Deleting a Named VLAN from a Port Profile, page 5](#)
- [Adding a Port Profile Client to a Port Profile, page 5](#)
- [Deleting a Port Profile Client from a Port Profile, page 7](#)

## Port Profiles

Port profiles contain the properties and settings that you can use to configure virtual interfaces in Cisco UCS for VM-FEX. The port profiles are created and administered in Cisco UCS Manager. After a port profile is created, assigned to, and actively used by one or more clusters, any changes made to the networking properties of the port profile in Cisco UCS Manager are immediately applied to those clusters.

## Port Profile Clients

The port profile client determines the cluster or clusters to which a port profile is applied.

# Creating a Port Profile


**Note**

In a VM-FEX for KVM system, the following conditions apply:

- The **set max-ports** command applies to the cluster; there is no distributed virtual switch (DVS).
- The **set host-nwio-perf** command has no effect.

**Procedure**

	Command or Action	Purpose
<b>Step 1</b>	UCS-A# <b>scope system</b>	Enters system mode.
<b>Step 2</b>	UCS-A /system # <b>scope vm-mgmt</b>	Enters system VM management mode.
<b>Step 3</b>	UCS-A /system/vm-mgmt # <b>scope profile-set</b>	Enters system VM management profile set mode.
<b>Step 4</b>	UCS-A /system/vm-mgmt/profile-set # <b>create port-profile profile-name</b>	Creates the specified port profile and enters system VM management profile set port profile mode.
<b>Step 5</b>	UCS-A /system/vm-mgmt/profile-set/port-profile # <b>set descr description</b>	(Optional) Provides a description for the port profile. <b>Note</b> If your description includes spaces, special characters, or punctuation, you must begin and end your description with quotation marks. The quotation marks do not appear in the description field of any <b>show</b> command output.
<b>Step 6</b>	UCS-A /system/vm-mgmt/profile-set/port-profile # <b>set host-nwio-perf {high-performance   none}</b>	You can choose one of the following options: <ul style="list-style-type: none"> <li>• <b>high-performance</b></li> <li>• <b>none</b></li> </ul>
<b>Step 7</b>	UCS-A /system/vm-mgmt/profile-set/port-profile # <b>set max-ports max-num</b>	Specifies the maximum number of ports that the port profile can use.  The maximum number of ports that can be associated to a port profile is 4096. The default is 64 ports. If the DVS has more than one associated port profile, each port profile client can be set to use a maximum of 4096 ports.
<b>Step 8</b>	UCS-A /system/vm-mgmt/profile-set/port-profile # <b>set nw-control-policy policy-name</b>	Specifies the network control policy to use for the profile.

	Command or Action	Purpose
<b>Step 9</b>	UCS-A /system/vm-mgmt/profile-set/port-profile # <b>set pin-group</b> <i>group-name</i>	Specifies the LAN pin group to use for the port profile.
<b>Step 10</b>	UCS-A /system/vm-mgmt/profile-set/port-profile # <b>set qos-policy</b> <i>policy-name</i>	Specifies the QoS policy to use for the port profile.
<b>Step 11</b>	UCS-A /system/vm-mgmt/profile-set/port-profile # <b>commit-buffer</b>	Commits the transaction.

The following example shows how to create and configure a port profile named MyProfile and commit the transaction:

```
UCS-A# scope system
UCS-A /system # scope vm-mgmt
UCS-A /system/vm-mgmt # scope profile-set
UCS-A /system/vm-mgmt/profile-set # create port-profile MyProfile
UCS-A /system/vm-mgmt/profile-set/port-profile* # set descr "This is my port profile"
UCS-A /system/vm-mgmt/profile-set/port-profile* # set max-ports 24
UCS-A /system/vm-mgmt/profile-set/port-profile* # set nw-control-policy ncp5
UCS-A /system/vm-mgmt/profile-set/port-profile* # set pin-group PinGroup54
UCS-A /system/vm-mgmt/profile-set/port-profile* # set qos-policy QosPolicy34
UCS-A /system/vm-mgmt/profile-set/port-profile* # commit-buffer
UCS-A /system/vm-mgmt/profile-set/port-profile #
```

### What to Do Next

Add a port profile client to the port profile.

## Deleting a Port Profile

You cannot delete a port profile if a VM is actively using that port profile.

### Procedure

	Command or Action	Purpose
<b>Step 1</b>	UCS-A# <b>scope system</b>	Enters system mode.
<b>Step 2</b>	UCS-A /system # <b>scope vm-mgmt</b>	Enters system VM management mode.
<b>Step 3</b>	UCS-A /system/vm-mgmt # <b>scope profile-set</b>	Enters system VM management profile set mode.
<b>Step 4</b>	UCS-A /system/vm-mgmt/profile-set # <b>delete port-profile</b> <i>profile-name</i>	Deletes the specified port profile.
<b>Step 5</b>	UCS-A /system/vm-mgmt/profile-set # <b>commit-buffer</b>	Commits the transaction. Cisco UCS Manager deletes the port profile and all associated port profile clients.

The following example shows how to delete the port profile named MyProfile and commit the transaction:

```
UCS-A# scope system
UCS-A /system # scope vm-mgmt

UCS-A /system/vm-mgmt # scope profile-set
UCS-A /system/vm-mgmt/profile-set # delete port-profile MyProfile
UCS-A /system/vm-mgmt/profile-set* # commit-buffer
UCS-A /system/vm-mgmt/profile-set #
```

## Adding a Named VLAN to a Port Profile

### Procedure

	Command or Action	Purpose
<b>Step 1</b>	UCS-A# <b>scope system</b>	Enters system mode.
<b>Step 2</b>	UCS-A /system # <b>scope vm-mgmt</b>	Enters system VM management mode.
<b>Step 3</b>	UCS-A /system/vm-mgmt # <b>scope profile-set</b>	Enters system VM management profile set mode.
<b>Step 4</b>	UCS-A /system/vm-mgmt/profile-set # <b>scope port-profile profile-name</b>	Enters system VM management profile set port profile mode for the specified port profile.
<b>Step 5</b>	UCS-A /system/vm-mgmt/profile-set/port-profile # <b>create vlan vlan-name</b>	Specifies a named VLAN to use for the port profile. <b>Note</b> You can create multiple VLANs for guest VLAN trunking.
<b>Step 6</b>	UCS-A /system/vm-mgmt/profile-set/port-profile/vlan # <b>set default-net no</b>	(Optional) Sets the default-net VLAN as the native VLAN in UCS Manager.
<b>Step 7</b>	UCS-A /system/vm-mgmt/profile-set/port-profile/vlan # <b>commit-buffer</b>	Commits the transaction.

The following example shows how to add the VLAN named accounting to the port profile named MyProfile, set the VLAN as non-native, and commit the transaction:

```
UCS-A# scope system
UCS-A /system # scope vm-mgmt

UCS-A /system/vm-mgmt # scope profile-set
UCS-A /system/vm-mgmt/profile-set # scope port-profile MyProfile
UCS-A /system/vm-mgmt/profile-set/port-profile # create vlan accounting
UCS-A /system/vm-mgmt/profile-set/port-profile/vlan* # set default-net no
UCS-A /system/vm-mgmt/profile-set/port-profile/vlan* # commit-buffer
UCS-A /system/vm-mgmt/profile-set/port-profile/vlan #
```

## Deleting a Named VLAN from a Port Profile

### Procedure

	Command or Action	Purpose
<b>Step 1</b>	UCS-A# <b>scope system</b>	Enters system mode.
<b>Step 2</b>	UCS-A /system # <b>scope vm-mgmt</b>	Enters system VM management mode.
<b>Step 3</b>	UCS-A /system/vm-mgmt # <b>scope profile-set</b>	Enters system VM management profile set mode.
<b>Step 4</b>	UCS-A /system/vm-mgmt/profile-set # <b>scope port-profile profile-name</b>	Enters system VM management profile set port profile mode for the specified port profile.
<b>Step 5</b>	UCS-A /system/vm-mgmt/profile-set/port-profile # <b>delete vlan vlan-name</b>	Deletes the specified named VLAN from the port profile.
<b>Step 6</b>	UCS-A /system/vm-mgmt/profile-set/port-profile # <b>commit-buffer</b>	Commits the transaction.

The following example shows how to delete the VLAN named accounting from the port profile named MyProfile and commit the transaction:

```
UCS-A# scope system
UCS-A /system # scope vm-mgmt

UCS-A /system/vm-mgmt# scope profile-set
UCS-A /system/vm-mgmt/profile-set # scope port-profile MyProfile
UCS-A /system/vm-mgmt/profile-set/port-profile # delete vlan accounting
UCS-A /system/vm-mgmt/profile-set/port-profile* # commit-buffer
UCS-A /system/vm-mgmt/profile-set/port-profile #
```

## Adding a Port Profile Client to a Port Profile

### Procedure

	Command or Action	Purpose
<b>Step 1</b>	UCS-A# <b>scope system</b>	Enters system mode.
<b>Step 2</b>	UCS-A /system # <b>scope vm-mgmt</b>	Enters system VM management mode.
<b>Step 3</b>	UCS-A /system/vm-mgmt # <b>scope profile-set</b>	Enters system VM management profile set mode.

	Command or Action	Purpose
<b>Step 4</b>	UCS-A /system/vm-mgmt/profile-set # <b>scope port-profile</b> <i>profile-name</i>	Enters system VM management profile set port profile mode for the specified port profile.
<b>Step 5</b>	UCS-A /system/vm-mgmt/profile-set/port-profile # <b>create client</b> <i>client-name</i>	Creates the specified port profile client and enters system VM management profile set port profile client mode.  The port profile client determines the clusters to which the port profile is applied. By default, a port profile applies to all clusters; however, you can use the optional <b>set data-center</b> , <b>set folder</b> , and <b>set cluster</b> commands to apply the port profile to all clusters in a specific datacenter or datacenter folder, or to a specific cluster.
<b>Step 6</b>	UCS-A /system/vm-mgmt/profile-set/port-profile/client # <b>set descr</b> <i>description</i>	(Optional) Provides a description for the port profile client.  <b>Note</b> If your description includes spaces, special characters, or punctuation, you must begin and end your description with quotation marks. The quotation marks do not appear in the description field of any <b>show</b> command output.
<b>Step 7</b>	UCS-A /system/vm-mgmt/profile-set/port-profile/client # <b>set cluster</b> <i>name</i>	(Optional) Specifies the cluster to which the port profile is applied.  In a VM-FEX for KVM system, apply the profile to the default cluster.
<b>Step 8</b>	UCS-A /system/vm-mgmt/profile-set/port-profile/client # <b>commit-buffer</b>	Commits the transaction.

The following example shows how to create a port profile client named MyClient that applies the port profile to the default cluster and commit the transaction:

```
UCS-A# scope system
UCS-A /system # scope vm-mgmt
UCS-A /system/vm-mgmt # scope profile-set
UCS-A /system/vm-mgmt/profile-set # scope port-profile MyProfile
UCS-A /system/vm-mgmt/profile-set/port-profile* # create client MyClient
UCS-A /system/vm-mgmt/profile-set/port-profile/client* # set descr "This is the client for
my port profile"
UCS-A /system/vm-mgmt/profile-set/port-profile/client* # set cluster default
UCS-A /system/vm-mgmt/profile-set/port-profile/client* # commit-buffer
UCS-A /system/vm-mgmt/profile-set/port-profile/client #
```

# Deleting a Port Profile Client from a Port Profile

You cannot delete a port profile client if a VM is actively using the port profile with which the client is associated.

## Procedure

	Command or Action	Purpose
<b>Step 1</b>	UCS-A# <b>scope system</b>	Enters system mode.
<b>Step 2</b>	UCS-A /system # <b>scope vm-mgmt</b>	Enters system VM management mode.
<b>Step 3</b>	UCS-A /system/vm-mgmt # <b>scope profile-set</b>	Enters system VM management profile set mode.
<b>Step 4</b>	UCS-A /system/vm-mgmt/profile-set # <b>scope port-profile <i>profile-name</i></b>	Enters system VM management profile set port profile mode for the specified port profile.
<b>Step 5</b>	UCS-A /system/vm-mgmt/profile-set/port-profile # <b>delete client <i>client-name</i></b>	Deletes the specified port profile client.
<b>Step 6</b>	UCS-A /system/vm-mgmt/profile-set/port-profile # <b>commit-buffer</b>	Commits the transaction.

The following example shows how to delete the port profile client named OtherClient from the port profile named MyProfile and commit the transaction:

```
UCS-A# scope system
UCS-A /system # scope vm-mgmt

UCS-A /system/vm-mgmt# scope profile-set
UCS-A /system/vm-mgmt/profile-set # scope port-profile MyProfile
UCS-A /system/vm-mgmt/profile-set/port-profile # delete client OtherClient
UCS-A /system/vm-mgmt/profile-set/port-profile* # commit-buffer
UCS-A /system/vm-mgmt/profile-set/port-profile #
```

