



APIC

This chapter contains the following sections:

- [Get VLAN From Deployed Device Cluster 5_3, on page 2](#)
- [GetL4L7DeviceNtpSnmParameters, on page 3](#)

Get VLAN From Deployed Device Cluster 5_3

Summary

Description

Inputs

Input	Description	Mappable To Type	Mandatory
Device Cluster		ApicDeviceTenantDeviceClusterIdentity	Y
Service Container		ServiceContainer	
Tier1		gen_text_input	
Tier2		gen_text_input	

Outputs

Output	Description	Type
OUTPUT_ASAV_VLAN1		vlanID
OUTPUT_ASAV_VLAN2		vlanID
SP_VNICs	Service Profile vNICs	ucsServiceProfileMultiVNICIdentity
UCS_Account	UCS Account	ucsAccountIdentity
ConfigureUCSM	ConfigureUCSM	gen_text_input

GetL4L7DeviceNtpSnmParameters

Summary

Description

Inputs

Input	Description	Mappable To Type	Mandatory
serviceContainer		ServiceContainer	Y

Outputs

Output	Description	Type
ntpServer		gen_text_input
snmpTrapClass		gen_text_input
snmpTrapDestination		gen_text_input
snmpCommunity		gen_text_input
snmpPermission		gen_text_input
snmpName		gen_text_input
snmpGroup		gen_text_input
snmpAuthType		gen_text_input
snmpAuthPwd		password
snmpPrivType		gen_text_input
snmpPrivPwd		password
isNetworkParameters		Boolean

