



Port Utilization in Unified CCX

- [Port Utilization Table Columns, page 1](#)
- [Unified CCX Port Utilization, page 2](#)
- [Unified IP IVR Port Utilization, page 7](#)

Port Utilization Table Columns

The columns in the port utilization tables in this document describe the following:

Listener (Process or Application Protocol)

A value representing the server or application and where applicable, the open or proprietary application protocol.

Listener Protocol and Port

An identifier for the TCP or UDP port that the server or application is listening on, along with the IP address for incoming connection requests when acting as a server.

Remote Device (Process or Application Protocol)

The remote application or device making a connection to the server or service specified by the protocol; or listening on the remote protocol and port.

Remote Protocol and Port

The identifier for the TCP or UDP port that the remote service or application is listening on, along with the IP address for incoming connection requests when acting as the server.

Traffic Direction

The direction that traffic flows through the port: Inbound, Bidirectional, Outbound.

**Note**

The operating system dynamically assigns the source port that the local application or service uses to connect to the destination port of a remote device. In most cases, this port is assigned randomly above TCP/UDP 1024.

Unified CCX Port Utilization

Table 1: Unified CCX Port Utilization

Listener (Process or Application Protocol)	Listener Protocol and Port	Remote Device (Process or Application Protocol)	Remote Protocol and Port	Traffic direction	Purpose
System Service	TCP 7	Editor	—	Bidirectional	- Echo for Editor - ICM Controller
System Service	TCP 22	—	—	Bidirectional	SFTP and SSH access
Tomcat (HTTP)	TCP 80	—	—	Bidirectional	Web access
FIPPA Server	TCP 80	Intracluster communication (see table note)	—	Bidirectional	Used for page push to phone from the FIPPA Service
System Service	UDP 123	—	—	Bidirectional	Network time sync
SNMP Agent	UDP 161	—	—	Inbound	Provide services for SNMP-based management applications
AON Management Console (AMC) Service	TCP 1090	Intracluster communication	—	Bidirectional	Provide RTMT data collecting, logging and alerting functionalities (AMC RMI Object Port)
AON Management Console (AMC) Service	TCP 1099	Intracluster communication	—	Bidirectional	Provide RTMT data collecting, logging and alerting functionalities (AMC RMI Registry Port)
Unified CCX	TCP 1994	—	—	Bidirectional	—

Listener (Process or Application Protocol)	Listener Protocol and Port	Remote Device (Process or Application Protocol)	Remote Protocol and Port	Traffic direction	Purpose
Cisco Unified CCX Socket.IO Service	TCP 12014	—	—	Bidirectional	This is the port where live-data reporting clients can connect to socket.IO server.
Cisco Unified CCX Socket.IO Service	TCP 12015	—	—	Bidirectional	This is the secure port where live-data reporting clients can connect to socket.IO server.
DBMON	TCP 1500	—	—	Bidirectional	This is the port where the IDS engine listens for DB clients
DBMON	TCP 1501	—	—	Bidirectional	- This is an alternate port to bring up a second instance of IDS during upgrade. - Localhost traffic only
Informix Dynamic Server (IDS)	TCP 1504	External process like HRC, WallBoard Client, External DB clients (like Squirrel or others for custom reporting) can connect	—	Bidirectional	Unified CCX database port
DBL RPC (XML)	TCP 1515	Intracluster communication	—	Bidirectional	DBL RPC, this is used during installation to set up IDS replication between nodes
Real-Time Information Server (RIS) Data Collector service (RISDC)	TCP 2555	Intracluster communication	—	Bidirectional	Connect to other RISDC services in the cluster to provide cluster-wide real-time information
RISDC	TCP 2556	Intracluster communication	—	Bidirectional	Allowed RIS client connection to retrieve real-time information
JTAPI Client (QBE)	TCP 2789	Unified CM	2748	Bidirectional	Provide services to CTI applications
Disaster Recovery System (DRS)	TCP 4040	—	—	Bidirectional	DRF master agent server port accepts connections from local agent GUI and CLI

Listener (Process or Application Protocol)	Listener Protocol and Port	Remote Device (Process or Application Protocol)	Remote Protocol and Port	Traffic direction	Purpose
Real-time service	TCP 5001	—	—	Bidirectional	SOAP Monitor
Perfmon service	TCP 5002	—	—	Bidirectional	SOAP Monitor
Control center service	TCP 5003	—	—	Bidirectional	SOAP Monitor
Log Collection Service	TCP 5004	—	—	Bidirectional	SOAP Monitor
System Service	TCP 5007	—	—	Bidirectional	SOAP Monitor - a troubleshooting tool for SOAP infrastructure
Engine	UDP 5065	SIP gateway	—	Bidirectional	Communicate with SIP gateway
Notification Service	TCP 5222	Openfire/SMAC	—	Bidirectional	OpenFire socket based client connection
Notification Service	TCP 5443	Openfire/SMAC	—	Bidirectional	OpenFire socket based client connection
CVD	TCP 5900	CVD of other node in cluster	—	Bidirectional	Heartbeats between CVDs in the cluster
CVD ActiveMQ	TCP 6161	Internal	6161	Bidirectional	Publish JMS events across JMS network connectors in the cluster
CVD	TCP 6999	Engine, Tomcat, CVD, and Editor	—	Bidirectional	RMI Port
Notification Service	TCP 7071	Web Browser	—	Bidirectional	HTTP bind
Notification Service	TCP 7443	Web Browser	—	Bidirectional	Secure HTTP bind
DBMON (CN)	TCP 8001	Intracluster communication	—	Bidirectional	DB change notification port

Listener (Process or Application Protocol)	Listener Protocol and Port	Remote Device (Process or Application Protocol)	Remote Protocol and Port	Traffic direction	Purpose
Tomcat (HTTP)	TCP 8080	Client Browser	—	Bidirectional	-Client browser trying to access any of the Administration interfaces or User Options interface. -Web services client using RTMT, configuration APIs, and mobile supervisor applications.
Cisco Unified Intelligence Center Tomcat (HTTP)	TCP 8081	Client Browsers	—	Bidirectional	Client browser trying to access the Cisco Unified Intelligence Center web interface
Cisco Finesse Tomcat (HTTP)	TCP 8082	Cisco Finesse Agent/Supervisor Desktop, Cisco Finesse Administration Console, and REST APIs	—	Bidirectional	HTTP port to access Cisco Finesse Tomcat web applications. Note Cisco Finesse Agent/Supervisor Desktop and Cisco Finesse Administration Console accessed using port 8082 is automatically redirected to port 8445.
Tomcat (HTTPs)	TCP 8443	Client Browser	—	Bidirectional	- Client browser trying to access any of the Administration interfaces or User Options interface - Web services client using RTMT, configuration APIs, and mobile supervisor applications
Cisco Unified Intelligence Center Tomcat (HTTPs)	TCP 8444	Client Browsers	—	Bidirectional	Client browser trying to access the Cisco Unified Intelligence Center web interface
Cisco Finesse Tomcat (HTTPs)	TCP 8445	Cisco Finesse Agent/Supervisor Desktop, Cisco Finesse Administration Console, and REST APIs	—	Bidirectional	Secured HTTP port to access Cisco Finesse Tomcat web applications.

Listener (Process or Application Protocol)	Listener Protocol and Port	Remote Device (Process or Application Protocol)	Remote Protocol and Port	Traffic direction	Purpose
IPSec Manager daemon	UDP 8500	—	—	Bidirectional	Cluster replication of platform data (hosts) certificates. Uses a proprietary protocol.
IPSec Manager daemon	TCP 8500	—	—	Bidirectional	Connectivity testing. Uses a proprietary protocol.
Engine	TCP 9080	—	—	Bidirectional	- Tomcat instance used by Unified CCX engine - Clients trying to access HTTP triggers or documents / prompts / grammars / live data
Engine	TCP 9443	—	—	Bidirectional	- Secure port used by Tomcat instance - Used by live-data client for authentication
Unified CCX Engine, Cisco Mobile Supervisor	TCP 12028	—	—	Bidirectional	CTI Server
Cisco IP Voice Media Streaming application (RTP RTCP)	UDP 24576 ~ 32767	—	—	Bidirectional	- Audio media streaming - Kernel streaming device driver
	TCP 32768 ~ 61000	—	—	Bidirectional	Generic ephemeral TCP ports (see table note)
	UDP 32768 ~ 61000	—	—	Bidirectional	Generic ephemeral UDP ports (see table note)
	UDP 58000	Custom application	—	Bidirectional	Provides an interface to control Agent Desktop over a custom protocol.
Notification Service ActiveMQ	TCP 61616	Chat applications	—	Bidirectional	Notification Service — ActiveMQ OpenWire transport connector

Table Notes

- 1 Intracluster communication in the table represents communication between Unified CCX servers in a cluster.
- 2 TCP Ephemeral ports are used to accept connections during Java RMI communication. Java RMI clients know which port it need to connect, because RMI first connects to RMI Registry (well-known port - 6999) and get the information which ephemeral port client need to connect to Unified
CCX Administration page, Engine and CVD use RMI communication in CCX/IP-IVR, so TCP ephemeral port range is opened up for intracluster communication between these processes.
- 3 UDP Ephemeral ports are used to receive audio/video RTP streams; so UDP Ephemeral port range is opened for incoming connections for streaming RTP media from CTI ports.
- 4 Port 38983 is open only on Unified CCX systems that were upgraded from versions earlier than 9.0(1).

Unified IP IVR Port Utilization

Table 2: Cisco Unified IP IVR Port Utilization

Listener (Process or Application Protocol)	Listener Protocol and Port	Remote Device (Process or Application Protocol)	Remote Protocol and Port	Traffic direction	Purpose
System Service	TCP 7	Editor	—	Bidirectional	- Echo for Editor - ICM Controller
System Service	TCP 22	—	—	Bidirectional	SFTP and SSH access
Tomcat (HTTP)	TCP 80	—	—	Bidirectional	Web access
System Service	UDP 123	—	—	Bidirectional	Network time sync
SNMP Agent	UDP 161	—	—	Inbound	Provide services for SNMP-based management applications
Tomcat	TCP 443	Client Browser	—	Bidirectional	Web access
AON Management Console (AMC) Service	TCP 1090	Intracluster communication (see table note 1)	—	Bidirectional	Provide RTMT data collecting, logging and alerting functionalities (AMC RMI Object Port)

Listener (Process or Application Protocol)	Listener Protocol and Port	Remote Device (Process or Application Protocol)	Remote Protocol and Port	Traffic direction	Purpose
AON Management Console (AMC) Service	TCP 1099	Intracluster communication	—	Bidirectional	Provide RTMT data collecting, logging and alerting functionalities (AMC RMI Registry Port)
DBMON	TCP 1500	—	—	Bidirectional	This is the port where the IDS engine listens for DB clients
DBMON	TCP 1501	—	—	Bidirectional	- This is an alternate port to bring up a second instance of IDS during upgrade. - Localhost traffic only
Informix Dynamic Server (IDS)	TCP 1504	External process like HRC, WallBoard Client, External DB clients (like Squirrel or others for custom reporting) can connect	—	Bidirectional	Unified IP IVR database port
DBL RPC (XML)	TCP 1515	Intracluster communication	—	Bidirectional	DBL RPC, this is used during installation to set up IDS replication between nodes
Unified IP IVR Cluster View Daemon (CVD)	TCP 1994	—	—	Bidirectional	—
Real-Time Information Server (RIS) Data Collector service (RISDC)	TCP 2555	Intracluster communication	—	Bidirectional	Connect to other RISDC services in the cluster to provide cluster-wide real-time information
RISDC	TCP 2556	Intracluster communication	—	Bidirectional	Allowed RIS client connection to retrieve real-time information
JTAPI Client (QBE)	TCP 2789	Unified CM	2748	Bidirectional	Provide services to CTI applications
Disaster Recovery System (DRS)	TCP 4040	—	—	Bidirectional	DRF master agent server port accepts connections from local agent GUI and CLI

Listener (Process or Application Protocol)	Listener Protocol and Port	Remote Device (Process or Application Protocol)	Remote Protocol and Port	Traffic direction	Purpose
Unified IP IVR Engine	TCP 5000	Unified ICM	—	Bidirectional	Using this port Unified ICM Subsystem listens to GED-125Clients. This port is modifiable
Real-time service	TCP 5001	—	—	Bidirectional	SOAP Monitor
Perfmon service	TCP 5002	—	—	Bidirectional	SOAP Monitor
Control center service	TCP 5003	—	—	Bidirectional	SOAP Monitor
Log Collection Service	TCP 5004	—	—	Bidirectional	SOAP Monitor
System Service	TCP 5007	—	—	Bidirectional	SOAP Monitor - a troubleshooting tool for SOAP infrastructure
CVD	TCP 5900	CVD of other node in cluster	—	Bidirectional	Heartbeats between CVDs in the cluster
CVD	TCP 6161	Intracluster communication only	6161	Bidirectional	Publish JMS events across JMS network connectors in the cluster (ActiveMQ)
CVD	TCP 6999	Engine, Tomcat, CVD, and Editor	—	Bidirectional	RMI Port
DBMON (CN)	TCP 8001	Intracluster communication	—	Bidirectional	DB change notification port.
Tomcat (HTTP)	TCP 8080	Client Browser	—	Bidirectional	-Client browser trying to access any of the Administration interfaces or User Options interface. Web services client using RTMT, configuration APIs, and mobile supervisor applications.
Finesse Tomcat (HTTP)	TCP 8082	Client Browser	—	Bidirectional	To access the Finesse Administration page and Finesse Agent Desktop.

Listener (Process or Application Protocol)	Listener Protocol and Port	Remote Device (Process or Application Protocol)	Remote Protocol and Port	Traffic direction	Purpose
Tomcat	TCP 8443	—	—	Bidirectional	DB access via SOAP; Tomcat forwards the SOAP request to AXL
Tomcat (HTTPS)	TCP 8443	Client Browser	—	Bidirectional	- Client browser trying to access any of the Administration interfaces or User Options interface - Web services client using RTMT, configuration APIs, and mobile supervisor applications
IPSec Manager daemon	UDP 8500	—	—	Bidirectional	Cluster replication of platform data (hosts) certificates etc. Uses a proprietary protocol.
IPSec Manager daemon	TCP 8500	—	—	Bidirectional	Connectivity testing. Uses a proprietary protocol.
Engine	TCP 9080	—	—	Bidirectional	- Tomcat instance used by Unified CCX engine - Clients trying to access HTTP triggers or documents / prompts / grammars
Cisco IP Voice Media Streaming application (RTP RTCP)	UDP 24576 ~ 32767	—	—	Bidirectional	- Audio media streaming. - Kernel streaming device driver
—	TCP 32768 ~ 61000	—	—	Bidirectional	Generic ephemeral TCP ports (see table note 2)
—	UDP 32768 ~ 61000	—	—	Bidirectional	Generic ephemeral UDP ports (see table note 3)

Table Notes

- 1 Intracluster communication in the table represents communication between Unified IP IVR servers in a cluster.
- 2 TCP Ephemeral ports are used to accept connections during Java RMI communication. Java RMI clients know which port it need to connect, because RMI first connects to RMI Registry (well-known port - 6999)

and get the information which ephemeral port client need to connect to. AppAdmin, Engine and CVD use RMI communication in CCX/IP-IVR, so TCP ephemeral port range is opened up for intracluster communication between these processes.

- 3 UDP Ephemeral ports are used to receive audio/video RTP streams; so UDP Ephemeral port range is opened for incoming connections for streaming RTP media from CTI ports.

