

Preface

- Change History, on page i
- About this Guide, on page i
- Audience, on page i
- Conventions, on page i
- Related Documents, on page iii
- Documentation and Support, on page iii
- Documentation Feedback, on page iv
- Field Alerts and Field Notices, on page iv

Change History

This table lists changes made to this guide. Most recent changes appear at the top.

Change	See	Date
Initial Release of Document for Release 12.0(1)		January 2019

About this Guide

This document provides a list of the TCP and UDP ports that Cisco Unified Contact Center products use. You use this information to configure Quality of Service (QoS) and Firewall/VPN solutions. Proper configuration is important on a network with an Architecture for Voice, Video, and Integrated Data (AVVID) solution.

Audience

This document is intended primarily for network administrators.

Conventions

This manual uses the following conventions.

I

Convention	Description	
boldface font	Boldface font is used to indicate commands, such as user entries, keys, buttons, and folder and submenu names. For example:	
	• Choose Edit > Find	
	• Click Finish .	
<i>italic</i> font	Italic font is used to indicate the following:	
	• To introduce a new term. Example: A <i>skill group</i> is a collection of agents who share similar skills.	
	• For emphasis. Example: <i>Do not</i> use the numerical naming convention.	
	• An argument for which you must supply values.	
	Example:	
	IF (condition, true-value, false-value)	
	• A book title. Example:	
	See the Cisco Unified Contact Center Express Installation Guide.	
window font	Window font, such as Courier, is used for the following:	
	• Text as it appears in code or information that the system displays. Example:	
	<html><title> Cisco Systems,Inc.
</title></html>	
	• File names. Example: tserver.properties.	
	• Directory paths. Example:	
	C:\Program Files\Adobe	
string	Nonquoted sets of characters (strings) appear in regular font. Do not use quotation marks around a string or the string will include the quotation marks.	
[]	Optional elements appear in square brackets.	
{ x y z }	Alternative keywords are grouped in braces and separated by vertical bars.	
[x y z]	Optional alternative keywords are grouped in brackets and separated by vertical bars.	

Convention	Description
<>	Angle brackets are used to indicate the following:
	• For arguments where the context does not allow italic, such as ASCII output.
	• A character string that the user enters but that does not appear on the window such as a password.
^	The key labeled Control is represented in screen displays by the symbol ^. For example, the screen instruction to hold down the Control key while you press the D key appears as ^D.

Related Documents

Document or Resource	Link
Cisco Unified Contact Center Express	https://www.cisco.com/en/US/products/sw/custcosw/ps1846/
Documentation Guide	products_documentation_roadmaps_list.html
cisco.com site for Cisco Unified CCX	https://www.cisco.com/en/US/products/sw/custcosw/ps1846/tsd_
documentation	products_support_series_home.html
cisco.com site for Cisco Unified	https://www.cisco.com/en/US/products/ps9755/tsd_products_
Intelligence Center documentation	support_series_home.html
cisco.com site for Cisco Finesse	https://www.cisco.com/en/US/products/ps11324/tsd_products_
documentation	support_series_home.html
cisco.com site for Cisco SocialMiner	https://www.cisco.com/c/en/us/support/customer-collaboration/
documentation	socialminer/tsd-products-support-series-home.html
cisco.com site for Cisco Unified CCX Virtualization Information	https://www.cisco.com/c/dam/en/us/td/docs/voice_ip_comm/uc_ system/virtualization/ virtualization-cisco-unified-contact-center-express.html
cisco.com site for Cisco Unified CCX Compatibility Information	https://www.cisco.com/c/en/us/support/customer-collaboration/ unified-contact-center-express/ products-device-support-tables-list.html

Documentation and Support

To download documentation, submit a service request, and find additional information, see *What's New in Cisco Product Documentation* at https://www.cisco.com/en/US/docs/general/whatsnew/whatsnew.html.

You can also subscribe to the *What's New in Cisco Product Documentation* RSS feed to deliver updates directly to an RSS reader on your desktop. The RSS feeds are a free service. Cisco currently supports RSS Version 2.0.

Documentation Feedback

To provide your feedback for this document, send an email to:

contactcenterproducts_docfeedback@cisco.com

Field Alerts and Field Notices

Cisco can modify its products or determine key processes to be important. These changes are announced through use of the Cisco Field Alerts and Cisco Field Notices. You can register to receive Field Alerts and Field Notices through the Product Alert Tool on Cisco.com. This tool enables you to create a profile to receive announcements by selecting all products of interest.

Sign in www.cisco.com and then access the tool at https://www.cisco.com/cisco/support/notifications.html.