

# **Product Architecture**

- Cisco Unified Contact Center, on page 1
- Router, on page 3
- Logger, on page 3
- Peripheral Gateway, on page 4
- Configuration System, on page 7
- Reporting System, on page 9
- Outbound Option, on page 15

# **Cisco Unified Contact Center**

Unified CCE delivers intelligent contact routing, call treatment, network-to-desktop computer telephony integration (CTI), and multichannel contact management over an IP infrastructure. It combines multichannel automatic call distributor (ACD) functionality with IP telephony in a unified solution, enabling you to rapidly deploy a distributed contact center infrastructure.

Unified CCE provides the following services:

- · Segmentation of customers and monitoring of resource availability
- Delivery of each contact to the most appropriate resource anywhere in the enterprise
- · Comprehensive customer profiles using contact-related data, such as dialed number and calling line ID
- Routing to the most appropriate resource to meet caller needs based on real-time conditions (such as agent skills, availability, and queue lengths)

Unified CCE enables you to smoothly integrate inbound and outbound voice applications with internet applications such as real-time chat, web collaboration, and email. This integration enables a single agent to support multiple interactions simultaneously regardless of which communications channel the customer chooses.

Unified CCE is a distributed solution with no single-server implementation. Unified CCE employs multiple servers each with multiple software components. Deployment options are flexible with performance, capacity, and network topology driving the deployment design.

Unified CCE was derived from Unified ICME with the primary difference being that Unified CCE integrates only with the Cisco Unified Communications Manager (Unified CM) IP PBX. All other major components of the Unified CCE solution are the same as the Unified ICM solution.

The Unified ICM platform is designed to route calls between various nodes in the TDM phone network. It is designed with an emphasis on reliability and flexibility. All processing in these components is message-based. The content of the message and the current state of the process determines the processing of each message. The messages are delivered to these components using the Unified ICM Message Delivery Service (MDS). MDS ensures that both processes are fed the exact same set of messages in the same order.

One of the most important concepts to understand about Unified CCE is its redundancy strategy. The components that contain centralized state are run in duplex. Two of these components work in lockstep to ensure redundancy and immediate recovery from a fault.

From a device standpoint, a typical Unified CCE deployment looks as follows:

Figure 1: Unified CCE Architecture



There are four major components of a Unified CCE deployment: the Router, the Logger, the Peripheral Gateway (PG), and the Administration & Data Server. The basic function of each is as follows:

- **Router**—Make the routing decisions. The router selects a peripheral or agent to receive an inbound contact (voice call, email, chat, and so on).
- Logger-Store (and replicate) all configuration, real-time and historical data.
- **Peripheral Gateway**—Act as a gateway to a peripheral device, like an IP PBX or a Voice Response Unit (VRU), and a CTI gateway linking agent desktops.
- Administration & Data Server—A server implementation that provides configuration data (from the Logger), an interface for real-time data, and a platform for the historical data server (HDS). The Administration & Data Server also offers an interface for administrators to alter configuration and routing scripts (Script Editor, Internet Script Editor).



**Note** Unified CCE applications do not report their resource usage to monitoring solutions, like Cisco Prime Collaboration. The monitoring solution retrieves CPU and memory usage data directly from the Windows Server operating system. On multicore systems, Windows Server might report usage greater than 100% while the Unified CCE solution is running as usual.

## **Unified CM Peripheral Support and CTI OS**

Cisco Finesse replaces CTI OS for Unified CCE.

CTI OS is no longer supported with Unified CCE. However, CTI OS is supported with UCCE System PG and other TDM peripheral types.

The CTI OS server setup now has the option to select UCCE System instead of UCCE. The setup also validates whether the selected peripheral is configured, through the Peripheral Gateway Setup, as UCCE System peripheral or not.

# Router

The Router is the brain of Unified CCE. Unified CCE can run user-defined scripts to make decisions on what happens with calls, and can determine how to get a call from one place to another. The Router communicates with several other components, including the Logger, the PGs, and the Administration & Data Servers (ADSs).

The Router receives notification from routing clients (PGs) that a call is in need of some form of routing. It then runs a user-defined script to determine what to tell the routing client to do with the call.

In addition, the Router receives status events and reporting events from PGs. The Router uses these messages to update its current representation of the agents and resources in the system, which is used by the scripts to determine where to send calls. It also sends these messages to the Logger for storage and some of the messages to the Admin Workstations for real-time reporting.

Routers, Loggers and PGs are fault tolerant, having two instances of each component so that a failure of one provides for bump-less continuation of function through the remaining half of a duplex pair. Routers are duplex entities, which means that two separate, distributed instances (identified as Side A and Side B) use the MDS to keep in lockstep with the other side, ensuring that any outage of one side guarantees that the system continues operating without failures or impairments—the opposite side assuming sole responsibility for making routing decisions. All data as well as call control messaging is shared between sides to ensure that both sides have the same data by which to make (the same) routing decisions. Both Router sides are concurrently in service.

## **Network Interface Controller**

Like a PG, a Network Interface Controller (NIC) is a type of routing client. However, a NIC is more limited than a PG. A NIC is used to interact with a telephony network, usually the TDM. A NIC is typically coresident with the Router and used for Unified ICM deployments.

# Logger

Unified CCE uses the Logger to store historical data and configuration data about the call center. The Logger is the place where historical data is first stored, and from which it is later distributed. The Logger receives messages from the Router. These messages include detail messages about the calls and summary messages that the PGs compute and send through the Router. Examples of these summary messages are half-hour summaries (how many calls were received during a given period).

The Logger uses a synchronization process that is a little different than the Router. The messages coming to the Logger are sent only from the corresponding Router. Side A Router sends messages only to the Side A Logger. Side B Router sends messages only to the Side B Logger. Because the Routers are running in lockstep,

it is guaranteed that while messages are flowing they are the same messages. However, recovery happens directly from Logger to Logger, using bulk database copy algorithms for efficiency.

The Loggers also distribute historical data to HDS and configuration and real-time data to the Administration & Data Servers through MDS. Loggers are duplex as well and are tightly coupled with their respective Router. In many deployments, a side of the Router and Logger are collocated on the same physical server. A Router/Logger combination is often referred to as the Central Controller.

#### Figure 2: Central Controller Architecture



## **Peripheral Gateway**

The PG is the component that talks to the telephony devices through their own proprietary CTI interface in a Unified CCE system. These devices can be ACDs, IVR devices or, in cases such as with Unified CCE, an IP PBX. The PG normalizes whatever protocol the telephony device speaks, and keeps track of the state of agents and calls that are on that device. The PG sends this status to the Router, as well as forwards requests requiring customer logic to the Router.

The PG also exposes a normalized CTI interface to clients. These clients can be traditional CTI clients (wallboards, agent/supervisor desktop clients, and so on), or they can be another instance of Unified CCE, as is the case in a parent/child deployment.

The component of the PG that does the normalization is called a Peripheral Interface Manager (PIM). This component talks to the peripheral and translates whatever proprietary language it speaks into the normalized one that the Open Peripheral Controller (OPC) and the rest of the PG understand.

PGs fall into several groups. The first classification of PG includes those that talk to an ACD or Unified CM that has agents on it. This is the typical case for a PG. It talks a proprietary CTI protocol to the switch, and maintains the state of agents and calls in queue on the device. While all of these PGs report agent state to the Central Controller, they do it in a different way. In the case of a PG talking to an ACD, the PG mirrors the state of the agents on the ACD; it keeps a copy of the primary state of the agents tracked by the ACD. In the case of a PG attached to a Unified CM, the Unified CM does not know about agents or agent states, it only knows about phone lines. In this case the PG is the primary for the agent state.

The second classification of PG is a VRU or Media Routing (MR) PG. These PGs expose an interface that is client-neutral. In the case of the VRU PG, this interface is tailored to voice calls; in the case of the MR PG,

it is more generic task routing that is exposed. These PGs do not maintain agent state, but only maintain the state of calls (or tasks) and expose an interface for the devices to get instructions from the Router.

The third classification of PG is the group PG. There are two types of PGs that talk to groups of peripherals. The first is the Generic PG. This PG allows multiple PIMs of different types to reside inside of the same PG. Each peripheral on this PG behaves completely independently. Currently the Generic PG is supported only for Unified CCE, where it contains a Communications Manager PIM and a VRU PIM talking to an IP-IVR or Customer Voice Portal (CVP). The second type of group PG is a Unified CCE System PG. This PG, like the generic PG, has one Call Manager PIM and one or more VRU PIMs. The System PG ties these multiple PIMs together. In a traditional Unified CCE, a call that comes into the Communications Manager then gets transferred to the IP-IVR and then back to an agent looks like three separate calls to Unified CCE. The System PG coordinates these calls and makes that call look like a single call. This is what happens on a traditional TDM ACD, where the ACD also has a queue point.

#### Figure 3: Peripheral Gateway Architecture



The PG is duplexed using the same technology as the Central Controller, MDS. This means that there are two PGs operating at any time. All of the messages to the critical process on the PG (OPC) go through the MDS queue, to keep the two operating in lock-step. However, the PG operates slightly different from the Router – from a fault tolerance standpoint – in that while both sides share the same data, for many PG components, only one side is active. Should a fault occur, the opposite side activates and continues functioning, having the context of the other side without losing calls.

PGs use the Device Management Protocol (DMP) to communicate between themselves and the central controller. The following figure depicts the components involved in this communication and the communication links employed.

#### Figure 4: DMP Flows



Coresident with the PG is the CTI Gateway (CG - CTI Server component).

### **Open Peripheral Controller**

The Open Peripheral Controller (OPC) computes and maintains the state of agents on the PG. The OPC reports that state to the Router, knows when a call requests instructions from the Router, and performs the CTI operations on the telephony device as necessary. OPC is the critical process on the PG. It is kept in lock-step with its sibling on the other side.

### **Peripheral Interface Manager**

The Peripheral Interface Manager (PIM) is responsible for the connection to the peripheral (ACD, PBX, IVR). This process is not a lock-step process nor is data shared between the two sides. Instead either the Side A or Side B PIM is active for each peripheral. If one side loses its connection, the other side activates.

### Unified Communications Manager PIM

Unified CCE Only

The Communications Manager PIM provides the interface between the Unified CM and the Unified CCE OPC process. This PIM communicates with Unified CM through the JTAPI Gateway.

#### **VRU PIM**

The VRU PIM provides an interface to a VRU (or IVR). The communication protocol used between the PIM and the VRU is GED-125.

### Media Routing PIM

The Media Routing (MR) PIM provides the integration point for multimedia contacts such as emails or collaboration (chat) sessions. It is also a necessary component for integration of the Outbound Option Dialer.

### TDM ACD PIMs

The TDM ACD PIMs provide interfaces to various manufacturers' Automatic Call Distributors. The communication protocol between the PIM and the ACD is typically proprietary.

## **JTAPI** Gateway

Unified CCE only

The JTAPI Gateway is a process that connects to the Unified CM CTI Manager and provides the link between the peripheral gateway and the Unified CM cluster. The Unified CM CTI Manager communicates CTI messages to and from other nodes in the Unified CM cluster. The JTAPI Gateway provides an added level of translation between the (Java) JTAPI interface and the ( $C^{++}$ ) Unified Communications Manager PIM.

## **CTI Gateway (CTI Server)**

The CTI Server is the interface from OPC to CTI clients. It provides an interface (protocol) specified as GED-188. This interface has many variances and message sets. It was used as a direct CTI connection to agent desktops or third-party desktops. This use is deprecated.

GED-188 helps to hide the details of individual peripherals, but does not fully complete the job. The messages sent from a CTI Server connected to an Aspect PG differ from the messages sent from a CTI Server connected to a Unified CCE PG.

Today the CTI Server connects to several types of clients:

- Agent Reporting and Monitoring (ARM) clients this variance of GED-188 allows reporting agent status and receiving information about the status of agents. It is one of the integration points for multichannel (email and web collaboration) applications and for the Outbound Dialing options.
- Parent ICM a single connection is allowed to a CTI Server attached to a Unified CCE System PG. This connection allows the parent ICM to receive status about agents and calls on this PG, and to take control of certain incoming calls and route them itself. This variance of GED-188 is known as ACMI.

At any given time, only Side A or Side B CTI Server is active, not both. Clients must connect to one or the other.

# **Configuration System**

The Unified CCE configuration system is also based around the concept of reliability and scalability. There can be multiple configuration database copies, which are kept in sync using MDS and a synchronization process from the central controller. Each of these can send updates to the Router, but only the Logger configuration database is authoritative.

The configuration system consists of the DBAgent process on the Router, which accepts connections from the Administration & Data Servers, and distributes configuration updates to those Administration & Data Servers. The Administration & Data Servers have a copy of the configuration and expose a GUI for browsing and making changes. The Administration & Data Servers also expose an API (ConAPI) for accessing the configuration information and for making changes.

## Administration & Data Server

The Administration & Data Server is the main interface to the Unified ICM/Unified CCE configuration. On the Administration & Data Server resides a database that contains a copy of the configuration information in the Logger. A Distributor process, which receives updates from the central controller, writes to the database to keep everything in sync. Multiple clients read the configuration from the database and send update messages to the central controller DBAgent process.

The two main clients in the Administration & Data Server are the configuration tools, and the Configuration Management Server (CMS) process. The configuration tools are used to provide a GUI to update the configuration. The CMS process is used to provide the Configuration API (ConAPI).

Processes that connect to ConAPI are the multichannel components for agent and skill group management and CCMP.

The Administration & Data Server does not have a dependent twin, but rather provides fault tolerance in numbers (N+1 model). A typical Unified ICM/Unified CCE deployment often has two or more Administration & Data Servers. Administration & Data Servers connect to each central controller side – a primary and a secondary. If a failure occurs on the primary link, the secondary recovers from the failure and restores connectivity.

Configuration data is supported on multiple Administration & Data Server types:

- Administration Server and Real-time Data Server (AW Distributor) (with no HDS; configuration and real-time data but no historical or call detail data)
- Administration Server, Real-time and Historical Data Server, and Detail Data Server (AW-HDS-DDS), (configuration, real-time, historical, and call detail data)
- Administration Server and Real-time and Historical Data Server (AW-HDS) (configuration, real-time and historical data but no call detail data)
- Administration & Data Server configuration (AW-CONFIG, configuration data only)

Configuration changes are not supported on the HDS-DDS type (which includes historical and call detail data but excludes real-time data). The HDS-DDS type includes only configuration data needed for historical reporting purposes.

### **Configuration Updates**

Figure 5: Configuration System Message Flow



Figure 5 illustrates how a configuration update may happen in Unified CCE:

• In the first step (not shown) an Administration Client reads configuration from the database, and determines that a change is required.

- When this determination happens, the GUI connects to the DBAgent process on the central controller and sends the update (Step 1).
- DBAgent sends the message to the Router, through MDS (Steps 2, 3).
- The Router validates the configuration message and sends it to the Logger to be run (Steps 4, 5).
- The Logger updates its configuration (Step 6).
- The Logger sends confirmation of the update to the Router (Steps 7, 8).
- The Router then sends the update to all its clients (DBAgent, PGs, and so on) (Step 9, 10).
- DBAgent sends this message to each of its Administration Server and Real-time Data Servers (Step 11). The Administration Server and Real-time Data Servers update their database (Step 12).
- The Configuration GUI detects the change happen (Step 13).

# **Reporting System**

The reporting system for Unified ICM/Unified CCE is similar to its configuration system; they use the same distribution channel:

Reporting messages are generated by PGs (this includes both detail messages and summary messages) and then are sent to the Central Controller, which consists of the Router and the Logger.

The Router feeds real-time data to the Administration Server and Real-time Data Servers.

The Logger stores historical data and replicates it to the Historical Database.

Administration Server and Real-time Data Servers write those records into the real-time reporting database. Those Administration Server and Real-time Data Servers that are configured to have Historical Data Servers also write the appropriate records to the historical database. Cisco Unified Intelligence Suite (Unified IS) are web applications that uses Java Servlets to build reports to be viewed from thin (web browser) clients.

### **Historical Data Server**

The Historical Data Server (HDS) is an option to be installed with an Administration Server and Real-time Data Server. It uses the same distributor technology used to keep the configuration database up to date. The HDS provides a long-term repository for historical data and offloads historical reporting from the Logger. Historical data is replicated from the Logger to one or more HDSs.

There are three types of HDSs:

- Administration Server, Real-time and Historical Data Server, and Detail Data Server (AW-HDS-DDS): HDS with call detail data store. This type includes both real-time and configuration data and you can use it to source historical data for the Analysis Call Path tool. This type is intended for small- to medium-sized deployments. There may be a maximum of two AW-HDS-DDS servers per Logger side in small or medium deployments but only one per Logger side in a large deployment (presumably with multiple AW-HDS servers).
- Administration Server and Real-time and Historical Data Server (AW-HDS): HDS without a call detail data store (no call detail, call variable, agent state data). This type also includes both real-time and configuration data but you cannot use it to source data for the Analysis Call Path tool. This type is intended for large deployments. There may be a maximum of three AW-HDS per Logger side.
- HDS-DDS: HDS with call detail data store but no real-time data or configuration data. This type may be used to source historical data for the Analysis Call Path tool. This type is intended for large deployments and for use with multiple AW-HDS servers. There may be a maximum of one HDS-DDS per Logger side (presumably with multiple AW-HDS servers).

## **Unified Intelligence Center**

Unified Intelligence Center is a web-based reporting platform for the Cisco Unified Communications products and is supported by Unified ICME and Unified CCE.

You can install Unified Intelligence Center as a standalone server or in a cluster of a maximum of eight server nodes. There is one mandatory publisher node (called the Controller) and up to seven subscriber nodes (called Members). The Controller node includes a Member, which means a deployment can consist of a Controller only.

Cisco Unified Intelligence Center offers both a web-based reporting application and an administration interface. The reporting application runs on the Members. The administration application runs on the Controller.

Unified Intelligence Center reporting features include multi-user support, customized reports, security, multiple display formats, web accessibility, and Web 2.0-like mashup support to display data from multiple sources on a single dashboard. These features make Unified Intelligence Center a valuable tool in the information technology arsenal of any organization and position it as a drop-in replacement or solution for most reporting requirements.

Cisco Unified Intelligence Center reporting capabilities include:

- Web 2.0 based dashboard mashups
- · Powerful grid presentations of reports with sorting and grouping
- Chart and gauge presentations of reports
- · Association of multiple report displays with the same report definition
- Custom filters
- Custom thresholds to alert on the data
- · Pre-installed stock report templates for Unified CCE data
- · Ability to report data from JDBC compatible data sources

Unified Intelligence Center supports the following:

- Multiple users
- · Customized dashboards and custom reports
- · Report scheduler
- Detailed security levels and LDAP/local database authentication
- · Import and export of report XML files
- · Export of grid reports to Microsoft Excel
- Multiple languages
- Clustered deployment
- Management support through Simple Network Management Protocol (SNMP), Java Management Extensions (JMX), and Cisco Analysis Manager

#### Unified Intelligence Center Standard Deployment Model

The Unified Intelligence Center deployment with Unified CCE uses the AW-HDS as its data source server. You can connect to multiple AW-HDS databases to handle the load from multiple Unified Intelligence Center reporting nodes. You can use other data sources, such as the CVP Reporting Server, along with the Unified CCE AW-HDS as data source servers. The ACE load balancer, an optional component, provides load balancing for report queries across the multiple reporting nodes and servers as a single point of access to the cluster. You can use Unified CCE deployments with a distributed AW-HDS as a data source for Unified Intelligence Center reports. However, local area network AW-HDS access ensures enhanced throughput in data extracted and ensures faster response times for reports, especially real-time reports with repeated refresh intervals.



Figure 6: Unified Intelligence Center Standard Deployment

### **Unified Intelligence Center Scaled Deployment Model**

You can deploy Unified Intelligence Center as the reporting solution with Unified CCE deployments that scale over WAN networks. In these deployments, Unified Intelligence Center is deployed locally with one section or data center of the scaled Unified CCE deployment. Unified Intelligence Center can access the local AW-HDS over the Local Area Network (LAN), and the remote AW-HDS, which is deployed along with the remote section of Unified CCE over the Wide Area Network (WAN).

You can deploy other data sources, such as the Cisco Unified Customer Voice Portal, along with Unified CCE. Firewall considerations when you deploy over the WAN apply to the data source servers. Open appropriate ports as described in *Solution Design Guide for Cisco Unified Contact Center Enterprise* at https://www.cisco.com/en/US/products/sw/custcosw/ps1844/tsd\_products\_support\_series\_home.html, depending on the remote database configuration.



#### Figure 7: CUIC Scaled Deployment

## **Unified Contact Center Management Portal**

Unified CCMP is a suite of server components that simplify the operations and procedures for performing basic administrative functions such as managing agents and equipment, and provide a common, web-based user interface within the entire Unified CCE product set. Unified CCMP consists of four components:

- The Database Server component, which uses an application called the Importer to import enterprise data from different data sources into a Microsoft SQL Server management information database. The database consists of separate database elements that sit on top of the SQL Server and that provide data to different reporting elements:
  - RDBMS Database (known as the datamart) holds the imported enterprise data.
  - Reporting Services Database imports and processes data from the datamart so that SQL Server Reporting Services can use it to populate reports.
- The Application Server component manages security and failover. It manages security by ensuring that users can view only specific folders and folder content as defined by their security sign-in credentials. It verifies that a user is valid and then loads the system configuration that applies to that user. It also manages failover. So if one database server fails, the application can automatically retrieve the required data via an alternative database server.
- The Web Server component provides a user interface to the platform. The user interface allows users to work with report data, and perform administrative functions.
- The Data Import Server component is an Extract, Transform, and Load (ETL) server for data warehouses. The Data Import component imports the data used to build reports. It is designed to handle high volume data (facts) such as call detail records and data that is rarely changed (dimensions) such as agents, peripherals, and skill groups.

If you install these components on more than one server, you generally install the Data Import and Database components on the Database Server. You usually install the Application and Web components on the Web Application Server.

Unified CCMP maintains a complete data model of the contact center equipment to which it is connected and periodically synchronized. In addition to configuration information such as agents or skill groups, the Unified CCMP can optionally record the events logged by the equipment. These records are used for management information and reporting purposes. Unified CCMP data model and synchronization activity allows for items to be provisioned either through the Unified CCMP Web interface or from the standard equipment specific user interfaces.

The following illustration shows the Unified CCMP system architecture. The top half of the diagram is a traditional three tier application. This application includes a presentation layer (an ASP.NET web application), a business logic application server, and a SQL Server database. The lower half of the system architecture is a process orchestration and systems integration layer called the Data Import Server.





#### Web Application

The user interface to Unified CCMP is via a web application that you access using a web browser. You gain access to the Unified CCMP application through a secure sign-in screen. Every user has a unique username. This user is assigned privileges by the system administrator, which defines the system functions the user can access and perform.

The user interface is time-zone aware and connections to it are secured through HTTPS. The web application is hosted on the server by Microsoft Internet Information Services (IIS) so it is suitable for lockdown in secure environments.

#### **Application Server**

The Unified CCMP Application Server component provides a secure layer in which all business logic is implemented. The application server component runs in a separate service and is always hosted with the web server component. The application server component also includes caching to improve performance and audits all actions taken by signed-in users.

#### **Reporting Services**

Unified CCMP uses Microsoft Reporting Services technology for generating reports. Microsoft Reporting Services is a part of SQL Server Enterprise Edition. Unified CCMP provides a flexible reporting system in which reports are authored in the industry standard Report Definition Language (RDL).

#### **Data Import Server**

The Data Import Server component is an Extract, Transform, and Load application for Unified CCMP. The Data Import Server component imports the data used in Unified CCMP. The Data Import Server component is designed to handle high volume data (facts), such as call detail records and data which is changed irregularly (resources), such as agents, peripherals, and skill groups. The Data Import Server component is also responsible for monitoring changes in Unified CCMP system and ensuring that those changes are updated onto Unified ICM/Unified CCE and Unified Communications Manager. The Data Import Server component orchestrates the creation, deletion, and update of resources to Unified ICM/Unified CCE and Unified Communications Manager. The Microflow Runtime is the heart of the Data Import Server component. It orchestrates systems without resorting to low level programming languages. The Microflow Runtime is a general purpose scripting environment and can be applied to a wide range of problems. The term microflow describes any modular, reusable, and independent unit of business logic. An example microflow might update an agent on Unified ICM/Unified CCE when changes are made in the Unified Communications Manager web server component.

#### **Unified CCMP Services**

- Management Portal, Data Import Server: The Data Import Server is responsible for importing new
  dimensions and changes to dimensions such as agents, skill groups, call types, and dialed numbers from
  Unified CCE. The Data Import Server periodically checks whether there are any new dimensions to
  import or whether there have been any changes made to dimensions that have already been imported.
  This periodic check allows for closed-loop management of changes made to dimensions provisioned by
  Unified CCMP.
- Management Portal, Provisioning Server: The Provisioning Server is responsible for sending provisioning requests from Unified CCMP to Unified CCE. The requests are move, add, change, and delete (MACD) operations for the resource types that Unified CCMP can manage such as creation of new resources, for example a new agent, or new memberships, such as an Agent to Skill Group membership. These updates are applied via the ConAPI interface.

Norvices				_	
Eile Action View Help					
Services (Local)	Name A	Description	Status	Startup Type	L.▲
	Service Service	Indexes co		Disabled	ι
	🖏 InstallDriver Table Manager	Provides s		Manual	ι
	Sintersite Messaging	Enables me		Disabled	L
	Services	Provides e	Started	Automatic	ι
	Kerberos Key Distribution Center	On domain		Disabled	ι
	Science Logging	Monitors a		Disabled	- T
	Scott Disk Manager	Detects an	Started	Automatic	ι
	Service Administrative Service	Configures		Manual	ι
	Management Portal: Data Import Server	Data Impor	Started	Automatic	l
	Management Portal: Provisioning Server	Provisionin	Started	Automatic	L
	See State And America State And America State America Stat	Provides a	Started	Automatic	ι
	See Messenger	Transmits		Disabled	ι
	Search Microsoft Search	Creates ful	Started	Automatic	ι
	Microsoft Software Shadow Copy Provider	Manages s		Manual	ι
	MSSQLSERVER		Started	Automatic	L
	Net Logon	Maintains a	Started	Automatic	ι
	NetMeeting Remote Desktop Sharing	Enables an		Disabled	ι_,
	Sin Network Connections	Manager o	Started	Maryial	_ <b>_</b> _
					<u> </u>
	Extended A Standard /				

#### Figure 9: Unified CCMP Services

Unified CCMP exposes a rich set of performance (known as PerfMon) counters that you can monitor in real time to gauge status, performance and health.

A shortcut to the 32-bit version of Performance Monitor application is available in the Cisco Unified CCE Tools folder for easy access. This shortcut launches the 32-bit version of PerfMon utility so that you can easily monitor the Unified CCE processes.

## **Outbound Option**

Unified ICM and Unified CCE support outbound campaign dialing through its Outbound Dialing subsystem (also known as Blended Agent or BA). The Outbound Dialing subsystem consists of three major components: the Campaign Manager, the Import Process, and the Dialers.

Outbound campaigns start with the Import process. Use the Import process to import a set of outbound calls into the BA database. This data defines what calls are made and how they are made.

The Campaign Manager is responsible for running the Outbound Dialing campaigns. It reads the campaigns from the BA DB. It then distributes the calls to be made to the Dialers. It takes the results of calls and sends reporting information to the Unified ICM/Unified CCE central controller where it is recorded in Unified ICM/Unified CCE reporting database.

The Outbound Option Dialer maximizes the resources in a contact center by dialing several customers per agent. This component resides on the PG server.

The outbound Option deployment uses the Session Initiation Protocol (SIP) Dialer. The SIP dialer performs dialing, call control, Voice Gateway Interaction functionality instead of using resources on managing the call. In an Outbound Option deployment that uses the SIP Dialer handles the Call Progress Analysis for Outbound campaigns. This helps in increasing the number of outbound agents that a deployment can service on a PG. This reduces the number of PGs and Dialers deployed for larger enterprise systems.

The following diagram provides a high-level view of the Outbound Option components and their relationship with other Unified ICM components.

Figure 10: Outbound Option Component Relationships



Enable the Outbound Option high availability option to provides continuous service without any disruptions, using redundant SIP Dialers and Campaign Managers.