



Requirements

- [Hardware Requirements for Cisco Jabber for Mac, page 1](#)
- [Software Requirements, page 2](#)
- [Ports and Protocols, page 4](#)
- [CTI Supported Devices, page 5](#)
- [Supported Codecs for Cisco Jabber for Windows and Cisco Jabber for Mac, page 5](#)
- [COP Files for Cisco Jabber for Windows and Cisco Jabber for Mac, page 5](#)
- [VPN Support, page 6](#)

Hardware Requirements for Cisco Jabber for Mac

Installed RAM

2 GB RAM

Free Physical Memory

1 GB

Free Disk Space

300 MB

CPU Speed and Type

Intel Core 2 Duo or later processors in any of the following Apple hardware:

- Mac Pro
- MacBook Pro (including Retina Display model)
- MacBook
- MacBook Air

- iMac
- Mac Mini

I/O Ports

USB 2.0 for USB camera and audio devices.

Software Requirements

For successful deployment, ensure that client workstations meet the software requirements.

Operating Systems for Cisco Jabber for Mac

You can install Cisco Jabber for Mac on the following operating systems:

- Apple OS X Lion Version 10.7.4 (or later)
- Apple OS X Mountain Lion 10.8.1 (or later)
- Apple OS X Mavericks 10.9 (or later)

This version of Cisco Jabber for Mac is not supported on Apple OS X Yosemite 10.10

On-Premises Servers for Cisco Jabber for Windows and Cisco Jabber for Mac

Cisco Jabber uses domain name system (DNS) servers during startup. DNS servers are mandatory for Cisco Jabber.

Cisco Jabber supports the following on-premises servers:

- Cisco Unified Communications Manager, release 8.0(1) or later
- Cisco Unified Presence, release 8.0(3) or later
- Cisco Unity Connection, release 8.5 or later
- Cisco WebEx Meetings Server, version 1.1 or later

Cisco Jabber supports the following features with Cisco Unified Survivable Remote Site Telephony, Version 8.5:

- Basic call functionality
- Ability to hold and resume calls

Refer to the *Cisco Unified SCCP and SIP SRST System Administrator Guide* for information about configuring Cisco Unified Survivable Remote Site Telephony at: http://www.cisco.com/en/US/docs/voice_ip_comm/cusrst/admin/sccp_sip_srst/configuration/guide/SCCP_and_SIP_SRST_Admin_Guide.html.

For Cisco Unified Communications Manager Express support details, refer to the Cisco Unified CME documentation: http://www.cisco.com/en/US/products/sw/voicew/ps4625/products_device_support_tables_list.html

Cloud-Based Servers

Cisco Jabber supports integration with the following hosted servers:

- Cisco WebEx Messenger service
- Cisco WebEx Administration Tool, minimum supported version is 7.5
- Cisco WebEx Meeting Center, minimum supported versions are as follows:
 - Version T26L with Service Pack EP 20
 - Version T27L with Service Pack 9

Directory Servers

You can use the following directory servers with Cisco Jabber:

**Note**

Cisco Unified Communications Manager User Data Server (UDS) is not supported for directory integration in this release.

- Active Directory Domain Services for Windows Server 2012 R2
- Active Directory Domain Services for Windows Server 2008 R2
- Active Directory for Windows Server 2003 R2
- OpenLDAP

**Restriction**

Directory integration with OpenLDAP requires that you define specific parameters in a Cisco Jabber configuration file. See *LDAP Directory Servers* for more information.

Computer Telephony Integration Servitude

Cisco Jabber for Windows and Cisco Jabber for Mac support CTI servitude of Cisco Jabber from a third party application.

Computer Telephony Integration (CTI) enables you to use computer-processing functions while making, receiving, and managing telephone calls. A CTI application can allow you to retrieve customer information from a database on the basis of information that caller ID provides and can enable you to use information that an interactive voice response (IVR) system captures.

For more information on CTI servitude, see the CTI sections in the appropriate release of the *Cisco Unified Communications Manager System Guide*. Or you can see the following sites on the Cisco Developer Network for information about creating applications for CTI control through Cisco Unified Communications Manager APIs:

- Cisco TAPI: <http://developer.cisco.com/web/tapi/home>

- Cisco JTAPI: <http://developer.cisco.com/web/jtapi/home>

Ports and Protocols

The client uses the ports and protocols listed in the following tables:

Inbound

Port	Protocol	Description
16384 to 32766	UDP	Real-Time Transport Protocol (RTP) media streams for audio and video

Outbound

Port	Protocol	Description
69	UDP	Trivial File Transfer Protocol (TFTP) service
6970	HTTP	TFTP service to download client configuration
80	TCP (HTTP)	Cisco Unified Communications Manager administrator and user web pages
389	UDP / TCP	LDAP directory server
636	LDAPS	LDAP directory server (secure)
3268	TCP	Global Catalog server
3269	LDAPS	Global Catalog server (secure)
2748	TCP	CTI gateway
5060	UDP / TCP	Session Initiation Protocol (SIP) call signaling
5061	TCP	Secure SIP call signaling
5070	UDP	Binary Floor Control Protocol (BFCP) for video desktop sharing
5222	TCP (XMPP)	Cisco Unified Presence or Cisco Unified Communications IM and Presence in on-premise deployments
8443	HTTPS	Web access to Cisco Unified Communications Manager and includes connections for the following: <ul style="list-style-type: none"> • Cisco Unified Communications Manager IP Phone (CCMCIP) server for assigned devices
16384 to 32766	UDP	RTP media streams for audio and video
53	UDP / TCP	Domain Name System (DNS) traffic

Port	Protocol	Description
1080	SOCKS5 Bytestreams	<p>Peer to peer file transfers</p> <p>If port 1080 is in use, the client attempts to use the next available port in the range from 1081 to 1089.</p> <p>In on-premise deployments, the client also uses port 1080 to send screen captures.</p> <p>Note If port 1080 is blocked, the client uses the following port range: 37200 to 37209.</p>

CTI Supported Devices

To view the list of Computer Telephony Integration (CTI) supported devices: From Cisco Unified Reporting, select **Unified CM Phone Feature List**. From the **Feature** drop-down list, select **CTI controlled**.

Supported Codecs for Cisco Jabber for Windows and Cisco Jabber for Mac

Supported Audio Codecs

- G.722.1—32k and 24k. G.722.1 is supported on Cisco Unified Communications Manager 8.6.1 or later.
- G.711—a-law and u-law
- G.729a

Supported Video Codec

- H.264/AVC

COP Files for Cisco Jabber for Windows and Cisco Jabber for Mac

In certain cases, you might need to apply COP files to Cisco Unified Communications Manager.

You can download the following COP files from the Cisco Jabber administration package on Cisco.com:

COP File	Description	Cisco Unified Communications Manager Versions
ciscoem.installescfddevicetype.cop.sgn	Adds the CSF device type to Cisco Unified Communications Manager. For more information, see <i>Software Requirements</i> .	7.1.3
ciscoem.addcsfsupportfield.cop.sgn	Adds the CSF Support Field field for group configuration files. For more information, see <i>Create Group Configurations</i> .	8.6.1 and earlier
cmterm-cupc-dialrule-wizard-0.1.cop.sgn	Publishes application dial rules and directory lookup rules to Cisco Jabber. For more information, see <i>Publish Dial Rules</i> .	8.6.1 and earlier

VPN Support

Cisco Jabber for Mac supports the following software VPN clients.

- Cisco AnyConnect release 3.0.5, and 3.1
- Cisco AnyConnect releases 2.2, 2.3, and 2.4
- Cisco VPN client release 5.0
- Cisco VPN client release 4.9.01