



Feature Defaults Quick Reference

- [Feature Defaults](#), on page 1

Feature Defaults

The following table indicates what features are enabled or disabled by default.

Feature	Default
APN, QCI, and ARP-based DSCP Mapping for WPS Sessions	Disabled - Configuration Required
Capability to Record and Produce Call Transactions on ePDG	Disabled - Configuration Required
Cisco Ultra Traffic Optimization Bulk Statistics Enhancements	Disabled - Configuration Required
Closed Subscriber Groups Mobility Event Support on P-GW and GGSN	Disabled - Configuration Required
Crowd Sourcing Optimization	Disabled - Configuration Required
Customizing Last User Location Information	Disabled - Configuration Required
Customizing TAC Field in CDR	Disabled - Configuration Required
Enhanced Event Logging	Enabled - Always-on
Diameter Route Table Entries Display Limit and Filtration Enhancement	Not Applicable
Dynamic Enabling of UBR Buffering in MME Services	Disabled - Configuration Required
Extraction of IPv4 Addresses Embedded in IPv6 Addresses	Disabled - License Required
Failure Counters for CSFB MT Counters	Enabled - Always-on
Gy Interface Spec Compliance 2019	Disabled - Configuration Required
IMS PCO Configurations when Gx is Down	Disabled - Configuration Required
Increasing Maximum Chunks Per User NAPT for 5G MiFi	Disabled - Configuration Required

Feature	Default
Inter-MME Handover for Modify Bearer Requests without S11-U TEID	Disabled - Configuration Required
MME Masked IMEISV	Disabled - Configuration Required
MME Bearer Request Message Enhancements During Handover Process	Disabled - Configuration Required
Mobile Hot Spot Usage on RADIUS Accounting	Disabled - Configuration Required
4G Network Upgrade Gx Interface	Disabled - Configuration Required
Password Expiration Notification	Enabled - Always-on
P-GW Buffering Mechanism	Enabled - Configuration Required
P-GW Buffering Optimization	Enabled - Always-on
PLMN Level Statistics for ePDG Services	Disabled - Configuration Required
PLMN Level Statistics for SaMOG Services	Disabled - Configuration Required
Separation of 2G 3G 4G and WLAN Bulkstatistics	Disabled - Configuration Required
Sessmgr Restart While Processing Secondary RAT Usage CDR Records	Enabled - Configuration Required
Secondary RAT Usage Report in CDR Records	Disabled - Configuration Required
Suppressing Handover Request for VoWiFi IR Subscribers	Disabled - Configuration Required
Support to Add Two Additional Attributes in EDR	Enabled - Always-on
Timeout Exclusion from CSFB Counters	Enabled - Always-on