



Feature Defaults Quick Reference

- Feature Defaults, on page 1

Feature Defaults

The following table indicates what features are enabled or disabled by default.

| Feature | Default |
|--|-----------------------------------|
| Addition of Server Unreachable Field in CDR | Disabled - Configuration Required |
| Capability to Record and Produce Call Transactions | Disabled - Configuration Required |
| Cloud Initialization Support for Elastic Services Controller | Enabled - Always-on |
| Configuring Access-Link Fastpath to Enforce APN MTU for IPv4 Traffic | Enabled - Always-on |
| Configuring SRP Checkpoint | Disabled - Configuration Required |
| Deprecated CLI for MME Initiated PDN Disconnection | Disabled - Configuration Required |
| ePDG Support on VPC-D | Disabled - Configuration Required |
| ePDG Interworking with SMF+P-GW-IWK Support | Disabled - License Required |
| Enable mme clear-route-multipath-zero in CLI | Disabled - Configuration Required |
| Enforcing Detach on Last PDN Deactivation | Disabled - Configuration Required |
| IKEv2 Authentication Failure Counters | Disabled - Configuration Required |
| LTE-M RAT Indication Support | Disabled - Configuration Required |
| No IMSI or MSISDN Included in LRR for VoLTE EM Call from User of Foreign Network | Disabled - Configuration Required |
| SaMOG Support on VPC-DI | Disabled - Configuration Required |
| Support for 187 and 188 Information Element Types on S2b Interface | Disabled - Configuration Required |

| Feature | Default |
|---|-----------------------------------|
| Support for 187 and 188 Information Element Types on S5 and S8 Interfaces | Disabled - Configuration Required |
| TCP RESET Support | Disabled - Configuration Required |
| Timestamp Accuracy Improvement | Disabled - Configuration Required |
| VLR Round-Robin Load Balancing | Disabled - Configuration Required |