



Configuring Access Points with Dual-Band Radios

- [Configuring Access Points with Dual-Band Radios \(GUI\), on page 1](#)
- [Configuring Access Points with Dual-Band Radios \(CLI\), on page 1](#)

Configuring Access Points with Dual-Band Radios (GUI)

- Step 1** Choose **Wireless > Access Points > Radios > Dual-Band Radios** to open the Dual-Band Radios page.
- Step 2** Hover your cursor over the blue drop-down arrow of the AP and click **Configure**.
- Step 3** Configure the Admin Status.
- Step 4** Configure CleanAir Admin Status as one of the following:
- Enable
 - Disable
 - 5 GHz Only
 - 2.4 GHz Only
- Step 5** Click **Apply**.
- Step 6** Click **Save Configuration**.
-

What to do next

You can monitor the access points with dual-band radios by navigating to **Monitor > Access Points > Radios > Dual-Band Radios**.

Configuring Access Points with Dual-Band Radios (CLI)

Procedure

- Configure an access point with dual-band radios by entering this command:

config 802.11-abgn {enable | disable} *ap-name*

- Configure the CleanAir features for an access point with dual-band radios by entering this command:

config 802.11-abgn cleanair {enable | disable} *ap-name* band 2.4-or-5-GHz