

Release Notes for Cisco Wireless Control System Navigator 1.1.62.11

January 24, 2008

These release notes describe open and resolved caveats for the Cisco Wireless Control System Navigator 1.1.62.11.

The Cisco Wireless Control System Navigator is hereafter referred to as Cisco WCS Navigator.

Contents

These release notes contain the following sections.

- Introduction, page 2
- Cisco WCS Navigator Features, page 2
- Requirements for Cisco WCS Navigator, page 2
- Important Notes, page 3
- Caveats, page 4
- Troubleshooting, page 5
- Related Documentation, page 5
- Obtaining Documentation, Obtaining Support, and Security Guidelines, page 5



Introduction

The Cisco WCS Navigator manages multiple Cisco WCSs (running the same release as Navigator) and provides a unified view of the network. It uses SOAP/XML over HTTPs to communicate with individual WCSs. Navigator provides monitoring functionality and reporting capability across all WCSs. In addition, network-wide searches are available. In Windows and Linux, Cisco WCS Navigator runs as a service continuously and resumes running after a reboot.

Cisco WCS Navigator delivers an aggregated platform for enhanced scalability, manageability, and visibility of large-scale implementations of the Cisco Unified Wireless Network. This software-based solution gives network administrators easy access to information from multiple geographically diverse Cisco WCS management platforms. It supports partitioning of the unified wireless network at the management level.

Cisco WCS Navigator Features

The Cisco WCS Navigator provides:

- Management of multiple Cisco WCSs
 - Supports up to 20 Cisco WCS management platforms
 - Management of up to 30,000 Cisco Aironet lightweight access points from a single management console
- A unified view of the network
- Overview and multilevel monitoring of wireless networks
- The ability to run reports for all WCSs
- Network-wide searches
- A link to return to the Navigator when directed to a regional WCS from Navigator

Requirements for Cisco WCS Navigator

Hardware Requirements for Navigator

The following server hardware and software is required to support Cisco WCS Navigator for Windows or Linux.

- Supports up to 20 wireless control systems depending on the Navigator license.
- A 3.2 GHz Intel Dual Core processor with 4 GB of RAM and an 80-GB hard drive.
- A 40-GB minimum of available disk space on your hard drive.



The available disk space listed is a minimum requirement but may be different for your system depending on the number of backups.



Note

The screen resolution should be set to 1024 x 768 pixels for Navigator.

Supported Operating Systems

The following operating systems are supported:

- Windows 2003/SP2 or later with all critical and security Windows updates installed. 64-bit installations are not supported.
- Red Hat Linux Enterprise Server 4.0 Update 5 or Advanced Server 4.0 Update 5. Only 32-bit operating system installations are supported. 64-bit operating system installations are not supported.
- Windows 2003 and Redhat Linux version support on VmWare ESX 3.0.1 version and above.



VmWare must be installed on a system with these minimum requirements: Quad CPU running at 3.16 GHz 8 GBs RAM

200 GB hard drive



The Cisco WCS Navigator supports both Internet Explorer 6.0 and 7.0.

Important Notes

WCS and Navigator Compatibility

WCS and Navigator must be from the same release in order to be compatible (see Table 1). Although the release numbers will not be the same, you must verify whether they were part of the same release. For example, Navigator 1.0 is compatible with WCS 4.1, and Navigator 1.1 is compatible with WCS 4.2.

Table 1 Compatiblity Matrix

Navigator Release Number	WCS Release Number
1.0.83.0	4.1.83.0
1.0.91.0	4.1.91.0
1.1.62.0	4.2.62.0
1.1.62.11	4.2.62.11

Japanese Microsoft Windows Support

This release adds support for the use of Cisco WCS Navigator on a server running the Japanese version of Microsoft Windows. Cisco Navigator will run in English.

Caveats

This section lists Open Caveats and Resolved Caveats for this software release.

Open Caveats

These caveats are open in Cisco WCS Navigator 1.1.62.11:

- CSCsi04593—The Monitor Network summary page has an incorrect graph.
 - Workaround: After a refresh, the graphs works fine.
- CSCsi24635—When a WCS on Navigator becomes unreachable, a WCS alarm appears on the alarm dashboard. Clicking the alarm opens the Alarm Details page. Clicking the link to the events history produces an unknown exception.
 - Workaround: None at this time.
- CSCsi31663—Accessing the wireless control system pages from Navigator results in a prompt stating that http is not enabled and that user must click the designated link to use https.
 - Workaround: Under Configure > WCS within the affected wireless control system, change the protocol to **https**.
- CSCsj98464—If you delete a WCS from Navigator and run an inventory report, the devices associated with that WCS (such as controllers, access points, and so on) still show in the report.
 - Workaround: None at this time.
- CSCsk14508 and CSCsk17233—WCS and Navigator must be on the same release in order to be compatible.
 - Workaround: Upgrade WCS and Navigator to be the same release. Navigator 1.0 is compatible with WCS 4.1, and Navigator 1.1 is compatible with WCS 4.2.
- CSCsk94951—The alarm status icon is incorrect. It shows as green when an alarm is critical. Workaround: None at this time.

Resolved Caveats

This caveat is resolved in Cisco WCS Navigator 1.1.62.11:

• CSCsl35056—CGI-bin URLs are no longer accessible through Cisco WCS and Navigator.

If You Need More Information

If you need information about a specific caveat that does not appear in these release notes, you can use the Cisco Bug Toolkit to find caveats of any severity. Click this URL to browse to the Bug Toolkit:

http://tools.cisco.com/Support/BugToolKit/

(If you request a defect that cannot be displayed, the defect number might not exist, the defect might not yet have a customer-visible description, or the defect might be marked Cisco Confidential.)

Troubleshooting

For the most up-to-date, detailed troubleshooting information, refer to the Cisco TAC website at the following location:

http://www.cisco.com/tac

Click Technology Support, select Wireless from the menu on the left, and click Wireless LAN.

Related Documentation

For information on the Cisco WCS Navigator, refer to the Cisco Wireless Control System Navigator 1.1.62 Installation Guide.

Obtaining Documentation, Obtaining Support, and Security Guidelines

For information on obtaining documentation, obtaining support, providing documentation feedback, security guidelines, and also recommended aliases and general Cisco documents, see the monthly What's New in Cisco Product Documentation, which also lists all new and revised Cisco technical documentation, at:

http://www.cisco.com/en/US/docs/general/whatsnew/whatsnew.html

CCDE, CCVP, Cisco Eos, Cisco StadiumVision, the Cisco logo, DCE, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn is a service mark; and Access Registrar, Aironet, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0801R)