

ăf;ă,ăfăăf¼ ăfăăfăăf¼ă,¹	è,†ă¼±æ€šă®ăă,ă,ăăăăăăăăăă,¹
12.0S	15ă€ 16ă€ 17ă€ 18ă€ 19ă€ 21
12.0SC	15 16
12.0SL	15ă€ 17ă€ 19
12.0ST	16ă€ 17ă€ 18ă€ 19ă€ 20ă€ 21
12.0SP	19 20
12.0SX	21
12.1	10ă€ 10aă€ 11ă€ 11aă€ 11bă€ 12ă€ 12aă€ 12bă€ 12că€ 13ă€ 14ă€
12.1E	10ă€ 11bă€ 11.5
12.1EA	8 9
12.1EC	10 10.5
12.1EX	10
12.1EY	10
12.2	6.8aă€ 7ă€ 7aă€ 7bă€ 7c
12.2DA	7 9.4

12.2S	9 10.5
-------	--------

è,†ã¼±æ€šã,'ã«ã,"ãšã,,ãªã,,ã"ã"ãœçç°èªã•ã,œãÿè½ã"

ä»-ã®ã,ã,¹ã,³è½ã"ã«ãšã,,ã|ã"ã®ã,çãf%ããfã,ãã,¶ããã®ã½±éÿã,ã—ã'ã,

è©³ç°

RTRæÿè½ã,'ã½ç"ªã™ã,ã"ã€ã¿œç"æ™,é-ã"ã,çãf™ã,ããf©ãf"ãfãftã,£ã,'æ,-ã®šã—ã|

Time

Reporter(RTR)ã®çµ±è"æf...ã±ã«ãÿªã¥ã,,ã|ã€ãf^ãf©ãf-ãf«ã,ãã¥ãf¼ãftã,£ã³ã,°ã€ã•

ãf«ãf¼ã,ãã-ã€RTRãf-ã,¹ãfãf³ãfãœãœ%ããš¹ã«ãªã£ã|ã,,ã,ã'ã^ã«ã®ã¿è,,

<#root>

Router>

show rtr responder

```
RTR Responder is: Enabled
Number of control messages received: 0 Number of errors: 0
Recent sources:
Recent error sources:
```

ã€RTR Responder is:

Enabledã€ã"ã,,ãtè;œãœj"çªã•ã,œãÿã'ã^ã-ã€è,†ã¼±æ€šãœããœ"ã—ã

ã¾ãÿã-ã€æ¬ã®æ%ãé tã,'ã½ç"ªãšãã¾ã™ã€,

<#root>

Router>

show ip socket

```
show ip socket
Proto Remote Port Local Port In Out Stat TTY OutputIF
....
17 0.0.0.0 0 10.0.0.1 1967 0 0 89 0
```

ã,šè"ã®ã¾ã®ã,ããtã«ãœãf«ãf¼ã,ãœãfãf¼ãf¹967ã,'ãfãffã,¹ãf³ã—ã|ã,,ã,è;œã

Cisco IOSã,½ãfãf^ã,ã,šã,çã®ã'ã^ã€ãã"ã®è,,†ã¼±æ€šã-²ããã®Cisco Bug ID

CSCdx17916ãŠã,^ã³CSCdx61997ã ¨ã—ã|æ-†æ>åĀ-ã•ã,Āã|ã,,ã¾ã™ã€,

ã>žé¿ç-

RTRãf-ã,¹ãfã³ãfãĀ,‘ç,,jãŠ¹ã«ã™ã,ã»¥ã-ã«ã>žé¿ç-ã-ã,ã,Šã¾ãã,“ã€ãf«ãf¼ã,¿ã«

RTRã, ’ãf†ã,£ã,»ãf¼ãf-ãf«ã«ã™ã,ã«ã-ã€æ-¡ã®ã,³ãfžãf³ãf%ã,ã®ÿè;Āã™ã,ã¿...è|ã

<#root>

Router#

conf t

Enter configuration commands, one per line. End with CNTL/Z.

Router(config)#

no rtr responder

Router(config)#

exit

Router#

copy running-config startup-config

ãfãffãf^ãfãf¼ã,ã,ãffã,,ã,Šã®ã™ã¹ã|ã®ã•é;Āãfã,±ãffãf^ã,ãf-ãfãffã,ã™ã,ãã’ã

<#root>

Router#

conf t

Enter configuration commands, one per line. End with CNTL/Z.

Router(config)#

access-list 101 deny udp any any eq 1967

Router(config)#

interface eth0

Router(config)#

ip access-group 101 in

ã”ã®ã¾ãŠã-ã€ã,ããf³ã,¿ãf¼ãf•ã,Šã,ãã,¹eth0ã-ãfãffãf^ãfãf¼ã,ã,ãffã,ã®æ-¹ã’ã

ã”ã,Āã«ã,^ã,Šã€ãfãf¼ãf^1967/UDPã®ã|ã®ãfã,±ãffãf^ãĀãfãffãf^ãfãf¼ã,ã«ã..

Router>
Router#

<#root>

Router#

conf t

Enter configuration commands, one per line. End with CNTL/Z.

Router(config)#

access-list 101 permit udp 10.0.0.1 10.0.0.10 eq 1967

Router(config)#

access-list 101 deny udp any 10.0.0.10 eq 1967

Router(config)#

interface eth0

Router(config-if)#

ip access-group 101 in

Router(config-if)#

Router(config-if)#

Cisco IOS Router configuration commands, one per line. End with CNTL/Z.

Router(config-if)#
access-list 101 permit udp 10.0.0.1 10.0.0.10 eq 1967

Router(config-if)#
access-list 101 deny udp any 10.0.0.10 eq 1967

Router(config-if)#
interface eth0

Router(config-if-if)#
ip access-group 101 in

- Maintenance of the configuration file. The configuration file is stored in the flash memory of the router. The configuration file is named `config.text` or `config.txt`. The configuration file is used to store the configuration commands that you enter in the router. The configuration file is used to restore the configuration of the router if it is lost or corrupted. The configuration file is used to backup the configuration of the router. The configuration file is used to restore the configuration of the router if it is lost or corrupted. The configuration file is used to backup the configuration of the router.
- The configuration file is stored in the flash memory of the router. The configuration file is named `config.text` or `config.txt`. The configuration file is used to store the configuration commands that you enter in the router. The configuration file is used to restore the configuration of the router if it is lost or corrupted. The configuration file is used to backup the configuration of the router.
- The configuration file is stored in the flash memory of the router. The configuration file is named `config.text` or `config.txt`. The configuration file is used to store the configuration commands that you enter in the router. The configuration file is used to restore the configuration of the router if it is lost or corrupted. The configuration file is used to backup the configuration of the router.

Router(config-if)#
ip access-group 101 in

12.0SP	c10720
12.0ST	MPLS/ã, ç, ã, °ã, 1ã, ðãffãf ðãf³ã, °ã€ ðGSR 12000ã€
12.0SX	ESRã ð'ã ð'çÿæœÿã^ ðæœÿã°Žã...¥10000ãfãf
12.0SY	
12.0WC	2900XLã ðŠã, ^ã ð³3500XLç""ã ð®çÿæœÿé-“ã^ ð
12.0XE	çÿæœÿé-“ã ð®æ—©æœÿã°Žã...¥ãfãfãfãf¼ã, 1
Affected 12.1-Based Releases	
12.1	General Deployment(GD)ã€™™èŁœi¼šã€™™ã ð¹ã ð!
12.1E	ã, ³ã, ç/ISPã, ðf ðãf¼ãf^i¼šGSRã€ ðRSPã€ ðc7200
12.1EA	Catalyst 2950
12.1EC	æ—©æœÿã°Žã...¥(ED):ubr7200ã€ ðUBRãf~ãffãf%
12.1EW	Early Deploymentãfãfãf¼ã, 1ã€ ðé™™ ðã®šãf—ãf
12.1EW	Early Deploymentãfãfãf¼ã, 1ã€ ðé™™ ðã®šãf—ãf
12.1EX	Catalyst 6000

12.2XD	ICS7750/820/soho70
12.2XE	806ã€◆828ã€◆soho78
12.2XH	1700 820/800/soho70
12.2XI	820/soho
12.2XJ	1700
12.2XK	820/soho
12.2XL	1700 820/800/soho70
12.2XM	çÿæœÿé–“ã◆®æ—©æœÿå°Žå...¥ãfªãfªãf¼ã,¹
12.2YA	çÿæœÿé–“ã◆®æ—©æœÿå°Žå...¥ãfªãfªãf¼ã,¹
12.2YB	çÿæœÿé–“ã◆®æ—©æœÿå°Žå...¥ãfªãfªãf¼ã,¹
12.2YC	çÿæœÿé–“ã◆®æ—©æœÿå°Žå...¥ãfªãfªãf¼ã,¹

12.2YF	Cisco Packet Data Serving
12.2YG	çÿæœÿé–“ã®æ—©æœÿå°Žå...¥ãfãfãf¼ã,¹
12.2YH	çÿæœÿé–“ã®æ—©æœÿå°Žå...¥ãfãfãf¼ã,¹



*ã™ã¹ã |ã®æ—¥ä»~ã¯æ |,ç®—ãšã,ã,šã€ãå%œæ'ã•ã,Œã,ã¯èf½æ€šãŒã,ã,šã
 é€šã,ã®ãfjãf³ãftãfšãf³ã,¹
 ãfãfãf¼ã,¹ã æ"è¼fã—ãÿå 'ã^ã€æš«ã®šãfãfãf¼ã,¹ã«ã¾ã—ã |ã¯ãŽ³æ¼ãª

ã,æfã^©ç"ã°<ã¾ã"ã...-ã¼ç™ºèj"

Cisco PSIRT

ãšã¯ã€æœ-ã,çãf%œãfã,ãã,¶ãfã«è"è¼%œã•ã,Œã |ã,ã,ã,è,,tã¼±æ€šã®ã,æfã^©ç

URL

<https://sec.cloudapps.cisco.com/security/center/content/CiscoSecurityAdvisory/cisco-sa-20030515-saa>

æ"¹è,ã±¥æ´

ãfãfã,ãfšãf³ 1.0	2003ã¹'5æœ^15æ—¥ã€15:00 UTC(GMT)	ã^ã>žå...-é-ãfãfãf¼ã,¹
ãfãfã,ãfšãf³ 1.1	2003ã¹'12æœ^12æ—¥	ã€Œã,æfã^©ç"ã"ã...-é-ã,çãfšã,ãf³ã,ãfjãf³ãf^ã€ access-group 101 inã,'Router(config-if)#ip access-group 10

ã^©ç"è|ç´,,

æœ-ã,çãf%œãfã,ãã,¶ãfã¯ç,,ãç"è"¼ã®ã,,ã®ã"ã—ã |ã"æã¾ã—ã |ãšã,šã€
 æœ-ã,çãf%œãfã,ãã,¶ãfã®æf...ã±ãšã,ã³ãfãf³ã,ã®ã½çç"ã«é-çã™ã,è²-ã»ã®ã,€
 ã¾ãÿã€ã,ã,¹ã,³ã¯æœ-ãf%œã,ãfãfãf³ãfã®ãt...ã®¹ã,'ã°ã'šãªã—ã«ã%œæ'ã—ã

æœ-ã,çãf%ãfã,ã,ã,ãfãã®è~èç°ãt...ã®1ã«é-çã—ã|æf...ã±é...ãzjã® URL
ã,çœç•ã—ã€ããç<-ã®è»çè¼%ã,,æ,,è~³ã,'æ-½ã—ãÿã'ã^ã€ã½"ç³¼ãÇç®;ç
ã"ã®ãf%ã,ãfãf;ãf³ãf^ã®æf...ã±ã-ã€ã,ã,ã,ã,³è£½ã"ã®ã,ãf³ãf%ãf!ãf¼ã,ã,ã,ã³¼è±;ã

翻訳について

シスコは世界中のユーザにそれぞれの言語でサポート コンテンツを提供するために、機械と人による翻訳を組み合わせて、本ドキュメントを翻訳しています。ただし、最高度の機械翻訳であっても、専門家による翻訳のような正確性は確保されません。シスコは、これら翻訳の正確性について法的責任を負いません。原典である英語版（リンクからアクセス可能）もあわせて参照することを推奨します。