



BCE_Config.xml のパラメータ

次の表に、アカウント管理者が変更できる BCE_Config.xml ファイルのパラメータを示します。

パラメータ	オプション	説明	許容値
plugin	Edition	プラグインタイプ	encrypt、decrypt、flag
	maxMailSize	暗号化メールの最大サイズ	デフォルト：7MB、最大値 = 25 MB
checkForUpdates	checkAutomatically	Outlook を起動したときに更新の自動チェックを有効にするには true を、無効にするには false を設定します。デフォルト値は true です。	true、false

パラメータ	オプション	説明	許容値
callHome	callHomeEnable	Outlook を起動したときに使用状況データの送信を有効にするには true に、送信を無効にするには false に設定します。デフォルト値は true です。false に設定すると、ユーザーは匿名の使用状況データをシスコに送信できません。	true、false
	callHomeAdminEnable	Outlook を起動したときに使用状況データの送信を有効にするには true に、送信を無効にするには false に設定します。デフォルト値は true です。false に設定すると、使用状況データ収集に関する通知を受信できず、シスコに匿名の使用状況データを送信することができなくなります。	true、false
	displayUsageReminder	暗号化中に使用状況リマインダを表示するかどうかを指定します。	true、false
	encryptByDefault	暗号化を有効にするかどうかを指定します。iOS または Andriod には適用されません。	true、false

パラメータ	オプション	説明	許容値
	subjectFlag	plugin edition が「flag」の場合にのみ使用して、メッセージの暗号化にフラグを付ける方法を定義します。subjectFlag：指定したテキストを件名フィールドに追加します。元の件名に\${subject}を使用します。	例：[SECURE]\${subject}
Password	duration	ユーザーパスワードをキャッシュする期間（分単位の整数）。 max == 0 の場合、パスワードキャッシュはなく、毎回パスワードが必要です。 max == -1 の場合、パスワードは無期限にキャッシュされます。	min = 0、max = 1440 (分)

パラメータ	オプション	説明	許容値
outlook	showEncryptDialog	暗号化されたメッセージの送信中に [Secure Envelope Options] ダイアログを表示します。	true、false
	showPluginOptions	暗号化、診断、追加オプションを実行できる [Plug-in Options] ダイアログボックスを開く [Plug-in Options] ボタンを有効にするには true に、無効にするには false に設定します。false を設定すると、[Plug-in Options] ボタンは表示されません。	true、false
	showManageMessageButton	true または false に設定して、[Manage Messages] ダイアログボックスを開く [Manage Messages] ボタンを有効または無効にします。このダイアログボックスでメッセージをロックしたり、メッセージの有効期限を設定したりできます。false を設定すると、[Manage Messages] ボタンは表示されません。	true、false
	useKeyServerMessageBody	true の場合、プラグインはプラグインの代わりにキーサーバーからの発信メッセージの本文を使用します。このフィールドは、Microsoft Outlook にのみ適用されます。	true、false
	locale		en、es、it、ja、de、zh、fr、pt

パラメータ	オプション	説明	許容値
		<p>未登録ユーザーの場合など、受信者のロケール設定を決定できない場合のデフォルトロケールを定義します。この値を省略すると、キーサーバーがデフォルトロケールを決定します。</p> <p>キーサーバーでサポートされているロケールのリスト：</p>	
keyserver	connection_timeout	キーサーバーへの接続が確立されるまでに待機する時間の長さ。	整数（ミリ秒単位）
	socket_timeout	キーサーバーからのデータを待機する時間の長さ。	整数（ミリ秒単位）
	accept_untrusted_certificates	無効な証明書に対してSSL接続を続行するかどうかを決定します。	true、false

パラメータ	オプション	説明	許容値
proxies	proxy	プロキシ設定の名前。 <proxies> セクションに指定し、キーサー バーと通信する場合に 使用します。	空白、カスタム名
	proxy name	特定のプロキシの設定 を入力する場合に選択 します。	デフォルト
	host	システムまたはプロキ シサーバーのホスト名 または IP アドレスを 指定します。	有効な IP アドレスま たはホスト名。
	port	システムまたはプロキ シサーバーのポートを 指定します。	整数
	user	サーバーでユーザー名 が必要な場合に、ユー ザー名を入力します。	character
	password	システムまたはプロキ シサーバーに対して入 力したユーザー名に関 連するパスワードを入 力します。	パスワード
	addmessagebar	セキュアメッセージに メッセージバーを追加 する場合に選択しま す。	true、false
message	sensitivity	暗号化した電子メール のセキュリティを設定 します。デフォルト値 は BCE_Config.xml ファイルに定義されて います。	0 = 低、10 = 中、50 = 高

パラメータ	オプション	説明	許容値
messagebar	replyenabled	メッセージバーが有効になっている場合、メッセージバーに [Reply] が表示されます。	true、false
	replyallenabled	メッセージバーが有効になっている場合、メッセージバーに [Reply to All] が表示されます。	true、false
	forwardenabled	メッセージバーが有効になっている場合、メッセージバーに [Forward] が表示されます。	true、false
	openinsamewindow	エンベロープと同じウィンドウでセキュアメッセージを開く場合に選択します。	true、false
	sendreturnreceipt	受信者が送信された電子メールが開いたときに受信確認を要求するには、このオプションを選択します。	true、false

パラメータ	オプション	説明	許容値
recipient	menu	エンベロープが登録済みエンベロープの受信者のドロップダウンメニューを表示するかどうかを決定するブール値。true の場合、ドロップダウンメニューが表示されます。それ以外の場合は、メッセージの一意の受信者がエンベロープに埋め込まれ、メニューが不要になります。 このメッセージの受信者が複数いる場合、この値は無視されます。	true、false



(注) このリストに示されていないパラメータは変更しないことを推奨します。

一例として、サンプルの BCE_Config.xml ファイルを以下に示します。



注意 次のコードスニペットの内容をコピーして使用しないでください。これは参考のみとしてください。

```
<?xml version="1.0" encoding="UTF-8"?>
<!--&#xa;If the plugin supports the possibility for the user to edit a parameter in the
UI,&#xa;the display XML attribute gives the account administrator the ability to
change&#xa;this behavior by setting it to one of the following values:&#xa;    editable
- The configuration is visible and editable in the UI&#xa;    readonly - The configuration
is viewable but not editable in the UI&#xa;    hidden - The configuration is not viewable
in the UI&#xa;-->
<encryption acctId="XXXX" version="1.0" id="$Revision: 1.27 $">
  <!--&#xa;    Plugin related configuration. Valid type edition values are:&#xa;
decrypt - Plugin can only decrypt PXE envelopes.&#xa;    flag - Plugin can decrypt
and flag a message for encryption.&#xa;    encrypt - Plugin can decrypt and encrypt
a message on the device.&#xa;    -->
  <plugin edition="encrypt">
    <!-- reportingComponent - section responsible for configuring reporting plug-in.
-->
    <reportingComponent>
      <lockUiOptions>>false</lockUiOptions>
      <enabled>>true</enabled>
      <keepSentReports>>false</keepSentReports>
      <!--&#xa;    reportingFormat - Defines format of the report. Supported
values:&#xa;    encrypted - report will be encrypted before sending;&#xa;
plain - report will be sent without encryption;&#xa;
```



```

Default value: encrypted.&#xa;          -->
<report>
  <format>encrypted</format>
  <subject>Cisco Email Security Plug-in Report (${reportType})</subject>
</report>
<maxMailSize>1005000</maxMailSize>
<attachmentName>orig_msg.enc</attachmentName>
<showReportSuccessOne>true</showReportSuccessOne>
<showReportSuccessMultiple>true</showReportSuccessMultiple>
<addExplorerCommandBar>true</addExplorerCommandBar>
<addInspectorCommandBar>true</addInspectorCommandBar>
<addContextMenu>true</addContextMenu>
<addBlockSenderButton>true</addBlockSenderButton>
<reportTypes>
  <reportType name="spam">
    <!-- Only one email address is allowed for each report type -->
    <address>outlook_spam@access.ironport.com</address>
    <copyAddressInPlainFormat></copyAddressInPlainFormat>
    <headerValue>spam</headerValue>
    <showInJunkFolder>true</showInJunkFolder>
    <largeRibbonButton>true</largeRibbonButton>
  </reportType>
  <reportType name="ham">
    <!-- Only one email address is allowed for each report type -->
    <address>outlook_ham@access.ironport.com</address>
    <copyAddressInPlainFormat></copyAddressInPlainFormat>
    <headerValue>ham</headerValue>
    <showInJunkFolder>true</showInJunkFolder>
    <largeRibbonButton>true</largeRibbonButton>
  </reportType>
  <reportType name="virus">
    <!-- Only one email address is allowed for each report type -->
    <address>outlook_virus@access.ironport.com</address>
    <copyAddressInPlainFormat></copyAddressInPlainFormat>
    <headerValue>virus</headerValue>
    <showInJunkFolder>true</showInJunkFolder>
    <largeRibbonButton>>false</largeRibbonButton>
  </reportType>
  <reportType name="phish">
    <!-- Only one email address is allowed for each report type -->
    <address>outlook_phish@access.ironport.com</address>
    <copyAddressInPlainFormat></copyAddressInPlainFormat>
    <headerValue>phish</headerValue>
    <showInJunkFolder>true</showInJunkFolder>
    <largeRibbonButton>>false</largeRibbonButton>
  </reportType>
  <reportType name="marketing">
    <!-- Only one email address is allowed for each report type -->
    <address>outlook_mktg@access.ironport.com</address>
    <copyAddressInPlainFormat></copyAddressInPlainFormat>
    <headerValue>marketing</headerValue>
    <showInJunkFolder>true</showInJunkFolder>
    <largeRibbonButton>>false</largeRibbonButton>
  </reportType>
</reportTypes>
</reportingComponent>
<!-- Check for update for the plugin -->
<checkForUpdates>
  <checkAutomatically display="hidden">false</checkAutomatically>
  <serverURL>http://updates.res.cisco.com</serverURL>
</checkForUpdates>
<!-- Call home section -->
<callHome>
  <callHomeEnabled>true</callHomeEnabled>

```

```

        <callHomeAdminEnabled>true</callHomeAdminEnabled>
    </callHome>

    <!-- Specify whether show Usage Reminder during encryption (true) or not (false).
-->
    <displayUsageReminder>true</displayUsageReminder>
    <!--&#xa; In case of an error, this will be the email address and subject
that will&#xa; appear in the user generated diagnostic email.&#xa; The
diagnostic email field should only be used when a company is hosting their own&#xa;
encryption helpdesk.&#xa; The following entries are not allowed:
support@cisco.com,support@res.cisco.com &#xa; This feature is not supported in
Outlook.&#xa; -->
    <diagnostic>
        <email display="readonly"><!-- Add your support email address here --></email>

        <subject display="readonly">Cisco BCE Diagnostic Information</subject>
    </diagnostic>
    <!--&#xa; Specify whether encryption should be enabled (true) or not
(false).&#xa; Not applicable on iOS or Android.&#xa; -->
    <encryptByDefault display="editable">false</encryptByDefault>
    <!--&#xa; Used only if plugin edition="flag", defines how the message
should&#xa; be flagged for encryption. Only one of the following XML elements&#xa;
can be specified.&#xa; subjectFlag - Add specified text to subject
field.&#xa; Use ${subject} for the original subject.&#xa;
headerFlag - Add specified MIME header.&#xa; For example:&#xa;
<subjectFlag>[SECURE]${subject}[ME]</subjectFlag>&#xa; or:&#xa;
<headerFlag>X-IronPort-Encrypt: True</headerFlag>&#xa; Note: Not all plugins
support the XML element, headerFlag, especially, mobile devices.&#xa; -->
    <subjectFlag>[SECURE]${subject}</subjectFlag>
    <!-- Note: Not all plugins will provide access to these links -->
    <links>
    <!-- URL containing help about the PXE envelope -->
    <!-- If help xml element is not defined the plugin should use its system default
<help display="hidden"/> -->
    </links>
    <cache>
        <password>
            <!--&#xa; How long user passwords should be cached (an
integer, in minutes).&#xa; if max == 0, there is no password cache and
passwords are required everytime.&#xa; if max == -1, passwords are cached
indefinitely.&#xa; -->
            <duration min="0" max="1440" display="editable">1440</duration>
        </password>
        <!-- The section below sets the caching of the session in clients -->
        <samlSession>
            <cacheSession>True</cacheSession>
        </samlSession>
        <envelope>
            <!-- Cache size of PXE envelope storage (an integer, in MB) -->
            <storage display="editable">6</storage>
            <!-- Maximum duration to retain envelopes files (an integer, in minutes).
-->
            <duration display="editable">43200</duration>
        </envelope>
    </cache>
    <outgoingSMTP>
        <!-- If true then outgoing SMTP is enabled, otherwise native mail client
will be used.&#xa; display=editable will allow user to change the approach,
in case if he is outside of corporate VPN network. -->
        <isEnabled display="hidden">false</isEnabled>
        <!-- Corporate server address -->
        <server></server>
        <!-- SMTP port -->
        <port></port>

```

```

        <!-- Enable or disable SSL for connection -->
        <sslEnabled></sslEnabled>
    </outgoingSMTP>
    <!-- Outlook specific configuration -->
    <outlook>
        <!-- Show "Secure Envelope Options" dialog while sending encrypted message
        (true) or not (false). -->
        <showEncryptDialog display="editable">true</showEncryptDialog>
        <!--&#xa;          Used only if plugin edition="flag", defines how the
message should&#xa;          be flagged for encryption using the Outlook message
sensitivity flag.&#xa;          Valid values are private, confidential, and public&#xa;
        <sensitivityFlag display="editable"></sensitivityFlag>&#xa;          -->
        <!-- Determines whether plug-in options dialog will be shown in Outlook -->
        <showPluginOptions>true</showPluginOptions>
        <!-- Determines whether the manage message button will be shown in Outlook
-->
        <showManageMessageButton>true</showManageMessageButton>
    </outlook>
    <!--&#xa;          If true, the plugin will use the outgoing message body from
the key server&#xa;          instead of the plugin. This field is only applicable
to Microsoft Outlook.&#xa;          -->
    <useKeyServerMessageBody display="editable">true</useKeyServerMessageBody>
    </plugin>
    <application>
        <!-- ##### -->
        <!-- Do not modify these "application" URLs -->
        <!-- ##### -->
        <companyURL>https://res.cisco.com</companyURL>
        <helpURL>https://res.cisco.com/websafe/help?topic=RegEnvelope</helpURL>
        <notListedURL>https://res.cisco.com/websafe/help?topic=AddrNotShown</notListedURL>

    <forgotPasswordURL>https://res.cisco.com/websafe/pswdForgot.action</forgotPasswordURL>

    <passwordNotShownURL>https://res.cisco.com/websafe/help?topic=PPNotShown</passwordNotShownURL>

    </application>
    <external>
        <!--&#xa;          Secure base URL to use for the key server, message bar logo,&#xa;
message bar secure reply, and enrollment URL.&#xa;          -->
        <secure><url>https://res.cisco.com</url></secure>
        <!--&#xa;          Unsecure base URL to use for the message bar help and GET Payload
Transport.&#xa;          If omitted, then external secure url will be used.&#xa;
-->
        <unsecure><url>http://res.cisco.com</url></unsecure>
    </external>
    <!--&#xa;          Defines the default locale if the recipient's locale preference&#xa;
can not be determined, such as for an unregistered user. If this value&#xa;          is
omitted, the key server will determine the default locale.&#xa;          List of locales
supported by the key server:&#xa;          en - English (US)&#xa;          nl_NL - Dutch&#xa;
de - German&#xa;          es - Spanish&#xa;          fr - French&#xa;          it -
Italian&#xa;          pl - Polish&#xa;          pt - Portugese&#xa;          ru - Russian&#xa;
zh_CN - Chinese (Simplified)&#xa;          ja - Japanese&#xa;          ko - Korean&#xa;
List of locales supported by Outlook plug-in:&#xa;          en - English&#xa;
es - Spanish&#xa;          it - Italian&#xa;          ja - Japanese&#xa;          de -
German&#xa;          zh - Chinese&#xa;          fr - French&#xa;          pt - Portuguese
&#xa;          Please note, if you want to use locales from plug-in, useKeyserverMessageBody
option should be set to 'False'&#xa;          -->
        <locale display="editable"></locale>
    <keyserver>
        <!-- Key server token file used for encryption. -->
    </keyserver>

    <token><![CDATA[data@id=19916&aId=7058&name=Token7058&desc=Default+Token&value=gsCkHZEfFQq&hXJ4jr2ugDCSoG7nKw3]]></token>

```

```

        <!-- How long to wait for a connection to the key server to be established (an
integer, in milliseconds). -->
        <connection_timeout display="editable">20000</connection_timeout>
        <!-- How long to wait for data from the key server (an integer, in milliseconds).
-->
        <socket_timeout>30000</socket_timeout>
        <!-- Determines if the SSL connection should continue for invalid certificates
-->
        <accept_untrusted_certificates>>false</accept_untrusted_certificates>
        <!-- Name of proxy configuration, specified in the <proxies> section, to use
when communicating with key server. Supported values are:
blank - No Proxy (Recommended). For Outlook, this will update the plugin's
connection settings to either "No Proxy" or "Use System Proxy
Settings", depending if the <proxy> name is specified as "Default"
in the <proxies> section.
custom_name - Name of a custom proxy configuration to use, defined in the
<proxies> section. For Outlook, do not use "Default" as a custom name.
To update Outlook to use the system proxy, this field should
remain blank. -->
        <proxy></proxy>
    </keyserver>
    <!-- Proxy configurations. This feature is not supported on Android, or
iOS. -->
    <proxies>
        <!-- Name of the proxy configuration that will be used when communicating with
the key server. For Outlook, specifying a name of "Default" will update
the plugin's connection setting to "Use System Proxy Settings". In
this case, the proxy settings are irrelevant and ignored. -->
        <proxy name="Default">
            <!-- Proxy implementation class to use. Supported values
are: Web; SOCKS4; SOCKS4a; SOCKS5; -->
            <type></type>
            <!-- Host name of proxy server. -->
            <host></host>
            <!-- Port number of proxy server. -->
            <port></port>
            <!-- User name, if applicable, to authenticate with proxy server. -->
            <user></user>
            <!-- Password, if applicable, to authenticate with proxy server. -->
            <password></password>

```

If you have enabled Easy Open on your account and you are using a proxy server, make sure that you configure the user credentials for the proxy server.

```

        </proxy>
    </proxies>
    <!-- Whether to add the message bar to the secure message (true) or not (false). -->
    <addressmessagebar>true</addressmessagebar>
    <address>
        <!-- Forwarding email address used for Mobile Device Support. -->
        <mobile>mobile@res.cisco.com</mobile>
    </address>
    <algorithms>
        <!-- Payload encryption algorithm to use when creating the
envelope. Valid values are: ARC4; ARC4-160; ARC4-256; AES; AES-128; AES-192; AES-256; -->
        <PayloadEnc>AES</PayloadEnc>
        <!-- Payload verification algorithm to use when creating the
envelope. Valid values are: CRC-32; SHA-1; SHA-256; -->
        <PayloadVer>SHA-256</PayloadVer>
        <!-- Key server key hash algorithm to use when creating the
envelope. Valid values are: plain; SHA-1; -->

```

```

        plain should only be used when the user is authenticated against an
        external repository, like an LDAP server, and the repository requires
        cleartext passwords; -->
        <KeyServerKeyHash>SHA-1</KeyServerKeyHash>
    </algorithms>
    <!--&#xa; Name of the envelope attachment file where ${date} and ${time}
    are replaced by the date and time&#xa; when the envelope was generated.&#xa; -->
    <attachmentname display="hidden">securedoc_${date}T${time}.html</attachmentname>
    <checkbox>
        <!--&#xa; Boolean indicating whether the checkbox for open offline
        should&#xa; be visible on the envelope (true) or not (false).&#xa; This
        feature is not visible in Outlook.&#xa; -->
        <openoffline>>false</openoffline>
        <!--&#xa; Boolean indicating whether the checkbox for remember user
        key&#xa; should be visible on the envelope (true) or not (false).&#xa;
        This feature is not visible in Outlook.&#xa; -->
        <rememberkey>>false</rememberkey>
        <!--&#xa; Boolean indicating whether the checkbox for remember envelope&#xa;
        key should be visible on the envelope (true) or not (false).&#xa; This
        feature is not visible in Outlook.&#xa; -->
        <rememberenvelopekey>>false</rememberenvelopekey>
        <!--&#xa; Boolean indicating whether the checkbox for remember me
        should&#xa; be visible on the envelope (true) or not (false).&#xa; -->
        <rememberme>>true</rememberme>
        <!--&#xa; Boolean indicating whether the checkbox for enable personal
        security&#xa; phrase should be visible on the envelope (true) or not (false).&#xa;
        -->
        <enablepsp>>false</enablepsp>
        The Enable Personal Security Phrase functionality is no longer supported for Encryption
        Service. Make sure that you always set the tag as false in the BCE_Config.xml file.
        <!--&#xa; Boolean indicating whether the checkbox for auto open should&#xa;
        be visible on the envelope (true) or not (false).&#xa; This feature is
        not visible in Outlook.&#xa; -->
        <autoopen>>false</autoopen>
    </checkbox>
    <date>
        <!--&#xa; Time format string when a reminder notification will be sent
        to&#xa; the recipient if the envelope has not been read.&#xa; Note: Cisco
        Secure Email Encryption Service does not support this feature.&#xa; Format
        Description&#xa; =====
        Relative time *&#xa; +d Relative time in days&#xa;
        s Absolute time in UTC milliseconds from the epoch *&#xa;
        0 No reminder notification&#xa; * Not supported on mobile
        devices&#xa; -->
        <readyby display="hidden">0</readyby>
        <!--&#xa; Time format string when the envelope will expire.&#xa;
        Format Description&#xa; =====
        +hh:mm:ss Relative time *&#xa; +d Relative time
        in days&#xa; s Absolute time in UTC milliseconds from the epoch
        *&#xa; 0 Never expires&#xa; * Not supported on
        mobile devices&#xa; -->
        <expiration display="editable">0</expiration>
    </date>
    <!-- Envelope profile to use. -->
    <envelopeprofilename>CRES</envelopeprofilename>
    <!-- Image profile to use. -->
    <imageProfileName>CRES</imageProfileName>
    <message>
        <!--&#xa; Sensitivity of the envelope. Acceptable levels are 0 to
        50.&#xa; For label, the values should be listed in the order they will be
        displayed.&#xa; For localization purposes, do not change or reword the existing
        sensitivity&#xa; labels Low | Medium | High.&#xa; -->
        <sensitivity label="Low=0&amp;Medium=10&amp;High=50"
        display="editable">50</sensitivity>

```

```

</message>
<messagebar>
  <!--&#xa;      If the message bar is enabled, show "Reply" button in the message
bar (true) or not (false).&#xa;      -->
  <replyenabled display="editable">true</replyenabled>
  <!--&#xa;      If the message bar is enabled, show "Reply to All" button in
the message bar (true) or not (false).&#xa;      -->
  <replyallenabled display="editable">true</replyallenabled>
  <!--&#xa;      If the message bar is enabled, show "Forward" button in the
message bar (true) or not (false).&#xa;      -->
  <forwardenabled display="editable">true</forwardenabled>
</messagebar>
  <!--&#xa;      Boolean indicating whether the envelope's payload should force the
applet to&#xa;      open the main document in the same window as the envelope. If set to
true,&#xa;      the applet opens the main document in the window it's running in, but as
a&#xa;      consequence can't delete the files in the payload when shutting down,
leaving&#xa;      decrypted files on disk. It does, however, avoid pop-up blockers, as no
new&#xa;      window is being opened.&#xa;      -->
  <openinsamewindow>true</openinsamewindow>
  <!--&#xa;      Whether a return receipt email should be sent when the recipient opens
the email (true) or not (false).&#xa;      -->
  <sendreturnreceipt display="editable">>false</sendreturnreceipt>
  <show>
    <recipient>
      <!--&#xa;      Boolean that determines if the envelope will show a
dropdown&#xa;      menu of recipients for Registered Envelopes. If true, the
dropdown&#xa;      menu will be shown, otherwise the unique recipient of the
message&#xa;      will be embedded in the envelope to make the menu unnecessary.&#xa;
      If there is more than one recipient for this message then this&#xa;
value will be ignored.&#xa;      -->
      <menu>true</menu>
    </recipient>
  </show>
  <!--&#xa;      Boolean indicating whether the envelope's payload should suppress opening
with the&#xa;      applet. If set to true, opening an envelope with a multi-file payload
uses the online&#xa;      opener instead of the applet.&#xa;      -->
  <suppressappletforopen>true</suppressappletforopen>
</encryption>

```

翻訳について

このドキュメントは、米国シスコ発行ドキュメントの参考和訳です。リンク情報につきましては、日本語版掲載時点で、英語版にアップデートがあり、リンク先のページが移動/変更されている場合がありますことをご了承ください。あくまでも参考和訳となりますので、正式な内容については米国サイトのドキュメントを参照ください。