
Symbols

- # character (privileged EXEC mode prompt) [5](#)
- \$ character [8, 10](#)
- * (asterisk) [7](#)
- + (plus sign) [7](#)
- . (period) [7](#)
- ? command [1](#)
- ^ (caret) [8, 10](#)
- _ (underscore) [8, 10](#)
- | (pipe or vertical bar)
 - specifying alternative patterns [10](#)

Numerics

- 802.3ad
 - See LACP

A

- abbreviating commands
 - context-sensitive help [1](#)
- access control lists
 - See ACLs
- acronyms, list of [1](#)
- Address Resolution Protocol
 - See ARP
- audience [7](#)

B

- bidirectional PIM
 - See BIDIR
- binary decision diagrams
 - See BDD
- Border Gateway Protocol
 - See BGP
- bridge protocol data unit

See BPDU

C

- CAs
 - exporting
 - PEM [5](#)
 - importing
 - PEM [5](#)
- certificate authority pool
 - entering
 - configuration submode [70](#)
- certificate authority pool configuration submode
 - entering [70](#)
- Cisco Express Forwarding
 - See CEF
- CLI
 - string search
 - alternation [10](#)
 - anchoring [10](#)
 - expressions [7](#)
 - filtering [7](#)
 - multiple-character patterns [9](#)
 - multipliers [9](#)
 - parentheses for recall [11](#)
 - searching outputs [7](#)
 - single-character patterns [7](#)
 - using [7](#)
 - command-line interface
 - See CLI
 - command modes
 - accessing [5](#)
 - exiting [5](#)
 - understanding [5](#)
 - commands
 - mode types [5](#)
 - committed information rate
 - See CIR
 - Content Switching Module

See CSM

D

default form of a command, using [6](#)

designated forwarder

See DF

Distributed Forwarding Card

See DFC

documentation

conventions [8](#)

organization [7](#)

dot1q

See also 802.1Q tunneling

dot1x

See 802.1x

E

Enhanced Address Recognition Logic

See EARL

Ethernet over Multiprotocol Label Switching

See EoMPLS

EXEC-level commands

issuing in other modes [20](#)

expressions

matching multiple expression occurrences [9](#)

multiple-character patterns [9](#)

multiplying pattern occurrence [11](#)

single-character patterns [7](#)

specifying alternative patterns [10](#)

F

fast software upgrade

See FSU

feature interaction engine

See FIE

field-replaceable unit

See FRU

file system consistency check

See fsck utility

Firewall Services Module

See FWSM

fm

See feature manager

G

global configuration mode, summary [5](#)

H

Hot Standby Router Protocol

See HSRP

HSRP

configuring

initialization delay period [84](#)

MAC address [88](#)

preemption delay [92](#)

priority [94](#)

virtual MAC address [88](#)

disabling

filtering of ICMP redirect messages [95](#)

HSRP

configuring

secondary interface [86](#)

initialization delay period [84](#)

enabling [86](#)

filtering of ICMP redirect messages [95](#)

ICMP redirect messages

disabling [95](#)

enabling [95](#)

MAC address

configuring [88](#)

preemption delay

configuring [92](#)

- restoring default [92](#)
- priority
 - configuring [94](#)
- restoring
 - preemption delay default [92](#)
- virtual MAC address
 - configuring [88](#)
- HSRP (Hot Standby Router Protocol)
 - burned-in address [101](#)
 - MAC refresh interval [90](#)
 - password, configuring [83](#)
 - timers, setting [97](#)
- HTTP header
 - configuring
 - policy [58](#)
 - displaying
 - policy information [34](#)
 - entering
 - insertion configuration submode [58](#)

- inter-card communication
 - See ICC
- interface configuration mode
 - summary [6](#)
 - table defining modes [6](#)
- intermediate system-to-intermediate system
 - See IS-IS
- Internet Group Management Protocol
 - See IGMP
- Internetwork Packet Exchange
 - See IPX
- interprocessor communication
 - See IPC
- Inter-Switch Link VLANs
 - See ISL VLANs

L

- Link Aggregation Control Protocol
 - See LACP

M

- maintenance loop signaling entity
 - See MLSE
- MDSS
 - Multicast Distributed Shortcut Switching
- Media Access Control
 - See MAC address table
- message digest 5
 - See MD5
- message-of-the-day
 - See MOTD
- MLSM
 - multilayer switching for multicast
- modes
 - See command modes
- more commands
 - filter [7](#)
 - search [7](#)
- More-- prompt [7](#)
 - filter [7](#)
 - search [7](#)
- Multilayer Switch Feature Card
 - See MSFC
- Multilayer Switching
 - See MLS
- multiple-character patterns [9](#)
- Multiple Spanning Tree
 - See MST
- Multiprotocol Label Switching
 - See MPLS

N

NetFlow Data Export

See NDE

network entity title

See NET

no form of a command, using [6](#)

O

order-dependent merge algorithm

See ODD

P

paging prompt

see --More-- prompt

per-VLAN spanning tree

See PVST+

pipe symbol

specifying alternative patterns [10](#)

PKI event history

clearing the memory [56](#)disabling [56](#)enabling [56](#)

policy-service configuration submode

entering [71](#)

privacy-enhanced mail

See PEM

private VLANs

See PVLANS

privileged EXEC mode, summary [5](#)

prompts

system [5](#)

Protocol Independent Multicast

See PIM

proxy policy

displaying

configured HTTP header information [34](#)configured SSL information [34](#)configured TCP information [34](#)configured URL rewrite information [34](#)

Q

Q-in-Q

802.1Q in 802.1Q

See 802.1Q tunneling

QoS Device Manager

See QDM

question command [1](#)

R

Rapid Spanning Tree Protocol

See RSTP

Rapid Spanning Tree Protocol+

See RSTP+

related documentation [7](#)

remote procedure call

See RPC

remote SPAN

See RSPAN

Reverse Path Forwarding

See RPF

RFC 2281, Cisco Hot Standby Router Protocol (HSRP) [88](#)

ROM monitor mode,

summary [6](#)

Route Processor Redundancy

See RPR

Route Processor Redundancy+

See RPR+

S

Secure Sockets Layer

See SSL

server load balancing
 See SLB

show commands
 filter [7](#)
 search [7](#)

single-character patterns
 special characters, table [7](#)

source specific multicast
 See SSM

special characters
 anchoring, table [10](#)

SP QoS manager
 See QM-SP

SSL policy
 configuring [58](#)
 defining
 HTTP header insertion content policy [58](#)
 SSL policy [60](#)
 TCP policy templates [64](#)
 defining URL rewrite policy [68](#)
 entering
 configuration submode [58](#)
 HTTP header configuration submode [58](#)
 SSL configuration submode [60](#)
 TCP configuration submode [64](#)

ssl pre-remove-http-hdr [51](#)

SSL proxy
 enabling
 certificate expiring notification traps [50](#)
 enabling operation status notification traps [50](#)

ssl-proxy device-check [53](#)

standby authentication command [83](#)

standby mac-address command [88](#)

standby mac-refresh command [90](#)

standby timers command [97](#)

standby track command [99](#)

standby use-bia command [101](#)

subinterface configuration mode, summary [6](#)

Switch-Module Configuration Protocol

 See SCP

system prompts [5](#)

T

Tab key
 command completion [1](#)

table contention level
 See TCL

tables
 characters with special meaning [7](#)
 special characters
 multipliers, table [9](#)
 used for anchoring [10](#)

TCP
 displaying
 policy information [34](#)

TCP configuration
 defining policy [64](#)
 entering submode [64](#)

Ternary Content Addressable Memory
 See TCAM

U

URL rewrite
 defining
 content policy [68](#)
 displaying
 policy information [34](#)
 entering
 configuration submode [68](#)

user EXEC mode, summary [5](#)

V

value mask result
 See VMR

virtual MAC address [88](#)

VLAN access control lists

See VACL

VMR

acronym for value mask result

W

Web Cache Coprocessor Protocol

See WCCP

weighted random early detection

See WRED

weighted round robin

See WRR