



Flexible NetFlow Ingress support

Last Updated: November 16, 2012

The Flexible NetFlow Ingress support feature supports the monitoring of traffic that a router is receiving on an interface or sub interface.

- [Finding Feature Information, page 1](#)
- [Information About Flexible NetFlow Ingress support , page 1](#)
- [Additional References, page 2](#)
- [Feature Information for Flexible NetFlow—Ingress support , page 2](#)

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest caveats and feature information, see [Bug Search Tool](#) and the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the feature information table at the end of this module.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Information About Flexible NetFlow Ingress support

- [Flexible NetFlow Ingress support Overview, page 1](#)

Flexible NetFlow Ingress support Overview

The Flexible NetFlow Ingress support feature supports the monitoring of traffic that a device is receiving on an interface or subinterface.

The feature is enabled by applying a flow monitor in input (ingress) mode on the receiving device.

If you configure a Flexible NetFlow exporter for the flow monitors you use for the Flexible NetFlow-Ingress support feature, the receiving device will export the captured flows to the configured collector devices in the provider network.



Americas Headquarters:
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

Additional References

Related Documents

Related Topic	Document Title
Cisco IOS commands	Cisco IOS Master Command List, All Releases
Flexible NetFlow conceptual information and configuration tasks	<i>Flexible NetFlow Configuration Guide</i>
Flexible NetFlow commands	<i>Cisco IOS Flexible NetFlow Command Reference</i>

Standards/RFCs

Standard	Title
No new or modified standards/RFCs are supported by this feature.	—

MIBs

MIB	MIBs Link
None	To locate and download MIBs for selected platforms, Cisco software releases, and feature sets, use Cisco MIB Locator found at the following URL: http://www.cisco.com/go/mibs

Technical Assistance

Description	Link
The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.	http://www.cisco.com/cisco/web/support/index.html

Feature Information for Flexible NetFlow—Ingress support

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software

release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Table 1 **Feature Information for Flexible NetFlow—Ingress support**

Feature Name	Releases	Feature Information
Flexible NetFlow—Ingress support	Cisco IOS XE Release 3.1S Cisco IOS XE Release 3.2SE	Monitors traffic that a router is receiving on an interface or subinterface. No commands were introduced or modified by this feature.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

© 2010-2012 Cisco Systems, Inc. All rights reserved.