



HTTP Services Configuration Guide, Cisco IOS Release 15M&T

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
<http://www.cisco.com>
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 527-0883

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <http://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

© 2014 Cisco Systems, Inc. All rights reserved.



CONTENTS

CHAPTER 1

HTTP 1.1 Web Server and Client 1

Finding Feature Information 1

Information About the HTTP 1.1 Web Server and Client 1

 About HTTP Server General Access Policies 2

How to Configure HTTP 1.1 Web Server and Client 3

 Configuring the HTTP 1.1 Web Server 3

 Configuring the HTTP Client 5

 Verifying HTTP Connectivity 7

Configuration Examples for HTTP 1.1 Web Server 8

 Configuring the HTTP 1.1 Web Server Example 8

Where to Go Next 8

Additional References 8

Feature Information for the HTTP 1.1 Web Server and Client 10

CHAPTER 2

HTTPS--HTTP Server and Client with SSL 3.0 13

Finding Feature Information 13

Information About HTTPS--HTTP Server and Client with SSL 3.0 13

 Secure HTTP Server and Secure HTTP Client 14

 Certificate Authority Trustpoints 14

 CipherSuites 14

How to Configure the HTTPS--HTTP Server and Client with SSL 3.0 15

 Declaring a Certificate Authority Trustpoint 15

 Configuring the HTTPS Server with SSL 3.0 18

 Verifying the Configuration of the HTTPS Server 21

 Providing Additional Security and Efficiency 21

 Configuring the HTTPS Client with SSL 3.0 23

Configuration Examples for the HTTPS--HTTP Server and Client with SSL 3.0 feature 25

Additional References 26

Feature Information for HTTPS--HTTP Server and Client with SSL 3.0 27

Glossary 29

CHAPTER 3

HTTP Client API for Tcl IVR 31

Finding Feature Information 31

Prerequisites for HTTP Client API for Tcl IVR and New Cisco Voice Application

Command-Line Interface Structure 31

Restrictions for HTTP Client API for Tcl IVR and New Cisco Voice Application Command-Line

Interface Structure 32

Information About HTTP Client API for Tcl IVR and New Cisco Voice Application

Command-Line Interface Structure 32

HTTP API for Tcl IVR 2.0 32

Newly-Supported Tcl 8.3.4 Commands 32

New Cisco Voice Application Command-Line Interface Structure 33

Feature Information for HTTP Client API for Tcl IVR 33

CHAPTER 4

HTTP Inspection Engine 35

Finding Feature Information 35

Restrictions for HTTP Inspection Engine 36

Information About HTTP Inspection Engine 36

What Is a Security Policy 36

Cisco IOS HTTP Application Policy Overview 36

How to Define and Apply an HTTP Application Policy to a Firewall for Inspection 36

Defining an HTTP Application Policy 36

What to Do Next 40

Applying an HTTP Application Policy to a Firewall for Inspection 40

Troubleshooting Tips 43

Configuration Examples for Setting Up an HTTP Inspection Engine 43

Setting Up and Verifying an HTTP Inspection Engine Example 43

Additional References 44

CHAPTER 5

Selective Enabling of Applications Using an HTTP or HTTPS Server 47

Finding Feature Information 47

Information About Selective Enabling of Applications Using an HTTP or HTTPS Server 48

Selective Enabling of Applications Within the HTTP and HTTPS Infrastructure 48

How to Enable Selected Applications Using an HTTP or HTTPS Server	48
Enabling Selected HTTP Applications	48
Enabling Selected HTTPS Applications	50
Configuration Examples for Selective Enabling of Applications Using an HTTP or HTTPS Server	51
Example: Enabling Selected HTTP and HTTPS Applications	51
Example: Verifying HTTP and HTTPS Applications	51
Additional References for Selective Enabling of Applications Using an HTTP or HTTPS Server	52
Feature Information for Selective Enabling of Applications Using an HTTP or HTTPS Server	53



CHAPTER

1

HTTP 1.1 Web Server and Client

The HTTP 1.1 Web Server and Client feature provides a consistent interface for users and applications by implementing support for HTTP 1.1 in Cisco IOS XE software-based devices. When combined with the HTTPS feature, the HTTP 1.1 Web Server and Client feature provides a complete, secure solution for HTTP services between Cisco devices.

This module describes the concepts and the tasks related to configuring the HTTP 1.1 Web Server and Client feature.

- [Finding Feature Information, page 1](#)
- [Information About the HTTP 1.1 Web Server and Client, page 1](#)
- [How to Configure HTTP 1.1 Web Server and Client, page 3](#)
- [Configuration Examples for HTTP 1.1 Web Server, page 8](#)
- [Where to Go Next, page 8](#)
- [Additional References, page 8](#)
- [Feature Information for the HTTP 1.1 Web Server and Client, page 10](#)

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest caveats and feature information, see [Bug Search Tool](#) and the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the feature information table at the end of this module.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Information About the HTTP 1.1 Web Server and Client

This feature updates the Cisco implementation of the Hypertext Transfer Protocol (HTTP) from 1.0 to 1.1. The HTTP server allows features and applications, such as the Cisco web browser user interface, to be run on your routing device.

The Cisco implementation of HTTP 1.1 is backward-compatible with previous Cisco IOS XE releases. If you are currently using configurations that enable the HTTP server, no configuration changes are needed, as all defaults remain the same.

The process of enabling and configuring the HTTP server also remains the same as in previous releases. Support for Server Side Includes (SSIs) and HTML forms has not changed. Additional configuration options, in the form of the **ip http timeout-policy** command and the **ip http max-connections** command, have been added. These options allow configurable resource limits for the HTTP server. If you do not use these optional commands, the default policies are used.

Remote applications may require that you enable the HTTP server before using them. Applications that use the HTTP server include:

- Cisco web browser user interface, which uses the Cisco IOS XE Homepage Server, HTTP-based EXEC Server, and HTTP IOS File System (IFS) Server
- VPN Device Manager (VDM) application, which uses the VDM Server and the XML Session Manager (XSM)
- QoS Device Manager (QDM) application, which uses the QDM Server
- IP Phone and Cisco IOS XE Telephony Service applications, which use the ITS Local Directory Search and IOS Telephony Server (ITS)

About HTTP Server General Access Policies

The **ip http timeout-policy** command allows you to specify general access characteristics for the server by configuring a value for idle time, connection life, and request maximum. By adjusting these values you can configure a general policy; for example, if you want to maximize throughput for HTTP connections, you should configure a policy that minimizes connection overhead. You can configure this type of policy by specifying large values for the **life** and **request** options so that each connection stays open longer and more requests are processed for each connection.

Another example would be to configure a policy that minimizes the response time for new connections. You can configure this type of policy by specifying small values for the **life** and **request** options so that the connections are quickly released to serve new clients.

A throughput policy would be better for HTTP sessions with dedicated management applications, as it would allow the application to send more requests before the connection is closed, while a response time policy would be better for interactive HTTP sessions, as it would allow more people to connect to the server at the same time without having to wait for connections to become available.

In general, you should configure these options as appropriate for your environment. The value for the **idle** option should be balanced so that it is large enough not to cause an unwanted request or response timeout on the connection, but small enough that it does not hold a connection open longer than necessary.

Access security policies for the HTTP server are configured using the **ip http authentication** command, which allows only selective users to access the server, the **ip http access-class** command, which allows only selective IP hosts to access the server, and the **ip http accounting commands** command, which specifies a particular command accounting method for HTTP server users.

How to Configure HTTP 1.1 Web Server and Client

Configuring the HTTP 1.1 Web Server

Perform this task to enable the HTTP server and configure optional server characteristics. The HTTP server is disabled by default.



Note

If you want to configure authentication (step 4), you must configure the authentication type before you begin configuring the HTTP 1.1 web server.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip http server**
4. **ip http authentication** {aaa | enable | local | tacacs}
5. **ip http accounting commands** level {default | named-accounting-method-list}
6. **ip http port** port-number
7. **ip http path** url
8. **ip http access-class** access-list-number
9. **ip http max-connections** value
10. **ip http timeout-policy** idle seconds life seconds requests value

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2	configure terminal Example: Router# configure terminal	Enters global configuration mode.
Step 3	ip http server Example: Router(config)# ip http server	Enables the HTTP 1.1 server, including the Cisco web browser user interface. Note If you are enabling the HTTP over Secure Socket Layer (HTTPS) server using the ip http secure-server command, you should disable the standard HTTP server using the no ip http server command. This command is required to ensure only secure connections to the server.

	Command or Action	Purpose
Step 4	<p>ip http authentication {aaa enable local tacacs}</p> <p>Example:</p> <pre>Router(config)# ip http authentication local</pre>	<p>(Optional) Specifies the authentication method to be used for login when a client connects to the HTTP server. The methods for authentication are:</p> <ul style="list-style-type: none"> • aaa --Indicates that the authentication method used for the AAA login service (specified by the aaa authentication login default command) should be used for authentication. • enable --Indicates that the “enable” password should be used for authentication. (This is the default method.) • local --Indicates that the login user name, password and privilege level access combination specified in the local system configuration (by the username global configuration command) should be used for authentication and authorization. • tacacs --Indicates that the TACACS (or XTACACS) server should be used for authentication.
Step 5	<p>ip http accounting commands level {default named-accounting-method-list}</p> <p>Example:</p> <pre>Router(config)# ip http accounting commands 15 default</pre>	<p>(Optional) Specifies a particular command accounting method for HTTP server users. Command accounting for HTTP and HTTPS is automatically enabled when authentication, authorization, and accounting (AAA) is configured on the device. It is not possible to disable accounting for HTTP and HTTPS. HTTP and HTTPS will default to using the global AAA default method list for accounting. The CLI can be used to configure HTTP and HTTPS to use any predefined AAA method list.</p> <ul style="list-style-type: none"> • level --Valid privilege level entries are integers from 0 to 15. • default --Indicates the default accounting method list configured by the aaa accounting commands CLI. • named-accounting-method-list --Indicates the name of the predefined command accounting method list.
Step 6	<p>ip http port port-number</p> <p>Example:</p> <pre>Router(config)# ip http port 8080</pre>	<p>(Optional) Specifies the server port that should be used for HTTP communication (for example, for the Cisco web browser user interface).</p>
Step 7	<p>ip http path url</p> <p>Example:</p> <pre>Router(config)# ip http path slot1:</pre>	<p>(Optional) Sets the base HTTP path for HTML files. The base path is used to specify the location of the HTTP server files (HTML files) on the local system. Generally, the HTML files are located in system flash memory.</p>

	Command or Action	Purpose
Step 8	<p>ip http access-class <i>access-list-number</i></p> <p>Example:</p> <pre>Router(config)# ip http access-class 20</pre>	(Optional) Specifies the access list that should be used to allow access to the HTTP server.
Step 9	<p>ip http max-connections <i>value</i></p> <p>Example:</p> <pre>Router(config)# ip http max-connections 10</pre>	(Optional) Sets the maximum number of concurrent connections to the HTTP sever that will be allowed. The default value is 5.
Step 10	<p>ip http timeout-policy idle <i>seconds life seconds requests</i> <i>value</i></p> <p>Example:</p> <pre>Router(config)# ip http timeout-policy idle 30 life 120 requests 100</pre>	<p>(Optional) Sets the characteristics that determine how long a connection to the HTTP server should remain open. The characteristics are:</p> <ul style="list-style-type: none"> • idle --The maximum number of seconds the connection will be kept open if no data is received or response data cannot be sent out on the connection. Note that a new value may not take effect on any already existing connections. If the server is too busy or the limit on the life time or the number of requests is reached, the connection may be closed sooner. The default value is 180 seconds (3 minutes). • life --The maximum number of seconds the connection will be kept open, from the time the connection is established. Note that the new value may not take effect on any already existing connections. If the server is too busy or the limit on the idle time or the number of requests is reached, it may close the connection sooner. Also, since the server will not close the connection while actively processing a request, the connection may remain open longer than the specified life time if processing is occurring when the life maximum is reached. In this case, the connection will be closed when processing finishes. The default value is 180 seconds (3 minutes). The maximum value is 86400 seconds (24 hours). • requests --The maximum limit on the number of requests processed on a persistent connection before it is closed. Note that the new value may not take effect on already existing connections. If the server is too busy or the limit on the idle time or the life time is reached, the connection may be closed before the maximum number of requests are processed. The default value is 1. The maximum value is 86400.

Configuring the HTTP Client

Perform this task to enable the HTTP client and configure optional client characteristics.

The standard HTTP 1.1 client and the secure HTTP client are always enabled. No commands exist to disable the HTTP client. For information about configuring optional characteristics for the HTTPS client, see the HTTPS--HTTP Server and Client with SSL 3.0 feature module.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip http client cache** {ager interval *minutes* | memory {file *file-size-limit* | pool *pool-size-limit*}
4. **ip http client connection** {forceclose | idle timeout *seconds* | retry count | timeout *seconds*}
5. **ip http client password** *password*
6. **ip http client proxy-server** *proxy-name* **proxy-port** *port-number*
7. **ip http client response timeout** *seconds*
8. **ip http client source-interface** *type number*
9. **ip http client username** *username*

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: Router> enable	Enables privileged EXEC mode. • Enter your password if prompted.
Step 2	configure terminal Example: Router# configure terminal	Enters global configuration mode.
Step 3	ip http client cache {ager interval <i>minutes</i> memory {file <i>file-size-limit</i> pool <i>pool-size-limit</i> }	Configures HTTP client cache.
	Example: Router(config)# ip http client cache memory file 5	
Step 4	ip http client connection {forceclose idle timeout <i>seconds</i> retry count timeout <i>seconds</i> }	Configures an HTTP client connection.
	Example: Router(config)# ip http client connection timeout 10	
Step 5	ip http client password <i>password</i>	Configures the default password used for connections to remote HTTP servers.
	Example: Router(config)# ip http client password pswd1	

	Command or Action	Purpose
Step 6	<p>ip http client proxy-server <i>proxy-name</i> proxy-port <i>port-number</i></p> <p>Example:</p> <pre>Router(config)# ip http client proxy-server server1 proxy-port 52</pre>	Configures an HTTP proxy server.
Step 7	<p>ip http client response timeout <i>seconds</i></p> <p>Example:</p> <pre>Router(config)# ip http client response timeout 60</pre>	Specifies the timeout value, in seconds, that the HTTP client waits for a response from the server.
Step 8	<p>ip http client source-interface <i>type number</i></p> <p>Example:</p> <pre>Router(config)# ip http client source-interface ethernet1/0</pre>	Configures a source interface for the HTTP client.
Step 9	<p>ip http client username <i>username</i></p> <p>Example:</p> <pre>Router(config)# ip http client user1</pre>	Configures the default username used for connections to remote HTTP servers.

Verifying HTTP Connectivity

To verify remote connectivity to the HTTP server, enter the system IP address in a web browser, followed by a colon and the appropriate port number (80 is the default port number).

For example, if the system IP address is 209.165.202.129 and the port number is 8080, enter `http://209.165.202.129:8080` as the URL in a web browser.

If HTTP authentication is configured, a login dialog box will appear. Enter the appropriate username and password. If the default login authentication method of “enable” is configured, you may leave the username field blank, and use the “enable” password to log in.

The system home page should appear in your browser.

Configuration Examples for HTTP 1.1 Web Server

Configuring the HTTP 1.1 Web Server Example

The following example shows a typical configuration that enables the server and sets some of the characteristics:

```
ip http server
ip http authentication aaa
ip http accounting commands 15 default
ip http path flash:
ip access-list standard 20
 permit 209.165.202.130 0.0.0.255
 permit 209.165.201.1 0.0.255.255
 permit 209.165.200.225 0.255.255.255
! (Note: all other access implicitly denied)
end
ip http access-class 10
ip http max-connections 10
ip http accounting commands 1 oneacct
```

In the following example, a Throughput timeout policy is applied. This configuration would allow each connection to be idle a maximum of 30 seconds (approximately). Each connection will remain open (be “alive”) until either the HTTP server has been busy processing requests for approximately 2 minutes (120 seconds) or until approximately 100 requests have been processed.

```
ip http timeout-policy idle 30 life 120 requests 100
```

In the following example, a Response Time timeout policy is applied. This configuration would allow each connection to be idle a maximum of 30 seconds (approximately). Each connection will be closed as soon as the first request has been processed.

```
ip http timeout-policy idle 30 life 30 requests 1
```

Where to Go Next

For information about secure HTTP connections using Secure Sockets Layer (SSL) 3.0, refer to the HTTPS--HTTP with SSL 3.0 feature module at:

http://www.cisco.com/en/US/docs/ios/12_2t/12_2t15/feature/guide/ftsslsh.html

Additional References

Related Documents

Related Topic	Document Title
Cisco IOS commands	Cisco IOS Master Commands List, All Releases
HTTP commands: complete command syntax, command mode, command history, defaults, usage guidelines, and examples	Cisco IOS HTTP Services Command Reference

Related Topic	Document Title
HTTPS	<ul style="list-style-type: none"> • HTTPS--HTTP with SSL 3.0 feature module • Firewall Support of HTTPS Authentication Proxy feature module

Standards and RFCs

Standard/RFC	Title
No specific standards are supported by this feature. Note that HTTP 1.1, as defined in RFC 2616, is currently classified as a “Standards Track” document by the IETF.	—
RFC 2616	<i>Hypertext Transfer Protocol -- HTTP/1.1</i>

The Cisco implementation of the HTTP Version 1.1 supports a subset of elements defined in RFC 2616. Following is a list of supported RFC 2616 headers:

- Allow (Only GET, HEAD, and POST methods are supported)
- Authorization, WWW-Authenticate - Basic authentication only
- Cache-control
- Chunked Transfer Encoding
- Connection close
- Content-Encoding
- Content-Language
- Content-Length
- Content-Type
- Date, Expires
- Location

MIBs

MIB	MIBs Link
<ul style="list-style-type: none"> • No specific MIBs are supported for this feature. 	<p>To locate and download MIBs for selected platforms, Cisco software releases, and feature sets, use Cisco MIB Locator found at the following URL:</p> <p>http://www.cisco.com/go/mibs</p>

Technical Assistance

Description	Link
The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.	http://www.cisco.com/cisco/web/support/index.html

Feature Information for the HTTP 1.1 Web Server and Client

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Table 1: Feature Information for HTTP 1.1 Web Server and Client

Feature Name	Releases	Feature Information
HTTP 1.1 Web Server and Client	Cisco IOS XE Release 2.1	<p>The HTTP 1.1 Web Server and Client feature provides a consistent interface for users and applications by implementing support for HTTP 1.1 in Cisco IOS XE software-based devices. When combined with the HTTPS feature, the HTTP 1.1 Web Server and Client feature provides a complete, secure solution for HTTP services between Cisco devices.</p> <p>The following commands were introduced or modified by this feature: debug ip http all, debug ip http client, ip http access-class, ip http authentication, ip http client cache, ip http client connection, ip http client password, ip http client proxy-server, ip http client response timeout, ip http client source-interface, ip http client username, ip http max-connections, ip http path, ip http port, ip http server, ip http timeout-policy, show ip http client, show ip http client connection, show ip http client history, show ip http session-module, show ip http server, show ip http server secure status.</p>

Feature Name	Releases	Feature Information
HTTP TACAC+ Accounting Support	Cisco IOS XE Release 2.1	<p>The HTTP TACAC+ Accounting Support feature introduces the ip http accounting commands command. This command is used to specify a particular command accounting method for HTTP server users. Command accounting provides information about the commands for a specified privilege level that are being executed on a device. Each command accounting record corresponds to one IOS XE command executed at its respective privilege level, as well as the date and time the command was executed, and the user who executed it. The following sections provide information about this feature:</p> <p>The following commands were introduced or modified by this feature: ip http accounting commands.</p>
HTTP Security	Cisco IOS XE Release 2.1	This feature was introduced on Cisco ASR 1000 Series Routers.



HTTPS--HTTP Server and Client with SSL 3.0

The HTTPS--HTTP Server and Client with SSL 3.0 feature provides Secure Socket Layer (SSL) version 3.0 support for the HTTP 1.1 server and HTTP 1.1 client within Cisco IOS XE software. SSL provides server authentication, encryption, and message integrity to allow secure HTTP communications. SSL also provides HTTP client authentication. HTTP over SSL is abbreviated as HTTPS.

- [Finding Feature Information, page 13](#)
- [Information About HTTPS--HTTP Server and Client with SSL 3.0, page 13](#)
- [How to Configure the HTTPS--HTTP Server and Client with SSL 3.0, page 15](#)
- [Configuration Examples for the HTTPS--HTTP Server and Client with SSL 3.0 feature, page 25](#)
- [Additional References, page 26](#)
- [Feature Information for HTTPS--HTTP Server and Client with SSL 3.0, page 27](#)
- [Glossary, page 29](#)

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest caveats and feature information, see [Bug Search Tool](#) and the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the feature information table at the end of this module.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Information About HTTPS--HTTP Server and Client with SSL 3.0

To configure the HTTP with SSL 3.0 (HTTPS) feature, you should understand the following concepts:

Secure HTTP Server and Secure HTTP Client

A secure HTTP connection means that data sent to and received from an HTTP server are encrypted before being sent out over the Internet. HTTP with SSL encryption provides a secure connection to allow such functions as configuring a router from a web browser. Cisco's implementation of the secure HTTP server and secure HTTP client uses an implementation of the SSL version 3.0. Application layer encryption provides an alternative to older methods such as having to set up a tunnel to the HTTP server for remote management. HTTP over SSL is abbreviated as HTTPS; the URL of a secure connection will begin with https:// instead of http://.

The Cisco IOS XE HTTP secure server's primary role is to listen for HTTPS requests on a designated port (the default HTTPS port is 443) and to pass the request to the HTTP 1.1 web server. The HTTP 1.1 server processes requests and passes responses (served pages) back to the HTTP secure server, which, in turn, responds to the original request.

The Cisco IOS XE HTTP secure client's primary role is to respond to Cisco IOS XE application requests for HTTPS User Agent services, perform HTTPS User Agent services on the application's behalf, and pass the response back to the application.

Certificate Authority Trustpoints

Certificate authorities (CAs) are responsible for managing certificate requests and issuing certificates to participating IPsec network devices. These services provide centralized security key and certificate management for the participating devices. Specific CA servers are referred to as "trustpoints."

The HTTPS server provides a secure connection by providing a certified X.509v3 certificate to the client when a connection attempt is made. The certified X.509v3 certificate is obtained from a specified CA trustpoint. The client (usually a web browser), in turn, has a public key that allows it to authenticate the certificate.

Configuring a CA trustpoint is highly recommended for secure HTTP connections. However, if a CA trustpoint is not configured for the routing device running the HTTPS server, the server will certify itself and generate the needed RSA key pair. Because a self-certified (self-signed) certificate does not provide adequate security, the connecting client will generate a notification that the certificate is self-certified, and the user will have the opportunity to accept or reject the connection. This option is available for internal network topologies (such as testing).

The HTTPS--HTTP Server and Client with SSL 3.0 feature also provides an optional command (**ip http secure-client-auth**) that, when enabled, has the HTTPS server request an X.509v3 certificate from the client. Authenticating the client provides more security than server authentication by itself.

For additional information on certificate authorities, see the "Configuring Certification Authority Interoperability" chapter in the Cisco IOS XE Security Configuration Guide .

CipherSuites

A CipherSuite specifies the encryption algorithm and digest algorithm to use on an SSL connection. Web browsers offer a list of supported CipherSuites when connecting to the HTTPS server, and the client and server will negotiate the best encryption algorithm to use from those that are supported by both. For example, Netscape Communicator 4.76 supports U.S. security with RSA Public Key Cryptography, MD2, MD5, RC2-CBC, RC4, DES-CBC, and DES-EDE3-CBC.

For the best possible encryption, you should use a browser that supports 128-bit encryption, such as Microsoft Internet Explorer version 5.5 (or later), or Netscape Communicator version 4.76 (or later). The SSL_RSA_WITH_DES_CBC_SHA CipherSuite provides less security than the other CipherSuites, because it does not offer 128-bit encryption.

In terms of router processing load (speed), the following list ranks the CipherSuites from fastest to slowest (slightly more processing time is required for the more secure and more complex CipherSuites):

- 1 SSL_RSA_WITH_DES_CBC_SHA
- 2 SSL_RSA_WITH_RC4_128_MD5
- 3 SSL_RSA_WITH_RC4_128_SHA
- 4 SSL_RSA_WITH_3DES_EDE_CBC_SHA

How to Configure the HTTPS--HTTP Server and Client with SSL 3.0

Declaring a Certificate Authority Trustpoint

Configuring a CA trustpoint is highly recommended for secure HTTP connections. The certified X.509v3 certificate for the secure HTTP server (or client) is obtained from the specified CA trustpoint. If you do not declare a CA trustpoint, then a self-signed certificate will be used for secure HTTP connections. The self-signed certificate is generated automatically.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **hostname *name***
4. **ip domain-name *name***
5. **crypto key generate rsa usage-keys**
6. **crypto ca trustpoint *name***
7. **enrollment url *url***
8. **enrollment http-proxy *host-name port-number***
9. **crl {query *url* | optional | best-effort}**
10. **primary**
11. **exit**
12. **crypto ca authenticate *name***
13. **crypto ca enrollment *name***
14. Do one of the following:
 - **copy running-config startup-config**
 -
 - **copy system:running-config nvram:startup-config**

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2	configure terminal Example: Router# configure terminal	Enters global configuration mode.
Step 3	hostname <i>name</i> Example: Router(config)# hostname Router	Specifies the hostname of the router. <ul style="list-style-type: none"> • This step is needed only if you have not previously configured a hostname for your router. The hostname is required because a fully qualified domain name is needed for security keys and certificates.
Step 4	ip domain-name <i>name</i>	Specifies the IP domain name of the router.

	Command or Action	Purpose
	<p>Example:</p> <pre>Router(config)# ip domain-name example.com</pre>	<ul style="list-style-type: none"> This step is needed only if you have not previously configured an IP domain name for your router. The domain name is required because a fully qualified domain name is needed for security keys and certificates.
Step 5	<p>crypto key generate rsa usage-keys</p> <p>Example:</p> <pre>Router(config)# crypto key generate rsa usage-keys</pre>	<p>(Optional) Generates an RSA key pair.</p> <ul style="list-style-type: none"> The usage-keys keyword specifies that two RSA special-usage key pairs should be generated (that is, one encryption pair and one signature pair) instead of one general-purpose key pair. RSA key pairs are used to sign and encrypt Internet key exchange (IKE) key management messages and are required before you can obtain a certificate for your router. RSA key pairs are generated automatically. This command can be used to regenerate the keys, if needed. <p>Note There are other keywords and arguments for this command, but they do not pertain to this feature.</p>
Step 6	<p>crypto ca trustpoint name</p> <p>Example:</p> <pre>Router(config)# crypto ca trustpoint TP1</pre>	<p>Specifies a local configuration name for the CA trustpoint and enters CA trustpoint configuration mode.</p> <p>Note The crypto ca identity command was replaced by the crypto ca trustpoint command.</p>
Step 7	<p>enrollment url url</p> <p>Example:</p> <pre>Router(ca-trustpoint)# enrollment url http://example.com</pre>	<p>Specifies a URL of the CA where your router should send certificate requests.</p> <ul style="list-style-type: none"> If you are using Simple Certificate Enrollment Protocol (SCEP) for enrollment, the URL argument must be in the form http://CA-name, where <i>CA-name</i> is the host Domain Name System (DNS) name or IP address of the CA trustpoint.
Step 8	<p>enrollment http-proxy host-name port-number</p> <p>Example:</p> <pre>Router(ca-trustpoint)# enrollment http-proxy example.com 8080</pre>	<p>(Optional) Configures the router to obtain certificates from the CA through an HTTP proxy server.</p>
Step 9	<p>crl {query url optional best-effort}</p> <p>Example:</p> <pre>Router(ca-trustpoint)# crl query ldap://example.com</pre>	<p>Configures the router to request a certificate revocation list (CRL), make CRL checking optional, or perform CRL checking on a “best-effort” basis.</p> <ul style="list-style-type: none"> CRLs ensure that the certificate of the peer has not been revoked. The crl optional command configures the router to accept certificates even if the appropriate CRL cannot be downloaded.

	Command or Action	Purpose
		<ul style="list-style-type: none"> Use the cr1 query url command to specify the Lightweight Directory Access Protocol (LDAP) URL of the CA server; for example, <code>ldap://another-server</code>.
Step 10	primary Example: <pre>Router(ca-trustpoint)# primary</pre>	(Optional) Specifies that this trustpoint should be used as the primary (default) trustpoint for CA requests. <ul style="list-style-type: none"> Use this command if more than one CA trustpoint will be configured on this router.
Step 11	exit Example: <pre>Router(ca-trustpoint)# exit</pre>	Exits CA trustpoint configuration mode and returns to global configuration mode.
Step 12	crypto ca authenticate name Example: <pre>Router(config)# crypto ca authenticate TP1</pre>	Authenticates the CA by getting the public key of the CA. <ul style="list-style-type: none"> Use the same name that you used when declaring the CA in the crypto ca trustpoint command.
Step 13	crypto ca enrollment name Example: <pre>Router(config)# crypto ca enrollment TP1</pre>	Obtains the certificate from the specified CA trustpoint. <ul style="list-style-type: none"> This command requests a signed certificate from the CA for each RSA key pair.
Step 14	Do one of the following: <ul style="list-style-type: none"> copy running-config startup-config copy system:running-config nvram:startup-config Example: <pre>Router(config)# copy running-config startup-config</pre>	Saves the configuration to NVRAM. <ul style="list-style-type: none"> This command is required to save the certificates into NVRAM. If not used, the certificates would be lost at router reload. Note To execute EXEC mode commands in global configuration mode, you can add the do keyword before the command. For example, instead of copy running-config startup-config , you could enter do copy running-config startup-config .

Configuring the HTTPS Server with SSL 3.0

To disable the standard HTTP server and configure the HTTPS server with SSL 3.0, complete the procedure in this section.

Before You Begin

If a certificate authority is to be used for certification, you should declare the CA trustpoint on the routing device before enabling the secure HTTP server.

SUMMARY STEPS

1. **enable**
2. Router# **show ip http server status**
3. **configure terminal**
4. **no ip http server**
5. **ip http secure-server**
6. **ip http secure-port** *port-number*
7. **ip http secure-ciphersuite** [*3des-ede-cbc-sha*] [*rc4-128-sha*] [*rc4-128-md5*] [*des-cbc-sha*]
8. **ip http secure-client-auth**
9. **ip http secure-trustpoint** *name*
10. **end**
11. **show ip http server secure status**

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2	Router# show ip http server status Example: Router# show ip http server status Example:	(Optional) Displays the status of the HTTP server. <ul style="list-style-type: none"> • If you are unsure whether the secure HTTP server is supported in the software image you are running, enter this command and look for the line "HTTP secure server capability: {Present Not present}". • This command displays the status of the standard HTTP server (enabled or disabled).
Step 3	configure terminal Example: Router# configure terminal	Enters global configuration mode.
Step 4	no ip http server Example: Router(config)# no ip http server	Disables the standard HTTP server. Note When enabling the HTTPS server you should always disable the standard HTTP server to prevent insecure connections to the same services. This is a precautionary step (typically, the HTTP server is disabled by default).

	Command or Action	Purpose
Step 5	<p>ip http secure-server</p> <p>Example:</p> <pre>Router(config)# ip http secure-server</pre>	Enables the HTTPS server.
Step 6	<p>ip http secure-port <i>port-number</i></p> <p>Example:</p> <pre>Router(config)# ip http secure-port 1025</pre>	(Optional) Specifies the port number that should be used for the HTTPS server. The default port number is 443. Valid options are 443 or any number in the range 1025 to 65535.
Step 7	<p>ip http secure-ciphersuite [3des-ede-cbc-sha] [rc4-128-sha] [rc4-128-md5] [des-cbc-sha]</p> <p>Example:</p> <pre>Router(config)# ip http secure-ciphersuite rc4-128-sha rc4-128-md5</pre>	<p>(Optional) Specifies the CipherSuites (encryption algorithms) that should be used for encryption over the HTTPS connection.</p> <ul style="list-style-type: none"> • This command allows you to restrict the list of CipherSuites that the server offers the connecting clients. For example, you may want to allow only the most secure CipherSuite to be used. • Unless you have a reason to specify the CipherSuites that should be used, or you are unfamiliar with the details of these CipherSuites, you should leave this command unconfigured and let the server and client negotiate the CipherSuite that they both support (this is the default).
Step 8	<p>ip http secure-client-auth</p> <p>Example:</p> <pre>Router(config)# ip http secure-client-auth</pre>	<p>(Optional) Configures the HTTP server to request an X.509v3 certificate from the client in order to authenticate the client during the connection process.</p> <ul style="list-style-type: none"> • In the default connection and authentication process, the client requests a certificate from the HTTP server, but the server does not attempt to authenticate the client. Authenticating the client provides more security than server authentication by itself, but not all clients may be configured for CA authentication.
Step 9	<p>ip http secure-trustpoint <i>name</i></p> <p>Example:</p> <pre>Router(config)# ip http secure-trustpoint trustpoint-01</pre>	<p>Specifies the CA trustpoint that should be used to obtain an X.509v3 security certificate and to authenticate the connecting client's certificate.</p> <ul style="list-style-type: none"> • Use of this command assumes you have already declared a CA trustpoint using the crypto ca trustpoint command and associated submode commands. • Use the same trustpoint name that you used in the associated crypto ca trustpoint command.
Step 10	<p>end</p> <p>Example:</p> <pre>Router(config)# end</pre>	Ends the current configuration session and returns you to privileged EXEC mode.

	Command or Action	Purpose
Step 11	show ip http server secure status Example: Router# show ip http server secure status	Displays the status of the HTTP secure server configuration.

Verifying the Configuration of the HTTPS Server

To verify the configuration of the HTTPS server, connect to the router running the HTTPS server with a web browser by entering **https://url**, where *url* is the IP address or hostname of the router. Successful connection using the **https** prefix (instead of the standard **http**) indicates that the HTTPS server is configured properly. If a port other than the default port is configured (using the **ip http secure-port** command), you must also specify the port number after the URL. For example:

```
https://209.165.202.129:1026
or
```

```
https://host.domain.com:1026
```

Generally, you can verify that the HTTPS server is configured and that you have a secure connection by locating an image of a padlock at the bottom of your browser window. Also note that secure HTTP connections have a URL that starts with "https:" instead of "http:".

Providing Additional Security and Efficiency

The configuration of the standard HTTP server applies to the secure HTTP server as well. To provide additional security and efficiency to both the standard HTTP server and the HTTPS server, complete the procedure in this section.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip http path** *path-name*
4. **ip http access-class** *access-list-number*
5. **ip http max-connections** *value*
6. **ip http timeout-policy idle** *seconds* **life** *seconds* **requests** *value*

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable	Enables privileged EXEC mode.

	Command or Action	Purpose
	<p>Example:</p> <pre>Router> enable</pre>	<ul style="list-style-type: none"> • Enter your password if prompted.
Step 2	<p>configure terminal</p> <p>Example:</p> <pre>Router# configure terminal</pre>	Enters global configuration mode.
Step 3	<p>ip http path <i>path-name</i></p> <p>Example:</p> <pre>Router(config)# ip http path slot1:</pre>	<p>(Optional) Sets the base HTTP path for HTML files.</p> <ul style="list-style-type: none"> • The base path is used to specify the location of the HTTP server files (HTML files) on the local system. Generally, the HTML files are located in system flash memory.
Step 4	<p>ip http access-class <i>access-list-number</i></p> <p>Example:</p> <pre>Router(config)# ip http access-class 20</pre>	(Optional) Specifies the access list that should be used to allow access to the HTTP server.
Step 5	<p>ip http max-connections <i>value</i></p> <p>Example:</p> <pre>Router(config)# ip http max-connections 10</pre>	(Optional) Sets the maximum number of concurrent connections to the HTTP server that will be allowed. The default value is 5.
Step 6	<p>ip http timeout-policy idle <i>seconds</i> life <i>seconds</i> requests <i>value</i></p> <p>Example:</p> <pre>Router(config)# ip http timeout-policy idle 30 life 120 requests 100</pre>	<p>(Optional) Sets the characteristics that determine how long a connection to the HTTP server should remain open. The characteristics are:</p> <ul style="list-style-type: none"> • idle --The maximum number of seconds the connection will be kept open if no data is received or response data cannot be sent out on the connection. Note that a new value may not take effect on any already existing connections. If the server is too busy or the limit on the life time or the number of requests is reached, the connection may be closed sooner. The default value is 180 seconds (3 minutes). • life --The maximum number of seconds the connection will be kept open, from the time the connection is established. Note that the new value may not take effect on any already existing connections. If the server is too busy or the limit on the idle time or the number of requests is reached, it may close the connection sooner. Also, because the server will not close the connection while actively processing a request, the connection may remain open longer than the specified life time if processing is occurring when the life maximum is reached. In this case, the connection will be closed when processing finishes.

	Command or Action	Purpose
		<p>The default value is 180 seconds (3 minutes). The maximum value is 86,400 seconds (24 hours).</p> <ul style="list-style-type: none"> • requests --The maximum limit on the number of requests processed on a persistent connection before it is closed. Note that the new value may not take effect on any already existing connections. If the server is too busy or the limit on the idle time or the life time is reached, the connection may be closed before the maximum number of requests are processed. The default value is 1. The maximum value is 86,400.

Configuring the HTTPS Client with SSL 3.0

To configure the HTTPS client with SSL 3.0, complete the procedure in this section.

Before You Begin

The standard HTTP client and the secure HTTP client are always enabled.

A certificate authority is required for secure HTTP client certification; the following steps assume that you have previously declared a CA trustpoint on the routing device. If a CA trustpoint is not configured, and the remote HTTPS server requires client authentication, connections to the secure HTTP client will fail.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip http client secure-trustpoint** *trustpoint-name*
4. **ip http client secure-ciphersuite** [3des-edc-cbc-sha] [rc4-128-sha] [rc4-128-md5] [des-cbc-sha]
5. **end**
6. **show ip http client secure status**

DETAILED STEPS

	Command or Action	Purpose
Step 1	<p>enable</p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> • Enter your password if prompted.

	Command or Action	Purpose
Step 2	configure terminal Example: <pre>Router# configure terminal</pre>	Enters global configuration mode.
Step 3	ip http client secure-trustpoint <i>trustpoint-name</i> Example: <pre>Router(config)# ip http client secure-trustpoint trustpoint01</pre>	(Optional) Specifies the CA trustpoint that should be used if the remote HTTP server requests client authentication. <ul style="list-style-type: none"> • Use of this command assumes you have already declared a CA trustpoint using the crypto ca trustpoint command and associated submode commands. • Use the same trustpoint name that you used in the associated crypto ca trustpoint command. • This command is optional if client authentication is not needed, or if a primary trustpoint has been configured. If the ip http client secure-trustpoint command is not used, the router will use the primary trustpoint, as specified by the primaryCA trustpoint configuration mode command.
Step 4	ip http client secure-ciphersuite [3des-edc-cbc-sha] [rc4-128-sha] [rc4-128-md5] [des-cbc-sha] Example: <pre>Router(config)# ip http client secure-ciphersuite rc4-128-sha rc4-128-md5</pre>	(Optional) Specifies the CipherSuites (encryption algorithms) that should be used for encryption over the HTTPS connection. <ul style="list-style-type: none"> • This command allows you to restrict the list of CipherSuites that the client offers when connecting to a secure HTTP server. For example, you may want to allow only the most secure CipherSuites to be used. • Unless you have a reason to specify the CipherSuites that should be used, or you are unfamiliar with the details of these CipherSuites, you should leave this command unconfigured and let the server and client negotiate the CipherSuite that they both support (this is the default).
Step 5	end Example: <pre>Router (config) # end</pre>	Ends the current configuration session and returns to privileged EXEC mode.
Step 6	show ip http client secure status Example: <pre>Router# show ip http client secure status</pre>	Displays the status of the HTTP secure server configuration.

Configuration Examples for the HTTPS--HTTP Server and Client with SSL 3.0 feature

The following example shows a configuration session in which the secure HTTP server is enabled, the port for the secure HTTP server is configured as 1025, and the remote CA trustpoint server "CA-trust-local" is used for certification.

```
Router# show ip http server status

HTTP server status: Disabled
HTTP server port: 80
HTTP server authentication method: enable
HTTP server access class: 0
HTTP server base path:
Maximum number of concurrent server connections allowed: 5
Server idle time-out: 600 seconds
Server life time-out: 600 seconds
Maximum number of requests allowed on a connection: 1
HTTP secure server capability: Present
HTTP secure server status: Disabled
HTTP secure server port: 443
HTTP secure server ciphersuite: 3des-ede-cbc-sha des-cbc-sha rc4-128-md5 rc4-12a
HTTP secure server client authentication: Disabled
HTTP secure server trustpoint:
Router# configure terminal
```

```
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)# ip http secure-server
```

```
Router(config)# ip http client secure-trustpoint CA-trust-local
```

```
Router(config)# ip http secure-port 1024
```

```
Invalid secure port value.
Router(config)# ip http secure-port 1025
```

```
Router(config)# ip http secure-ciphersuite rc4-128-sha rc4-128-md5
Router(config)# end
```

```
Router# show ip http server secure status
```

```
HTTP secure server status: Enabled
HTTP secure server port: 1025
HTTP secure server ciphersuite: rc4-128-md5 rc4-128-sha
HTTP secure server client authentication: Disabled
HTTP secure server trustpoint: CA-trust-local
```

In the following example, the CA trustpoint CA-trust-local is specified, and the HTTPS client is configured to use this trustpoint for client authentication requests:

```
Router# config terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)# crypto ca trustpoint CA-trust-local

Router(ca-trustpoint)# enrollment url http://example.com

Router(ca-trustpoint)# crl query ldap://example.com

Router(ca-trustpoint)# primary

Router(ca-trustpoint)# exit
```

```
Router(config)# ip http client secure-trustpoint CA-trust-local
Router(config)# end
Router# copy running-config startup-config
```

Additional References

The following sections provide references related to the HTTPS--HTTP Server and Client with SSL 3.0 feature.

Related Documents

Related Topic	Document Title
SSL 3.0	The SSL Protocol Version 3.0 <i>This document is available from various sources online.</i>
Standard Cisco Web Client	HTTP 1.1 Web Client
Standard Cisco Web Server	HTTP 1.1 Web Server
Certification Authority Interoperability	<ul style="list-style-type: none"> • Configuring Certification Authority Interoperability • Certificate Autoenrollment • Certificate Enrollment Enhancements • Trustpoint CLI • Source Interface Selection for Outgoing Traffic with Certificate Authority

Standards

Standard	Title
No new or modified standards are supported by this feature.	--

Related MIBs

MIBs	MIBs Link
<ul style="list-style-type: none"> No new or modified MIBs are supported by this feature and support for existing MIBs has not been modified by this feature. 	To locate and download MIBs for selected platforms, Cisco IOS XE releases, and feature sets, use Cisco MIB Locator found at the following URL: http://www.cisco.com/go/mibs

Related RFCs

RFCs	Description
RFC 2616	Cisco's implementation of HTTP is based on RFC 2616: Hypertext Transfer Protocol -- HTTP/1.1 .

Technical Assistance

Description	Link
<p>The Cisco Support website provides extensive online resources, including documentation and tools for troubleshooting and resolving technical issues with Cisco products and technologies.</p> <p>To receive security and technical information about your products, you can subscribe to various services, such as the Product Alert Tool (accessed from Field Notices), the Cisco Technical Services Newsletter, and Really Simple Syndication (RSS) Feeds.</p> <p>Access to most tools on the Cisco Support website requires a Cisco.com user ID and password.</p>	http://www.cisco.com/techsupport

Feature Information for HTTPS--HTTP Server and Client with SSL 3.0

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Table 2: Feature Information for HTTPS--HTTP Server and Client with SSL 3.0

Feature Name	Releases	Feature Information
HTTPS--HTTP Server and Client with SSL 3.0	Cisco IOS XE Release 2.1	<p>This feature provides Secure Socket Layer (SSL) version 3.0 support for the HTTP 1.1 server and HTTP 1.1 client within Cisco IOS XE software. SSL provides server authentication, encryption, and message integrity to allow secure HTTP communications. SSL also provides HTTP client authentication.</p> <p>This feature is supported only in Cisco software images that support SSL. Specifically, SSL is supported in "IPSec 56" and "IPSec 3DES" images (contains "k8" or "k9" in the image name).</p> <p>The following commands are introduced or modified in the feature or features documented in this module.</p> <ul style="list-style-type: none"> • debug ip http ssl error • ip http client secure-ciphersuite • ip http client secure-trustpoint • ip http secure-ciphersuite • ip http secure-client-auth • ip http secure-port • ip http secure-server • ip http secure-trustpoint • show ip http client secure status • show ip http server secure status

Glossary

RSA--RSA is a widely used Internet encryption and authentication system that uses public and private keys for encryption and decryption. The RSA algorithm was invented in 1978 by Ron Rivest, Adi Shamir, and Leonard Adleman. The abbreviation RSA comes from the first letter of the last names of the three original developers. The RSA algorithm is included in many applications, such as the web browsers from Microsoft and Netscape. The RSA encryption system is owned by RSA Security.

SHA --The Secure Hash Algorithm. SHA was developed by NIST and is specified in the Secure Hash Standard (SHS, FIPS 180). Often used as an alternative to Digest 5 algorithm.

signatures, digital--In the context of SSL, "signing" means to encrypt with a private key. In digital signing, one-way hash functions are used as input for a signing algorithm. In RSA signing, a 36-byte structure of two hashes (one SHA and one MD5) is signed (encrypted with the private key).

SSL 3.0--Secure Socket Layer version 3.0. SSL is a security protocol that provides communications privacy over the Internet. The protocol allows client and server applications to communicate in a way that is designed to prevent eavesdropping, tampering, or message forgery. SSL uses a program layer located between the Internet's HTTP and TCP layers. SSL is included as part of most web server products and as part of most Internet browsers.



HTTP Client API for Tcl IVR

The HTTP Client API for Tcl IVR feature provides support for Tcl IVR applications to retrieve data from or post data to an HTTP server. Also introduced with this feature is a new command-line interface structure for configuring voice applications and support for additional Tcl 8.3.4 commands.

- [Finding Feature Information, page 31](#)
- [Prerequisites for HTTP Client API for Tcl IVR and New Cisco Voice Application Command-Line Interface Structure, page 31](#)
- [Restrictions for HTTP Client API for Tcl IVR and New Cisco Voice Application Command-Line Interface Structure, page 32](#)
- [Information About HTTP Client API for Tcl IVR and New Cisco Voice Application Command-Line Interface Structure, page 32](#)
- [Feature Information for HTTP Client API for Tcl IVR, page 33](#)

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest caveats and feature information, see [Bug Search Tool](#) and the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the feature information table at the end of this module.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Prerequisites for HTTP Client API for Tcl IVR and New Cisco Voice Application Command-Line Interface Structure

- Familiarity with Tcl IVR, VoiceXML, and Cisco IOS commands.
- Required hardware:
 - Cisco 3600 series

- Cisco AS5300
 - Cisco AS5350
 - Cisco AS5400
 - Cisco AS5800
 - Cisco AS58550
- Required software:
 - Cisco IOS Release 12.3(14)T or later
 - Tcl 8.3.4
 - VoiceXML 2.0

Restrictions for HTTP Client API for Tcl IVR and New Cisco Voice Application Command-Line Interface Structure

If Cisco IOS configuration commands are used within the Tcl scripts, submode commands must be entered as quoted arguments on the same line as the configuration command.

Information About HTTP Client API for Tcl IVR and New Cisco Voice Application Command-Line Interface Structure

HTTP API for Tcl IVR 2.0

An HTTP application programming interface to the IOS HTTP client is provided. The HTTP package is accessed using the **package require httpios 1.0** Tcl command. Additional commands are provided to configure HTTP. See the [Tcl IVR API Version 2.0 Programming Guide](#) for more information.

Newly-Supported Tcl 8.3.4 Commands

The following Tcl 8.3.4 commands are now supported:

- cd
- close
- eof
- fconfigure
- file
- fileevent

- flush
- glob
- namespace
- open
- package
- pwd
- read
- seek

The following command is modified:

- puts

See the [Tcl IVR API Version 2.0 Programming Guide](#) for more information.

New Cisco Voice Application Command-Line Interface Structure

The **call application** command structure for configuring Tcl and IVR applications has been restructured to provide easier configuration of application parameters than the earlier CLI structure.

For more information, see the “Cisco IOS Release 12.3(14)T and Later Voice Application Command-Line Interface Structure Changes” section in Configuring Basic Functionality for Tcl IVR and VoiceXML Applications in the Cisco IOS Tcl IVR and VoiceXML Application Guide.

Feature Information for HTTP Client API for Tcl IVR

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Table 3: Feature Information for HTTP Client API for Tcl IVR

Feature Name	Releases	Feature Information
HTTP Client API for Tcl IVR	12.3(14)T	This feature was introduced.



HTTP Inspection Engine

The HTTP Inspection Engine feature allows users to configure their Cisco IOS Firewall to detect and prohibit HTTP connections--such as tunneling over port 80, unauthorized request methods, and non-HTTP compliant file transfers--that are not authorized within the scope of the security policy configuration. Tunneling unauthorized protocols through port 80 and over HTTP exposes a network to significant security risks.

The Cisco IOS Firewall can now be configured with a security policy that adheres to the following tasks:

- Allowing specific traffic targeted for port 80 to traverse the firewall. The traffic is inspected for protocol conformance and for the types of HTTP commands that are allowed or disallowed.
- Denying specific traffic targeted for port 80 that does not comply to HTTP traffic standards. The firewall is enabled to drop the packet, reset the connection, and send a syslog message, as appropriate.

Feature History for HTTP Inspection Engine

Release	Modification
12.3(14)T	This feature was introduced.

- [Finding Feature Information](#), page 35
- [Restrictions for HTTP Inspection Engine](#), page 36
- [Information About HTTP Inspection Engine](#), page 36
- [How to Define and Apply an HTTP Application Policy to a Firewall for Inspection](#), page 36
- [Configuration Examples for Setting Up an HTTP Inspection Engine](#), page 43
- [Additional References](#), page 44

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest caveats and feature information, see [Bug Search Tool](#) and the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the feature information table at the end of this module.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Restrictions for HTTP Inspection Engine

The Cisco 831 router with 48M RAM does not have enough memory to support this feature.

Information About HTTP Inspection Engine

Before configuring an application firewall to detect and police specific traffic targeted for port 80, you should understand the following concepts:

What Is a Security Policy

The application firewall uses a security policy, which consists of a collection of static signatures, to detect security violations. A static signature is a collection of parameters that specify protocol conditions that must be met before an action is taken. (For example, a signature may specify that an HTTP data stream containing the POST method must reset the connection.) These protocol conditions and reactions are defined by the end user via the command-line interface (CLI) to form a security policy.

Cisco IOS HTTP Application Policy Overview

HTTP uses port 80 to transport Internet web services, which are commonly used on the network and rarely challenged with regards to their legitimacy and conformance to standards. Because port 80 traffic is typically allowed through the network without being challenged, many application developers are leveraging HTTP traffic as an alternative transport protocol in which to enable their application to travel through or even bypass the firewall.

Most firewalls provide only packet filtering capabilities that simply permit or deny port 80 traffic without inspecting the data stream; the Cisco IOS application firewall for HTTP performs packet inspection as follows:

- Detects HTTP connections that are not authorized within the scope of the security policy configuration.
- Detects users who are tunneling applications through port 80.

If the packet is not in compliance with the HTTP protocol, it will be dropped, the connection will be reset, and a syslog message will be generated, as appropriate.

How to Define and Apply an HTTP Application Policy to a Firewall for Inspection

Defining an HTTP Application Policy

Use this task to create an HTTP application firewall policy.



Note Although application firewall policies are defined in global configuration mode, only one global policy for a given protocol is allowed per interface.

>

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. `appfw policy-name policy-name`
4. **application** *protocol*
5. `strict-http action {reset | allow} [alarm]`
6. `content-length {min bytes max bytes | min bytes | max bytes} action {reset | allow} [alarm]`
7. `content-type-verification [match-req-resp] action {reset | allow} [alarm]`
8. `max-header-length {request bytes response bytes} action {reset | allow} [alarm]`
9. `max-uri-length bytes action {reset | allow} [alarm]`
10. `request method {rfc rfc-method | extension extension-method} action {reset | allow} [alarm]`
11. `port-misuse {p2p | tunneling | im | default} action {reset | allow} [alarm]`
12. `transfer-encoding type {chunked | compress | deflate | gzip | identity | default} action {reset | allow} [alarm]`
13. **timeout** *seconds*
14. `audit-trail {on | off}`
15. **end**

DETAILED STEPS

	Command or Action	Purpose
Step 1	<p>enable</p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2	<p>configure terminal</p> <p>Example:</p> <pre>Router# configure terminal</pre>	<p>Enters global configuration mode.</p>
Step 3	<p><code>appfw policy-name policy-name</code></p> <p>Example:</p> <pre>Router(config)# appfw policy-name mypolicy</pre>	<p>Defines an application firewall policy and puts the router in application firewall policy configuration mode.</p>

	Command or Action	Purpose
Step 4	<p>application <i>protocol</i></p> <p>Example:</p> <pre>Router(cfg-appfw-policy)# application http</pre>	<p>Allows you to configure inspection parameters for a given protocol. Currently, only HTTP traffic can be inspected.</p> <ul style="list-style-type: none"> • <i>protocol</i> --Specify the http keyword. <p>This command puts you in <i>appfw-policy-protocol</i> configuration mode, where “<i>protocol</i>” is dependent upon the specified protocol. Because only HTTP can be specified, the configuration mode is <i>appfw-policy-http</i>.</p>
Step 5	<p>strict-http action {reset allow} [alarm]</p> <p>Example:</p> <pre>Router(cfg-appfw-policy-http)# strict-http action allow alarm</pre>	<p>(Optional) Allows HTTP messages to pass through the firewall or resets the TCP connection when HTTP noncompliant traffic is detected.</p>
Step 6	<p>content-length {min bytes max bytes min bytes max bytes} action {reset allow} [alarm]</p> <p>Example:</p> <pre>Router(cfg-appfw-policy-http)# content-length max 1 action allow alarm</pre>	<p>(Optional) Permits or denies HTTP traffic through the firewall on the basis of message size.</p> <ul style="list-style-type: none"> • min max bytes--Minimum or maximum content length, in bytes, allowed per message. Number of bytes range: 0 to 65535.
Step 7	<p>content-type-verification [match-req-resp] action {reset allow} [alarm]</p> <p>Example:</p> <pre>Router(cfg-appfw-policy-http)# content-type-verification match-req-resp action allow alarm</pre>	<p>(Optional) Permits or denies HTTP traffic through the firewall on the basis of content message type.</p>
Step 8	<p>max-header-length {request bytes response bytes} action {reset allow} [alarm]</p> <p>Example:</p> <pre>Router(cfg-appfw-policy-http)# max-header-length request 1 response 1 action allow alarm</pre>	<p>(Optional) Permits or denies HTTP traffic on the basis of the message header length.</p> <ul style="list-style-type: none"> • <i>bytes</i> --Number of bytes ranging from 0 to 65535.
Step 9	<p>max-uri-length bytes action {reset allow} [alarm]</p> <p>Example:</p> <pre>Router(cfg-appfw-policy-http)# max-uri-length 1 action allow alarm</pre>	<p>(Optional) Permits or denies HTTP traffic on the basis of the URI length in the request message.</p>
Step 10	<p>request method {rfc rfc-method extension extension-method} action {reset allow} [alarm]</p>	<p>(Optional) Permits or denies HTTP traffic according to either the request methods or the extension methods.</p>

	Command or Action	Purpose
	<p>Example:</p> <pre>Router(cfg-appfw-policy-http)# request-method rfc default action allow alarm</pre>	<ul style="list-style-type: none"> • rfc --Specifies that the supported methods of RFC 2616, <i>Hypertext Transfer Protocol--HTTP/1.1</i>, are to be used for traffic inspection. • rfc-method --Any one of the following RFC 2616 methods can be specified: connect, default, delete, get, head, options, post, put, trace. • extension --Specifies that the extension methods are to be used for traffic inspection. • extension-method --Any one of the following extension methods can be specified: copy, default, edit, getattribute, getproperties, index, lock, mkdir, move, revadd, revlabel, revlog, save, setattribute, startrev, stoprev, unedit, unlock.
<p>Step 11</p>	<pre>port-misuse {p2p tunneling im default} action {reset allow} [alarm]</pre> <p>Example:</p> <pre>Router(cfg-appfw-policy-http)# port-misuse default action allow alarm</pre>	<p>(Optional) Permits or denies HTTP traffic through the firewall on the basis of specified applications in the HTTP message.</p> <ul style="list-style-type: none"> • p2p --Peer-to-peer protocol applications subject to inspection: Kazaa and Gnutella. • tunneling --Tunneling applications subject to inspection: HTTPPort/HTTPHost, GNU Httptunnel, GotoMyPC, Firethru, Httptunnel.com Client • im --Instant messaging protocol applications subject to inspection: Yahoo Messenger. • default --All applications are subject to inspection.
<p>Step 12</p>	<pre>transfer-encoding type {chunked compress deflate gzip identity default} action {reset allow} [alarm]</pre> <p>Example:</p> <pre>Router(cfg-appfw-policy-http)# transfer-encoding type default action allow alarm</pre>	<p>(Optional) Permits or denies HTTP traffic according to the specified transfer-encoding of the message.</p> <ul style="list-style-type: none"> • chunked --Encoding format (specified in RFC 2616, <i>Hypertext Transfer Protocol--HTTP/1</i>) in which the body of the message is transferred in a series of chunks; each chunk contains its own size indicator. • compress --Encoding format produced by the UNIX “compress” utility. • deflate --“ZLIB” format defined in RFC 1950, <i>ZLIB Compressed Data Format Specification version 3.3</i>, combined with the “deflate” compression mechanism described in RFC 1951, <i>DEFLATE Compressed Data Format Specification version 1.3</i>. • gzip --Encoding format produced by the “gzip” (GNU zip) program. • identity --Default encoding, which indicates that no encoding has been performed. • default --All of the transfer encoding types.

	Command or Action	Purpose
Step 13	timeout <i>seconds</i> Example: <pre>Router(cfg-appfw-policy-http)# timeout 60</pre>	(Optional) Overrides the global TCP idle timeout value for HTTP traffic. Note If this command is not issued, the default value specified via the ip inspect tcp idle-time command will be used.
Step 14	audit-trail {on off} Example: <pre>Router(cfg-appfw-policy-http)# audit-trail on</pre>	(Optional) Turns audit trail messages on or off. Note If this command is not issued, the default value specified via the ip inspect audit-trail command will be used.
Step 15	end Example: <pre>Router(cfg-appfw-policy-http)# end</pre>	Exits cfm-appfw-policy-http configuration mode.

What to Do Next

After you have successfully defined an application policy for HTTP traffic inspection, you must apply the policy to an inspection rule. Thereafter, the inspection rule must be applied to an interface. For information on completing this task, see the section [“Applying an HTTP Application Policy to a Firewall for Inspection, on page 40.”](#)

Applying an HTTP Application Policy to a Firewall for Inspection

Use this task to apply an HTTP application policy to an inspection rule, followed by applying the inspection rule to an interface.



Note

An application policy can coexist with other inspection protocols (for example, an HTTP policy and an FTP policy can coexist).

Before You Begin

You must have already defined an application policy (as shown in the section [“Defining an HTTP Application Policy, on page 36”](#)).

or

```
show ip inspect name inspection-name | config | interfaces | session [detail] | statistics | all
```

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip inspect name** *inspection-name* **appfw** *policy-name*
4. **ip inspect name** *inspection-name* **http** [**alert** {**on** | **off**}] [**audit-trail** {**on** | **off**}] [**timeout** *seconds*]
5. **interface** *type number*
6. **ip inspect** *inspection-name* **in** | **out**}
7. **exit**
8. **exit**
9. **show appfw** configuration [*name*]

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: Router> enable	Enables privileged EXEC mode. • Enter your password if prompted.
Step 2	configure terminal Example: Router# configure terminal	Enters global configuration mode.
Step 3	ip inspect name <i>inspection-name</i> appfw <i>policy-name</i> Example: Router(config)# ip inspect name firewall appfw mypolicy	Defines a set of inspection rules for the application policy. • <i>policy-name</i> --Must match the policy name specified via the appfw policy-name command.
Step 4	ip inspect name <i>inspection-name</i> http [alert { on off }] [audit-trail { on off }] [timeout <i>seconds</i>] Example: Router(config)# ip inspect name firewall http	Defines a set of inspection rules that is to be applied to all HTTP traffic. • The <i>inspection-name</i> argument must match the <i>inspection-name</i> argument specified in Step 3.
Step 5	interface <i>type number</i> Example: Router#(config)# interface FastEthernet0/0	Configures an interface type and enters interface configuration mode.

	Command or Action	Purpose
Step 6	<p>ip inspect <i>inspection-name</i> in out}</p> <p>Example:</p> <pre>Router#(config-if)# ip inspect firewall in</pre>	<p>Applies the inspection rules (defined in Step 3 and Step 4) to all traffic entering the specified interface.</p> <ul style="list-style-type: none"> The <i>inspection-name</i> argument must match the inspection name defined via the ip inspect name command.
Step 7	<p>exit</p> <p>Example:</p> <pre>Router#(config-if)# exit</pre>	<p>Exits interface configuration mode.</p>
Step 8	<p>exit</p> <p>Example:</p> <pre>Router(config)# exit</pre>	<p>Exits global configuration mode.</p>
Step 9	<p>show appfw configuration [name]</p> <p>Example:</p> <pre>Router# show appfw configuration</pre> <p>Example:</p> <p>or</p> <p>Example:</p> <pre>show ip inspect {name inspection-name config interfaces session [detail] statistics all}</pre> <p>Example:</p> <pre>Router# show ip inspect config</pre>	<p>(Optional) Displays application firewall policy configuration information.</p> <p>(Optional) Displays firewall-related configuration information.</p>

Troubleshooting Tips

To help troubleshoot the application firewall configuration, issue the following application-firewall specific debug command: **debug appfw application protocol | function-trace | object-creation | object-deletion | events | timers | detailed** .

The following sample configuration shows how to configure an HTTP policy with application firewall debugging enabled:

```
Router(config)# appfw policy-name myPolicy APPFW FUNC:appfw_policy_find
APPFW FUNC:appfw_policy_find -- Policy myPolicy is not found
APPFW FUNC:appfw_policy_alloc
APPFW FUNC:appfw_policy_alloc -- policy_alloc 0x65727278
APPFW FUNC:appfw_policy_alloc -- Policy 0x65727278 is set to valid
APPFW FUNC:appfw_policy_alloc -- Policy myPolicy has been created
APPFW FUNC:appfw_policy_command -- memlock policy 0x65727278

! Debugging sample for application (HTTP) creation

Router(cfg-appfw-policy)# application http APPFW FUNC:appfw_http_command
APPFW FUNC:appfw_http_appl_find
APPFW FUNC:appfw_http_appl_find -- Application not found
APPFW FUNC:appfw_http_appl_alloc
APPFW FUNC:appfw_http_appl_alloc -- appl http 0x64D7A25C
APPFW FUNC:appfw_http_appl_alloc -- Application HTTP parser structure 64D7A25C created
! Debugging sample for HTTP-specific application inspection
Router(cfg-appfw-policy-http)#
Router(cfg-appfw-policy-http)# strict-http action reset alarm
APPFW FUNC:appfw_http_subcommand
APPFW FUNC:appfw_http_subcommand -- strict-http cmd turned on
Router# debug appfw detailed
APPFW Detailed Debug debugging is on
fw7-7206a#debug appfw object-creation
APPFW Object Creations debugging is on
fw7-7206a#debug appfw object-deletion
APPFW Object Deletions debugging is on
```

Configuration Examples for Setting Up an HTTP Inspection Engine

Setting Up and Verifying an HTTP Inspection Engine Example

The following example show how to define the HTTP application firewall policy “mypolicy.” This policy includes all supported HTTP policy rules. This example also includes sample output from the **show appfw configuration** and **show ip inspect config** commands, which allow you to verify the configured setting for the application policy.

```
! Define the HTTP policy.
appfw policy-name mypolicy
application http
  strict-http action allow alarm
  content-length maximum 1 action allow alarm
  content-type-verification match-req-rsp action allow alarm
  max-header-length request 1 response 1 action allow alarm
  max-uri-length 1 action allow alarm
  port-misuse default action allow alarm
  request-method rfc put action allow alarm
  transfer-encoding type default action allow alarm
```

```

!
!
! Apply the policy to an inspection rule.
ip inspect name firewall appfw mypolicy
ip inspect name firewall http
!
!
! Apply the inspection rule to all HTTP traffic entering the FastEthernet0/0 interface.
interface FastEthernet0/0
 ip inspect firewall in
!
!
! Issue the show appfw configuration
  command and the show ip inspect config
command after the inspection rule "mypolicy" is applied to all incoming HTTP traffic on the
FastEthernet0/0 interface.
!
Router# show appfw configuration

Application Firewall Rule configuration
Application Policy name mypolicy
  Application http
    strict-http action allow alarm
    content-length minimum 0 maximum 1 action allow alarm
    content-type-verification match-req-rsp action allow alarm
    max-header-length request length 1 response length 1 action allow alarm
    max-uri-length 1 action allow alarm
    port-misuse default action allow alarm
    request-method rfc put action allow alarm
    transfer-encoding default action allow alarm
Router# show ip inspect config

Session audit trail is disabled
Session alert is enabled
one-minute (sampling period) thresholds are [400:500] connections
max-incomplete sessions thresholds are [400:500]
max-incomplete tcp connections per host is 50. Block-time 0 minute.
tcp synwait-time is 30 sec -- tcp finwait-time is 5 sec
tcp idle-time is 3600 sec -- udp idle-time is 30 sec
dns-timeout is 5 sec
Inspection Rule Configuration
Inspection name firewall
http alert is on audit-trail is off timeout 3600

```

Additional References

The following sections provide references related to the HTTP Inspection Engine feature.

Related Documents

Related Topic	Document Title
Firewall commands: complete command syntax, command mode, defaults, usage guidelines, and examples	<i>Cisco IOS Security Command Reference</i>

Standards

Standards	Title
No new or modified standards are supported by this feature.	--

MIBs

MIBs	MIBs Link
No new or modified MIBs are supported by this feature.	To locate and download MIBs for selected platforms, Cisco IOS releases, and feature sets, use Cisco MIB Locator found at the following URL: http://www.cisco.com/go/mibs

RFCs

RFCs	Title
RFC 2616	Hypertext Transfer Protocol -- HTTP/1.1

Technical Assistance

Description	Link
The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.	http://www.cisco.com/cisco/web/support/index.html



Selective Enabling of Applications Using an HTTP or HTTPS Server

The Selective Enabling of Applications Using an HTTP or HTTPS Server feature eliminates a potential security vulnerability by providing a facility to enable selected HTTP and HTTP over Secure Socket Layer (HTTPS) services on both the Cisco IOS HTTP and HTTPS server infrastructure. This feature also provides the capability to view the current state of the HTTP and HTTPS services, including which services are enabled or disabled.

- [Finding Feature Information, page 47](#)
- [Information About Selective Enabling of Applications Using an HTTP or HTTPS Server, page 48](#)
- [How to Enable Selected Applications Using an HTTP or HTTPS Server, page 48](#)
- [Configuration Examples for Selective Enabling of Applications Using an HTTP or HTTPS Server, page 51](#)
- [Additional References for Selective Enabling of Applications Using an HTTP or HTTPS Server, page 52](#)
- [Feature Information for Selective Enabling of Applications Using an HTTP or HTTPS Server, page 53](#)

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest caveats and feature information, see [Bug Search Tool](#) and the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the feature information table at the end of this module.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Information About Selective Enabling of Applications Using an HTTP or HTTPS Server

Selective Enabling of Applications Within the HTTP and HTTPS Infrastructure

The Selective Enabling of Applications Using an HTTP or HTTPS Server feature eliminates a potential security vulnerability by providing a facility to enable selected HTTP and HTTPS services on both the Cisco IOS HTTP and HTTPS server infrastructure. This feature also provides the capability to view the current state of the HTTP and HTTPS services, including which services are enabled or disabled.

Prior to this feature, HTTP or HTTPS applications running on a router or a switch, were either all enabled or all disabled when the HTTP server or HTTPS server was enabled or disabled, respectively (using the **ip http server** and **ip http secure-server** commands). In the situation where all HTTP or HTTPS applications were enabled, remote end-users were given potential access to services that could allow them to pose a potential security threat to service providers.

With this new feature, the Cisco IOS HTTP and HTTPS infrastructure provides a way to enable only selected HTTP and HTTPS applications to run on a router or a switch, thereby bypassing a potential security vulnerability. Selected HTTP and HTTPS applications can be enabled using the new **ip http active-session-modules** and **ip http secure-active-session-modules** configuration commands, respectively.

**Note**

The maximum number of sessions that can be registered with the Cisco IOS HTTP or HTTPS server is 32.

How to Enable Selected Applications Using an HTTP or HTTPS Server

Enabling Selected HTTP Applications

Perform this task to selectively enable the HTTP applications that will service incoming HTTP requests from remote clients.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip http session-module-list** *list-name prefix-1 [prefix-2,...,prefix-n]*
4. **ip http active-session-modules** {*list-name* | **none** | **all**}
5. **end**
6. **show ip http server session-module**

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: <pre>Router> enable</pre>	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2	configure terminal Example: <pre>Router# configure terminal</pre>	Enters global configuration mode.
Step 3	ip http session-module-list <i>list-name prefix-1</i> <i>[prefix-2,...,prefix-n]</i> Example: <pre>Router(config)# ip http session-module-list list1 SCEP,HOME_PAGE</pre>	Defines a list of HTTP or HTTPS application names.
Step 4	ip http active-session-modules <i>{list-name none all}</i> Example: <pre>Router(config)# ip http active-session-modules list1</pre>	Selectively enables HTTP applications that will service incoming HTTP requests from remote clients. <ul style="list-style-type: none"> • The <i>listname</i> argument enables only those HTTP services configured in the list identified by the ip http session-module-list command to serve HTTP requests. • The keyword none disables all HTTP services from serving HTTP requests. • The keyword all enables all HTTP services to serve HTTP requests.
Step 5	end Example: <pre>Router(config)# end</pre>	Ends your configuration session and returns to privileged EXEC mode.
Step 6	show ip http server session-module Example: <pre>Router# show ip http server session-module</pre>	(Optional) Displays information about all HTTP and HTTPS services available on the router or switch, including their current state of service, such as whether they are enabled or disabled.

Enabling Selected HTTPS Applications

Perform this task to selectively enable the HTTPS applications that will service incoming HTTPS requests from remote clients.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip http session-module-list** *list-name prefix-1 [prefix-2,...,prefix-n]*
4. **ip http secure-active-session-modules** {*list-name* | **none** | **all**}
5. **end**
6. **show ip http server session-module**

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2	configure terminal Example: Router# configure terminal	Enters global configuration mode.
Step 3	ip http session-module-list <i>list-name prefix-1 [prefix-2,...,prefix-n]</i> Example: Router(config)# ip http session-module-list list1 SCEP,HOME_PAGE	Defines a list of HTTP or HTTPS application names.
Step 4	ip http secure-active-session-modules { <i>list-name</i> none all }	Selectively enables HTTPS applications that will service incoming HTTPS requests from remote clients. <ul style="list-style-type: none"> • The <i>listname</i> argument enables only those HTTPS services configured in the list identified by the ip http session-module-list command to serve HTTPS requests. • The keyword none disables all HTTPS services from serving HTTPS requests. • The keyword all enables all HTTPS services to serve HTTPS requests.

	Command or Action	Purpose
Step 5	end Example: Router(config)# end	Ends your configuration session and returns the CLI to Privileged Exec mode.
Step 6	show ip http server session-module Example: Router# show ip http server session-module	(Optional) Displays information about all HTTP and HTTPS services available on the router or switch, including their current state of service, such as whether they are enabled or disabled.

Configuration Examples for Selective Enabling of Applications Using an HTTP or HTTPS Server

Example: Enabling Selected HTTP and HTTPS Applications

The following configuration sample shows a configuration with different set of services available for HTTP and HTTPS requests. In this example, all HTTP applications are enabled for providing services to remote clients, but for HTTPS services, only the HTTPS applications defined in list1 (Simple Certificate Enrollment Protocol [SCEP] and HOME_PAGE) are enabled.

```
ip http session-module-list list1 SCEP,HOME_PAGE
ip http active-session-modules all
ip http server
ip http secure-server
ip http secure-active-session-modules list1
```

Example: Verifying HTTP and HTTPS Applications

The following example shows how to list the HTTP and HTTPS applications that have been selectively enabled or disabled using the **ip http session-module-list list-name prefix-1 [prefix-2,...,prefix-n]** command:

```
Device# show ip http server session-module
```

```
HTTP server application session modules:
Session module Name  Handle Status  Secure-status  Description
HOME_PAGE            2       Active  Active         IOS Homepage Server
GSI3D3FD3DC-wsma    6       Active  Active         wsma infra
HTTP_IFS              1       Active  Active         HTTP based IOS File Server
BANNER_PAGE          3       Active  Active         HTTP Banner Page Server
WEB_EXEC              4       Active  Active         HTTP based IOS EXEC Server
IXI                   5       Active  Active         IOS XML Infra Application Server
GSI3D31BCA4-wsma    7       Active  Active         wsma infra
EXTERN                9       Active  Active         External Distributed HTTP server
dot11                 30      Active  Active         dot11
links                 31      Active  Active         links
tgconfig              32      Active  Active         tgconfig
```

system	33	Active	Active	system
javascript	34	Active	Active	javascript
css	35	Active	Active	css
images	36	Active	Active	images
wlan	37	Active	Active	wlan
wireless	38	Active	Active	wireless

**Note**

The applications that can be enabled or disabled vary based on the platform and applications that register with HTTP infra during run time. HTTP infra provides a web interface that is referred to as legacy WebUI. This WebUI provides links to the following applications:

- Diagnostic log
- HTML access to command-line interface
- Connectivity test —ping interface
- Platform utilities
- Show tech support
- Extended ping
- Any platform-specific home page
- Contact information

Additional References for Selective Enabling of Applications Using an HTTP or HTTPS Server

Related Documents

Related Topic	Document Title
Additional HTTP configuration information	<i>Using the Cisco Web Browser User Interface</i>
Additional HTTPS configuration information	<i>HTTPS - HTTP Server and Client with SSL 3.0</i>
Additional HTTP and HTTPS commands	<i>Cisco IOS Network Management Command Reference</i>

Technical Assistance

Description	Link
<p>The Cisco Support website provides extensive online resources, including documentation and tools for troubleshooting and resolving technical issues with Cisco products and technologies.</p> <p>To receive security and technical information about your products, you can subscribe to various services, such as the Product Alert Tool (accessed from Field Notices), the Cisco Technical Services Newsletter, and Really Simple Syndication (RSS) Feeds.</p> <p>Access to most tools on the Cisco Support website requires a Cisco.com user ID and password.</p>	<p>http://www.cisco.com/public/support/tac/home.shtml</p>

Feature Information for Selective Enabling of Applications Using an HTTP or HTTPS Server

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Table 4: Feature Information for Selective Enabling of Applications Using an HTTP or HTTPS Server

Feature Name	Releases	Feature Information
<p>Selective Enabling of Applications Using an HTTP or HTTPS Server</p>	<p>12.3(14)T</p>	<p>The Selective Enabling of Applications Using an HTTP or HTTPS Server feature eliminates a potential security vulnerability by providing a facility to enable selected HTTP and HTTPS over Secure Socket Layer (HTTPS) services on both the Cisco IOS HTTP and HTTPS server infrastructure. This feature also provides the capability to view the current state of the HTTP and HTTPS services, including which services are enabled or disabled.</p>

