



K

- [keepalive retries](#), on page 2
- [keepalive target](#), on page 4
- [keepalive timeout](#), on page 6
- [keepalive trigger](#), on page 7

keepalive retries



Note The documentation set for this product strives to use bias-free language. For purposes of this documentation set, bias-free is defined as language that does not imply discrimination based on age, disability, gender, racial identity, ethnic identity, sexual orientation, socioeconomic status, and intersectionality. Exceptions may be present in the documentation due to language that is hardcoded in the user interfaces of the product software, language used based on RFP documentation, or language that is used by a referenced third-party product.

To set the number of keepalive retries from Skinny Client Control Protocol (SCCP) to Cisco Unified CallManager, use the **keepalive retries** command in SCCP Cisco CallManager configuration mode. To reset this number to the default value, use the **no** form of this command.

keepalive retries *number*
no keepalive retries

Syntax Description

<i>number</i>	Number of keepalive attempts. Range is 1 to 32. Default is 3.
---------------	---

Command Default

3 keepalive attempts

Command Modes

SCCP Cisco CallManager configuration

Command History

Release	Modification
12.3(8)T	This command was introduced.
Cisco IOS XE Amsterdam 17.2.1r	Introduced support for YANG models.

Usage Guidelines

Use this command to control the number of keepalive retries before SCCP confirms that the Cisco Unified CallManager link is down. When SCCP confirms that the Cisco Unified CallManager link is down (if the number of keepalive messages sent without receiving an Ack reaches the keepalive retries value), Cisco Unified CallManager switchover is initiated.



Note The optimum setting for this command depends on the platform and your individual network characteristics. Adjust the keepalive retries to meet your needs.

Examples

The following example sets the number of times that a Cisco Unified CallManager retries before confirming that the link is down to seven:

```
Router(conf-sccp-ccm) # keepalive retries 7
```

Related Commands

Command	Description
keepalive timeout	Sets the length of time between keepalive messages from SCCP to Cisco Unified CallManager.
sccp ccm group	Creates a Cisco CallManger group and enters the SCCP Cisco CallManager configuration mode.

keepalive target

To identify Session Initiation Protocol (SIP) servers that will receive keepalive packets from the SIP gateway, use the **keepalive target** command in SIP user-agent configuration mode. To disable the **keepalive target** command behavior, use the **no** form of this command.

keepalive target { { {**ipv4:address** | **ipv6:address** }[:**port**] | **dns:host**} | [**tcp** [**tls**]] | [**udp**] | [**secondary**]}
no keepalive target [**secondary**]

Syntax Description

ipv4: <i>address</i>	IP address (in IP version 4 format) of the primary or secondary SIP server to monitor.
ipv6: <i>address</i>	IPv6 address of the primary or secondary SIP server to monitor.
: <i>port</i>	(Optional) SIP port number. Default SIP port number is 5060.
dns: <i>hostname</i>	DNS hostname of the primary or secondary SIP server to monitor.
tcp	(Optional) Sends keepalive packets over TCP.
tls	(Optional) Sends keepalive packets over Transport Layer Security (TLS).
udp	(Optional) Sends keepalive packets over User Datagram Protocol (UDP).
secondary	(Optional) Associates the IP version 4 address or the domain name system (DNS) hostname to a secondary SIP server to monitor.

Command Default

No keepalives are sent by default from SIP gateway to SIP gateway. The SIP port number is 5060 by default.

Command Modes

SIP user-agent configuration (config-sip-ua)

Command History

Release	Modification
12.4(6)T	This command was introduced.
12.4(22)T	Support for IPv6 was added.

Usage Guidelines

The primary or secondary SIP server addresses are in the following forms: dns:example.sip.com or ipv4:172.16.0.10.

Examples

The following example sets the primary SIP server address and defaults to the UDP transport:

```
sip-ua
keepalive target ipv4:172.16.0.10
```

The following example sets the primary SIP server address and the transport to UDP:

```
sip-ua
keepalive target ipv4:172.16.0.10 udp
```

The following example sets both the primary and secondary SIP server address and the transport to UDP:

```
sip-ua
  keepalive target ipv4:172.16.0.10 udp
  keepalive target ipv4:172.16.0.20 udp secondary
```

The following example sets both the primary and secondary SIP server addresses and defaults to the UDP transport:

```
sip-ua
  keepalive target ipv4:172.16.0.10
  keepalive target ipv4:172.16.0.20 secondary
```

The following example sets the primary SIP server address and the transport to TCP:

```
sip-ua
  keepalive target ipv4:172.16.0.10 tcp
```

The following example sets both the primary and secondary SIP server addresses and the transport to TCP:

```
sip-ua
  keepalive target ipv4:172.16.0.10 tcp
  keepalive target ipv4:172.16.0.20 tcp secondary
```

The following example sets the primary SIP server address and the transport to TCP and sets security to TLS mode:

```
sip-ua
  keepalive target ipv4:172.16.0.10 tcp tls
```

The following example sets both the primary and secondary SIP server addresses and the transport to TCP and sets security to the TLS mode:

```
sip-ua
  keepalive target ipv4:172.16.0.10 tcp tls
  keepalive target ipv4:172.16.0.20 tcp tls secondary
```

Related Commands

Command	Description
busyout monitor keepalive	Selects a voice port or ports to be busied out in cases of a keepalive failure.
keepalive trigger	Sets the trigger count to the number of Options message requests that must consecutively receive responses from the SIP servers in order to unbusy the voice ports when in the down state.
retry keepalive	Sets the retry keepalive count for retransmission.
timers keepalive	Sets the timers keepalive interval between sending Options message requests when the SIP server is active or down.

keepalive timeout

To set the length of time between keepalive messages from Skinny Client Control Protocol (SCCP) to Cisco Unified CallManager, use the **keepalive timeout** command in SCCP Cisco CallManager configuration mode. To reset the length of time to the default value, use the **no** form of this command.

keepalive timeout *seconds*
no keepalive timeout

Syntax Description	<i>seconds</i> Time between keepalive messages. Range is 1 to 180. Default is 30.
---------------------------	---

Command Default 30 seconds

Command Modes SCCP Cisco CallManager configuration

Command History	Release	Modification
	12.3(8)T	This command was introduced.
	Cisco IOS XE Amsterdam 17.2.1r	Introduced support for YANG models.

Usage Guidelines Whenever SCCP sends the keepalive message to the Cisco Unified CallManager, it initiates this timer. Once the timeout occurs, it sends the next keepalive message unless the number of keepalive (messages without an Ack) reaches the number set by the **keepalive retries** command. As of now, the SCCP protocol uses the value provided by the Cisco Unified CallManager.



Note The optimum setting for this command depends on the platform and your individual network characteristics. Adjust the keepalive timeout value to meet your needs.

Examples

The following example sets the length of time between Cisco Unified CallManager keepalive messages to 120 seconds (2 minutes):

```
Router(config-sccp-ccm)# k eepalive timeout 120
```

Related Commands	Command	Description
	keepalive retries	Sets the number of keepalive retries from SCCP to Cisco Unified CallManager.
	sccp ccm group	Creates a Cisco CallManger group and enters SCCP Cisco CallManager configuration mode.

keepalive trigger

The trigger count represents the number of Options message requests that must consecutively receive responses from the SIP servers when in the down state in order to unbusy the voice ports, use the **keepalive trigger** command in SIP user agent configuration mode. To restore to the default value of 3 seconds, use the **no** form of this command.

keepalive trigger *count*
no keepalive trigger *count*

Syntax Description

<i>count</i>	Keepalive trigger value in the range from 1 to 10. The default value is 3.
--------------	--

Command Default

The default value for the keepalive trigger is 3.

Command Modes

SIP user agent configuration

Command History

Release	Modification
12.4(6)T	This command was introduced.

Usage Guidelines

Sets the count to represent the number of Options message requests that must be consecutively receive responses from the SIP servers in order to unbusy the voice ports when in the down state. The default is 3.

Examples

The following example sets a time interval after the number of Options message requests that must consecutively receive responses from the SIP servers in order to unbusy the voice ports when in the down state. The trigger interval is set to 8 in the following example:

```
sip-ua
  keepalive trigger 8
```

Related Commands

Command	Description
busyout monitor keepalive	Selects a voice port or ports to be busied out in cases of a keepalive failure.
keepalive target	Identifies a SIP server that will receive keepalive packets from the SIP gateway.
retry keepalive	Sets the retry keepalive for retransmission.
timers keepalive	Sets the time interval between sending Options message requests when the SIP server is active or down.

