



# Release Notes for Cisco AS5300 Universal Access Servers for Cisco IOS Release 12.1

---

January 2, 2001



**Note**

---

You can find the most current Cisco IOS documentation on CCO. These electronic documents may contain updates and modifications made after the hardcopy documents were printed.

---

These release notes for Cisco AS5300 universal access servers support Cisco IOS Release 12.1(6). These release notes are updated to describe new memory requirements, hardware support, software platform deferrals, and changes to the microcode or modem code and related documents.

For a list of the software caveats that apply to Cisco IOS Release 12.1, see *Caveats for Cisco IOS Release 12.1* that accompanies these release notes. The caveats document is updated for every maintenance release and is located on Cisco Connection Online (CCO) and the Documentation CD-ROM.

Use these release notes with *Cross-Platform Release Notes for Cisco IOS Release 12.1* on CCO and the Documentation CD-ROM.

## Contents

These release notes describe the following topics:

- Introduction, page 2
- System Requirements, page 2
- New and Changed Information, page 7
- MIBs, page 8
- Important Information, page 9
- Caveats, page 9
- Related Documentation, page 10



---

**Corporate Headquarters:** Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

Copyright © 2001. Cisco Systems, Inc. All rights reserved.

78-10636-06

- Obtaining Documentation, page 16
- Obtaining Technical Assistance, page 17

## Introduction

The Cisco AS5300 is a versatile data communications platform that performs two functions in a single modular chassis depending on the installed feature cards and IOS images:

- Remote Access Server
- Voice Gateway

The remote access server is intended for Internet service providers (ISPs), telecommunications carriers, and other service providers that offer managed Internet connections and medium to large sites that provide both digital and analog access to users on an enterprise network. By terminating both analog and digital calls on the same chassis simultaneously, the access server provides a clear, simple, and easy migration path from analog dial access services to digital dial access services.

The Cisco AS5300/Voice Gateway is a versatile data communications platform that provides the functions of an access server, router, and digital modem(s) in a single modular chassis. The Cisco AS5300 includes three feature card slots: one holds a T1/E1/PRI feature card, and the other two support modem feature cards or voice digital signal processor (DSP) feature cards. When equipped with modem cards, the Cisco AS5300 serves as a remote access concentrator for dial-up (modem or ISDN) Internet access. When equipped with voice feature cards and Voice IOS, the Cisco AS5300/Voice Gateway serves as a voice (VoIP) gateway. By using one slot for modems and the other for voice DSPs, the Cisco AS5300 can serve in both capacities. Modem, voice, or fax calls are routed to the appropriate cards/resources via Dialed Number Identification Service (DNIS).

For information on new features and Cisco IOS commands supported by Cisco IOS Release 12.1(6), see the “New and Changed Information” section on page 7 and the “Related Documentation” section on page 10.

## System Requirements

This section describes the system requirements for Cisco IOS Release 12.1:

- Memory Recommendations, page 3
- Hardware Supported, page 3
- Determining the Software Version, page 4
- Upgrading to a New Software Release, page 4
- Microcode and Modem Code Software, page 5
- Feature Set Tables, page 5

## Memory Recommendations

Table 1 lists the memory recommendations for the Cisco AS5300.

**Table 1** *Memory Recommendations for the Cisco AS5300*

Feature Set	Image Name	Flash Memory Recommended	DRAM Memory Recommended	Runs From
IP	c5300-i-mz	16 MB	64 MB	RAM
IP Plus	c5300-is-mz	16 MB	64 MB	RAM
IP Plus IPsec 56	c5300-is56i-mz	16 MB	64 MB	RAM
IP Plus IPsec 3DES	c5300-ik2s-mz	16 MB	64 MB	RAM
IP/IPX/AT/DEC	c5300-d-mz	16 MB	64 MB	RAM
IP/IPX/AT/DEC Plus	c5300-ds-mz	16 MB	64 MB	RAM
Enterprise	c5300-j-mz	16 MB	64 MB	RAM
Enterprise Plus	c5300-js-mz	16 MB	64 MB	RAM
Enterprise Plus IPsec 56	c5300-js56i-mz	16 MB	64 MB	RAM
Enterprise Plus IPsec 3DES	c5300-jk2s-mz	16 MB	64 MB	RAM

## Hardware Supported

Cisco IOS Release 12.1 supports the Cisco AS5300.

For detailed descriptions of the new hardware features, see the “New and Changed Information” section on page 7. Table 2 lists the interfaces supported by the Cisco AS5300.

**Table 2** *Supported Interfaces for the Cisco AS5300*

Interface and Modem Cards	Product Description	In <sup>1</sup>
Interface Cards	Ethernet RJ-45 (included w/ unit)	
	Ethernet/Fast Ethernet (RJ-45) (included w/ unit)	
	ISDN PRI	
	E1-G.703/G.704	
	Channelized T1 (4 ports) without serial support	
	Channelized T1 (4 ports) with 4 serial ports	
	Channelized T1 (8 ports) with 4 serial ports	
	Channelized E1 (4 ports) without serial support	
	Channelized E1 (4 ports) with 4 serial ports	
	Channelized E1 (8 ports) with 4 serial ports	

**Table 2 Supported Interfaces for the Cisco AS5300 (continued)**

<b>Interface and Modem Cards</b>	<b>Product Description</b>	<b>In<sup>1</sup></b>
<b>Interface Cards (continued)</b>	HMM/48 channel	
	HMM/54 channel	
	HMM/60 channel	
	DMM/48 channel	
	DMM/96 channel	
	DMM/108 channel	
	DMM/120 channel	
	48-Channel, TI C549-based VoIP feature card (Uses High Density AS53-VOXD DSP modules)	
	60-Channel, TI C549-based VoIP feature card (Uses High Density AS53-VOXD DSP modules)	
	24-Channel, TI C542-based VoIP feature card (First generation, uses AS53-6VOX DSP modules)	
	48-Channel, TI C542-based VoIP feature card (First generation, uses AS53-6VOX DSP modules)	
<b>Modem Cards</b>	MICA modems	
	Microcom 56K modems	

1. The number in the “In” column indicates the Cisco IOS release when the interface was introduced. For example, (4) means an interface was introduced in Cisco IOS Release 12.1(4). If a cell in this column is empty, the interface was included in the initial base release.

## Determining the Software Version

To determine the version of Cisco IOS software running on your Cisco AS5300, log in to the Cisco AS5300 and enter the **show version EXEC** command:

```
router> show version
Cisco Internetwork Operating System Software
IOS (tm) 12.1 Software c5300-i-mz, Version 12.1(6), RELEASE SOFTWARE
```

## Upgrading to a New Software Release

For general information about upgrading to a new software release, see *Cisco IOS Upgrade Ordering Instructions* located at:

[http://www.cisco.com/warp/public/cc/pd/iosw/prodlit/957\\_pp.htm](http://www.cisco.com/warp/public/cc/pd/iosw/prodlit/957_pp.htm)

## Microcode and Modem Code Software

Microcode software images are bundled with the system software image—with the exception of the Channel Interface Processor (CIP) microcode (all system software images). Bundling eliminates the need to store separate microcode images. When the router starts, the system software unpacks the microcode software bundle and loads the proper software on all the interface processor boards. Table 3 lists the current microcode versions for the Cisco AS5300.

You could have received a later version of modem code than the one bundled with the Cisco IOS software. The modem code in Flash memory is mapped to the modems. Unless you fully understand how Cisco IOS software uses modem code, it is important to keep the factory configuration.

The modem code release notes are on CCO and the Documentation CD-ROM:

On CCO at:

**Technical Documents: Documentation Home Page: Access Servers and Access Routers: Firmware and Portware Information**

On the Documentation CD-ROM at:

**Cisco Product Documentation: Access Servers and Access Routers: Firmware and Portware Information**

**Table 3** *Current Modem Code Versions for the Cisco AS5300*

Modem Module	Current Bundled Modem Code Version	Minimum Version Required
Microcom modems	Microcom Version 5.1.20	12.0(5)T and later
MICA modems	MICA portware Version 2.7.1.0	12.0(5)T and later

## Feature Set Tables

The Cisco IOS software is packaged in feature sets consisting of software images—depending on the platform. Each feature set contains a specific set of Cisco IOS features.



### Caution

Cisco IOS images with strong encryption (including, but not limited to 168-bit (3DES) data encryption feature sets) are subject to United States government export controls and have limited distribution. Strong encryption images to be installed outside the United States are likely to require an export license. Customer orders may be denied or subject to delay due to United States government regulations. When applicable, purchaser/user must obtain local import and use authorizations for all encryption strengths. Please contact your sales representative or distributor for more information, or send an e-mail to [export@cisco.com](mailto:export@cisco.com).

Table 4 lists the features and feature sets supported by the Cisco AS5300 in Cisco IOS Release 12.1 and uses the following conventions:

- Yes—The feature is supported in the software image.
- No—The feature is not supported in the software image.



### Note

This feature set table might contain a selected list of features. This table might not be cumulative or list all the features in each image.

Table 4 Feature List by Feature Set for the Cisco AS5300

Feature	Software Images by Feature Set									
	IP	IP Plus	IP Plus IPsec 56	IP Plus IPsec 3DES	Desk-top	Desk-top Plus	Enterprise	Enterprise Plus	Enterprise Plus IPsec 56	Enterprise Plus IPsec 56 3DES
<b>Authentication and Accounting</b>										
Selecting AAA Server Groups Based on DNIS	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Internet</b>										
Extended Simple Mail Transfer Protocol (ESMTP) Accounting in Store and Forward Fax	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
<b>IP Routing</b>										
H.323 Version 2 Support	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
Easy IP (Phase 2) DHCP Server	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	No
Asynchronous Serial Traffic over UDP	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>LAN Support</b>										
Subnetwork Bandwidth Manager	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
CLI String Search	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Parse Bookmarks	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Dynamic Multiple Encaps for Dial-in over ISDN	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
ISDN LAPB-TA	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
L2TP Dialout	No	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes
Large Scale Dialout	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
SS7	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
<b>Management</b>										
Cisco SNMP Version 3	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
CNS Client for Cisco IOS Software	No	No	Yes	Yes	No	No	Yes	Yes	Yes	Yes
CNS client for IOS 12.05(t) (aka IPsec Policy Agent II)	No	No	No	No	No	No	Yes	Yes	Yes	Yes
ISDN MIB RFC 2127	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	No
Multicast Routing Monitor	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Process MIB	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Time-Based Access Lists Using Time Ranges	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

**Table 4 Feature List by Feature Set for the Cisco AS5300 (continued)**

Feature	Software Images by Feature Set									
	IP	IP Plus	IP Plus IPsec 56	IP Plus IPsec 3DES	Desk-top	Desk-top Plus	Enterprise	Enterprise Plus	Enterprise Plus IPsec 56	Enterprise Plus IPsec 56 3DES
<b>Miscellaneous</b>										
Debit Card Accounting and New RADIUS Attributes for IP Telephony	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
Voice over IP Q.SIG Network Transparency for Cisco AS5300	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
<b>Quality of Service</b>										
BERT/TDM Enhancements for Cisco AS5300 8PRI/4T Cards	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Enhanced IVR	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
Service Provider Features for Voice over IP	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Security</b>										
IPsec with Triple-DES	No	No	No	Yes	No	No	No	No	No	Yes
High-Density Voice over IP for Cisco AS5300/Voice Gateway	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
Interactive Voice Response for Cisco Access	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
Resource Pool Management Server	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Resource Pool Management with Direct Remote Services	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Voice Technologies</b>										
Open Settlements Protocol (OSP) for IP Telephony	No	No	Yes	Yes	No	No	No	No	Yes	Yes
Voice over IP	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

## New and Changed Information

The following sections list the new hardware and software feature categories supported by the Cisco AS5300 for Cisco IOS Release 12.1. These categories are broken down into features in Table 4.

- Authentication and Accounting
- Internet
- IP Routing
- LAN Support
- Management

- Quality of Service
- Security
- Voice Technologies

## MIBs

### Current MIBs

If you have an account with CCO, you can find the current list of MIBs supported by Cisco. To reach the Cisco Network Management Toolkit, **Login** to CCO and click **Software Center: Network Mgmt Products: Cisco Network Management Toolkit: Cisco MIB**.

### Deprecated and Replacement MIBs

Old Cisco Management Information Bases (MIBs) will be replaced in a future release. Currently, OLD-CISCO-\* MIBs are being converted into more scalable MIBs—without affecting existing Cisco IOS products or NMS applications. You can update from deprecated MIBs to the replacement MIBs as shown in Table 5.

**Table 5** *Deprecated and Replacement MIBs*

Deprecated MIB	Replacement
OLD-CISCO-APPLETALK-MIB	RFC1243-MIB
OLD-CISCO-CHASSIS-MIB	ENTITY-MIB
OLD-CISCO-CPUK-MIB	To be decided
OLD-CISCO-DECNET-MIB	To be decided
OLD-CISCO-ENV-MIB	CISCO-ENVMON-MIB
OLD-CISCO-FLASH-MIB	CISCO-FLASH-MIB
OLD-CISCO-INTERFACES-MIB	IF-MIB CISCO-QUEUE-MIB
OLD-CISCO-IP-MIB	To be decided
OLD-CISCO-MEMORY-MIB	CISCO-MEMORY-POOL-MIB
OLD-CISCO-NOVELL-MIB	NOVELL-IPX-MIB
OLD-CISCO-SYS-MIB	(Compilation of other OLD* MIBs)
OLD-CISCO-SYSTEM-MIB	CISCO-CONFIG-COPY-MIB
OLD-CISCO-TCP-MIB	CISCO-TCP-MIB
OLD-CISCO-TS-MIB	To be decided
OLD-CISCO-VINES-MIB	CISCO-VINES-MIB
OLD-CISCO-XNS-MIB	To be decided

**Note**

---

*Cisco Management Information Base (MIB) User Quick Reference* is no longer published. If you have an account with CCO, you can find the current list of MIBs supported by Cisco. To reach the *Cisco Network Management Toolkit*, go to CCO, press **Login**, and click to **Software Center: Network Mgmt Products: Cisco Network Management Toolkit: Cisco MIB**.

---

## Important Information

The following section contains important notes about Cisco IOS Release 12.1(6) that can apply to the Cisco AS5300.

### Caveat CSCdr91706 and IOS HTTP Vulnerability

A defect in multiple releases of Cisco IOS software will cause a Cisco router or switch to halt and reload if the IOS HTTP service is enabled, browsing to `http://router-ip/anytext?/` is attempted, and the enable password is supplied when requested. This defect can be exploited to produce a denial of service (DoS) attack.

The vulnerability, identified as Cisco bug ID CSCdr91706, affects virtually all mainstream Cisco routers and switches running Cisco IOS software releases 12.0 through 12.1, inclusive. This is not the same defect as CSCdr36952.

The vulnerability has been corrected and Cisco is making fixed releases available for free to replace all affected IOS releases. Customers are urged to upgrade to releases that are not vulnerable to this defect as shown in detail below.

This vulnerability can only be exploited if the enable password is known or not set.

You are strongly encouraged to read the complete advisory, which is available at <http://www.cisco.com/warp/public/707/ioshttpserverquery-pub.shtml>.

### Enhancement to ppp ipcp Command

The **ppp ipcp** command, which supplies Domain Name System (DNS) or Windows Internet Naming Service (WINS) addresses during IP Control Protocol (IPCP) negotiation, has been enhanced with the reject and accept keywords. These keywords allow enabling or disabling support for the Microsoft IPCP extensions defined by RFC 1877.

## Caveats

Caveats describe unexpected behavior in Cisco IOS software releases. Severity 1 caveats are the most serious caveats; severity 2 caveats are less serious. Severity 3 caveats are moderate caveats, and only select severity 3 caveats are included in the caveats document.

For information on caveats in Cisco IOS Release 12.1, see *Caveats for Cisco IOS Release 12.1*, which lists severity 1 and 2 caveats and select severity 3 caveats for Cisco IOS Release 12.1 and is located on CCO and the Documentation CD-ROM.

**Note**

If you have an account with CCO, you can use Bug Navigator II to find caveats of any severity for any release. To reach Bug Navigator II, go to CCO and press **Login**. Then go to **Software Center: Cisco IOS Software: Cisco Bugtool Navigator II**. Another option is to go to <http://www.cisco.com/support/bugtools>.

## Open Caveats—Release 12.1(6)

The caveat listed in this section are open in Cisco IOS Release 12.1(6).

- CSCdr91652

When a Media Gateway Controller (MGC) places a call on a b-channel that is already in use on a Cisco AS5300 functioning as part of a Network Access Solution (NAS), the NAS might reload with a software-forced crash. This problem can, for example, occur after a failover. There is no workaround.

- CSCdr95699

When a SC2200 Signalling Controller in a Cisco SS7 Interconnect for Access Servers Solution sends a Continuity Test (COT) request to a Cisco AS5300 functioning as part of a NAS, the outgoing modem calls fail on the Cisco AS5300.

Workaround: Do not set a COT percentage on any SC2200 that will be servicing modem calls of this type. Run COT tests manually on these trunks with the **test-cot** command. The command can also be scripted to run automatically as a UNIX chronologically started job.

## Closed or Resolved Caveats—Release 12.1(6)

The caveat listed in this section is resolved in Cisco IOS Release 12.1(6).

- CSCds02173

Making a V.110 call from a Cisco AS5300 that is used as a NAS connected to an SC2200 Signalling Controller in a Cisco SS7 Interconnect for Access Servers Solution results in the call being rejected with the following message:

```
Invalid information element contents
```

This has been resolved in Cisco IOS Release 12.1(6).

## Related Documentation

The following sections describe the documentation available for the Cisco AS5300. These documents consist of hardware and software installation guides, Cisco IOS configuration and command references, system error messages, and other documents.

Documentation is available as printed manuals or electronic documents.

Use these release notes with these documents:

- Release-Specific Documents, page 11
- Platform-Specific Documents, page 11

- Feature Modules, page 12
- Cisco IOS Software Documentation Set, page 12

## Release-Specific Documents

The following documents are specific to Cisco IOS Release 12.1 and are located on CCO and the Documentation CD-ROM:

- *Cross-Platform Release Notes for Cisco IOS Release 12.1*

On CCO at:

**Technical Documents: Documentation Home Page: Cisco IOS Software Configuration: Cisco IOS Release 12.1**

On the Documentation CD-ROM at:

**Cisco Product Documentation: Cisco IOS Software Configuration: Cisco IOS Release 12.1: Release Notes: Cross-Platform Release Notes**

- Product bulletins, field notices, and other release-specific documents on CCO at:

**Technical Documents**

- *Caveats for Cisco IOS Release 12.1*

See *Caveats for Cisco IOS Release 12.1*, which contain caveats applicable to all platforms for all maintenance releases of Release 12.1.

On CCO at:

**Technical Documents: Documentation Home Page: Cisco IOS Software Configuration: Cisco IOS Release 12.1: Caveats**

On the Documentation CD-ROM at:

**Cisco Product Documentation: Cisco IOS Software Configuration: Cisco IOS Release 12.1: Caveats**



**Note**

If you have an account with CCO, you can use Bug Navigator II to find caveats of any severity for any release. To reach Bug Navigator II, go to CCO and press **Login**. Then go to **Software Center: Cisco IOS Software: Cisco Bugtool Navigator II**. Another option is to go to <http://www.cisco.com/support/bugtools>.

## Platform-Specific Documents

These documents are available for the Cisco AS5300 on CCO and the Documentation CD-ROM:

- *Cisco AS5300 Universal Access Server Quick Start Guide (with Fast Step)*
- *Cisco AS5300 Universal Access Server Chassis Installation Guide*
- *Cisco AS5300 Universal Access Server Module Installation Guide*
- *Cisco AS5300 Universal Access Server Software Configuration Guide*
- *Configuring Cisco IOS Software Features*
- Cisco IOS Release Notes

- *Dial Case Study*
- Port Information—Firmware/portware release notes, configuration notes, command references, FAQs (frequently asked questions)
- Documentation for Spare Parts—Removal and replacement procedures for modem modules, feature cards, power supply
- *Regulatory Compliance and Safety Information*
- *Single and High Density VolP Support for the Cisco AS5300/Voice Gateway*
- *Media Gateway Control Protocol for the Cisco AS3500 Voice/Gateway*

On CCO at:

**Technical Documents: Documentation Home Page: Access Servers and Access Routers: Access Servers: Cisco AS5300**

On the Documentation CD-ROM at:

**Cisco Product Documentation: Access Servers and Access Routers: Access Servers: Cisco AS5300**

## Feature Modules

Feature modules describe new features supported by Cisco IOS Release 12.1 and are updates to the Cisco IOS documentation set. A feature module consists of a brief overview of the feature, benefits, configuration tasks, and a command reference. As updates, the feature modules are available online only. Feature module information is incorporated in the next printing of the Cisco IOS documentation set.

On CCO at:

**Technical Documents: Documentation Home Page: Cisco IOS Software Configuration: Cisco IOS Release 12.1: New Feature Documentation**

On the Documentation CD-ROM at:

**Cisco Product Documentation: Cisco IOS Software Configuration: Cisco IOS Release 12.1: New Feature Documentation**

## Cisco IOS Software Documentation Set

The Cisco IOS software documentation set consists of the Cisco IOS configuration guides, Cisco IOS command references, and several other supporting documents that are shipped with your order in electronic form on the Documentation CD-ROM—unless you specifically ordered the printed versions.

## Documentation Modules

Each module in the Cisco IOS documentation set consists of two books: a configuration guide and a corresponding command reference. Chapters in a configuration guide describe protocols, configuration tasks, Cisco IOS software functionality, and contain comprehensive configuration examples. Chapters in a command reference provide complete command syntax information. Use each configuration guide with its corresponding command reference.

On CCO and the Documentation CD-ROM, two master hot-linked documents provide information for the Cisco IOS software documentation set.

On CCO at:

**Technical Documents: Documentation Home Page: Cisco IOS Software Configuration: Cisco IOS Release 12.1: Configuration Guides and Command References**

On the Documentation CD-ROM at:

**Cisco Product Documentation: Cisco IOS Software Configuration: Cisco IOS Release 12.1: Configuration Guides and Command References**

## Cisco IOS Release 12.1 Documentation Set

Table 6 describes the contents of the Cisco IOS Release 12.1 software documentation set, which is available in electronic form and in printed form if so ordered.



**Note**

You can find the most current Cisco IOS documentation on CCO and the Documentation CD-ROM. These electronic documents may contain updates and modifications made after the hard-copy documents were printed.

On CCO at:

**Technical Documents: Documentation Home Page: Cisco IOS Software Configuration: Cisco IOS Release 12.1**

On the Documentation CD-ROM at:

**Cisco Product Documentation: Cisco IOS Software Configuration: Cisco IOS Release 12.1**

**Table 6 Cisco IOS Software Release 12.1 Documentation Set**

Books	Chapter Topics
<ul style="list-style-type: none"> <li>• <i>Configuration Fundamentals Configuration Guide</i></li> <li>• <i>Configuration Fundamentals Command Reference</i></li> </ul>	Configuration Fundamentals Overview Cisco IOS User Interfaces File Management System Management
<ul style="list-style-type: none"> <li>• <i>Bridging and IBM Networking Configuration Guide</i></li> <li>• <i>Bridging and IBM Networking Command Reference</i></li> </ul>	Transparent Bridging Source-Route Bridging Token Ring Inter-Switch Link Remote Source-Route Bridging DLSw+ STUN and BSTUN LLC2 and SDLC IBM Network Media Translation DSPU and SNA Service Point SNA Frame Relay Access Support APPN Cisco Database Connection NCIA Client/Server Topologies Cisco Mainframe Channel Connection Airline Product Set

**Table 6 Cisco IOS Software Release 12.1 Documentation Set (continued)**

Books	Chapter Topics
<ul style="list-style-type: none"> <li>• <i>Dial Solutions Configuration Guide</i></li> <li>• <i>Dial Solutions Command Reference</i></li> </ul>	X.25 over ISDN Appletalk Remote Access Asynchronous Callback, DDR, PPP, SLIP Bandwidth Allocation Control Protocol ISDN Basic Rate Service ISDN Caller ID Callback PPP Callback for DDR Channelized E1 & T1 Dial Backup for Dialer Profiles Dial Backup Using Dialer Watch Dial Backup for Serial Lines Peer-to-Peer DDR with Dialer Profiles DialOut Dial-In Terminal Services Dial-on-Demand Routing (DDR) Dial Backup Dial-Out Modem Pooling Large-Scale Dial Solutions Cost-Control Solutions Virtual Private Dialup Networks Dial Business Solutions and Examples
<ul style="list-style-type: none"> <li>• <i>Cisco IOS Interface Configuration Guide</i></li> <li>• <i>Cisco IOS Interface Command Reference</i></li> </ul>	Interface Configuration Overview LAN Interfaces Logical Interfaces Serial Interfaces
<ul style="list-style-type: none"> <li>• <i>Network Protocols Configuration Guide, Part 1</i></li> <li>• <i>Network Protocols Command Reference, Part 1</i></li> </ul>	IP Overview IP Addressing and Services IP Routing Protocols
<ul style="list-style-type: none"> <li>• <i>Network Protocols Configuration Guide, Part 2</i></li> <li>• <i>Network Protocols Command Reference, Part 2</i></li> </ul>	AppleTalk Novell IPX
<ul style="list-style-type: none"> <li>• <i>Network Protocols Configuration Guide, Part 3</i></li> <li>• <i>Network Protocols Command Reference, Part 3</i></li> </ul>	Network Protocols Overview Apollo Domain Banyan VINES DECnet ISO CLNS XNS
<ul style="list-style-type: none"> <li>• <i>Security Configuration Guide</i></li> <li>• <i>Security Command Reference</i></li> </ul>	AAA Security Services Security Server Protocols Traffic Filtering and Firewalls IP Security and Encryption Passwords and Privileges Neighbor Router Authentication IP Security Options
<ul style="list-style-type: none"> <li>• <i>Cisco IOS Switching Services Configuration Guide</i></li> <li>• <i>Cisco IOS Switching Services Command Reference</i></li> </ul>	Switching Services Switching Paths for IP Networks Virtual LAN (VLAN) Switching and Routing

**Table 6** Cisco IOS Software Release 12.1 Documentation Set (continued)

Books	Chapter Topics
<ul style="list-style-type: none"> <li>• <i>Wide-Area Networking Configuration Guide</i></li> <li>• <i>Wide-Area Networking Command Reference</i></li> </ul>	Wide-Area Network Overview ATM Frame Relay SMDS X.25 and LAPB
<ul style="list-style-type: none"> <li>• <i>Voice, Video, and Home Applications Configuration Guide</i></li> <li>• <i>Voice, Video, and Home Applications Command Reference</i></li> </ul>	Voice over IP Voice over Frame Relay Voice over ATM Voice over HDLC Frame Relay-ATM Internetworking Synchronized Clocks Video Support Universal Broadband Features
<ul style="list-style-type: none"> <li>• <i>Quality of Service Solutions Configuration Guide</i></li> <li>• <i>Quality of Service Solutions Command Reference</i></li> </ul>	Policy-Based Routing QoS Policy Propagation via BGP Committed Access Rate Weighted Fair Queueing Custom Queueing Priority Queueing Weighted Random Early Detection Scheduling Signaling RSVP Packet Drop Frame Relay Traffic Shaping Link Fragmentation RTP Header Compression
<ul style="list-style-type: none"> <li>• <i>Cisco IOS Configuration Guide Master Index</i></li> <li>• <i>Cisco IOS Command Reference Master Index</i></li> <li>• <i>Cisco IOS Software Command Summary</i></li> <li>• <i>Dial Solutions Quick Configuration Guide</i></li> <li>• <i>System Error Messages</i></li> <li>• <i>Debug Command Reference</i></li> </ul>	

**Note**

*Cisco Management Information Base (MIB) User Quick Reference* is no longer published. If you have an account with CCO, you can find the latest list of MIBs supported by Cisco. To reach the *Cisco Network Management Toolkit*, go to CCO, press **Login**, and click to **Software Center: Network Mgmt Products: Cisco Network Management Toolkit: Cisco MIB**.

# Obtaining Documentation

The following sections provide sources for obtaining documentation from Cisco Systems.

## World Wide Web

You can access the most current Cisco documentation on the World Wide Web at the following sites:

- <http://www.cisco.com>
- <http://www-china.cisco.com>
- <http://www-europe.cisco.com>

## Documentation CD-ROM

Cisco documentation and additional literature are available in a CD-ROM package, which ships with your product. The Documentation CD-ROM is updated monthly and may be more current than printed documentation. The CD-ROM package is available as a single unit or as an annual subscription.

## Ordering Documentation

Cisco documentation is available in the following ways:

- Registered Cisco Direct Customers can order Cisco Product documentation from the Networking Products MarketPlace:  
[http://www.cisco.com/cgi-bin/order/order\\_root.pl](http://www.cisco.com/cgi-bin/order/order_root.pl)
- Registered Cisco.com users can order the Documentation CD-ROM through the online Subscription Store:  
<http://www.cisco.com/go/subscription>
- Nonregistered Cisco.com users can order documentation through a local account representative by calling Cisco corporate headquarters (California, USA) at 408 526-7208 or, in North America, by calling 800 553-NETS(6387).

## Documentation Feedback

If you are reading Cisco product documentation on the World Wide Web, you can submit technical comments electronically. Click **Feedback** in the toolbar and select **Documentation**. After you complete the form, click **Submit** to send it to Cisco.

You can e-mail your comments to [bug-doc@cisco.com](mailto:bug-doc@cisco.com).

To submit your comments by mail, for your convenience many documents contain a response card behind the front cover. Otherwise, you can mail your comments to the following address:

Cisco Systems, Inc.  
Document Resource Connection  
170 West Tasman Drive  
San Jose, CA 95134-9883

We appreciate your comments.

# Obtaining Technical Assistance

Cisco provides Cisco.com as a starting point for all technical assistance. Customers and partners can obtain documentation, troubleshooting tips, and sample configurations from online tools. For Cisco.com registered users, additional troubleshooting tools are available from the TAC website.

## Cisco.com

Cisco.com is the foundation of a suite of interactive, networked services that provides immediate, open access to Cisco information and resources at anytime, from anywhere in the world. This highly integrated Internet application is a powerful, easy-to-use tool for doing business with Cisco.

Cisco.com provides a broad range of features and services to help customers and partners streamline business processes and improve productivity. Through Cisco.com, you can find information about Cisco and our networking solutions, services, and programs. In addition, you can resolve technical issues with online technical support, download and test software packages, and order Cisco learning materials and merchandise. Valuable online skill assessment, training, and certification programs are also available.

Customers and partners can self-register on Cisco.com to obtain additional personalized information and services. Registered users can order products, check on the status of an order, access technical support, and view benefits specific to their relationships with Cisco.

To access Cisco.com, go to the following website:

<http://www.cisco.com>

## Technical Assistance Center

The Cisco TAC website is available to all customers who need technical assistance with a Cisco product or technology that is under warranty or covered by a maintenance contract.

## Contacting TAC by Using the Cisco TAC Website

If you have a priority level 3 (P3) or priority level 4 (P4) problem, contact TAC by going to the TAC website:

<http://www.cisco.com/tac>

P3 and P4 level problems are defined as follows:

- P3—Your network performance is degraded. Network functionality is noticeably impaired, but most business operations continue.
- P4—You need information or assistance on Cisco product capabilities, product installation, or basic product configuration.

In each of the above cases, use the Cisco TAC website to quickly find answers to your questions.

To register for Cisco.com, go to the following website:

<http://www.cisco.com/register/>

If you cannot resolve your technical issue by using the TAC online resources, Cisco.com registered users can open a case online by using the TAC Case Open tool at the following website:

<http://www.cisco.com/tac/caseopen>

## Contacting TAC by Telephone

If you have a priority level 1 (P1) or priority level 2 (P2) problem, contact TAC by telephone and immediately open a case. To obtain a directory of toll-free numbers for your country, go to the following website:

<http://www.cisco.com/warp/public/687/Directory/DirTAC.shtml>

P1 and P2 level problems are defined as follows:

- P1—Your production network is down, causing a critical impact to business operations if service is not restored quickly. No workaround is available.
- P2—Your production network is severely degraded, affecting significant aspects of your business operations. No workaround is available.

---

This document is to be used in conjunction with the documents listed in the “Related Documentation” section on page 10.

AtmDirector, Browse with Me, CCDA, CCDE, CDDP, CCIE, CCNA, CCNP, CCSI, CD-PAC, *CiscoLink*, the Cisco NetWorks logo, the Cisco Powered Network logo, Cisco Systems Networking Academy, the Cisco Systems Networking Academy logo, Fast Step, Follow Me Browsing, FormShare, FrameShare, GigaStack, IGX, Internet Quotient, IP/VC, iQ Breakthrough, iQ Expertise, iQ FastTrack, the iQ Logo, iQ Net Readiness Scorecard, MGX, the Networkers logo, *Packet*, PIX, RateMUX, ScriptShare, SlideCast, SMARTnet, TransPath, Voice LAN, Wavelength Router, WebViewer are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, Empowering the Internet Generation, are service marks of Cisco Systems, Inc.; and Aironet, ASIST, BPX, Catalyst, Cisco, the Cisco Certified Internetwork Expert Logo, Cisco IOS, the Cisco IOS logo, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Enterprise/Solver, EtherChannel, EtherSwitch, FastHub, IOS, IP/TV, LightStream, Post-Routing, Pre-Routing, Registrar, StrataView Plus, Stratm, SwitchProbe, TeleRouter, and VCO are registered trademarks of Cisco Systems, Inc. or its affiliates in the U.S. and certain other countries.

All other brands, names, or trademarks mentioned in this document or Web site are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0011R)

Copyright © 2000-2001, Cisco Systems, Inc.  
All rights reserved.

