



# Release Notes for the Cisco PDSN 2.1 Feature in Cisco IOS Release 12.3(11)YF4

---

15 September 2005

Cisco IOS Release 12.3(11)YF4 is a special release that is based on Cisco IOS Release 12.3, with the addition of enhancements to the Cisco Packet Data Serving Node (Cisco PDSN) feature. Cisco IOS Release 12.3(11)YF1 is optimized for PDSN Release 2.1 on the Cisco 7206VXR router, the Cisco 7206VXR Router with Cisco NPE-G1 Network Processing Engine, the Cisco Multi-Processor WAN Application Module on the Cisco 6500 Catalyst switch platform, and the 7600 Internet router platform.

## Contents

These release notes include important information and caveats for the Cisco PDSN software feature provided in Cisco IOS 12.3(11)YF4 for the Cisco 7206VXR series router, the Cisco 7609 Internet Router, and Cisco 6500 Catalyst Switch platforms.

Caveats for Cisco IOS Release 12.3 can be found on CCO at:

[http://www.cisco.com/en/US/products/sw/iosswrel/ps5187/tsd\\_products\\_support\\_series\\_home.html](http://www.cisco.com/en/US/products/sw/iosswrel/ps5187/tsd_products_support_series_home.html)

Release notes for Cisco 7000 Family for Release 12.3T can be found on CCO at:

[http://www.cisco.com/en/US/products/sw/iosswrel/ps5207/prod\\_release\\_notes\\_list.html](http://www.cisco.com/en/US/products/sw/iosswrel/ps5207/prod_release_notes_list.html)

Release notes for the Cisco 6000 Family for 12.3T can be found on CCO at:

[http://www.cisco.com/en/US/products/sw/iosswrel/ps5207/prod\\_release\\_notes\\_list.html](http://www.cisco.com/en/US/products/sw/iosswrel/ps5207/prod_release_notes_list.html)

This release note includes the following topics:

- [Contents, page 1](#)
- [Introduction, page 2](#)
- [System Requirements, page 2](#)
- [New and Changed Information, page 6](#)
- [Packet Data Serving Node Software Features in Release 12.3\(11\)YF4, page 6](#)
- [Caveats, page 7](#)



---

**Corporate Headquarters:**  
**Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA**

Copyright © 2003. Cisco Systems, Inc. All rights reserved.

- [Related Documentation, page 36](#)
- [Obtaining Documentation, page 40](#)
- [Obtaining Technical Assistance, page 41](#)

## Introduction

Cisco PDSN is an IOS software feature that enables a Cisco 7206VXR router, or a Multi-Processor WAN Application Module (MWAM) on a Catalyst 6500 Switch or 7600 Internet router to function as a gateway between the wireless Radio Access Network (RAN) and the Internet. With Cisco PDSN enabled on a router, a stationary or roaming mobile user can access the Internet, a corporate network intranet, or Wireless Application Protocol (WAP) services. Cisco PDSN supports both Simple IP operation and Mobile IP operation.

## System Requirements

This section describes the system requirements for Cisco IOS Release 12.3(11)YF4:

- [Memory Requirements, page 2](#)
- [Hardware Supported, page 3](#)
- [Software Compatibility, page 3](#)
- [Determining the Software Version, page 4](#)
- [Upgrading to a New Software Release, page 4](#)
- [MIBs, page 4](#)

## Memory Requirements

[Table 1](#) shows the memory requirements for the PDSN Software Feature Set that supports the Cisco 7206VXR router, the Cisco 7206VXR Router with Cisco NPE-G1 Network Processing Engine, the MWAM card on the Cisco 6500 Catalyst Switch platform and 7600 Internet router platform. The table also lists the memory requirements for the IP Standard Feature Set (for the Home Agent [HA]).

**Table 1** Memory Requirements for the Cisco 7206VXR Router and MWAM on the 6500 Catalyst Switch and 7600 Router

Platform	Software Feature Set	Image Name	Flash Memory Required	DRAM Memory Required	Runs From
Cisco 7206VXR Router	PDSN Software Feature Set	c7200-c6is-mz.123-11.YF4 c7200-c6ik9s-mz.123-11.YF4	20 MB	512 MB	RAM
Cisco 6500 Catalyst Switch	PDSN Software Feature Set	c6svc5fmwam-c6is-mz (This is a bundled image)	40MB	512MB	RAM
Cisco 7600 Internet Router	PDSN Software Feature Set	c6svc5fmwam-c6is-mz (This is a bundled image)	40MB	512MB	RAM
Cisco 7206VXR with NPE-G1	PDSN Software Feature Set	c7200-c6is-mz.123-11.YF4 c7200-c6ik9s-mz.123-11.YF4	40MB	512MB	RAM

## Hardware Supported

Cisco IOS Release 12.3(11)YF4 is optimized for PDSN Release 2.1 on Cisco 7206VXR router, the Cisco 7206VXR Router with Cisco NPE-G1 Network Processing Engine, the MWAM card on the Cisco 6500 Catalyst Switch platform and 7600 Internet router platform.

A Hardware-Software Compatibility Matrix is available on CCO for users with CCO login accounts. This matrix allows users to search for supported hardware components by entering a Cisco platform and IOS Release. The Hardware-Software Compatibility Matrix tool is available at the following URL:

<http://www.cisco.com/cgi-bin/front.x/Support/HWSWmatrix/hwswwmatrix.cgi>

## Software Compatibility

Cisco IOS Release 12.3(11)YF4 is a special release that is developed on Cisco IOS Release 12.3.

Cisco IOS Release 12.3(11)YF4 supports the same features that are in Cisco IOS Release 12.3, with the addition of the PDSN Release 2.1 feature.

## Determining the Software Version

To determine the version of Cisco IOS software running on your router, log in to the router and enter the **show version EXEC** command:

```
Router#show version
mwt5-6509a-06-4#sh ver
Cisco IOS Software, MWAM Software (MWAM-C6IS-M), Version 12.3(11)YF4, RELEASE SOFTWARE
(fc1) Technical Support: http://www.cisco.com/techsupport Copyright (c) 1986-2005 by Cisco
Systems, Inc.
Compiled Mon 25-Jul-05 15:24 by ssearch

ROM: System Bootstrap, Version 12.2(11)YS2 RELEASE SOFTWARE

mwt5-6509a-06-4 uptime is 2 hours, 9 minutes System returned to ROM by reload at 07:35:31
UTC Wed Jul 6 2005 System restarted at 02:31:05 UTC Tue Jul 26 2005 System image file is
"svcmwam-c6is-mz"

Cisco MWAM (MWAM) processor with 473088K/32768K bytes of memory.
SB-1 CPU at 700MHz, Implementation 1025, Rev 0.2

Last reset from power-on
1 Gigabit Ethernet interface
511K bytes of non-volatile configuration memory.

Configuration register is 0x4

mwt5-6509a-06-4#
```

## Upgrading to a New Software Release

For information on upgrading to a new software release, see the product bulletin *Cisco IOS Software Upgrade Ordering Instructions* located at:

[http://www.cisco.com/warp/public/cc/pd/iosw/prodlit/957\\_pp.htm](http://www.cisco.com/warp/public/cc/pd/iosw/prodlit/957_pp.htm)

## MIBs

Old Cisco Management Information Bases (MIBs) will be replaced in a future release. Currently, OLD-CISCO-\* MIBs are being converted into more scalable MIBs—without affecting existing Cisco IOS products or NMS applications. You can update from deprecated MIBs to the replacement MIBs as shown in [Table 2](#).

**Table 2** *Deprecated and Replacement MIBs*

Deprecated MIB	Replacement
OLD-CISCO-APPLETALK-MIB	RFC1243-MIB
OLD-CISCO-CHASSIS-MIB	ENTITY-MIB
OLD-CISCO-CPUK-MIB	To be decided
OLD-CISCO-DECNET-MIB	To be decided
OLD-CISCO-ENV-MIB	CISCO-ENVMON-MIB
OLD-CISCO-FLASH-MIB	CISCO-FLASH-MIB

**Table 2** *Deprecated and Replacement MIBs (continued)*

<b>Deprecated MIB</b>	<b>Replacement</b>
OLD-CISCO-INTERFACES-MIB	IF-MIB CISCO-QUEUE-MIB
OLD-CISCO-IP-MIB	To be decided
OLD-CISCO-MEMORY-MIB	CISCO-MEMORY-POOL-MIB
OLD-CISCO-NOVELL-MIB	NOVELL-IPX-MIB
OLD-CISCO-SYS-MIB	(Compilation of other OLD* MIBs)
OLD-CISCO-SYSTEM-MIB	CISCO-CONFIG-COPY-MIB
OLD-CISCO-TCP-MIB	CISCO-TCP-MIB
OLD-CISCO-TS-MIB	To be decided
OLD-CISCO-VINES-MIB	CISCO-VINES-MIB
OLD-CISCO-XNS-MIB	To be decided

## Cisco IOS Feature Sets

The Cisco IOS software is packaged in feature sets consisting of software images—depending on the platform. Each feature set contains a specific set of Cisco IOS features.

Cisco IOS Release 12.3(11)YF4 supports the same feature sets as Cisco Release 12.3, with the exception that Cisco Release 12.3(11)YF4 includes the PDSN feature. The PDSN feature is optimized for the Cisco 7206VXR router, the Cisco MWAM card on the 6500 Catalyst Switch and 7600 Internet router, and the Cisco NPE-G1 router.



### Caution

Cisco IOS images with strong encryption (including, but not limited to 168-bit (3DES) data encryption feature sets) are subject to United States government export controls and have limited distribution. Strong encryption images to be installed outside the United States are likely to require an export license. Customer orders may be denied or subject to delay due to United States government regulations. When applicable, purchaser/user must obtain local import and use authorizations for all encryption strengths. Please contact your sales representative or distributor for more information, or send an e-mail to [export@cisco.com](mailto:export@cisco.com).

## New and Changed Information

There are no new features for the PDSN 2.1 Release in Cisco IOS Release 12.3(11)YF4. The following information was new for the PDSN 2.1 Release in Cisco IOS Release 12.3(11)YF3:

### Mobile IP Dynamic Home Address Deletes Older Sessions With Different IMSI

The PDSN cannot recognize 1xRTT to EVDO as a handoff due to a change of IMSI. The result is that the “cdma-reason-ind” in the account stop message will not reflect the same.

By default, the PDSN keeps the first call session if the Mobile does a static home address. In this release, the PDSN supports deleting the first call session for dynamic home address cases (1x-RTT to EVDO handoff where IMSI changes during the handoff).

The old call scenario is established as follows:

1. Mobile Node with IMSI = imsi1, NAI = nai1 establishes session.
2. When PDSN receives an RRQ from the same mobile node with the same NAI but with different IMSI (with IMSI = imsi2, NAI = nai1), currently a new session does not come up on the PDSN, and old session remains.
3. During the mobile handoff between 1XRTT and EVDO call, handoff will not succeed due to the above behaviour of PDSN.

A new CLI is introduced in this release that allows you to delete the old session. When you issue **ip mobile cdma imsi dynamic** command, the PDSN releases the old session and allow the new session to come up.

## Packet Data Serving Node Software Features in Release 12.3(11)YF4

The Cisco IOS Release 12.3(11)YF4 supports the same feature sets as Cisco Release 12.3, with the exception that Cisco Release 12.3(11)YF4 includes the PDSN feature. The PDSN 2.1 feature is optimized for the Cisco 7206VXR router, the Cisco MWAM card on the 6500 Catalyst Switch and 7600 Internet Router, and the Cisco NPE-G1 router, and includes the following features:

- Mobile IP Dynamic Home Address Deletes Older Sessions With Different IMSI
- Protocol Layering and RP Connections
- PPPoGRE RP Interface
- A11 Session Update
- SDB Indicator Marking
- Resource Revocation for Mobile IP
- Packet of Disconnect
- IS-835 Prepaid Support
- Prepaid Billing
- Mobile IP Call Processing Per Second Improvements
- IS-835-B Compliant Static IPsec
- On-Demand Address Pools (ODAP)

- Always On Feature
- NPE-G1 Platform Support
- PDSN Cluster Controller / Member Architecture
- PDSN MIB Enhancement
- Conditional Debugging Enhancements
- PDSN Cluster Controller / Member Architecture
- PDSN MIB Enhancement
- Cisco Proprietary Prepaid Billing
- 3 DES Encryption
- Mobile IP IPsec
- Hardware IPsec Acceleration Using IPsec Acceleration Module—Static IPsec
- 1xEV-DO Support
- Integrated Foreign Agent (FA)
- AAA Support
- Packet Transport for VPDN
- Proxy Mobile IP
- Multiple Mobile IP Flows
- PDSN Clustering Peer-to-Peer and Controller / Member Architecture

All other software features in Cisco IOS Release 12.3 are described in the documentation for Cisco IOS Release 12.3, which can be found at:

[http://www.cisco.com/en/US/products/sw/iosswrel/tsd\\_products\\_support\\_category\\_home.html](http://www.cisco.com/en/US/products/sw/iosswrel/tsd_products_support_category_home.html)

## Caveats

Caveats describe unexpected behavior in Cisco IOS software releases. Severity 1 caveats are the most serious caveats; severity 2 caveats are less serious.

Caveats for Cisco IOS Releases 12.3 can be found on CCO at [http://www.cisco.com/en/US/products/sw/iosswrel/ps5187/prod\\_release\\_notes\\_list.html](http://www.cisco.com/en/US/products/sw/iosswrel/ps5187/prod_release_notes_list.html)

The “[Open Caveats](#)” section lists open caveats that apply to the current release and might also apply to previous releases.

The “[Resolved Caveats](#)” section lists caveats resolved in a particular release, which may have been open in previous releases.



### Note

If you have an account with CCO, you can use Bug Navigator II to find caveats of any severity for any release. You can reach Bug Navigator II on CCO at **Software Center: Cisco IOS Software: Cisco Bug Toolkit: Cisco Bugtool Navigator II**, or at <http://www.cisco.com/support/bugtools>.

## Open Caveats

There are no new unresolved caveats in Cisco IOS Release 12.3(11)YF4.

The following caveats are unresolved in Cisco IOS Release 12.3(11)YF3:

- CSCee74242—Flow Count Incorrect When Prepaid Flows Get Deleted

Total flow count displayed in the **show cdma pdsn** output does not match the actual number of flows present on the box.

This occurs only for prepaid sessions on Cisco PDSN.

**Workaround:** none.
- CSCef31289—Unsupported Attr Debugs While Opening Sessions in PDSN

On a Cisco PDSN running the Cisco IOS 12.3(8)XW R2.0 PDSN image, on opening a session with radius debugs enabled, the "AAA Unsupported Attr" debug messages are printed even though no functionality is affected.

**Workaround:** none.
- CSCef36788—Downstream Throughput Lower Than Expected Number by 10%

Downstream packet throughput for the Cisco PDSN R2.0 release has degraded. Throughput on the 7200 NPE-G1 and MWAM platform is 10% lower than target numbers.

This condition occurs when packet size is 512 Bytes and traffic is pumped on all 20K sessions.

**Workaround:** none.
- CSCef39494—Prepaid MIP Flow Not Deleted on Quota Expiry

On a Cisco router running Release 2.0 PDSN software, when multiple prepaid flows are opened for the same user and traffic is sent through a single flow so as to cross the threshold and quota granted, the PDSN does not close the flow. However, traffic through the flow is not switched as expected.

This symptom occurs when prepaid accounting is enabled, and multiple Mobile IP prepaid flows are opened for the same user.

**Workaround:** none.
- CSCef40729—Session is Not Cleared in PDSN With Tunnel Scalability Turned Off

A Mobile IP session, created with UDP tunneling between the HA and PDSN, does not get cleared when the session is closed from MN.

**Workaround:** use other modes of tunneling like, IPINIP or GRE between the PDSN and HA.
- CSCef40742—PDSN Accepts Value 0 for cCdmaSessionPdsnMaxFailHistory from NMS.

On a Cisco router running R2.0 Packet Data Serving Node (PDSN) Software, the CISCO-CDMA-PDSN-MIB counter cCdmaSessionPdsnMaxFailHistory accepts a value of zero (0) when configured through NMS.

**Workaround:** none.
- CSCef54687—Incorrect Disconnect Reason Send For Prepaid PMIP Flow

On a Cisco router running Release 2.0 PDSN software, for a volume based prepaid proxy mobile IP flow with resource revocation enabled, when the PDSN deletes prepaid flow on receiving the resource revocation request from the HA, the PDSN sets the "disconnect reason" as "client service termination" instead of "remote forced disconnect" in online access-request.

This symptom occurs for revocation enabled proxy mobile IP prepaid flows alone.

**Workaround:** none.

- CSCef61626—MSID Flow is Opened When Quota Provided Has Both Volume and Duration Attribute

On a Cisco router running Release 2.0 PDSN software, an MSID flow is opened when the quota allocated by HAAA has both volume and duration attributes

This symptom only occurs for MSID flows.

**Workaround:** none.

- CSCef61637—MSID Flow is Opened For Undefined PPAQ

On a Cisco Router running Release 2.0 PDSN software, an MSID flow is opened without prepaid capability when the **SelectedforSession** attribute has an incorrect value and PPAQ value is received in Access Accept.

The session should have been terminated in this case.

This symptom occurs for msid flow, when the SelectedforSession attribute has an incorrect value and PPAQ value is received in Access Accept.

**Workaround:** none.

- CSCef64126—CDMA IPsec Support for VRF and HA-SLB.

Cisco PDSN Release 2.0 currently supports CDMA IPsec only for non-VRF MIP flows. The PDSN needs to support CDMA IPsec for VRF flows also.

**Workaround:** none.

- CSCef68963—Incorrect CISCO-MOBILE-IP-MIB Counter Values

On a Cisco router running R2.0 Packet Data Serving Node (PDSN) or Home Agent Software, the CISCO-MOBILE-IP-MIB counters "cmiFaRegVisitorRegFlagsRev1" and "cmiSecAssoc" table entries show incorrect values.

**Workaround:** none.

- CSCef92130—CDMA IPsec Fails When Packets Are Sent Over Different Interface

On a Cisco Router running PDSN R2.0 software with CDMA IPsec configured, if the outgoing interface is changed (example due to OSPF cost), then packets from PDSN go unencrypted.

**Workaround:** ensure that all MIP packets are sent over the interface on which crypto maps get applied. For interface redundancy, port channel configuration may be used.

- CSCeg83033—G1 and G16 Counter Value Mismatch When Compliance IS835c Configured

On a Cisco router running Release 2.1 PDSN software, with the **cdma pdsn compliance is835c account ipmobile control-packets** CLI configured to account for Mobile IP control packets on G1 and G2 counters, the values displayed on G1 and G16 do not match.

This issue occurs on R2.1 PDSN images. Opening a MIP flow, we found that the values displayed on G1 and G16 do not match. Given that, there is no traffic sent through the flow, these values should be the same.

**Workaround:** none.

- CSCin75685—A11 Update Other Reason Incorrect For Closed RP Session Open/Close

When a closed RP session is opened and closed on the Packet Data Service Node (PDSN), the statistics counter update reason "other" shows invalid value.

This condition is seen only when a closed RP session is opened and closed

**Workaround:** none. Since the A11 update counter is not used for closed RP sessions on the PDSN, this counter can be ignored.

- CSCin78778—Session-down Counter Increments Even When There is no Session

On a Cisco router running PDSN R2.0 image configured as Cluster Controller, the Session-down counter is incremented even if there are no active sessions on any of its members.

**Workaround:** none.
- CSCin78831—Cluster Member Displayed Twice in show Command Display

Cluster members are displayed twice in the show cdma pdsn cluster controller member load command.

This condition occurs only when all members except one are removed from the controller.

**Workaround:** none.
- CSCin85270—IPsec Tunnel Torn Down Before Revocation Completion for PMIP Session

The Cisco PDSN closes the IPsec tunnel and cannot decrypt and process revocation acknowledgements from the Home Agent under the following scenario:

  - CDMA IPsec is enabled on the PDSN.
  - Revocation is triggered on the PDSN for a proxy mobileip session.
  - No more mobiles are connected to the corresponding Home Agent (i.e., the PDSN closes the mobileip tunnel)

**Workaround:** none. This is a cosmetic issue; it happens rarely and not processing revocation acknowledgements does not break any functionality.
- CSCin88147—Traceback Found While PDSN Cluster Controller CLI

On a Cisco router running PDSN software, traceback is found while configuring "cdma pdsn cluster controller interface <interface-name>"

This issue occurs under the following conditions:

  - a. Configure the HSRP ACTIVE/STANDBY in the controllers.
  - b. Configure the cluster in both the controllers.

**Workaround:** none.
- CSCin88503—PDSN Crashed During Handoff

Cisco PDSN running 12.3(11)YF image may crash while handoff of a session happens from one PCF to another.

This issue occurs during a PCF to PCF handoff; however, this is a rare condition.

**Workaround:** issue the **cdma pdsn compliance is835a handoff** command.
- CSCin94219—ClosedRP PDSN Reloads During CRP tunnel Going Down

Cisco PDSN enabled for Closed RP feature reloads, when the Closed RP PCF opens multiple L2TP tunnels with the PDSN and distributes the Closed RP sessions among these L2TP tunnels.

**Workaround:** none.

- CSCsa44570—PDSN Member Info Not Synching With Standby Controller.

On Cisco router running Release 2.0 PDSN software, the PDSN Member Info is not getting synched from the active to the standby PDSN controller if the **redundancy inter-device** command has been configured on the controller. This rules out the possibility of configuring the ODAP server redundancy on the PDSN controllers.

This behaviour is seen only if the **redundancy inter-device** command has been configured on the processor. The PDSN controller redundancy works fine if this CLI is not configured on the processor.

**Workaround:** do not configure ODAP server redundancy on the controllers.

- CSCsa79410—PDSN MIP Client Upload Fails With Large IP Packet

When uploading files from a Mobile IP client to a server through the PDSN, packets that are larger than 1480 bytes (and the DF bit is set) are dropped by the PDSN. The PDSN does not send ICMP UNFRAG error to MIP client, and fails to learn the smaller mtu path. The MIP client will continue to send packets larger than 1480 and it will never get to the server. SIP clients are not affected.

The IP MTU setting for the IP/IP tunnel between the FA and HA is 1480 bytes.

**Workaround:** issue the **no ip mobile tunnel path-mtu-discovery** command to disable path MTU discovery on the PDSN.

- CSCsb29278—Tracebacks Seen With Active Controller.

On Cisco router running R2.1 PDSN software, the active controller was idle for sometime, and suddenly the following traceback was seen:

```
tb1-7600a-cont1#
Jun 24 23:51:27.327: %SCHED-3-STUCKTMR: Sleep with expired timer 221E9418, time
0xAC91BF0 (00:00:00 ago).
-Process= "masterPdsn", ipl= 5, pid= 137
-Traceback= 20698F7C 20799884 20799C54 2036C51C
```

**Workaround:** none.

- CSCsb30480—Out-of-Sequence Acct-Response Packets Triggers Interim Accounting

On a Cisco router running R2.1 PDSN software, after a dormant handoff, the PDSN sends “watchdog” packets to the Radius Server periodically in a scenario where the Accounting-response received from the Radius server are out of sequence.

This Issue occurs during dormant handoffs, only if the "Accounting-Reponse" for Accounting-Stop was received first, followed by Accounting-Response for Accounting-Start.

**Workaround:** none.

- CSCsb39828—PDSN Sends Packets Out Of Sequence When MPPC Compression is Enabled

A Cisco router running PDSN software will send MPPC compressed packets out of sequence towards a client.

This condition occurs when MPPC compression is enabled on the PDSN.

**Workaround:** alternate compression methods such as STAC can be used, or data can be sent uncompressed.

- CSCsb40378—PDSN Crash During Session Deletion

A crash may occur on the PDSN running IOS 12.3(11)T3 resulting in "System returned to ROM by bus error."

**Workaround:** none.

## Unresolved Caveats Prior to Cisco IOS Release 12.3(11)YF3

The following caveats are unresolved in Cisco IOS Release 12.3(11)YF2:

- CSCee74242—Flow Count Incorrect When Prepaid Flows Get Deleted  
Total flow count displayed in the **show cdma pdsn** output does not match the actual number of flows present on the box.  
This occurs only for prepaid sessions on Cisco PDSN.  
**Workaround:** none.
- CSCef36788—Downstream Throughput Lower Than Expected Number by 10%  
Downstream packet throughput for the Cisco PDSN R2.0 release has degraded. Throughput on the 7200 NPE-G1 and MWAM platform is 10% lower than target numbers.  
This condition occurs when packet size is 512 Bytes and traffic is pumped on all 20K sessions.  
**Workaround:** none.
- CSCef39342—Non-Crypto Packets Dropped Due to CDMA and CLI IPSEC Interoperability  
When CDMA IPsec is configured on the PDSN and CLI IPsec is configured on the HA, in the absence of a IPsec user MIP tunnel, normal IP traffic is dropped because no crypto tunnel is established between PDSN and HA.  
This symptom has been observed on the PDSN and HA routers running Cisco IOS release 12.3T.  
**Workaround:** none.
- CSCef39494—Prepaid MIP Flow Not Deleted on Quota Expiry  
On a Cisco router running Release 2.0 PDSN software, when multiple prepaid flows are opened for the same user and traffic is sent through a single flow so as to cross the threshold and quota granted, the PDSN does not close the flow. However, traffic through the flow is not switched as expected.  
This symptom occurs when prepaid accounting is enabled, and multiple Mobile IP prepaid flows are opened for the same user.  
**Workaround:** none.
- CSCef40729—Session is Not Cleared in PDSN With Tunnel Scalabilty Turned Off  
A Mobile IP session, created with UDP tunneling between the HA and PDSN, does not get cleared when the session is closed from MN.  
**Workaround:** use other modes of tunneling like, IPINIP or GRE between the PDSN and HA.
- CSCef40742—PDSN Accepts Value 0 for cCdmaSessionPdsnMaxFailHistory From NMS.  
On a Cisco router running R2.0 Packet Data Serving Node (PDSN) software, the CISCO-CDMA-PDSN-MIB counter “cCdmaSessionPdsnMaxFailHistory” accepts a value of zero when configured through NMS.  
**Workaround:** none.
- CSCef54687—Incorrect Disconnect Reason Send For Prepaid PMIP Flow  
On a Cisco router running Release 2.0 PDSN software, for a volume based prepaid proxy mobile IP flow with resource revocation enabled, when the PDSN deletes prepaid flow on receiving the resource revocation request from the HA, the PDSN sets the “disconnect reason” as “client service termination” instead of “remote forced disconnect” in online access-request.  
This symptom occurs for revocation enabled proxy mobile IP prepaid flows alone.  
**Workaround:** none.

- CSCef61626—MSID Flow is Opened When Quota Provided Has Both Volume and Duration Attribute  
On a Cisco router running Release 2.0 PDSN software, an MSID flow is opened when the quota allocated by HAAA has both volume and duration attributes  
This symptom only occurs for MSID flows.  
**Workaround:** none.
- CSCef61637—MSID Flow is Opened For Undefined PPAC  
On a Cisco Router running Release 2.0 PDSN software, an MSID flow is opened without prepaid capability when the **SelectedforSession** attribute has an incorrect value and PPAQ value is received in Access Accept.  
The session should have been terminated in this case.  
This symptom occurs for msid flow, when the SelectedforSession attribute has an incorrect value and PPAQ value is received in Access Accept.  
**Workaround:** none.
- CSCef75738—PDSN Rejects an RRQ With Active Stop If Prior Record Not Start/stop  
Rp counters are not incrementing in a Cisco router running 12.3T R2.0 Release PDSN software.  
The PDSN rejects an RRQ with Active Stop if a prior record is not started or stopped.  
**Workaround:** none.
- CSCin75685—A11 Update Other Reason Incorrect For Closed RP Session Open/Close  
When a closed RP session is opened and closed on the Packet Data Service Node (PDSN), the statistics counter update reason “other” shows invalid value.  
This condition is seen only when a closed RP session is opened and closed  
**Workaround:** none. Since the A11 update counter is not used for closed RP sessions on the PDSN, this counter can be ignored.
- CSCin85270—IPsec Tunnel Torn Down Before Revocation Completion for PMIP Session  
The Cisco PDSN closes the IPsec tunnel and cannot decrypt and process revocation acknowledgements from the Home Agent under the following scenario:
  - CDMA IPsec is enabled on the PDSN.
  - Revocation is triggered on the PDSN for a proxy mobileip session.
  - No more mobiles are connected to the corresponding Home Agent (i.e., the PDSN closes the mobileip tunnel)**Workaround:** none. This is a cosmetic issue; it happens rarely and not processing revocation acknowledgements does not break any functionality.

## Unresolved Caveats Prior to Cisco IOS Release 12.3(11)YF2

The following caveats are unresolved in Cisco IOS Release 12.3(11)YF1:

- CSCee74242—Flow Count Incorrect When Prepaid Flows Get Deleted  
Total flow count displayed in the **show cdma pdsn** output does not match the actual number of flows present on the box.  
This occurs only for prepaid sessions on Cisco PDSN.  
**Workaround:** none.

- CSCef36788—Downstream Throughput Lower Than Expected Number by 10%  
Downstream packet throughput for the Cisco PDSN R2.0 release has degraded. Throughput on the 7200 NPE-G1 and MWAM platform is 10% lower than target numbers.  
This condition occurs when packet size is 512 Bytes and traffic is pumped on all 20K sessions.  
**Workaround:** none.
- CSCef39342—Non-Crypto Packets Dropped Due to CDMA and CLI IPSEC Interoperability  
When CDMA IPsec is configured on the PDSN and CLI IPsec is configured on the HA, in the absence of a IPsec user MIP tunnel, normal IP traffic is dropped because no crypto tunnel is established between PDSN and HA.  
This symptom has been observed on the PDSN and HA routers running Cisco IOS release 12.3T.  
**Workaround:** none.
- CSCef39494—Prepaid MIP Flow Not Deleted on Quota Expiry  
On a Cisco router running Release 2.0 PDSN software, when multiple prepaid flows are opened for the same user and traffic is sent through a single flow so as to cross the threshold and quota granted, the PDSN does not close the flow. However, traffic through the flow is not switched as expected.  
This symptom occurs when prepaid accounting is enabled, and multiple Mobile IP prepaid flows are opened for the same user.  
**Workaround:** none.
- CSCef40729—Session is Not Cleared in PDSN With Tunnel Scalability Turned Off  
A Mobile IP session, created with UDP tunneling between the HA and PDSN, does not get cleared when the session is closed from MN.  
**Workaround:** use other modes of tunneling like, IPINIP or GRE between the PDSN and HA.
- CSCef40742—PDSN Accepts Value 0 for cCdmaSessionPdsnMaxFailHistory From NMS.  
On a Cisco router running R2.0 Packet Data Serving Node (PDSN) software, the CISCO-CDMA-PDSN-MIB counter “cCdmaSessionPdsnMaxFailHistory” accepts a value of zero when configured through NMS.  
**Workaround:** none.
- CSCef54687—Incorrect Disconnect Reason Send For Prepaid PMIP Flow  
On a Cisco router running Release 2.0 PDSN software, for a volume based prepaid proxy mobile IP flow with resource revocation enabled, when the PDSN deletes prepaid flow on receiving the resource revocation request from the HA, the PDSN sets the “disconnect reason” as “client service termination” instead of “remote forced disconnect” in online access-request.  
This symptom occurs for revocation enabled proxy mobile IP prepaid flows alone.  
**Workaround:** none.
- CSCef61626—MSID Flow is Opened When Quota Provided Has Both Volume and Duration Attribute  
On a Cisco router running Release 2.0 PDSN software, an MSID flow is opened when the quota allocated by HAAA has both volume and duration attributes  
This symptom only occurs for MSID flows.  
**Workaround:** none.

- CSCef61637—MSID Flow is Opened For Undefined PPAC

On a Cisco Router running Release 2.0 PDSN software, an MSID flow is opened without prepaid capability when the **SelectedforSession** attribute has an incorrect value and PPAQ value is received in Access Accept.

The session should have been terminated in this case.

This symptom occurs for msid flow, when the SelectedforSession attribute has an incorrect value and PPAQ value is received in Access Accept.

**Workaround:** none.
- CSCef75738—PDSN Rejects an RRQ With Active Stop If Prior Record Not Start/stop

Rp counters are not incrementing in a Cisco router running 12.3T R2.0 Release PDSN software. The PDSN rejects an RRQ with Active Stop if a prior record is not started or stopped.

**Workaround:** none.
- CSCin75685—A11 Update Other Reason Incorrect For Closed RP Session Open/Close

When a closed RP session is opened and closed on the Packet Data Service Node (PDSN), the statistics counter update reason “other” shows invalid value.

This condition is seen only when a closed RP session is opened and closed

**Workaround:** none. Since the A11 update counter is not used for closed RP sessions on the PDSN, this counter can be ignored.
- CSCin85270—IPsec Tunnel Torn Down Before Revocation Completion for PMIP Session

The Cisco PDSN closes the IPsec tunnel and cannot decrypt and process revocation acknowledgements from the Home Agent under the following scenario:

  - CDMA IPsec is enabled on the PDSN.
  - Revocation is triggered on the PDSN for a proxy mobileip session.
  - No more mobiles are connected to the corresponding Home Agent (i.e., the PDSN closes the mobileip tunnel)

**Workaround:** none. This is a cosmetic issue; it happens rarely and not processing revocation acknowledgements does not break any functionality
- CSCin86601—PDSN A11 Session Update Retransmission is not Working Correctly

The Cisco PDSN is not taking the configured a11 session update timeout value into consideration while retransmitting the a11 session update message.

This condition occurs when the Cisco router is configured for PDSN.

**Workaround:** none.
- CSCin86667—SDB Airlink Record Rejected After Dormant Handoff

When an SDB airlink record is received after a SETUP/START airlink record, the RRQ is rejected with an error code of 86H, with the following debug printed:

“Bad Airlink record. Received SDB airlink after SETUP/START”.

**Workaround:** none.

- CSCin86716—PDSN to Parse SDB Records as per IOS 4.x

The Cisco PDSN cannot parse A11 Registration request message from a PCF that contains attribute value 32 in SDB airlink record.

This condition occurs when the PCF sends attribute value 32 in the SDB airlink record.

**Workaround:** none.

## Unresolved Caveats Prior to Cisco IOS Release 12.3(11)YF1

The following caveats are unresolved in Cisco IOS Release 12.3(11)YF:

- CSCee74242—Flow Count Incorrect When Prepaid Flows Get Deleted

Total flow count displayed in the **show cdma pdsn** output does not match the actual number of flows present on the box.

This occurs only for prepaid sessions on Cisco PDSN.

**Workaround:** none.

- CSCef36788—Downstream Throughput Lower Than Expected Number by 10%

Downstream packet throughput for the Cisco PDSN R2.0 release has degraded. Throughput on the 7200 NPE-G1 and MWAM platform is 10% lower than target numbers.

This condition occurs when packet size is 512 Bytes and traffic is pumped on all 20K sessions.

**Workaround:** none.

- CSCef39342—Non-Crypto Packets Dropped Due to CDMA and CLI IPSEC Interoperability

When CDMA IPsec is configured on the PDSN and CLI IPsec is configured on the HA, in the absence of a IPsec user MIP tunnel, normal IP traffic is dropped because no crypto tunnel is established between PDSN and HA.

This symptom has been observed on the PDSN and HA routers running Cisco IOS release 12.3T.

**Workaround:** none.

- CSCef39494—Prepaid MIP Flow Not Deleted on Quota Expiry

On a Cisco router running Release 2.0 PDSN software, when multiple prepaid flows are opened for the same user and traffic is sent through a single flow so as to cross the threshold and quota granted, the PDSN does not close the flow. However, traffic through the flow is not switched as expected.

This symptom occurs when prepaid accounting is enabled, and multiple Mobile IP prepaid flows are opened for the same user.

**Workaround:** none.

- CSCef40729—Session is Not Cleared in PDSN With Tunnel Scalability Turned Off

A Mobile IP session, created with UDP tunneling between the HA and PDSN, does not get cleared when the session is closed from MN.

**Workaround:** use other modes of tunneling like, IPINIP or GRE between the PDSN and HA.

- CSCef40742—PDSN Accepts Value 0 for cCdmaSessionPdsnMaxFailHistory From NMS.

On a Cisco router running R2.0 Packet Data Serving Node (PDSN) software, the CISCO-CDMA-PDSN-MIB counter “cCdmaSessionPdsnMaxFailHistory” accepts a value of zero when configured through NMS.

**Workaround:** none.

- CSCef43555—PDSN Sends Wrong Counter When cCdmaPcfSoRpUpdOtherReaReqs is Requested

On a Cisco router running R2.0 PDSN software, the CISCO-CDMA-PDSN-MIB counter cCdmaPcfSoRpUpdOtherReaReqs shows incorrect values.

**Workaround:** none.
- CSCef54687—Incorrect Disconnect Reason Send For Prepaid PMIP Flow

On a Cisco router running Release 2.0 PDSN software, for a volume based prepaid proxy mobile IP flow with resource revocation enabled, when the PDSN deletes prepaid flow on receiving the resource revocation request from the HA, the PDSN sets the “disconnect reason” as “client service termination” instead of “remote forced disconnect” in online access-request.

This symptom occurs for revocation enabled proxy mobile IP prepaid flows alone.

**Workaround:** none.
- CSCef57647—Incorrect PDSN CISCO-CDMA-PDSN-MIB Counter Values

On a Cisco router running R2.0 Packet Data Serving Node (PDSN) software, the CISCO-CDMA-PDSN-MIB counters “cCdmaActiveSessions”, “cCdmaDormantSessions”, and “cCdmaPcfSoRpUpdOtherReaReqs” show incorrect values.

**Workaround:** none.
- CSCef61626—MSID Flow is Opened When Quota Provided Has Both Volume and Duration Attribute

On a Cisco router running Release 2.0 PDSN software, an MSID flow is opened when the quota allocated by HAAA has both volume and duration attributes

This symptom only occurs for MSID flows.

**Workaround:** none.
- CSCef61637—MSID Flow is Opened For Undefined PPAC

On a Cisco Router running Release 2.0 PDSN software, an MSID flow is opened without prepaid capability when the **SelectedforSession** attribute has an incorrect value and PPAQ value is received in Access Accept.

The session should have been terminated in this case.

This symptom occurs for msid flow, when the SelectedforSession attribute has an incorrect value and PPAQ value is received in Access Accept.

**Workaround:** none.
- CSCef75730—RP Counters are Not Incremented When Different GRE With Nosetup

Rp counters are not incrementing in a Cisco router running 12.3T R2.0 Release PDSN software. RP counters and poorly formed Request are not incrementing in the PDSN.

The RP counters in the PDSN are not incremented when a different GRE with nosetup was sent by simulator.

**Workaround:** none.
- CSCef75738—PDSN Rejects an RRQ With Active Stop If Prior Record Not Start/stop

Rp counters are not incrementing in a Cisco router running 12.3T R2.0 Release PDSN software.

The PDSN rejects an RRQ with Active Stop if a prior record is not started or stopped.

**Workaround:** none.

- CSCef86875—PDSN Reloads While Disabling Conditional Debugging For Prepaid  
On Cisco router running Release 2.1 PDSN software, the router reloads while disabling conditional debugging feature for Prepaid Accounting.  
The symptom occurs when prepaid accounting is enabled with conditional debugging.  
**Workaround:** none.
- CSCef92130—CDMA IPsec Fails When Packets Are Sent Over Different Interface  
On a Cisco Router running PDSN R2.0 software with CDMA IPsec configured, if the outgoing interface is changed (example due to OSPF cost), then packets from PDSN go unencrypted.  
**Workaround:** ensure that all MIP packets are sent over the interface on which crypto maps get applied. For interface redundancy, port channel configuration may be used.
- CSCin85270—IPsec Tunnel Torndown Before Revocation Completion For PMIP Session  
PDSN closes IPsec tunnel and so cannot decrypt and process revocation acknowledgements from Home Agent under the following conditions:
  - CDMA IPsec is enabled on PDSN.
  - Revocation is triggered on PDSN for a proxy mobileip session.
  - No more mobiles are connected to the corresponding Home Agent (for example, the PDSN closes the mobileip tunnel).**Workaround:** none. This is a cosmetic issue, as it happens rarely and not processing revocation acknowledgement does not break any functionality
- CSCsa44772—PDSN Should Not Send A11 Session UPD if Current RNPDIIT <= prev RNPDIIT  
The PDSN sends a session update message to the PCF when RN-PDIIT downloaded <= RN-PDIIT stored.  
This condition occurs when the second MIP flow is opened for a user and the same RN-PDIIT, Always-On values are downloaded from RADIUS server.  
**Workaround:** none.
- CSCsa45264—Last Character of Calling Station ID Stripped When PDSN Sends to LNS  
On Cisco PDSN running 12.3(8)XW03, when VPDN flows are opened on the A11 session, the PDSN acting as LAC will send an ICRQ to the LNS. In the ICRQ message PDSN will include the Calling Station ID received in the A11 Registration Request. When the Calling Station ID is sent from PDSN, the last character of Calling Station ID is not encoded in the ICRQ to the LNS.  
This condition occurs for all VPDN flows opened over the A11 session.  
**Workaround:** none.

## Unresolved Caveats Prior to Cisco IOS Release 12.3(11)YF

The following caveats are unresolved in Cisco IOS Release 12.3(8)XW3

- CSCed65017—MWAM: Config CLI That Fail Batch Mode Copy Fail Config-mode SUP  
Some configuration commands fail, do not operate properly, or cause dead memory when using batch mode config download or config-mode supervisor.  
This problem occurs when the MWAM processor is configured for **supervisor** config-mode.  
**Workaround:** Use config-mode local on MWAM.

- CSCef64126—CDMA IPSec Support for VRF and HA-SLB.  
Cisco PDSN Release 2.0 currently supports CDMA IPSec only for non-VRF MIP flows. The PDSN needs to support CDMA IPSec for VRF flows also.  
**Workaround:** none.
- CSCef75989—**ip radius source-interface** Command not Working  
On a Cisco router running R2.0 Home Agent Software 12.3(8)XW, the **ip radius source-interface** command does not work. Even if you configure **ip radius source-interface xyz**, the router still sends the address of the physical interface connected to the radius server, rather than the interface configured in the command (*xyz*).  
**Workaround:** Configure the **ip radius source-interface** at the server-group level.
- CSCef79940—Unable to Configure CLI **radius-server attribute 44 include-in-access**  
On a Cisco PDSN running the 12.3(8)XW R2.0 PDSN image on MWAM platform, configuring the **radius-server attribute 44 include-in-access-req** command, or the **ip rad source-interface** command causes an error message “% Can't insert AAA config node for vrf=”, if the **aaa accounting system default start-stop** command is configured on the MWAM, and the MWAM config mode is the supervisor mode.  
**Workaround:** This issue is not seen if the configuration **aaa accounting system default start-stop** command is not configured on the MWAM or if the MWAM config mode is local.
- CSCef92130—CDMA IPSec Fails When Packets Are Sent Over Different Interface  
On a Cisco Router running PDSN R2.0 software with CDMA IPSec configured, MIP flows will not come up if the Mobile IP tunnel endpoint is different that of IPSec tunnel end point. This issue is seen only for MIP flows, and not for PMIP flows.  
**Workaround:** Configure the IPSec tunnel end point as the MIP tunnel end point.

## Unresolved Caveats Prior to Cisco IOS Release 12.3(8)XW3

The following caveats are unresolved in Cisco IOS Release 12.3(8)XW2

- CSCed86177—Tracebacks Found on PDSN with CEF and NAT Enabled for SIP Flow  
A Cisco router running 12.3T R2.0 Release PDSN software, sometimes produces tracebacks while sending bidirectional traffic from mobile node to the reflector in SIP flow with compress stack enabled and cef switched.  
**Workaround:** none.
- CSCee13372—IPSec Tunnel Goes Down Before Receiving ACK for Revocation Request  
When the last mobile tunnel binding is brought down on the Cisco HA, a revocation message is sent from the HA and the CDMA IPSec tunnel is brought down without waiting for a revocation acknowledgement message from the PDSN.  
This symptom has been observed on a router that is running Cisco IOS release 12.3T software.  
**Workaround:** none.
- CSCee74242—Flow Count Incorrect When Prepaid Flows Get Deleted  
Total flow count displayed in **show cdma pdsn** output does not match the actual number of flows present on the box.  
This occurs only for prepaid sessions on Cisco PDSN.  
**Workaround:** none.

- CSCef27300—Framed-IP-Addr Attr Not Sent When Both RADIUS and CDMA CLI Configured  
Framed-IP-Address in the Access-Request for MIP flows is not sent even if the **ip mobile foreign-agent send-mn-address** command is configured on the Cisco PDSN (PDSN) and Home Agent (HA).  
The **radius-server attribute 8 include-in-access-req** command is also configured along with CLI **ip mobile foreign-agent send-mn-address**, and it is not sending the “Framed-IP-Addr” attribute in its Access Request to AAA.  
**Workaround:** unconfigure the **radius-server attribute 8 include-in-access-req** command on the box.
- CSCef31289—Unsupported Attr Debugs While Opening Sessions in PDSN  
On a Cisco PDSN running the Cisco IOS 12.3(8)XW R2.0 PDSN image, on opening a session with radius debugs enabled, the “AAA Unsupported Attr” debug messages are printed even though no functionality is affected.  
**Workaround:** none.
- CSCef36788—Downstream Throughput Lower Than Expected Number by 10%  
Downstream packet throughput for Cisco PDSN R2.0 release has degraded. Throughput on 7200 NPE-G1 and MWAM platform is 10% lower than target numbers.  
The following conditions exist for this problem: packet size is 512 Bytes and traffic is pumped on all 20K sessions.  
**Workaround:** none.
- CSCef39342—Non-Crypto Packets Dropped Due to CDMA and CLI IPSec Interoperability  
When CDMA IPSec is configured on PDSN and CLI IPSec is configured on HA, in the absence of IPSec user MIP tunnel, normal IP traffic is dropped as no crypto tunnel is established between PDSN and HA.  
This symptom has been observed on PDSN and HA routers that are running Cisco IOS release 12.3T.  
**Workaround:** none.
- CSCef39494—Prepaid MIP Flow Not Deleted on Quota Expiry  
On a Cisco router running Release 2.0 PDSN software, when multiple prepaid flows are opened for the same user and traffic is sent through a single flow so as to cross the threshold and quota granted, the PDSN does not close the flow. However, traffic through the flow is not switched as expected.  
This symptom occurs when prepaid accounting is enabled and multiple mobile IP prepaid flows are opened for the same user.  
**Workaround:** none.
- CSCef40729—Session is Not Cleared in PDSN With Tunnel Scalability Turned Off  
A mobile IP session, created with UDP tunneling between the HA and PDSN, does not get cleared when the session is closed from MN.  
**Workaround:** Use other modes of tunneling like, IPINIP or GRE between PDSN and HA.
- CSCef40742—PDSN Accepts Value 0 for cCdmaSessionPdsnMaxFailHistory from NMS.  
On a Cisco router running R2.0 Packet Data Serving Node (PDSN) Software, the CISCO-CDMA-PDSN-MIB counter cCdmaSessionPdsnMaxFailHistory accepts a value of zero (0) when configured through NMS.  
**Workaround:** none.

- CSCef43555—PDSN Sends Wrong Counter When cCdmaPcfSoRpUpdOtherReaReqs is Requested  
On a Cisco router running R2.0 PDSN Software, the CISCO-CDMA-PDSN-MIB counter cCdmaPcfSoRpUpdOtherReaReqs show incorrect values.

**Workaround:** none.

- CSCef50548—TOS Value Set to Non-zero Value for PPP Control Packets

On Cisco router running Release 2.0 PDSN software, during Point-to-Point (PPP) negotiation, the IPCP control packets sent downstream to the Mobile Node from PDSN are encapsulated using GRE and then sent to Mobile Node. The DSCP marking on Type of Service (TOS) filed in the outer header, found be a non-zero (Garbage) value.

This behavior is seen only when the PPP negotiations happens.If traffic is sent over the established tunnel, those packets are marked with correct (TOS =0) value.

**Workaround:** none.

- CSCef54687—Incorrect Disconnect Reason Send For Prepaid PMIP Flow

On a Cisco router running Release 2.0 PDSN software for a volume-based prepaid proxy mobile IP flow with resource revocation enabled, when the PDSN deletes a prepaid flow on receiving the resource revocation request from the HA, the PDSN sets the “disconnect reason” as “client service termination” instead of “remote forced disconnect” in online access-request.

This condition occurs for revocation enabled proxy mobile IP prepaid flows alone

**Workaround:** none.

- CSCef66797—Accounting ON/OFF Message Not Sent Upon Processor Reload

On Cisco router running Release 2.0 PDSN software, upon reload of the MWAM processor where the PDSN is loaded, the Accounting OFF message is not sent towards the AAA. Also the Accounting ON message is not sent when the processor comes up after reload.

This problem exists under the following conditions:

- both the Accounting ON/OFF message is not sent if the MWAM Config-mode is set to Supervisor.
- If the MWAM Config-mode is set to local, then the Accounting ON message alone sent after the processor comes up, whereas the Accounting OFF message is not sent after the reload.

**Workaround:** Include the “Broadcast” keyword in the following accounting configuration of PDSN:

**aaa accounting system default start-stop broadcast group *group name*.**

Additionally, the MWAM config-mode should be set to “Local”.

- CSCef61626—MSID Flow is Opened When Quota Provided Has Both Vol and Dur Attribute

On a Cisco Router running Release 2.0 PDSN Software, the MSID flow is opened when the quota allocated by HAAA has both volume and duration attributes.

This symptom only occurs for MSID flows.

**Workaround:** none.

- CSCef61637—MSID Flow is Opened For Undefined PPAC

On a Cisco Router running Release 2.0 PDSN Software, a MSID flow is opened without prepaid capability when the “SelectedforSession” attribute has an incorrect value, and the PPAQ value is received in Access Accept.

In this case, the session should have been terminated.

This symptom occurs for MSID flows when the “SelectedforSession” attribute has an incorrect value and PPAQ value is received in Access Accept.

**Workaround:** none.
- CSCef68963—Incorrect CISCO-MOBILE-IP-MIB Counter Values

On a Cisco router running R2.0 Packet Data Serving Node (PDSN) or Home Agent Software, the CISCO-MOBILE-IP-MIB counters “cmiFaRegVisitorRegFlagsRev1” and “cmiSecAssoc” table entries show incorrect values.

**Workaround:** none.
- CSCin77744—PDSN Drops Fragmented PCF Packets Intermittently

On the Packet Data Service Node (PDSN), when the Generic Routing Encapsulation (GRE) packets received from the Packet Control Function (PCF), they are dropped intermittently, if these packets are fragmented.

Packets drops are seen on the PDSN when the PPP negotiation between the PDSN and Mobile Node Terminates the Compression Control Protocol (CCP) and then during the data transfer the Mobile Node sends another CCP ConfReq to the PDSN.

**Workaround:** by disabling compression on PDSN Virtual Template packet drop was not observed
- CSCin78778—Session-down Counter Increments Even When There is no Session

On a Cisco router running PDSN R2.0 image configured as Cluster Controller, the Session-down counter is incremented even if there are no active sessions on any of its members.

**Workaround:** none.
- CSCin78831—Cluster Member Displayed Twice in **show** Command Display

Cluster members are displayed twice in the **show cdma pdsn cluster controller member load** command. This condition occurs only when all members except one are removed from the controller.

**Workaround:** none.
- CSCin79106—Mismatch in Session Count in Cluster Controller

On a Cisco router running the PDSN R2.0 image, a mismatch of cluster statistics is encountered. Statistics of the total number of sessions displayed in the **show cdma pdsn cluster controller member load** command do not match with statistics of the **show cdma pdsn cluster controller session count** command.

**Workaround:** none.
- CSCin81236—Conditional Debugging Skips Some RADIUS Msgs for MIP Flows

When conditional debugging is enabled on Cisco PDSN running Cisco IOS 12.3(8)XW image, RADIUS related debugs are not shown sometimes for a Mobile IP flow that is opened on the box.

This condition occurs when conditional debugging is set for RADIUS related debugs.

**Workaround:** none.

- CSCin81520—Extra Mobile IP Debugs are Printed For Conditional Debugging

Some extra mobile IP debugs are printed on a Cisco PDSN, running Cisco IOS 12.3(08)XW software, when mobile IP conditional debugging is enabled on it. Debugs that get printed are not corresponding to the user.

This condition occurs when conditional debugging for mobile IP is turned on.

**Workaround:** none.

## Unresolved Caveats Prior to Cisco IOS Release 12.3(8)XW2

The following caveats are unresolved in Cisco IOS Release 12.3(8)XW2

- CSCed86177—Tracebacks Found on PDSN While Opening Simple IP Session (Simple IP session)

Cisco routers running Packet Data Serving Node software may show traceback when the compression stack is enabled while opening simple IP sessions.

**Workaround:** none.

- CSCee13372—IPSec Tunnel Goes Down Before Receiving ACK for Revocation Request (Resource Revocation)

On clearing the IP mobile bindings manually on PDSN, ipsec tunnel goes down before waiting for the acknowledgement for the Resource Revocation from HA

This condition is observed under the following conditions

- a. Clear the ip mobile bindings manually on PDSN,
- b. PDSN sends Resource revocation message to HA.
- c. IPSec tunnel goes down before ACK from HA.

**Workaround:** none.

### 3. CSCed86144—Tracebacks Found in Clustering (Clustering)

A Cisco router running Packet Data Serving Node (PDSN) software in cluster controller member environment may show tracebacks on backup controller.

This occurs under the rare condition when controllers are present in a redundancy environment with a active and standby controller, and simple IP sessions are opened. Tracebacks may appear on the backup controller after sessions are opened.

**Workaround:** none.

- CSCed86177—Tracebacks Found on PDSN (ip\_feature\_fastswitch) (Clustering)

A Cisco router running 12.3T R2.0 Release PDSN software sometimes produces tracebacks while sending bidirectional traffic from mobile node to reflector in SIP flow with compress stack enabled and CEF switched

The condition occurs when sending bidirectional traffic from mobile node to reflector in SIP flow with compress stack enabled, and CEF switched tracebacks can be seen on PDSN console.

**Workaround:** none.

- CSCin78876—MIP CPS Low With Mobile IP Global Configuration

A Cisco router running PDSN 2.0 Release software (Cisco IOS 12.3T) has a lower CPS rate for Mobile IP calls

The number of MIP calls that can be established per second is below 30.

**Workaround:** none.

## Resolved Caveats

The following caveats are resolved in Cisco IOS Release 12.3(11)YF4:

- CSCei61732

Cisco IOS may permit arbitrary code execution after exploitation of a heap-based buffer overflow vulnerability. Cisco has included additional integrity checks in its software, as further described below, that are intended to reduce the likelihood of arbitrary code execution.

Cisco has made free software available that includes the additional integrity checks for affected customers.

This advisory is posted at <http://www.cisco.com/warp/public/707/cisco-sa-20051102-timers.shtml>.

- CSCei76358—os-boot Cleanup of User Interface Data

Through normal software maintenance processes, Cisco is removing deprecated functionality from the OS boot routine. These changes have no impact on system operation or feature availability.

- CSCsb24007

Multiple voice-related vulnerabilities are identified in Cisco IOS software, one of which is also shared with Cisco Unified Communications Manager. These vulnerabilities pertain to the following protocols or features:

- Session Initiation Protocol (SIP)
- Media Gateway Control Protocol (MGCP)
- Signaling protocols H.323, H.254
- Real-time Transport Protocol (RTP)
- Facsimile reception

Cisco has made free software available to address these vulnerabilities for affected customers. Fixed Cisco IOS software listed in the Software Versions and Fixes section contains fixes for all vulnerabilities mentioned in this advisory.

There are no workarounds available to mitigate the effects of any of the vulnerabilities apart from disabling the protocol or feature itself.

- This advisory is posted at <http://www.cisco.com/warp/public/707/cisco-sa-20070808-IOS-voice.shtml>

## Caveats Resolved Prior to Cisco IOS Release 12.3(11)YF3

The following caveats are resolved in Cisco IOS Release 12.3(11)YF3 and are listed by component:

### PDSN

- CSCef39342—Non-Crypto Packets Dropped Due to CDMA and CLI IPSEC Interoperability

When CDMA IPsec is configured on the PDSN and CLI IPsec is configured on the HA, in the absence of a IPsec user MIP tunnel, normal IP traffic is dropped because no crypto tunnel is established between PDSN and HA.

This symptom has been observed on the PDSN and HA routers running Cisco IOS release 12.3T.

**Workaround:** none.

- CSCef75738—PDSN Rejects an RRQ With Active Stop If Prior Record Not Start/stop  
Rp counters are not incrementing in a Cisco router running 12.3T R2.0 Release PDSN software. The PDSN rejects an RRQ with Active Stop if a prior record is not started or stopped.  
**Workaround:** none.
- CSCin88336—CISCO-ENHANCED-MEMORY-POOL Objects are not Populated in R2.1  
CISCO-ENHANCED-MEMORY-POOL objects are not populated in Release 2.1  
No specific condition. This happens when the objects of this MIB is queried.  
**Workaround:** none.
- CSCin89969—PDSN Deletes Session Incorrectly Due to MobileIP RRQ Timeout  
On a Cisco PDSN the simple IP flow is deleted incorrectly due to mobile ip registration request timeout. The race condition for deleting the session incorrectly only if all the following condition matches  
Mobile Node in the initial PPP negotiation rejects PPP Authentication and during the IPCP stage does not include the IP Address options in the IPCP ConfReq.  
Mobile Node before the initial Mobile IP registration request (cdma pdsn timeout mobile-ip-registration) timeout occurs, does PPP renegotiation. During the PPP renegotiation the mobile request for PPP authentication and includes IP address options in the IPCP stage because of which Simple IP flow is created.  
**Workaround:** none. The mobile needs to be configured to do PPP authentication.
- CSCin91064—PPP Packets over PPPoGRE Session Dropped for VPDN Flows  
On Cisco router running R2.1 PDSN software, the PPPoGRE session is dropped for VPDN flows if PPP-acfc packet is received with FF03.  
This issue is seen only for VPDN session and for SIP.  
**Workaround:** none.
- CSCin91735—AHDLC IO Memory Leak for BadCRC packets with no ahdhc trailer closed rp  
On Cisco PDSN software running 12.3(11)YF1 image with Closed RP feature enabled and the **no cdma pdsn a10 ahdhc trailer** command is configured. If AHDLC packets with Bad CRC errors are received then IO memory allocated for the packets are not released which may lead to low IO memory situation on the PDSN.  
**Workaround:** configure the **cdma pdsn a10 ahdhc trailer** CLI.
- CSCin92305—Dormant Handoff Triggers Interim Accounting  
After dormant handoff, with "cdma pdsn accounting send start-stop" configured, the PDSN starts sending out interim accounting records to the RADIUS server.  
In IOS, RADIUS watchdog records are not triggered after an accounting STOP is sent to the RADIUS server. They are only sent after an accounting START is sent. However, it is observed that after dormant handoff, with **cdma pdsn accounting send start-stop** configured, the PDSN starts sending out interim accounting records to the AAA server. This is not expected, as an accounting STOP is sent to the AAA server during the dormant handoff process.  
In the case of dormant handoffs with **cdma pdsn accounting send start-stop** configured, the following is observed:

  - a. When a simple IP session is opened, an Accounting START is sent (as expected) with e.g. Accounting Session ID = 1.
  - b. Watchdog records are sent at the configured interval.

- c. When the session is made dormant, an Accounting STOP is sent (as expected) with eg. Accounting Session ID = 1.

Now, when a dormant handoff is executed:

- a. The target PCF sends an airlink SETUP. The PDSN then sends an accounting START followed by an accounting STOP (as expected) with e.g. Accounting Session ID = 2.
- b. When the source PCF sends a Reg Upd Ack, the PDSN then again sends an accounting START followed by an accounting STOP (as expected) with e.g. Accounting Session ID = 3.
- c. After the above sequence, it is found that the PDSN incorrectly sends watchdog records with Accounting Session ID = 2. These records should not be sent, as a accounting STOP has been sent.

**Workaround:** none.

- CSCin92122—Abort Does Not Increment in **show cdma pdsn stat ppp pcf**  
Statistics counter corresponding to Abort in **show cdma pdsn statistics ppp pcf** does not increment. This condition occurs on a Cisco router configured for PDSN.

**Workaround:** none.

- CSCin92700—Incorrect Downstream Accounting With TCP Header Compression Enabled  
On Cisco Packet Data Service Node(PDSN) when TCP header compression is enabled and mobile negotiates TCP header compression, then incorrect accounting is done on the packet bytes by the PDSN for the downstream direction.

**Workaround:** none.

- CSCsa67420—PDSN: Spurious Access and Bus Error Crash in PPP Compression  
A 7200 PDSN running 12.3(4)T and configured for MPPC might crash by Bus error.

Right before the reload, the following Alignment Error is displayed:

```
%ALIGN-1-FATAL: Illegal access to a low address
```

This condition occurs on a PDSN running IOS version 12.3(4)T or later, that is configured for MPPC.

**Workaround:** none.

- CSCsa93388—PDSN Not Parsing SDB if g10 Sent Before Y4 With ios4.1 Complaine  
On Cisco router running PDSN software, the PDSN throws parsing error if g10 attribute received before y4 in the SDB record.

The PDSN should be able to parse the SDB records in whatever order the data arrives.

This issue occurs in PDSN YF release images, and also when ios4.1 complaine for SDB record is enabled.

**Workaround:**none.

**MWAM**

- CSCeh67507—MWAM Processor Hangs, SR system Unavailable When Lot of Debugs Enabled  
MWAM processor appears to be hung. However it does send out HSRP hellos now and then causing its peer to not takeover or cause RF induced reloads on peer(based on HSRP priority). So, SR system does not recover completely. Note that this affects the partner processors in the same complex as well.

This condition occurs when too many debug or error messages are printed.

**Workaround:** configure **no logging console guaranteed** to avoid lock up of the console, or the logger process hijacking the CPU.

**NAT**

- CSCef50065—NAT Causes Spurious Memory Access Made at 0x80A3B064 Reading 0x36  
Spurious memory accesses and tracebacks are generated on a Cisco 831.

This symptom is observed when NAT/PAT is configured.

**Workaround:** none.

- CSCef97573—NAT: H225/H245 pak Cause Crash in ipnat\_destroy\_seqdelta

A router may reload with a bus error exception, the crashinfo file shows an address error (a load or instruction fetch), and there is a spurious access in the crashinfo file.

These symptoms are observed on a Cisco router that performs NAT on H.323 voice traffic.

**Workaround:** none.

- CSCsb22290—NAT Overload Broken With CLI **ip nat service fullrange udp port 500**

When the user configures the **ip nat service fullrange udp port** *number* command, the port-allocation logic is broken. If a PAT port is taken the next-port logic fails.

The **ip nat service fullrange** CLI is only for specific customers, and the regular port-allocation logic is not affected. Only when this command is enabled are things broken as explained above.

**Workaround:** disable the **ip nat service fullrange** CLI if it is enabled.

**Miscellaneous**

- CSCee45312—Radius Authentication Bypass When Configured With a None Fallback Method

Remote Authentication Dial In User Service (RADIUS) authentication on a device that is running certain versions of Cisco Internetworking Operating System (IOS) and configured with a fallback method to none can be bypassed.

Systems that are configured for other authentication methods or that are not configured with a fallback method to none are not affected.

Only the systems that are running certain versions of Cisco IOS are affected. Not all configurations using RADIUS and none are vulnerable to this issue. Some configurations using RADIUS, none and an additional method are not affected.

Cisco has made free software available to address this vulnerability. There are workarounds available to mitigate the effects of the vulnerability.

More details can be found in the security advisory which posted at the following URL  
<http://www.cisco.com/warp/public/707/cisco-sa-20050629-aaa.shtml>

- CSCef73460—ISA Card Not Detected in C7200 Router

An ISA encryption card is not activated when you boot the router.

This symptom is observed on a Cisco 7200 series that runs Cisco IOS Release 12.3(11)T or interim Release 12.3(11.4) and that is configured with an NPE-400. Note that the symptom does not occur when the router is configured with an NPE-G1.

**Workaround:** none.

## Caveats Resolved Prior to Cisco IOS Release 12.3(11)YF3

The following caveats are resolved in Cisco IOS Release 12.3(11)YF2:

- CSCef97018—VAM2: Authentication Error and Invalid packet Errors at High Stress

A Cisco 7200 router with VAM2 will display many output authentication errors and invalid packet errors.

This condition occurs under high stress and when QOS pre-classify is configured.

**Workaround:** Disable QOS or reduce the traffic rate.

- CSCeg08326—MWAM: Mobile IP Tunnel Source and Destination Reported as UNKNOWN

A Cisco Home Agent router may report the tunnel source and destination, for a dynamically created Mobile IP-IP Tunnel, as “UNKNOWN” in the **show interface** command output.

```
Router# show interface t1
Tunnell is up, line protocol is up
  Hardware is Tunnel
  Interface is unnumbered. Using address of Ethernet0/0 (10.1.1.1)
  MTU 1514 bytes, BW 9 Kbit, DLY 500000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation TUNNEL, loopback not set
  Keepalive not set
  Tunnel source UNKNOWN, destination UNKNOWN
```

**Workaround:** none.

- CSCeg17877—Common Crypto Engine Pak Cleanup

This DDTS is not a bug. The diffs for this DDTS provide functionality that is utilized by the fix for bug CSCeh14272.

Since CSCeh14272 needs to go into a throttle, CSCeg17877 will also need to go into a throttle.

(The commit moves duplicate functionality out of a pair of drivers into the common code for help with maintainability.)

- CSCeh23419—PDSN R2.0: acct-stop Wrong Release ReasonID

This behavior is seen when a timeout value is configured on the PDSN for a PPP session, and the PCF terminates the session. Since the timeout value is configured for the session, the PDSN does not respond to the LCP term req until the timeout value. If a RRQ with lifetime zero is received for the session, the PDSN terminates the session immediately and removes the timer. In this scenario, the cdma\_release\_ind, which is one of the 3gpp2 radius attributes, was not set properly. Ideally this needs to be set to “PPP Termination”.

This condition occurs when RRQ 0 is received before the timeout expiry in the PDSN for session termination.

**Workaround:** none.

- CSCin46180—PDSN Should Not Reject Retransmit Sequence Number in A11 RRQ with 2 Airlink Received

The Cisco Packet Data Serving Node(PDSN) running 12.2(08)ZB01 image may reject registration request(RRQ) received on the Packet control function(PCF) and PDSN signalling interface(A11) by setting reply code to 8DH in the A11 registration reply (RRP)sent back to PCF.

This condition exists when an A11 RRQ with two airlink records (setup airlink record and start airlink record) is retransmitted, and the airlink sequence numbers in the airlink records is same as received in the previous A11 RRQ.

**Workaround:** none.

- CSCin81520—Extra Mobile IP Debugs are Printed for Conditional Debugging

Some extra mobile IP debugs are printed on Cisco PDSN running 12.3(08)XW software when mobile IP conditional debugging is enabled on it. Debugs that get printed are not corresponding to the user.

**Workaround:** none.

- CSCin86716—PDSN to Parse SDB Records as Per IOS 4.x

The Cisco PDSN cannot parse A11 Registration request message from PCF that contains attribute value 32 in SDB airlink record.

This conditions exists when the PCF sends attribute value 32 in SDB airlink record.

**Workaround:** none.

- CSCin86601—PDSN a11 session update retransmission is not working correctly

The Cisco PDSN is not taking the configured a11 session update timeout value into consideration while retransmitting the a11 session update message.

This condition occurs when the Cisco router is configured for the PDSN.

**Workaround:** none.

- CSCin86667—SDB Airlink Record Rejected After Dormant Handoff

When an SDB airlink record is received after a SETUP/START airlink record, the RRQ is rejected with an error code of 86H, with the following debug printed:

“Bad Airlink record. Received SDB airlink after SETUP/START”.

**Workaround:** None.

- CSCin86686—Interim Accounting Behavior Changed for Dormant-Active Transition

In the following PDSN scenario, the interim accounting update interval is not working properly.

This problem occurs when the following conditions exist:

- a. Open a call.
- b. Force the call to dormant state.
- c. Wait for less than PPP idle timeout value.
- d. Force the call to active state.

**Workaround:** none.

- CSCin88505—Active and Dormant Session Counts Incorrect After Handoff

The Active Session Counter and Dormant Session Counter carry junk values upon handoffs. The junk values are observed in the following scenarios:

Scenario 1:

- Open a Simple IP flow with PCF1 --- Keep the session Active
- Handoff the flow to PCF2
- Active Count becomes 2 and Dormant Count Becomes Junk Huge Value.

Scenario 2:

- Open a simple IP flow with PCF1 (keep session active).
- Make the session dormant.
- Handoff the session to PCF2.
- Make the session dormant.
- Active count carries a huge junk value.

**Workaround:** none.

- CSCsa46707—VAM2 Encryption Card Stops Encrypt/Decrypt Traffic After a Few Hours

An SA-VAM2 stops processing all packets.

This condition is observed sporadically on a Cisco 7200 series that is configured with an NPE-G1 when the SA-VAM2 is configured for AES 192 or AES 256.

**Workaround:** Reset the SA-VAM2 by entering the **no crypto engine accelerator** command followed by **crypto engine accelerator** command. If the symptom persists, disable the SA-VAM2 by entering the **no crypto engine accelerator** command. Doing so causes the router to switch to software encryption.

## Caveats Resolved Prior to Cisco IOS Release 12.3(11)YF2

The following caveats are resolved in Cisco IOS Release 12.3(11)YF1:

- CSCef57647—Incorrect PDSN CISCO-CDMA-PDSN-MIB Counter Values

On a Cisco router running R2.0 Packet Data Serving Node (PDSN) software, the CISCO-CDMA-PDSN-MIB counters “cCdmaActiveSessions”, “cCdmaDormantSessions”, and “cCdmaPcfSoRpUpdOtherReaReqs” show incorrect values.

**Workaround:** none.

- CSCef86875—PDSN Reloads While Disabling Conditional Debugging For Prepaid

On Cisco router running Release 2.1 PDSN software, the router reloads while disabling conditional debugging feature for Prepaid Accounting.

The symptom occurs when prepaid accounting is enabled with conditional debugging.

**Workaround:** none.

- CSCeg21567—**show cdma pdsn statistics ppp** - Wrong Release Counter Value

On a Cisco router configured for PDSN, the “release total” counter might increase by 2 instead of 1 in the output of **show cdma pdsn statistics ppp** command.

**Workaround:** none.

- CSCeg33664—PDSN Does Not Send AHDLC FF03 Fields for VPN Traffic

On Cisco Packet Data Service Node (PDSN), when VPDN calls are made from the Mobile Node (MN), the PDSN in the downstream path (packets destined to the mobile) does not include the Address and Control Field (ACF - FF03) in the packet.

**Workaround:** none.
- CSCin77352—[CRP]:Memory Leak While Opening and Closing CRP Sessions at 125 CPS

When closed RP sessions are opened and closed at a high rate on the PDSN, a memory leak occurs. This condition occurs only when closed RP sessions are opened and closed.

**Workaround:** none.
- CSCin86234—Add Message Authenticator Attribute for Prepaid Online Access Requests

The Cisco PDSN does not include a Message-Authenticator attribute in the online Access Requests that are being sent by prepaid sessions for quota retrieval.

**Workaround:** none.
- CSCin86235—Configuring **skip-aaa-reauth** Made the HA Fail MIP Registration

When the **ip mobile foreign-agent skip-aaa-reauthentication** command is configured, the **ip mobile foreign-agent nat traversal force** command also gets configured. This causes the initial RRQ from the PDSN to the HA to fail.

**Workaround:** unconfiguring the **ip mobile foreign-agent nat traversal force** command will help correct this.
- CSCsa44772—PDSN Should Not Send A11 Session Update if Current RNPDIIT <= Previous RNPDIIT

The Cisco PDSN sends session update message to PCF when the RN-PDIIT downloaded is less than RN-PDIIT stored.

This condition occurs when the second MIP flow is opened for a user and the same RN-PDIIT, Always-On values are downloaded from radius server.

**Workaround:** none.
- CSCsa45264—Last Character of Calling Station ID Stripped When PDSN Sends to LNS

On Cisco PDSN running 12.3(8)XW3, when VPDN flows are opened on the A11 session, the PDSN acting as LAC will send an ICRQ to the LNS. In the ICRQ message PDSN will include the Calling Station ID received in the A11 Registration Request. When the Calling Station ID is sent from PDSN, the last character of Calling Station ID is not encoded in the ICRQ to the LNS.

This condition occurs for all VPDN flows opened over the A11 session.

**Workaround:** none.
- CSCsa48683—MWAM Should Return cevC6xxxMWAMBlade When Queried for sysObjectID

The MWAM processor returns a sysObjectId of “ciscoWsSvcMWAM1” instead of “cevC6xxxMWAMBlade”. Because of this, the network management station running RME 4.0 may not be able to identify the device successfully.

This condition occurs when the MWAM processor is running a Cisco IOS image 123(11)YF, or later.

**Workaround:** none.

## Caveats Resolved Prior to Cisco IOS Release 12.3(11)YF1

The following caveats are resolved in Cisco IOS Release 12.3(11)YF:

- CSCed65017—MWAM: Config CLI That Fail Batch Mode Copy Fail config-mode sup

Some configuration commands fail, do not operate properly, or cause dead memory when using batch mode config download or config-mode supervisor.

This problem occurs when the MWAM processor is configured for “supervisor” config-mode.

**Workaround:** use config-mode local on MWAM.
- CSCee45296—MWAM Does Not Retrieve its Configuration From the Supervisor

When using config on supervisor with the MWAM, the processors are not able to retrieve their configurations from the supervisor.

This problem was first seen when using supervisor release 122-18.2.2.SX. This defect would be present in all future supervisor releases when mated with an MWAM IOS image that did not contain this fix.

**Workaround:** configure an arbitrary tftp-server (for example, tftp-server nvram:startup-config) on the supervisor. It does not matter what file you serve up, even one of the mwam configs. If you do serve up one of the MWAM configs, be sure to add the alias: “tftp-server bootflash:SLOTxPCy.cfg alias SLOTxPCy.cfg”.

Supervisor release 122-18.2.2.SX changed the mechanism used by the MWAM processors to retrieve their configurations. This dds changed the mechanism used by the MWAM processors to be compatible with the supervisor IOS change. This dds is also backwards compatible with previous supervisor images.
- CSCef71485—MWAM Processor Reloads While Sending Certain Fragmented Packets

The MWAM reloads while sending fragmented downstream packets.

This problem occurs when you send downstream data with more fragmented packets.

**Workaround:** disable cef .
- CSCin79481—PDSN Reloads When Parsing a MSG\_PENDING Selection Message From Peer

Cisco Packet Data Service Node (PDSN) Release 1.2 will reload when parsing a Messaging pending selection message from a peer participating in a peer-peer model of selection (under the condition explained below), if the PDSN address communicated in the message is not present in its load list.

This condition occurs when the Peer-Peer mode of selection with load balancing is enabled, and a PDSN receives a MSG\_PENDING CVSE and the PDSN address communicated in the message is not present in its load list.

**Workaround:** disable load balancing in peer-peer mode of selection.

## Resolved Caveats Prior to IOS Release 12.3(11)YF

The following caveats are resolved in Cisco IOS Release 12.3(8)XW3:

- CSCed86177—Tracebacks Found On PDSN With CEF and NAT Enabled for SIP flow

A Cisco router running 12.3T R2.0 Release PDSN software sometimes produces tracebacks while sending bidirectional traffic from mobile node to reflector in SIP flow with compress stack enabled and cef switched

This condition occurs while sending bidirectional traffic from mobile node to reflector in SIP flow with compress stack enabled and cef switched .

**Workaround:** none.
- CSCee13372—IPSec Tunnel Goes Down Before Receiving ACK for Revocation Request

When the last mobile tunnel binding is brought down on HA, a revocation message is sent from HA and CDMA IPSec tunnel is brought down without waiting for a revocation acknowledgement message from the PDSN.

This condition has been observed on a router that is running Cisco IOS release 12.3T software.

**Workaround:** none.
- CSCef50548—TOS Value Set to Non-Zero Value for PPP Control Packets

On Cisco router running Release 2.0 PDSN software, during Point to Point (PPP) negotiation, the IPCP control packets sent downstream to the Mobile Node from PDSN are encapsulated using GRE, and then sent to Mobile Node.

The DSCP marking on the Type of Service (TOS) filed in the outer header, was found to be a non-zero (Garbage) value.

This behaviour is seen only when the PPP negotiations happens. If we send traffic over the established tunne, those packets are marked with correct (TOS =0) value.

**Workaround:** none.
- CSCin77744—PDSN Drops Fragmented PCF Packets Intermittently

On the Packet Data Service Node (PDSN), when the Generic Routing Encapsulation (GRE) packets received from the Packet Control Function (PCF), they are dropped intermittently if the packets are fragmented.

Packets drops are seen on the PDSN when the PPP negotiation between the PDSN and Mobile Node Terminates the Compression Control Protocol (CCP), and then during the data transfer the Mobile Node sends another CCP ConfReq to the PDSN.

**Workaround:** By disabling compression on PDSN Virtual Template, packet drop was not observed
- CSCin81236—Conditional Debugging Skips Some RADIUS Msgs for MIP Flows

When conditional debugging is enabled on Cisco PDSN running 12.3(8)XW image, RADIUS related debugs are not shown sometimes for a Mobile IP flow that is opened on the box.

This condition occurs when conditional debugging is set for RADIUS related debugs.

**Workaround:** none.

- CSCin81520—Extra Mobile IP Debugs Are Printed for Conditional Debugging  
Some extra mobile IP debugs are printed on Cisco PDSN running 12.3(08)XW software when mobile IP conditional debugging is enabled on it. Debugs that get printed are not corresponding to the user.  
This condition occurs when conditional debugging for Mobile IP is turned on.  
**Workaround:** none.

## Resolved Caveats Prior to IOS Release 12.3(8)XW3

The following caveats are resolved in Cisco IOS Release 12.3(8)XW2:

- CSCed86144—Tracebacks Found in Clustering  
Cisco router running Packet Data Serving Node (PDSN) Software in redundant cluster controller member environment may show tracebacks on active controller and may lead to a reload.  
This condition occurs under a rare condition when controllers are present in redundancy environment with active and standby controller and simple IP sessions are opened. On the active controller preemption is enabled and this has the higher priority. If active is brought down and recovers, when it tries to take control back from the standby, tracebacks may appear on active controller and may lead to a reload.  
**Workaround:** Disable preemption on the active controller.
- CSCee18749—PDSN deletes only a single flow when POD received  
When the Cisco Packet Data Service Node (PDSN) has multiple MIP flows for the same user and receives a Packet of Disconnect (POD) request with IMSI for the user, it deletes only a single flow for the IMSI. One flow for the IMSI is deleted each time the POD request is resent.  
This problem is only seen when multiple flows with the same username exists for the session.  
**Workaround:** none.
- CSCee31554—ODAP Lease Renewal Out of Sync on Active and Standby  
On Cisco 7600 running HA Release 2.0 image, lease time is not sync on Active and Standby HA's. This will result into out of sync between Active and Standby HA.  
Open 25 k bindings on active and standby HA reload active mwam standby HA become active, and try to renew lease, some subnets are out of sync with server. Unable to renew lease. Server is deleting subnets after lease expiry. Due to this both active and standby bindings are deleted  
**Workaround:** none.
- CSCee81662—PPP May Get Stuck in TERMSENT in High CPU Situation  
PPP sessions may get stuck in the TERMSENT state. This symptom is observed on a Cisco platform that has a high CPU utilization.  
**Workaround:** Clear the underlying layer (VPDN, PPPoA, or PPPoE).
- CSCef09658—Tracebacks [Spurious Memory] Seen in the Standby Controller.  
Tracebacks were seen when a standby controller was added to the cluster.  
**Workaround:** none.

- CSCef18987—POD Debugs Display NACK Error Message For a Valid POD Request

A Cisco PDSN running R2.0 S/W incorrectly displays a NACK message being sent even though it correctly sends an ACK message to RADIUS server in response to a POD request.

This condition occurs when the POD feature is enabled, and the PDSN receives a POD request from RADIUS server with only NAI and NAS-ID and no session identification attributes in it.

**Workaround:** none

- CSCef19117—**ip tcp adjust-mss** Command Fails to Set Value for Outbound Packets

Cisco router configured with the **ip tcp adjust-mss** command may fail to set the value for outbound packets.

The command works on 12.3(7)T2 code, but fails on 12.3(8)T code. This issue is currently seen on a 3700 router.

**Workaround:** disable cef.




---

**Note** This can affect the router performance. This issue is not seen with cef disabled on the router.

---

- CSCef25623—PDSN Reloads While Unconfiguring Cluster Member Interface

A Cisco router running 12.3(7)T3 R1.2 Release of the PDSN software reloads when you unconfigure the **cdma pdsn cluster member interface** command.

**Workaround:** none.

- CSCee31554—ODAP Lease Renewal Out Of Sync on Active and Standby

On a Cisco 7600 running the HA R2.0 Image, the lease time is not synchronized on active and standby HAs. This causes the active and standby HAs to be out of sync.

The following conditions must exist for this problem to occur:

- Open 25k bindings on active and standby HA.
- Reload active MWAM.
- Standby HA become Active, and try to renew lease.
- Some subnets are out of sync with server. Unable to renew lease. Server is deleting subnets after lease expiry. Due to this, both active and standby bindings are deleted

**Workaround:** none.

- CSCef39286—Incorrect Tunnel Endpoint for PMIP Flows While Using HA-SLB.

On Cisco router running Release 2.0 PDSN software, when Proxy MIP flow is opened in a setup with HA-SLB, the MIP tunnel endpoint for the session on the PDSN is incorrect. This causes re-registrations and data transfer through this session to fail.

This symptom occurs when Proxy MIP flow is opened with HA-SLB. This issue is not seen when HA SLB is not used.

**Workaround:** none.

- CSCef59046—Crashed By Bus Error When Issuing IP Mobile

The router reloaded by bus error when the customer issued command **no ip mobile host nai @xxx.xxx.xxx.xxx address pool local ha-pool interface FastEthernet x/x aaa** after configuring **ip mobile host nai @xxx.xxx.xxx.xxx address pool local ha-pool interface FastEthernet x/x aaa**.

**Workaround:** none.

- CSCin78876—MIP CPS Low With MobileIP Global Configuration  
On a Cisco Packet Data Service Node (PDSN), when Mobile IP flows are opened at the rate of 1000 cps, some of Mobile IP flows are closed.  
This occurs when the Mobile IP registration lifetime in the Registration Request is not INFINITE (65535).  
**Workaround:** none.
- CSCin79040—CPS Degradation on Configuring Accounting Start-Stop  
On Cisco Packet Data Serving Node (PDSN), calls per second on a cluster of 8 Members and 2 Controllers is lower than the PRD requirement.  
**Workaround:** none.
- CSCin80761—PDSN Does Not Set Proper PPP Call Fail Reason For Authentication Fail  
Cisco Packet Data Service Node (PDSN) Rel 1.2 sends an invalid PPP call fail reason for authentication fail scenario.  
This condition occurs when sending of PPP call fail reason to a Proprietary PCF is enabled and MN fails authentication in PPP authentication phase.  
**Workaround:** none.

## Related Documentation

Except for feature modules, documentation is available as printed manuals or electronic documents. Feature modules are available online on CCO and the Documentation CD-ROM.

Use these release notes with these documents:

- [Release-Specific Documents, page 36](#)
- [Platform-Specific Documents, page 37](#)
- [Feature Modules, page 37](#)
- [Cisco IOS Software Documentation Set, page 37](#)

## Release-Specific Documents

The following documents are specific to Cisco IOS Release 12.3T:

- *Packet Data Serving Node (PDSN) Release 2.1* at the following url:  
[http://www.cisco.com/en/US/products/sw/wirelssw/ps4341/tsd\\_products\\_support\\_series\\_home.html](http://www.cisco.com/en/US/products/sw/wirelssw/ps4341/tsd_products_support_series_home.html)

The following documents are specific to Release 12.3 and are located on CCO and the Documentation CD-ROM:

- *Cross-Platform Release Notes for Cisco IOS Release 12.3*

On CCO at:

**Technical Documents: Cisco IOS Software Configuration: Cisco IOS Release 12.3: Release Notes: Cross-Platform Release Notes**

- *Caveats for Cisco IOS Release 12.3 T*

See *Caveats for Cisco IOS Release 12.3T*, which contain caveats applicable to all platforms for all maintenance releases of Release 12.3.

On CCO at:

**Technical Documents: Cisco IOS Software Configuration: Cisco IOS Release 12.3: Caveats**




---

**Note** If you have an account with CCO, you can use Bug Navigator II to find caveats of any severity for any release. You can reach Bug Navigator II on CCO at **Software Center: Cisco IOS Software: Cisco Bug Toolkit: Cisco Bugtool Navigator II**, or at <http://www.cisco.com/support/bugtools>.

---

- Product bulletins, field notices, and other release-specific documents on CCO at:

**Technical Documents**

## Platform-Specific Documents

Documentation specific to the Cisco 7206 Router is located at the following locations:

- On Cisco.com at:  
[http://www.cisco.com/en/US/products/hw/routers/ps341/tsd\\_products\\_support\\_series\\_home.html](http://www.cisco.com/en/US/products/hw/routers/ps341/tsd_products_support_series_home.html)

Documentation specific to the Cisco 7600 Router is located at the following location:

- On Cisco.com at:  
[http://www.cisco.com/en/US/products/hw/routers/ps368/tsd\\_products\\_support\\_series\\_home.html](http://www.cisco.com/en/US/products/hw/routers/ps368/tsd_products_support_series_home.html)

Documentation specific to the Cisco Catalyst 6500 Switch is located at the following location:

- On Cisco.com at:  
[http://www.cisco.com/en/US/products/hw/switches/ps708/tsd\\_products\\_support\\_series\\_home.html](http://www.cisco.com/en/US/products/hw/switches/ps708/tsd_products_support_series_home.html)

## Feature Modules

Feature modules describe new features supported by Release 12.3 and are updates to the Cisco IOS documentation set. A feature module consists of a brief overview of the feature, benefits, configuration tasks, and a command reference. As updates, the feature modules are available online only. Feature module information is incorporated in the next printing of the Cisco IOS documentation set.

On CCO at:

**Technical Documents: Cisco IOS Software Configuration: Cisco IOS Release 12.3: New Feature Documentation**

## Cisco IOS Software Documentation Set

The Cisco IOS software documentation set consists of the Cisco IOS configuration guides, Cisco IOS command references, and several other supporting documents that are shipped with your order in electronic form on the Documentation CD-ROM, unless you specifically ordered the printed versions.

## Documentation Modules

Each module in the Cisco IOS documentation set consists of two books: a configuration guide and a corresponding command reference. Chapters in a configuration guide describe protocols, configuration tasks, Cisco IOS software functionality, and contain comprehensive configuration examples. Chapters in a command reference provide complete command syntax information. Use each configuration guide with its corresponding command reference.

On CCO and the Documentation CD-ROM, two master hot-linked documents provide information for the Cisco IOS software documentation set.

On CCO at:

**Technical Documents: Cisco IOS Software Configuration: Cisco IOS Release 12.2: Configuration Guides and Command References**

## Release 12.3 Documentation Set

[Table 3](#) describes the contents of the Cisco IOS Release 12.3 software documentation set, which is available in electronic form and in printed form when ordered.



**Note**

You can find the most current Cisco IOS documentation on CCO and the Documentation CD-ROM. These electronic documents may contain updates and modifications made after the hard-copy documents were printed.

On CCO at:

**Technical Documents: Documentation Home Page: Cisco IOS Software Configuration: Cisco IOS Release 12.3**

**Table 3 Cisco IOS Software Release 12.3 Documentation Set**

Books	Major Topics
<ul style="list-style-type: none"> <li><i>Cisco IOS Configuration Fundamentals Configuration Guide</i></li> <li><i>Cisco IOS Configuration Fundamentals Command Reference</i></li> </ul>	Cisco IOS User Interfaces Cisco IOS File Management Cisco IOS System Management
<ul style="list-style-type: none"> <li><i>Cisco IOS Bridging and IBM Networking Configuration Guide</i></li> <li><i>Cisco IOS Bridging and IBM Networking Command Reference, Volume I</i></li> <li><i>Cisco IOS Bridging and IBM Networking Command Reference, Volume II</i></li> </ul>	Using Cisco IOS Software Overview of SNA Internetworking Bridging IBM Networking

**Table 3 Cisco IOS Software Release 12.3 Documentation Set (continued)**

Books	Major Topics
<ul style="list-style-type: none"> <li>• <i>Cisco IOS Dial Services Configuration Guide: Terminal Services</i></li> <li>• <i>Cisco IOS Dial Services Configuration Guide: Network Services</i></li> <li>• <i>Cisco IOS Dial Services Command Reference</i></li> </ul>	Preparing for Dial Access Modem Configuration and Management ISDN and Signalling Configuration PPP Configuration Dial-on-Demand Routing Configuration Dial-Backup Configuration Terminal Service Configuration Large-Scale Dial Solutions Cost-Control Solutions Virtual Private Networks X.25 on ISDN Solutions Telco Solutions Dial-Related Addressing Services Interworking Dial Access Scenarios
<ul style="list-style-type: none"> <li>• <i>Cisco IOS Interface Configuration Guide</i></li> <li>• <i>Cisco IOS Interface Command Reference</i></li> </ul>	Interface Configuration Overview Configuring LAN Interfaces Configuring Serial Interfaces Configuring Logical Interfaces
<ul style="list-style-type: none"> <li>• <i>Cisco IOS IP and IP Routing Configuration Guide</i></li> <li>• <i>Cisco IOS IP and IP Routing Command Reference</i></li> </ul>	IP Addressing and Services IP Routing Protocols IP Multicast
<ul style="list-style-type: none"> <li>• <i>Cisco IOS AppleTalk and Novell IPX Configuration Guide</i></li> <li>• <i>Cisco IOS AppleTalk and Novell IPX Command Reference</i></li> </ul>	AppleTalk and Novell IPX Overview Configuring AppleTalk Configuring Novell IPX
<ul style="list-style-type: none"> <li>• <i>Cisco IOS Apollo Domain, Banyan VINES, DECnet, ISO CLNS, and XNS Configuration Guide</i></li> <li>• <i>Cisco IOS Apollo Domain, Banyan VINES, DECnet, ISO CLNS, and XNS Command Reference</i></li> </ul>	Apollo Domain, Banyan VINES, DECnet, ISO CLNS, and XNS Overview Configuring Apollo Domain Configuring Banyan VINES Configuring DECnet Configuring ISO CLNS Configuring XNS
<ul style="list-style-type: none"> <li>• <i>Cisco IOS Multiservice Applications Configuration Guide</i></li> <li>• <i>Cisco IOS Multiservice Applications Command Reference</i></li> </ul>	Multiservice Applications Overview Voice Video Broadband
<ul style="list-style-type: none"> <li>• <i>Cisco IOS Quality of Service Solutions Configuration Guide</i></li> <li>• <i>Cisco IOS Quality of Service Solutions Command Reference</i></li> </ul>	Quality of Service Overview Classification Congestion Management Congestion Avoidance Policing and Shaping Signalling Link Efficiency Mechanisms Quality of Service Solutions

**Table 3 Cisco IOS Software Release 12.3 Documentation Set (continued)**

Books	Major Topics
<ul style="list-style-type: none"> <li>• <i>Cisco IOS Security Configuration Guide</i></li> <li>• <i>Cisco IOS Security Command Reference</i></li> </ul>	Security Overview Authentication, Authorization, and Accounting (AAA) Security Server Protocols Traffic Filtering and Firewalls IP Security and Encryption Other Security Features
<ul style="list-style-type: none"> <li>• <i>Cisco IOS Switching Services Configuration Guide</i></li> <li>• <i>Cisco IOS Switching Services Command Reference</i></li> </ul>	Cisco IOS Switching Services Overview Cisco IOS Switching Paths Cisco Express Forwarding NetFlow Switching MPLS Switching Multilayer Switching Multicast Distributed Switching Virtual LANs LAN Emulation
<ul style="list-style-type: none"> <li>• <i>Cisco IOS Wide-Area Networking Configuration Guide</i></li> <li>• <i>Cisco IOS Wide-Area Networking Command Reference</i></li> </ul>	Wide-Area Networking Overview Configuring ATM Configuring Frame Relay Configuring Frame Relay-ATM Interworking Configuring SMDS Configuring X.25 and LAPB
<ul style="list-style-type: none"> <li>• <i>New Features in 12.3-Based Limited Lifetime Releases</i></li> <li>• <i>New Features in Release 12.3 T</i></li> <li>• Release Notes (Release note and caveat documentation for 12.3-based releases and various platforms)</li> <li>• <i>Cisco IOS Debug Command Reference</i></li> <li>• <i>Cisco IOS Dial Services Quick Configuration Guide</i></li> </ul>	



**Note**

*Cisco Management Information Base (MIB) User Quick Reference* is no longer published. If you have an account with CCO, you can find the current list of MIBs supported by Cisco. To reach the *Cisco Network Management Toolkit*, go to CCO, press **Login: Technical Support: Software Center: Network Mgmt Software: Cisco Network Management Toolkit: Cisco MIBs**.

## Obtaining Documentation

### World Wide Web

You can access the most current Cisco documentation on the World Wide Web (WWW) at <http://www.cisco.com>, <http://www-china.cisco.com>, or <http://www-europe.cisco.com>.

## Ordering Documentation

Registered CCO users can order the Documentation CD-ROM and other Cisco Product documentation through our online Subscription Services at <http://www.cisco.com/cgi-bin/subcat/kaojump.cgi>.

Nonregistered CCO users can order documentation through a local account representative by calling Cisco's corporate headquarters (California, USA) at 408 526-4000 or, in North America, call 800 553-NETS (6387).

## Obtaining Technical Assistance

Cisco.com provides a starting point for all technical assistance. Warranty or maintenance contract customers can use the Technical Assistance Center (TAC). All customers can submit technical feedback on Cisco documentation using the web, e-mail, a self-addressed stamped response card included in many Cisco printed documents, or by sending mail to Cisco.

### Technical Assistance Center

The Cisco TAC is available to warranty or maintenance contract customers who need technical assistance with a Cisco product that is under warranty or covered by a maintenance contract.

To display the TAC web site that includes links to technical support information and software upgrades and for requesting TAC support, use <http://www.cisco.com/public/support/tac>.

To contact by e-mail, use one of the following addresses:

Language	E-mail Address
English	<a href="mailto:tac@cisco.com">tac@cisco.com</a>
Hanzi (Chinese)	<a href="mailto:chinese-tac@cisco.com">chinese-tac@cisco.com</a>
Kanji (Japanese)	<a href="mailto:japan-tac@cisco.com">japan-tac@cisco.com</a>
Hangul (Korean)	<a href="mailto:korea-tac@cisco.com">korea-tac@cisco.com</a>
Spanish	<a href="mailto:tac@cisco.com">tac@cisco.com</a>
Thai	<a href="mailto:thai-tac@cisco.com">thai-tac@cisco.com</a>

In North America, TAC can be reached at 800 553-2447 or 408 526-7209. For other telephone numbers and TAC e-mail addresses worldwide, consult the following web site: <http://www.cisco.com/warp/public/687/Directory/DirTAC.shtml>.

## Software Configuration Tips on the Cisco Technical Assistance Center Home Page

If you have a CCO login account, you can access the following URL, which contains links and tips on configuring your Cisco products:

[http://www.cisco.com/kobayashi/technotes/serv\\_tips.shtml](http://www.cisco.com/kobayashi/technotes/serv_tips.shtml)

This URL is subject to change without notice. If it changes, point your Web browser to CCO and click on this path: **Technical Assistance Center: Technical Tips**.

The following sections are provided from the Technical Tips page:

- Access Dial Cookbook—Contains common configurations or recipes for configuring various access routes and dial technologies.
- Field Notices—Notifies you of any critical issues regarding Cisco products and includes problem descriptions, safety or security issues, and hardware defects.
- Frequently Asked Questions—Describes the most frequently asked technical questions about Cisco hardware and software.
- Hardware—Provides technical tips related to specific hardware platforms.
- Hot Tips—Describes popular tips and hints gathered from the Cisco Technical Assistance Center (TAC). Most of these documents are available from the TAC Fax-on-demand service. To reach Fax-on-demand and receive documents at your fax machine from the United States, call 888-50-CISCO (888-502-4726). From other areas, call 650-596-4408.
- Internetworking Features—Lists tips on using Cisco IOS software features and services.
- Sample Configurations—Provides actual configuration examples that are complete with topology and annotations.

## Documentation Feedback

If you are reading Cisco product documentation on the World Wide Web, you can submit technical comments electronically. Click **Feedback** in the toolbar and select **Documentation**. After you complete the form, click **Submit** to send it to Cisco.

You can e-mail your comments to [bug-doc@cisco.com](mailto:bug-doc@cisco.com).

To submit your comments by mail, for your convenience many documents contain a response card behind the front cover. Otherwise, you can mail your comments to the following address:

Cisco Systems, Inc.  
 Document Resource Connection  
 170 West Tasman Drive  
 San Jose, CA 95134-9883

We appreciate and value your comments.

This document is to be used in conjunction with the documents listed in the [“Related Documentation”](#) section.

CCSP, CCVP, the Cisco Square Bridge logo, Follow Me Browsing, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Access Registrar, Aironet, ASIST, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Empowering the Internet Generation, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, FormShare, GigaDrive, GigaStack, HomeLink, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MeetingPlace, MGX, the Networkers logo, Networking Academy, Network Registrar, *Packet*, PIX, Post-Routing, Pre-Routing, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, StrataView Plus, TeleRouter, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0502R)

Copyright © 2005, Cisco Systems, Inc.  
All rights reserved.





