



---

# Monitoring and Maintaining NAT

---

**First Published: May 2, 2005**

**Last Updated: February 16, 2009**

This module describes how to:

- Monitor Network Address Translation (NAT) using translation information and statistics displays.
- Maintain NAT by clearing NAT translations before the timeout has expired.
- Enable logging of NAT translation by way of syslog to log and track system error messages, exceptions, and other information.

## Finding Feature Information

Your software release may not support all the features documented in this module. For the latest feature information and caveats, see the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the [“Feature Information for Monitoring and Maintaining NAT” section on page 11](#).

Use Cisco Feature Navigator to find information about platform support and Cisco IOS and Catalyst OS software image support. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>. An account on Cisco.com is not required.

## Contents

- [Prerequisites for Monitoring and Maintaining NAT, page 2](#)
- [Information About Monitoring and Maintaining NAT, page 2](#)
- [How to Monitor and Maintain NAT, page 3](#)
- [Examples for Monitoring and Maintaining NAT, page 7](#)
- [Where to Go Next, page 8](#)
- [Additional References, page 9](#)



---

**Americas Headquarters:**

**Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA**

# Prerequisites for Monitoring and Maintaining NAT

Before performing the tasks in the module, you should be familiar with the concepts described in the “Configuring NAT for IP Address Conservation” module and have NAT configured.

## Information About Monitoring and Maintaining NAT

Before performing the tasks in this module, you should understand the following concepts:

- [NAT Display Contents, page 2](#)
- [Syslog Usage, page 3](#)

## NAT Display Contents

There are two basic types of IP NAT translation information:

- [Translation Entries, page 2](#)
- [Statistical Information, page 2](#)

### Translation Entries

Translation entry information includes the following:

- The protocol of the port identifying the address.
- The legitimate IP address that represents one or more inside local IP addresses to the outside world.
- The IP address assigned to a host on the inside network; probably not a legitimate address assigned by the NIC or service provider.
- The IP address of an outside host as it appears to the inside network; probably not a legitimate address assigned by the NIC or service provider.
- The IP address assigned to a host on the outside network by its owner.
- The time since the entry was created (in hours:minutes:seconds).
- The time since the entry was last used (in hours:minutes:seconds).
- Flags indicating the type of translation. Possible flags are:
  - extended—Extended translation
  - static—Static translation
  - destination—Rotary translation
  - outside—Outside translation
  - timing out—Translation will no longer be used, due to a TCP finish (FIN) or reset (RST) flag.

### Statistical Information

Statistical information includes the following:

- The total number of translations active in the system. This number is incremented each time a translation is created and is decremented each time a translation is cleared or times out.

- A list of interfaces marked as outside with the **ip nat outside** command.
- A list of interfaces marked as inside with the **ip nat inside** command.
- The number of times the software does a translations table lookup and finds an entry.
- The number of times the software does a translations table lookup, fails to find an entry, and must try to create one.
- A cumulative count of translations that have expired since the router was booted.
- Information about dynamic mappings.
- Information about an inside source translation.
- The access list number being used for the translation.
- The name of the pool.
- The number of translations using this pool.
- The IP network mask being used in the pool.
- The starting IP address in the pool range.
- The ending IP address in the pool range.
- The type of pool. Possible types are generic or rotary.
- The number of addresses in the pool available for translation.
- The number of addresses being used.
- The number of failed allocations from the pool.

NAT does not support ACL with the log option. The same functionality can be achieved by using one of the following options:

- By having a physical interface or VLAN with the logging option
- By using NetFlow
- By using the syslog feature

## Syslog Usage

Syslog Analysis lets you centrally log and track system error messages, exceptions, and other information (such as device configuration changes). You can use the logged error message data to analyze router and network performance. You can customize Syslog Analysis to produce the information and message reports important to your operation.

For more information see the *Resource Manager Essentials and Syslog Analysis: How-To* document:

[http://www.cisco.com/warp/public/477/RME/rme\\_syslog.html](http://www.cisco.com/warp/public/477/RME/rme_syslog.html)

## How to Monitor and Maintain NAT

This section contains the following procedures:

- [Displaying NAT Translation Information, page 4](#) (optional)
- [Clearing NAT Entries Before the Timeout, page 5](#) (optional)

- [Enabling Syslog for Logging NAT Translations, page 6](#) (optional)

## Displaying NAT Translation Information

Perform this task to display translation data and statistical information.

### SUMMARY STEPS

1. `enable`
2. `show ip nat translations [verbose]`
3. `show ip nat statistics`

### DETAILED STEPS

	Command or Action	Purpose
Step 1	<code>enable</code>  <b>Example:</b> Router> <code>enable</code>	Enables privileged EXEC mode. <ul style="list-style-type: none"> <li>• Enter your password if prompted.</li> </ul>
Step 2	<code>show ip nat translations [verbose]</code>  <b>Example:</b> Router# <code>show ip nat translations</code>	(Optional) Displays active NAT translations.
Step 3	<code>show ip nat statistics</code>  <b>Example:</b> Router# <code>show ip nat statistics</code>	(Optional) Displays active NAT translation statistics.

## Displaying NAT Translation Information: Examples

This section contains the following examples:

- [Displaying NAT Translations, page 4](#)
- [Displaying NAT Statistics, page 5](#)

### Displaying NAT Translations

The following is sample output from the `show ip nat translations` command. Without overloading, two inside hosts are exchanging packets with some number of outside hosts.

```
Router# show ip nat translations
```

```
Pro Inside global      Inside local      Outside local      Outside global
--- 192.168.2.1        192.168.2.12      ---                ---
--- 192.168.2.21      192.168.2.89     ---                --
```

With overloading, a translation for a Domain Name Server (DNS) transaction is still active, and translations for two Telnet sessions (from two different hosts) are also active. Note that two different inside hosts appear on the outside with a single IP address.

```
Router# show ip nat translations
```

```
Pro Inside global      Inside local      Outside local      Outside global
udp 192.168.2.20:1220  192.168.2.95:1220 192.168.2.22:53 192.168.2.20:53
tcp 192.168.2.20:11012 192.168.2.209:11012 192.168.1.220:23 192.168.2.20:23
tcp 192.168.2.20:1067 192.168.2.20:1067 192.168.2.20:23 192.168.2.20:23
```

The following is sample output that includes the **verbose** keyword:

```
Router# show ip nat translations verbose
```

```
Pro Inside global      Inside local      Outside local      Outside global
udp 192.168.2.20:1220 192.168.2.23:1220 192.168.2.24:53 192.168.2.25:53
      create 00:00:02, use 00:00:00, flags: extended
tcp 192.168.2.23:11012 192.168.2.30:11012 192.168.2.20:23 192.168.2.28:23
      create 00:01:13, use 00:00:50, flags: extended
tcp 192.168.2.24:1067 192.168.2.29:1067 192.168.2.20:23 192.168.2.50:23
      create 00:00:02, use 00:00:00, flags: extended
```

### Displaying NAT Statistics

The following is sample output from the **show ip nat statistics** command:

```
Router# show ip nat statistics
```

```
Total translations: 2 (0 static, 2 dynamic; 0 extended)
Outside interfaces: Serial0
Inside interfaces: Ethernet1
Hits: 135 Misses: 5
Expired translations: 2
Dynamic mappings:
-- Inside Source
access-list 1 pool net-208 refcount 2
  pool net-208: netmask 255.255.255.240
    start 192.168.0.0 end 192.168.255.255
    type generic, total addresses 14, allocated 2 (14%), misses 0
```

## Clearing NAT Entries Before the Timeout

By default, dynamic address translations will time out from the NAT translation table at some point. Perform this task to clear the entries before the timeout.

## SUMMARY STEPS

1. **enable**
2. **clear ip nat translation inside** *global-ip local-ip* [**outside** *local-ip global-ip*]
3. **clear ip nat translation outside** *global-ip local-ip*
4. **clear ip nat translation protocol inside** *global-ip global-port local-ip local-port* [**outside** *local-ip local-port-global-ip global-port*]
5. **clear ip nat translation** *{\* | [forced] | [inside global-ip local-ip] [outside local-ip global-ip]}*

## DETAILED STEPS

	Command or Action	Purpose
Step 1	<b>enable</b>  <b>Example:</b> Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"><li>• Enter your password if prompted.</li></ul>
Step 2	<b>clear ip nat translation inside</b> <i>global-ip local-ip</i> [ <b>outside</b> <i>local-ip global-ip</i> ]  <b>Example:</b> Router# clear ip nat translation udp inside 192.168.2.209 1220 192.168.2.95 1220 192.168.2.100 53 192.168.2.101 53	(Optional) Clears a simple dynamic translation entry containing an inside translation, or both inside and outside translation.
Step 3	<b>clear ip nat translation outside</b> <i>global-ip local-ip</i>  <b>Example:</b> Router# clear ip nat translation outside 192.168.2.100 1220 192.168.2.80	(Optional) Clears a simple dynamic translation entry containing an outside translation.
Step 4	<b>clear ip nat translation protocol inside</b> <i>global-ip global-port local-ip local-port</i> [ <b>outside</b> <i>local-ip local-port-global-ip global-port</i> ]  <b>Example:</b> Router# clear ip nat translation udp inside 192.168.2.209 1220 192.168.2.195 1220 192.168.2.13 53 192.168.2.132 53	(Optional) Clears a UDP translation entry.
Step 5	<b>clear ip nat translation</b> <i>{*   [forced]   [inside global-ip local-ip] [outside local-ip global-ip]}</i>  <b>Example:</b> Router# clear ip nat translation *	(Optional) Clears all dynamic translations.

## Enabling Syslog for Logging NAT Translations

The logging of NAT translations can be enabled and disabled by way of the **syslog** command.

Syslog Analysis lets you centrally log and track system error messages, exceptions, and other information (such as NAT translations). You can use the logged error message data to analyze router and network performance. You can customize Syslog Analysis to produce the information and message reports important to your operation.

## Prerequisites

Prior to performing this task, you must specify the necessary **syslog** commands such as making sure that logging is enabled, configuring the server's IP address, and establishing the level of messages to be trapped.

## SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip nat log translations syslog**
4. **no logging console**

## DETAILED STEPS

	Command or Action	Purpose
Step 1	<b>enable</b>  <b>Example:</b> Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"><li>• Enter your password if prompted.</li></ul>
Step 2	<b>configure terminal</b>  <b>Example:</b> Router# configure terminal	Enters global configuration mode.
Step 3	<b>ip nat log translations syslog</b>  <b>Example:</b> Router(config)# ip nat log translations syslog	Enables the syslog for logging NAT translations.
Step 4	<b>no logging console</b>  <b>Example:</b> Router(config)# no logging console	(Optional) Disables the log display to the console. <ul style="list-style-type: none"><li>• Logging to the console is enable by default.</li></ul>

## Examples for Monitoring and Maintaining NAT

This section provides the following configuration examples:

- [Clearing UDP NAT Translations: Example, page 8](#)
- [Enabling Syslog: Example, page 8](#)

## Clearing UDP NAT Translations: Example

The following example shows the NAT entries before and after the User Datagram Protocol (UDP) entry is cleared:

```
Router# show ip nat translation

Pro Inside global      Inside local      Outside local      Outside global

udp 192.168.2.20:1220  192.168.2.95:1220 192.168.2.22:53 192.168.2.20:53

tcp 192.168.2.20:11012 192.168.2.209:11012 171.69.1.220:23 192.168.2.20:23

tcp 192.168.2.20:1067 192.168.2.20:1067 192.168.2.20:23 192.168.2.20:23

Router# clear ip nat translation udp inside 192.168.2.20:1067 192.168.2.20:1067
192.168.2.20:23 192.168.2.20:23

Router# show ip nat translation

Pro Inside global      Inside local      Outside local      Outside global

udp 192.168.2.20:1220 192.168.2.95:1220 192.168.2.22:53 192.168.2.20:53

tcp 192.168.2.20:11012 192.168.2.209:11012 171.69.1.220:23 192.168.2.20:23
```

## Enabling Syslog: Example

The following example shows how to NAT entries into syslog.

```
Router(config)# logging on
Router(config)# logging 1.1.1.1
Router(config)# logging trap informational
Router(Config)# ip nat log translations syslog
```

The format of NAT information logged (for example, for ICMP Ping via NAT Overload configurations) will be as follows:

```
Apr 25 11:51:29 [10.0.19.182.204.28] 1: 00:01:13: NAT:Created icmp
135.135.5.2:7 171 12.106.151.30:7171 54.45.54.45:7171
54.45.54.45:7171
Apr 25 11:52:31 [10.0.19.182.204.28] 8: 00:02:15: NAT:Deleted icmp
135.135.5.2:7 172 12.106.151.30:7172 54.45.54.45:7172
54.45.54.45:7172
```

## Where to Go Next

- To configure NAT for use with application level gateways, see the “Using Application Level Gateways with NAT” module.
- To integrate NAT with MPLS VPNs, see the “Integrating NAT with MPLS VPNs” module.
- To configure NAT for high availability, see the “Configuring NAT for High Availability” module.

# Additional References

The following sections provide references related to Monitoring and Maintaining NAT.

## Related Documents

Related Topic	Document Title
NAT commands: complete command syntax, command mode, command history, defaults, usage guidelines, and examples	" <i>IP Addressing Commands</i> " chapter in the <i>Cisco IOS IP Command Reference, Volume 1 of 3: Addressing and Services</i> , Release 12.3.

## Standards

Standard	Title
None	

## MIBs

MIB	MIBs Link
None	To locate and download MIBs for selected platforms, Cisco IOS releases, and feature sets, use Cisco MIB Locator found at the following URL: <a href="http://www.cisco.com/go/mibs">http://www.cisco.com/go/mibs</a>

## RFCs

RFC	Title
None	

## Technical Assistance

Description	Link
<p>The Cisco Support website provides extensive online resources, including documentation and tools for troubleshooting and resolving technical issues with Cisco products and technologies.</p> <p>To receive security and technical information about your products, you can subscribe to various services, such as the Product Alert Tool (accessed from Field Notices), the Cisco Technical Services Newsletter, and Really Simple Syndication (RSS) Feeds.</p> <p>Access to most tools on the Cisco Support website requires a Cisco.com user ID and password.</p>	<p><a href="http://www.cisco.com/techsupport">http://www.cisco.com/techsupport</a></p>

## Command Reference

The following commands are introduced or modified in the feature or features documented in this module. For information about these commands, see the *Cisco IOS <Technology> Command Reference* at [http://www.cisco.com/en/US/docs/ios/ipaddr/command/reference/iad\\_cr\\_book.html](http://www.cisco.com/en/US/docs/ios/ipaddr/command/reference/iad_cr_book.html). For information about all Cisco IOS commands, use the Command Lookup Tool at <http://tools.cisco.com/Support/CLILookup> or the *Cisco IOS Master Command List, All Releases*, at [http://www.cisco.com/en/US/docs/ios/mcl/allreleasemcl/all\\_book.html](http://www.cisco.com/en/US/docs/ios/mcl/allreleasemcl/all_book.html).

This feature uses no new or modified commands.

# Feature Information for Monitoring and Maintaining NAT

Table 1 lists the features in this module and provides links to specific configuration information. Only features that were introduced or modified in Cisco IOS Release 12.2(1) or Cisco IOS Releases 12.2(1) or 12.0(3)S or a later release appear in the table.

Not all commands may be available in your Cisco IOS software release. For release information about a specific command, see the command reference documentation.

Use Cisco Feature Navigator to find information about platform support and software image support. Cisco Feature Navigator enables you to determine which Cisco IOS and Catalyst OS Software images support a specific software release, feature set, or platform. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>. An account on Cisco.com is not required.


**Note**

Table 1 lists only the Cisco IOS software release that introduced support for a given feature in a given Cisco IOS software release train. Unless noted otherwise, subsequent releases of that Cisco IOS software release train also support that feature.

**Table 1** Feature Information for Monitoring and Maintaining NAT

Feature Name	Releases	Feature Information
This table is intentionally left blank because no features were introduced or modified in Cisco IOS Release 12.2(1) or later. This table will be updated when feature information is added to this module.	—	—

CCDE, CCENT, Cisco Eos, Cisco HealthPresence, the Cisco logo, Cisco Lumin, Cisco Nexus, Cisco StadiumVision, Cisco TelePresence, Cisco WebEx, DCE, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn and Cisco Store are service marks; and Access Registrar, Aironet, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0812R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

© 2009 Cisco Systems, Inc. All rights reserved.

