



# Intelligent Services Gateway Features Roadmap

---

**First Published: March 20, 2006**  
**Last Updated: November 20, 2009**

This feature roadmap lists the Cisco IOS features documented in the *Cisco IOS Intelligent Services Gateway Configuration Guide* and maps them to the documents in which they appear. The roadmap is organized so that you can select your release train and see the features in that release. Find the feature name you are searching for and click on the URL in the “Where Documented” column to access the document containing that feature.

## Feature and Release Support

Table 1 lists ISG feature support for the following Cisco IOS software release trains:

- [Cisco IOS Release 12.2SB](#)
- [Cisco IOS Release 12.2SR](#)

Use Cisco Feature Navigator to find information about platform support and software image support. Cisco Feature Navigator enables you to determine which Cisco IOS and Catalyst OS software images support a specific software release, feature set, or platform. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>. An account on Cisco.com is not required.



### Note

---

Table 1 lists only the Cisco IOS software release that introduced support for a given feature in a given Cisco IOS software release train. Unless noted otherwise, subsequent releases of that Cisco IOS software release train also support that feature.

---

Table 1 lists the most recent release of each software train first and the features in alphabetical order within the release.



---

**Americas Headquarters:**  
**Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA**

**Table 1 Supported ISG Features in Cisco IOS Releases 12.2SB and 12.2(33)SR**

Release	Feature Name	Feature Description	Where Documented
<b>Cisco IOS Release 12.2SB</b>			
12.2(31)SB2	ISG:Policy Control: Policy Server: CoA ASCII Command Code Support	This feature enables ISG to receive ASCII command codes for Account Logon, Account Logoff, Service Logon, Service Logoff, and Account Status queries and to perform the required functionality based on the command code.	<a href="#">Cisco IOS ISG RADIUS Interface Guide</a>
12.2(31)SB2	ISG:Policy Control: RADIUS Proxy Enhancement	The ISG RADIUS proxy feature enables ISG to serve as a proxy between a client device that uses RADIUS authentication and a AAA server. ISG RADIUS proxy functionality enables ISG to “sniff” (look at) the RADIUS packet flows and, upon successful authentication, transparently create a corresponding ISG session.	<a href="#">Configuring ISG as a RADIUS Proxy</a>
12.2(31)SB2	IP Subscriber Session CLI Updates	Some of the commands that are used to configure ISG IP subscriber sessions were modified or replaced in this release.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(28)SB	ISG:Accounting: Per Session, Service, and Flow	ISG accounting provides a means to bill for account or service usage. ISG accounting uses the RADIUS protocol to facilitate interaction between ISG and an external RADIUS-based AAA or mediation server.	<a href="#">Configuring ISG Accounting</a>
12.2(28)SB	ISG:Accounting: Postpaid	ISG accounting provides a means to bill for account or service usage. ISG sends accounting start and stop records for sessions and services to an accounting server for postpaid billing. The accounting server interprets the records to generate bills.	<a href="#">Configuring ISG Accounting</a>
12.2(28)SB	ISG:Accounting: Tariff Switching	ISG accounting provides a means to bill for account or service usage. Where billing rates change at fixed times and sessions are active across the boundary at which the rates change, ISG will provides accounting data to the billing server indicating the boundary. Tariff switching can also be used between accounting methods, such as switching from prepaid billing to post paid billing.	<a href="#">Configuring ISG Accounting</a> <a href="#">Configuring ISG Support for Prepaid Billing</a>
12.2(28)SB	ISG:Accounting: Time-Based Prepaid	ISG prepaid billing support allows ISG to check a subscriber’s available credit to determine whether to allow the subscriber access to a service and how long the access can last. ISG supports time-based prepaid billing.	<a href="#">Configuring ISG Support for Prepaid Billing</a>
12.2(28)SB	ISG:Accounting: Volume-Based Prepaid	ISG prepaid billing support allows ISG to check a subscriber’s available credit to determine whether to allow the subscriber access to a service and how long the access can last. ISG supports volume-based prepaid billing.	<a href="#">Configuring ISG Support for Prepaid Billing</a>
12.2(28)SB	ISG:Authentication: DHCP Option 82 Line ID - AAA Authorization Support	This feature enhances ISG automatic subscriber logon by providing support for authorization on the basis of the circuit-Id and remote-Id.	<a href="#">Configuring ISG Policies for Automatic Subscriber Logon</a>

**Table 1** Supported ISG Features in Cisco IOS Releases 12.2SB and 12.2(33)SR

Release	Feature Name	Feature Description	Where Documented
12.2(28)SB	ISG:Flow Control: Flow Redirect	The ISG Layer 4 Redirect feature enables service providers to better control the user experience by allowing subscriber TCP or UDP packets to be redirected to specified servers for appropriate handling. ISG Layer 4 redirection can be applied to individual subscriber sessions or flows.	<a href="#">Redirecting Subscriber Traffic Using ISG Layer 4 Redirect</a>
12.2(28)SB	ISG:Flow Control: QoS Control: Dynamic Rate Limiting	ISG can change the allowed bandwidth of a session or flow by dynamically applying rate-limiting policies.	<a href="#">Configuring ISG Network Forwarding Policies</a>
12.2(28)SB	ISG:Instrumentation: Advanced Conditional Debugging	ISG provides the ability to define various conditions for filtering debug output. Conditional debugging generates very specific and relevant information that can be used for session, flow, subscriber, and service diagnostics.	<a href="#">Troubleshooting ISG with Session Monitoring and Distributed Conditional Debugging</a>
12.2(28)SB	ISG:Instrumentation: Session and Flow Monitoring	ISG provides a mechanism for continuously monitoring interface and CPU statistics. This feature introduces the <b>show interface monitor</b> and <b>show processes cpu monitor</b> commands, which display statistics that are updated at specified intervals.	<a href="#">Troubleshooting ISG with Session Monitoring and Distributed Conditional Debugging</a>
12.2(28)SB	ISG:Network Interface: IP Routed, VRF-Aware MPLS	ISG supports several types of forwarding to connect subscriber sessions to networks. These connections can be to the Internet, corporate intranets, ISPs, or walled gardens for content delivery. ISG supports both routed and MPLS-enabled interfaces for network access.	<a href="#">Configuring ISG Network Forwarding Policies</a>
12.2(28)SB	ISG:Network Interface: Tunneled (L2TP)	ISG supports several types of forwarding to connect subscriber sessions to networks. These connections can be to Internet, corporate Intranets, ISPs or walled gardens for content delivery. ISG supports tunneled interfaces to networks.	<a href="#">Configuring ISG Network Forwarding Policies</a>
12.2(28)SB	ISG:Policy Control: Cisco Policy Language	ISG control policies are a structured replacement for feature-specific configuration commands and allow configurable functionality to be expressed in terms of an event, a condition, and an action. Control policies provide an intuitive and extensible framework, with a consistent set of CLI commands, for specifying system behavior. The ISG policy language is aligned with the Cisco Common Classification Policy Language (C3PL).	<a href="#">Configuring ISG Control Policies</a>
12.2(28)SB	ISG:Policy Control: DHCP Proxy	This feature enables ISG to dynamically interact with DHCP and apply policies that influence the IP addresses that DHCP assigns to subscribers.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(28)SB	ISG:Policy Control: Multidimensional Identity per Session	ISG control policies provide a flexible way to collect pieces of subscriber identity during session establishment. Control policies also allow session policy to be applied iteratively as more elements of identity become available to the system.	<a href="#">Configuring ISG Control Policies</a>

**Table 1 Supported ISG Features in Cisco IOS Releases 12.2SB and 12.2(33)SR**

Release	Feature Name	Feature Description	Where Documented
12.2(28)SB	ISG:Policy Control: Policy: Domain Based (Auto-domain, Proxy)	ISG control policies manage the primary services and rules used to enforce particular contracts. Polices can be configured to interpret the domain as a request to activate the service associated with that domain name, allowing users to automatically receive services in accordance with the domain that they are attempting to connect.	<a href="#">Configuring ISG Control Policies</a>
12.2(28)SB	ISG:Policy Control: Policy: Triggers	ISG control policies can be configured with time-based, volume-based, and duration-based policy triggers. Time-based triggers use an internal clock, allowing policies to be applied at specific times. Volume-based triggers are based on packet count; when the packet count reaches a specified value, the specified policy is applied. Duration-based triggers are based on an internal timer. Upon expiration of the timer, the specified policy is applied.	<a href="#">Configuring ISG Control Policies</a>
12.2(28)SB	ISG:Policy Control: Policy Server: CoA	This feature provides ISG support for the RADIUS Change of Authorization (CoA) extension, which facilitates dynamic authorization.	<a href="#">Enabling ISG to Interact with External Policy Servers</a>
12.2(28)SB	ISG:Policy Control: Policy Server: SSG-SESM Protocol	ISG supports Cisco's proprietary protocol to communicate with the SESM policy server.	<a href="#">Cisco SSG-to-ISG DSL Broadband Migration Guide</a>
12.2(28)SB	ISG:Policy Control: Service Profiles	ISG defines a service as a collection of policies that can be applied to any subscriber session. Services can be configured on the router or on an external AAA server.	<a href="#">Configuring ISG Subscriber Services</a>
12.2(28)SB	ISG:Policy Control: User Profiles	ISG user profiles specify services and functionality that should be applied to ISG sessions for the specified subscriber. User profiles are defined on an external AAA server.	<a href="#">Overview of ISG</a>
12.2(28)SB	ISG:Session: Auth: PBHK	The ISG Port-Bundle Host Key feature serves as an in-band signaling mechanism for session identification at external portals. TCP packets from subscribers are mapped to a local IP address for the ISG gateway and a range of ports. This mapping allows the portal to identify the ISG gateway from which the session originated.	<a href="#">Configuring ISG Port-Bundle Host Key</a>
12.2(28)SB	ISG:Session: Auth: Single Sign-On	Single sign-on eliminates the need to authenticate a session more than once when a subscriber has access to services provided by other devices in the administrative domain of the access or service provider.	<a href="#">Overview of ISG</a>

**Table 1** Supported ISG Features in Cisco IOS Releases 12.2SB and 12.2(33)SR

Release	Feature Name	Feature Description	Where Documented
12.2(28)SB	ISG:Session: Authentication	ISG automatic subscriber logon enables another specified identifier to be used in place of the username in authorization requests. Enabling the AAA server to authorize subscribers on the basis of a specified identifier allows subscriber profiles to be downloaded from the AAA server as soon as packets are received from subscribers.	<a href="#">Configuring ISG Policies for Automatic Subscriber Logon</a>
12.2(28)SB	ISG:Session: Creation: Interface IP Session: L2	ISG IP interface sessions include all IP traffic received on a specific physical or virtual interface. IP interface sessions are provisioned through the CLI; that is, a session is created when the IP interface session commands are entered.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(28)SB	ISG:Session: Creation: Interface IP Session: L3	ISG IP interface sessions include all IP traffic received on a specific physical or virtual interface. IP interface sessions are provisioned through the CLI; that is, a session is created when the IP interface session commands are entered.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(28)SB	ISG:Session: Creation: IP Session: Protocol Event (DHCP)	Most ISG sessions are created upon detection of a data flow that cannot be affiliated with an already active session. An ISG can be configured to create an IP session upon receipt of the first DHCP DISCOVER packet received from a subscriber.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(28)SB	ISG:Session: Creation: IP Session: Subnet and Source IP: L2	The ISG session is the primary component used for associating services and policies across specific data flows. An IP subnet session is an ISG session that includes any IP traffic from a single IP subnet. A source-IP-based session includes traffic from a single source IP address.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(28)SB	ISG: Session: Creation: IP Session: Subnet and Source IP: L3	The ISG session is the primary component used for associating services and policies across specific data flows. An IP subnet session is an ISG session that includes any IP traffic from a single IP subnet. A source-IP-based session includes traffic from a single source IP address.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(28)SB	ISG:Session: Creation: P2P Session (PPPoE, PPPoXoX)	The ISG session is the primary context to which services and policies are associated across specific data flows. Point-to-point (P2P) sessions are established through a signaling protocol. ISG handles many variants of P2P encapsulation, such as PPP, PPPoE, and PPPoA.	<a href="#">Configuring ISG Access for PPP Sessions</a>
12.2(28)SB	ISG:Session: Lifecycle: Idle Timeout	The ISG idle timeout controls how long a connection can be idle before it is terminated.	<a href="#">Configuring ISG Policies for Session Maintenance</a>

**Table 1 Supported ISG Features in Cisco IOS Releases 12.2SB and 12.2(33)SR**

Release	Feature Name	Feature Description	Where Documented
12.2(28)SB	ISG:Session: Lifecycle: Packet of Disconnect (POD)	An ISG can be configured to interact with external policy servers. A policy server can use RADIUS Packet of Disconnect (POD) to manage the life cycle of any ISG session. The primary role of the POD message is to terminate an ISG session.	<a href="#">Configuring ISG Policies for Session Maintenance</a>
12.2(28)SB	ISG:Session: VRF Transfer	The ISG session is the primary component used for associating services and policies with specific data flows. ISG sessions are associated with virtual routing and forwarding instances when routing is required for the network service. ISG VRF transfer provides a means to dynamically switch an active session between virtual routing domains.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
<b>Cisco IOS Release 12.2SR</b>			
12.2(33)SRE	ISG:AAA Wireless Enhancements	RADIUS proxy enhancements provide additional support for mobile wireless environments. It includes changes to RADIUS attribute 31 processing.	<a href="#">Configuring ISG as a RADIUS Proxy</a>
12.2(33)SRE	ISG:Authentication: RADIUS Proxy WiMax Enhancements	RADIUS proxy enhancements provide additional support for WiMax broadband environments.	<a href="#">Configuring ISG as a RADIUS Proxy</a>
12.2(33)SRE	ISG: Instrumentation: DHCP Lease Query Support	The DHCP Lease Query transaction is a DHCP transaction with special message types that enable, among other things, clients to query DHCP servers regarding the owner and the lease-expiration-time of an IP address.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(33)SRE	ISG: Policy Control: Differentiated Initial Policy Control	This feature provides minimal or temporary network access to subscribers when the RADIUS servers are down or cannot be accessed because of network problems.	<a href="#">Configuring ISG Control Policies</a>
12.2(33)SRE	ISG: Session: Multicast: Coexistence	This feature introduces the ability to host all the subscribers and services (data and multicast) on the same VLAN by enabling multicast and IP sessions to coexist on the same subinterface.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(33)SRE	ISG: Static Session Creation	This feature enables administrator-initiated static IP sessions	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(33)SRC	IP Subscriber Session CLI Updates	Some of the commands that are used to configure ISG IP subscriber sessions were modified or replaced in this release.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(33)SRC	ISG:Accounting: Per Session, Service, and Flow	ISG accounting provides a means to bill for account or service usage. ISG accounting uses the RADIUS protocol to facilitate interaction between ISG and an external RADIUS-based AAA or mediation server.	<a href="#">Configuring ISG Accounting</a>

**Table 1** Supported ISG Features in Cisco IOS Releases 12.2SB and 12.2(33)SR

Release	Feature Name	Feature Description	Where Documented
12.2(33)SRC	ISG:Accounting: Postpaid	ISG accounting provides a means to bill for account or service usage. ISG sends accounting start and stop records for sessions and services to an accounting server for postpaid billing. The accounting server interprets the records to generate bills.	<a href="#">Configuring ISG Accounting</a>
12.2(33)SRC	ISG:Accounting: Tariff Switching	ISG accounting provides a means to bill for account or service usage. Where billing rates change at fixed times and sessions are active across the boundary at which the rates change, ISG will provides accounting data to the billing server indicating the boundary. Tariff switching can also be used between accounting methods, such as switching from prepaid billing to post paid billing.	<a href="#">Configuring ISG Accounting</a> <a href="#">Configuring ISG Support for Prepaid Billing</a>
12.2(33)SRC	ISG:Accounting: Time-Based Prepaid	ISG prepaid billing support allows ISG to check a subscriber's available credit to determine whether to allow the subscriber access to a service and how long the access can last. ISG supports time-based prepaid billing.	<a href="#">Configuring ISG Support for Prepaid Billing</a>
12.2(33)SRC	ISG:Accounting: Volume-Based Prepaid	ISG prepaid billing support allows ISG to check a subscriber's available credit to determine whether to allow the subscriber access to a service and how long the access can last. ISG supports volume-based prepaid billing.	<a href="#">Configuring ISG Support for Prepaid Billing</a>
12.2(33)SRC	ISG:Authentication: DHCP Option 82 Line ID - AAA Authorization Support	This feature enhances ISG automatic subscriber logon by providing support for authorization on the basis of the circuit-Id and remote-Id.	<a href="#">Configuring ISG Policies for Automatic Subscriber Logon</a>
12.2(33)SRC	ISG:Flow Control: Flow Redirect	The ISG Layer 4 Redirect feature enables service providers to better control the user experience by allowing subscriber TCP or UDP packets to be redirected to specified servers for appropriate handling. ISG Layer 4 redirection can be applied to individual subscriber sessions or flows.	<a href="#">Redirecting Subscriber Traffic Using ISG Layer 4 Redirect</a>
12.2(33)SRC	ISG:Flow Control: QoS Control: Dynamic Rate Limiting	ISG can change the allowed bandwidth of a session or flow by dynamically applying rate-limiting policies.	<a href="#">Configuring ISG Network Forwarding Policies</a>
12.2(33)SRC	ISG:Instrumentation: Advanced Conditional Debugging	ISG provides the ability to define various conditions for filtering debug output. Conditional debugging generates very specific and relevant information that can be used for session, flow, subscriber, and service diagnostics.	<a href="#">Troubleshooting ISG with Session Monitoring and Distributed Conditional Debugging</a>
12.2(33)SRC	ISG:Instrumentation: Session and Flow Monitoring	ISG provides a mechanism for continuously monitoring interface and CPU statistics. This feature introduces the <b>show interface monitor</b> and <b>show processes cpu monitor</b> commands, which display statistics that are updated at specified intervals.	<a href="#">Troubleshooting ISG with Session Monitoring and Distributed Conditional Debugging</a>

**Table 1** Supported ISG Features in Cisco IOS Releases 12.2SB and 12.2(33)SR

Release	Feature Name	Feature Description	Where Documented
12.2(33)SRC	ISG:Network Interface: IP Routed, VRF-Aware MPLS	ISG supports several types of forwarding to connect subscriber sessions to networks. These connections can be to the Internet, corporate intranets, ISPs, or walled gardens for content delivery. ISG supports both routed and MPLS-enabled interfaces for network access.	<a href="#">Configuring ISG Network Forwarding Policies</a>
12.2(33)SRC	ISG:Network Interface: Tunneled (L2TP)	ISG supports several types of forwarding to connect subscriber sessions to networks. These connections can be to Internet, corporate Intranets, ISPs or walled gardens for content delivery. ISG supports tunneled interfaces to networks.	<a href="#">Configuring ISG Network Forwarding Policies</a>
12.2(33)SRC	ISG:Policy Control: Cisco Policy Language	ISG control policies are a structured replacement for feature-specific configuration commands and allow configurable functionality to be expressed in terms of an event, a condition, and an action. Control policies provide an intuitive and extensible framework, with a consistent set of CLI commands, for specifying system behavior. The ISG policy language is aligned with the Cisco Common Classification Policy Language (C3PL).	<a href="#">Configuring ISG Control Policies</a>
12.2(33)SRC	ISG:Policy Control: DHCP Proxy	This feature enables ISG to dynamically interact with DHCP and apply policies that influence the IP addresses that DHCP assigns to subscribers.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(33)SRC	ISG:Policy Control: ISG-SCE Control Bus	This feature enables integration of an ISG device with an SCE device at the control plane level, allowing the two devices to work as one when policies are applied to a subscriber session.	<a href="#">Configuring ISG Integration with SCE</a>
12.2(33)SRC	ISG:Policy Control: Multidimensional Identity per Session	ISG control policies provide a flexible way to collect pieces of subscriber identity during session establishment. Control policies also allow session policy to be applied iteratively as more elements of identity become available to the system.	<a href="#">Configuring ISG Control Policies</a>
12.2(33)SRC	ISG:Policy Control: Policy: Domain Based (Auto-domain, Proxy)	ISG control policies manage the primary services and rules used to enforce particular contracts. Policies can be configured to interpret the domain as a request to activate the service associated with that domain name, allowing users to automatically receive services in accordance with the domain that they are attempting to connect.	<a href="#">Configuring ISG Control Policies</a>
12.2(33)SRC	ISG:Policy Control: Policy: Triggers	ISG control policies can be configured with time-based, volume-based, and duration-based policy triggers. Time-based triggers use an internal clock, allowing policies to be applied at specific times. Volume-based triggers are based on packet count; when the packet count reaches a specified value, the specified policy is applied. Duration-based triggers are based on an internal timer. Upon expiration of the timer, the specified policy is applied.	<a href="#">Configuring ISG Control Policies</a>

**Table 1** Supported ISG Features in Cisco IOS Releases 12.2SB and 12.2(33)SR

Release	Feature Name	Feature Description	Where Documented
12.2(33)SRC	ISG:Policy Control: Policy Server: CoA	This feature provides ISG support for the RADIUS Change of Authorization (CoA) extension, which facilitates dynamic authorization.	<a href="#">Enabling ISG to Interact with External Policy Servers</a>
12.2(33)SRC	ISG:Policy Control: Policy Server: CoA ASCII Command Code Support	This feature enables ISG to receive ASCII command codes for Account Logon, Account Logoff, Service Logon, Service Logoff, and Account Status queries and to perform the required functionality based on the command code.	<a href="#">Cisco IOS ISG RADIUS Interface Guide</a>
12.2(33)SRC	ISG:Policy Control: Policy Server: SSG-SESM Protocol	ISG supports Cisco's proprietary protocol to communicate with the SESM policy server.	<a href="#">Cisco SSG-to-ISG DSL Broadband Migration Guide</a>
12.2(33)SRC	ISG:Policy Control: RADIUS Proxy Enhancement	The ISG RADIUS proxy feature enables ISG to serve as a proxy between a client device that uses RADIUS authentication and a AAA server. ISG RADIUS proxy functionality enables ISG to "sniff" (look at) the RADIUS packet flows and, upon successful authentication, transparently create a corresponding ISG session.	<a href="#">Configuring ISG as a RADIUS Proxy</a>
12.2(33)SRC	ISG:Policy Control: Service Profiles	ISG defines a service as a collection of policies that can be applied to any subscriber session. Services can be configured on the router or on an external AAA server.	<a href="#">Configuring ISG Subscriber Services</a>
12.2(33)SRC	ISG:Policy Control: User Profiles	ISG user profiles specify services and functionality that should be applied to ISG sessions for the specified subscriber. User profiles are defined on an external AAA server.	<a href="#">Overview of ISG</a>
12.2(33)SRC	ISG:Session: Auth: PBHK	The ISG Port-Bundle Host Key feature serves as an in-band signaling mechanism for session identification at external portals. TCP packets from subscribers are mapped to a local IP address for the ISG gateway and a range of ports. This mapping allows the portal to identify the ISG gateway from which the session originated.	<a href="#">Configuring ISG Port-Bundle Host Key</a>
12.2(33)SRC	ISG:Session: Auth: Single Sign-On	Single sign-on eliminates the need to authenticate a session more than once when a subscriber has access to services provided by other devices in the administrative domain of the access or service provider.	<a href="#">Overview of ISG</a>
12.2(33)SRC	ISG:Session: Authentication	ISG automatic subscriber logon enables another specified identifier to be used in place of the username in authorization requests. Enabling the AAA server to authorize subscribers on the basis of a specified identifier allows subscriber profiles to be downloaded from the AAA server as soon as packets are received from subscribers.	<a href="#">Configuring ISG Policies for Automatic Subscriber Logon</a>

**Table 1** Supported ISG Features in Cisco IOS Releases 12.2SB and 12.2(33)SR

Release	Feature Name	Feature Description	Where Documented
12.2(33)SRC	ISG:Session: Creation: Interface IP Session: L2	ISG IP interface sessions include all IP traffic received on a specific physical or virtual interface. IP interface sessions are provisioned through the CLI; that is, a session is created when the IP interface session commands are entered.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(33)SRC	ISG:Session: Creation: Interface IP Session: L3	ISG IP interface sessions include all IP traffic received on a specific physical or virtual interface. IP interface sessions are provisioned through the CLI; that is, a session is created when the IP interface session commands are entered.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(33)SRC	ISG:Session: Creation: IP Session: Protocol Event (DHCP)	Most ISG sessions are created upon detection of a data flow that cannot be affiliated with an already active session. An ISG can be configured to create an IP session upon receipt of the first DHCP DISCOVER packet received from a subscriber.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(33)SRC	ISG:Session: Creation: IP Session: Subnet and Source IP: L2	The ISG session is the primary component used for associating services and policies across specific data flows. An IP subnet session is an ISG session that includes any IP traffic from a single IP subnet. A source-IP-based session includes traffic from a single source IP address.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(33)SRC	ISG: Session: Creation: IP Session: Subnet and Source IP: L3	The ISG session is the primary component used for associating services and policies across specific data flows. An IP subnet session is an ISG session that includes any IP traffic from a single IP subnet. A source-IP-based session includes traffic from a single source IP address.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(33)SRC	ISG:Session: Creation: P2P Session (PPPoE, PPPoXoX)	The ISG session is the primary context to which services and policies are associated across specific data flows. Point-to-point (P2P) sessions are established through a signaling protocol. ISG handles many variants of P2P encapsulation, such as PPP, PPPoE, and PPPoA.	<a href="#">Configuring ISG Access for PPP Sessions</a>
12.2(33)SRC	ISG:Session: Lifecycle: Idle Timeout	The ISG idle timeout controls how long a connection can be idle before it is terminated.	<a href="#">Configuring ISG Policies for Session Maintenance</a>
12.2(33)SRC	ISG:Session: Lifecycle: Packet of Disconnect (POD)	An ISG can be configured to interact with external policy servers. A policy server can use RADIUS Packet of Disconnect (POD) to manage the life cycle of any ISG session. The primary role of the POD message is to terminate an ISG session.	<a href="#">Configuring ISG Policies for Session Maintenance</a>

**Table 1** Supported ISG Features in Cisco IOS Releases 12.2SB and 12.2(33)SR

Release	Feature Name	Feature Description	Where Documented
12.2(33)SRC	ISG:Session: VRF Transfer	The ISG session is the primary component used for associating services and policies with specific data flows. ISG sessions are associated with virtual routing and forwarding instances when routing is required for the network service. ISG VRF transfer provides a means to dynamically switch an active session between virtual routing domains.	<a href="#">Configuring ISG Access for IP Subscriber Sessions</a>
12.2(33)SRC	ISG:Session Protection and Resiliency: Keepalive—ARP, ICMP	This feature allows IP subscriber session health to be monitored by configuring keepalive messages using ARP or ICMP, depending upon the type of connection to be monitored.	<a href="#">Configuring ISG Policies for Session Maintenance</a>
12.2(33)SRC	ISG: Subscriber Aware Ethernet	This feature makes ISG functionality available on the Cisco 7600 router.  The following ISG accounting functions are not supported on the Cisco 7600 router: <ul style="list-style-type: none"> <li>• Per service</li> <li>• Per flow</li> <li>• Postpaid</li> <li>• Tariff switching</li> <li>• Time-based or volume-based prepaid</li> </ul>	<a href="#">ISG: Subscriber Aware Ethernet</a>
12.2(33)SRC	Service Gateway Interface	The SGI implements a web services interface to access the policy, subscriber, and session management functionality of ISG.	<a href="#">Service Gateway Interface</a>

CCDE, CCENT, CCSI, Cisco Eos, Cisco HealthPresence, Cisco IronPort, the Cisco logo, Cisco Nurse Connect, Cisco Pulse, Cisco SensorBase, Cisco StackPower, Cisco StadiumVision, Cisco TelePresence, Cisco Unified Computing System, Cisco WebEx, DCE, Flip Channels, Flip for Good, Flip Mino, Flipshare (Design), Flip Ultra, Flip Video, Flip Video (Design), Instant Broadband, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn, Cisco Capital, Cisco Capital (Design), Cisco:Financed (Stylized), Cisco Store, Flip Gift Card, and One Million Acts of Green are service marks; and Access Registrar, Aironet, AllTouch, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Lumin, Cisco Nexus, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, Continuum, EtherFast, EtherSwitch, Event Center, Explorer, Follow Me Browsing, GainMaker, iLYNX, IOS, iPhone, IronPort, the IronPort logo, Laser Link, LightStream, Linksys, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, PCNow, PIX, PowerKEY, PowerPanels, PowerTV, PowerTV (Design), PowerVu, Prisma, ProConnect, ROSA, SenderBase, SMARTnet, Spectrum Expert, StackWise, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0910R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2006–2009 Cisco Systems, Inc. All rights reserved.

