



# Service Gateway Interface

---

**First Published: July 25, 2008**

**Last Updated: September 22, 2008**

The Service Gateway Interface (SGI) feature implements a web services interface to access the policy, subscriber, and session management functionality of the Intelligent Services Gateway (ISG). It allows application developers to author subscriber management applications using commonly available commercial and open source protocols, encoding, and toolkits.

ISG is a framework of components for the policy-based control of sessions and services on network devices. The SGI feature comprises the data model for policy and associated elements and the operational interface to provision, update, delete, and control activation of those policies.

## Finding Feature Information

Your software release may not support all the features documented in this module. For the latest feature information and caveats, see the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the [“Feature Information for Service Gateway Interface” section on page 8](#).

Use Cisco Feature Navigator to find information about platform support and Cisco IOS and Catalyst OS software image support. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>. An account on Cisco.com is not required.

## Contents

- [Restrictions for Service Gateway Interface, page 2](#)
- [Information About Service Gateway Interface, page 2](#)
- [How to Enable Service Gateway Interface, page 2](#)
- [Configuration Examples for Service Gateway Interface, page 5](#)
- [Additional References, page 6](#)
- [Feature Information for Service Gateway Interface, page 8](#)



---

**Americas Headquarters:**

**Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA**

# Restrictions for Service Gateway Interface

The SGI feature does not support HTTP transport policies in Release 12.2(33)SRC.

No client has currently been developed to access the SGI feature in Release 12.2(33)SRC.

## Information About Service Gateway Interface

Before you configure Service Gateway Interface you should understand the following concepts:

- [ISG, page 2](#)
- [BEEP, page 2](#)
- [Benefits of SGI, page 2](#)

### ISG

ISG is a Cisco IOS software feature set that provides a structured framework in which edge devices can deliver flexible and scalable services to subscribers. See [Overview of ISG](#) for further information

### BEEP

Block Extensible Exchange Protocol (BEEP) is a protocol standard that is scalable, efficient, simple, extensible, and robust. BEEP is a framework for designing application protocols.

### Benefits of SGI

SGI is a protocol that allows Cisco IOS software to be controlled using third-party applications, toolkits, and development platforms for web services.

The SGI feature is a common model that can express ISG provisioning in many languages, and it is easy to use.

## How to Enable Service Gateway Interface

This section contains the following tasks:

- [Configuring BEEP Listener Connection, page 2](#) (required)
- [Troubleshooting SGI, page 3](#) (optional)

### Configuring BEEP Listener Connection

Perform this task to enable SGI.

## SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **sgi beep listener** [*port*] [**acl** *access-list*] [**sasl** *sasl-profile*] [**encrypt** *trustpoint*]
4. **command** [**keyword** *argument*]
5. **exit**

## DETAILED STEPS

	Command or Action	Purpose
Step 1	<b>enable</b>  <b>Example:</b> Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"><li>• Enter your password if prompted.</li></ul>
Step 2	<b>configure terminal</b>  <b>Example:</b> Router# configure terminal	Enters global configuration mode.
Step 3	<b>sgi beep listener</b> [ <i>port</i> ] [ <b>acl</b> <i>access-list</i> ] [ <b>sasl</b> <i>sasl-profile</i> ] [ <b>encrypt</b> <i>trustpoint</i> ]  <b>Example:</b> Router(config)# sgi beep listener 2089	Enables the SGI feature.
Step 4	<b>end</b>  <b>Example:</b> Router(config)# end	Exits global configuration mode.

## Troubleshooting SGI

Perform this task to troubleshoot the SGI.

### SUMMARY STEPS

1. **enable**
2. **show sgi** [**session** | **statistics**]
3. **debug sgi** [**error** | **info** | **xml** | **gsi** | **isg-api** | **all**]
4. **test sgi xml** *filename*

### DETAILED STEPS

- |        |  |
|--------|--|
| Step 1 | <b>enable</b><br><br>Enables privilege EXEC mode. Enter your password if prompted. |
| Step 2 | <b>show sgi</b> [ <b>session</b>   <b>statistics</b> ]                             |

Displays information about current SGI session. This command shows information about SGI sessions that have been started and are currently running, including the running state. It also shows statistical information about SGI sessions that have been started and are currently running. The following is sample output from this command:

```
Router# show sgi session
```

```
sgi sessions: open 1(max 10, started 15
session id:1;started at 9:08:05; state OPEN
```

```
Router# show sgi statistics
```

```
sgi statistics
total messages received 45
current active messages 5; maximum active messages 7
total isg service requests 4
current active services 2; maximum active services 2

sgi process statistics
process sgi handler 1
pid 95, cpu percent (last minute) 1, cpu runtime 10(msec), memory accocated 4200 (bytes)
```

### Step 3 debug sgi [error | info | xml | gsi | isg-api | all]

Enables debugging of SGI sessions. The following is sample output from this command when all debugging has been enabled:

```
Router# debug sgi all
```

```
Router# show debug
```

```
SGI:
SGI All debugging is on
SGI Errors debugging is on
SGI XML debugging is on
SGI Informational debugging is on
SGI Generic Service Interface debugging is on
SGI ISG_API Events debugging is on
SGI ISG_API Errors debugging is on
Router#
```

```
Router#
```

```
*Jul 1 20:55:11.364: SGI: Session created, session Id 7
*Jul 1 20:55:11.372: sgi beep listen app beep[0x66245188]: frame_available: type=M
number=1 answer=-1 more=* size=1400

*Jul 1 20:55:11.372: sgi beep listen app beep[0x66245188]: Content-Type: application/xml

<?xml version="1.0" encoding="UTF-8"?>
...
*Jul 1 20:55:11.372: sgi beep listen app beep[0x66245188]: frame_available: type=M
number=1 answer=-1 more=. size=111

*Jul 1 20:55:11.372: sgi beep listen app beep[0x66245188]: gitypes:policyGroup>

</objects>
</sgiops:insertPolicyObjectsRequest>
...
*Jul 1 20:55:11.372: SGI: GSI message received, msgid 1, session 7
*Jul 1 20:55:11.376: SGI: XML parsed successfully, request insertPolicyObjectsRequest,
msgid 1
*Jul 1 20:55:11.376: SGI: authentication request sent to AAA
*Jul 1 20:55:11.376: SGI: req = [0x67454088] authentication succeeded
*Jul 1 20:55:11.376: SGI: Processing insertPolicyObjectsRequest
```

```
*Jul 1 20:55:11.376: SGI: insertPolicyObjectsRequest processing policyGroup:VPDN1, type 1,
result: 0
*Jul 1 20:55:11.376: SGI: Processing insertPolicyObjectsResponse
*Jul 1 20:55:11.376: SGI: GSI message sent, msgid 1, session 7
*Jul 1 20:55:12.088: sgi beep listen app beep[0x66245188]: close confirmation: status=+ no
error origin=L scope=C
*Jul 1 20:55:12.088: SGI: Session terminating, session Id 7
Router#
```

**Step 4** `test sgi xml filename`

Verifies the format of an SGI XML request. The XML file must be copied to the router before it can be used.

---

## Configuration Examples for Service Gateway Interface

This section provides the following configuration examples:

- [Configuring BEEP Listener Connection: Example, page 5](#)

### Configuring BEEP Listener Connection: Example

The following example shows how to configure the BEEP listener connection. The port number is set to 2089.

```
enable
configure terminal
sgi beep listener 2089
```

# Additional References

The following sections provide references related to the Service Gateway Interface feature.

## Related Documents

Related Topic	Document Title
Overview of ISG	<i>Cisco IOS Intelligent Services Gateway Configuration Guide</i> ,
ISG commands	<i>Cisco IOS Intelligent Services Gateway Command Reference</i>

## Standards

Standard	Title
None	—

## MIBs

MIB	MIBs Link
<ul style="list-style-type: none"> <li>None</li> </ul>	<p>To locate and download MIBs for selected platforms, Cisco IOS releases, and feature sets, use Cisco MIB Locator found at the following URL:</p> <p><a href="http://www.cisco.com/go/mibs">http://www.cisco.com/go/mibs</a></p>

## RFCs

RFC	Title
None	—

## Technical Assistance

Description	Link
<p>The Cisco Support website provides extensive online resources, including documentation and tools for troubleshooting and resolving technical issues with Cisco products and technologies.</p> <p>To receive security and technical information about your products, you can subscribe to various services, such as the Product Alert Tool (accessed from Field Notices), the Cisco Technical Services Newsletter, and Really Simple Syndication (RSS) Feeds.</p> <p>Access to most tools on the Cisco Support website requires a Cisco.com user ID and password.</p>	<p><a href="http://www.cisco.com/techsupport">http://www.cisco.com/techsupport</a></p>

# Feature Information for Service Gateway Interface

Table 1 lists the release history for this feature.

Not all commands may be available in your Cisco IOS software release. For release information about a specific command, see the command reference documentation.

Use Cisco Feature Navigator to find information about platform support and software image support. Cisco Feature Navigator enables you to determine which Cisco IOS and Catalyst OS software images support a specific software release, feature set, or platform. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>. An account on Cisco.com is not required.



## Note

Table 1 lists only the Cisco IOS software release that introduced support for a given feature in a given Cisco IOS software release train. Unless noted otherwise, subsequent releases of that Cisco IOS software release train also support that feature.

**Table 1** Feature Information for Service Gateway Interface

Feature Name	Releases	Feature Information
Service Gateway Interface	12.2(33)SRC	The SGI implements a web services interface to access the policy, subscriber, and session management functionality of ISG.  The following commands were introduced or modified: <b>debug sgi, sgi beep listener, show sgi, test sgi xml.</b>

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2008 Cisco Systems, Inc. All rights reserved.