



DNS Server Support for NS Records

This feature module describes the DNS Server Support for NS Records feature and includes the following sections:

- [Feature Overview, page 1](#)
- [Supported Platforms, page 2](#)
- [Supported Standards, MIBs, and RFCs, page 2](#)
- [Configuration Tasks, page 2](#)
- [Configuration Examples, page 3](#)
- [Command Reference, page 4](#)

Feature Overview

Domain Name System (DNS) is a client/server mechanism used to access a distributed database. The server portion of the DNS client/server mechanism is the name server (NS). An NS can be responsible for presenting information about a portion of the DNS distributed database or can be a forwarding/caching NS. In the latter case, the NS queries other NSs rather than maintaining a local portion of the DNS database.

DistributedDirector has improved server load-balancing capacity with the DNS Server Support for NS Records feature. This feature adds support for NS records to the Cisco IOS DNS server. With this feature, the DistributedDirector can distribute the server-selection process to multiple DistributedDirectors, improving overall server capacity.

Benefits

This feature allows an NS to delegate server responsibility for a domain by returning an NS record when queried. This function is useful to DistributedDirector because a computationally load can be distributed over a large number of DistributedDirectors, so each DistributedDirector can be free to perform computational expensive actions to select the best server.



Americas Headquarters:
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

© 2007 Cisco Systems, Inc. All rights reserved.

Related Documents

For more information on the Cisco DistributedDirector, see the following documents, which are located on Cisco.com at <http://www.cisco.com/univercd/cc/td/doc/product/iaabu/distrdir/index.htm>:

- Cisco DistributedDirector 4700-M Installation and Configuration Guide
- Release Notes for Cisco DistributedDirector System Software
- Cisco DistributedDirector Enhancements for Release 11.1(18)IA
- Cisco DistributedDirector Enhancements for Release 11.1(25)IA
- Cisco DistributedDirector Enhancements for Release 11.1(28)IA
- Cisco DistributedDirector Enhancements for Release 12.1(5)T
- Dynamic Feedback Protocol Support in DistributedDirector

Supported Platforms

- Cisco DistributedDirector 4500

Supported Standards, MIBs, and RFCs

Standards

None

MIBs

None

To obtain lists of supported MIBs by platform and Cisco IOS release, and to download MIB modules, go to the Cisco MIB website on Cisco.com at the following URL:

<http://www.cisco.com/public/sw-center/netmgmt/cmtk/mibs.shtml>

RFCs

DNS is defined in RFC 1035.

Configuration Tasks

See the following sections for configuration tasks for this feature. Each task in the list is identified as either required or optional.

- [Configuring DNS Server Support for NS Records](#) (required)
- [Verifying DNS Server Support for NS Records](#) (optional)

Configuring DNS Server Support for NS Records

To configure the DistributedDirector to create an NS resource record to be returned when the DNS server is queried for the associated domain, use the following commands in global configuration mode:

	Command	Purpose
Step 1	Router(config)# ip host www.xyz.com ns ns.xyz.com	Configures the DistributedDirector to create an NS resource record to be returned when the DNS server is queried for the associated domain.
Step 2	Router(config)# ip host ns.xyz.com 10.0.0.1 10.0.0.2 10.0.0.3	Defines a static host-name-to-address mapping in the host cache.
Step 3	Router(config)# ip director host ns.xyz.com priority random 1	Configures the order in which the DistributedDirector considers metrics when picking a server.
Step 4	Router(config)# ip dns primary xyz.com soa ns.xyz.com	Identifies the DistributedDirector as the primary DNS NS for a domain and as the SOA record source.

Verifying DNS Server Support for NS Records

To verify that the DistributedDirector is configured with NS record support, use the **show running-config** command or the **show host** command.

Configuration Examples

This section provides the following configuration example:

- [DNS Server Support for NS Records Example](#)

DNS Server Support for NS Records Example

The following example shows a top-level DistributedDirector using a low-cost metric, such as portion or random, to distribute load over second-level DistributedDirectors. Second-level DistributedDirectors then use more expensive metrics, such as drp-ext or drp-rtt, to perform more precise server selection. The relevant portions of this configuration are show below:

Top-Level DistributedDirector

```
ip host www.xyz.com ns ns.xyz.com
ip host ns2.xyz.com 10.0.0.1 10.0.0.2 10.0.0.3
ip director host ns.xyz.com priority random 1
ip dns primary www.xyz.com soa ns2.xyz.com
```

Second-Level DistributedDirector

```
ip host www.xyz.com 10.0.0.4 10.0.0.5 10.0.0.6
ip director host www.xyz.com priority drp-ext 1
ip director host www.xyz.com priority drp-rtt 2
ip director server 10.0.0.4 drp-association 10.0.0.7
ip director server 10.0.0.5 drp-association 10.0.0.8
ip director server 10.0.0.6 drp-association 10.0.0.9
```

Command Reference

The following new command is pertinent to this feature. To see the command pages for this command and other commands used with this feature, go to the *Cisco IOS Master Commands List*, Release 12.4, at <http://www.cisco.com/univercd/cc/td/doc/product/software/ios124/124mindx/124index.htm>.

- **ip host ns**

CCVP, the Cisco logo, and Welcome to the Human Network are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn is a service mark of Cisco Systems, Inc.; and Access Registrar, Aironet, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, iQuick Study, LightStream, Linksys, MeetingPlace, MGX, Networkers, Networking Academy, Network Registrar, PIX, ProConnect, ScriptShare, SMARTnet, StackWise, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0711R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2007 Cisco Systems, Inc. All rights reserved.