



HTTP Client API for Tcl IVR

The HTTP Client API for Tcl IVR feature provides support for Tcl IVR applications to retrieve data from or post data to an HTTP server. Also introduced with this feature is a new command-line interface structure for configuring voice applications and support for additional Tcl 8.3.4 commands.

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest feature information and caveats, see the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the [“Feature Information for HTTP Client API for Tcl IVR”](#) section on page 4.

Use Cisco Feature Navigator to find information about platform support and Cisco IOS and Catalyst OS software image support. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>. An account on Cisco.com is not required.

Contents

- [Prerequisites for HTTP Client API for Tcl IVR and New Cisco Voice Application Command-Line Interface Structure, page 1](#)
- [Restrictions for HTTP Client API for Tcl IVR and New Cisco Voice Application Command-Line Interface Structure, page 2](#)
- [Information About HTTP Client API for Tcl IVR and New Cisco Voice Application Command-Line Interface Structure, page 2](#)

Prerequisites for HTTP Client API for Tcl IVR and New Cisco Voice Application Command-Line Interface Structure

- Familiarity with Tcl IVR, VoiceXML, and Cisco IOS commands.
- Required hardware:



Americas Headquarters:
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

© 2005-2006 Cisco Systems, Inc. All rights reserved.

- Cisco 3600 series
- Cisco AS5300
- Cisco AS5350
- Cisco AS5400
- Cisco AS5800
- Cisco AS58550
- Required software:
 - Cisco IOS Release 12.3(14)T or later
 - Tcl 8.3.4
 - VoiceXML 2.0

Restrictions for HTTP Client API for Tcl IVR and New Cisco Voice Application Command-Line Interface Structure

If Cisco IOS configuration commands are used within the Tcl scripts, submode commands must be entered as quoted arguments on the same line as the configuration command.

Information About HTTP Client API for Tcl IVR and New Cisco Voice Application Command-Line Interface Structure

- [HTTP API for Tcl IVR 2.0, page 2](#)
- [Newly-Supported Tcl 8.3.4 Commands, page 2](#)
- [New Cisco Voice Application Command-Line Interface Structure, page 3](#)

HTTP API for Tcl IVR 2.0

An HTTP application programming interface to the IOS HTTP client is provided. The HTTP package is accessed using the **package require httpios 1.0** Tcl command. Additional commands are provided to configure HTTP. See the [Tcl IVR API Version 2.0 Programming Guide](#) for more information.

Newly-Supported Tcl 8.3.4 Commands

The following Tcl 8.3.4 commands are now supported:

- cd
- close
- eof
- fconfigure
- file

- fileevent
- flush
- glob
- namespace
- open
- package
- pwd
- read
- seek

The following command is modified:

- puts

See the [Tcl IVR API Version 2.0 Programming Guide](#) for more information.

New Cisco Voice Application Command-Line Interface Structure

The **call application voice** command structure for configuring Tcl and IVR applications has been restructured to provide easier configuration of application parameters than the earlier CLI structure.

For more information, see the “[Cisco IOS Release 12.3\(14\)T and Later Voice Application Command-Line Interface Structure Changes](#)” section in [Configuring Basic Functionality for Tcl IVR and VoiceXML Applications](#) in the *Cisco IOS Tcl IVR and VoiceXML Application Guide*.

Feature Information for HTTP Client API for Tcl IVR

Table 1 lists the release history for this feature.

Not all commands may be available in your Cisco IOS software release. For release information about a specific command, see the command reference documentation.

Use Cisco Feature Navigator to find information about platform support and software image support. Cisco Feature Navigator enables you to determine which Cisco IOS and Catalyst OS software images support a specific software release, feature set, or platform. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>. An account on Cisco.com is not required.



Note

Table 1 lists only the Cisco IOS software release that introduced support for a given feature in a given Cisco IOS software release train. Unless noted otherwise, subsequent releases of that Cisco IOS software release train also support that feature.

Table 1 Feature Information for <Phrase Based on Module Title>

Feature Name	Releases	Feature Information
HTTP Client API for Tcl IVR	12.3(14)T	This feature was introduced.

CCDE, CCENT, Cisco Eos, Cisco Lumin, Cisco Nexus, Cisco StadiumVision, Cisco TelePresence, Cisco WebEx, the Cisco logo, DCE, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn and Cisco Store are service marks; and Access Registrar, Aironet, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0809R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2005-2006 Cisco Systems, Inc. All rights reserved.