



# Regulating Packet Flow on a Per-Interface Basis — Using Generic Traffic Shaping

---

Packet flow on a network can be regulated using a traffic shaping mechanism. One such traffic shaping mechanism is a Cisco feature called Generic Traffic Shaping (GTS). Generic Traffic Shaping allows you to regulate the flow of packets going out an interface or subinterface, matching the packet flow to the speed of the interface. This module describes the concepts and tasks related to configuring Generic Traffic Shaping.

## Module History

This module was first published on May 2, 2005, and last updated on May 2, 2005.

## Finding Feature Information in This Module

Your Cisco IOS software release may not support all of the features documented in this module. For the latest feature information and caveats, see the release notes for your platform and software release. To reach links to specific feature documentation in this module and to see a list of the releases in which each feature is supported, use the [“Feature Information for Generic Traffic Shaping”](#) section on page 11.

## Finding Support Information for Platforms and Cisco IOS and Catalyst OS Software Images

Use Cisco Feature Navigator to find information about platform support and Cisco IOS and Catalyst OS software image support. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>. An account on Cisco.com is not required.

## Contents

- [Prerequisites for Configuring Generic Traffic Shaping, page 2](#)
- [Restrictions for Configuring Generic Traffic Shaping, page 2](#)
- [Information About Configuring Generic Traffic Shaping, page 2](#)
- [How to Configure Generic Traffic Shaping, page 3](#)
- [Configuration Examples for Generic Traffic Shaping, page 8](#)
- [Where to Go Next, page 9](#)



---

**Americas Headquarters:**  
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

© 2007 Cisco Systems, Inc. All rights reserved.

- [Additional References](#), page 9
- [Feature Information for Generic Traffic Shaping](#), page 11

## Prerequisites for Configuring Generic Traffic Shaping

### Knowledge

- Be familiar with the concepts in the “[Regulating Packet Flow Using Traffic Shaping](#)” module.

### Platform Support

- Use Feature Navigator to determine if the platform in use supports GTS. Access Cisco Feature Navigator at <http://www.cisco.com/go/fn>.

## Restrictions for Configuring Generic Traffic Shaping

- GTS is not supported on the following interfaces:
  - Multilink PPP (MLP) interfaces
  - Integrated Services Digital Networks (ISDNs), dialer interfaces, or generic routing encapsulation (GRE) tunnel interfaces on the Cisco 7500 series router
- GTS is not supported with flow switching.

## Information About Configuring Generic Traffic Shaping

To configure GTS, you should understand the following concepts:

- [Generic Traffic Shaping Functionality](#), page 2
- [Adaptive Generic Traffic Shaping on Frame Relay Networks](#), page 3
- [Benefits of Generic Traffic Shaping](#), page 3

## Generic Traffic Shaping Functionality

GTS is a traffic shaping mechanism (also known as a “traffic shaper”). A traffic shaper typically delays excess traffic using a buffer, or queueing mechanism, to hold packets and shape the flow when the data rate of the source is higher than expected. It holds and shapes traffic to a particular bit rate by using the token bucket mechanism. See the “[Regulating Packet Flow Using Traffic Shaping](#)” module.



### Note

---

GTS is similar to Class-Based Traffic Shaping. Although Class-Based Traffic Shaping is the Cisco-recommended mechanism, GTS is still supported.

---

GTS supports traffic shaping on most media and encapsulation types on the router.

GTS works with a variety of Layer 2 technologies, including Frame Relay, ATM, Switched Multimegabit Data Service (SMDS), and Ethernet.

GTS performs the following tasks:

- Applies traffic shaping on a per-interface basis and uses access control lists (ACLs) to select the traffic to shape.
- On a Frame Relay subinterface, dynamically adapts to available bandwidth by integrating backward explicit congestion notification (BECN) signals, or shapes to a specified rate. This is known as adaptive GTS.
- On an ATM/ATM Interface Processor (AIP) interface, responds to the Resource Reservation Protocol (RSVP) feature signalled over statically configured ATM permanent virtual circuits (PVCs).

## Adaptive Generic Traffic Shaping on Frame Relay Networks

If adaptive GTS is configured on a Frame Relay network using the **traffic-shape rate** command, you can also use the **traffic-shape adaptive** command to specify the minimum bit rate to which the traffic is shaped.

With adaptive GTS, the router uses backward explicit congestion notifications (BECNs) to estimate the available bandwidth and adjust the transmission rate accordingly. The actual maximum transmission rate will be between the rate specified in the **traffic-shape adaptive** command and the rate specified in the **traffic-shape rate** command.

Configure these two commands on both ends of the network link, enabling the router at the high-speed end to detect and adapt to congestion even when traffic is flowing primarily in one direction.

For more information about configuring adaptive GTS, see the [“Configuring Adaptive Generic Traffic Shaping for Frame Relay Networks”](#) section on page 7.

## Benefits of Generic Traffic Shaping

All of the benefits associated with traffic shaping also apply to GTS. For information about the benefits of traffic shaping, see the [“Regulating Packet Flow Using Traffic Shaping”](#) module.

## How to Configure Generic Traffic Shaping

This section contains the following procedures. While all three procedures are listed as optional, you must choose either the first or the second procedure.

- [Configuring Generic Traffic Shaping on an Interface, page 3](#) (optional)
- [Configuring Generic Traffic Shaping Using an Access Control List, page 5](#) (optional)
- [Configuring Adaptive Generic Traffic Shaping for Frame Relay Networks, page 7](#) (optional)

## Configuring Generic Traffic Shaping on an Interface

To configure GTS on an interface, complete the following steps.

### SUMMARY STEPS

1. **enable**

2. **configure terminal**
3. **interface** *type number*
4. **traffic-shape rate** *bit-rate [burst-size] [excess-burst-size] [buffer-limit]*
5. **end**
6. **show traffic-shape** [*interface-type interface-number*]
7. **show traffic-shape statistics** [*interface-type interface-number*]
8. **exit**

## DETAILED STEPS

	Command or Action	Purpose
Step 1	<b>enable</b>  <b>Example:</b> Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> <li>• Enter your password if prompted.</li> </ul>
Step 2	<b>configure terminal</b>  <b>Example:</b> Router# configure terminal	Enters global configuration mode.
Step 3	<b>interface</b> <i>type number</i>  <b>Example:</b> Router(config)# interface s4/0	Configures an interface (or subinterface) type and enters interface configuration mode. <ul style="list-style-type: none"> <li>• Enter the interface type number.</li> </ul>
Step 4	<b>traffic-shape rate</b> <i>bit-rate [burst-size] [excess-burst-size] [buffer-limit]</i>  <b>Example:</b> Router(config-if)# traffic-shape rate 128000	Enables traffic shaping for outbound traffic on an interface based on the bit rate specified. <ul style="list-style-type: none"> <li>• Enter the bit rate.</li> </ul>
Step 5	<b>end</b>  <b>Example:</b> Router(config-if)# end	Returns to privileged EXEC mode.
Step 6	<b>show traffic-shape</b> [ <i>interface-type interface-number</i> ]  <b>Example:</b> Router# show traffic-shape serial4/0	(Optional) Displays the current traffic-shaping configuration.

Command or Action	Purpose
<pre>show traffic-shape statistics [interface-type interface-number]</pre> <p><b>Example:</b> Router# show traffic-shape statistics serial4/0</p>	(Optional) Displays the current traffic-shaping statistics.
<p><b>Step 7</b></p> <pre>exit</pre> <p><b>Example:</b> Router# exit</p>	(Optional) Exits privileged EXEC mode.

## Configuring Generic Traffic Shaping Using an Access Control List

To configure GTS for outbound traffic using an access control list (ACL), complete the following steps.

### Access Control List Functionality

Access control lists filter network traffic by controlling whether routed packets are forwarded or blocked at the router interface. When configured with GTS, the router examines each packet to determine how to shape the traffic on the basis of the criteria you specified for the access control list.

Access control list criteria could be the source address of the traffic, the destination address of the traffic, the upper-layer protocol, or other information. Note that sophisticated users can sometimes successfully evade or fool basic access control lists because no authentication is required.

### SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **access-list** *access-list-number* {deny | permit} *source* [*source-wildcard*]
4. **interface** *type number*
5. **traffic-shape group** *access-list bit-rate* [*burst-size* [*excess-burst-size*]]
6. **end**
7. **show traffic-shape** [*interface-type interface-number*]
8. **show traffic-shape statistics** [*interface-type interface-number*]
9. **exit**

## DETAILED STEPS

	Command or Action	Purpose
Step 1	<b>enable</b>  <b>Example:</b> Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> <li>Enter your password if prompted.</li> </ul>
Step 2	<b>configure terminal</b>  <b>Example:</b> Router# configure terminal	Enters global configuration mode.
Step 3	<b>access-list</b> <i>access-list-number</i> { <b>deny</b>   <b>permit</b> } <i>source</i> [ <i>source-wildcard</i> ]  <b>Example:</b> Router(config)# access-list 1 permit 192.5.34.0 0.0.0.255	Shapes traffic according to specified access list. <ul style="list-style-type: none"> <li>Enter the access list number, one of the required keywords, and the source information.</li> </ul>
Step 4	<b>interface</b> <i>type number</i>  <b>Example:</b> Router(config)# interface s4/0	Configures an interface (or subinterface) type and enters interface configuration mode. <ul style="list-style-type: none"> <li>Enter the interface type number.</li> </ul>
Step 5	<b>traffic-shape group</b> <i>access-list bit-rate</i> [ <i>burst-size</i> [ <i>excess-burst-size</i> ]]  <b>Example:</b> Router(config-if)# traffic-shape group 101 128000	Enables traffic shaping based on a specific access list for outbound traffic on an interface. <ul style="list-style-type: none"> <li>Enter the access list number and the bit rate.</li> </ul>
Step 6	<b>end</b>  <b>Example:</b> Router(config-if)# end	Returns to privileged EXEC mode.
Step 7	<b>show traffic-shape</b> [ <i>interface-type</i> <i>interface-number</i> ]  <b>Example:</b> Router# show traffic-shape serial4/0	(Optional) Displays the current traffic-shaping configuration.
Step 8	<b>show traffic-shape statistics</b> [ <i>interface-type</i> <i>interface-number</i> ]  <b>Example:</b> Router# show traffic-shape statistics serial4/0	(Optional) Displays the current traffic-shaping statistics.
Step 9	<b>exit</b>  <b>Example:</b> Router# exit	(Optional) Exits privileged EXEC mode.

**Note**

Repeat the above procedure for each additional type of traffic you want to shape.

## Configuring Adaptive Generic Traffic Shaping for Frame Relay Networks

To configure adaptive GTS for Frame Relay networks, complete the following steps.

### SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **interface** *type number*
4. **traffic-shape rate** *bit-rate [burst-size] [excess-burst-size] [buffer-limit]*
5. **traffic-shape adaptive** *bit-rate*
6. **traffic-shape fecn-adapt**
7. **end**
8. **show traffic-shape** [*interface-type interface-number*]
9. **show traffic-shape statistics** [*interface-type interface-number*]
10. **exit**

### DETAILED STEPS

	Command or Action	Purpose
Step 1	<b>enable</b>  <b>Example:</b> Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> <li>• Enter your password if prompted.</li> </ul>
Step 2	<b>configure terminal</b>  <b>Example:</b> Router# configure terminal	Enters global configuration mode.
Step 3	<b>interface</b> <i>type number</i>  <b>Example:</b> Router(config)# interface s4/0	Configures an interface (or subinterface) type and enters interface configuration mode. <ul style="list-style-type: none"> <li>• Enter the interface type number.</li> </ul>
Step 4	<b>traffic-shape rate</b> <i>bit-rate [burst-size] [excess-burst-size] [buffer-limit]</i>  <b>Example:</b> Router(config-if)# traffic-shape rate 128000	Enables traffic shaping for outbound traffic on an interface based on the bit rate specified. <ul style="list-style-type: none"> <li>• Enter the bit rate.</li> </ul>
Step 5	<b>traffic-shape adaptive</b> <i>bit-rate</i>  <b>Example:</b> Router(config-if)# traffic-shape adaptive 64000	Configures a Frame Relay subinterface to estimate the available bandwidth when BECNs are received. <ul style="list-style-type: none"> <li>• Enter the bit rate.</li> </ul>

	Command or Action	Purpose
Step 6	<b>traffic-shape fecn-adapt</b>  <b>Example:</b> Router(config-if)# traffic-shape fecn-adapt	Configures reflection of forward explicit congestion notifications (FECNs) as BECNs.
Step 7	<b>end</b>  <b>Example:</b> Router(config-if)# end	Returns to privileged EXEC mode.
Step 8	<b>show traffic-shape</b> [ <i>interface-type</i> <i>interface-number</i> ]  <b>Example:</b> Router# show traffic-shape serial4/0	(Optional) Displays the current traffic-shaping configuration.
Step 9	<b>show traffic-shape statistics</b> [ <i>interface-type</i> <i>interface-number</i> ]  <b>Example:</b> Router# show traffic-shape statistics serial4/0	(Optional) Displays the current traffic-shaping statistics.
Step 10	<b>exit</b>  <b>Example:</b> Router# exit	(Optional) Exits privileged EXEC mode.

## Configuration Examples for Generic Traffic Shaping

This section contains the following examples:

- [Generic Traffic Shaping on an Interface Configuration: Example, page 8](#)
- [Generic Traffic Shaping Using an Access Control List Configuration: Example, page 9](#)
- [Adaptive Generic Traffic Shaping for a Frame Relay Network Configuration: Example, page 9](#)

### Generic Traffic Shaping on an Interface Configuration: Example

The following is an example of GTS configured on serial interface s4/0:

```
enable
configure terminal
interface s4/0
  traffic-shape rate 128000
end
```

## Generic Traffic Shaping Using an Access Control List Configuration: Example

The following is an example of GTS configured using an ACL. In this example, GTS is configured for the outbound traffic on ACL 1.

```
enable
configure terminal
access-list 1 permit 192.5.34.0 0.0.0.255
interface s4/0
  traffic-shape group 101 128000
end
```

## Adaptive Generic Traffic Shaping for a Frame Relay Network Configuration: Example

The following is an example of adaptive GTS configured on Frame Relay network. In this example, adaptive GTS is configured using the **traffic-shape rate** command. The **traffic-shape adaptive** command specifies the minimum bit rate to which the traffic is shaped. The actual maximum transmission rate will be between the rate specified in the **traffic-shape adaptive** command and the rate specified in the **traffic-shape rate** command.

```
enable
configure terminal
interface s4/0
  traffic-shape rate 128000
  traffic-shape adaptive 64000
  traffic-shape fecn-adapt
end
```

## Where to Go Next

To configure Class-Based Traffic Shaping, see the [“Regulating Packet Flow on a Per-Class Basis — Using Class-Based Traffic Shaping”](#) module.

To configure Frame Relay Traffic Shaping (FRTS), see the [“MQC-Based Frame Relay Traffic Shaping”](#) module.

## Additional References

The following sections provide additional references related to configuring GTS.

## Related Documents

Related Topic	Document Title
QoS commands: complete command syntax, command modes, command history, defaults, usage guidelines, and examples	<a href="#">Cisco IOS Quality of Service Solutions Command Reference</a>
Overview information about using traffic shaping to regulate packet flow on a network	<a href="#">“Regulating Packet Flow Using Traffic Shaping”</a> module
Class-Based Traffic Shaping	<a href="#">“Regulating Packet Flow on a Per-Class Basis — Using Class-Based Traffic Shaping”</a> module
FRTS	<a href="#">“MQC-Based Frame Relay Traffic Shaping”</a> module

## Standards

Standard	Title
No new or modified standards are supported, and support for existing standards has not been modified.	—

## MIBs

MIB	MIBs Link
No new or modified MIBs are supported, and support for existing MIBs has not been modified.	To locate and download MIBs for selected platforms, Cisco IOS releases, and feature sets, use Cisco MIB Locator found at the following URL: <a href="http://www.cisco.com/go/mibs">http://www.cisco.com/go/mibs</a>

## RFCs

RFC	Title
No new or modified RFCs are supported, and support for existing RFCs has not been modified.	—

## Technical Assistance

Description	Link
<p>The Cisco Support website provides extensive online resources, including documentation and tools for troubleshooting and resolving technical issues with Cisco products and technologies.</p> <p>To receive security and technical information about your products, you can subscribe to various services, such as the Product Alert Tool (accessed from Field Notices), the Cisco Technical Services Newsletter, and Really Simple Syndication (RSS) Feeds.</p> <p>Access to most tools on the Cisco Support website requires a Cisco.com user ID and password.</p>	<p><a href="http://www.cisco.com/techsupport">http://www.cisco.com/techsupport</a></p>

## Feature Information for Generic Traffic Shaping

Table 1 lists the release history for this feature

Not all commands may be available in your Cisco IOS software release. For details on when support for specific commands was introduced, see the command reference documents.

For information on a feature in this technology that is not documented here, see the “[Regulating Packet Flow Roadmap](#).”

Use Cisco Feature Navigator to find information about platform support and software image support. Cisco Feature Navigator enables you to determine which Cisco IOS and Catalyst OS software images support a specific software release, feature set, or platform. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>. An account on Cisco.com is not required.



### Note

Table 1 lists only the Cisco IOS software release that introduced support for a given feature in a given Cisco IOS software release train. Unless noted otherwise, subsequent releases of that Cisco IOS software release train also support that feature.

**Table 1** Feature Information for Generic Traffic Shaping

Feature Name	Software Releases	Feature Configuration Information
This table is intentionally left blank because no features were introduced or modified in Cisco IOS Release 12.2(1) or later. This table will be updated when feature information is added to this module.	—	—

CCDE, CCENT, CCSI, Cisco Eos, Cisco HealthPresence, Cisco IronPort, the Cisco logo, Cisco Lumin, Cisco Nexus, Cisco Nurse Connect, Cisco Pulse, Cisco StackPower, Cisco StadiumVision, Cisco TelePresence, Cisco Unified Computing System, Cisco WebEx, DCE, Flip Channels, Flip for Good, Flip Mino, Flipshare (Design), Flip Ultra, Flip Video, Flip Video (Design), Instant Broadband, and Welcome to the Human Network

are trademarks; Changing the Way We Work, Live, Play, and Learn, Cisco Capital, Cisco Capital (Design), Cisco:Financed (Stylized), Cisco Store, and Flip Gift Card are service marks; and Access Registrar, Aironet, AllTouch, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, Continuum, EtherFast, EtherSwitch, Event Center, Explorer, Fast Step, Follow Me Browsing, FormShare, GainMaker, GigaDrive, HomeLink, iLYNX, Internet Quotient, IOS, iPhone, iQuick Study, IronPort, the IronPort logo, Laser Link, LightStream, Linksys, MediaTone, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerKEY, PowerPanels, PowerTV, PowerTV (Design), PowerVu, Prisma, ProConnect, ROSA, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

---

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0908R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2007 Cisco Systems, Inc. All rights reserved.