



# Throttling of AAA (RADIUS) Records

---

**First Published: December 3, 2007**

**Last Updated: October 9, 2009**

The Throttling of AAA (RADIUS) Records feature supports throttling of access (authentication and authorization) and accounting records that are sent to the RADIUS server. This feature allows a user to configure the appropriate throttling rate to avoid network congestion and instability; such as when there is insufficient bandwidth to accommodate a sudden burst of records generated from the Cisco IOS router to the RADIUS server.

## Finding Feature Information

Your software release may not support all the features documented in this module. For the latest feature information and caveats, see the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the [“Feature Information for Throttling of AAA \(RADIUS\) Records”](#) section on page 9.

Use Cisco Feature Navigator to find information about platform support and Cisco IOS and Catalyst OS software image support. To access Cisco Feature Navigator, go to <http://tools.cisco.com/ITDIT/CFN/jsp/index.jsp>. An account on Cisco.com is not required.

## Contents

- [Information About Throttling of AAA \(RADIUS\) Records, page 2](#)
- [How to Configure Throttling of AAA \(RADIUS\) Records, page 3](#)
- [Configuration Examples for Throttling of AAA \(RADIUS\) Records, page 5](#)
- [Additional References, page 7](#)
- [Feature Information for Throttling of AAA \(RADIUS\) Records, page 9](#)



---

**Americas Headquarters:**

**Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA**

# Information About Throttling of AAA (RADIUS) Records

To configure the Throttling of AAA (RADIUS) Records feature, you should understand the following concepts:

- [Benefits of the Throttling of AAA \(RADIUS\) Records Feature, page 2](#)
- [Throttling Access Requests and Accounting Records, page 2](#)

## Benefits of the Throttling of AAA (RADIUS) Records Feature

A Network Access Server (NAS), acting as RADIUS client, can generate a burst of accounting or access requests, causing severe network congestion or causing the RADIUS server to become overloaded with a burst of RADIUS traffic. This problem could be compounded when multiple NASs interact with the RADIUS servers.

The following conditions can trigger a sudden burst of RADIUS traffic:

- An interface flap, which in turn brings down all the subscriber sessions and generates accounting requests for each subscriber.
- The Cisco IOS High Availability (HA) program generating a START record for every session that survived a switchover, such as the scenario described the preceding bullet.

A large number of generated requests can make the network unstable if there is insufficient bandwidth or if the RADIUS server is slow to respond. Neither the User Datagram Protocol (UDP) transport layer nor the RADIUS protocol has a flow control mechanism. The throttling mechanism provided by this feature provides a solution for these issues.

## Throttling Access Requests and Accounting Records

The Throttling of AAA (RADIUS) Records feature introduces a mechanism to control packets (flow control) at the NAS level, which improves the RADIUS server performance.

Because of their specific uses, access requests and accounting records must be treated separately. Access request packets are time sensitive, while accounting record packets are not.

- If a response to an access request is not returned to the client in a timely manner, the protocol or the user will time out, impacting the device transmission rates.
- Accounting records packets are not real-time critical.

When configuring threshold values on the same server, it is important to prioritize threshold values for the handling of the time-sensitive access request packets and to place a lesser threshold value on the accounting records packets.

In some cases, when an Internet Service Provider (ISP) is using separate RADIUS servers for access requests and accounting records, only accounting records throttling may be required.

### Summary

- The Throttling of AAA (RADIUS) Records is disabled, by default.
- Throttling functionality can be configured globally or at server group level.

# How to Configure Throttling of AAA (RADIUS) Records

This section describes how to configure throttling of access (authentication and authorization) and accounting records that are sent to the RADIUS server for both, global and server groups.

Server-group configurations are used to enable or disable throttling for a particular server group and to specify the threshold value for that server group.



## Note

Server-group configurations override any configured global configurations.

This section includes the following tasks.

- [Throttling Accounting and Access Request Packets Globally, page 3](#)
- [Throttling Accounting and Access Request Packets Per Server Group, page 4](#)

## Throttling Accounting and Access Request Packets Globally

To globally configure the throttling of accounting and access request packets, perform the following task.

### SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **radius-server throttle** {[*accounting threshold*] [*access threshold*] [*access-timeout number-of-timeouts*]}
4. **exit**

### DETAILED STEPS

	Command or Action	Purpose
Step 1	<b>enable</b>  <b>Example:</b> Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> <li>• Enter your password if prompted.</li> </ul>
Step 2	<b>configure terminal</b>  <b>Example:</b> Router# configure terminal	Enters global configuration mode.

	Command or Action	Purpose
Step 3	<p><b>radius-server throttle</b> { [<b>accounting threshold</b>] [<b>access threshold</b> [<b>access-timeout number-of-timeouts</b>]] }</p> <p><b>Example:</b> Router(config)# radius-server throttle accounting 100 access 200 access-timeout 2</p>	<p>Configures global throttling for accounting and access request packets.</p> <p>For this example:</p> <ul style="list-style-type: none"> <li>The accounting threshold value (the range is 0-65536) is set to 100, and the access threshold value is set to 200.</li> </ul> <p><b>Note</b> The default threshold value is 0 (throttling disabled).</p> <ul style="list-style-type: none"> <li>The number of timeouts per transaction value (the range is 1-10) is set to 2.</li> </ul>
Step 4	<p><b>exit</b></p> <p><b>Example:</b> Router(config)# exit</p>	Exits global configuration mode.

## Throttling Accounting and Access Request Packets Per Server Group

The following server-group configuration can be used to enable or disable throttling for a specified server group and to specify the threshold value for that server group.

To configure throttling of server-group accounting and access request packets, perform the following task.

### SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **aaa group server radius** *server-group-name*
4. **throttle** { [**accounting threshold**] [**access threshold** [**access-timeout number-of-timeouts**]] }
5. **exit**

### DETAILED STEPS

	Command or Action	Purpose
Step 1	<p><b>enable</b></p> <p><b>Example:</b> Router&gt; enable</p>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> <li>Enter your password if prompted.</li> </ul>
Step 2	<p><b>configure terminal</b></p> <p><b>Example:</b> Router# configure terminal</p>	Enters global configuration mode.

	Command or Action	Purpose
Step 3	<pre>aaa group server radius server-group-name</pre> <p><b>Example:</b> Router(config)# aaa group server radius myservergroup</p>	Enters server-group configuration mode.
Step 4	<pre>throttle {[accounting threshold] [access threshold [access-timeout number-of-timeouts]]}</pre> <p><b>Example:</b> Router(config-sg-radius)# throttle accounting 100 access 200 access-timeout 2</p>	<p>Configures the specified server-group throttling values for accounting and access request packets.</p> <p>For this example:</p> <ul style="list-style-type: none"> <li>The accounting threshold value (the range is 0-65536) is set to 100, and the access threshold value is set to 200.</li> </ul> <p><b>Note</b> The default threshold value is 0 (throttling disabled).</p> <ul style="list-style-type: none"> <li>The number of time-outs per transaction value (the range is 1-10) is set to 2.</li> </ul>
Step 5	<pre>exit</pre> <p><b>Example:</b> Router(config-sg-radius)# exit</p>	Exits server-group configuration mode.

## Configuration Examples for Throttling of AAA (RADIUS) Records

This section provides the following configuration examples:

- [Throttling Accounting and Access Request Packets Globally: Example, page 5](#)
- [Throttling Accounting and Access Request Packets Per Server Group: Example, page 6](#)

### Throttling Accounting and Access Request Packets Globally: Example

The following example shows how to limit the number of accounting requests sent to a server to 100:

```
enable
configure terminal
radius-server throttle accounting 100
```

The following example shows how to limit the number of access requests packets sent to a server to 200 and sets the number of time-outs allowed per transactions to 2:

```
enable
configure terminal
radius-server throttle access 200
radius-server throttle access 200 access-timeout 2
```

The following example shows how to throttle both accounting and access request packets:

```
enable
configure terminal
radius-server throttle accounting 100 access 200
```

## Throttling Accounting and Access Request Packets Per Server Group: Example

The following example shows how to limit the number of accounting requests sent to server-group-A to 100:

```
enable
configure terminal
aaa group server radius server-group-A
throttle accounting 100
```

The following example shows how to limit the number of access requests packets sent to server-group-A to 200 and sets the number of time-outs allowed per transactions to 2:

```
enable
configure terminal
aaa group server radius server-group-A
throttle access 200 access-timeout 2
```

The following example shows how to throttle both accounting and access request packets for server-group-A:

```
enable
configure terminal
aaa group server radius server-group-A
throttle accounting 100 access 200
```

# Additional References

The following sections provide references related to the Throttling of AAA (RADIUS) Records feature.

## Related Documents

Related Topic	Document Title
AAA and RADIUS	<i>Cisco IOS Security Configuration Guide: Securing User Services</i> , Release 15.0.

## Standards

Standard	Title
No new or modified standards are supported by this feature, and support for existing standards has not been modified by this feature.	—

## MIBs

MIB	MIBs Link
No new or modified MIBs are supported by this feature, and support for existing MIBs has not been modified by this feature.	To locate and download MIBs for selected platforms, Cisco IOS releases, and feature sets, use Cisco MIB Locator found at the following URL: <a href="http://www.cisco.com/go/mibs">http://www.cisco.com/go/mibs</a>

## RFCs

RFC	Title
No new or modified RFCs are supported by this feature, and support for existing RFCs has not been modified by this feature.	—

## Technical Assistance

Description	Link
<p>The Cisco Support website provides extensive online resources, including documentation and tools for troubleshooting and resolving technical issues with Cisco products and technologies.</p> <p>To receive security and technical information about your products, you can subscribe to various services, such as the Product Alert Tool (accessed from Field Notices), the Cisco Technical Services Newsletter, and Really Simple Syndication (RSS) Feeds.</p> <p>Access to most tools on the Cisco Support website requires a Cisco.com user ID and password.</p>	<p><a href="http://www.cisco.com/techsupport">http://www.cisco.com/techsupport</a></p>

# Feature Information for Throttling of AAA (RADIUS) Records

Table 1 lists the release history for this feature.

Not all commands may be available in your Cisco IOS software release. For release information about a specific command, see the command reference documentation.

Use Cisco Feature Navigator to find information about platform support and software image support. Cisco Feature Navigator enables you to determine which Cisco IOS and Catalyst OS software images support a specific software release, feature set, or platform. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>. An account on Cisco.com is not required.



**Note**

Table 1 lists only the Cisco IOS software release that introduced support for a given feature in a given Cisco IOS software release train. Unless noted otherwise, subsequent releases of that Cisco IOS software release train also support that feature.

**Table 1** Feature Information for Throttling of AAA (RADIUS) Records

Feature Name	Releases	Feature Information
Throttling of AAA (RADIUS) Records	12.2(33)SRC 12.4(20)T	<p>The Throttling of AAA (RADIUS) Records feature supports throttling of access (authentication and authorization) and accounting records that are sent to the RADIUS server. This feature allows a user to configure the appropriate throttling rate to avoid network congestion and instability; such as when there is insufficient bandwidth to accommodate a sudden burst of records generated from the Cisco IOS router to the RADIUS server.</p> <p>In Release 12.2(33)SRC, this feature was introduced on the Cisco 7200 and Cisco 7200 routers.</p> <p>The following commands were introduced or modified by this feature: <b>radius-server throttle</b>, <b>throttle</b></p>

---

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2007–2008 Cisco Systems, Inc. All rights reserved.