



X.25 Annex G Session Status Change Reporting

This feature module describes the X.25 Annex G Session Status Change Reporting feature and includes the following sections:

- [Feature Overview, page 1](#)
- [Supported Platforms, page 2](#)
- [Supported Standards, MIBs, and RFCs, page 2](#)
- [Configuration Tasks, page 3](#)
- [Configuration Examples, page 3](#)
- [Command Reference, page 4](#)

Feature Overview

The X.25 Annex G Session Status Change Reporting feature introduces the **logging event frame-relay x25** interface configuration command, which provides console or system log notification of X.25 Annex G session status changes when an X.25 Annex G session changes state. Before this feature was introduced, there was no notification.

This feature detects changes in X.25 Annex G session status using an X.25 Link Access Procedure, Balanced (LAPB) N2 counter. The LAPB N2 counter records the number of unsuccessful transmit attempts that are made before the link is declared down. If the N2 consecutive polled commands have not been answered, a notification is generated, indicating that the X.25 profile or context associated with the data-link connection identifier (DLCI) that is running across the failed link has gone down. A message is generated to the console or system log when the link goes down. A message is also generated to the console or system log when the link comes back up. The notification response time is contingent on the values assigned to the LAPB N2 counter and the LAPB the retransmission timer in milliseconds (T1) timer.

Benefits

For X.25 Annex G sessions, if Local Management Interface (LMI) keepalives are disabled, Frame Relay (FR) DLCI status changes can be detected using the **logging event frame-relay x25** interface configuration command



Americas Headquarters:
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

© 2007 Cisco Systems, Inc. All rights reserved.

Restrictions

The following restrictions apply to the X.25 Annex G Session Status Change Reporting feature:

- Notification is displayed for the UP or DOWN event only if traffic is initiated when an X.25 Annex G session is active.
- The notification response time is contingent on the values assigned to the LAPB N2 counter and the LAPB T1 timer.
- The PVCs continue to be reported as UP unless the serial link directly connected to the router goes down.

Related Documents

- *Cisco IOS Wide-Area Networking Configuration Guide*, Release 12.2
- *Cisco IOS Wide-Area Networking Command Reference*, Release 12.2

Supported Platforms

- Cisco 1600 series
- Cisco 2500
- Cisco 2600
- Cisco 3640
- Cisco 3660
- Cisco 4000
- Cisco 4500
- Cisco 7000 series
- Cisco 7200 series
- Cisco 7500 series

Supported Standards, MIBs, and RFCs

Standards

No new or modified standards are supported by this feature.

MIBs

No new or modified MIBs are supported by this feature.

To obtain lists of supported MIBs by platform and Cisco IOS release, and to download MIB modules, go to the Cisco MIB website on Cisco.com at <http://www.cisco.com/public/sw-center/netmgmt/cmtk/mibs.shtml>.

RFCs

No new or modified RFCs are supported by this feature.

Prerequisites

The **logging event frame-relay x25** interface configuration command is available for all interfaces that have Frame Relay encapsulation.

Configuration Tasks

See the following sections for configuration tasks for the X.25 Annex G Session Status Change Reporting feature. Each task in the list is identified as either required or optional.

- [Enabling X.25 Annex G Session Status Change Reporting](#) (required)
- [Verifying X.25 Annex G Session Status Change Reporting](#) (optional)

Enabling X.25 Annex G Session Status Change Reporting

Command	Purpose
Router(config-if)# logging event frame-relay x25	Enables notification of X.25 Annex G session status changes to be displayed on a console or system log.

Verifying X.25 Annex G Session Status Change Reporting

Command	Purpose
Router(config-if)# show run logging event frame-relay x25	Shows whether the command is enabled.

Configuration Examples

This section provides the following configuration example:

X.25 Annex G Session Status Change Reporting Configuration Example

The following configuration example shows how to enable notification of X.25 Annex G session status changes to be displayed on a console or system log using the **logging event frame-relay x25** interface configuration command:

```
router(config-if)# logging event frame-relay x25
```

The following is an example of the Annex G session status change notifications:

```
%X25-5-UPDOWN: Interface <interface> - DLCI <dlci number> X.25 packet layer changed state to DOWN
```

```
%X25-5-UPDOWN: Interface <interface> - DLCI <dlci number> X25 packet layer changed state to UP
```

Command Reference

The following commands are introduced or modified in the feature or features documented in this module. For information about these commands, see the *Cisco IOS Wide-Area Networking Command Reference* at http://www.cisco.com/en/US/docs/ios/wan/command/reference/wan_book.html. For information about all Cisco IOS commands, go to the Command Lookup Tool at <http://tools.cisco.com/Support/CLILookup> or to the *Cisco IOS Master Commands List*.

- **logging event frame-relay x25**

CCVP, the Cisco logo, and Welcome to the Human Network are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn is a service mark of Cisco Systems, Inc.; and Access Registrar, Aironet, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, iQuick Study, LightStream, Linksys, MeetingPlace, MGX, Networkers, Networking Academy, Network Registrar, PIX, ProConnect, ScriptShare, SMARTnet, StackWise, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0711R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2007 Cisco Systems, Inc. All rights reserved.