



# Cisco IOS XR Configuration Guide Master Index, Release 3.8

This page contains a list of all the indexed terms contained in the Cisco IOS XR configuration guides for Release 3.8, ordered alphabetically. Use the **Alphabet Key** or your web browser's Find function to search for a command. To access the documentation for a particular command, click on the command name.

---

## Page Number Designators

<b>HC</b>	Cisco IOS XR Interface and Hardware Component Configuration Guide
<b>IC</b>	Cisco IOS XR Addresses and Services Configuration Guide
<b>MCC</b>	Cisco IOS XR Multicast Configuration Guide
<b>MNC</b>	Cisco IOS XR System Monitoring Configuration Guide
<b>MPC</b>	Cisco IOS XR MPLS Configuration Guide
<b>QC</b>	Cisco IOS XR Modular Quality of Service Configuration Guide
<b>RC</b>	Cisco IOS XR Routing Configuration Guide
<b>SC</b>	Cisco IOS XR System Security Configuration Guide
<b>SMC</b>	Cisco IOS XR System Management Configuration Guide
<b>VFC</b>	Cisco IOS XR Virtual Firewall Command Reference

---

## Numerics

### 6PE

- BGP multipath [MPC-310](#)
- conditions for use [MPC-308](#)
- configuring [MPC-310](#)
- deploying [MPC-309](#)
- overview [MPC-308](#)
- prerequisites [MPC-308](#)
- service provider considerations [MPC-308](#)

- supported protocols [MPC-311](#)
- ### 6VPE
- configuration tasks [MPC-456](#)
  - configuring PE-CE [MPC-460](#)
  - configuring VRFs [MPC-458](#)

---

## A

### AAA (authentication, authorization, and accounting)

- accounting services, enabling [SC-52](#)
- authentication [SC-9](#)
- authorization, enabling [SC-50](#)
- configuring
  - AAA service restrictions [SC-3](#)
  - accounting method lists [SC-45](#)
  - authentication method lists [SC-39](#)
  - authorization method lists [SC-41](#)
  - individual users [SC-22](#)
  - login parameters [SC-54](#)
  - prerequisites for AAA services [SC-3](#)
  - RADIUS server groups [SC-35](#)
  - remote AAA [SC-8](#)
  - router to RADIUS server communication [SC-24](#)
  - services (examples) [SC-55](#)
  - TACACS+ server [SC-32](#)
  - TACACS+ server groups, [SC-37](#)
  - task groups for task-based authorization [SC-18](#)
  - user groups [SC-20](#)
- database [SC-7](#)
- interim accounting records, generating [SC-48](#)
- per VRF (VPN routing and forwarding) definition [SC-30](#)
- task-based authorization

- task groups, definition [SC-6](#)
- task IDs [SC-12](#)
- user and group attributes [SC-4](#)
- user groups
  - definition [SC-5](#)
  - inheritance [SC-5](#)
  - predefined [SC-5](#)
  - privilege level mapping as an alternative to task IDs [SC-15](#)
- XML schema [SC-15](#)
- aaa accounting command [SC-48](#)
- aaa accounting update command [SC-48](#)
- aaa authentication login command
  - no form [SMC-33](#)
  - regular form [SMC-30](#)
- ABF (ACL-based forwarding)
  - filter configuration, IPv4 packets [IC-11](#)
  - forward a next hop [IC-11](#)
  - overview [IC-11](#)
  - pure ACL-based forwarding, how to [IC-32](#)
  - security ACL, how to [IC-30](#)
- ABRs (area border routers) [RC-204](#)
- accept-lifetime command [SC-221](#)
- accept-tolerance command [SC-216](#)
- access lists
  - applying [IC-15](#)
  - IPv4 or IPv6 [IC-12](#)
- access-lists, extended [MPC-59](#)
- accounting, configuring
  - RADIUS server accounting settings [VFC-89](#)
  - TACACS+ server accounting settings [VFC-87](#)
- ACK (hello acknowledgment)
  - objects [MPC-58](#)
  - RSVP messages [MPC-58](#)
- ACL compilation process out of memory [VFC-318](#)
- ACL Deny [QC-19](#)
- ACL match, returning implicit deny [MPC-68](#)
- ACL-based prefix filtering, RSVP [MPC-59](#)
- ACLs
  - implicit deny [VFC-97](#)
  - inbound [VFC-111](#)
  - IPs with NAT [VFC-112](#)
  - maximum entries [VFC-97](#)
  - merged [VFC-96](#)
  - order of entries [VFC-96](#)
  - outbound [VFC-111](#)
- action command
  - logging keyword [MNC-126](#)
  - trigger keyword [MNC-126](#)
- active targeted hellos, prerequisites [MPC-17](#)
- address conflict resolution [IC-179](#)
- address family command [RC-299](#)
- address ipv4 (MPP) command [SC-243](#)
- address ipv6 (MPP) command [SC-246](#)
- address repository manager [IC-179](#)
- address space, PE routers [MPC-353](#)
- address-family command (IS-IS) [RC-314](#)
- address-family ipv4 command [HC-73](#), [HC-74](#), [RC-170](#)
- address-family ipv4 mdt command [RC-130](#)
- adjacencies, tuning [RC-336](#)
- ADM (add drop multiplexer)
  - defining [MPC-211](#)
  - O-UNI client device [MPC-212](#)
  - with O-UNI [MPC-212](#)
- Admin
  - context [VFC-46](#)
  - description [VFC-46](#), [VFC-49](#)
  - permissions [VFC-49](#)
- administrative distance [RC-361](#)
- administrative distance, static routes [RC-465](#)
- advertisement, label [MPC-10](#)
- advertising tunnels, VPN services [MPC-353](#)
- affinities, process placement [SMC-142](#)
- ageout command
  - ICMP Echo operation [MNC-79](#)
  - ICMP Path Echo operation [MNC-86](#)
  - ICMP Path Jitter operation [MNC-94](#)
  - UDP Echo operation [MNC-72](#)

- UDP Jitter operation [MNC-64](#)
- aggregatable global address [IC-167](#)
- aggregatable global address format, figure [IC-168](#)
- aggregate-address command [RC-65](#)
- aging, MAC address
  - configuring [MPC-301](#)
  - defining [MPC-270](#)
- ais-shut command [HC-429](#)
- alarm cards (16-slot CRS-1), node ID components [SMC-227](#)
- Alarm Logging and Debugging Event Management System
  - see ALDEMS [MNC-3](#)
- alarms
  - bi-state alarms [MNC-7](#)
  - capacity threshold setting [MNC-8](#)
  - severity level [MNC-7](#)
  - severity level and filtering [MNC-7](#)
- ALDEMS [MNC-3](#)
- ALDEMS (Alarm Management and Debugging Event System), description [MNC-3](#)
- alert messages [VFC-338](#)
- allow command [SC-243](#), [SC-246](#)
- allowas-in command [RC-121](#)
- antireplay window (IPSec)
  - checking a crypto profile [SC-170](#)
  - description [SC-145](#)
  - expanding and disabling globally procedure [SC-169](#)
- application processes, placing
  - See process placement
- application protocol inspection
  - class map overview [VFC-122](#)
  - configuration examples [VFC-182](#)
  - DNS [VFC-124](#)
  - FTP [VFC-125](#)
  - HTTP [VFC-124](#)
  - ICMP [VFC-126](#)
  - ILS [VFC-121](#), [VFC-127](#)
  - limitations [VFC-120](#)
  - NAT and PAT support [VFC-120](#)
  - policy map overview [VFC-122](#)
  - RTSP [VFC-127](#)
  - SCCP [VFC-121](#), [VFC-128](#), [VFC-158](#)
  - SIP [VFC-121](#), [VFC-122](#), [VFC-129](#), [VFC-151](#)
  - standards [VFC-120](#)
  - supported protocols [VFC-120](#)
- apply command [RC-414](#)
- aps group command
- aps submode
  - See aps group command
  - channel command [HC-105](#), [HC-106](#), [HC-428](#)
  - interface loopback command [HC-428](#)
- archiving messages [MNC-156](#), [MNC-177](#), [MNC-181](#)
- area command [RC-222](#)
- area command (BFD) [HC-69](#), [HC-71](#)
- ARM (Address Repository Manager) [IC-179](#)
- ARP
  - inspection check failure [VFC-324](#)
- ARP (Address Resolution Protocol) [IC-45](#)
  - address resolution [IC-43](#)
  - cache entries [IC-44](#)
  - definition [IC-42](#)
  - MAC (Media Access Control) [IC-41](#)
  - proxy ARP [IC-44](#)
  - RFC 1027 [IC-44](#)
  - RFC 826 [IC-44](#)
- ASBRs (autonomous system boundary routers) [RC-204](#)
- as-override command [RC-121](#)
- ATM (asynchronous transfer mode)
  - defining [MPC-107](#)
  - MPLS L2VPN [MPC-229](#)
- atm address-registration command [HC-44](#)
- ATM CLP bit, matching on [QC-49](#)
- atm ilmi-config disable command [HC-46](#)
- atm ilmi-keepalive command [HC-44](#)
- ATM interface
  - address registration and callback functions [HC-44](#)
  - ATM overview [HC-3](#)
  - attaching a vc-class [HC-40](#), [HC-41](#), [HC-43](#)

- bringing up [HC-8, HC-53](#)
  - configuring
    - IP address and subnet mask [HC-22](#)
    - OAM AIS/RDI [HC-37](#)
    - OAM F5 loopback [HC-37](#)
    - OAM management [HC-37](#)
    - optional parameters [HC-10, HC-53](#)
    - PVC [HC-14](#)
    - traffic shaping [HC-19, HC-38](#)
    - VC class [HC-36, HC-56](#)
    - VP tunnel [HC-18, HC-21, HC-55](#)
  - creating
    - interface [HC-13](#)
    - PVC [HC-14](#)
    - subinterface [HC-13](#)
    - VP tunnel [HC-19](#)
  - F4 OAM overview [HC-4](#)
  - ILMI
    - disabling [HC-45, HC-46](#)
    - enabling [HC-43, HC-44](#)
    - overview [HC-5](#)
  - OAM packets [HC-19](#)
  - prerequisites [HC-2](#)
  - VC class-mapping overview [HC-3](#)
  - vc-class, attaching [HC-39](#)
  - verifying
    - connectivity [HC-23](#)
    - ILMI configuration [HC-45, HC-47](#)
  - VP tunnel
    - displaying [HC-20, HC-23](#)
    - overview [HC-4](#)
  - ATM on Layer 2 VPN [QC-20](#)
  - AToM (any transport over MPLS)
    - IP Interworking [MPC-237](#)
    - like-to-like pseudowires [MPC-239](#)
    - static pseudowire [MPC-290](#)
    - using static labels [MPC-290](#)
  - attached bit on an IS-IS instance [RC-304](#)
  - attached-bit send command [RC-344](#)
  - attachment circuits
    - defining [MPC-268](#)
    - xconnects [MPC-343](#)
  - attacks, spoofing [VFC-323, VFC-324](#)
  - authentication
    - local database [VFC-66](#)
    - MD5 (OSPFv2) [RC-206](#)
    - route, key rollover (OSPFv2) [RC-207](#)
    - strategies [RC-206](#)
    - TACACS+ server accounting settings, configuring [VFC-86](#)
  - authentication command (OSPFv2) [RC-232](#)
  - authentication message-digest command [RC-238](#)
  - automatic bandwidth, configuring [MPC-193](#)
  - automatic bandwidth, MPLS-TE
    - (example) [MPC-208](#)
    - restrictions [MPC-119](#)
  - automatic route distinguisher, MPLS Layer 3 VPN [MPC-385](#)
  - automatic switchover [SMC-237](#)
  - autonomous system [MPC-386](#)
  - autonomous system number format [RC-8](#)
  - autonomous systems [RC-203](#)
  - auto-summary command [RC-380](#)
  - auto-update definition [SC-91](#)
  - averaged threshold violation [MNC-119](#)
- 
- B**
- backbone area [RC-203](#)
  - backup disk
    - backing up onto [SMC-96](#)
    - booting from, procedure [SMC-100](#)
    - configuration examples [SMC-104](#)
    - creating
      - for all SDRs (example) [SMC-104](#)
      - for SDR (example) [SMC-105](#)
      - prerequisites
      - procedure for [SMC-96](#)

- defining (example) [SMC-104](#)
- description [SMC-95](#)
- feature history [SMC-93](#)
- bandwidth
  - configuring control channel [MPC-64](#)
  - configuring data channel [MPC-64](#)
  - constraint models [MPC-103](#)
    - overview [MPC-103](#)
    - RDM and MAM [MPC-103](#)
  - pools [MPC-103](#)
- bandwidth command [QC-85](#)
- bandwidth remaining command, bandwidth remaining percent [QC-117](#)
- bandwidth-percent command [RC-171](#)
- banner
  - definition [SC-91](#)
- banner command [SC-102](#)
- benefits, IP SLA [MNC-50](#)
- bert pattern command [HC-463](#), [HC-466](#)
- bestpath algorithm [RC-28](#)
- BFD
  - BFD configuration mode [HC-75](#), [HC-76](#)
  - BGP configuration mode [HC-67](#)
  - counters
    - clearing [HC-77](#)
    - displaying [HC-77](#)
  - echo mode, disabling [HC-74](#), [HC-75](#), [HC-77](#)
  - enabling
    - fast detection [HC-73](#), [HC-74](#)
    - interface [HC-68](#), [HC-70](#)
    - local device and peer, between [HC-68](#)
    - neighbor [HC-66](#)
    - static route [HC-72](#)
  - examples [HC-78](#)
  - fast detection, configuring [HC-69](#), [HC-71](#)
  - IPv6 [HC-64](#)
  - OSPF configuration mode [HC-69](#)
  - OSPFv3 configuration mode [HC-71](#)
  - overview [HC-63](#)
  - packet formats [HC-65](#)
  - prerequisites [HC-62](#)
  - setting
    - BFD multiplier [HC-67](#)
    - minimum interval [HC-67](#), [HC-69](#), [HC-71](#)
    - multiplier [HC-69](#), [HC-71](#)
  - static routes, configuring [HC-73](#)
  - VLAN bundles [HC-65](#)
  - VPN VRF instance, specifying [HC-73](#)
- bfd command [HC-75](#), [HC-76](#)
- bfd fast-detect command [HC-68](#), [HC-69](#), [HC-71](#)
- bfd minimum-interval command [HC-67](#), [HC-69](#), [HC-71](#)
- bfd multiplier command [HC-67](#), [HC-69](#), [HC-71](#)
- BGP nonstop routing
  - configuration example [RC-151](#)
- BGP (Border Gateway Protocol)
  - (MDT) multicast distribution tree [RC-128](#)
  - autonomous system number format [RC-8](#)
  - bestpath algorithm [RC-28](#)
  - BGP keychains [RC-41](#)
- BGP (border gateway protocol)
  - bgp neighbor address family submode
    - route-policy command [RC-51](#)
- BGP (Border Gateway Protocol)
  - bgp router submode
    - address-family ipv4 mdt command [RC-130](#)
    - bgp bestpath compare-routerid command [RC-62](#)
    - bgp bestpath med always command [RC-61](#)
    - bgp bestpath med confed command [RC-61](#)
    - bgp bestpath med missing-as-worst command [RC-61](#)
    - bgp confederation identifier command [RC-52](#)
    - bgp confederation peers command [RC-53](#)
    - bgp default local-preference command [RC-56](#)
    - bgp router-id command [RC-102](#)
    - default-metric command [RC-58](#)
    - router bgp command [RC-8](#)
  - bgp vrf neighbor address family submode

- allowas-in command [RC-121](#)
- bidirectional forwarding detection [RC-4](#)
- configuration
  - grouping [RC-10](#)
  - inheriting templates [RC-12](#)
- default address family [RC-39](#)
- description [RC-1](#)
- distributed BGP [RC-39](#)
- BGP (border gateway protocol)
  - distributing routes [MPC-398](#)
- BGP (Border Gateway Protocol)
  - functional overview [RC-4](#)
  - inheritance, monitoring [RC-16](#)
  - IPv6 and IPv6 VPN provider edge transport over MPLS [RC-41](#)
  - IPv6 prefixes over IPv4 session [RC-6](#)
  - IPv6 provider edge multipath [RC-42](#)
- BGP (border gateway protocol)
  - messages and MPLS labels [MPC-398](#)
- BGP (Border Gateway Protocol)
  - MPLS VPN carrier supporting carrier [RC-40](#)
  - multicast VPN [RC-43](#)
  - multiprotocol [RC-33](#)
  - neighbors, maximum limits on [RC-5](#)
  - policy attach points
    - aggregation [RC-416](#)
    - allocate label [RC-423](#)
    - clear policy [RC-424](#)
    - dampening [RC-417](#)
    - debug [RC-425](#)
    - default originate [RC-417](#)
    - export [RC-422](#)
    - import [RC-421](#)
    - neighbor export [RC-418](#)
    - neighbor import [RC-418](#)
    - neighbor-orf [RC-423](#)
    - network [RC-419](#)
    - next-hop [RC-424](#)
    - redistribute [RC-419](#)
    - retain route target [RC-422](#)
    - show bgp [RC-420](#)
    - table policy [RC-421](#)
- BGP (border gateway protocol)
  - route policy submode
    - route-policy command [RC-49](#)
- BGP (Border Gateway Protocol)
  - router bgp neighbor group address family configuration mode,address family command [RC-11](#)
  - router identifier [RC-4](#)
- BGP (border gateway protocol)
  - routing information [MPC-397](#)
- BGP (Border Gateway Protocol)
  - routing policy, enforcing [RC-21](#)
- BGP (border gateway protocol)
  - SSA function [MPC-353](#)
- BGP (Border Gateway Protocol)
  - update groups
    - description [RC-23](#)
    - example [RC-147](#)
  - VPNv4 and VPNv6 over the IP core using L2TPv3 tunnels [RC-42](#)
  - vrf address family submode
    - export route-policy command [RC-101](#)
    - import route-policy command [RC-101](#)
    - import route-target command [RC-101](#)
    - maximum prefix command [RC-101](#)
- bgp address family submode, retain route-target command [RC-118](#)
- BGP Attributes Download [IC-59](#)
- bgp cost community [RC-23](#)
- bgp dampening command [RC-71](#)
- bgp global address family submode
  - See* address family command [RC-71](#)
  - address family command [RC-9](#)
  - aggregate-address command [RC-65](#)
  - bgp dampening command [RC-71](#)
  - distance bgp command [RC-78](#)

- network command [RC-63](#)
- table-policy command [RC-76](#)
- bgp global address family submode, redistribute command [RC-69](#)
- BGP multipath
  - 6PE [MPC-310](#)
  - load sharing [MPC-354](#)
- bgp neighbor address family submode [RC-299](#)
  - <I\_Italic>See<Default Para Font> neighbor address family command [RC-88](#)
  - neighbor address family command [RC-9](#)
  - next-hop self command [RC-88](#)
  - route-reflector-client command [RC-83](#)
  - send-community-ebgp command [RC-90](#)
  - soft-reconfiguration inbound always command [RC-97](#)
  - weight command [RC-60](#)
- bgp neighbor group submode
  - neighbor-group command [RC-11](#)
- bgp neighbor submode
  - bgp neighbor command [RC-10](#)
  - keychain command [RC-128](#)
  - neighbor command [RC-299](#)
  - password command [RC-115](#)
  - shutdown command [RC-115](#)
  - timers command [RC-115](#)
  - update-source command [RC-115](#)
  - use command [RC-80](#)
- BGP nonstop routing [RC-44](#)
- BGP Non-Stop Routing
  - configuring [RC-144](#)
- bgp policy accounting command [IC-66](#)
- bgp redistribute-internal command [RC-66](#)
- bgp router submode
  - bgp redistribute-internal command [RC-66](#)
  - timers bgp command [RC-54](#)
- bgp router-id command [RC-119](#)
- bgp session group submode [RC-11](#)
- BGP update groups example [RC-147](#)
- bgp VPNv4 address family submode [RC-10](#)
- bgp VPNv6 address family submode [RC-10](#)
- bgp vrf address family submode [RC-9](#)
  - aggregate-address command [RC-120](#)
  - maximum-paths command [RC-123](#)
  - redistribute command [RC-126](#)
- bgp VRF neighbor address family submode [RC-9](#)
- BGP VRF neighbor address family submode
  - as-override command [RC-121](#)
  - route-policy command [RC-122](#)
  - site-of-origin command [RC-121](#)
- bgp VRF neighbor submode [RC-9](#)
- BGP VRF neighbor submode, ebgp-multihop command [RC-121](#)
- bgp vrf neighbor submode, password command [RC-121](#)
- bgp vrf submode [RC-9](#)
  - bgp router-id command [RC-119](#)
  - label-allocation-mode per-ce command [RC-120](#)
- BGP vrf submode
  - rd command [RC-103](#)
- BGP4 configuration [MPC-308](#)
- boot disk recovery [SMC-242](#)
- border control model
  - configuring [MPC-167](#)
  - overview [MPC-167](#)
- bridge domain
  - associating members [MPC-276](#)
  - configuring parameters [MPC-278](#)
  - creating [MPC-273](#)
  - disabling [MPC-280](#)
  - overview [MPC-269](#)
  - split horizon [MPC-269](#)
- broadcast addresses, used instead of [IC-171](#)
- broadcast-for-v2 command [RC-378](#)
- browser-proxy definition [SC-91](#)
- BSR (bootstrap router)
  - See multicast routing, BSR (bootstrap router)
- buckets command [MNC-67](#)
- bug fix PIE files
  - See SMU (Software Maintenance Update)

bundle command [HC-337](#)

bundle id command [HC-207](#), [HC-211](#)

Bundle-Ether command [HC-206](#)

bundle-hash command [IC-73](#)

## C

cablelength command [HC-439](#), [HC-446](#), [HC-453](#)

cache entries command [HC-266](#)

cache entries, definition [IC-44](#)

cache permanent command [HC-266](#)

cache timeout command [HC-266](#)

card type

changing to T1 mode [HC-441](#)

changing to T3 mode [HC-441](#)

changing to E1 mode [HC-441](#)

changing to E3 mode [HC-441](#)

cards

alarm cards, node ID components (XR 12000) [SMC-227](#)

CRS-16-FC/S card, replacing (example) [SMC-250](#)

CSCs (clock and scheduler cards)

node ID components (XR 12000) [SMC-227](#)

removing and replacing [SMC-270](#)

CSFCs (consolidated switch fabric cards)

node ID components (XR 12000) [SMC-227](#)

removing and replacing [SMC-275](#)

DRP, node ID components (CRS-1) [SMC-226](#)

fan controller cards, node ID components [SMC-227](#)

line cards

node ID components (XR 12000) [SMC-227](#)

removing [SMC-244](#)

MSCs (modular services cards)

node ID components [SMC-226](#)

removing [SMC-244](#)

node ID components per card type [SMC-226](#)

PLIMs (physical layer interface modules)

node ID components [SMC-226](#)

removing [SMC-244](#)

PRP

hardware requirements [SMC-276](#)

software requirements [SMC-276](#)

standby, adding [SMC-276](#)

replacing CRS-16-FC/S card (example) [SMC-267](#)

RPs (route processors)

node ID components (CRS-1) [SMC-226](#)

node ID components (XR 12000) [SMC-227](#)

SFCs (switch fabric cards)

node ID components (Cisco CRS-1) [SMC-227](#)

node ID components (Cisco XR 12000) [SMC-227](#)

removing and replacing [SMC-270](#)

SIPs (SPA interface processors)

node ID components (CRS-1) [SMC-227](#)

node ID components (XR 12000) [SMC-227](#)

SPAs (shared port adapters)

node ID components (XR 12000) [SMC-227](#)

SPAs (shared port adaptors)

node ID components [SMC-227](#)

cautions, usage in text [15](#)

CDP

configuration examples [SMC-289](#)

enabling [SMC-283](#)

feature history [SMC-281](#)

functional overview [SMC-282](#)

introduction [SMC-281](#)

modifying default settings [SMC-285](#)

monitoring [SMC-286](#)

prerequisites [SMC-282](#)

cdp (global) command [SMC-284](#)

cdp advertise v1 command [SMC-285](#)

cdp holdtime command [SMC-285](#)

cdp timer command [SMC-286](#)

CEF (Cisco Express Forwarding)

benefits [IC-53](#)

BGP policy accounting, classification [IC-54](#)

description [IC-51](#)

exact route, how to verify [IC-73](#)

- features [IC-53](#)
- FIB (Forwarding Information Base) [IC-53](#)
- CEF (cisco express forwarding)
  - L2TPv3 prerequisite [MPC-316](#)
- CEF (Cisco Express Forwarding)
  - reverse path forwarding [IC-55](#)
  - route processor management ethernet forwarding [IC-56](#)
- cef load-balancing fields command [IC-57](#)
- cef purge delay command [IC-68](#)
- CE-PE eBGP, configuring route-policy definition [MPC-359](#)
- certification authority interoperability
  - See also certificates\*
  - authenticating the CA [SC-68](#)
  - CA description
  - configuring
    - domain names (example) [SC-64](#)
    - host names (examples) [SC-64](#)
    - trusted points [SC-66](#)
  - description [SC-268](#)
  - generating RSA (Rivest, Shamir, and Adelman) key pairs [SC-65](#)
  - manual enrollment, cutting and pasting [SC-70](#)
  - requesting certificates from the CA [SC-69](#)
  - supported standards
    - Internet Key Exchange (IKE) Security protocol [SC-61](#)
    - IP Network Security (IPSec) protocol [SC-61](#)
    - Public-Key Cryptography Standard #10 (PKCS#10) [SC-61](#)
    - Public-Key Cryptography Standard #7(PKCS#7) [SC-61](#)
    - RSA (Rivest, Shamir, and Adelman) keys [SC-61](#)
    - Secure Socket Layer (SSL) protocol [SC-61](#)
    - X.509v3 certificate [SC-61](#)
- CFI VRF interface, configuring [MPC-363](#)
- changing refresh interval [MPC-92](#)
- changing restart time [MPC-93](#)
- changing summary refresh message size [MPC-92](#)
- channel command [HC-105](#), [HC-106](#), [HC-428](#)
- channel-group command [HC-184](#), [HC-189](#), [HC-335](#), [HC-457](#)
- Channelized ATM [HC-47](#), [HC-57](#)
- Channelized SONET, configuring [HC-92](#), [HC-96](#)
- CHAP
  - defined [HC-285](#)
  - enabling [HC-316](#)
  - password, configuring [HC-321](#)
  - ppp [HC-315](#), [HC-361](#)
  - refusing [HC-330](#)
- CIDR format
  - using [IC-6](#)
- circuit emulation [HC-6](#)
- circuit-type command [RC-351](#)
- Cisco inetd
  - See host services and applications*
- Cisco IOS XR Software Selector tool [SMC-58](#)
- Cisco Systems-supported security standards [SC-79](#)
- Cisco XR 12000 SIP (SPA interface processor)
  - 10 Gbps throughput
    - license for [SMC-118](#)
    - prerequisites for enabling [SMC-119](#)
- class command [HC-406](#), [HC-407](#), [QC-131](#)
- class map submode
  - match access-group command [QC-25](#)
  - match discard-class command [QC-25](#)
  - match dscp command [QC-26](#)
  - match mpls experimental topmost command [HC-405](#)
  - match precedence command [HC-406](#), [QC-26](#)
  - match protocol command [QC-26](#)
  - match qos-group command [QC-26](#)
- class map, overview in application protocol inspection process [VFC-122](#)
- class-based packet marking
  - configuring [QC-32](#)
  - set qos-group command [QC-33](#)
- classification
  - See class-based packet marking*

- See IP precedence
  - description [QC-11](#)
  - methods [QC-11](#)
  - QoS group [QC-14](#)
  - set cos command [QC-14](#)
  - set qos-group command [QC-14](#)
  - summary [QC-3](#)
- class-int command [HC-40](#)
- class-map command [HC-405](#), [HC-406](#), [QC-25](#)
- class-vc command [HC-43](#)
- clear bfd counters packet command [HC-78](#)
- clear bgp flap-statistics command [RC-73](#)
- clear bgp flap-statistics reexp command [RC-74](#)
- clear bgp flap-statistics route-policy command [RC-74](#)
- clear bgp soft in command [RC-136](#)
- clear bgp soft out command [RC-137](#)
- clear channel [HC-57](#)
- clear channel ATM [HC-50](#), [HC-57](#)
- clear crypto session command [SC-90](#)
- clear eigrp neighbors command [RC-186](#)
- clear eigrp topology command [RC-186](#)
- clear flow exporter command [HC-269](#)
- clear flow monitor command [HC-269](#)
- clear logging correlator delete all-in-buffer command [MNC-28](#)
- clear logging correlator delete command [MNC-28](#)
- clear logging delete command [MNC-28](#)
- clear logging events delete first command [MNC-38](#)
- clear logging events delete group command [MNC-39](#)
- clear logging events delete last command [MNC-38](#)
- clear logging events delete location command [MNC-38](#)
- clear logging events delete message command [MNC-38](#)
- clear logging events delete timestamp-lo-limit command [MNC-38](#)
- clear logging events reset all-in-buffer command [MNC-39](#)
- clear ospf command [RC-281](#)
- clear ospfv3 command [RC-281](#)
- clock set command [SC-253](#)
- clock source command [HC-439](#), [HC-440](#)
- command summary, FPD commands (table) [SMC-127](#)
- command syntax
  - conventions [14](#)
- commit command [HC-394](#)
- config-register command [SMC-241](#)
- configuration
  - examples
    - application protocol inspection [VFC-182](#)
    - virtualization [VFC-60](#)
  - file replication failure [VFC-328](#)
  - modified by command [VFC-317](#), [VFC-318](#)
- configuration examples
  - building MPLS-TE topology and tunnels [MPC-200](#)
  - fast reroute and SONET APS [MPC-200](#)
- LDP
  - advertisement [MPC-49](#)
  - discovery [MPC-48](#)
  - discovery for targeted hellos [MPC-48](#)
  - forwarding [MPC-49](#)
  - IGP synchronization [MPC-50](#)
  - inbound label filtering [MPC-50](#)
  - link [MPC-48](#)
  - local label allocation control [MPC-50](#)
  - neighbors [MPC-49](#)
  - non-stop forwarding with graceful restart [MPC-50](#)
  - session protection [MPC-50](#)
  - with graceful restart [MPC-48](#)
- MPLS L2VPN [MPC-258](#)
- O-UNI
  - connection establishment [MPC-224](#)
  - connection tear-down [MPC-224](#)
  - neighbor and data link [MPC-223](#)
- RSVP
  - ACL-based prefix filtering [MPC-93](#)
  - bandwidth (MAM) [MPC-91](#)
  - bandwidth (Prestandard) [MPC-91](#)
  - bandwidth (RDM) [MPC-91](#)
  - DSCP [MPC-93](#)

- graceful restart [MPC-92](#)
- configuration register, displaying [SMC-225](#)
- configure command [HC-393](#)
- configuring
  - outbound traffic (key chain) [SC-222](#)
- configuring hash algorithm [IC-71](#)
- configuring relay agent [IC-103](#)
- conform-action command [QC-95](#)
- congestion avoidance
  - description [QC-107](#)
  - summary [QC-4](#)
- congestion management, summary [QC-3](#)
- consecutive threshold violation [MNC-119](#)
- content type verification, HTTP message [VFC-142](#)
- context
  - Admin [VFC-46](#)
  - configuration file [VFC-46](#)
  - configuration synchronization failure [VFC-331](#)
  - configuring [VFC-50](#)
  - database [VFC-46](#)
  - description [VFC-46](#), [VFC-47](#)
  - diagram [VFC-47](#)
  - displaying information [VFC-59](#)
  - domains [VFC-47](#), [VFC-48](#)
  - moving from one to another [VFC-47](#)
  - overview [VFC-45](#)
  - startup-config [VFC-46](#)
  - state change [VFC-331](#)
  - user role [VFC-48](#)
- control ethernet inactive link test [HC-139](#)
- control ethernet ping test [HC-139](#)
- control message
  - hashing, L2TPv3 [MPC-330](#)
  - with LDP [MPC-3](#)
- control packets [HC-390](#)
- control plane failure [MPC-6](#)
- control plane protection, MPP
  - CoPP (Control Plane Policing) [SC-241](#)
  - definition [SC-241](#)
- control protocol, IP SLA [MNC-53](#)
- control-channels
  - configuring authentication parameters [MPC-328](#)
  - configuring L2TP maintenance parameters [MPC-337](#)
  - configuring L2TP parameters [MPC-326](#)
  - configuring method of authentication [MPC-329](#)
  - configuring timing parameters [MPC-327](#)
  - message authentication [MPC-328](#)
  - parameters, how to configure [MPC-326](#)
  - timing parameters, how to configure [MPC-327](#)
- controller e1 command [HC-465](#)
- controller fabric plane command [SMC-248](#), [SMC-256](#), [SMC-257](#), [SMC-265](#)
- controller mgmtmultilink command [HC-336](#)
- controller sonet command
- controllers command [SMC-243](#)
- controllers fabric plane command [SMC-250](#), [SMC-258](#), [SMC-266](#)
- control-plane command [SC-243](#)
- copy ftp command [SMC-60](#)
- copy rpc command [SMC-60](#)
- copy tftp command [SMC-59](#)
- copying
  - files from remote server [VFC-252](#)
  - files to remote server [VFC-251](#)
  - packet capture buffer [VFC-251](#)
- core network, how to configure [MPC-364](#)
- correlated message [MNC-6](#)
- CoS (class of service), defining classes [QC-16](#)
- cost community, BGP [RC-23](#)
- CPU controller bits, upgrading [SMC-277](#)
- crc command [HC-284](#), [HC-365](#)
- critical messages [VFC-338](#)
- CRLs\
- crypto ipsec df-bit command [SC-167](#)
- crypto ipsec pmtu command [SC-192](#)
- crypto ipsec pre-fragmentation command [SC-177](#)
- crypto ipsec profile command [SC-170](#)

crypto ipsec security-association idle-time command [SC-174](#)

crypto ipsec security-association replay disable command [SC-169](#)

crypto ipsec security-association replay window-size command [SC-169](#)

crypto ipsec server send-update command [SC-91](#)

crypto ipsec transform-set command [SC-160](#)

crypto isakmp client configuration group command [SC-102](#)

crypto keyrings

- configuring [SC-116](#)
- guidelines and restrictions [SC-116](#)

crypto mib ipsec flowmib history failure size command [SC-182](#)

crypto nat-transparency command [SC-172](#)

cryptographic-algorithm command [SC-223](#)

CSC (Carrier Supporting Carrier)

- configuration examples [MPC-451](#)
- configuration options for backbone and customer carriers [MPC-399](#)
- configuring a CSC-PE link [MPC-445](#)
- configuring a static route to a peer [MPC-451](#)
- customer carrier network options [MPC-400](#)
- identifying topology [MPC-444](#)

CSC-CE link, how to configure [MPC-449](#)

CSC-PE link, how to configure [MPC-445](#)

CSCs (clock and scheduler cards)

- node ID components (XR 12000) [SMC-227](#)
- removing and replacing [SMC-270](#)

CSFCs (consolidated switch fabric cards)

- node ID components (XR 12000) [SMC-227](#)
- removing and replacing [SMC-275](#)

csnp-interval command [RC-325](#)

customer edge router

- 6PE [MPC-309](#)

customer edge router (CE)

- MPLS Layer 3 VPN [MPC-381](#)

---

**D**

dampening, route [RC-35](#)

datasize request command

- ICMP Echo operation [MNC-82](#)
- ICMP Path Echo operation [MNC-89](#)
- ICMP Path Jitter operation [MNC-98](#)
- UDP Echo operation [MNC-75](#)
- UDP Jitter operation [MNC-67](#)

DDoS [VFC-277](#)

dead interval command [RC-228](#)

dead-time

- RADIUS server setting [VFC-73](#)
- TACACS+ server setting [VFC-79](#)

deadtime command [SC-36](#)

debug chdlc slarp packet command [HC-285](#)

debug logging failure [VFC-337](#)

debugging messages [VFC-341](#)

default address family [RC-20](#)

default settings

- flow control, Management Ethernet [HC-239](#)
- mac-address (Management Ethernet) [HC-239](#)
- speed (Management Ethernet) [HC-239](#)

default software profile [SMC-9](#)

default traffic class

- summary [QC-13](#)
- tail drop [QC-13](#)

default-cost command [RC-225](#)

default-information originate command [RC-342](#)

defining preemption [IC-138](#)

delay trigger command [HC-423](#)

denial of service. See DoS [VFC-277](#)

DES (Data Encryption Standard)

- IKE policy parameter [SC-82](#)

description (ISAKMP peer) command [SC-90](#)

destination address command

- ICMP Echo operation [MNC-79](#)
- ICMP Path Echo operation [MNC-86](#)
- ICMP Path Jitter operation [MNC-94](#)

- UDP Echo operation [MNC-71](#)
- UDP Jitter operation [MNC-63](#)
- destination command [HC-261](#)
- destination NAT [VFC-294](#), [VFC-296](#), [VFC-307](#)
- destination port command
  - UDP Echo operation [MNC-72](#)
  - UDP Jitter operation [MNC-63](#)
- DF (Don't Fragment) bit override
  - configuring [SC-167](#)
  - description [SC-144](#)
- DHCP (Dynamic Host Configuration Protocol)
  - configuring relay agent [IC-103](#)
  - forwarding UDP broadcasts to DHCP server, figure [IC-97](#)
- DHCP relay agent
  - definition [IC-96](#)
- dhcp relay information option command [IC-104](#)
- diagnostics [HC-137](#)
- differentiated service model, classification [QC-16](#)
- Differentiated Services Traffic-Engineering
  - bandwidth constraints [MPC-103](#)
  - configuring bandwidth [MPC-64](#)
  - overview [MPC-103](#)
- Diff-Serv
  - RDM (russian doll model) and MAM (maximum allocation model) [MPC-103](#)
- digest secret graceful switchover, L2TPv3 [MPC-332](#)
- directory, copying files [VFC-251](#)
- disk backup
  - See* backup disk
- disk mirroring
  - about [SMC-95](#)
  - enabling [SMC-102](#)
  - enabling (example) [SMC-107](#)
  - feature history [SMC-93](#)
  - mirror verify output (example) [SMC-108](#)
  - prerequisites
  - show mirror output (example) [SMC-107](#)
- disk0, overview [VFC-249](#)
- distance bgp command [RC-78](#)
- distance command [RC-170](#)
- distributed BGP [RC-39](#)
- distributed denial of service. *See* DDoS [VFC-277](#)
- distribution count command [MNC-67](#)
- distribution interval command [MNC-67](#)
- DNS (Domain Name System)
  - application protocol support [VFC-120](#)
  - configuration example [VFC-182](#)
  - inspection overview [VFC-124](#)
  - packet message [VFC-325](#)
- documentation
  - conventions [14](#)
  - modules [2](#)
- domain
  - description [VFC-48](#)
  - diagram [VFC-47](#)
  - function within a context [VFC-47](#)
  - information, displaying [VFC-59](#)
  - name [VFC-48](#)
- domain command [IC-123](#)
- domain name command [IC-122](#)
- domain name-server command [IC-122](#)
- domain services
  - See* host services and applications
- Don't Fragment bit, handling [VFC-279](#)
- DoS protection, SYN cookie [VFC-277](#)
- dot1q native vlan command [HC-488](#)
- dot1q vlan command [HC-486](#), [HC-490](#)
- downloading software package files [SMC-59](#)
- DPD (Dead Peer Detection) message, configuring [SC-126](#)
- DR (designated router)
  - See* multicast routing, DR (designated router)
- draft-bonica-tcp-auth-05.txt [RC-152](#)
- draft-ietf-idr-as4bytes-12.txt [RC-152](#)
- draft-ietf-idr-avoid-transition-00.txt [RC-152](#)
- draft-ietf-idr-bgp4-24.txt, BGP [RC-152](#)
- draft-ietf-idr-bgp4-mib-15.txt, BGP [RC-152](#)

- draft-ietf-idr-cease-subcode-05.txt [RC-152](#)
- draft-ietf-isis-igp-p2p-over-lan-05.txt, Point-to-point operation over LAN [RC-357](#)
- draft-ietf-isis-ipv6-05.txt, Routing IPv6 with IS-IS [RC-357](#)
- draft-ietf-isis-restart-04.txt, Restart Signalling for IS-IS [RC-357](#)
- draft-ietf-isis-traffic-05.txt, IS-IS Extensions for Traffic Engineering [RC-357](#)
- draft-ietf-isis-wg-multi-topology-06.txt, M-ISIS
  - Multi Topology (MT) Routing in IS-IS [RC-357](#)
- draft-ietf-rtgwg-ipfrr-framework-06.txt [RC-357](#)
- draft-ietf-rtgwg-ipfrr-framework-06.txt, IP fast reroute [RC-371](#)
- draft-ietf-rtgwg-lf-conv-frmwk-00.txt [RC-357](#)
- draft-ietf-rtgwg-lf-conv-frmwk-00.txt [RC-371](#)
- draft-nalawade-idr-mdt-safi-03.txt [RC-152](#)
- drives, formatting [SMC-243](#)
- DRP pairing configuration mode
  - location command [SMC-14](#)
- dr-priority command [MCC-11](#)
- DRPs (distributed route processors)
  - node ID components (CRS-1) [SMC-226](#)
  - process distribution among
    - See* process placement
- DSC (designated shelf controller)
  - DSDRSC for owner SDR, is [SMC-6](#)
  - migration [SMC-11](#)
- dscp command [HC-261](#)
- DSDRSC (designated secure domain router shelf controller) [SMC-6](#)
- DS-TE modes, prestandard and IETF [MPC-64](#)
- duplex command [HC-243](#)
- duplex full command [HC-158](#)
- duplex half command [HC-158](#)
- Dynamic Packet Transport (DPT), Cisco [HC-389](#)
- card type, setting [HC-441](#)
- default configuration values [HC-439](#), [HC-440](#)
- frame type [HC-440](#), [HC-460](#)
- E1 mode, changing to T1 mode [HC-441](#)
- E3 controller
  - cable length, setting [HC-439](#)
  - card type, setting [HC-441](#)
  - clock source, default value [HC-439](#)
  - configuration prerequisites [HC-438](#)
  - configuring
    - clear channel [HC-443](#)
    - clear channel serial [HC-444](#)
    - national reserved bits [HC-439](#)
  - E3 configuration mode [HC-444](#)
  - frame type [HC-439](#), [HC-446](#)
  - E3 mode, changing to T3 mode [HC-441](#)
- Easy VPN (Virtual Private Network) features
  - auto-update [SC-91](#)
  - banner [SC-91](#)
  - URL configuration description [SC-92](#)
- eBGP [MPC-380](#)
- ebgp-multihop command [RC-121](#)
- echo disable command [HC-75](#), [HC-77](#)
- edit command [RC-457](#)
- EIGRP
  - authentication keychain configuration [RC-187](#)
  - authentication keychain example [RC-193](#)
  - authentication using keychain [RC-168](#)
- EIGRP (Enhanced Interior Gateway Routing Protocol)
  - features [RC-157](#)
  - hello interval and hold time [RC-165](#)
  - overview [RC-157](#)
  - policy attach points
    - default-accept-out [RC-444](#)
    - if-policy-in [RC-445](#)
    - if-policy-out [RC-445](#)
    - policy-in [RC-445](#)
    - policy-out [RC-445](#)
    - redistribute [RC-445](#)

---

**E**

E1 controller

- policy attach points, default-accept-in [RC-444](#)
- restrictions [RC-178](#)
- routing policy options [RC-166](#)
- split horizon [RC-164](#)
- stub routing [RC-165](#)
- encap command (Frame Relay) [HC-170](#), [HC-171](#), [HC-179](#)
- Encap table full [VFC-324](#)
- encapsulation command [HC-37](#), [HC-284](#), [HC-365](#)
- encapsulation frame relay command [HC-171](#)
- encryption algorithm
  - See also* IKE algorithms
- end command [HC-394](#)
- end-policy command [RC-49](#)
- end-time, key chain management [SC-214](#)
- end-to-end recovery, GMPLS [MPC-109](#)
- environment information, displaying [SMC-229](#)
- Environmental variables (example) [MNC-278](#)
- EoMPLS (ethernet over MPLS)
  - ethernet port mode [MPC-231](#)
  - Ethernet remote port shutdown [MPC-232](#)
  - inter-as port mode [MPC-233](#)
  - Mac-in-Mac [MPC-235](#)
  - overview [MPC-231](#)
  - QinAny mode [MPC-234](#)
  - QinQ mode [MPC-234](#)
- error messages [VFC-339](#)
  - levels [MNC-158](#)
  - logging keywords (table) [MNC-158](#)
- Ethernet interface
  - configuring
    - attachment circuit [HC-161](#)
    - flow control [HC-146](#)
    - IP address and subnet mask [HC-154](#)
    - MAC accounting [HC-146](#), [HC-160](#)
    - MAC address [HC-146](#), [HC-155](#)
    - MTU [HC-146](#), [HC-155](#)
  - default settings
    - flow control [HC-146](#)
    - MAC accounting [HC-146](#)
    - MAC address [HC-146](#)
    - mtu [HC-146](#)
  - displaying
    - Ethernet interfaces [HC-156](#)
    - MAC accounting statistics [HC-161](#)
  - enabling
    - flow-control [HC-155](#)
    - Layer 2 transport mode [HC-162](#)
  - Gigabit Ethernet standards [HC-148](#)
    - IEEE 802.3 Physical Ethernet Infrastructure [HC-148](#)
    - IEEE 802.3ab 1000BASE-T Gigabit Ethernet [HC-148](#)
    - IEEE 802.3ae 10 Gbps Ethernet [HC-149](#)
    - IEEE 802.3z 1000 Mbps Gigabit Ethernet [HC-149](#)
  - Layer 2 VPN
    - Layer 2 protocol tunneling and data units, configuring [HC-162](#)
    - Layer 2 VPN, port [HC-161](#)
    - overview [HC-147](#)
    - VLAN support [HC-484](#)
  - VLANs
    - 802.1Q frames tagging [HC-483](#)
    - attachment circuit, configuring [HC-490](#)
    - Layer 2 VPN attachment circuit, configuring [HC-489](#)
    - Layer 2 VPN, configuring [HC-491](#)
    - MTU inheritance [HC-483](#)
    - native VLAN description [HC-483](#)
    - native VLAN, configuring [HC-488](#)
    - overview [HC-482](#)
    - subinterface overview [HC-483](#)
    - subinterface, configuring [HC-485](#)
    - subinterface, removing [HC-492](#)
    - VLAN AC, assigning [HC-486](#)
    - VLAN interfaces, displaying [HC-487](#)
    - VLAN trunks, displaying [HC-487](#)
- ethernet port mode [MPC-231](#)

## example

linecard throughput, displaying [SMC-118](#)

SIP throughput, displaying [SMC-120](#)

exceed-action command [QC-89](#)

EXEC mode [RC-18](#)

clear bgp flap statistics command [RC-73](#)

clear bgp flap statistics reexp command [RC-74](#)

clear bgp flap statistics route-policy  
command [RC-74](#)

clear bgp soft in command [RC-136](#)

clear bgp soft out command [RC-137](#)

clear eigrp neighbors command [RC-186](#)

clear eigrp topology command [RC-186](#)

clear ospf command [RC-281](#)

clear ospfv3 command [RC-281](#)

edit command [RC-457](#)

show bgp af-group command [RC-18](#)

show bgp cidr-only command [RC-140](#)

show bgp community command [RC-142](#)

show bgp count-only command [RC-141](#)

show bgp flap statistics reexp command [RC-72](#)

show bgp flap statistics route-policy  
command [RC-73](#)

show bgp flap-statistics command [RC-72](#)

show bgp inheritance command [RC-17](#)

show bgp neighbor command [RC-16](#)

show bgp neighbor-group command [RC-19](#)

show bgp neighbors command [RC-140](#)

show bgp paths command [RC-140](#)

show bgp reexp command [RC-140](#)

show bgp summary command [RC-141](#)

show eigrp accounting command [RC-186](#)

show eigrp interfaces command [RC-186](#)

show eigrp neighbors command [RC-180](#)

show eigrp topology command [RC-187](#)

show eigrp traffic command [RC-187](#)

show isis command [RC-310](#)

show isis database command [RC-326](#)

show isis database-log command [RC-326](#)

show isis interface command [RC-339](#)

show isis lsp-log command [RC-326](#)

show isis mpls command [RC-335](#)

show isis mpls traffic-eng adjacency-log  
command [RC-335](#)

show isis mpls traffic-eng advertisements  
command [RC-335](#)

show isis neighbors command [RC-339](#)

show isis spf-log command [RC-341](#)

show isis topology command [RC-315](#)

show protocols eigrp command [RC-187](#)

show rpl route-policy command [RC-457](#)

show running-config command [RC-328](#)

exit command [HC-406](#), [HC-407](#)

export route-target command [RC-101](#)

exporter command [HC-266](#)

exporter map [HC-255](#)

extended access-lists [MPC-59](#)

extended networks, using IP secondary  
addresses [IC-187](#)

extensions, MPLS TE [MPC-102](#)

---

**F**

f4oam disable command [HC-19](#)

fabric diagnostic test [HC-140](#)

fabric multicast diagnosis test [HC-140](#)

fabric ping test [HC-139](#)

fabric quality of service

configuring [QC-130](#)

configuring (examples) [QC-132](#)

creating a fabric QoS service policy [QC-130](#)

overview [QC-128](#)

policy-map command [QC-131](#)

failure recovery, graceful restart [MPC-9](#)

fan controller cards (16-slot CRS-1), node ID  
components [SMC-227](#)

Fast Ethernet interface

auto-negotiation [HC-147](#), [HC-158](#)

configuring

- duplex operation [HC-147](#), [HC-158](#)
- interface speed [HC-158](#)
- IP address and subnet mask [HC-157](#)
- MAC accounting [HC-147](#)
- MTU [HC-147](#), [HC-158](#)
- default settings
  - auto-negotiation [HC-147](#)
  - duplex operation [HC-147](#)
  - interface speed [HC-147](#)
  - MAC accounting [HC-147](#)
  - mtu [HC-147](#)
- shutdown configuration, removing [HC-158](#)
- fault manager environment command [MNC-245](#), [MNC-246](#)
- fault manager policies
  - persist-time [MNC-247](#)
  - registering [MNC-247](#)
  - registration (example) [MNC-279](#)
- fault manager policy command [MNC-247](#), [MNC-249](#)
- fault tolerance
  - See HA [VFC-327](#)
- FCC serial number
  - displaying [SMC-224](#)
- fdl ansi [HC-440](#)
- fdl command [HC-440](#), [HC-456](#)
- feature history
  - CDP [SMC-281](#)
  - configuring SDRs [SMC-1](#)
  - disk backup and mirroring [SMC-93](#)
  - NTP [SMC-157](#)
  - object tracking [SMC-185](#)
  - physical and virtual terminals [SMC-201](#)
  - process placement [SMC-139](#)
  - router hardware management
  - SNMP [SMC-293](#)
  - software entitlement [SMC-111](#)
  - upgrading and managing Cisco IOS XR Software [SMC-39](#)
- FIB (Forwarding Information Base) [IC-53](#)
- field-programmable gate array
  - See FPGA
- file system
  - copying files
    - from remote server [VFC-252](#)
    - to directory [VFC-251](#)
    - to remote server [VFC-251](#)
  - copying packet capture buffer [VFC-251](#)
  - overview [VFC-249](#)
- file system functionality verification test [HC-140](#)
- File Transfer Protocol (FTP) [SMC-59](#)
- file transfer services
  - See host services and applications
- filtering routes by a prefix list [IC-10](#)
- fixups
  - See application protocol inspection [VFC-119](#)
- flash disk recovery [SMC-242](#)
- Flash memory, file system overview [VFC-249](#)
- flooding
  - MAC address [MPC-270](#)
  - thresholds [MPC-105](#)
  - triggers [MPC-105](#)
- flow command [HC-268](#), [IC-157](#)
- flow exporter map configuration submode [HC-256](#)
- flow exporter map version configuration submode [HC-256](#)
- flow exporter-map command [HC-261](#)
- flow monitor map configuration submode [HC-257](#)
- flow monitor-map command [HC-260](#), [HC-265](#), [HC-274](#)
- flow-control command [HC-146](#), [HC-155](#)
- format command [SMC-102](#), [SMC-243](#)
- formatting drives [SMC-243](#)
- forwarding adjacency [RC-307](#)
- forwarding UDP broadcasts to DHCP server, figure [IC-97](#)
- FPDs (field-programmable devices)
  - compatibility, displaying [SMC-232](#)
  - images
    - description [SMC-125](#)

- displaying [SMC-128](#)
  - overview for SPAs [SMC-126](#)
  - upgrade [SMC-128](#), [SMC-129](#), [SMC-135](#), [SMC-136](#)
  - upgrading [SMC-75](#)
- FPGA (field-programmable gate array)
- description
  - devices, methods of upgrading [SMC-126](#)
- Frame Relay
- configuration examples [HC-192](#)
  - configuring
    - PVC encapsulation [HC-179](#)
    - support type [HC-171](#), [HC-178](#)
  - default configuration, modifying [HC-177](#), [HC-178](#)
  - default settings [HC-171](#)
  - LMI
    - configuring [HC-171](#), [HC-179](#)
    - disabling [HC-171](#), [HC-179](#), [HC-180](#)
    - enabling [HC-171](#)
    - overview [HC-171](#)
    - polling [HC-172](#), [HC-173](#)
  - overview [HC-170](#)
  - POS interfaces [HC-281](#)
  - prerequisites [HC-170](#)
  - PVCs [HC-171](#)
  - serial interfaces [HC-363](#)
- Frame Relay discard eligibility bit
- matching [QC-48](#)
  - setting [QC-47](#)
- Frame Relay on Layer 2 VPN [QC-19](#)
- frame relay, MPLS L2VPN [MPC-229](#)
- frame-relay intf-type command [HC-171](#), [HC-178](#)
- frame-relay intf-type dce command [HC-172](#)
- frame-relay intf-type dte command [HC-172](#)
- frame-relay lmi command [HC-171](#)
- frame-relay lmi disable command [HC-180](#)
- frame-relay lmi-t391dte command [HC-173](#)
- frame-relay lmi-type command [HC-171](#), [HC-179](#)
- framing command [HC-439](#), [HC-440](#)
- frequency (IP SLA) command
- ICMP Echo operation [MNC-79](#)
  - ICMP Path Echo operation [MNC-86](#)
  - ICMP Path Jitter operation [MNC-94](#)
  - UDP Echo operation [MNC-72](#)
  - UDP Jitter operation [MNC-64](#)
- FRR (fast reroute)
- link protection [MPC-106](#)
  - over link bundles [MPC-106](#)
  - with MPLS TE [MPC-106](#)
- FT group
- context name mismatch [VFC-328](#)
  - peer state change [VFC-336](#)
  - two active devices detected [VFC-328](#)
- FT interface, peer
- unreachable [VFC-328](#)
- FT track, state change [VFC-334](#)
- FTP [SMC-59](#)
- application protocol support [VFC-120](#), [VFC-121](#)
  - inspection overview [VFC-125](#)
  - strict [VFC-125](#)
- FTP (File Transfer Protocol)
- configuring a router [IC-126](#)
  - definition [IC-119](#)
  - troubleshooting tips [IC-128](#)
- ftp client anonymous-password command [IC-127](#)
- ftp client passive command [IC-127](#)
- ftp client source-interface command [IC-128](#)
- FVRF (front door virtual routing and forwarding) [MPC-322](#)

---

**G**

- Generalized TTL Security Mechanism (GTSM), configuring virtual links [RC-219](#)
- global configuration mode
  - access-list command [MCC-33](#), [MCC-36](#), [MCC-38](#)
  - hw-module qos multicast enable command [MCC-65](#)

- hw-module qos multicast priority queue command [MCC-65](#)
  - interface command [MCC-59](#)
  - ipv4 access-list command [MCC-64](#)
  - permit command [MCC-34](#), [MCC-36](#)
  - global parameters [RC-405](#)
  - GMPLS (generalized multiprotocol label switching)
    - benefits [MPC-108](#)
    - configuring [MPC-141](#)
    - overview [MPC-107](#)
    - prerequisites [MPC-110](#)
    - protection and restoration [MPC-109](#)
    - support [MPC-108](#)
    - traffic engineering protocols [MPC-107](#)
  - Golden disk
    - See <Default Para Font>backup disk
  - graceful restart
    - failure recovery [MPC-9](#)
    - LDP [MPC-6](#)
    - mechanism [MPC-7](#)
    - NSR [MPC-13](#)
    - phases [MPC-7](#)
    - RSVP [MPC-57](#)
    - session parameters [MPC-6](#)
  - graceful-restart helper command [RC-215](#)
  - graceful-restart interval command [RC-215](#)
  - graceful-restart lifetime command [RC-215](#)
- 
- H**
- HA
    - alternate pings [VFC-334](#), [VFC-335](#)
    - context
      - name mismatch [VFC-328](#)
      - state change [VFC-331](#)
    - data dropped [VFC-337](#)
    - failure
      - communication [VFC-330](#)
      - configuration replication [VFC-331](#)
      - initialization [VFC-329](#)
      - replication [VFC-328](#), [VFC-330](#)
    - FT track, state change [VFC-334](#)
    - heartbeat
      - interval mismatch [VFC-333](#)
      - unidirectional [VFC-333](#)
    - internal error [VFC-330](#)
    - module [VFC-329](#)
    - peer
      - compatibility [VFC-335](#)
      - incompatibility [VFC-329](#)
      - reachable [VFC-332](#), [VFC-335](#)
      - state change [VFC-336](#)
      - unreachable [VFC-327](#), [VFC-328](#)
    - peer unreachable [VFC-336](#)
    - receive error [VFC-336](#)
    - redundancy heartbeat stopped [VFC-335](#)
    - replication
      - configuration failure [VFC-331](#)
      - failure [VFC-328](#)
      - in process [VFC-333](#)
      - state transitions [VFC-331](#)
      - two active devices detected [VFC-328](#)
  - hardware
    - environment information [SMC-229](#)
    - managing, feature history
    - managing, prerequisites for [SMC-216](#)
    - node IDs and dtatus, displaying [SMC-228](#)
    - SDR version, displaying [SMC-216](#)
    - serial numbers, displaying [SMC-224](#)
    - status, displaying [SMC-216](#)
    - version info, displaying
  - hash algorithm
    - See IKE, algorithms
  - HDLC [HC-284](#)
  - header value string expressions [VFC-134](#), [VFC-138](#)
  - heartbeat
    - interval mismatch [VFC-333](#)
    - started [VFC-335](#)

- stopped [VFC-327, VFC-334, VFC-335](#)
- unidirectional [VFC-333](#)
- hello interval (OSPF) command [RC-228](#)
- hello interval, changing [MPC-93](#)
- hello-interval (IS-IS) command [RC-337](#)
- hello-multiplier command [RC-337](#)
- hello-padding command [RC-337](#)
- hello-password command [RC-338](#)
- hierarchical ingress policing
  - configuring [QC-42](#)
  - example [QC-65](#)
- hierarchical optical network, GMPLS [MPC-107](#)
- High Availability
  - See HA [VFC-327](#)
- high availability overview [SC-149](#)
- high availability, RSVP [MPC-56](#)
- hitless key rollover
  - accept-tolerance command [SC-216](#)
- hitless key rollover, configuring [SC-216](#)
- holdtime command [RC-170](#)
- host services and applications
  - Cisco inetd [IC-117](#)
  - description [IC-115](#)
  - domain services [IC-117, IC-122](#)
    - configuration [IC-121](#)
  - file transfer services [IC-117, IC-125, IC-126, IC-129](#)
    - File Transfer Protocol (FTP) [IC-119](#)
    - remote copy protocol (RCP) [IC-119](#)
    - fttp server command [IC-124](#)
    - Trivial File Transfer Services (TFTP) [IC-119](#)
  - network connectivity
    - ping tool [IC-117](#)
  - prerequisites [IC-116](#)
  - telnet [IC-120](#)
  - TFTP server [IC-118](#)
  - tools [IC-117](#)
- HSRP (Hot Standby Router Protocol)
  - configuring activation delay [IC-147](#)
  - configuring group attributes [IC-141](#)
  - description [IC-135](#)
  - enabling [IC-139](#)
  - enabling support for ICMP redirect messages [IC-149](#)
  - groups [IC-137](#)
  - overview [IC-136](#)
  - preemption [IC-138](#)
- HSRP (Hot Standby Router Protocol), figure [IC-138](#)
- hsrp command [IC-139](#)
- hsrp redirects command [IC-149](#)
- HTTP
  - application protocol support [VFC-121](#)
  - content type verification match criteria, defining [VFC-142](#)
  - header value string expressions [VFC-134, VFC-138](#)
  - HTTP/1/1 header fields, supported [VFC-137](#)
  - inline match commands in policy map [VFC-142](#)
  - inspection overview [VFC-124](#)
  - internal compliance checks [VFC-143](#)
  - strict HTTP match criteria, defining [VFC-143](#)
- hw-module linecard throughput location command [SMC-119](#)
- hw-module location command [SMC-239, SMC-242, SMC-272, SMC-273](#)
- hw-module location reload command [SMC-239](#)
- hw-module location shutdown command [SMC-239](#)
- hw-module node reload command [HC-394](#)
- hw-module port command [HC-393](#)
- hw-module power disable command [SMC-257](#)
- hw-module power disable location command [SMC-249, SMC-265](#)
- hw-module qos multicast command [MCC-64](#)
- hw-module qos multicast priorityq disable command [MCC-64](#)
- hw-module subslot cardtype command [HC-441, HC-442](#)
- hw-module subslot reload command [SMC-129](#)