

# Cisco IOS XR Configuration Guide Master Index, Release 3.8

This page contains a list of all the indexed terms contained in the Cisco IOS XR configuration guides for Release 3.8, ordered alphabetically. Use the **Alphabet Key** or your web browser's Find function to search for a command. To access the documentation for a particular command, click on the command name.

## Page Number Designators

<b>HC</b>	Cisco IOS XR Interface and Hardware Component Configuration Guide
<b>IC</b>	Cisco IOS XR Addresses and Services Configuration Guide
<b>MCC</b>	Cisco IOS XR Multicast Configuration Guide
<b>MNC</b>	Cisco IOS XR System Monitoring Configuration Guide
<b>MPC</b>	Cisco IOS XR MPLS Configuration Guide
<b>QC</b>	Cisco IOS XR Modular Quality of Service Configuration Guide
<b>RC</b>	Cisco IOS XR Routing Configuration Guide
<b>SC</b>	Cisco IOS XR System Security Configuration Guide
<b>SMC</b>	Cisco IOS XR System Management Configuration Guide
<b>VFC</b>	Cisco IOS XR Virtual Firewall Command Reference

## I

### ICMP (Internet Control Message Protocol)

- application protocol support [VFC-121](#)
- initialization failure [VFC-322](#)
- inspection overview [VFC-126](#)
- memory failure [VFC-323](#)
- packet denied [VFC-322](#)
- security, disabling [VFC-277](#)
- session established [VFC-320](#)

- session removed [VFC-320](#)
- ICMP Path Jitter operation parameters, list of [MNC-92](#)
- ICMP rate limiting [IC-192](#)
- IEEE 802.3ad standard [HC-205](#)
- IETF DS-TE mode [MPC-103](#)
- if preconfiguration submode, ipv4 address command [HC-351](#)
- if submode
  - See* interface command
  - See* interface preconfigure command
  - bundle id command [HC-211](#), [HC-218](#), [HC-222](#)
  - controller sonet command [HC-429](#)
  - duplex command [HC-243](#)
  - interface command [HC-428](#)
  - ipv4 address command [HC-185](#), [RC-259](#)
  - keepalive command [HC-429](#)
  - mtu command [HC-241](#)
  - no shutdown command [HC-211](#)
  - pos crc command [HC-429](#)
  - show srp ips interface srp command [HC-404](#)
  - speed command [HC-244](#)
  - srp interface srp request manual-switch command [HC-404](#)
  - srp ips request forced-switch command [HC-403](#), [HC-409](#), [HC-410](#)
  - srp ips timer command [HC-403](#)
  - srp ips wtr-timer command [HC-403](#)
  - srp topology-timer command [HC-400](#)
  - tunnel destination command [HC-477](#)
  - tunnel source command [HC-477](#)
- IFIB (Internal Forwarding Information Base) [IC-156](#)
- Ignore IS-IS
  - overload bit setting
    - configuring [MPC-140](#)

- ignore-lsp-errors command [RC-325](#)
- IGP (interior gateway protocols)
  - prefixes [MPC-4](#)
  - routing protocols [MPC-3](#)
  - synchronizing with LDP [MPC-11](#)
- IKE (Internet Key Exchange Security Protocol)
  - See also* IPsec\
  - Advanced Encryption Standard (AES)
    - definition [SC-80](#)
  - algorithms
    - encryption
    - hash
    - MD5 (Message Digest 5) [SC-80](#)
    - options [SC-83](#)
    - SHA (Secure Hash Algorithm),
      - definition [SC-80](#)
  - authentication methods [SC-83, SC-96](#)
  - Call Admission Control (CAC)
    - limiting CPU resources consumed [SC-89](#)
  - Call Admission Control (CAC) definition [SC-89](#)
  - configuring
    - a banner as a client group attribute for Cisco Easy VPN Server [SC-102](#)
    - auto-update as a group attribute for the Cisco Easy VPN Server [SC-103](#)
    - browser-proxy as a client group attribute for the Cisco Easy VPN Server [SC-105](#)
    - client group attributes for Cisco Easy VPN Server [SC-102](#)
    - IKE security association (SA) limit for call admission control [SC-112](#)
    - ISAKMP group policy attributes [SC-97](#)
    - ISAKMP identity [SC-85](#)
    - policies [SC-95](#)
  - definition [SC-79](#)
  - DES (Data Encryption Standard)
    - definition [SC-80](#)
  - DH (Diffie-Hellman)
    - IKE policy parameter [SC-82](#)
    - specifying the group identifier [SC-96](#)
  - DPD (Dead Peer Detection)
    - periodic message [SC-93](#)
  - Easy VPN (Virtual Private Network) features
    - browser-proxy [SC-91](#)
    - enabling and disabling [SC-93](#)
    - enabling config-isakmp command mode [SC-95](#)
    - extended authentication [SC-88](#)
  - Internet Security Association and Key Management Protocol (ISAKMP)
    - definition [SC-80](#)
  - ISAKMP peer description [SC-90](#)
  - keyring configuration mode enablement [SC-109](#)
  - keys
    - See* keys, preshared\
    - mask preshared [SC-86](#)
    - preshared
  - negotiations [SC-82](#)
  - Oakley Key Exchange Protocol definition [SC-80](#)
  - policies
    - configuring (example) [SC-128](#)
    - identifying [SC-95](#)
    - multiple [SC-84](#)
    - parameters [SC-83](#)
    - purpose [SC-81](#)
    - viewing [SC-96](#)
  - Public Key Cryptographic Protocol
    - Diffie-Hellman [SC-80](#)
  - public key cryptographic system
    - RSA (Rivest, Shamir, and Adelman) [SC-80](#)
  - requirements
    - RSA encrypted nonces method [SC-85](#)
    - RSA signatures method [SC-85](#)
  - RFC 2408, ISAKMP [SC-80](#)
  - RSA (Rivest, Shamir, and Adelman)
    - encrypted nonces [SC-80, SC-82](#)
    - signatures [SC-82](#)
  - Skeme Key Exchange Protocol
    - definition [SC-80](#)
  - VPN monitoring

- adding an IKE peer description [SC-118](#)
  - clearing a crypto session [SC-90](#), [SC-120](#)
  - X.509v3 certificates standard [SC-81](#)
- ILMI, on ATM interfaces [HC-43](#)
- ILS inspection [VFC-121](#), [VFC-127](#)
- immediate threshold violation [MNC-119](#)
- implicit deny [MPC-68](#)
- inband management interface, MPP
  - allow command [SC-243](#)
  - definition [SC-240](#)
  - inband command [SC-243](#)
  - interface command [SC-243](#)
- inbound ACLs [VFC-111](#)
- inbound connection, telnet [IC-120](#)
- indexes, master [2](#)
- informational messages [VFC-340](#)
- inheritance
  - configurations (BGP) [RC-12](#)
  - monitoring [RC-16](#)
- initialization failure [VFC-329](#)
- inline match commands
  - content type verification for HTTP inspection [VFC-142](#)
  - in Layer 7 HTTP deep packet inspection policy map [VFC-142](#)
  - strict HTTP for HTTP inspection [VFC-143](#)
- in-place policy modification
  - (examples) [QC-66](#)
  - description [QC-20](#)
- insertion and removal
  - see OIR [MNC-5](#)
- inspection engines
  - See application protocol inspection [VFC-119](#)
- install activate command [SMC-73](#)
- install add command [SMC-71](#)
- install commit command [SMC-75](#)
- install deactivate command [SMC-83](#)
- install label command [SMC-88](#)
- install log, displaying [SMC-54](#)
- install operation command [SMC-86](#)
- install rollback to command [SMC-87](#)
- install rollback to committed command [SMC-87](#), [SMC-90](#)
- install verify packages command [SMC-63](#), [SMC-74](#)
- installation
  - See also* software packages
  - examples [SMC-75](#)
  - preparing for [SMC-60](#)
  - prerequisites [SMC-57](#)
  - procedures
    - SDR, operations, concurrent [SMC-54](#)
- interarea tunnels [RC-307](#)
- Inter-AS configurations
  - BGP [MPC-387](#)
  - interprovider VPN [MPC-387](#)
  - L2VPN quality of service [MPC-246](#)
  - supported [MPC-387](#)
- Inter-AS mode [MPC-233](#)
- interface
  - configuration status change [VFC-326](#)
  - line protocol change of state [VFC-325](#)
  - interface Bundle-Ether command [HC-209](#), [HC-214](#)
  - interface Bundle-POS command [HC-206](#)
  - interface command [HC-13](#), [IC-65](#), [RC-379](#)
  - interface configuration mode
    - cdp (interface) command [SMC-284](#)
    - interface (track) command [SMC-189](#)
    - line-protocol track command [SMC-190](#), [SMC-193](#), [SMC-196](#)
  - interface ID application [MPC-213](#)
  - interface loopback command [HC-428](#)
  - interface POS command [HC-222](#)
  - interface preconfigure command, [SMC-244](#), [SMC-246](#)
  - interface service-gre command [SC-149](#)
  - interface service-ipsec command [SC-148](#)
  - interface submode
    - See also* interface command
  - interface submode, ipv4 address command [MCC-59](#)

- interface submode, service-policy command [HC-408](#)
  - interface-inheritance disable command [MCC-23](#)
  - interfaces
    - Link Bundling [HC-199](#)
      - configuring [HC-208](#)
      - link switchover [HC-207](#)
      - prerequisites [HC-200, HC-201](#)
      - QoS [HC-206](#)
      - tunnel [HC-474](#)
  - interfaces, IP addresses [IC-187](#)
    - primary, IP address [IC-183](#)
  - interior routers [RC-205](#)
  - interprovider VPN, MPLS VPN [MPC-387](#)
  - introduction to CTM [1](#)
  - invert command [HC-371](#)
  - IP
    - addresses
      - multiple, assigning [IC-187](#)
      - primary [IC-183](#)
      - secondary [IC-187](#)
    - for ACL with NAT [VFC-112](#)
    - options, handling [VFC-279](#)
  - IP DSCP (differentiated services code point) value, when to use [QC-18](#)
  - IP fast reroute [RC-307](#)
  - IP Fast Reroute [RC-363](#)
    - loop-free alternate [RC-363](#)
  - IP header option error [VFC-325](#)
  - IP Network Security Protocol (IPSec)
    - definition [SC-80](#)
  - IP precedence
    - default [QC-17](#)
    - edge router function [QC-16](#)
    - low-latency queueing (LLQ) [QC-14](#)
    - overview [QC-16](#)
    - packet classification [QC-16](#)
    - QoS features supported [QC-17](#)
    - reset recommendation [QC-17](#)
    - ToS field [QC-16](#)
    - values (table) [QC-17](#)
    - when to use [QC-18](#)
    - WRED [QC-14](#)
- IP router, O-UNI client device [MPC-212](#)
- IP Service Level Agreements
  - <I\_Italic> See<Default Para Font> IP SLA [MNC-47](#)
- IP SLA
  - benefits [MNC-50](#)
  - control protocol [MNC-53](#)
  - improvements, list of [MNC-50](#)
  - introduction [MNC-47](#)
  - operation, types of [MNC-52](#)
  - performance measurement [MNC-51](#)
  - reaction [MNC-54](#)
  - responder
    - about [MNC-53](#)
    - enabling [MNC-59](#)
  - response time [MNC-53](#)
  - schedule [MNC-54](#)
  - technology [MNC-49](#)
  - threshold monitoring [MNC-54](#)
  - vrf [MNC-54](#)
- IP Time to Live (TTL) [MPC-58](#)
- IPARM conflict resolution [IC-194](#)
- IPCC (IP Control Channel)
  - configuring [MPC-142](#)
  - connectivity using O-UNI devices [MPC-213](#)
- IPS (Intelligent Protection Switching) [HC-401](#)
- IPSec
  - L2TPv3 [MPC-322](#)
  - mapping [MPC-322](#)
  - over L2TPv3 [MPC-322](#)
  - scenarios [MPC-322](#)
  - securing tunnels [MPC-322](#)
- IPSec (IP Network Security Protocol)
  - CAs
    - implementing with [SC-63](#)
    - implementing without [SC-63](#)

- checkpointing [SC-144](#)
- configuring
  - default path MTU (maximum transmission unit) [SC-192](#)
  - IPSec failure history table size [SC-182](#)
  - NAT transparency [SC-172](#)
- crypto access lists [SC-142](#)
  - cautions, creating [SC-183](#)
  - creating [SC-158](#)
  - purpose [SC-142](#)
- crypto profiles [SC-140](#)
  - applying to transport [SC-184](#)
  - applying to tunnel-ipsec interfaces [SC-183](#)
  - configuring static or dynamic [SC-161](#)
- dynamic crypto profile description [SC-141](#)
- IPSec VPN SPA
  - antireplay window [SC-145](#)
  - DF bit override description [SC-144](#)
  - NAT transparency [SC-145](#)
  - prefragmentation [SC-145](#)
  - restrictions [SC-139](#)
- IPSec-protected GRE virtual interfaces, configuring [SC-189](#)
- load balancing [SC-149](#)
- PFS (perfect forward secrecy) description [SC-144](#)
- prerequisites for implementation [SC-139](#)
- restrictions for implementation [SC-139](#)
- setting global lifetimes [SC-156](#)
- transform sets
  - defining [SC-160](#)
  - description [SC-142](#)
- virtual interfaces
  - configuring IPSec-protected GRE [SC-189](#)
- virtual interfaces (IPSec)
  - description [SC-148](#)
- IPSec support for SNMP (Simple Network Management Protocol) [SC-147](#)
- IPSec VPN SPA
  - description [SC-147](#)
  - displaying the SPA hardware type [SC-147](#), [SC-196](#)
  - DPD message [SC-93](#)
  - load balancing and high availability [SC-149](#)
  - SA idle timers [SC-145](#)
- IPSec\
  - ipsla operation command
    - ICMP Echo operation [MNC-78](#)
    - ICMP Path Echo operation [MNC-85](#)
    - ICMP Path Jitter operation [MNC-93](#)
    - UDP Echo operation [MNC-71](#)
    - UDP Jitter operation [MNC-63](#)
  - ipsla reaction operation command [MNC-54](#)
  - ipsla reaction trigger command [MNC-126](#)
  - ipsla responder command
    - description [MNC-59](#)
    - example [MNC-59](#)
  - ipsla schedule operation command
    - ICMP Echo operation [MNC-79](#)
    - ICMP Path Echo operation [MNC-86](#)
    - ICMP Path Jitter operation [MNC-94](#)
    - UDP Echo operation [MNC-72](#)
    - UDP Jitter operation [MNC-64](#)
- ipv4 address command [HC-13](#), [HC-206](#)
- IPv4 and IPv6 multicast routing, supported features [MCC-4](#)
- IPv4 and IPv6 protocol stacks, configuring [IC-189](#)
- IPv4 loopback interface, how to configure [MPC-360](#)
- IPv4 packet header format, figure [IC-171](#)
- IPv4 TNA address support [MPC-213](#)
- ipv4 unreachable command [HC-232](#)
- IPv4 virtual addresses [IC-184](#)
- IPv4-compatible IPv6 address [IC-169](#)
- IPv4-compatible IPv6 address format, figure [IC-169](#)
- IPv6
  - address argument [IC-185](#)
  - address formats [IC-166](#)
  - address types [IC-170](#)
  - assigning addresses to individual router interfaces [IC-185](#)
  - extension header format, figure [IC-173](#)

- ICMP packet header [IC-179](#)
- introduction (IPv6 for Cisco IOS XR) [IC-165](#)
- IS-IS support
  - multitopology [RC-301](#)
  - single-topology [RC-301](#)
- multicast address [IC-171](#)
- multicast address, figure [IC-170](#)
- multicast groups [IC-185](#)
- neighbor discovery [IC-175](#)
- neighbor redirect message [IC-178](#)
- neighbor redirect message, figure [IC-178](#)
- neighbor solicitation message, figure [IC-175](#)
- packet header [IC-171](#)
- packet header format, figure [IC-172](#)
- path MTU discovery [IC-174](#)
- prefix argument [IC-185](#)
- RFC 2460 [IC-165](#)
- RIB support [RC-362](#)
- router advertisement method, figure [IC-177](#)
- routing [RC-300](#)
- solicited-node multicast address format, figure [IC-171](#)
- IPv6 and IPv6 VPN provider edge transport over MPLS [RC-41](#)
- IPv6 provider edge multipath [RC-42](#)
- ISAKMP
  - See also* IKE[ISAKMP  
zzz]
- ISAKMP profile
  - description [SC-86](#)
  - locally sourced and destined traffic procedure [SC-121](#)
- IS-IS (ignore intermediate system-to-intermediate system)
  - overload bit setting
    - defining [MPC-107](#)
- IS-IS (Intermediate System-to-Intermediate System)
  - adjacencies, tuning [RC-336](#)
  - attached bit on an instance [RC-304](#)
  - authentication, configuring [RC-329](#)
  - configuration
    - grouped configuration [RC-298](#)
    - Level 1 or Level 2 routing [RC-308](#)
    - multitopology [RC-323](#)
    - restrictions [RC-297](#)
    - single topology [RC-311](#)
  - configuration, grouped [RC-298](#)
  - configuring authentication [RC-331](#)
  - customizing routes [RC-341](#)
  - default routes [RC-304](#)
  - description [RC-295](#)
  - enabling [RC-308](#)
  - enabling multicast-intact [RC-346](#)
  - functional overview [RC-298](#)
  - grouped configuration [RC-298](#)
  - IP fast reroute [RC-351](#)
- IS-IS (intermediate system-to-intermediate system)
  - IP Fast Reroute Loopfree Alternative [MPC-106](#)
- IS-IS (Intermediate System-to-Intermediate System)
  - IPv6 routing [RC-300](#)
  - Level 1 or Level 2 routing, configuration [RC-308](#)
  - LSP flooding
    - controlling [RC-323](#)
    - lifetime maximum [RC-301](#)
    - limiting [RC-300](#)
  - MPLS LDP IS-IS synchronization [RC-344](#)
  - MPLS TE
    - description [RC-303](#)
  - multi-instance IS-IS [RC-303](#)
  - multitopology, configuring [RC-323](#)
  - nonstop forwarding [RC-302](#)
    - configuring [RC-327](#)
  - overload bit
    - configuring [RC-304](#)
    - on router [RC-303](#)
  - policy attach points
    - default originate [RC-442](#)
    - inter-area-propagate [RC-443](#)
    - redistribute [RC-442](#)
  - priority for prefixes added to RIB [RC-349](#)

- restrictions, configuring [RC-297](#)
- set SPF interval [RC-339](#)
- single topology, configuring [RC-311](#)
- single topology, IPv6 support [RC-301](#)
- tagging IS-IS interface routes [RC-347](#)
- IS-IS address family submode [RC-299](#)
- IS-IS Overload Bit Avoidance [RC-304](#)
- ISP requirements, MPLS L2VPN [MPC-230](#)
- ispf command [RC-340](#)
- is-type command [RC-310](#)

## K

- keepalive command [HC-284, HC-300](#)
- keepalive timer
  - description [HC-286](#)
  - monitoring
    - POS link state [HC-285, HC-286](#)
    - SLARP packets [HC-285](#)
- key (key chain) command [SC-218](#)
- key chain command [SC-215](#)
- key chain management
  - configuring [SC-215, SC-225](#)
    - key identifiers [SC-217](#)
    - key string text [SC-219](#)
    - outbound traffic [SC-222](#)
  - description [SC-214](#)
  - end-time [SC-214](#)
  - key lifetime [SC-214](#)
  - key validation [SC-220](#)
  - start-time [SC-214](#)
- keychain command [RC-128](#)
- keychains [RC-41](#)
- keyring command [SC-121](#)
- keys, preshared using AAA server\
- key-string command [SC-220](#)

## L

- l2protocol command [HC-162, HC-491](#)
- L2TPv3
  - benefits [MPC-317](#)
  - control message hashing [MPC-328](#)
  - dynamic
    - configuring pseudowires [MPC-337](#)
    - sessions [MPC-318](#)
  - IPSec [MPC-322](#)
  - MPLS [MPC-317](#)
  - multipoint tunnel network [MPC-352](#)
  - operation [MPC-316](#)
  - peer authentication [MPC-318](#)
  - prerequisites [MPC-316](#)
  - services [MPC-317](#)
  - static sessions [MPC-318](#)
  - xconnect support [MPC-317](#)
- L2TPv3 tunnels [RC-42](#)
- l2transport command [HC-162](#)
- L2VPN
  - See Layer 2 VPN*
- L2VPN, QoS restrictions [MPC-246](#)
- label advertisement
  - configuring [MPC-21](#)
  - control [MPC-10](#)
  - control, LDP [MPC-10](#)
  - prerequisites [MPC-21](#)
- label bindings
  - configuring [MPC-4](#)
  - exchanging [MPC-4](#)
- label-allocation-mode per-ce command [RC-120](#)
- LACP (Link Aggregation Control Protocol) [HC-205](#)
- lawful intercept, implementing [SC-229](#)
- Layer 2 VPN
  - configuring
    - attachment circuit [HC-161](#)
    - Layer 2 protocol tunneling and data units [HC-162](#)

- Layer 2 transport mode [HC-162](#)
- overview [HC-147](#)
- Layer 3 and 4 application protocol inspection, configuring
  - policy actions [VFC-166](#)
- Layer 3 information (load-balancing) [IC-57](#)
- Layer 4 information (load-balancing) [IC-57](#)
- LCC serial number, displaying [SMC-224](#)
- LCP (Link Control Protocol) [HC-285](#), [HC-360](#)
- LDAP server
  - directory server overview [VFC-67](#)
  - port, setting [VFC-83](#)
  - timeout, setting [VFC-83](#)
  - virtualization attributes, defining [VFC-87](#), [VFC-90](#), [VFC-92](#)
- LDP discovery prerequisites
  - for active targeted hellos [MPC-17](#)
  - for passive targeted hellos [MPC-19](#)
  - over a link [MPC-16](#)
- LDP forwarding
  - configuring [MPC-26](#)
  - how to set up [MPC-5](#)
  - prerequisites [MPC-26](#)
- LDP label advertisement [MPC-10](#)
- LDP neighbors prerequisites [MPC-23](#)
- LDP NSF graceful restart prerequisites [MPC-28](#)
- LDP(label distribution protocol)
  - configuration examples [MPC-47](#)
  - control communication failure [MPC-8](#)
  - control messages [MPC-3](#)
  - control plane
    - failure [MPC-6](#)
  - Control Protocol (example) [MPC-3](#)
  - control state recovery [MPC-8](#)
  - discovery
    - active targeted hellos, configuration [MPC-17](#)
    - parameters, configuring [MPC-14](#)
    - passive targeted hellos, configuration [MPC-19](#)
  - discovery over a link
    - configuring [MPC-15](#)
    - prerequisites [MPC-16](#)
  - dynamic path setup [MPC-3](#)
  - failure recovery [MPC-9](#)
  - forwarding, configuring [MPC-26](#)
  - graceful restart
    - setting up LDP NSF [MPC-28](#)
  - hello discovery mechanism [MPC-3](#)
  - hop-by-hop [MPC-3](#)
  - IGP prefixes [MPC-4](#)
  - IGP synchronization [MPC-11](#)
  - implementation [MPC-13](#)
  - keepalive mechanism [MPC-4](#)
  - label advertisement [MPC-10](#)
  - local and remote label binding [MPC-4](#)
  - local label advertisement control [MPC-10](#)
  - local label allocation control [MPC-10](#)
  - LSPs, setting up [MPC-4](#)
  - neighbors
    - support for [MPC-3](#)
  - NSF services [MPC-6](#)
  - NSR [MPC-13](#)
  - peer control plane [MPC-8](#)
  - persistent forwarding [MPC-8](#)
  - prerequisites [MPC-2](#)
  - session protection [MPC-11](#)
- levels
  - overview [VFC-237](#)
  - severity listing [VFC-237](#)
- license
  - adding [SMC-114](#)
    - prerequisites [SMC-114](#)
    - restrictions [SMC-115](#)
  - backing up [SMC-121](#)
  - corrupted, restoring [SMC-121](#)
  - implicit with upgrade [SMC-116](#)
  - pools [SMC-113](#)
  - slots, allocated to [SMC-114](#)
  - tool on Cisco.com [SMC-115](#)
  - types [SMC-113](#)

- UDI, locked to [SMC-113](#)
- license add command [SMC-116](#)
- license backup command [SMC-121](#)
- license for user contexts [VFC-45](#), [VFC-50](#)
- license restore command [SMC-122](#)
- licensing
  - See* software entitlement
- life command
  - ICMP Echo operation [MNC-79](#)
  - ICMP Path Echo operation [MNC-86](#)
  - ICMP Path Jitter operation [MNC-94](#)
  - UDP Echo operation [MNC-72](#)
  - UDP Jitter operation [MNC-64](#)
- limit, MAC address
  - actions [MPC-271](#)
  - configuring [MPC-299](#)
- line cards
  - node ID components (XR 12000) [SMC-227](#)
  - removing [SMC-244](#)
  - removing and replacing [SMC-243](#)
- line command [SMC-203](#)
- line console command [SMC-206](#)
- line default command [SMC-206](#)
- line protocol, status change [VFC-325](#)
- line template command [SMC-207](#)
- line template configuration mode [SMC-203](#)
- link bundling, configuring VLAN bundles [HC-483](#)
- link local address format, figure [IC-169](#)
- link switchover [HC-207](#)
- link-local address [IC-169](#)
- link-state advertisement (LSA)
  - OSPFv2 [RC-208](#)
  - OSPFv3 [RC-208](#)
- list tracking configuration mode
  - delay command [SMC-195](#)
  - object command [SMC-195](#)
  - type list boolean command [SMC-195](#)
- LLQ (low-latency queueing)
  - See* queueing
- LMI [HC-171](#), [HC-179](#), [HC-180](#)
- lmi-n391dte command [HC-173](#)
- lmi-n392dce command [HC-172](#)
- lmi-n392dte command [HC-173](#)
- lmi-n393dce command [HC-172](#)
- lmi-n393dte command [HC-173](#)
- lmi-t392dce command [HC-172](#)
- LMP message exchange
  - disabling [MPC-155](#)
  - enabling [MPC-153](#)
- load balancing, HA data dropped [VFC-337](#)
- load-balancing
  - 7-tuple hash algorithm, configuring [IC-71](#)
  - functions [IC-56](#)
  - Layer 3 information [IC-57](#)
  - Layer 4 information [IC-57](#)
  - overview [IC-56](#)
  - verification, CEF exact route [IC-73](#)
- local and remote TE links
  - configuring numbered and unnumbered links [MPC-146](#)
- local database authentication [VFC-66](#)
- local label advertisement control, LDP [MPC-10](#)
- local label allocation control, LDP [MPC-10](#)
- local label binding [MPC-4](#)
- Local Management Interface (LMI) [HC-364](#)
- Local Packet Transport Services (LPTS)
  - components [IC-156](#)
  - policers
    - configuring [IC-156](#)
    - overview [IC-156](#)
- local reservable bandwidth, how to configure [MPC-149](#)
- local switching capability descriptors, how to configure [MPC-150](#)
- log adjacency changes command [RC-223](#)
- log files, logging levels [VFC-237](#)
- logging
  - levels [VFC-237](#)
  - message format [VFC-237](#)

overview [VFC-236](#)  
 severity levels [VFC-237](#)  
 variables [VFC-238](#)

logging buffered command [MNC-160](#), [MNC-166](#)  
 logging command [MNC-162](#)  
 logging console command [MNC-167](#)  
 logging correlation [MNC-5](#)  
     correlation rules, configuring [MNC-42](#)  
 logging correlation rules [MNC-5](#)  
     applying [MNC-11](#), [MNC-20](#), [MNC-22](#)  
     configuring [MNC-11](#)  
 logging correlator apply-rule command [MNC-20](#),  
[MNC-22](#)  
 logging correlator buffer  
     buffer settings, modifying [MNC-27](#)  
 logging correlator buffer-size command [MNC-28](#)  
 logging correlator rule command [MNC-12](#), [MNC-15](#),  
[MNC-17](#)  
 logging events buffer [MNC-5](#)  
     buffer settings, modifying [MNC-25](#)  
 logging events buffer-size command [MNC-26](#)  
 logging events level command [MNC-26](#)  
 logging events threshold command [MNC-26](#)  
 logging facility command [MNC-162](#)  
 logging history command [MNC-164](#)  
 logging history size command [MNC-164](#)  
 logging hostname prefix command [MNC-162](#)  
 logging monitor command [MNC-160](#)  
 logging out a user [VFC-59](#)  
 logging process [MNC-5](#)  
 logging source-interface command [MNC-163](#)  
 logging suppress duplicates command [MNC-171](#)  
 logging trap command [MNC-162](#)  
 log-neighbor-changes command [RC-185](#)  
 log-neighbor-warnings command [RC-185](#)  
 Longest Prefix Resolution [IC-195](#)  
 loopback command [HC-424](#)  
 loopback, naming convention [HC-227](#)  
 loop-free alternate [RC-307](#)

loose hop reoptimization [MPC-112](#)  
 lpts pifib hardware police command [IC-157](#)

LSP

- configuring [MPC-166](#)
- defining [MPC-3](#)
- hierarchy [MPC-166](#)
- MPLS-TE [MPC-102](#)
- with LDP [MPC-3](#)

LSP flooding

- controlling [RC-323](#)
- lifetime maximum [RC-301](#)
- limiting [RC-300](#)
- mesh group configuration [RC-301](#)
- on specific interfaces [RC-300](#)

LSP Path Discovery (LPD) [MNC-58](#)

lsp-check-interval command [RC-324](#)

lsp-gen-interval command [RC-324](#)

lsp-interval command [RC-325](#)

lsp-mtu command [RC-324](#)

lsp-password command [RC-330](#)

lsp-refresh-interval command [RC-324](#)

lsp-path command [MNC-90](#)

---

## M

MAC (Media Access Control) [IC-41](#)  
 MAC (message authentication code) [SC-223](#)  
     authentication option [SC-214](#)  
     cryptographic algorithm procedure [SC-223](#)  
 mac accounting command [HC-160](#)

MAC address

- aging [MPC-270](#)
- flooding [MPC-270](#)
- forwarding [MPC-270](#)
- limit actions [MPC-271](#)
- related parameters [MPC-269](#)
- source-based learning [MPC-270](#)
- withdrawal [MPC-271](#)

mac address command [HC-146](#), [HC-155](#)

- mac-accounting command [HC-146](#), [HC-147](#)
- Mac-in-Mac, Provide Backbone Bridging [MPC-235](#)
- MAM (maximum allocation model), constraint characteristics [MPC-104](#)
- management ethernet interface, configuring [HC-238](#)
- management plane
  - MPP feature [SC-242](#)
- management-plane command [SC-243](#)
- match access-group command [QC-25](#)
- match cos command [QC-25](#)
- match discard-class command [QC-25](#)
- match dscp command [QC-26](#)
- match identity command [SC-121](#)
- match mpls experimental topmost command [HC-405](#)
- match precedence command [HC-406](#), [QC-26](#)
- match protocol command [QC-26](#)
- match qos-group command [QC-26](#)
- match vlan command [QC-26](#)
- maximum paths command [RC-175](#)
- maximum-paths command [RC-123](#)
- maximum-prefix command [RC-175](#)
- max-lsp-lifetime command [RC-324](#)
- MBI (minimum boot image) [SMC-236](#)
- MD5 (Message Digest 5)
  - IKE policy parameter [SC-82](#)
- MD5 password authentication
  - See* multicast routing,MSDP (Multicast Source Discovery Protocol), MD5
- mdl string command [HC-453](#)
- mdl transmit command [HC-439](#), [HC-453](#)
- MDRR (modified deficit round robin), description [QC-74](#)
- MDRR/WRED [MPC-354](#)
- memory mapping failure [VFC-337](#)
- merged ACLs [VFC-96](#)
- mesh restoration, GMPLS [MPC-109](#)
- mesh-group command [RC-325](#)
- Message Digest 5 (MD5) authentication [RC-219](#)
- message logging
  - facility types
    - (table) [MNC-155](#)
    - syslog server [MNC-154](#)
- message statistics [RC-362](#)
- message URL http
  - [//www.cisco.com/en/US/docs/ios\\_xr\\_sw/iosxr\\_r3.8/common/configuration/guide/rm38.html](http://www.cisco.com/en/US/docs/ios_xr_sw/iosxr_r3.8/common/configuration/guide/rm38.html) [11](#)
  - [//www.cisco.com/en/US/docs/ios\\_xr\\_sw/iosxr\\_r3.8/system\\_management/command/reference/yr38term.html#wp1311395](http://www.cisco.com/en/US/docs/ios_xr_sw/iosxr_r3.8/system_management/command/reference/yr38term.html#wp1311395) [27](#)
- message-digest-key command [RC-232](#)
- messages
  - format [VFC-237](#)
  - severity levels [VFC-237](#)
  - understanding [VFC-237](#)
  - variables [VFC-238](#)
- metric-style wide command [RC-348](#)
- metro-zero-accept command [RC-381](#)
- MFI (MPLS forwarding infrastructure)
  - control plane [MPC-97](#)
  - data plane services [MPC-97](#)
  - LDP [MPC-97](#)
  - TE [MPC-97](#)
- MIB, description [SMC-295](#)
- mirror location command [SMC-103](#)
- mirror verify location command [SMC-103](#)
- mode command [HC-444](#)
- modified deficit round robin [MPC-354](#)
- modular service card
  - see* MSC [MNC-3](#)
- module number notation [SMC-226](#), [SMC-229](#)
- monitor map [HC-254](#)
- MPLS
  - IPv6 and IPv6 VPN provider edge transport [RC-363](#), [RC-468](#)
  - LDP IGP synchronization [RC-306](#)
- MPLS (Multiprotocol Label Switching), encapsulated packets [SC-149](#)
- MPLS forwarding forms [MPC-97](#)
- MPLS L2VPN
  - configuration examples [MPC-258](#)

- configuring [MPC-239](#)
- configuring QoS in VLAN mode [MPC-248](#)
- high availability [MPC-236](#)
- interface or connection, how to configure [MPC-239](#)
- ISP requirements [MPC-230](#)
- prerequisites [MPC-228](#)
- Quality of service (QoS) [MPC-235](#)
- MPLS Layer 3 VPN
  - automatic route distinguisher [MPC-385](#)
  - autonomous system [MPC-386](#)
  - components [MPC-381](#)
  - concepts [MPC-381](#)
  - customer edge router [MPC-381](#)
  - customer router [MPC-381](#)
  - defining [MPC-381](#)
  - distributed routing information [MPC-384](#)
  - FIB [MPC-380](#)
  - implementing [MPC-381](#)
  - major components [MPC-385](#)
  - MPLS forwarding [MPC-384](#)
  - PE router [MPC-381](#)
  - prerequisites [MPC-380](#)
  - provider router [MPC-381](#)
  - restrictions [MPC-380](#)
  - scalability [MPC-382](#)
  - security [MPC-382](#)
  - topology [MPC-381](#)
  - VPN routing information [MPC-384](#)
  - working [MPC-383](#)
- MPLS LDP IS-IS synchronization [RC-344](#)
- mpls ldp sync command [RC-345](#)
- MPLS LSP monitor (MPLSLM) [MNC-58](#)
- MPLS TE (Multiprotocol Label Switching traffic engineering), configuring for OSPFv2 [RC-251](#)
- MPLS TE forwarding adjacency [RC-307](#)
- MPLS TE interarea tunnels [RC-307](#)
- mpls traffic-eng area command [RC-253](#)
- mpls traffic-eng command [RC-334](#)
- mpls traffic-eng multicast-intact command [MCC-10](#)
- mpls traffic-eng router-id command [RC-252](#)
- mpls traffic-engineering multicast-intact command [RC-347](#)
- MPLS VPN
  - Inter-AS ASBRs [MPC-386](#)
  - major components [MPC-385](#)
- MPLS VPN carrier supporting carrier [RC-40](#)
- MPLS VPNs over IP tunnels
  - BGP SSA [MPC-353](#)
  - concepts [MPC-352](#)
  - feature overview [MPC-351](#)
  - multiple tunnel source address [MPC-355](#)
  - prerequisites [MPC-352](#)
  - QoS policy assignment [MPC-354](#)
  - quality of service [MPC-354](#)
  - restrictions [MPC-352](#)
  - task IDs [MPC-352](#)
  - tunnel types [MPC-353](#)
  - verifying [MPC-372](#)
  - VPN services [MPC-352](#)
- MPLS-TE
  - backbone [MPC-101](#)
  - benefits [MPC-101](#)
  - concepts [MPC-102](#)
  - engineering a backbone [MPC-102](#)
  - extensions [MPC-102](#)
  - fast reroute [MPC-106](#)
  - flooding
    - thresholds [MPC-105](#)
    - triggers [MPC-105](#)
  - implementation [MPC-120](#)
  - link management module [MPC-102](#)
  - overview [MPC-101](#)
  - path calculation module [MPC-102](#)
  - prerequisites [MPC-100](#)
  - topology
    - building [MPC-120](#)
  - tunnels
    - creating [MPC-123](#)

- prerequisites [MPC-123](#)
- with label switching forwarding [MPC-102](#)
- with RSVP [MPC-102](#)
- MPP (Management Plane Protection) [SMC-300](#)
  - benefits [SC-242](#)
  - control plane protection [SC-241](#)
  - description [SC-239](#), [SC-242](#)
  - device configuration [SC-243](#)
  - management interface
    - inband [SC-240](#)
    - out-of-band [SC-241](#)
  - management plane
    - description [SC-241](#)
  - peer-filtering option [SC-241](#)
- MQC (modular QoS command-line interface), description [QC-4](#)
- MQC (Modular Quality of Service), configuring with SRP [HC-404](#)
- MQC, quality of service [MPC-354](#)
- MSC [MNC-3](#)
- MS-CHAP authentication
  - disabling [HC-331](#)
  - enabling [HC-316](#), [HC-317](#)
  - password, configuring [HC-323](#)
  - ppp [HC-285](#), [HC-316](#), [HC-323](#), [HC-331](#)
  - viewing [HC-318](#)
- MSCs (modular services cards)
  - 40-Gbps throughput
    - license for [SMC-116](#)
    - prerequisites for enabling [SMC-117](#)
  - node ID components [SMC-226](#)
  - removing [SMC-244](#)
  - replacing [SMC-245](#)
- mtu command [HC-146](#), [HC-147](#), [HC-284](#), [HC-365](#)
- multi-area adjacency
  - configuring [RC-270](#)
  - interface attributes and limitations [RC-217](#)
  - overview [RC-217](#)
- multi-area-interface command [RC-271](#)
- multicast routing
  - Auto-RP (automatic route processing)
    - configuring [MCC-34](#)
    - description [MCC-13](#)
    - preventing messages (configuration example) [MCC-71](#)
    - RP-mapping agent, designating [MCC-13](#)
  - BSR (bootstrap router)
    - configuring
      - description [MCC-13](#)
  - Class D IP addresses [MCC-6](#)
  - DR (designated router)
    - failure
      - multiaccess segment [MCC-11](#)
      - purpose [MCC-11](#)
  - Generic Routing Encapsulation tunnels [MCC-15](#)
  - Internet Group Management Protocol (IGMP)
    - description [MCC-6](#)
    - host group addresses [MCC-6](#)
    - versions [MCC-6](#)
  - MFIB (Multicast Forwarding Information Base) [MCC-24](#)
  - MRIB (Multicast Routing Information Base) [MCC-24](#)
  - MSDP (Multicast Source Discovery Protocol)
    - Anycast RP [MCC-68](#)
    - default peering [MCC-58](#)
    - description [MCC-20](#)
    - inheriting commands (configuration example) [MCC-71](#)
    - logical RP [MCC-58](#)
    - MD5 password authentication, configuring
    - MD5 password authentication, description [MCC-24](#)
    - PIM-SM domains, interconnecting [MCC-58](#)
    - source information, controlling [MCC-61](#)
  - multicast domain [MCC-14](#)
  - Multicast Listener Discovery (MLD)
    - description [MCC-6](#)
  - Multicast Listener Discovery (MLD)

- versions [MCC-6](#)
- multicast NSF (multicast nonstop forwarding)
  - configuring [MCC-41](#)
  - converging and reconnecting [MCC-42](#)
  - high availability [MCC-20](#)
  - prerequisites [MCC-42](#)
  - timeout values [MCC-41](#)
- multicast protocol-specific submodes
  - description [MCC-21](#)
  - IGMP configuration submode (config-igmp) [MCC-22](#)
  - interface configuration inheritance [MCC-22](#)
  - MLD configuration submode (config-mld) [MCC-22](#)
  - MSDP configuration submode (config-msdp) [MCC-22](#)
  - PIM configuration submode (config-pim-ipv4) [MCC-22](#)
- multicast QoS (multicast quality of service)
  - configuring [MCC-64](#)
  - differentiated services [MCC-21](#)
  - overview [MCC-21](#)
- multitopology routing [MCC-16](#)
  - configuring [MCC-53](#)
- MVPN (multicast VPN)
  - BGP requirements
  - configuring IPv4 MVPN (example) [MCC-73](#)
  - configuring IPv6 MVPN (example) [MCC-83](#)
  - configuring MVPN [MCC-45](#)
  - IGMP VRF instance, specifying [MCC-51](#)
  - multicast distribution tree [MCC-15](#)
  - multicast VRF forwarding, enabling [MCC-46](#)
  - PIM VRF instance, specifying [MCC-49](#)
- MVPN extranet routing [MCC-16](#)
  - configuring [MCC-55](#)
  - configuring (example) [MCC-95](#)
  - information about [MCC-17](#)
  - RPF policies in an extranet [MCC-19](#)
  - supported protocols [MCC-56](#)
  - topologies [MCC-18](#)
  - unicast routes, importing [MCC-55](#)
- MVRF (VPN-specific multicast routing and forwarding database) [MCC-14](#), [MCC-17](#)
- PIM (Protocol Independent Multicast)
  - configuring
  - description [MCC-8](#)
  - leaf routers [MCC-10](#)
  - multicast-intact [MCC-10](#)
  - restrictions
  - shared tree, source tree, and shortest path tree [MCC-9](#)
- PIM-SM (PIM sparse mode)
  - configuring [MCC-25](#)
  - description [MCC-8](#)
  - RP [MCC-8](#)
- PIM-SSM (PIM source-specific multicast mapping )
  - (S,G) channels [MCC-9](#)
  - configuring [MCC-25](#)
  - datagrams, delivery [MCC-9](#)
  - description [MCC-5](#), [MCC-8](#)
  - IGMPv3 support [MCC-9](#)
  - legacy multicast deployments [MCC-28](#)
  - SSM mapping, restrictions [MCC-29](#)
  - SSM mapping, set of access lists, configuring [MCC-29](#)
  - SSM mapping, set of sources, configuring [MCC-30](#)
- rates per route
  - (example) [MCC-70](#)
  - calculating [MCC-40](#)
- RP (rendezvous point)
  - description [MCC-12](#)
  - manually configuring [MCC-12](#)
- RPF (Reverse Path Forwarding) [MCC-14](#)
- RSI (router space infrastructure) [MCC-16](#)
- static RP, configuring [MCC-32](#)
- multicast routing configuration mode interfaces, enabling and disabling [MCC-23](#)
- multicast rprotocol-specific submodes, IPv6 multicast routing (config-mcast-ipv6) [MCC-21](#)

multicast topology [RC-305](#)  
 multicast VPN [RC-43](#)  
 multicast-intact  
     OSPFv2 [RC-216](#)  
 multicast-routing command [MCC-27](#), [MCC-42](#),  
[MCC-47](#)  
 multicast-routing ipv4 command [MCC-21](#)  
 multicast-routing ipv6 command [MCC-21](#)  
 multicast-routing submode  
     interface all enable command [MCC-47](#)  
     mdt data command [MCC-48](#)  
     mdt default command [MCC-48](#)  
     nsf command [MCC-43](#)  
     vrf command [MCC-48](#)  
 multi-instance IS-IS [RC-303](#)  
 multilink command [HC-340](#)  
 multilink fragment-size command [HC-185](#), [HC-338](#)  
 multilink Frame Relay bundle interface [HC-185](#)  
 multilink interleave command [HC-340](#)  
 multiple action set  
     (examples) [QC-101](#)  
     conditional multiple action set  
         policer egress markings [QC-79](#)  
         policer ingress markings [QC-79](#)  
     description [QC-78](#)  
     unconditional multiple action set [QC-15](#)  
         egress markings [QC-15](#)  
         ingress markings [QC-15](#)  
 multiprotocol BGP [RC-33](#)  
 Multiprotocol Label Switching (MPLS)  
     LDP IS-IS synchronization [RC-344](#)  
 Multiprotocol Label Switching control processor  
 (MPLSCP) [HC-285](#), [HC-361](#)  
 Multiprotocol Label Switching traffic engineering (MPLS  
 TE), configuring for IS-IS [RC-333](#)  
 multitopology  
     (example) [RC-354](#)  
     configuring [RC-323](#)  
 multitopology routing [RC-316](#)  
 MVPN (multicast VPN)

*See* multicast routing, MVPN (multicast VPN)

## N

naming conventions  
     loopback [HC-227](#)  
     null interface [HC-227](#)  
     preconfigure [HC-350](#)  
 NAT  
     application protocol inspection support [VFC-120](#)  
     destination [VFC-294](#), [VFC-296](#), [VFC-307](#)  
     IPs in ACLs [VFC-112](#)  
     source [VFC-293](#), [VFC-294](#), [VFC-295](#), [VFC-297](#)  
 NAT transparency (IPSec) description [SC-145](#)  
 national bits command [HC-439](#), [HC-440](#), [HC-447](#),  
[HC-460](#)  
 NBMA networks [RC-206](#)  
 negotiation auto command [HC-147](#), [HC-155](#), [HC-158](#)  
 neighbor address family command [RC-299](#)  
 neighbor command (BFD) [HC-67](#)  
 neighbor command (OSPFv2, OSPFv3) [RC-229](#)  
 neighbor command, enabling RIP [RC-378](#)  
 neighbor, IPv6 [IC-175](#)  
 neighbors  
     adjacency (OSPFv2) [RC-207](#)  
     maximum limits (BGP) [RC-5](#)  
 net command [RC-309](#)  
 NetFlow  
     accounting for IPv4, destination-based [HC-259](#)  
     accounting for IPv4, destination-based [HC-274](#),  
[HC-278](#)  
     configuring [HC-260](#)  
     exporter map [HC-255](#)  
     flow exporter map configuration submode [HC-256](#)  
     flow exporter map version configuration  
     submode [HC-256](#)  
     flow monitor map configuration submode [HC-257](#)  
     monitor map [HC-254](#)  
     overview [HC-251](#), [HC-253](#)  
     prerequisites [HC-252](#)

- restrictions [HC-253](#)
- sampler map [HC-254](#)
- sampler map configuration submode [HC-257](#)
- network command [RC-228](#)
- Network Admin
  - description [VFC-49](#)
  - permissions [VFC-49](#)
- network connectivity [IC-121](#)
  - traceroute [IC-117](#)
- Network Control Protocols (NCPs) [HC-285](#), [HC-361](#)
- network stack IPv4 and IPv6 [IC-179](#)
- Network-Monitor
  - description [VFC-49](#)
  - permissions [VFC-49](#)
- next-hop-self command [RC-88](#)
- no interface command [HC-493](#)
- no logging events link-status command [MNC-172](#)
- no shutdown command
  - (warning) [HC-350](#)
- nodes
  - administrative shutdown [SMC-242](#)
  - reload, shutdown, power cycling [SMC-239](#)
  - router, displaying status [SMC-228](#)
  - SDR, displaying status [SMC-226](#)
- non-owner SDRs
  - adding nodes to [SMC-19](#)
  - default configuration [SMC-9](#)
  - description [SMC-4](#)
  - username and password, configuring (example) [SMC-35](#)
  - username and password, creating [SMC-29](#)
- nonstop forwarding [HC-207](#)
- Nonstop Routing (NSR)
  - configuring failover as recovery [IC-203](#)
  - function [IC-202](#)
- normalization parameters
  - Don't Fragment bit, handling [VFC-279](#)
  - ICMP security, disabling [VFC-277](#)
  - IP options, handling [VFC-279](#)
  - packet TTL setting [VFC-279](#)
- notes, usage in text [15](#)
- notification messages [VFC-340](#)
- notifications
  - error messages [VFC-217](#)
  - SNMP [VFC-217](#)
  - virtual context change [VFC-217](#)
- not-so-stubby area [RC-204](#)
- NSF (nonstop forwarding)
  - enabling graceful restart [MPC-66](#)
  - high-availability [MPC-56](#)
  - with RSVP [MPC-56](#)
- nsf command [RC-327](#)
- nsf interface-expires command [RC-328](#)
- nsf interface-timer command [RC-328](#)
- nsf interval command [RC-251](#)
- nsf lifetime command [MCC-43](#), [RC-328](#)
- NSR (non-stop routing)
  - graceful restart [MPC-13](#)
  - how to define [MPC-13](#)
  - LDP [MPC-13](#)
- nsr process-failures switchover command [IC-203](#)
- nssa command [RC-225](#)
- NTP
  - access groups, configuring [SMC-169](#)
  - associations
    - broadcast-based, configuring [SMC-162](#)
    - multicast-based, configuring [SMC-166](#)
    - poll-based, configuring [SMC-160](#)
  - authentication, configuring [SMC-171](#)
  - broadcast client, configuring router as [SMC-163](#)
  - broadcast server, configuring router as [SMC-164](#)
  - configuration tasks [SMC-159](#)
  - configuring system calendar to update from [SMC-176](#)
  - feature history [SMC-157](#)
  - implementing [SMC-157](#)
  - information about [SMC-158](#)
  - multicast client, configuring router as [SMC-166](#)

- multicast server, configuring router as [SMC-167](#)
  - peers and servers, configuring [SMC-160](#)
  - prerequisites for implementing [SMC-158](#)
  - server, configuring router as [SMC-175](#)
  - services, disabling on interface [SMC-172](#)
  - source IP address, configuring [SMC-173](#)
  - ntp command [SMC-173](#)
  - NTP configuration mode
    - access-group command [SMC-170](#)
    - authenticate command [SMC-172](#)
    - authentication-key command [SMC-172](#)
    - broadcastdelay command [SMC-165](#)
    - master command [SMC-176](#)
    - peer command [SMC-162](#)
    - server command [SMC-161](#)
    - source command [SMC-175](#)
    - trusted-key command [SMC-172](#)
    - update-calendar command [SMC-178](#)
  - NTP interface configuration mode
    - broadcast client command [SMC-164](#)
    - broadcast destination command [SMC-165](#)
    - broadcastdelay command [SMC-163](#)
    - multicast client command [SMC-167](#)
    - multicast destination command [SMC-168](#)
  - null interface
    - configuring [HC-228](#)
    - displaying [HC-229](#)
    - naming convention [HC-227](#)
  - null0 submode, ipv4 unreachable command [HC-232](#)
- 
- O**
- Oakley key exchange protocol
    - See also* IKE[Oakley key exchange protocol  
zzz]
  - oam ais-rdi command [HC-37](#)
  - oam retry command [HC-37](#)
  - oam-pvc manage command [HC-37](#)
  - object
    - association with contexts and domains [VFC-48](#)
    - description [VFC-48](#)
  - object groups, overview [VFC-97](#)
  - object tracking
    - configuration examples [SMC-196](#)
    - configuration tasks [SMC-186](#)
    - feature history [SMC-185](#)
    - information about [SMC-186](#)
    - interface up down state (example) [SMC-197](#)
    - interface up down state, tracking [SMC-186](#)
    - IP route reachability (example) [SMC-197](#)
    - IP route reachability, tracking [SMC-191](#)
    - line protocol state (example) [SMC-197](#)
    - line protocol state, tracking [SMC-188](#)
    - prerequisites [SMC-185](#)
    - tracked list (example) [SMC-198](#)
    - tracked list, creating [SMC-194](#)
  - OIR [MNC-5](#)
  - OIR (online insertion and removal)
    - line cards, MSCs and PLIMs [SMC-244](#)
    - switch fabric cards, 16-slot FCC [SMC-246](#)
    - switch fabric cards, 4-slot FCC [SMC-263](#)
    - switch fabric cards, 8-slot FCC [SMC-254](#)
  - operation, IP SLA types [MNC-52](#)
  - optical switches, GMPLS [MPC-107](#)
  - options command [HC-262](#)
  - order of ACL entries [VFC-96](#)
  - OSPF
    - configuring over IPCC [MPC-144](#)
    - queue tuning parameters [RC-220](#)
    - queue tuning parameters configuration [RC-281](#)
    - queue tuning parameters configuration (example) [RC-290](#)
  - ospf area configuration submode
    - dead-interval command [RC-228](#)
    - default-cost command [RC-225](#)
    - hello interval command [RC-228](#)
    - interface command [RC-222](#)
    - network command [RC-228](#)

- nssa command [RC-225](#)
- range command [RC-241](#)
- stub command [RC-225](#)
- ospf area submode
  - authentication message-digest command [RC-238](#)
  - virtual-link command [RC-238](#)
- ospf interface configuration submode
  - log adjacency changes [RC-223](#)
  - log adjacency changes command [RC-277](#)
  - neighbor command [RC-229](#)
- OSPFv2
  - multicast-intact [RC-305](#)
- OSPFv2 (Open Shortest Path First Version 2)
  - Cisco IOS XR OSPFv3 and OSPFv2 differences [RC-201](#)
  - CLI (command-line interface) inheritance [RC-202](#)
  - configuration
    - neighbors, nonbroadcast networks [RC-226](#)
    - sham-links [RC-258](#)
  - configuration and operation, verifying [RC-280](#)
  - default route [RC-207](#)
  - description [RC-197](#)
  - designate router (DR) [RC-207](#)
  - enabling [RC-221](#)
  - enabling multicast-intact [RC-263](#)
  - functional overview [RC-200](#)
  - instance and router ID [RC-205](#)
  - LSA
    - controlling the frequency [RC-234](#)
    - on an OSPF ABR [RC-240](#)
    - types [RC-208](#)
  - MD5 authentication [RC-206](#)
  - neighbors, adjacency [RC-207](#)
  - neighbors, nonbroadcast networks, configuring [RC-226](#)
  - nonstop forwarding [RC-249](#)
    - description [RC-213](#)
  - policy attach points
    - area-in [RC-439](#)
    - area-out [RC-439](#)
    - default originate [RC-438](#)
    - redistribute [RC-438](#)
  - route authentication methods
    - key rollover [RC-207](#)
    - MD5 [RC-206](#)
    - plain text [RC-206](#)
    - strategies [RC-206](#)
  - route redistribution
    - configuring [RC-242](#)
    - description [RC-212](#)
  - sham-link [RC-258](#)
  - Shortest Path First (SPF) throttling
    - description [RC-212](#)
  - Shortest Path First (SPF) throttling, configuring [RC-246](#)
  - SPF throttling, configuring [RC-246](#)
  - stub and not-so-stubby area types, configuring [RC-223](#)
  - supported OSPF network types
    - NBMA networks [RC-206](#)
    - point to point networks [RC-206](#)
  - virtual link
    - creating [RC-236](#)
    - transit area [RC-209](#)
- OSPFv3
  - graceful restart [RC-214](#)
- OSPFv3 (Open Shortest Path First Version 3)
  - Cisco IOS XR OSPFv3 and OSPFv2 differences [RC-201](#)
  - CLI inheritance [RC-202](#)
  - configuration
    - SPF throttling [RC-246](#)
  - configuration and operation, verifying [RC-280](#)
  - configuring
    - graceful restart [RC-255](#)
  - default route [RC-207](#)
  - description [RC-197](#)
  - enabling [RC-221](#)
  - functional overview [RC-200](#)

- instance and router ID [RC-205](#)
  - link-state advertisement (LSA) [RC-216](#)
  - load balancing [RC-217](#)
  - LSA
    - controlling frequency [RC-234](#)
    - on an OSPF ABR [RC-240](#)
    - types [RC-208](#)
  - neighbors, configuring nonbroadcast networks [RC-226](#)
  - policy attach points
    - default originate [RC-440](#)
    - redistribute [RC-438](#)
  - routes, redistribute [RC-242](#)
  - SPF (Shortest Path First) throttling configuring [RC-246](#)
  - stub and not-so-stubby area types, configuring [RC-223](#)
  - virtual link, description [RC-209](#)
  - ospfv3 area configuration submode
    - dead-interval command [RC-228](#)
    - default-cost command [RC-225](#)
    - hello interval command [RC-228](#)
    - interface command [RC-222](#)
    - network command [RC-228](#)
    - nssa command [RC-225](#)
    - range command [RC-241](#)
    - stub command [RC-225](#)
  - OSPFv3 Graceful Restart feature
    - adjacency [RC-215](#)
    - displaying information [RC-258](#)
  - ospfv3 interface configuration submode
    - log adjacency changes [RC-223](#)
    - neighbor command [RC-229](#)
  - OTN (optical transport network)
    - defining [MPC-211](#)
    - transport services [MPC-212](#)
  - O-UNI (Optical User Network Interface)
    - configuring a neighbor [MPC-223](#)
    - configuring a router ID [MPC-223](#)
    - configuring bandwidth [MPC-66](#)
    - configuring data-links [MPC-223](#)
    - connections
      - configuring [MPC-215](#)
      - establishing [MPC-213](#)
      - identifying [MPC-213](#)
      - tearing down [MPC-219](#)
    - database requirement [MPC-212](#)
    - N node [MPC-212](#)
    - prerequisites
      - general [MPC-212](#)
      - how to set up a connection [MPC-215](#)
    - RSVP messages [MPC-212](#)
    - standards [MPC-211](#)
    - verifying [MPC-220](#)
  - O-UNI client devices
    - ADMs [MPC-212](#)
    - IP routers [MPC-212](#)
  - outbound ACLs [VFC-111](#)
  - out-of-band command [SC-246](#)
  - out-of-band management interface, MPP
    - definition [SC-241](#)
  - output locations, SNMP NMS [VFC-241](#)
  - output-delay command [RC-380](#)
  - overhead command [HC-424](#)
  - overload bit
    - configuration [RC-304](#)
    - on router [RC-303](#)
  - owner SDRs [SMC-3](#)
- 
- P**
- P2MDRR (packet-by-packet MDRR), description [QC-74](#)
  - packet buffer, copying capture buffer [VFC-251](#)
  - packet count command
    - ICMP Path Jitter operation [MNC-94](#)
    - UDP Jitter operation [MNC-63](#)
  - packet header fields, IPv6 [IC-172](#)
  - packet interval command

- ICMP Path Jitter operation [MNC-94](#)
- UDP Jitter operation [MNC-64](#)
- packet routes, checking [IC-121](#)
- packet TTL setting [VFC-279](#)
- packet validation
  - mechanism [MPC-354](#)
  - MPLS VPNs over IP tunnels [MPC-354](#)
- pairing command [SMC-14](#)
- PAP authentication
  - defined [HC-315](#)
  - disabling [HC-328](#)
  - enabling [HC-316](#), [HC-317](#), [HC-319](#), [HC-320](#)
  - ppp [HC-286](#), [HC-319](#)
  - refusing [HC-328](#)
  - viewing [HC-318](#)
- partitioning network, QoS packet marking [QC-14](#)
- passive targeted hellos, configuring [MPC-19](#)
- passive-interface command [RC-383](#)
- password command [RC-115](#)
- path calculation module, MPLS-TE [MPC-102](#)
- path command [HC-425](#), [HC-432](#)
- path discover command [MNC-58](#)
- path protection, GMPLS
  - forced reversion procedure [MPC-171](#)
  - LSP [MPC-168](#)
- path scrambling command [HC-429](#)
- PCE extensions to OSPFv2 [RC-219](#)
- PE router
  - address space [MPC-353](#)
  - MPLS Layer 3 VPN [MPC-381](#)
- PE-CE protocol
  - configuring [MPC-460](#)
- peer
  - alternate pings [VFC-334](#), [VFC-335](#)
  - communication failure [VFC-330](#)
  - heartbeat interval mismatch [VFC-333](#)
  - heartbeats unidirectional [VFC-333](#)
  - incompatibility [VFC-329](#)
  - reachable [VFC-332](#), [VFC-335](#)
  - receive error [VFC-336](#)
  - replication failure [VFC-328](#), [VFC-330](#)
  - replication in process [VFC-333](#)
  - state change [VFC-336](#)
  - unreachable [VFC-327](#), [VFC-328](#), [VFC-336](#)
- peer-filtering option
  - definition [SC-241](#)
  - peer keyword
    - inband interface [SC-244](#)
    - out-of-band interface [SC-247](#)
- per VRF (VPN routing and forwarding) AAA
  - procedure [SC-30](#)
  - server-private command [SC-31](#)
  - supported VSAs [SC-30](#)
- Performance Management (PM)
  - benefits [MNC-200](#)
  - functional overview [MNC-199](#)
  - PM entity instance monitoring
    - enabling [MNC-223](#)
    - overview [MNC-205](#)
  - PM statistics collection templates
    - creating [MNC-201](#), [MNC-218](#), [MNC-228](#)
    - description [MNC-201](#)
    - disabling [MNC-202](#), [MNC-220](#)
    - enabling [MNC-202](#), [MNC-220](#), [MNC-228](#)
    - TFTP server, configuring [MNC-217](#)
  - PM statistics collection, overview [MNC-200](#)
  - PM Statistics Collector, description [MNC-199](#)
  - PM Statistics Server, description [MNC-199](#)
  - PM threshold monitoring templates
    - creating [MNC-208](#), [MNC-223](#), [MNC-224](#)
    - disabling [MNC-216](#), [MNC-226](#)
    - enabling [MNC-216](#), [MNC-226](#), [MNC-228](#)
  - PM threshold monitoring, overview [MNC-207](#)
- performance measurement, IP SLA [MNC-51](#)
- performance-mgmt apply monitor command [MNC-223](#)
- performance-mgmt apply statistics command [MNC-221](#)
- performance-mgmt apply thresholds
  - command [MNC-226](#)

- performance-mgmt resources tftp-server [MNC-217](#)
- performance-mgmt statistics command [MNC-219](#)
- performance-mgmt thresholds command [MNC-225](#)
- persistent interface index, configuring [MPC-152](#)
- physical terminals
  - console line template
    - description [SMC-202](#)
    - modifying [SMC-205](#)
  - default line template
    - description [SMC-202](#)
    - modifying [SMC-205](#)
  - line template configuration mode, description [SMC-203](#)
  - line template guidelines [SMC-204](#)
- PIE (package installation envelope) files
  - See also* software packages
  - about
  - copying before installing, about [SMC-47](#)
  - filenames and versions [SMC-44](#)
  - for bug fixes
- PIM
  - See* multicast routing, PIM (Protocol Independent Multicast)
- ping
  - See* host services and applications
  - host services and applications [IC-121](#)
  - tool [IC-117](#)
- ping command [HC-23](#), [IC-121](#)
- placement memory command [SMC-146](#)
- placement program command [SMC-147](#), [SMC-148](#), [SMC-150](#), [SMC-151](#)
- placement program configuration mode
  - affinity location-set command [SMC-147](#)
  - affinity location-type command [SMC-149](#)
  - affinity program command [SMC-150](#)
  - affinity self command [SMC-152](#)
- placement reoptimize command [SMC-145](#)
  - about [SMC-142](#)
- PLIMs (physical layer interface modules)
  - node ID components [SMC-226](#)
  - removing [SMC-244](#)
- point-to-point networks [RC-206](#)
- Point-to-Point protocol
  - See* PPP
- poison-reverse command [RC-381](#)
- police command [HC-406](#), [QC-94](#)
- policers and shapers, description [QC-74](#)
- policy map
  - actions, defining [VFC-166](#)
  - Layer 7 HTTP deep packet inspection, inline match commands [VFC-142](#)
  - overview in application protocol inspection process [VFC-122](#)
- policy map class submode
  - bandwidth command [QC-85](#)
  - police command [QC-94](#)
  - set cos command [QC-34](#)
  - set discard-class command [QC-34](#)
  - set dscp command [QC-33](#)
  - set precedence command [QC-33](#)
  - set qos-group command [QC-37](#)
  - set srp-priority command [QC-34](#)
- policy map police submode
  - conform-action command [QC-95](#)
  - exceed-action command [QC-89](#)
- policy map submode
  - class command [HC-406](#), [HC-407](#), [QC-131](#)
  - police command [HC-406](#)
  - policy-map command [HC-406](#), [QC-29](#)
  - priority command [HC-406](#), [HC-407](#)
  - set cos command [HC-406](#), [HC-407](#)
- policy, modifying
  - attached [RC-450](#)
  - nonattached [RC-451](#)
- Policy-Based Tunnel Selection (PBTS)
  - configuring [MPC-191](#)
  - defining [MPC-115](#)
  - dynamic tunnel selection [MPC-116](#)
  - figure, implementation [MPC-116](#)

- functions [MPC-116](#)
- policy-map command [HC-406, QC-29](#)
- port for LDAP server [VFC-83](#)
- port mode, MPLS L2VPN [MPC-247](#)
- POS (Packet-over-SONET)
  - See* POS interface
- pos crc command [HC-99](#)
- POS interface
  - bringing up [HC-289](#)
  - configuring
    - CRC value [HC-99, HC-284, HC-293](#)
    - encapsulation type [HC-284](#)
    - interface encapsulation [HC-98, HC-293, HC-339](#)
    - keepalive timer [HC-284, HC-299, HC-300, HC-338](#)
    - MTU [HC-99, HC-284, HC-293, HC-307](#)
    - optional parameters [HC-292](#)
    - PPP authentication [HC-286](#)
  - default settings
    - CRC [HC-284](#)
    - encapsulation [HC-284](#)
    - keepalive [HC-284](#)
    - mtu [HC-284](#)
  - Frame Relay encapsulation [HC-281](#)
  - HDLC encapsulation
    - description
    - overview [HC-284](#)
  - interface configuration mode
    - interface command [HC-338](#)
    - interface multilink command [HC-338, HC-340](#)
    - interface pos command [HC-98, HC-290, HC-293](#)
  - PPP encapsulation
    - description, [HC-281](#)
    - overview [HC-285](#)
  - subinterfaces, creating with PVCs [HC-294](#)
- PPP
  - CHAP
    - authentication [HC-315](#)
    - enabling [HC-316, HC-317](#)
    - password, configuring [HC-321, HC-322](#)
    - refusing [HC-330](#)
    - viewing [HC-318](#)
  - default configuration, modifying [HC-324, HC-326](#)
  - interfaces, displaying [HC-327](#)
  - MS-CHAP
    - disabling [HC-331](#)
    - disabling [HC-331](#)
    - enabling [HC-316, HC-317](#)
    - password, configuring [HC-323](#)
    - ppp [HC-316, HC-361](#)
    - viewing [HC-318](#)
  - overview [HC-314](#)
  - PAP
    - authentication [HC-319, HC-361](#)
    - disabling [HC-328](#)
    - enabling [HC-316, HC-317, HC-319, HC-320](#)
    - refusing [HC-328](#)
    - viewing [HC-318](#)
  - POS configuration example [HC-341](#)
  - POS interface, [HC-285](#)
  - prerequisites [HC-314](#)
  - serial configuration example [HC-342](#)
  - serial interface [HC-360](#)
  - ppp authentication command [HC-286, HC-315, HC-317, HC-361](#)
  - ppp chap password command [HC-322](#)
  - ppp chap refuse command [HC-330](#)
  - ppp max-bad-auth command [HC-326](#)
  - ppp max-configure command [HC-326](#)
  - ppp max-failure command [HC-326](#)
  - ppp max-terminate command [HC-326](#)
  - ppp ms-chap password command [HC-323](#)
  - ppp ms-chap refuse command [HC-331](#)
  - ppp multilink minimum-active links command [HC-340](#)
  - ppp pap refuse command [HC-328](#)
  - ppp pap sent-username command [HC-319, HC-320](#)
  - ppp timeout authentication command [HC-327](#)

- ppp timeout retry command [HC-327](#)
- preconfiguration
  - advantages [HC-349](#)
  - directory [HC-347](#)
  - naming conventions [HC-350](#)
  - restriction to physical interface [HC-347](#)
- prefix filtering [MPC-59](#)
- prefix list [IC-10](#)
- prefix prioritization
  - OSPFv2 SPF [IC-57](#)
- prefragmentation
  - dependencies [SC-146](#)
  - description [SC-145](#)
  - disabling
    - service-gre interfaces [SC-178](#)
    - service-ipsec interfaces [SC-177](#)
- prerequisites
  - CDP [SMC-282](#)
  - configuring SDRs [SMC-2](#)
  - configuring terminals [SMC-202](#)
  - enabling 10 Gbps throughput on Cisco XR 12000 SIP [SMC-119](#)
  - for adding standby PRP [SMC-276](#)
  - for enabling 40-Gbps throughput on MSC [SMC-117](#)
  - for managing router hardware [SMC-216](#)
  - for removing and replacing SFCs (16-slot CRS-1) [SMC-246](#)
  - for removing and replacing SFCs (4-slot CRS-1) [SMC-263](#)
  - for removing and replacing SFCs (8-slot CRS-1) [SMC-255](#)
  - for removing and replacing SFCs and CSCs (XR-12000) [SMC-270](#)
  - NTP configuration [SMC-158](#)
  - object tracking [SMC-185](#)
  - process placement [SMC-140](#)
  - restoring license [SMC-121](#)
  - SNMP [SMC-294](#)
  - software entitlement [SMC-112](#)
- preshared key
  - RADIUS, setting for [VFC-73](#)
  - TACACS+, setting for [VFC-78](#)
- preshared keys
  - using the AAA Server [SC-87](#)
- Prestandard DS-TE mode [MPC-103](#)
- priority command [HC-406](#), [HC-407](#)
- process placement
  - affinities [SMC-142](#)
  - affinity hierarchy [SMC-144](#)
  - configuration examples [SMC-152](#)
  - configuration tasks [SMC-144](#)
  - default placement policy [SMC-141](#)
  - feature history [SMC-139](#)
  - guidelines [SMC-142](#)
  - location type affinity, how to create [SMC-148](#)
  - memory use thresholds, how to set [SMC-145](#)
  - memory use, based on [SMC-143](#)
  - prerequisites [SMC-140](#)
  - program affinity, how to create [SMC-149](#)
  - reoptimize, how to [SMC-145](#)
  - restrictions [SMC-140](#)
  - self affinity, how to create [SMC-151](#)
  - when to change [SMC-141](#)
- processing, ACL compilation process out of memory [VFC-318](#)
- profile command [HC-477](#)
- protection and restoration, GMPLS
  - end-to-end recovery [MPC-109](#)
  - requirements [MPC-110](#)
  - shared mesh [MPC-109](#)
  - span protection [MPC-109](#)
- protocol-based CLI [MPC-102](#)
- protocols
  - downloading, supported [SMC-59](#)
- Provide Backbone Bridging protocol, Mac-in-Mac [MPC-235](#)
- PRP
  - hardware requirements [SMC-276](#)
  - redundancy slot pairs [SMC-276](#)

software requirements [SMC-276](#)

standby [SMC-276](#)

## PVC

ATM interface [HC-14](#)

ATM subinterface [HC-13](#), [HC-42](#)

POS subinterface [HC-294](#), [HC-296](#)

VP tunnel [HC-21](#)

pvc command [HC-14](#)

PW (pseudowire)

configuring a bridge domain [MPC-274](#)

configuring for L2TPv3 [MPC-337](#)

congestion management [QC-3](#)

packet classification [QC-3](#)

QoS Services on mVPN

configuring conditional markings [QC-44](#)

configuring unconditional markings [QC-46](#)

description [QC-44](#)

example [QC-67](#)

queueing

low-latency queuing (LLQ) [QC-75](#)

quantum size [QC-74](#)

scheduling mechanism [QC-74](#)

strict priority [QC-75](#)

## Q

QinAny mode [MPC-234](#)

QinQ mode [MPC-234](#)

QoS (quality of service)

assigning policies for MPLS VPNs [MPC-354](#)

QoS (Quality of Service)

benefits [QC-2](#)

characteristics [QC-1](#)

QoS (quality of service)

configuring L2VPN [MPC-247](#)

configuring port modes [MPC-247](#)

QoS (Quality of Service)

congestion mechanisms, policers and shapers [QC-74](#)

features

class-based packet marking [QC-13](#)

traffic policing [QC-3](#)

traffic shaping [QC-3](#)

QoS (quality of service)

MPLS L2VPN [MPC-235](#)

MPLS VPNs over IP tunnels [MPC-354](#)

MQC [MPC-354](#)

QoS (Quality of Service)

techniques

classification [QC-11](#)

congestion avoidance [QC-4](#)

## R

rack/slot/module notation [SMC-226](#), [SMC-229](#)

RADIUS

configuring

dead-server detection [SC-28](#)

UDP ports [SC-24](#)

operation [SC-17](#)

RADIUS server

dead-time setting [VFC-73](#)

global preshared key setting [VFC-73](#)

number of retransmissions, setting [VFC-74](#)

server accounting settings, configuring [VFC-89](#)

server overview [VFC-66](#)

timeout setting [VFC-74](#)

radius-server dead-criteria time command [SC-29](#)

radius-server dead-criteria tries command [SC-29](#)

radius-server deadtime command [SC-28](#)

random command [HC-263](#)

range command [RC-241](#)

RAs (registration authorities)

*See* CAs[RAs

zzz]

RAs[CAs (certification authorities)

zzz]

RAW protocol [IC-203](#)

- RBAC (Role-Based Access Control)
  - description [VFC-48](#)
  - predefined user roles [VFC-49](#)
- rcp [SMC-59](#)
- rcp (remote copy protocol)
  - definition [IC-119](#)
  - troubleshooting tips [IC-126](#)
- rcp client- username command [IC-125](#)
- rcp client-source interface command [IC-126](#)
- rcp copy command [IC-119](#)
- rd command [RC-103](#)
- RDM (russian doll model) bandwidth constraint model [MPC-103](#)
- react command
  - connection-loss keyword [MNC-110](#)
  - jitter-average keyword [MNC-111](#)
  - packet-loss keyword [MNC-113](#)
  - rtt keyword [MNC-114](#)
  - timeout keyword [MNC-116](#)
  - verify-error keyword [MNC-117](#)
- Reaction, IP SLA [MNC-54](#)
- receive version command [RC-379](#)
- record ipv4 command [HC-266](#), [HC-275](#)
- recurring command
  - ICMP Echo operation [MNC-79](#)
  - ICMP Path Echo operation [MNC-86](#)
  - ICMP Path Jitter operation [MNC-95](#)
  - UDP Echo operation [MNC-72](#)
  - UDP Jitter operation [MNC-64](#)
- redistribute command
  - router eigrp address family configuration submode [RC-181](#)
- redistribute isis command [RC-342](#)
- redistribute maximum-prefix command [RC-175](#)
- redundancy
  - automatic switchover [SMC-237](#)
  - commands [SMC-237](#)
  - during RP reload [SMC-237](#)
  - establishing (CRS), about [SMC-234](#)
  - establishing (XR 12000 series), about [SMC-235](#)
  - introduction [SMC-234](#)
  - manual switchover between RPs [SMC-238](#)
  - primary RP [SMC-236](#)
  - PRP slot pairs [SMC-276](#)
- redundancy
  - See HA [VFC-327](#)
- redundancy
  - standby RP
    - communicating with [SMC-239](#)
    - role of [SMC-236](#)
- redundancy switchover command [SMC-237](#), [SMC-238](#)
- reload
  - reasons [VFC-318](#)
  - record [VFC-318](#)
- reload command [SMC-237](#), [SMC-240](#)
- Remote Copy Protocol (rcp) [SMC-59](#)
- remote label binding [MPC-4](#)
- remote server
  - copying files from [VFC-252](#)
  - copying files to [VFC-251](#)
- remote-as command
  - peer submode, remote-as command [MCC-60](#)
- remote-as command (BFD) [HC-67](#)
- resource class
  - customized [VFC-49](#)
  - default [VFC-49](#)
  - description [VFC-49](#)
- resources
  - customizing for contexts [VFC-49](#)
  - list of managed [VFC-56](#)
  - usage, monitoring [VFC-59](#)
- responder, IP SLA
  - and IP SLA Control Protocol [MNC-53](#)
  - enabling [MNC-59](#)
  - ipsla responder command [MNC-59](#)
  - type udp ipv4 address command [MNC-61](#)
- response time, IP SLA [MNC-53](#)
- restrictions

- for process placement [SMC-140](#)
- retransmit-interval command [RC-325](#)
- retransmit-throttle-interval command [RC-325](#)
- reverse-route command [SC-162](#), [SC-180](#)
- RFC
  - 1027 [IC-44](#)
  - 1195, OSI IS-IS usage [IC-191](#)
  - 2373 [IC-185](#)
  - 826 [IC-44](#)
  - 959 [IC-119](#)
- RFC 1142, OSI IS-IS Intra-domain Routing Protocol [RC-358](#)
- RFC 1195, Use of OSI IS-IS for Routing in TCP/IP and Dual Environments [RC-358](#)
- RFC 1587, Not So Stubby Area (NSSA) [RC-292](#)
- RFC 1700, Assigned Numbers [RC-153](#)
- RFC 1771 [RC-461](#)
- RFC 1793, OSPF over demand circuit [RC-292](#)
- RFC 1997, BGP Communities Attribute [RC-153](#)
- RFC 2236, extensions for IGMP [MCC-7](#)
- RFC 2328 [RC-292](#)
- RFC 2328, OSPF Version 2 [RC-201](#)
- RFC 2370, LSA [RC-292](#)
- RFC 2385, Protection of BGP Sessions via the TCP MD5 Signature Option [RC-153](#)
- RFC 2409, <I\_Italic>The Internet Key Exchange [SC-79](#)
- RFC 2439, BGP Route Flap Damping [RC-153](#)
- RFC 2453 [RC-391](#)
- RFC 2453, RIP Version 2 [RC-375](#)
- RFC 2545, Use of BGP-4 Multiprotocol Extensions for IPv6 Inter-Domain Routing [RC-153](#)
- RFC 2740 OSPFv3 [RC-201](#)
- RFC 2740, OSPFv3 [RC-292](#)
- RFC 2763, Dynamic Hostname Exchange Mechanism for IS-IS [RC-358](#)
- RFC 2796, BGP Route Reflection - An Alternative to Full Mesh IBGP [RC-153](#)
- RFC 2858, Multiprotocol Extensions for BGP-4 [RC-153](#)
- RFC 2918, Route Refresh Capability for BGP-4 [RC-153](#)
- RFC 2966, Domain-wide Prefix Distribution with Two-Level IS-IS [RC-358](#)
- RFC 2973, IS-IS Mesh Groups [RC-358](#)
- RFC 3065, Autonomous System Confederations for BGP [RC-153](#)
- RFC 3137, Router Advertisement [RC-292](#)
- RFC 3277, IS-IS Transient Blackhole Avoidance [RC-358](#)
- RFC 3373, Three-Way Handshake for IS-IS Point-to-Point Adjacencies [RC-358](#)
- RFC 3392, Capabilities Advertisement with BGP-4 [RC-153](#)
- RFC 3411, An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks [SMC-316](#)
- RFC 3412, Message Processing and Dispatching for the Simple Network Management Protocol (SNMP) [SMC-316](#)
- RFC 3413, Simple Network Management Protocol (SNMP) Applications [SMC-316](#)
- RFC 3414, User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3) [SMC-316](#)
- RFC 3415, View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP) [SMC-316](#)
- RFC 3416, Version 2 of the Protocol Operations for the Simple Network Management Protocol (SNMP) [SMC-316](#)
- RFC 3417, Transport Mappings for the Simple Network Management Protocol (SNMP) [SMC-316](#)
- RFC 3418, Management Information Base (MIB) for the Simple Network Management Protocol (SNMP) [SMC-316](#)
- RFC 3509 [RC-292](#)
- RFC 3567, IS-IS Cryptographic Authentication [RC-358](#)
- RFC 3623, OSPFv3 [RC-292](#)
- RFC 3682
  - Generalized TTL Security Mechanism (GTSM), TTL value [RC-219](#)
- RFC 4136, OSPF [RC-292](#)
- RFC 4271 [RC-153](#)
- RFC 4360 [RC-461](#)
- RFC 4364, BGP/MPLS IP Virtual Private Networks (VPNs) [RC-153](#)

- RFC 4444, IS-IS Management Information Base [RC-358](#)
- RFC 4576, L3VPN [RC-292](#)
- RFC 4577, Sham Link [RC-292](#)
- RFC 4601, motivation for and architecture of PIM [MCC-8](#)
- RFC 4724, Graceful Restart Mechanisms for BGP [RC-153](#)
- RFC 4750, OSPF Version 2 [RC-292](#)
- RFC 4811, OSPF [RC-292](#)
- RFC 4812, OSPF [RC-292](#)
- RFC 4813, OSPF [RC-292](#)
- RFC 791, Internet Protocol [QC-16](#)
- RIB
  - quarantining [RC-363](#)
  - statistics [RC-362](#)
- RIB (Routing Information Base)
  - administrative distance [RC-361](#)
  - data structures in BGP and other protocols [RC-361](#)
  - deploying [RC-364](#)
  - description [RC-359](#)
  - examples [RC-367](#)
  - functional overview [RC-361](#)
  - IPv4 and IPv6 support [RC-362](#)
  - monitoring [RC-364](#)
  - prerequisites [RC-360](#)
- rings (outer and inner) [HC-390](#)
- RIP (Routing Information Protocol )
  - global-inbound, policy attach points [RC-448](#)
- RIP (Routing Information Protocol)
  - administrative distance [RC-376](#)
  - bandwidth [RC-382](#)
  - benefits [RC-375](#)
  - CIDR [RC-374](#)
  - control or prevent routing updates [RC-382](#)
  - filter network updates [RC-382](#)
  - hop count [RC-374](#)
  - metrics [RC-374](#)
  - policy attach points
    - default-information originate [RC-447](#)
    - global-inbound [RC-448](#)
    - interface-inbound [RC-448](#)
    - interface-outbound [RC-448](#)
    - redistribute [RC-448](#)
  - redistribution [RC-376](#)
  - route policy creation [RC-384](#)
  - route timers [RC-375](#)
  - routing loops [RC-382](#)
  - routing policy options [RC-377](#)
  - split horizon, enabling IP [RC-375](#)
  - VLSMs (variable-length subnet masks) [RC-374](#)
  - WAN link [RC-382](#)
- RIP v2 supported features [RC-374](#)
- role, predefined [VFC-49](#)
- rolling back
  - about [SMC-49](#)
  - procedure [SMC-87](#)
- ROM Monitor mode [SMC-41](#)
- rommonrevision test [HC-140](#)
- root message [MNC-6](#)
- route dampening [RC-35](#)
- route filtering, prefix list [IC-10](#)
- route policy command [IC-63](#)
- route policy submode
  - <I\_Italic>See<Default Para Font> route-policy command [RC-49](#)
  - end-policy command [RC-49](#)
- route processor management ethernet forwarding [IC-56](#)
- route redistribution (OSPFv2, OSPFv3) [RC-212](#)
- route reflectors [RC-36](#)
- route tags [RC-305](#)
- route tracking configuration mode
  - route Ipv4 command [SMC-192](#)
  - vrf command [SMC-192](#)
- route-policy (BGP) command
  - bgp neighbor address family submode [RC-80](#)
- route-policy command
  - creating and attaching to EIGRP Process [RC-176](#)
  - defining a route-policy [RC-454](#)

- router rip interface configuration submode [RC-384](#)
- route-policy configuration submode
  - set eigrp-metric command [RC-176](#)
  - set rip-metric command [RC-385](#)
- route-policy pass-all command [RC-21](#)
- router
  - node IDs and status, displaying [SMC-228](#)
- router advertisement message [IC-177](#)
- router bgp address family command [IC-64](#)
- router bgp address family submode
  - See also* router bgp address family command
- router bgp command [HC-67](#), [IC-64](#)
- router bgp table policy command [IC-64](#)
- router eigrp address family configuration submode
  - default-metric command [RC-170](#)
  - distance command [RC-170](#)
  - log-neighbor-changes command [RC-185](#)
  - log-neighbor-warnings command [RC-185](#)
  - maximum paths command [RC-175](#)
  - maximum-prefix command [RC-175](#)
  - redistribute command [RC-183](#)
  - redistribute maximum-prefix command [RC-175](#)
  - stub command [RC-179](#)
  - timers nsf route-hold command [RC-175](#)
- router eigrp command [RC-170](#)
- router eigrp configuration mode, route-policy command [RC-172](#)
- router eigrp configuration submode
  - address-family ipv4 command [RC-170](#)
  - interface command [RC-170](#)
- router eigrp interface configuration submode
  - bandwidth-percent command [RC-171](#)
  - holdtime command [RC-170](#)
  - summary-address command [RC-173](#)
- router hardware
  - See* hardware
- router hsrp command [IC-139](#)
- router identifier [RC-4](#)
- router igmp command [MCC-22](#), [MCC-43](#), [MCC-51](#)
- router isis address family submode
  - attached-bit send command [RC-344](#)
  - default-information originate command [RC-342](#)
  - distance command [RC-343](#)
  - ispf command [RC-340](#)
  - maximum-paths command [RC-343](#)
  - metric-style wide command [RC-335](#)
  - mpls ldp sync command [RC-345](#)
  - mpls traffic-eng command [RC-334](#)
  - mpls traffic-eng multicast-intact command [RC-347](#)
  - mpls traffic-eng router-id command [RC-334](#)
  - redistribute isis command [RC-342](#)
  - single-topology command [RC-314](#)
  - spf prefix-priority command [RC-350](#)
  - spf-interval command [RC-340](#)
  - summary-prefix command [RC-343](#)
- router isis configuration submode
  - address-family command [RC-314](#)
  - ignore-lsp-errors command [RC-325](#)
  - is-type command [RC-310](#)
  - log adjacency changes command [RC-337](#)
  - lsp-check-interval command [RC-324](#)
  - lsp-gen-interval command [RC-324](#)
  - lsp-mtu command [RC-324](#)
  - lsp-password command [RC-330](#)
  - lsp-refresh-interval command [RC-324](#)
  - max-lsp-lifetime command [RC-324](#)
  - net command [RC-309](#)
  - nsf command [RC-327](#)
  - nsf interface-expires command [RC-328](#)
  - nsf interface-timer command [RC-328](#)
  - nsf lifetime command [RC-328](#)
  - set-overload-bit command [RC-342](#)
- router isis interface address family submode
  - tag command [RC-348](#)
- router isis interface configuration submode
  - address-family command [RC-314](#)
  - circuit-type command [RC-314](#)
  - csnp-interval command [RC-325](#)

- hello-interval command [RC-337](#)
- hello-multiplier command [RC-337](#)
- hello-padding command [RC-337](#)
- hello-password command [RC-331](#)
- ipv4 address command [RC-313](#)
- ipv6 address command [RC-313](#)
- ipv6 enable command [RC-313](#)
- lsp-interval command [RC-325](#)
- mesh-group command [RC-325](#)
- retransmit-interval command [RC-325](#)
- retransmit-throttle-interval command [RC-325](#)
- router isis interface submode
  - mesh-group command [RC-325](#)
- router mld command [MCC-22](#), [MCC-43](#)
- router mld submode, nsf lifetime command [MCC-43](#)
- router msdp command [MCC-22](#), [MCC-59](#), [MCC-62](#), [MCC-67](#)
- router msdp submode
  - cache-sa-state command [MCC-62](#)
  - connect-source command [MCC-59](#), [MCC-71](#)
  - default-peer command [MCC-59](#)
  - mesh-group command [MCC-59](#)
  - originator-id command [MCC-59](#)
  - password command [MCC-67](#)
  - peer command [MCC-59](#), [MCC-67](#)
  - remote-as command [MCC-59](#)
  - sa-filter command [MCC-62](#), [MCC-71](#)
  - ttl-threshold command [MCC-62](#), [MCC-71](#)
- router ospf command [RC-222](#)
- router ospf command (BFD) [HC-69](#)
- router ospf configuration submode [RC-222](#)
  - area command [RC-222](#)
  - authentication command [RC-232](#)
  - message-digest-key command [RC-232](#)
  - mpls traffic-eng area command [RC-253](#)
  - mpls traffic-eng router-id command [RC-252](#)
  - nsf interval command [RC-251](#)
  - router-id command [RC-222](#)
  - summary-prefix command [RC-245](#)
  - timers lsa group-pacing command [RC-236](#)
  - timers lsa min-interval command [RC-235](#)
  - timers lsa refresh command [RC-235](#)
  - timers throttle spf command [RC-247](#)
- router ospfv3 command [RC-222](#)
- router ospfv3 command (BFD) [HC-71](#)
- router ospfv3 configuration submode
  - area command [RC-222](#)
  - router-id command [RC-222](#)
  - summary-prefix command [RC-245](#)
  - timers lsa group-pacing command [RC-236](#)
  - timers lsa min-interval command [RC-235](#)
  - timers lsa refresh command [RC-235](#)
- router pim command [MCC-22](#), [MCC-33](#), [MCC-35](#), [MCC-37](#), [MCC-43](#), [MCC-50](#), [MCC-54](#)
- router pim submode
  - auto-rp candidate-rp command [MCC-35](#)
  - auto-rp mapping-agent command [MCC-35](#)
  - bsr candidate-bsr command [MCC-37](#)
  - bsr candidate-rp command [MCC-37](#)
  - interface command [MCC-37](#)
  - nsf lifetime command [MCC-43](#)
  - rp-address command [MCC-50](#), [MCC-52](#)
- router rib command [RC-367](#)
- router rib configuration submode,address-family command [RC-367](#)
- router rip command [RC-378](#)
- router rip configuration submode
  - auto-summary command [RC-380](#)
  - broadcast-for-v2 command [RC-378](#)
  - interface command [RC-379](#)
  - nsf command [RC-380](#)
  - output-delay command [RC-380](#)
  - timers basic command [RC-380](#)
- router rip interface configuration submode
  - metro-zero-accept command [RC-381](#)
  - passive-interface command [RC-383](#)
  - poison-reverse command [RC-381](#)
  - receive version command [RC-379](#)

- send version command [RC-379](#)
- split-horizon disable command [RC-381](#)
- router static command [RC-475](#)
- router static command (BFD) [HC-73](#)
- route-reflector-client command [RC-83](#)
- router-id command [RC-222](#)
- routes
  - customizing (IS-IS) [RC-341](#)
  - default
    - IS-IS [RC-304](#)
    - OSPFv2 [RC-207](#)
  - redistribute IS-IS routes (example) [RC-354](#)
  - redistributing (OSPFv2, OSPFv3) [RC-242](#)
- route-tag support for connected routes [IC-181](#)
- routing components
  - ABRs (area border routers ) [RC-204](#)
  - ASBRs (autonomous system boundary routers) [RC-204](#)
  - autonomous systems [RC-203](#)
  - backbone area [RC-203](#)
  - designated router (DR) [RC-207](#)
  - interior routers [RC-205](#)
  - not-so-stubby area [RC-204](#)
  - stub area [RC-204](#)
- routing domain confederation [RC-36](#)
- routing policy [RC-21](#)
  - attaching to BGP neighbor [RC-454](#)
  - configuration elements, editing [RC-451](#)
  - defining [RC-453](#)
  - enforcing, BGP [RC-21](#)
  - implementing in
    - prerequisites [RC-394](#)
  - inbound (example) [RC-458](#)
  - modifying [RC-456](#)
  - modular inbound (example) [RC-459](#)
  - statements
    - action [RC-412](#)
    - disposition [RC-410](#)
    - elseif [RC-413](#)
    - if [RC-412](#)
    - remark [RC-410](#)
- RP, preconfiguration directory [HC-347](#)
- RPL (routing policy language)
  - Boolean operators, types [RC-413](#)
  - components [RC-400](#)
  - overview [RC-395](#)
  - policy
    - Boolean operator precedence [RC-406](#)
    - configuration basics [RC-403](#)
    - default drop disposition [RC-407](#)
    - definitions [RC-403](#)
    - statement processing [RC-408](#)
    - statements, types [RC-410](#)
    - verification [RC-408](#)
  - policy attributes
    - modification [RC-406](#)
    - parameterization [RC-404](#)
  - structure
    - as-path-set, inline set form [RC-397](#)
    - as-path-set, named set form [RC-397](#)
    - community-set, inline set form [RC-398](#)
    - community-set, named set form [RC-397](#)
    - extended community set, inline form [RC-398](#)
    - extended community set, named form [RC-398](#)
    - names [RC-396](#)
    - prefix-set [RC-399](#)
    - sets [RC-396](#)
- RPs (route processors)
  - automatic switchover [SMC-237](#)
  - manual switchover [SMC-238](#)
  - node id components (CRS-1) [SMC-226](#)
  - node ID components (XR 12000) [SMC-227](#)
  - process distribution among
    - See* process placement
  - redundancy status, displaying [SMC-231](#)
  - redundancy, summary of commands [SMC-237](#)
  - reload, redundancy during [SMC-237](#)
  - reloading active RP [SMC-240](#)

- RRI (reverse-route injection)
    - configuring in a crypto profile [SC-180](#)
    - description [SC-150](#)
  - RSA (Rivest, Shamir, and Adelman)
    - encrypted nonces
      - requirements [SC-84, SC-85](#)
    - keys
      - configuring manually [SC-106](#)
      - configuring peers [SC-108](#)
      - deleting [SC-66](#)
      - generating [SC-106](#)
    - signatures [SC-85](#)
      - requirements [SC-84](#)
  - RSA encrypted nonces\
  - RSA keys
  - RSVP
    - compliance [MPC-55](#)
    - configuration
      - graceful restart [MPC-66](#)
      - interface-based graceful restart [MPC-66](#)
      - O-UNI LSP [MPC-55](#)
      - Packet dropping [MPC-68](#)
      - tunnel bandwidth, engineering [MPC-64](#)
      - verifying [MPC-70](#)
    - confirming diffserv-TE bandwidth [MPC-64](#)
    - description [MPC-53](#)
    - extensions [MPC-55](#)
      - generalized label request [MPC-55](#)
      - generalized UNI attribute [MPC-55](#)
      - New Error Spec sub-codes [MPC-55](#)
      - UNI session [MPC-55](#)
    - fault handling [MPC-57](#)
    - filtering ACL-based prefixes [MPC-59](#)
    - graceful restart [MPC-56](#)
    - head node [MPC-56](#)
    - hello messages [MPC-58](#)
    - high availability [MPC-56](#)
    - implementing [MPC-63](#)
    - message rate limiting [MPC-55](#)
    - node failure [MPC-58](#)
    - overview [MPC-55](#)
    - prerequisites [MPC-54](#)
    - recovery time [MPC-58](#)
    - refresh reduction [MPC-55](#)
    - restart time [MPC-58](#)
    - support for graceful restart [MPC-55](#)
    - tail node [MPC-56](#)
    - topology [MPC-70](#)
    - with O-UNI LSP, configuring [MPC-55](#)
  - RSVP nodes
    - head node [MPC-56](#)
    - tail node [MPC-56](#)
  - RTSP
    - application protocol support [VFC-121](#)
    - inspection overview [VFC-127](#)
    - restrictions [VFC-128](#)
  - rules, maximum in ACL [VFC-97](#)
  - RVSP node failure [MPC-58](#)
- 
- S**
- SA (security association) for IPsec VPN SPA
    - idle timers
      - configuring for each crypto profile [SC-175](#)
      - configuring globally [SC-174](#)
      - description [SC-145](#)
      - lifetimes [SC-174](#)
  - SA messages
    - default [MCC-62](#)
    - definition [MCC-20](#)
  - SAFI function [MPC-353](#)
  - SAM (Software Authentication Manager)
    - description [SC-253](#)
  - sample output [SMC-130](#)
  - sampler map [HC-254](#)
  - sampler map configuration submode [HC-257](#)
  - sampler-map command [HC-263](#)
  - SAs (security associations)

- lifetimes
  - configuring [SC-96](#), [SC-143](#)
  - IKE policy parameter [SC-82](#)
  - operation [SC-143](#)
  - resource limit configuration [SC-114](#)
- SAs[IKE (Internet Key Exchange Security Protocol) zzz]
- SCCP, inspection [VFC-121](#), [VFC-128](#), [VFC-158](#)
- schedule operation, IP SLA [MNC-54](#)
- scramble command [HC-371](#)
- scratch register test [HC-140](#)
- SDH (synchronous digital hierarchy) [MPC-211](#)
- sdr command [SMC-15](#), [SMC-18](#), [SMC-21](#), [SMC-22](#), [SMC-24](#), [SMC-26](#), [SMC-28](#)
- SDR configuration mode
  - location command [SMC-16](#)
  - location command [SMC-13](#), [SMC-15](#), [SMC-17](#), [SMC-18](#), [SMC-21](#), [SMC-23](#), [SMC-25](#), [SMC-27](#)
  - pair command [SMC-15](#)
- SDRs (secure domain routers)
  - about configuring [SMC-3](#)
  - access privileges [SMC-4](#)
  - adding nodes to (example) [SMC-34](#)
  - and nodes, removing [SMC-23](#)
  - configuration examples [SMC-33](#)
  - configuration tasks [SMC-12](#)
  - configuring, feature history [SMC-1](#)
  - configuring, prerequisites [SMC-2](#)
  - create, how to [SMC-12](#)
  - creating (example) [SMC-33](#), [SMC-34](#)
  - creating and configuring, restrictions [SMC-12](#)
  - default package profile [SMC-9](#)
  - definition [SMC-3](#)
  - DSDRSC(designated secure domain router shelf controller) [SMC-6](#)
  - hardware version info, displaying [SMC-216](#)
  - hardware version info, displaying (example) [SMC-216](#)
  - high availability [SMC-10](#)
  - node IDs and status, displaying [SMC-226](#)
  - non-owner
    - adding nodes to [SMC-19](#)
    - default configuration [SMC-9](#)
    - description [SMC-4](#)
    - username and password, configuring [SMC-35](#)
    - username and password, creating [SMC-29](#)
  - owner SDR [SMC-3](#)
  - process distribution throughout
    - See* process placement
  - remote login, disabling [SMC-32](#)
  - removing nodes from (example) [SMC-34](#)
  - software installation, about [SMC-50](#)
  - software profile, default [SMC-51](#)
- secondary addresses, IP [IC-187](#)
- securing L2TPv3 tunnels using IPsec [MPC-322](#)
- security context
  - added to system [VFC-327](#)
  - removed from system [VFC-327](#)
- security ttl command [RC-278](#)
- Security-Admin
  - description [VFC-49](#)
  - permissions [VFC-49](#)
- self-identity command [SC-121](#)
- self-ping over fabric test [HC-139](#)
- send version command [RC-379](#)
- send-community-ebgp command [RC-90](#)
- send-lifetime command [SC-223](#)
- sequence numbering behavior [IC-6](#)
- serial interface
  - configuring
    - CRC [HC-370](#)
    - interface encapsulation [HC-370](#)
    - IP address and subnet mask [HC-368](#)
    - keepalive timer [HC-378](#)
    - transmit delay [HC-371](#)
  - data stream, inverting [HC-371](#)
  - default settings
    - CRC [HC-365](#)
    - encapsulation [HC-365](#)

- keepalive [HC-365](#)
- mtu [HC-365](#)
- link state [HC-360](#), [HC-361](#), [HC-362](#)
- payload scrambling, enabling [HC-371](#)
- PPP encapsulation [HC-360](#)
- prerequisites [HC-356](#)
- serial numbers
  - configured, displaying [SMC-224](#)
  - displaying [SMC-224](#)
- server-private command [SC-31](#), [SC-35](#)
- service models, end-to-end, differentiated service [QC-4](#)
- service provider edge routers, 6PE [MPC-309](#)
- service providers, 6PE [MPC-308](#)
- service timestamps debug datetime command [MNC-167](#)
- service timestamps debug uptime command [MNC-167](#)
- service timestamps disable command [MNC-170](#)
- service timestamps log datetime command [MNC-167](#)
- service timestamps log uptime command [MNC-167](#)
- service-ipsecc interface [MPC-322](#)
- service-location command [SC-148](#)
- service-policy command, attaching traffic policies [QC-30](#)
- service-policy command [HC-408](#)
- Session Initiation Protocol. See SIP [VFC-122](#), [VFC-129](#)
- session protection, LDP [MPC-11](#)
- set cos command [HC-406](#), [HC-407](#), [QC-34](#)
- set discard-class command [QC-34](#)
- set dscp command [QC-33](#)
- set eigrp-metric command [RC-176](#)
- set interface tunnel-ipsecc command [SC-121](#)
- set pfs command [SC-144](#)
- set precedence command [QC-33](#)
- set qos-group command [QC-37](#)
- set rip-metric command [RC-385](#)
- set security-association idle-time command [SC-162](#)
- set security-association lifetime command [SC-162](#)
- set security-association replay disable command [SC-162](#)
- set session-key inbound ah command [SC-162](#)
- set session-key inbound esp command [SC-162](#)
- set session-key outbound ah command [SC-162](#)
- set session-key outbound esp command [SC-162](#)
- set srp-priority command [QC-34](#)
- set-overload-bit command [RC-342](#)
- severity level [MNC-7](#)
- severity level definitions [MNC-188](#)
- severity level messages
  - Level 1 messages [VFC-338](#)
  - Level 2 messages [VFC-338](#)
  - Level 3 messages [VFC-339](#)
  - Level 4 messages [VFC-339](#)
  - Level 5 messages [VFC-340](#)
  - Level 6 messages [VFC-340](#)
  - Level 7 messages [VFC-341](#)
  - overview [VFC-237](#)
- severity levels
  - alerts [VFC-338](#)
  - critical [VFC-338](#)
  - debugging [VFC-341](#)
  - errors [VFC-339](#)
  - informational [VFC-340](#)
  - notifications [VFC-340](#)
  - overview [VFC-237](#)
  - warning [VFC-339](#)
- SF (Signal Fail) [HC-402](#)
- SFCs (switch fabric cards)
  - node ID components (Cisco CRS-1) [SMC-227](#)
  - node ID components (Cisco XR 12000) [SMC-227](#)
  - removing and replacing (16-slot Cisco CRS-1) [SMC-246](#)
  - removing and replacing (4-slot Cisco CRS-1) [SMC-262](#)
  - removing and replacing (8-slot Cisco CRS-1) [SMC-254](#)
  - removing and replacing (Cisco XR 12000) [SMC-270](#)
  - replacing (8-slot Cisco CRS-1) (example) [SMC-259](#)
- SFTP [SMC-59](#)

## SHA (Secure Hash Algorithm)

IKE policy parameter [SC-82](#)

sham-links [RC-258](#)

shape command [HC-19](#)

show aps command [HC-106, HC-430](#)

show atm ilmi-status command [HC-45, HC-47](#)

show atm vp-tunnel command [HC-23](#)

show atm vp-tunnel interface atm command [HC-20](#)

show bfd counters command [HC-78](#)

show bgp af-group command [RC-18](#)

show bgp community command [RC-142](#)

show bgp count-only command [RC-141](#)

show bgp flap-statistics command [RC-72](#)

show bgp flap-statistics reexp command [RC-72](#)

show bgp flap-statistics route-policy command [RC-73](#)

show bgp inheritance command [RC-17](#)

show bgp neighbor command [RC-16](#)

show bgp neighbors command [RC-140](#)

show bgp paths command [RC-140](#)

show bgp process detail command [RC-142](#)

show bgp reexp command [RC-140](#)

show bgp session-group command [RC-18](#)

show bgp summary command [RC-141](#)

show bundle Bundle-Ether command [HC-212, HC-219](#)

show bundle Bundle-POS command [HC-223](#)

show cdp command [SMC-286](#)

show cdp entry command [SMC-287](#)

show cdp interface command [SMC-287](#)

show cdp neighbors command [SMC-287](#)

show cdp traffic command [SMC-287](#)

show cinetd services command [IC-124](#)

show clock command [SMC-64](#)

show controller sonet command [HC-426](#)

show controllers command [HC-445, SMC-243](#)

show controllers fabric plane all command [SMC-248, SMC-256, SMC-264](#)

show controllers fabric plane command [SMC-250, SMC-257, SMC-267](#)

show crypto session command [SC-90](#)

show diag chassis command [SMC-224](#)

show diag command [SMC-216, SMC-219](#)

show diags command [SC-147](#)

show eigrp accounting command [RC-186](#)

show eigrp interfaces command [RC-186](#)

show eigrp neighbors command [RC-180](#)

EXEC mode [RC-187](#)

show eigrp topology command [RC-187](#)

show eigrp traffic command [RC-187](#)

show environment command [SMC-229](#)

show fault manager environment command [MNC-245](#)

show fault manager metric process command (example) [MNC-279](#)

show fault manager policy available command [MNC-248](#)

show fault manager policy available command (example) [MNC-279](#)

show fault manager policy registered command [MNC-250](#)

show flow exporter-map command [HC-262, HC-275](#)

show flow monitor map command [HC-267](#)

show fpd package command [SMC-127, SMC-128](#)

show fpd package command (example) [SMC-131](#)

show frame-relay lmi command [HC-172](#)

show hw-module fdp command [SMC-232](#)

show hw-module fpd command [SMC-127, SMC-128, SMC-130](#)

show hw-module fpd command (example) [SMC-130](#)

show hw-module linecard throughput command [SMC-116, SMC-118, SMC-120](#)

(example) [SMC-118, SMC-120](#)

show hw-module subslot command [SMC-129](#)

show igmp nsf command [MCC-44](#)

show install active command [SMC-62, SMC-95](#)

show install active summary command [SMC-74](#)

show install committed command [SMC-79, SMC-95](#)

show install pie-info command [SMC-63](#)

show install rollback command [SMC-87, SMC-88](#)

show interfaces command [HC-154, HC-384, SMC-244](#)

show ip route command [HC-478](#)

- show ip route connected command [RC-369](#)
- show ipsla statistics aggregated command [MNC-70](#)
- show ipsla statistics command
  - ICMP Echo operation [MNC-80](#)
  - ICMP Path Echo operation [MNC-87](#)
  - ICMP Path Jitter operation [MNC-95](#)
  - UDP Echo operation [MNC-73](#)
  - UDP Jitter operation [MNC-70](#)
- show isis command [RC-310](#)
- show isis database command [RC-326](#)
- show isis database-log command [RC-326](#)
- show isis interface command [RC-339](#)
- show isis lsp-log command [RC-326](#)
- show isis mpls command [RC-335](#)
- show isis mpls traffic-eng adjacency-log command [RC-335](#)
- show isis mpls traffic-eng advertisements command [RC-335](#)
- show isis neighbors command [RC-339](#)
- show isis spf-log command [RC-341](#)
- show isis topology command [RC-315](#)
- show key chain command [SC-216](#)
- show lacp bundle Bundle-Ether command [HC-212](#)
- show lacp bundle Bundle-POS command [HC-223](#)
- show license backup command [SMC-122](#)
- show license udi command [SMC-115](#)
- show line command [SMC-210](#)
- show logging command [MNC-173](#)
- show logging correlator buffer all-in-buffer command [MNC-28](#), [MNC-36](#)
- show logging correlator buffer correlationID command [MNC-36](#)
- show logging correlator buffer rule-name command [MNC-36](#)
- show logging correlator info command [MNC-28](#), [MNC-36](#)
- show logging correlator rule command [MNC-12](#)
- show logging correlator ruleset command [MNC-14](#)
- show logging events buffer all-in-buffer command [MNC-35](#)
- show logging events buffer first command [MNC-34](#)
- show logging events buffer group command [MNC-33](#)
- show logging events buffer last command [MNC-34](#)
- show logging events buffer location command [MNC-35](#)
- show logging events buffer message command [MNC-33](#)
- show logging events buffer severity-hi-limit command [MNC-30](#)
- show logging events buffer severity-lo-limit command [MNC-30](#)
- show logging events buffer timestamp-hi-limit command [MNC-32](#)
- show logging events buffer timestamp-lo-limit command [MNC-32](#)
- show logging events info command [MNC-26](#)
- show logging history command [MNC-165](#)
- show logging location command [MNC-173](#)
- show logging lower-limit-timestamp command [MNC-173](#)
- show logging process command [MNC-173](#)
- show logging string command [MNC-173](#)
- show logging upper-limit-timestamp command [MNC-173](#)
- show lpts pifib hardware police command [IC-157](#)
- show mac accounting command [HC-161](#)
- show mfib hardware route command [MCC-65](#), [MCC-67](#)
- show mfib nsf command [MCC-44](#)
- show mgmt-plane command [SC-243](#)
- show mirror command [SMC-103](#)
- show mld nsf command [MCC-44](#)
- show mpls forwarding exact-route command [IC-73](#)
- show mrib nsf command [MCC-44](#)
- show msdp globals command [MCC-59](#)
- show msdp peer command [MCC-59](#)
- show msdp rpf command [MCC-59](#)
- show ntp associations command [SMC-179](#)
- show ntp status command [SMC-179](#)
- show ospf command [RC-238](#)
- show ospfv3 command [RC-238](#)
- show pim neighbor command [MCC-11](#)
- show pim nsf command [MCC-44](#)
- show placement location command [SMC-148](#), [SMC-149](#), [SMC-151](#), [SMC-152](#)

- show placement policy global command [SMC-145](#)
- show placement program command [SMC-148](#),  
[SMC-149](#), [SMC-151](#), [SMC-152](#)
- show placement program command  
(example) [SMC-153](#)
- show platform command [SMC-237](#)
  - administration EXEC mode [SMC-228](#)
  - EXEC mode [SMC-226](#)
- show platform command (example) [SMC-134](#)
- show policy-map interface command [QC-31](#)
- show ppp interfaces command [HC-318](#), [HC-327](#)
- show protocols eigrp command [RC-187](#)
- show radius dead-criteria host command [SC-29](#)
- show redundancy command [SMC-232](#), [SMC-236](#),  
[SMC-237](#), [SMC-238](#), [SMC-241](#)
- show route command [SC-180](#), [SC-186](#), [SC-190](#)
- show rpl route-policy command [RC-457](#)
- show rsi interface all global command [SMC-116](#)
- show running-config command [HC-401](#), [RC-328](#),  
[SMC-244](#)
- show sampler-map command [HC-264](#)
- show snmp command [SMC-302](#)
- show snmp engineid command [SMC-302](#)
- show snmp group command [SMC-302](#)
- show snmp host command [SMC-305](#)
- show snmp users command [SMC-303](#)
- show snmp view command [SMC-303](#)
- show srp ips interface srp command [HC-404](#)
- show system backup command [SMC-97](#), [SMC-100](#)
- show system verify command [SMC-64](#), [SMC-74](#)
- show terminal command [SMC-210](#)
- show user all command [SMC-247](#), [SMC-255](#),  
[SMC-263](#), [SMC-270](#)
- show user group command [SMC-247](#), [SMC-255](#),  
[SMC-263](#), [SMC-270](#)
- show users command [SMC-210](#)
- show variables boot command [SMC-240](#), [SMC-241](#)
- show version command [HC-154](#), [MCC-32](#), [SMC-95](#),  
[SMC-225](#)
- show vlan command [HC-487](#)
- show vlan interface command [HC-494](#)
- show vlan trunks command [HC-219](#)
- show vrrp command [IC-218](#)
- shutdown command [RC-115](#)
- signaling
  - pseudowires [MPC-269](#)
  - VPLS [MPC-269](#)
- Simple Network Management Protocol
  - see SNMP [MNC-5](#)
- simplified IPv6 packet header [IC-171](#)
- single LAN, process [IC-43](#)
- single-topology
  - command [RC-314](#)
  - configuring (example) [RC-354](#)
  - IPv6 support [RC-301](#)
  - set SPF interval [RC-339](#)
- SIP, inspection [VFC-121](#), [VFC-122](#), [VFC-129](#),  
[VFC-151](#)
- SIPs (SPA interface processors)
  - node ID components (CRS-1) [SMC-227](#)
  - node ID components (XR 12000) [SMC-227](#)
- site-of-origin command [RC-121](#)
- Skeme key exchange protocol
  - See also* IKE[Skeme key exchange protocol  
*zzz*]
- Skinny Client Control Protocol. See SCCP [VFC-128](#)
- SLARP (Serial Line Address Resolution Protocol) [HC-285](#), [HC-287](#), [HC-360](#), [HC-363](#)
- slot number notation [SMC-226](#), [SMC-229](#)
- SMU (Software Maintenance Update)
  - about
  - definition [SMC-41](#)
- SNMP [MNC-5](#)
  - daemon initialization failure [VFC-319](#)
  - memory allocation failure [VFC-319](#)
  - Shadow Table error [VFC-326](#)
- SNMP (Simple Network Management Protocol)
  - agent
    - description [SMC-295](#)
    - packet size, max, configuring [SMC-307](#)

- setting contact, location and serial number [SMC-305](#)
- configuration examples [SMC-311](#)
- configuration procedures [SMC-300](#)
- context mapping, displaying [SMC-311](#)
- DSCP values, setting [SMC-309](#)
- feature history [SMC-293](#)
- functional overview [SMC-294](#)
- get-next-request operation [SMC-297](#)
- get-request operation [SMC-297](#)
- get-response operation [SMC-297](#)
- IP DSCP value, setting (example) [SMC-315](#)
- IP precedence value, setting (example) [SMC-315](#)
- IP precedence, setting [SMC-309](#)
- manager, description [SMC-294](#)
- MIB, description [SMC-295](#)
- notifications
- prerequisites [SMC-294](#)
- security models and levels [SMC-297](#)
- set-request operation [SMC-297](#)
- SNMPv3
  - benefits [SMC-298](#)
  - configuring [SMC-300](#)
  - configuring (example) [SMC-311](#)
  - costs [SMC-299](#)
  - creating groups (example) [SMC-312](#)
  - creating users (example) [SMC-313](#)
  - creating view (example) [SMC-312](#)
  - engine ID, identifying (example) [SMC-311](#)
  - engine ID, setting (example) [SMC-311](#)
  - user-based security model [SMC-299](#)
  - verifying groups (example) [SMC-312](#)
  - view-based control model [SMC-299](#)
- trap notifications
  - about
  - configuring [SMC-303](#)
  - configuring (example) [SMC-314](#)
  - operation values, changing [SMC-308](#)
- trap operation [SMC-297](#)
- versions
  - comparison [SMC-297](#)
  - overview [SMC-296](#)
- SNMP, L2TPv3 prerequisite [MPC-316](#)
- snmp-server chassis-id command [SMC-306](#)
- snmp-server contact command [SMC-306](#)
- snmp-server enable traps command [SMC-304](#)
- snmp-server engineid local command [SMC-301](#), [SMC-304](#)
- snmp-server group command [SMC-301](#), [SMC-304](#)
- snmp-server host command [SMC-304](#)
- snmp-server ipv4 dscp command [SMC-310](#)
- snmp-server ipv4 precedence command [SMC-310](#)
- snmp-server location command [SMC-306](#)
- snmp-server packetsize command [SMC-308](#)
- snmp-server queue-length command [SMC-309](#)
- snmp-server trap source command [SMC-309](#)
- snmp-server trap-timeout command [SMC-309](#)
- snmp-server user command [SMC-302](#), [SMC-304](#)
- snmp-server view command [SMC-301](#)
- SNMPv1
  - See* SNMP
- SNMPv2c
  - See* SNMP
- SNMPv3
  - See* SNMP
- soft-reconfiguration inbound always command [RC-97](#)
- software
  - active, displaying [SMC-225](#)
- software entitlement
  - about
  - feature history [SMC-111](#)
  - impact when upgrading software [SMC-116](#)
  - information about [SMC-112](#)
  - prerequisites [SMC-112](#)
  - restrictions [SMC-112](#)
- software packages
  - about [SMC-40](#)
  - activating (example) [SMC-76](#)

- activating multiple, about [SMC-48](#)
- activating, about [SMC-48](#)
- activation, impact of [SMC-53](#)
- active, displaying (example) [SMC-77](#)
- adding (example) [SMC-75](#)
- adding and activating (example) [SMC-76](#)
- adding and activating, procedure [SMC-68](#)
- adding to SDR, about [SMC-47](#)
- adding, prerequisites for [SMC-69](#)
- available, summary [SMC-41](#)
- bundles [SMC-43](#)
- committed, displaying [SMC-79](#)
- committing [SMC-79](#)
- committing active set, about [SMC-49](#)
- deactivating and removing [SMC-80](#)
- deactivation, impact of [SMC-53](#)
- downgrading, about [SMC-52](#)
- downloading [SMC-59](#)
- feature history [SMC-39](#)
- for bug fixes
- impact of version changes [SMC-53](#)
- installing, about [SMC-46](#)
- managing for SDRs [SMC-10](#)
- multishelf system, in [SMC-50](#)
- obtaining and placing [SMC-58](#)
- operation ID, activating by specifying (example) [SMC-76](#)
- optional [SMC-42](#)
- prerequisites, installation [SMC-57](#)
- procedures
- procedures, examples [SMC-75](#)
- rolling back, about [SMC-49](#)
- Unicast Routing Core Bundle [SMC-42](#)
- upgrading and downgrading, about [SMC-49](#)
- upgrading, about [SMC-52](#)
- solicitation message, IPv6 [IC-175](#)
- SONET (Synchronous Optical Network)
  - APS [HC-426](#)
  - description [HC-417](#)
  - fast reroute (FFR) [HC-431](#)
  - SONET (synchronous optical network), with O-UNI [MPC-212](#)
  - SONET APS (SONET Automatic Protection Switching) [HC-426](#)
  - SONET controller
    - configuring [HC-422](#)
    - frame type [HC-423](#)
  - sonet submode
    - See* controller sonet command
    - ais-shut command [HC-429](#)
    - clock source command [HC-400](#), [HC-423](#), [HC-430](#)
    - delay trigger command [HC-423](#), [HC-432](#)
    - framing command [HC-423](#)
    - loopback command [HC-424](#)
    - overhead command [HC-424](#)
    - path command [HC-425](#), [HC-432](#)
    - path scrambling command [HC-429](#)
  - source command [HC-261](#)
  - source NAT [VFC-293](#), [VFC-294](#), [VFC-295](#), [VFC-297](#)
  - source pool address [MPC-355](#)
  - source-based learning, how to configure MAC address [MPC-294](#)
  - SPA (shared port adapter)
    - See also* FPDs (field-programmable devices)
    - images
  - span protection [MPC-109](#)
  - SPAs (shared port adapters)
    - See also* FPDs (field-programmable devices)
    - images
    - node ID components [SMC-227](#)
    - reloading after FPD upgrade [SMC-127](#)
  - SPAs (shared port adaptors)
    - node ID components (XR 12000) [SMC-227](#)
  - Spatial Reuse Protocol (SRP) [HC-389](#)
    - basic configuration [HC-399](#)
    - definition [HC-389](#)
    - MQC, configuring [HC-404](#)
    - node, adding to ring [HC-408](#)
    - PLIM, enabling on [HC-392](#)

- SPA, enabling on [HC-394](#), [HC-396](#)
- speed command [HC-147](#), [HC-158](#)
- spf prefix-priority command [RC-350](#)
- spf-interval command [RC-340](#)
- split-horizon disable command [RC-381](#)
- spoofing attack [VFC-323](#), [VFC-324](#)
- spt-threshold infinity command [MCC-10](#)
- SRLG (shared-risk link group)
  - configuring [MPC-198](#)
  - example [MPC-208](#)
- SRLG (Shared-Risk Link Group)
  - membership of each link, configuring [MPC-198](#)
- srp interface srp request manual-switch command [HC-404](#)
- srp ips request forced-switch command [HC-403](#), [HC-409](#), [HC-410](#)
- srp ips timer command [HC-403](#)
- srp ips wtr-timer command [HC-403](#)
- srp topology-timer command [HC-400](#)
- SSH (Secure Shell) [HC-475](#)
  - client
    - 3DES support [SC-258](#)
    - configuring [SC-262](#)
    - description [SC-258](#)
    - server support [SC-258](#)
  - configuring [SC-258](#)
  - prerequisites [SC-256](#)
  - restrictions [SC-256](#)
  - server [SC-257](#)
- SFTP (Standard File Transfer Protocol)
  - description [SC-258](#)
  - supported versions [SC-255](#)
  - troubleshooting [SC-263](#)
- SSH File Transfer Protocol [SMC-59](#)
- SSH, version [VFC-39](#)
- SSL (Secure Socket Layer) [HC-475](#)
  - configuring [SC-269](#)
  - description [SC-267](#)
  - prerequisites [SC-268](#)
- standby PRP, adding [SMC-276](#)
- start-time command
  - ICMP Echo operation [MNC-80](#)
  - ICMP Path Echo operation [MNC-87](#)
  - ICMP Path Jitter operation [MNC-95](#)
  - UDP Echo operation [MNC-73](#)
  - UDP Jitter operation [MNC-65](#)
- start-time, key chain management [SC-214](#)
- static [IC-194](#)
  - configuring a router to a peer [MPC-451](#)
  - configuring L2TPv3 pseudowires [MPC-340](#)
  - configuring routes [MPC-359](#)
  - defining L2TPv3 sessions [MPC-318](#)
  - point-to-point xconnects [MPC-242](#)
- static IPsec virtual interfaces, configuring [SC-186](#)
- static router submode
  - address-family command [RC-469](#)
  - maximum path command [RC-476](#)
  - vrf command [RC-469](#)
- static routes
  - administrative distance [RC-465](#)
  - associating with VRF [RC-476](#)
  - configuration between PE-CE routers [RC-473](#)
  - connected [RC-465](#)
  - defined [RC-464](#)
  - floating [RC-467](#)
  - floating configuration [RC-472](#)
  - maximum number of routes [RC-475](#)
  - MPLS layer 3 VPN [RC-465](#)
  - recursive [RC-466](#)
  - specified [RC-467](#)
- statistics command [MNC-67](#)
- storage devices, formatting [SMC-243](#)
- Stream Control Transmission Protocol (SCTP) [IC-203](#)
- stub area [RC-204](#)
- stub area types, configuring (OSPFv3) [RC-223](#)
- stub command [RC-225](#)
- subsystems [VFC-237](#)
- summary-address command [RC-173](#)
- summary-prefix command [RC-343](#)

switchover [HC-207](#)  
     automatic [SMC-237](#)  
     manual [SMC-238](#)

SYN cookie  
     configurational and operational considerations [VFC-278](#)  
     overview [VFC-277](#)

SYN flood attack [VFC-277](#)

syslog  
     archiving system logging messages [MNC-177](#)  
     configuring  
         logging buffer [MNC-165, MNC-180](#)  
         logging history table [MNC-163, MNC-180](#)  
         logging to a remote server [MNC-159](#)  
         logging to the console [MNC-165, MNC-180](#)  
         message destinations [MNC-180](#)  
         message destinations [MNC-159](#)  
     current terminal session, enabling logging for [MNC-154](#)  
     disabling the logging of link-status messages [MNC-172](#)  
     displaying system logging messages [MNC-173](#)  
     hostname prefix logging [MNC-155](#)  
     logging history table [MNC-157](#)  
     messages  
         archiving [MNC-156](#)  
         destinations [MNC-153](#)  
         format [MNC-151](#)  
         sending to destinations other than the console [MNC-154](#)  
     modifying time stamps [MNC-167, MNC-169, MNC-180](#)  
     severity levels  
         command defaults [MNC-158](#)  
         commands used to control [MNC-157](#)  
         definitions [MNC-158](#)  
     source address logging [MNC-155](#)  
     suppressing duplicate syslog messages [MNC-171](#)  
     system logging process [MNC-150](#)  
     UNIX syslog daemon configuration [MNC-155](#)

    UNIX system logging facilities [MNC-154](#)

system  
     hardware  
         *See* hardware  
     information, displaying [SMC-225](#)  
     uptime, displaying [SMC-225](#)

system backup command [SMC-99](#)

system boot-sequence command [SMC-98](#)

system message logging  
     format [VFC-237](#)  
     overview [VFC-236](#)  
     severity levels [VFC-237](#)  
     understanding [VFC-237](#)  
     variables [VFC-238](#)

---

## T

T1 controller  
     ANSI T1.403 or AT&T TR54016 performance reports [HC-440, HC-456](#)  
     BERT, configuring [HC-465](#)  
     card type, setting [HC-441](#)  
     clock source [HC-440, HC-456](#)  
     default configuration values [HC-439, HC-440](#)  
     DS0 timeslots, associating [HC-184, HC-189, HC-336, HC-457](#)  
     frame type [HC-440, HC-456](#)  
     T1 channel group, creating [HC-184, HC-189, HC-335, HC-457](#)  
     T1 configuration mode [HC-184, HC-189, HC-335, HC-456](#)  
     yellow alarms [HC-440](#)

T1 mode, changing to E1 mode [HC-441](#)

T3 controller  
     cable length, setting [HC-439](#)  
     card type, setting [HC-441](#)  
     clock source  
         configuring [HC-335, HC-446, HC-452](#)  
         default value [HC-439](#)  
     configuration prerequisites [HC-438](#)

- configuring [HC-448](#)
  - BERT [HC-463](#)
  - channelized T3 controller [HC-450](#)
  - clear channel E3 controller [HC-444](#)
  - clear channel T3 controller [HC-448](#)
  - FRF.12 end-to-end fragmentation [HC-188](#)
  - MDL messages [HC-439](#)
  - multilink Frame Relay bundle interfaces [HC-183](#)
- frame type [HC-439, HC-453](#)
- modifying
  - default E3 controller [HC-446](#)
  - default T3 controller [HC-452](#)
- T3 mode, changing to E3 mode [HC-441](#)
- table policy command [IC-64](#)
- table-policy command [RC-76](#)
- TACACS+ server
  - accounting settings, configuring [VFC-87](#)
  - Cisco Secure Access Control Server (ACS) [VFC-86, VFC-87](#)
  - dead-time setting [VFC-79](#)
  - global preshared key setting [VFC-78](#)
  - server authentication settings, configuring [VFC-86](#)
  - server overview [VFC-66](#)
  - timeout setting [VFC-79](#)
- tag command [RC-348](#)
  - ICMP Echo operation [MNC-82](#)
  - ICMP Path Echo operation [MNC-90](#)
  - ICMP Path Jitter operation [MNC-98](#)
  - UDP Echo operation [MNC-76](#)
- tasks
  - ABF with security ACL [IC-30](#)
  - access lists, applying [IC-15](#)
  - DHCP relay agent information [IC-103](#)
  - domain services [IC-121](#)
  - enabling HSRP [IC-139](#)
  - enabling IPv6 forward traffic globally [IC-185](#)
  - FTP connections [IC-126](#)
  - HSRP
    - configuring activation delay [IC-147](#)
    - configuring group attributes [IC-141](#)
    - enabling ICMP redirect messages [IC-149](#)
  - ICMP rate limiting [IC-192](#)
  - IP address conflict resolution [IC-196](#)
  - IPv4 and IPv6 protocol stacks [IC-189](#)
  - IPv6 addresses to individual router interfaces, assigning [IC-185](#)
  - network connectivity [IC-120](#)
  - packet routes [IC-121](#)
  - pure ACL-based forwarding [IC-32](#)
  - rcp connections [IC-124](#)
  - router as TFTP server [IC-123](#)
  - telnet service [IC-130](#)
  - TFTP connections [IC-129](#)
  - VRRP
    - verification [IC-218](#)
- TCP
  - connection slot creation [VFC-321](#)
  - connection slot termination [VFC-321](#)
- TCP (Transmission Control Protocol) [IC-203](#)
- TCP connection failure [VFC-330](#)
- TE
  - class and attributes [MPC-104](#)
  - class mapping [MPC-104](#)
  - description [MPC-99](#)
- technology, IP SLA [MNC-49](#)
- telnet service [IC-130](#)
- template command [HC-262](#)
- terminal monitor command [MNC-161](#)
- terminals, physical and virtual
  - See alsophysical terminals*
  - See alsovirtual terminals*
  - configuration examples [SMC-210](#)
  - configuration prerequisites [SMC-202](#)
  - configuration tasks [SMC-205](#)
  - feature history [SMC-201](#)
  - information about
    - monitoring [SMC-209](#)

- tests
  - control ethernet inactive link [HC-139](#)
  - control ethernet ping [HC-139](#)
  - fabric diagnostic [HC-140](#)
  - fabric multicast diagnosis [HC-140](#)
  - fabric ping [HC-139](#)
  - file system functionality verification test [HC-140](#)
  - rommonrevision [HC-140](#)
  - scratch register [HC-140](#)
  - self-ping over fabric [HC-139](#)
- TFTP [SMC-59](#)
- TFTP (Trivial File Transfer Protocol) [IC-124](#)
  - definition [IC-119](#)
  - router configuration [IC-129](#)
  - server, router configuration [IC-123](#)
  - troubleshooting tips [IC-130](#)
- fttp server command [IC-124](#)
- This is an index marker from the chapter [RC-11](#)
- This is an Index marker from the Preface [RC-9](#)
- threshold monitoring, IP SLA [MNC-54](#)
- threshold type average command [MNC-125](#)
- threshold type consecutive command [MNC-122](#)
- threshold type immediate command [MNC-120](#)
- threshold type xofy command [MNC-123](#)
- threshold violation types, IP SLA reaction [MNC-119](#)
- throughput
  - 10 Gbps on Cisco XR 12000 SIP [SMC-118](#)
  - 40-Gbps on MSC [SMC-116](#)
- timeout command [MNC-12](#)
  - ICMP Echo operation [MNC-82](#)
  - ICMP Path Echo operation [MNC-90](#)
  - ICMP Path Jitter operation [MNC-98](#)
  - UDP Echo operation [MNC-75](#)
  - UDP Jitter operation [MNC-68](#)
- timers basic command [RC-380](#)
- timers bgp command [RC-54](#)
- timers command [RC-115](#)
- timers lsa group-pacing command [RC-236](#)
- timers lsa min-interval command [RC-235](#)
- timers lsa refresh command [RC-235](#)
- timers nsf route-hold command [RC-175](#)
- timeslots command [HC-184](#), [HC-189](#), [HC-336](#), [HC-457](#)
- TLVs (type-length-value fields) [SMC-283](#)
- TNA addresses [MPC-213](#)
- tos command
  - ICMP Echo operation [MNC-82](#)
  - ICMP Path Echo operation [MNC-90](#)
  - ICMP Path Jitter operation [MNC-98](#)
  - UDP Echo operation [MNC-75](#)
  - UDP Jitter operation [MNC-68](#)
- traceroute
  - See* host services and applications
  - host services and applications
    - network connectivity [IC-121](#)
  - tool [IC-117](#)
- track command [SMC-187](#), [SMC-194](#)
- track configuration mode
  - delay command [SMC-187](#), [SMC-189](#), [SMC-192](#)
  - interface service-gre command [SMC-192](#), [SMC-195](#)
  - interface service-ipsec command [SMC-192](#), [SMC-195](#)
  - type line-protocol state command [SMC-188](#)
  - type route reachability command [SMC-191](#)
- tracking
  - See* object tracking
- traffic class
  - class-map command [QC-11](#)
  - creating [QC-24](#)
  - major elements [QC-11](#)
  - match commands [QC-11](#)
- traffic filtering [HC-228](#)
- traffic policer
  - committed information rate (CIR) [QC-78](#)
  - peak information rate (PIR) [QC-78](#)
  - purpose [QC-80](#)
  - single-rate, two color policer [QC-78](#)
- traffic policers and traffic shapers, use of traffic descriptor [QC-11](#)

- traffic policing
    - description [QC-78](#)
    - exceed-action command [QC-95](#)
    - packet marking [QC-80](#)
    - single-rate token bucket [QC-82](#)
    - summary [QC-3](#)
  - traffic policy
    - attaching to an interface [QC-30](#)
    - class command [QC-13](#)
    - creating [QC-28](#)
    - elements [QC-13](#)
    - maximum number of traffic classes [QC-13](#)
    - policy-map command [QC-13](#)
    - purpose [QC-13](#)
  - traffic shaping
    - description [QC-76](#)
    - enabled [QC-76](#)
    - shape average command [QC-91](#)
    - token bucket [QC-77](#)
    - traffic policing, contrasted with [QC-83](#)
  - transmit-delay command [HC-371](#)
  - transparent switchover [HC-238](#)
  - transport udp command [HC-262](#)
  - traps
    - See* SNMP
  - Trivial File Transfer Protocol (TFTP) [SMC-59](#)
  - Troubleshooting
    - FPD upgrade [SMC-135](#)
  - troubleshooting tips
    - FTP [IC-128](#)
    - rep [IC-126](#)
    - TFTP [IC-130](#)
  - TTL
    - RSVP [MPC-58](#)
    - with graceful restart [MPC-58](#)
  - TTL setting [VFC-279](#)
  - tunnel attributes [MPC-353](#)
  - tunnel bandwidth
    - configuring MAM [MPC-64](#)
    - configuring RDM [MPC-64](#)
  - tunnel destination command [HC-477](#)
  - Tunnel EA [MPC-355](#)
  - Tunnel MA [MPC-355](#)
  - tunnel source command [HC-477](#)
  - tunnel types
    - 6PE [MPC-309](#)
    - MPLS VPNs over IP tunnels [MPC-353](#)
  - tunnel vrf (IPSec) command [SC-149](#)
  - type icmp echo command [MNC-78](#)
  - type icmp path-echo command [MNC-85](#)
  - type icmp path-jitter command [MNC-93](#)
  - type udp echo command [MNC-71](#)
  - type udp ipv4 address command [MNC-61](#)
  - type udp jitter command [MNC-63](#)
- 
- ## U
- UDP
    - connection slot creation [VFC-320](#), [VFC-321](#)
    - connection slot deletion [VFC-320](#), [VFC-321](#)
    - DNS packet [VFC-325](#)
    - port numbers and key words [VFC-103](#)
  - UDP (User Datagram Protocol) [IC-203](#)
  - UDP Jitter operation parameters, list of [MNC-62](#)
  - unnumbered and numbered optical TE tunnels
    - configuring [MPC-161](#)
  - update groups
    - BGP configuration [RC-23](#)
    - BGP update generation [RC-23](#)
    - monitor [RC-142](#)
  - update-source command [RC-115](#)
  - upgrade cpuctrlbits command [SMC-278](#)
  - upgrade hw-module fpd command [SMC-127](#), [SMC-129](#)
  - upgrade hw-module fpd command (example) [SMC-133](#)
  - uptime, router, displaying [SMC-225](#)
  - URL configuration description [SC-92](#)
  - URLs
    - host access record [VFC-322](#)

- regular expressions [VFC-136](#)
  - uRPF (Unicast IPv4 and IPv6 Reverse Path Forwarding) [IC-55](#)
  - use command [RC-80](#)
  - user
    - displaying information [VFC-59](#)
    - session, clearing [VFC-59](#)
  - user role
    - predefined [VFC-49](#)
    - within a context [VFC-48](#)
  - username command [SMC-31](#)
  - username configuration mode
    - group command [SMC-31](#)
    - secret command [SMC-31](#)
  - using rcp connections [IC-124](#)
- 
- V**
- variables
    - fields [VFC-238](#)
    - in messages [VFC-238](#)
  - vc-class
    - ATM interfaces [HC-36](#), [HC-37](#), [HC-39](#)
    - ATM PVCs [HC-41](#)
    - ATM subinterfaces [HC-40](#)
    - configuring [HC-56](#)
    - creating [HC-56](#)
  - vc-class command [HC-37](#)
  - verify unicast source reachable-via command [IC-70](#)
  - verifying IP connectivity, CSC
    - MPLS Layer 3 VPN [MPC-445](#)
    - MPLS VPN over IP tunnel [MPC-368](#)
  - version v9 command [HC-262](#)
  - versions
    - hardware and software, displaying [SMC-225](#)
  - VFI (virtual forwarding instance)
    - adding under bridge domain [MPC-283](#)
    - associating bridge domain member [MPC-286](#)
    - associating pseudowires [MPC-284](#)
    - attaching pseudowire classes to pseudowires [MPC-288](#)
    - configuring AToM pseudowires [MPC-290](#)
    - disabling [MPC-292](#)
  - virtual interface
    - active/standby RPs [HC-229](#), [HC-350](#)
    - naming convention [HC-227](#), [HC-475](#)
    - null interface definition [HC-228](#)
    - switchover [HC-227](#)
  - virtual terminals
    - default line template
      - description [SMC-202](#)
      - modifying [SMC-205](#)
    - line template configuration mode
      - description [SMC-203](#)
    - line template guidelines [SMC-204](#)
    - user-defined line templates
      - configuring (example) [SMC-212](#)
      - description [SMC-202](#)
  - vty pools
    - configuring (example) [SMC-212](#)
    - creating [SMC-206](#)
    - default fault manager pool [SMC-204](#)
    - default vty pool [SMC-204](#)
    - description [SMC-204](#)
    - modifying [SMC-206](#)
  - virtualization
    - configuration (example) [VFC-60](#)
    - configuring [VFC-50](#)
    - overview [VFC-45](#)
  - virtual-link command [RC-238](#)
  - VLAN
    - figure, mode packet flow [MPC-233](#)
    - mode [MPC-232](#)
  - VLANs
    - 802.1Q frames tagging [HC-483](#)
    - configuring
      - bundles [HC-483](#)
      - IP address and subnet mask [HC-486](#)

- native VLAN [HC-488](#)
  - subinterfaces [HC-485](#)
  - displaying
    - VLAN interfaces [HC-487](#), [HC-494](#)
    - VLAN trunks [HC-487](#), [HC-494](#)
  - Layer 2 VPN
    - attachment circuit, configuring [HC-489](#), [HC-490](#)
    - Layer 2 protocol tunneling and data units, configuring [HC-491](#)
  - Layer 2 VPN support [HC-484](#)
  - MTU inheritance [HC-483](#)
  - native VLAN description [HC-483](#)
  - overview [HC-482](#)
  - subinterface overview [HC-483](#)
  - VLAN AC, assigning [HC-486](#)
  - VLAN subinterface, removing [HC-492](#)
  - volatile file system [VFC-250](#)
  - VP tunnel
    - configuring [HC-18](#), [HC-50](#)
    - creating [HC-18](#)
    - example [HC-57](#)
    - on ATM interfaces [HC-55](#)
  - VPLS (virtual private LAN services)
    - attachment circuits [MPC-268](#)
    - defining bridge domain [MPC-269](#)
    - defining signaling [MPC-269](#)
    - Layer 2 VPN, architecture [MPC-268](#)
    - simulating virtual bridge [MPC-268](#)
  - VPN monitoring
    - enhancements [SC-89](#)
    - per-IKE peer, function [SC-90](#)
    - summary status [SC-90](#)
  - VPN services
    - L2TPv3 [MPC-352](#)
    - MPLS [MPC-352](#)
  - VPNv4 address family command [RC-10](#)
  - VPNv4 and VPNv6 over the IP core using L2TPv3 tunnels [RC-42](#)
  - VPNv6 address family command [RC-10](#)
  - vp-tunnel command [HC-19](#)
  - vrf (AAA) command [SC-31](#)
  - vrf (IPSec) command [SC-149](#)
  - vrf (MPP) command [SC-246](#)
  - VRF (virtual routing and forwarding)
    - configuring backbone carrier core [MPC-445](#)
    - configuring CSC-PE routers [MPC-368](#)
  - VRF address family command [RC-9](#)
  - vrf address family submode,export route-target command [RC-101](#)
  - VRF command [RC-9](#)
  - vrf command (BFD) [HC-73](#)
  - VRF neighbor command [RC-9](#)
  - VRF neighbor address family command [RC-9](#)
  - vrf, IP SLA [MNC-54](#)
  - vrf-aware (IPSec) description [SC-149](#)
  - VRRP (Virtual Router Redundancy Protocol) [IC-218](#)
    - advertisement [IC-212](#)
    - customizing [IC-213](#)
    - description [IC-210](#)
    - enabling [IC-216](#)
    - IP protocol number [IC-213](#)
    - master virtual router [IC-212](#)
    - vrrp ipv4 command [IC-216](#)
  - VRRP Statistics, clearing [IC-219](#)
  - VSAs (vendor-specific attributes)
    - per VRF AAA [SC-30](#)
    - supported VSAs [SC-30](#)
  - vty pool command [SMC-208](#)
  - vty pool default command [SMC-208](#)
  - vty pool eem command [SMC-208](#)
- 
- ## W
- wait-to-restore (WTR) [HC-401](#)
  - warning messages [VFC-339](#)
  - wavelength division multiplexing (WDM) [HC-390](#)
  - weight command [RC-60](#)
  - withdrawal, MAC address

defining [MPC-271](#)

enabling [MPC-296](#)

fields [MPC-298](#)

WRED (weighted random early detection)

average queue size [QC-110](#)

IP Precedence [QC-109](#)

overview [QC-109](#)

TCP [QC-109](#)

uses [QC-109](#)

---

## X

X of Y threshold violation [MNC-119](#)

xconnects

configuring attachment circuits [MPC-343](#)

support [MPC-317](#)

---

## Y

yellow command [HC-440](#), [HC-456](#)