



TACACS+ Attribute-Value Pairs

The Cisco Secure Access Control Server Release 4.0 Solution Engine, hereafter referred to as ACS, supports Terminal Access Controller Access Control System (TACACS+) attribute-value (AV) pairs. You can enable different AV pairs for any supported attribute value.

Cisco IOS AV Pair Dictionary

To use the full range of the Cisco IOS AV-pair dictionary for TACACS+, the AAA client should use IOS version 11.3 or later. Cisco IOS 11.1 and 11.2 have only partial support for TACACS+ AV-pairs.



Note

If you specify a given AV pair in ACS, you must also enable the corresponding AV pair in the Cisco IOS software that is running on the AAA client. Therefore, you must consider which AV pairs your Cisco IOS release supports. If ACS sends an AV pair to the AAA client that the Cisco IOS software does not support, that attribute is not implemented.

For more information on TACACS+ AV pairs, refer to Cisco IOS documentation for the release of Cisco IOS that is running on your AAA clients.



Note

All TACACS+ values are strings. The concept of value *type* does not exist in TACACS+ as it does in Remote Access Dial-In User Service (RADIUS).

TACACS+ AV Pairs



Note

Beginning with ACS 2.3, some TACACS+ attributes no longer appear on the Group Setup page; because IP pools and callback supersede:

addr
addr-pool
callback-dialstring

Additionally, these attributes cannot be set via database synchronization, and **ip:addr=n.n.n.n** is not allowed as a Cisco vendor-specific attribute (VSA).

ACS supports many TACACS+ AV pairs. For descriptions of these attributes, refer to Cisco IOS documentation for the release of Cisco IOS that is running on your AAA clients. TACACS+ AV pairs supported in ACS are:

- acl=
- autocmd=
- callback-line
- callback-rotary
- cmd-arg=
- cmd=
- dns-servers=
- gw-password
- idletime=
- inacl#n
- inacl=
- interface-config=
- ip-addresses
- link-compression=
- load-threshold=n
- max-links=n
- nas-password
- nocallback-verify
- noescape=
- nohangup=
- old-prompts
- outacl#n
- outacl=
- pool-def#n
- pool-timeout=
- ppp-vj-slot-compression
- priv-lvl=
- protocol=
- route
- route#n
- routing=
- rte-ftr-in#n
- rte-ftr-out#n
- sap#n
- sap-fltr-in#n
- sap-fltr-out#n
- service=
- source-ip=
- timeout=
- tunnel-id
- wins-servers=
- zonelist=

TACACS+ Accounting AV Pairs

ACS supports many TACACS+ accounting AV pairs. For descriptions of these attributes, see Cisco IOS documentation for the release of Cisco IOS that is running on your AAA clients. TACACS+ accounting AV pairs supported in ACS are:

- bytes_in
- bytes_out
- cmd
- data-rate
- disc-cause
- disc-cause-ext
- elapsed_time
- event
- mlp-links-max
- mlp-sess-id
- nas-rx-speed
- nas-tx-speed
- paks_in
- paks_out
- port
- pre-bytes-in
- pre-bytes-out
- pre-paks-in
- pre-paks-out
- pre-session-time
- priv_level
- protocol
- reason
- service
- start_time
- stop_time
- task_id
- timezone
- xmit-rate

