



INDEX

A

AAL5 [D-8](#)

access domains

 creating [2-4](#)

assigning

 device roles [2-1](#)

ATM

 ATM over MPLS (ATMoMPLS) [D-8](#)

 defining an ATM policy with a CE [5-33](#)

 defining an ATM policy without a CE [5-36](#)

audience [iii-xi](#)

auditing

 service requests [9-1, 9-12](#)

autodiscovery, of L2 services [10-1](#)

C

cell relay over MPLS [D-8](#)

concepts

 Ethernet service definitions [D-2](#)

 Ethernet service term mappings [D-2, D-4](#)

 ISC terminology and supported network types [D-4](#)

 L2VPN service provisioning [D-5](#)

 Layer 2 terminology conventions [D-1](#)

 Layer 2 VPN concepts [D-1](#)

 mapping MEF terminologies to network technologies [D-3](#)

 MEF terminology conventions [D-1](#)

configlets

 ATM (port mode, pseudowire class, e-line, L2VPN group name, IOS XR device) [A-25](#)

 ATM over MPLS (VC mode) [A-23](#)

 ATM over MPLS (VP mode) [A-24](#)

ERS (EVPL) (1-to-1 VLAN translation) [A-6](#)

ERS (EVPL) (2-to-1 VLAN translation) [A-7](#)

ERS (EVPL) (NBI enhancements for L2VPN, IOS device) [A-9](#)

ERS (EVPL) (point-to-point) [A-3](#)

ERS (EVPL) (point-to-point, UNI port security) [A-4](#)

ERS (EVPL), EWS (EPL), ATM, or frame relay (additional template variables for L2VPN, IOS and IOS XR device) [A-14](#)

ERS (EVPL) and EWS (EPL) (local connect on e-line) [A-13](#)

ERS (EVPL) or EWS (EPL) (IOS XR device) [A-10](#)

ERS (pseudowire class, e-Line, L2VPN group name, IOS XR device) [A-8](#)

EWS (EPL) (hybrid) [A-18](#)

EWS (EPL) (NBI enhancements for L2VPN, IOS device) [A-22](#)

EWS (EPL) (point-to-point) [A-15](#)

EWS (EPL) (point-to-point, UNI port security, BPDU tunneling) [A-16](#)

EWS (EPL) (pseudowire class, e-line, L2VPN group name, IOS XR device) [A-21](#)

FlexUNI/EVC (local connect core connectivity, UNI, no port security, bridge domain) [A-37](#)

FlexUNI/EVC (local connect core connectivity, UNI port security) [A-35](#)

FlexUNI/EVC (pseudowire core connectivity, UNI, and pseudowire tunneling) [A-32](#)

FlexUNI/EVC (pseudowire core connectivity, UNI, without port security, with bridge domain) [A-31](#)

FlexUNI/EVC (pseudowire core connectivity, UNI port security) [A-30](#)

FlexUNI/EVC (VPLS core connectivity, no UNI port security) [A-34](#)

FlexUNI/EVC (VPLS core connectivity, UNI port security) [A-33](#)

frame relay (DLCI mode) [A-27](#)

frame relay over MPLS [A-26](#)

- overview [A-2](#)
- samples (see configlet examples) [A-2](#)
- viewing [9-9](#)
- VPLS (multipoint, EMS/EP-LAN), BPDU tunneling [A-29](#)
- VPLS (multipoint, ERMS/EVP-LAN) [A-28](#)

configuration

- checking of in FlexUNI/EVC [3-5](#)

configuring

- device settings [2-2](#)
- switches in VTP transparent mode [2-2](#)
- the network [1-1](#)
- transport mode when pseudowire classes are not supported [2-13](#)

conventions

- Layer 2 terminology conventions [D-1](#)

creating

- access domains [2-4](#)
- creating an EWS (EPL) L2VPN service request without a CE [6-16](#)
- devices [2-1](#)
- ERS (EVPL), ATM, or frame relay L2VPN service request without a CE [6-11](#)
- ERS (EVPL), ATM, or frame relay L2VPN with a CE service requests [6-2](#)
- EWS (EPL) L2VPN service request with a CE [6-8](#)
- FlexUNI/EVC policies
 - FlexUNI
 - creating policies for [3-1](#)
 - FlexUNI/EVC service requests [4-2](#)
 - L2VPN policies [5-1](#)
 - L2VPN service requests [6-2](#)
 - NPC links using autodiscovery [2-10](#)
 - NPCs [2-8](#)
 - pseudowire classes [2-11](#)
 - pseudowire classes for IOS XR devices [2-10](#)
 - ring-only NPCs [2-9](#)
 - VC ID pools [2-7](#)
 - VLAN pools [2-5](#)
 - VPLS policies [7-1](#)

- VPLS service requests [8-2](#)
- VPLS service requests with a CE [8-2](#)
- VPLS service requests without a CE [8-6](#)

customers

- defining [2-4](#)
- setting up [1-2](#)

D

data files

- creating a data file in the service request workflow [B-14](#)
- creating data files during service request creation [B-10](#)
- using in FlexUNI/EVC service requests [4-17](#)

defining

- customers and their sites [2-4](#)
- Ethernet/EMS (EP-LAN) policies with a CE [7-32](#)
- Ethernet/EMS (EP-LAN) policies without a CE [7-38](#)
- Ethernet/ERMS (EVP-LAN) policies with a CE [7-23](#)
- Ethernet/ERMS (EVP-LAN) policies without a CE [7-27](#)
- FlexUNI/EVC policies [3-5](#)
- L2VPN group names for IOS XR Devices [2-14](#)
- L2VPN policies [5-1](#)
- MPLS/ERMS (EP-LAN) policies with a CE [7-11](#)
- MPLS/ERMS (EP-LAN) policies without a CE [7-16](#)
- MPLS/ERMS (EVP-LAN) policies with a CE [7-3](#)
- MPLS/ERMS (EVP-LAN) policies without a CE [7-7](#)
- service provider and its regions [2-3](#)
- VPLS policies [7-1](#)
- VPNs [2-4](#)

definitions

- Ethernet service definitions [D-2](#)
- Ethernet service term mappings [D-2, D-4](#)
- ISC terminology and supported network types [D-4](#)
- mapping MEF terminologies to network technologies [D-3](#)
- MEF terminology conventions [D-1](#)

deploying, service requests [9-1,9-2](#)

devices

- assigning roles [2-1](#)
- configuring device settings to support ISC [2-2](#)
- creating target devices [2-1](#)
- roles in FlexUNI/EVC [3-4](#)
- setting the loopback addresses on N-PE devices [2-2](#)
- setting up [1-2](#)
- setting up devices for IOS XR support [2-3](#)

discovery, of L2 services [10-1](#)

documentation, obtaining [iii-xiv](#)

E

EPL

- Ethernet wire service (EWS or EPL) [D-5](#)
- L2VPN Ethernet over MPLS [D-5](#)
- point-to-point Ethernet services [D-5](#)

ERS

- defining an Ethernet ERS (EVPL) Policy with a CE [5-3](#)
- defining an Ethernet ERS (EVPL) policy without a CE [5-8](#)
- Ethernet relay service (ERS or EVPL) [D-5](#)
- L2VPN Ethernet over MPLS [D-5](#)
- multipoint ERS (EVP-LAN) for an Ethernet-based provider core [D-13](#)
- multipoint ERS (EVP-LAN) for an MPLS-based provider core [D-11](#)
- point-to-point Ethernet services [D-5](#)

Ethernet private line service (see EPL) [D-1](#)

Ethernet relay service (ERS or EVPL) [D-5](#)

Ethernet relay service (see ERS) [D-1](#)

Ethernet virtual private line service (see EVPL) [D-1](#)

Ethernet wire service (EWS or EPL) [D-5](#)

Ethernet wire service (see EWS) [D-1](#)

EVPL

- Ethernet relay service (ERS or EVPL) [D-5](#)
- L2VPN Ethernet over MPLS [D-5](#)
- point-to-point Ethernet services [D-5](#)

EWS

- defining an Ethernet EWS (EPL) policy with a CE [5-14](#)

- defining an Ethernet EWS (EPL) policy without a CE [5-22](#)

Ethernet wire service (EWS or EPL) [D-5](#)

L2VPN Ethernet over MPLS ([D-5](#))

- multipoint EWS (EP-LAN) for an Ethernet-based provider core [D-13](#)

- multipoint EWS (EP-LAN) for an MPLS-based provider core [D-11](#)

- point-to-point Ethernet services [D-5](#)

examples (see configlet examples) [A-2](#)

examples, FlexUNI/EVC platform support [3-3,3-4](#)

F

FlexUNI/EVC

- CE directly connected and FlexUNI case [3-5](#)

- CE directly connected and no FlexUNI/EVC case [3-5](#)

- CE directly connected case [3-4](#)

- CE not directly connected and no FlexUNI case [3-5](#)

- creating service requests for [4-2](#)

- device roles [3-4](#)

- enabling template association in FlexUNI/EVC policies [3-19](#)

- features [3-2](#)

- local core connectivity in service requests [4-6](#)

- managing FlexUNI/EVC service requests [4-1](#)

- modifying FlexUNI/EVC service requests [4-16](#)

- overview of support in ISC [3-1](#)

- platform support for [3-3](#)

- pseudowire core connectivity in service requests [4-3](#)

- saving FlexUNI/EVC service requests [4-17](#)

- service requests, introduction [4-1](#)

- setting direct connect links in service requests [4-8](#)

- setting FlexUNI attributes [3-9](#)

- setting interface attributes [3-14](#)

- setting links with L2 access nodes in service requests [4-15](#)

- setting service attributes [3-10](#)
- setting service request details [4-2](#)
- setting the service options [3-7](#)
- setting up links to the N-PE in service requests [4-8](#)
- setting VLAN matching criteria attributes [3-12](#)
- setting VLAN rewrite criteria attributes [3-12](#)
- topology overview [3-4](#)
- using templates and data files with FlexUNI/EVC service requests [4-17](#)
- VPLS core connectivity in service requests [4-5](#)

frame relay

- defining a frame relay policy with a CE [5-28](#)
- defining a frame relay policy without a CE [5-31](#)
- over MPLS (FRoMPLS) [D-9](#)

G

- getting started tasks [1-1](#)
 - installing ISC and configuring the network [1-1](#)
 - overview [1-1](#)
 - setting up basic ISC services [1-2](#)
 - setting up customers [1-2](#)
 - setting up devices [1-2](#)
 - setting up ISC resources for L2VPN and VPLS services [1-3](#)
 - setting up NPC [1-3](#)
 - setting up providers [1-2](#)
 - setting up the N-PE loopback address [1-3](#)
 - setting up VPNs [1-3](#)
 - terminology conventions [1-4](#)
 - working with L2VPN and VPLS policies and service requests
 - policies
 - working with L2VPN policies [1-4](#)
- group names
 - defining for IOS XR devices [2-14](#)

- installing, ISC [1-1](#)
- IOS XR
 - setting up devices for IOS XR support [2-3](#)
- ISC, setting up basic ISC services [1-2](#)
- ISC services, setting up [2-1](#)

L

- L2
 - reports [11-1](#)
 - service discovery [10-1](#)
- L2VPN
 - service requests, creating [6-2](#)
 - service requests, introducing [6-1](#)
- L2VPN service requests
 - modifying [6-20](#)
 - saving [6-26](#)
- local
 - core connectivity in FlexUNI/EVC service requests [4-6](#)
- loopback addresses
 - setting the loopback addresses on N-PE devices [2-2](#)
 - setting up [1-3](#)

M

- managing
 - L2VPN service requests [6-1](#)
 - VPLS service requests [8-1](#)
- MEF
 - Ethernet service term mappings [D-2](#)
 - terminology conventions [D-1](#)
- Metro Ethernet Forum (see MEF) [D-1](#)
- modifying
 - FlexUNI/EVC service requests [4-16](#)
 - L2VPN service requests [6-20](#)

- pseudowire class objects [2-12](#)
- VPLS service requests [8-9](#)
- monitoring
 - service requests [9-1, 9-10](#)
- multipoint
 - multipoint ERS (EVP-LAN) for an Ethernet-based provider core [D-13](#)
 - multipoint ERS (EVP-LAN) for an MPLS-based provider core [D-11](#)
 - multipoint EWS (EP-LAN) for an Ethernet-based provider core [D-13](#)
 - multipoint EWS (EP-LAN) for an MPLS-based provider core [D-11](#)

N

- Named Physical Circuits (see NPCs) [2-8](#)
- negate templates (see templates) [B-11](#)
- network, configuration [1-1](#)
- NPCs
 - creating [2-8](#)
 - creating NPC links using autodiscovery [2-10](#)
 - creating ring-only NPCs [2-9](#)
 - setting up [1-3](#)
- N-PEs
 - setting the loopback addresses on N-PE devices [2-2](#)
 - setting up links to in FlexUNI/EVC service requests [4-8](#)

O

- objective [iii-xi](#)
- organization [iii-xi](#)

P

- policies
 - ATM with a CE [5-33](#)
 - ATM without a CE [5-36](#)
 - creating L2VPN policies [5-1](#)

- defining FlexUNI/EVC policies [3-5](#)
- defining L2VPN policies [5-1](#)
- defining VPLS policies [7-1](#)
- Ethernet/EMS (EP-LAN) with a CE [7-32](#)
- Ethernet/EMS (EP-LAN) without a CE [7-38](#)
- Ethernet/ERMS (EVP-LAN) with a CE [7-23](#)
- Ethernet/ERMS (EVP-LAN) without a CE [7-27](#)
- Ethernet ERS (EVPL) with a CE [5-3](#)
- Ethernet ERS (EVPL) without a CE [5-8](#)
- Ethernet EWS (EPL) with a CE [5-14](#)
- Ethernet EWS (EPL) without a CE [5-22](#)
- frame relay with a CE [5-28](#)
- frame relay without a CE [5-31](#)
- MPLS/ERMS (EP-LAN) with a CE [7-11](#)
- MPLS/ERMS (EP-LAN) without a CE [7-16](#)
- MPLS/ERMS (EVP-LAN) with a CE [7-3](#)
- MPLS/ERMS (EVP-LAN) without a CE [7-7](#)
- using VLAN translation [C-2](#)
- working with VPLS policies [1-4](#)

- providers
 - defining [2-3](#)
 - setting up [1-2](#)
- provisioning, L2VPN service provisioning [D-5](#)
- pseudowire
 - core connectivity in FlexUNI/EVC service requests [4-3](#)
- pseudowire classes
 - creating [2-11](#)
 - creating for IOS XR devices [2-10](#)
 - modifying [2-12](#)

R

- regions
 - defining [2-3](#)
- related documentation [iii-xii](#)
- reports
 - accessing [11-1](#)
 - creating custom L2 and VPLS reports [11-11](#)

- generating L2 and VPLS reports [11-1](#)
- L2 and VPLS report [11-2](#)
- L2 end-to-end wire report [11-3](#)
- L2 PE service report [11-6](#)
- L2 VPN report [11-7](#)
- overview [11-1](#)
- VPLS attachment circuit report [11-8](#)
- VPLS PE service report [11-10](#)
- VPLS VPN report [11-11](#)

S

- sample configlets (see configlets) [A-1](#)

- saving

- L2VPN service requests [6-26](#)
 - VPLS service requests [8-12](#)

- security, guidelines [iii-xiv](#)

- service options, setting in FlexUNI/EVC policies [3-7](#)

- service policies, associating templates and data files to a policy [B-4](#)

- service providers, defining [2-3](#)

- service requests [9-3, C-3](#)

- associating templates and data files to a service request [B-9](#)

- auditing [9-1, 9-12](#)

- creating data files during service request creation [B-10](#)

- creating FlexUNI/EVC service requests [4-2](#)

- creating L2VPN service requests [6-2](#)

- creating VPLS service requests [8-2](#)

- decommissioning service requests with templates [B-15](#)

- deploying [9-1](#)

- ERS (EVPL), ATM, or frame relay L2VPN with a CE [6-2](#)

- ERS (EVPL), ATM, or frame relay L2VPN without a CE [6-11](#)

- EWS (EPL) L2VPN service request with a CE [6-8](#)

- EWS (EPL) L2VPN without a CE [6-16](#)

- introducing L2VPN service requests [6-1](#)

- managing FlexUNI/EVC service requests [4-1](#)

- managing L2VPN service requests [6-1](#)

- managing VPLS service requests [8-1](#)

- modifying FlexUNI/EVC service requests [4-16](#)

- modifying VPLS service requests [8-9](#)

- monitoring [9-1, 9-10](#)

- pre-deployment changes made to [9-1](#)

- saving FlexUNI/EVC service requests [4-17](#)

- saving VPLS service requests [8-12](#)

- service deployment [9-2](#)

- setting direct connect links in FlexUNI/EVC service requests [4-8](#)

- setting links with L2 access nodes in FlexUNI/EVC service requests [4-15](#)

- setting service request details for FlexUNI/EVC [4-2](#)

- states [9-4](#)

- states (table of) [9-5](#)

- user operations on [9-6](#)

- viewing configlets of [9-9](#)

- viewing details of [9-7](#)

- viewing history [9-9](#)

- viewing links [9-8](#)

- VPLS, introducing [8-1](#)

- VPLS with a CE [8-2](#)

- VPLS without a CE [8-6](#)

- services

- Ethernet relay service (ERS or EVPL) [D-5](#)

- Ethernet wire service (EWS or EPL) [D-5](#)

- multipoint ERS (EVP-LAN) for an Ethernet-based provider core [D-13](#)

- multipoint ERS (EVP-LAN) for an MPLS-based provider core [D-11](#)

- multipoint EWS (EP-LAN) for an Ethernet-based provider core [D-13](#)

- multipoint EWS (EP-LAN) for an MPLS-based provider core [D-11](#)

- point-to-point Ethernet (EWS and ERS) (EPL and EVPL) [D-5](#)

- setting

- FlexUNI/EVC attributes [3-9](#)

- FlexUNI/EVC service attributes [3-10](#)

- VLAN matching criteria attributes in FlexUNI/EVC policies [3-12](#)
- VLAN rewrite criteria attributes in FlexUNI/EVC policies [3-12](#)
- setting interface attributes in FlexUNI/EVC policies [3-14](#)
- states
 - service request states [9-4](#)
 - table of service request states [9-5](#)
- subtemplates (see templates) [B-10](#)
- support, obtaining [iii-xiv](#)
- switches, configuring switches in VTP transparent mode [2-2](#)

T

- templates
 - associating in FlexUNI/EVC policies [3-19](#)
 - associating subtemplates during service provisioning [B-9](#)
 - associating templates and data files to a policy [B-4](#)
 - associating templates to a service request [B-9](#)
 - choosing a template in the service request workflow [B-12](#)
 - decommissioning service requests with added templates [B-15](#)
 - decommissioning service requests with added templates. [B-15](#)
 - default subtemplate matching criteria [B-10](#)
 - overview [B-1](#)
 - overview of template support in ISC policies [B-4](#)
 - overview of template use in service requests [B-8](#)
 - summary of template manager features [B-1](#)
 - template and data file workflow [B-3](#)
 - using in FlexUNI/EVC service requests [4-17](#)
 - using negate templates to decommission template configurations [B-11](#)
 - using templates and data files with service requests [B-12](#)
 - using templates with ISC policies [B-4](#)
 - using templates with service requests [B-8](#)
 - viewing templates from the service requests window [B-16](#)

- terminology conventions [1-4](#)
 - Ethernet service terminology mappings [1-5](#)
- topology
 - for ATM/MPLS [D-8](#)
 - for Ethernet-based VPLS [D-13](#)
 - for frame relay over MPLS [D-9](#)
 - for MPLS-based VPLS [D-11](#)
 - L2VPN Ethernet over MPLS [D-5](#)
 - overview for FlexUNI/EVC [3-4](#)
- transport mode, configuring [2-13](#)

V

- VC ID pools, creating [2-7](#)
- verifying [9-3](#)
 - service requests [9-3](#)
- viewing, service request details [9-7](#)
- VLAN pools, creating [2-5](#)
- VLAN translation
 - 1-to-1 VLAN translation [C-3](#)
 - 2-to-1 VLAN translation [C-4](#)
 - creating policies using [C-2](#)
 - creating service requests using [C-3](#)
 - deleting a service request using VLAN translation [C-5](#)
 - failed service requests when hardware does not support it [C-6](#)
 - modifying a service request using VLAN translation [C-5](#)
 - on the 3750 [C-6](#)
 - on the 7600 [C-6](#)
 - overview [C-1](#)
 - platform-specific usage notes [C-6](#)
 - setting up VLAN translation [C-1](#)
 - specifying no VLAN translation [C-3](#)
 - using [C-3](#)
- VPLS
 - core connectivity in FlexUNI/EVC service requests [4-5](#)
 - defining VPLS policies [7-1](#)

for an Ethernet-based (L2) provider core [D-13](#)

policies, creating [7-1](#)

reports [11-1](#)

service provisioning concepts [D-10](#)

service requests

 creating [8-2](#)

 introducing [8-1](#)

 modifying [8-9](#)

 saving [8-12](#)

topology for Ethernet-based VPLS [D-13](#)

topology for MPLS-based VPLS [D-11](#)

VPNs

 defining [2-4](#)

 setting up [1-3](#)