



INDEX

Numerics

6VPE

- IPv6 and 6VPE support in MPLS VPN [4-1](#)
- overview [4-1](#)

A

access domains

- creating [2-12](#)
- management [12-11](#)

access ports [12-11](#)

addresses

- address space and routing separation [E-8](#)
- address space separation [E-8](#)
- IP addresses [5-2](#)

address pools, creating IPv4 address pools [2-16](#)

auditing

- configuration audit [6-29](#)
- MPLS VPN service requests [4-11](#)
- performing a configuration audit [6-30](#)
- performing a functional audit [6-28](#)
- service requests [6-28](#)
- where to find a configuration audit [6-30](#)
- where to find a functional audit [6-29](#)
- why a configuration audit could fail [6-30](#)
- why a functional audit could fail [6-29](#)

authentication [E-13](#)

autonomous systems

- benefits [13-2](#)
- exchanging VPN routing information [13-4](#)
- overview [13-1](#)
- routing between autonomous systems [13-3](#)

routing between subautonomous systems in a confederation [13-8](#)

spanning multiple autonomous systems [13-1](#)

using ISC to span multiple autonomous systems [13-9](#)

using templates to support inter-autonomous system solutions [13-11](#)

B

BGP

multipath load sharing and maximum path configuration [5-32](#)

protocol [5-18](#)

removing a multipath configuration [5-34](#)

C

cable services

benefits of cable MPLS VPNs [10-1](#)

cable MPLS VPN network [10-2](#)

cable VPN configuration overview [10-4](#)

cable VPN interfaces and subinterfaces [10-5](#)

creating a cable subinterface service request [10-6](#)

creating cable link service requests [10-10](#)

creating the service requests [10-6](#)

management VPN in the cable network [10-3](#)

overview of MPLS VPN cable services [10-1](#)

provisioning cable services [10-1](#)

provisioning cable services in ISC [10-5](#)

carrier supporting carrier (see CSC) [11-1](#)

CERCs, creating [2-32](#)

CE routing communities (see CERCs) [E-6](#)

- CEs
 - defining a CE as an MCE [9-8](#)
 - giving only default routes to CE [5-12](#)
 - managed CE routers [9-2](#)
 - specifying interface parameters [5-4](#)
 - unmanaged CE routers [9-1](#)
- CLEs, adding a CLE to a service request [6-25](#)
- configlet examples
 - CE-PE L3 MPLS VPN [A-7](#)
 - CE-PE L3 MPLS VPN (BGP with full-mesh) [A-5](#)
 - CE-PE L3 MPLS VPN (BGP with SOO) [A-6](#)
 - CE-PE L3 MPLS VPN (Q-in-Q/Second VLAN ID) [A-16](#)
 - L2 Access into L3 MPLS VPN [A-3](#)
 - N-PE L3 MPLS VPN (IPv4, IOS XR, OSPF) [A-8](#)
 - N-PE L3 MPLS VPN (IPv6, IOS XR, EIGRP) [A-12](#)
- configlets
 - overview [A-1](#)
 - sample configlets [A-1](#)
 - viewing configlets generated by a service request [6-31](#)
 - viewing configlets generated by the MPLS VPN service request [6-13](#)
 - viewing configlets on IOS XR devices [6-32](#)
 - VRF-related configlets [4-4](#)
- configuration audit [6-29](#)
 - performing a configuration audit [6-30](#)
 - where to find a configuration audit [6-30](#)
 - why a configuration audit could fail [6-30](#)
- configuration files, editing [6-33](#)
- configurations, collecting [2-4](#)
- configuring, ETTH [12-12](#)
- copying, VRF objects [3-5](#)
- CPEs, creating [2-8](#)
- creating
 - access domains [2-12](#)
 - cable link service requests [10-10](#)
 - cable subinterface service requests [10-6](#)
 - CERCs [2-32](#)
 - CPEs [2-8](#)
 - customers [2-8](#)
 - custom reports [14-7](#)
 - device groups [2-6](#)
 - devices [2-2](#)
 - IPv4 address pools [2-16](#)
 - logical devices [2-3](#)
 - MCE service requests [9-10](#)
 - MPLS VPN PE-CE service requests [7-8](#)
 - MPLS VPNs [2-22](#)
 - multicast pools [2-16](#)
 - multicast VPNs [2-26](#)
 - MVRFCE PE-CE service policies [8-4](#)
 - MVRFCE PE-CE service requests [8-8](#)
 - MVRFCE PE-noCE service requests [8-14](#)
 - new VRF objects [3-2](#)
 - PE-CE service policies [7-4](#)
 - PE-CE service requests [7-8](#)
 - PE-noCE service policies [7-6, 8-6](#)
 - PE-noCE service requests [7-12](#)
 - PEs [2-11](#)
 - providers [2-10](#)
 - regions [2-11](#)
 - resource pools [2-15](#)
 - route distinguisher pools [2-17](#)
 - route target pools [2-18](#)
 - site of origin pools [2-19](#)
 - sites [2-8](#)
 - unmanaged MVRFCEs [8-19](#)
 - VC ID pools [2-20](#)
 - VLAN pools [2-21](#)
 - VPNs [2-22](#)
- CSC
 - backbone network with BGP/MPLS VPN service provider customer carrier [11-3](#)
 - backbone network with ISP customer carrier [11-1](#)
 - defining CSC service policies [11-5](#)
 - IPv4 BGP label distribution [11-4](#)
 - ISC configuration options [11-4](#)
 - LDP/IGP [11-4](#)

- overview [11-1](#)
- provisioning [11-1, 11-5](#)
- service requests [11-5](#)
- support for [5-12](#)

customers, creating [2-8](#)

D

data files

- creating a data file in the service request workflow [B-14](#)
- creating data files during service request creation [B-10](#)

defining

- CSC service policies [11-5](#)
- MPLS VPN service policies [5-2](#)
- VPN for the PE-CE link [7-3](#)
- VPNs [2-22](#)
- VRF and VPN information [5-29](#)
- VRF service requests [3-11](#)

deleting

- VRF objects [3-10](#)
- VRF service requests [3-14](#)

deploying

- service requests [6-25](#)
- VRF service requests [3-13](#)

device groups, creating [2-6](#)

devices

- creating [2-2](#)
- creating logical devices [2-3](#)
- how ISC accesses network devices [6-5](#)
- setting up for IOS XR support [2-6](#)

E

editing

- configuration files [6-33](#)
- multi-VRF edit mode [3-7](#)
- PEs [2-12](#)

- service policies [5-1](#)
- single-VRF edit mode [3-7](#)

EIGRP, protocol [5-24](#)

encapsulation

- interface types and their corresponding encapsulations [5-6](#)

Ethernet-to-the-home (see ETTH) [12-9](#)

ETTH

- configuring [12-12](#)
- implementation [12-11](#)

F

full mesh, configurations [E-8](#)

functional audit [6-28](#)

- performing a functional audit [6-28](#)
- where to find a functional audit [6-29](#)
- why a functional audit could fail [6-29](#)

H

hub and spoke, configurations [E-7](#)

I

IGM, with MVR [12-11](#)

independent VRF management [3-1](#)

independent VRF management, overview of [3-1](#)

inter-AS

- 10B hybrid model [13-11](#)
- creating templates for [13-12](#)
- RT-rewrite [13-12](#)

interfaces

- interface types and their corresponding encapsulations [5-6](#)

intranets and extranets [E-2](#)

IOS

- comparison of IOS and IOS XR [4-3](#)
- comparison of IOS and IOS XR device configlets [4-3](#)

IOS XR

- comparison of IOS and IOS XR [4-3](#)
 - comparison of IOS and IOS XR device configlets [4-3](#)
 - multicast routing on IOS XR devices [4-6](#)
 - viewing configlets on IOS XR devices [6-32](#)
- IP addresses [5-2](#)
- resolution of [E-15](#)
 - specifying the IP address scheme [5-8](#)

IPv4, routing information [6-14](#)IPv6 [4-1](#)

- interface-related configlets [4-4](#)
- inventory and device management [4-7](#)
- IPv6 and 6VPE features not supported in ISC 5.0.1 [4-11](#)
- IPv6 and 6VPE support in MPLS VPN [4-1](#)
- ISC and MPLS VPN updates to support IPv6 and 6VPE [4-7](#)
- overview [4-1](#)
- routing information [6-15](#)
- using EIGRP as the PE-CE routing protocol [4-5](#)
- using OSPF as the PE-CE routing protocol [4-4](#)
- using static as the PE-CE routing protocol [4-5](#)
- VPN creation and configuration [4-8](#)
- VPN provider edge router (6VPE) [4-2](#)
- VRF object support [4-8](#)

ISC

- overview of services [2-1](#)
- service activation [1-1](#)
- setting up services for [2-1](#)

Llabel spoofing [E-12](#)LDP authentication [E-13](#)

links

- adding PE-CE links to management VPNs [9-14](#)
- defining a VPN for the PE-CE link [7-3](#)
- MPLS VPN PE-CE link overview [7-1](#)
- MVRFCE PE-CE link overview [8-1](#)

provisioning multi-VRFCE PE-CE links [8-1](#)provisioning regular PE-CE links [7-1](#)

logs

- monitoring task logs [2-5](#)
- used in troubleshooting [C-1](#)

loopback, using existing loopback interface number [5-10](#)**M**

management networks

- advantages of [9-6](#)
- defining CE as MCE [9-8](#)
- implementation techniques [9-4](#)
- management CE (MCE) [9-5](#)
- management PE (MPE) [9-5](#)
- management VPN [9-5](#)
- out-of-band technique [9-7](#)
- overview [9-1](#)
- provisioning a management CE in ISC [9-8](#)
- subnets [9-3](#)

maximum path, BGP multipath load sharing and maximum path configuration [5-32](#)

MCEs

- creating MCE service requests [9-10](#)
- defining a CE as an MCE [9-8](#)

modifying

- deployed VRF objects [3-9](#)
- non-deployed VRF objects [3-7](#)
- VRF service requests [3-14](#)

monitoring

- service requests [6-27](#)
- task logs [2-5](#)

MP-BGP security features [E-14](#)MPLS reports (see reports) [14-1](#)MPLS VPNs [4-9](#)

- concepts [E-1](#)
- creating [2-22](#)
- getting started [1-1](#)
- overview of MPLS VPN cable services [10-1](#)

- policies [1-2](#)
- prerequisites [1-1](#)
- prerequisite tasks [7-2](#)
- reports [4-11](#)
- security [E-8](#)
- service policies [5-1](#)
- service provisioning [4-9](#)
- service request auditing [4-11](#)
- service requests [1-2, 6-1](#)
- service requests (see also service requests) [4-10](#)
- topology example [6-6](#)

multicast, creating multicast VPNs [2-26](#)

multicast pools, creating [2-16](#)

multicast routing, on IOS XR devices [4-6](#)

multipath

- BGP multipath load sharing and maximum path configuration [5-32](#)
- removing a multipath configuration [5-34](#)

multi-VRF, creating a service request for [6-15](#)

multi-VRFCEs (see MVRFCEs) [8-1](#)

MVRFCEs

- creating an unmanaged MVRFCE [8-19](#)
- creating MVRFCE PE-CE service policies [8-4](#)
- creating MVRFCE PE-CE service requests [8-8](#)
- creating MVRFCE PE-noCE service requests [8-14](#)
- defining VPN for MVRFCE PE-CE links [8-3](#)
- MVRFCE PE-CE link overview [8-1](#)
- prerequisite tasks for [8-3](#)
- provisioning MVRFCE PE-CE links [8-1](#)

N

negate templates (see templates) [B-11](#)

networks

- backbone networks with BGP/MPLS VPN service provider customer carrier [11-3](#)
- backbone networks with ISP customer carrier [11-1](#)
- full mesh [E-8](#)
- hub and spoke [E-7](#)

- label spoofing [E-12](#)
- management network subnets [9-3](#)
- overview of the ISC management network [9-1](#)
- resistance to attacks [E-10](#)
- topology [7-2, 8-2](#)

NPC ring topology [12-1](#)

- configuring [12-5](#)
- creating ring of three PE-CLEs [12-2](#)
- overview [12-1](#)

O

OSPF, protocol [5-21](#)

out-of-band technique [9-7](#)

P

PEs

- creating [2-11](#)
- creating a PE-only service request [6-20](#)
- editing [2-12](#)
- specifying interface parameters [5-4](#)

prerequisites, for MPLS VPN [7-2](#)

protocols

- BGP [5-18](#)
- EIGRP [5-24](#)
- for cable services [5-28](#)
- OSPF [5-21](#)
- RIP [5-14](#)
- setting static routing protocol Attributes (for IPv4 and IPv6) [6-13](#)
- static protocol chosen [5-12](#)

providers, creating [2-10](#)

provisioning

- cable services [10-1](#)
- cable services in ISC [10-5](#)
- CSC [11-1](#)
- management CEs in ISC [9-8](#)
- management VPN [9-1](#)

multiple devices [12-1](#)
 MVRFCE PE-CE links [8-1](#)
 regular PE-CE links [7-1](#)
 PVLAN (protected ports) [12-11](#)

Q

Q-in-Q, usage notes [6-10](#)

R

regions, creating [2-11](#)
 reports
 6VPE supported devices report [14-6](#)
 accessing MPLS reports [14-1](#)
 creating custom reports [14-7](#)
 generating MPLS reports [14-1](#)
 MPLS PE service report [14-3](#)
 MPLS service request report [14-4](#)
 MPLS service request report - 6VPE [14-5](#)
 MPLS VPNs [4-11](#)
 overview [14-1](#)
 running reports [14-2](#)
 residential service [12-15](#)
 policy for residential services over shared VLAN [12-16](#)
 resource pools [4-9](#)
 creating [2-15](#)
 overview [2-15](#)
 ring topology (see NPC ring topology) [12-1](#)
 RIP, protocol [5-14](#)
 route distinguisher pools, creating [2-17](#)
 route distinguishers [E-5](#)
 routes
 giving only default routes to CE [5-12](#)
 redistribution of IP routes [5-12](#)
 route target communities [E-6](#)
 route target pools, creating [2-18](#)
 route targets [E-5](#)

routing
 authentication [E-13](#)
 IPv4 routing information [6-14](#)
 IPv6 routing information [6-15](#)
 separation [E-9](#)
 routing protocols
 securing [E-10](#)
 specifying the routing protocol for a service [5-11](#)

S

searching
 for VRF objects in the ISC repository [3-7](#)
 for VRF service requests [3-15](#)
 Second VLAN ID, usage notes [6-10](#)
 security
 address space and routing separation [E-8](#)
 address space separation [E-8](#)
 ensuring VPN isolation [E-15](#)
 hiding the MPLS core structure [E-9](#)
 IP address resolution [E-15](#)
 label spoofing [E-12](#)
 LDP authentication [E-13](#)
 MP-BGP security features [E-14](#)
 of MPLS VPNs [E-8](#)
 PE-CE interface [E-12](#)
 resistance to attacks [E-10](#)
 routing authentication [E-13](#)
 routing separation [E-9](#)
 securing the MPLS core [E-12](#)
 securing the routing protocol [E-10](#)
 separation of CE-PE links [E-13](#)
 trusted devices [E-12](#)
 service activation of ISC [1-1](#)
 service policies [4-9](#)
 associating templates and data files to a policy [B-4](#)
 associating templates with [5-34](#)
 creating a PE-CE service policy [7-4](#)
 creating a PE-noCE service policy [7-6](#)

- creating MPLS VPN PE-CE service policies [7-3](#)
 - creating MVRFCE PE-CE service policies [8-4](#)
 - creating PE-noCE service policies [8-6](#)
 - CSC [11-5](#)
 - defining [5-2](#)
 - editing [5-1](#)
 - MPLS VPN [4-9](#)
 - MPLS VPNs [5-1](#)
 - overview [5-1](#)
 - PE-CE service policy overview [7-3](#)
 - service provisioning, MPLS VPN [4-9](#)
 - service requests
 - adding a CLE to a service request [6-25](#)
 - associating templates and data files to a service request [B-9](#)
 - auditing [6-28](#)
 - cable services [10-6](#)
 - creating a cable subinterface service request [10-6](#)
 - creating a multi-VRF service request [6-15](#)
 - creating an MPLS VPN PE-CE service request [6-7](#)
 - creating a PE-only service request [6-20](#)
 - creating cable link service requests [10-10](#)
 - creating data files during service request creation [B-10](#)
 - creating MCE service requests [9-10](#)
 - creating MPLS VPN PE-CE service requests [7-8](#)
 - creating MVRFCE PE-CE service requests [8-8](#)
 - creating MVRFCE PE-noCE service requests [8-14](#)
 - creating PE-CE service requests [7-8](#)
 - creating PE-noCE service requests [7-12](#)
 - CSC [11-5](#)
 - decommissioning service requests with templates [B-15](#)
 - deploying [6-25](#)
 - examples of creating MPLS VPN service requests [6-6](#)
 - monitoring [6-27](#)
 - MPLS VPNs [4-10, 6-1](#)
 - overview [6-1](#)
 - provisioning using a unique route distinguisher [2-29](#)
 - residential services [12-18](#)
 - state transition paths for ISC service requests [D-1](#)
 - summary of states [6-3](#)
 - transition states [6-1, D-1](#)
 - user operations on [6-4](#)
 - viewing configlets generated by a service request [6-31](#)
 - viewing configlets generated by the MPLS VPN service request [6-13](#)
 - services, enhancements for [6-5](#)
 - setting up, devices for IOS XR support [2-6](#)
 - site of origin pools, creating [2-19](#)
 - sites, creating [2-8](#)
 - specifying
 - IP address scheme [5-8](#)
 - PE and CE interface parameters [5-4](#)
 - routing protocol for a service [5-11](#)
 - states, transitions of [6-1](#)
 - static
 - setting static routing protocol Attributes (for IPv4 and IPv6) [6-13](#)
 - static protocol [5-12](#)
 - subtemplates (see templates) [B-10](#)
-
- ## T
- templates
 - associating subtemplates during service provisioning [B-9](#)
 - associating templates and data files to a policy [B-4](#)
 - associating templates to a service request [B-9](#)
 - choosing a template in the service request workflow [B-12](#)
 - creating inter-AS templates [13-12](#)
 - decommissioning service requests with added templates [B-15](#)
 - decommissioning service requests with added templates. [B-15](#)
 - default subtemplate matching criteria [B-10](#)
 - enabling for policies [5-34](#)
 - overview [B-1](#)

- overview of template support in ISC policies [B-4](#)
- overview of template use in service requests [B-8](#)
- summary of template manager features [B-1](#)
- template and data file workflow [B-3](#)
- using negate templates to decommission template configurations [B-11](#)
- using templates and data files with service requests [B-12](#)
- using templates to support inter-autonomous system solutions [13-11](#)
- using templates with ISC policies [B-4](#)
- using templates with service requests [B-8](#)
- viewing templates from the service requests window [B-16](#)
- working with templates and data files [B-1](#)

topology

- example of MPLS VPN topology [6-6](#)
- networks [8-2](#)
- network topology [7-2](#)

transition states of service requests [D-1](#)

troubleshooting

- frequently asked questions [C-2](#)
- gathering logs [C-1](#)
- general troubleshooting guidelines [C-1](#)
- MPLS VPNs [C-1](#)

trusted devices [E-12](#)

U

- unique route distinguisher, enabling for a VPN [2-28](#)
- unique route distinguisher, using to provision service requests [2-29](#)

V

- VC ID pools, creating [2-20](#)
- VLAN ID, usage notes [6-10](#)
- VLAN pools, creating [2-21](#)
- VPN routing and forwarding tables (see also VRFs) [E-3](#)

VPNs

- adding PE-CE links to management VPNs [9-14](#)
- benefits of cable MPLS VPNs [10-1](#)
- connectivity between VPNs [E-13](#)
- creating [2-22](#)
- creating and configuring on IPv6 devices [4-8](#)
- defining [2-22](#)
- defining a VPN for the PE-CE link [7-3](#)
- defining VRF and VPN information [5-29](#)
- enabling a unique route distinguisher for a VPN [2-28](#)
- ensuring VPN isolation [E-15](#)
- issues regarding access to VPNs [9-4](#)
- provisioning management VPN [9-1](#)
- troubleshooting [C-1](#)
- VPN routing and forwarding tables [E-3](#)

VRFs

- copying a VRF object [3-5](#)
- creating a new VRF object [3-2](#)
- decommissioning and deleting VRF service requests [3-14](#)
- defining VRF and VPN information [5-29](#)
- defining VRF service requests [3-11](#)
- deleting VRF objects [3-10](#)
- deleting VRF objects associated with VRF service requests [3-10](#)
- deploying VRF service requests [3-13](#)
- implementation [E-4](#)
- independent VRF management [3-1](#)
- independent VRF object management [E-5](#)
- migrating existing MPLS VPN service requests to the VRF object model [3-21](#)
- modifying deployed VRF objects [3-9](#)
- modifying non-deployed VRF objects [3-7](#)
- modifying VRF service requests [3-14](#)
- multi-VRF edit mode [3-7](#)
- overview of VRF service requests [3-11](#)
- relationship of VRF object and service requests and PE device [3-16](#)
- searching for MPLS VPN service requests by VRF object name [3-20](#)

- searching for VRF objects in the ISC repository [3-7](#)
- searching for VRF service requests by VRF object name [3-15](#)
- single-VRF edit mode [3-7](#)
- specifying VRF objects within MPLS VPN service policies [3-20](#)
- specifying VRF objects within MPLS VPN service requests [3-16](#)
- using a VRF object in an MPLS service request [3-20](#)
- using VRFs with MPLS VPN service requests and policies [3-16](#)
- viewing the configlet generated by a deployed VRF service request [3-15](#)
- VRF instance [E-5](#)
- VRF object support for IPv6 [4-8](#)
- VRF-related configlets [4-4](#)
- working with VRF objects [3-2](#)
- working with VRF service requests [3-11](#)

