



About This Guide

Last Updated: January, 2008

The *Cisco Performance Visibility Manager Installation Guide* provides system administrators with instructions on how to install and start the application. This guide contains the following chapters and appendices:

- Chapter 1, “Planning the Installation”
- Chapter 2, “Installation Requirements”
- Chapter 3, “Installing Cisco PVM”
- Chapter 4, “Installing the Cisco PVM License”
- Chapter 5, “Starting and Stopping Cisco PVM”
- Appendix A, “Uninstalling Cisco PVM”
- Appendix B, “Troubleshooting the Cisco PVM Installation”

Command Line Convention

The backslash character (\) is used to indicate that the command line information listed in a procedure is actually a *single line*, rather than broken into two lines as they might appear on the pages of this guide. For example, the following command is actually a single line:

```
keytool -genkey -keyalg RSA -storepass changeit -keystore \  
$JBOSS_HOME/server/default/conf/ssl.keystore
```

Related Documentation

The following documents relate specifically to the Cisco PVM system:

- *Cisco Performance Visibility Manager User Guide, 1.0.2*
- *Cisco Performance Visibility Manager Troubleshooting Guide, 1.0.2*
- *Cisco Performance Visibility Manager Quick Start Guide, 1.0.2*
- *Cisco Performance Visibility Manager Release Notes, 1.0.2*

Obtaining Documentation, Obtaining Support, and Security Guidelines

For information on obtaining documentation, obtaining support, providing documentation feedback, security guidelines, and also recommended aliases and general Cisco documents, see the monthly *What's New in Cisco Product Documentation*, which also lists all new and revised Cisco technical documentation, at:

<http://www.cisco.com/en/US/docs/general/whatsnew/whatsnew.html>