



Release Notes for Cisco ONS 15310-MA Release 7.0

February 2006

Release notes address closed (maintenance) issues, caveats, and new features for the Cisco ONS 15310-MA. For detailed information regarding features, capabilities, hardware, and software introduced with this release, refer to Release 7.0 of the *Cisco ONS 15310-CL and Cisco ONS 15310-MA Procedure Guide*, *Cisco ONS 15310-CL and Cisco ONS 15310-MA Reference Manual*, *Cisco ONS SONET TLI Command Guide*, and the *Cisco ONS 15310-CL and Cisco ONS 15310-MA Troubleshooting Guide*. For the most current version of the Release Notes for Cisco ONS 15310-MA Release 7.0, visit the following URL:

http://www.cisco.com/en/US/products/hw/optical/ps2001/prod_release_notes_list.html

Cisco also provides Bug Toolkit, a web resource for tracking defects. To access Bug Toolkit, visit the following URL:

<http://tools.cisco.com/Support/BugToolKit/action.do?hdnAction=searchBugs>

Contents

[Changes to the Release Notes, page 2](#)

[Caveats, page 2](#)

[Resolved Caveats for Release 7.0, page 3](#)

[New Features and Functionality, page 4](#)

[Related Documentation, page 4](#)

[Obtaining Documentation and Submitting a Service Request, page 4](#)



Corporate Headquarters:

Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

Copyright © 2006 Cisco Systems, Inc. All rights reserved.

Changes to the Release Notes

This section documents supplemental changes that have been added to the *Release Notes for Cisco ONS 15310-MA Release 7.0* since the production of the Cisco ONS 15310-MA System Software CD for Release 7.0.

The following changes have been added to the release notes for Release 7.0.

Changes to Caveats

The following caveats have been added.

[CSCse85355](#)

[CSCsd52665](#)

[CSCsd56328](#)

Caveats

Review the notes listed below before deploying the ONS 15310-MA. Caveats with tracking numbers are known system limitations that are scheduled to be addressed in a subsequent release. Caveats without tracking numbers are provided to point out procedural or situational considerations when deploying the product.

Maintenance and Administration



Caution

VxWorks is intended for qualified Cisco personnel only. Customer use of VxWorks is not recommended, nor is it supported by Cisco's Technical Assistance Center. Inappropriate use of VxWorks commands can have a negative and service affecting impact on your network. Please consult the troubleshooting guide for your release and platform for appropriate troubleshooting procedures. To exit without logging in, enter a Control-D (hold down the Control and D keys at the same time) at the Username prompt. To exit after logging in, type "logout" at the VxWorks shell prompt.

CSCsc56694

IPPM enabled by CTC for an OCn trunk card is disabled automatically after two hours. This issue will be resolved in a future release.

Alarms

CSCse85355

The NE should report alarms or conditions on ingress port not on any internal ports. Alarm detected at the internal ports (TERM) side will be ingress map to the MON side. So the NE raises the STS-MON/VT-MON and STS-TERM/VT-TERM alarms or conditions on the STS-MON/VT-MON

ports, irrespective of the actual detection port (MON or TERM). If the user wants the customized severity to be reflected for a specific STS/VT alarms, the alarm profile entities of both STS-MON and STS-TERM, if available, should be changed to the same severity.

CSCsd52665

The NE should report alarms or conditions on ingress port not on any internal ports. Alarm detected at the internal ports (TERM) side will be ingress map to the MON side. So the NE raises the STS-MON/VT-MON and STS-TERM/VT-TERM alarms or conditions on the STS-MON/VT-MON ports, irrespective of the actual detection port (MON or TERM). If the user wants the customized severity to be reflected for a specific STS/VT alarms, the alarm profile entities of both STS-MON and STS-TERM, if available, should be changed to the same severity.

CSCsd56328

The NE should report alarms or conditions on ingress port not on any internal ports. Alarm detected at the internal ports (TERM) side will be ingress map to the MON side. So the NE raises the STS-MON/VT-MON and STS-TERM/VT-TERM alarms or conditions on the STS-MON/VT-MON ports, irrespective of the actual detection port (MON or TERM). If the user wants the customized severity to be reflected for a specific STS/VT alarms, the alarm profile entities of both STS-MON and STS-TERM, if available, should be changed to the same severity.

Common Control Cards

CSCsc52028

The CTX 2500 card does not accept more than 52 ENE sessions. Figuring 16 ENE sessions per GNE session, the expected ENE logins for 7 GNE sessions is 112, whereas the CTX 2500 accepts only 52. This issue will not be resolved.

TL1



Note

To be compatible with TL1 and DNS, all nodes must have valid names. Node names should contain alphanumeric characters or hyphens, but no special characters or spaces.

CSCsc51017

When multiple TL1 GNE and ENE sessions are created on a 30+ node network, some of the TL1 sessions might continue to be displayed in the user login pane under the network view, even when the sessions have been closed. If this occurs, restart CTC. This issue will be resolved in a future release.

Resolved Caveats for Release 7.0

The ONS 15310-MA is a new release, and so, there are no outstanding items resolved in Release 7.0.

New Features and Functionality

The ONS 15310-MA is a new release, and so, there are no changes in features from a previous release. For documentation of the full feature set for the ONS 15310-MA, consult the user documentation.

Related Documentation

Release-Specific Documents

- *Release Notes for the Cisco ONS 15310-CL Release 7.0*
- *Release Notes for the Cisco ONS 15454 SDH Release 7.0*
- *Release Notes for the Cisco ONS 15327 Release 7.0*
- *Release Notes for the Cisco ONS 15600 Release 7.0*
- *Release Notes for the Cisco ONS 15454 Release 7.0*

Platform-Specific Documents

- *Cisco ONS 15310-CL and Cisco ONS 15310-MA Procedure Guide*
Provides installation, turn up, test, and maintenance procedures
- *Cisco ONS 15310-CL and Cisco ONS 15310-MA Reference Manual*
Provides technical reference information for cards, nodes, and networks
- *Cisco ONS 15310-CL and Cisco ONS 15310-MA Troubleshooting Guide*
Provides a list of SONET alarms and troubleshooting procedures, general troubleshooting information, transient conditions, and error messages
- *Cisco ONS SONET TL1 Command Guide*
Provides a comprehensive list of TL1 commands
- *Cisco ONS SONET TL1 Reference Guide*
Provides general information, procedures, and errors for TL1
- *Cisco ONS 15310-CL and Cisco ONS 15310-MA Ethernet Card Software Feature and Configuration Guide*
Provides software feature and operation information for Ethernet cards

Obtaining Documentation and Submitting a Service Request

For information on obtaining documentation, submitting a service request, and gathering additional information, see the monthly *What's New in Cisco Product Documentation*, which also lists all new and revised Cisco technical documentation, at:

<http://www.cisco.com/en/US/docs/general/whatsnew/whatsnew.html>

Subscribe to the *What's New in Cisco Product Documentation* as a Really Simple Syndication (RSS) feed and set content to be delivered directly to your desktop using a reader application. The RSS feeds are a free service and Cisco currently supports RSS version 2.0.

This document is to be used in conjunction with the documents listed in the “[Related Documentation](#)” section.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2006 Cisco Systems, Inc. All rights reserved.