



APPENDIX **B**

Configuring GE_XP, 10GE_XP, GE_XPE, and 10GE_XPE Cards Using PCLI

This chapter explains how to provision GE_XP, 10GE_XP, GE_XPE, and 10GE_XPE cards using Pseudo Command Line Interface (PCLI).



Note

Unless otherwise specified, “ONS 15454” refers to both ANSI and ETSI shelf assemblies.

Before You Begin

Before performing any of the following procedures, investigate all alarms and clear any trouble conditions. Refer to the *Cisco ONS 15454 DWDM Troubleshooting Guide* as necessary.



Caution

Provisioning TXP and MXP cards can be service affecting. You should make all changes during a scheduled maintenance window.

This section lists the chapter procedures (NTPs). Turn to a procedure for applicable tasks (DLPs).

- [NTP-G222 Access PCLI Text Interface](#), page B-2.
- [NTP-G223 Create a Policy on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI](#), page B-3.
- [NTP-G216 Enable Link Integrity on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI](#), page B-12.
- [NTP-G220 Enable IGMP Snooping on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI](#), page B-14.
- [NTP-G217 Enabling IGMP Fast-Leave Processing on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI](#), page B-15.
- [NTP-G218 Configure a Multicast Router Port on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI](#), page B-16.
- [NTP-G219 Enable IGMP Report Suppression on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI](#), page B-17.
- [NTP-G224 Enable MVR on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI](#), page B-18.

- [NTP-G225 Provision SVLAN Rate Limiting on the GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Card Using PCLI](#), page B-13.
- [NTP-G226 Enable MAC Address Learning on SVLANs for GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI](#), page B-11.
- [NTP-G227 Create SVLAN for GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI](#), page B-19.

NTP-G222 Access PCLI Text Interface

Purpose	This procedure explains how to access PCLI text interface using CTC or Telnet.
Tools/Equipment	None
Prerequisite Procedures	None
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Retrieve or higher

Step 1 Complete the “[DLP-G46 Log into CTC](#)” task on [page 2-26](#) at the node where you want to access PCLI. If you are already logged in, continue with [Step 2](#).

Step 2 PCLI can be accesses in the following ways:

- To access PCLI text interface using CTC, select **Tools > Open Pseudo IOS Connection** menu option or right-click on the node in the Network View and select **Open Pseudo IOS Connection**.
- To access PCLI from the command prompt, telnet or SSH may be used depending on the access state set for PCLI access in **Provisioning > Security > Pseudo IOS Access** in Node view. If the access state is set to the default state, non-secure, a PCLI session can be established using telnet as shown in the following procedure:

	Command or Action	Purpose
Step 1	telnet <node ip or node name> <port number>	Establishes a PCLI session using Telnet.
	Example: telnet 10.76.148.176 65000 MSTP-176>	Note The default port number for non-secure mode is 65000. The port number can be provisioned in CTC. To do so, go to Node view and click Provisioning > Security > Pseudo IOS Access .
Step 2	exit	Exits PCLI text interface.
	Example: MSTP-176> exit	

	Command or Action	Purpose
Step 3	<code>enable shelf/slot</code>	Enters the Privileged EXEC mode from where you can enter other configuration modes. Several show commands are also available in the Privileged EXEC mode.
	Example: <code>MSTP 176# enable 1/12</code>	
	Stop. You have completed this procedure.	—

- If the access state is set to secure, a PCLI session can be established using a SSH client like Open SSH as shown in the following procedure:

	Command or Action	Purpose
Step 1	<code>ssh -p <node ip or node name > <port number></code>	Establishes a PCLI session using SSH.
	Example: <code>ssh -p 10.76.148.194 64000</code> <code>MSTP-176></code>	Note The default port number for secure mode is 64000. The port number can be provisioned in CTC. To do so, go to Node view and click Provisioning > Security > Pseudo IOS Access .
Step 2	<code>exit</code>	Exits PCLI text interface.
Step 3	Example: <code>MSTP-176> exit</code>	
	<code>enable shelf/slot</code>	Enters the Privileged EXEC mode from where you can enter other configuration modes. Several show commands are also available in the Privileged EXEC mode.
	Example: <code>MSTP 176> enable 1/12</code>	For more information on PCLI commands see the <i>Cisco ONS DWDM Reference Manual</i> .
	Stop. You have completed this procedure.	—

Stop. You have completed this procedure.

NTP-G223 Create a Policy on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI

Purpose	This procedure explains how to create a policy on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards using PCLI.
Tools/Equipment	None
Prerequisite Procedures	None
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher

**Note**

For detailed information on PCLI, see the *Cisco ONS 15454 DWDM Reference Manual*.

Step 1 Complete the “[NTP-G222 Access PCLI Text Interface](#)” task on page B-2 at the node where you want to create a policy. If you are already logged in, continue with [Step 2](#).

Step 2 Complete the following tasks, as needed:

- [DLP-G517 Create an Ingress Policy on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards Using PCLI](#), page B-4
- [DLP-G518 Create a Egress Policy on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI](#), page B-5
- [DLP-G519 Create a Service Instance Policy on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI](#), page B-6
- [DLP-G520 Apply an Ingress Policy to a Port on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI](#), page B-7
- [DLP-G521 Apply an Egress Policy to a Port on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI](#), page B-8
- [DLP-G522 Apply a Service Instance Policy to a Port on GE_XPE or 10GE_XPE Cards Using PCLI](#), page B-9

Stop. You have completed this procedure.

DLP-G517 Create an Ingress Policy on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards Using PCLI

Purpose	This procedure explains how to create CIR, EIR, CBS, EBS and Ingress COS parameters as part of Ingress policy on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards using PCLI.
Tools/Equipment	None
Prerequisite Procedures	None
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher

**Note**

Once the CIR, EIR, CBS, EBS and Ingress COS parameters are created, the policy can be used across other cards of these types in the node. See “[DLP-G520 Apply an Ingress Policy to a Port on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI](#)” task on page B-7.

Step 1 Complete the following tasks, as needed:

	Command or Action	Purpose
Step 1	configure terminal Example: MSTP 176# configure terminal	Enters global configuration mode.
Step 2	policy-map <i>name</i> Example: MSTP 176# (config) policy-map pmap MSTP-176# (config-pmap)#	Enters policy map configuration mode.
Step 3	police cir percent % bc bytes be bytes Example: MSTP-176(config-pmap)#police cir percent 20 bc 64 be 128	Sets CIR, EIR, CBS and EBS values.
Step 4	set cos <i>number</i> Example: MSTP 176 (config-pmap)# set cos 6	Sets the Ingress COS parameter.
Step 5	exit Example: MSTP-176(config-pmap# exit	Exits policy map configuration mode.
	Stop. You have completed this procedure.	—

DLP-G518 Create a Egress Policy on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI

Purpose	This procedure explains how to create an egress policy on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards using PCLI.
Tools/Equipment	None
Prerequisite Procedures	None
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher



Note

Once the Egress policy is created, the policy can be used across other cards of these types in the node. [“DLP-G521 Apply an Egress Policy to a Port on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI” task on page B-8.](#)

Before You Begin

Step 1 Complete the following tasks, as needed:

	Command or Action	Purpose
Step 1	<code>configure terminal</code>	Enters global configuration mode.
	Example: <code>MSTP 176# configure terminal</code>	
Step 2	<code>policy-map name</code>	Enters policy map configuration mode.
	Example: <code>MSTP 176# (config) policy-map pmap</code> <code>MSTP-176# (config-pmap)#</code>	
Step 3	<code>wrr-queue cos-map <queue-id> <cos1></code> <code><cosn></code>	Maps a queue ID to a given COS.
	Example: <code>MSTP-176(config-pmap)#wrr-queue cos-map</code> <code>1 1</code>	
Step 4	<code>wrr-queue <queue-id> weight <1-16></code> <code>bandwidth percent <%></code>	Sets the WRR and bandwidth values on a queue.
	Example: <code>MSTP 176 (config-pmap)# wrr-queue 1</code> <code>weight 2 band per 90</code>	
Step 5	<code>exit</code>	Exits policy map configuration mode.
	Example: <code>MSTP-176(config-pmap)# exit</code>	
	Stop. You have completed this procedure.	—

DLP-G519 Create a Service Instance Policy on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI

Purpose	This procedure explains how to create a service instance policy which can be used to define a COS for a CVLAN on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards using PCLI.
Tools/Equipment	None
Prerequisite Procedures	None
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher

**Note**

Once the service instance policy is created, the policy can be used across other cards of these types in the node. [“DLP-G522 Apply a Service Instance Policy to a Port on GE_XPE or 10GE_XPE Cards Using PCLI” task on page B-9](#)

Step 1 Complete the following tasks, as needed:

	Command or Action	Purpose
Step 1	configure terminal Example: MSTP 176# configure terminal	Enters global configuration mode.
Step 2	policy-map <i>name</i> Example: MSTP 176# (config) policy-map pmap MSTP-176# (config-pmap) #	Enters policy map configuration mode.
Step 3	set cos < <i>number</i> > Example: MSTP 176 (config-pmap) # set cos 6	Sets the COS value.
Step 4	exit Example: MSTP-176(config-pmap) # exit	Exits policy map configuration mode.
	Stop. You have completed this procedure.	—

DLP-G520 Apply an Ingress Policy to a Port on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI

Purpose	This procedure explains how to apply an Ingress policy to a port on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards using PCLI.
Tools/Equipment	None
Prerequisite Procedures	- Complete DLP-G517 Create an Ingress Policy on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards Using PCLI, page B-4. - Before you apply the Ingress policy on the GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE card, make sure the port is shutdown.
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher

Step 1 Complete the following tasks, as needed:

	Command or Action	Purpose
Step 1	<code>configure terminal</code>	Enters global configuration mode.
	Example: <code>MSTP 176# configure terminal</code>	
Step 2	<code>interface type port</code>	Enters interface configuration mode.
	Example: <code>MSTP 176# (config) interface giga 1</code> <code>MSTP-176# (config-if)#</code>	
Step 3	<code>service-policy input <name></code>	Maps the specified ingress policy to the port.
	Example: <code>MSTP 176 (config-if)# service-pol input</code> <code>ingresspolicy1</code>	
Step 4	<code>exit</code>	Exits interface configuration mode.
	Example: <code>MSTP-176(config-if# exit</code>	
	Stop. You have completed this procedure.	—

DLP-G521 Apply an Egress Policy to a Port on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI

Purpose	This procedure explains how to apply an Egress policy to a port on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards using PCLI.
Tools/Equipment	None
Prerequisite Procedures	Complete DLP-G518 Create a Egress Policy on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI, page B-5.
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher

Step 1 Complete the following tasks, as needed:

	Command or Action	Purpose
Step 1	<code>configure terminal</code> Example: MSTP 176# <code>configure terminal</code>	Enters global configuration mode.
Step 2	<code>interface type port</code> Example: MSTP 176# <code>(config) interface giga 1</code> MSTP-176# <code>(config-if)#</code>	Enters interface configuration mode.
Step 3	<code>service-policy output <name></code> Example: MSTP 176 <code>(config-if)# service-policy output egresspolicy1</code>	Maps the specified Egress policy to the port.
Step 4	<code>exit</code> Example: MSTP-176 <code>(config-if)# exit</code>	Exits interface configuration mode.
	Stop. You have completed this procedure.	—

DLP-G522 Apply a Service Instance Policy to a Port on GE_XPE or 10GE_XPE Cards Using PCLI

Purpose	This procedure explains how to apply a service instance policy to a port on GE_XPE or 10GE_XPE cards using PCLI.
Tools/Equipment	None
Prerequisite Procedures	- Complete DLP-G519 Create a Service Instance Policy on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI, page B-6. - Before you apply the Egress policy on the GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE card, make sure the port is shutdown.
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher



Note

A service instance cannot be edited on a port using PCLI. The service instance policy must be specified at the time of service instance creation.

Before You Begin

Step 1 Complete the following tasks, as needed:

	Command or Action	Purpose
Step 1	<pre>configure terminal</pre> Example: MSTP 176# configure terminal	Enters global configuration mode.
Step 2	<pre>interface type port</pre> Example: MSTP 176# (config) interface giga 1 MSTP-176# (config-if#	Enters interface configuration mode.
Step 3	<pre>service instance ethernet vlan</pre> Example: MSTP 176# (config-if) service instance ethernet vlan1 MSTP-176# (config-if-srv)#	Enters service instance configuration mode.
Step 4	<pre>rewrite ingress tag translate 1-to-1 <multipurpose vlan> push dot1q <svlan></pre> Example: MSTP 176 (config-if-srv)# rewrite ingress tag translate 1 1 push dot1 1	Specifies the CVLAN and SVLAN relation on the port.
Step 5	<pre>service policy input <policy name></pre> Example: MSTP 176 (config-if-srv)# service-policy input serviceinstancepolicy1	Associates the service instance policy specified to a port.
Step 6	<pre>exit</pre> Example: MSTP-176(config-if-srv)# exit MSTP-176(config-if)#	Exits service instance configuration mode.
Step 7	<pre>exit</pre> Example: MSTP-176(config-if)# exit	Exits interface configuration mode.
	Stop. You have completed this procedure.	—

NTP-G226 Enable MAC Address Learning on SVLANs for GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI

Purpose	This procedure explains how to enable MAC address learning on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards using PCLI.
Tools/Equipment	None
Prerequisite Procedures	NTP-G222 Access PCLI Text Interface, page B-2
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher



Note For detailed information on PCLI, see the *Cisco ONS 15454 DWDM Reference Manual*.

- Step 1** Complete the “[NTP-G222 Access PCLI Text Interface](#)” task on page B-2 at the node where you want to enable MAC address learning. If you are already logged in, continue with [Step 2](#).
- Step 2** Complete the following tasks, as needed:

	Command or Action	Purpose
Step 1	<code>enable shelf/slot</code>	Selects shelf and slot to be configured for a card.
	Example: <code>MSTP 176# enable 1/12</code>	
Step 2	<code>configure terminal</code>	Enters global configuration mode.
	Example: <code>MSTP 176# configure terminal</code>	
Step 3	<code>mac-address-table learning vlan <vlan-id></code>	Enables interface based learning of MAC address. Repeat the command on each SVLAN to enable MAC address learning.
	Example: <code>MSTP-176(config)# mac-address-table learning vlan 2</code>	
Step 4	<code>mac-address-table learning interface <type> <port></code>	Enables interface based learning of MAC address. Repeat the command on each SVLAN to enable MAC address learning.
	Example: <code>MSTP-176(config)# mac-address-table learning gigabitethernet 2</code>	
Step 5	<code>exit</code>	Exits global configuration mode.
	Example: <code>MSTP-176(config)# exit</code>	
Step 6	Return to your originating procedure (NTP).	—

NTP-G216 Enable Link Integrity on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI

Purpose	This procedure explains how to enable link integrity on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards using PCLI.
Tools/Equipment	None
Prerequisite Procedures	NTP-G222 Access PCLI Text Interface, page B-2
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher



Note For detailed information on PCLI, see the *Cisco ONS 15454 DWDM Reference Manual*.

- Step 1** Complete the “[NTP-G222 Access PCLI Text Interface](#)” task on page B-2 at the node where you want to enable link integrity. If you are already logged in, continue with [Step 2](#).
- Step 2** Complete the following tasks, as needed:

	Command or Action	Purpose
Step 1	<pre>configure terminal</pre> Example: MSTP 176# configure terminal	Enters global configuration mode.
Step 2	<pre>vlan profile name</pre> Example: MSTP 176 (config)# vlan profile profile4 MSTP 176 (config-profile)	Enters VLAN profile configuration mode.
Step 3	<pre>link integrity</pre> Example: MSTP 176 (config-profile) link integrity	Enables link integrity.
Step 4	<pre>exit</pre> Example: MSTP-176(config-profile)# exit	Exits VLAN profile configuration mode.
Step 5	<pre>vlan profile name vlan svlanid interface type port</pre> Example: MSTP 176 (config)# vlan profile a vlan 2 interface gigabitethernet 2	Associates the SVLAN profile to a SVLAN on a port.

	Command or Action	Purpose
Step 6	<pre>interface type port</pre> Example: MSTP 176 (config)# interface gigabitethernet 2	Enters interface configuration mode.
Step 7	<pre>link integrity action {none squelch propagate}</pre> Example: MSTP 176 (config-if)# link integrity action squelch	When an AIS packet is received on a SVLAN terminating on the UNI port, the UNI port is squelched.
Step 8	<pre>exit</pre> Example: MSTP-176(config-profile)# exit	Exits interface configuration mode.
Step 9	Return to your originating procedure (NTP).	—

NTP-G225 Provision SVLAN Rate Limiting on the GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Card Using PCLI



Note For detailed information on PCLI, see the *Cisco ONS 15454 DWDM Reference Manual*.

- Step 1** Complete the “[NTP-G222 Access PCLI Text Interface](#)” task on page B-2 at the node where you want to provision SVLAN rate limiting. If you are already logged in, continue with [Step 2](#).
- Step 2** Complete the following tasks, as needed:

	Command or Action	Purpose
Step 1	<pre>configure terminal</pre> Example: MSTP 176# configure terminal	Enters global configuration mode.
Step 2	<pre>vlan profile name</pre> Example: MSTP 176 (config)# vlan profile profile4 MSTP 176 (config-profile)	Enters VLAN profile configuration mode.

	Command or Action	Purpose
Step 3	<pre>police cir percent <%> pir percent <%> bc <byte> be <byte></pre> Example: MSTP-176(config-profile)# police cir percent 20 bc 64 be 128	Enters ingress rate limits.
Step 4	<pre>exit</pre> Example: MSTP-176(config-profile)# exit	Exits VLAN profile configuration mode.
Step 5	<pre>vlan profile name vlan svlanid interface type port</pre> Example: MSTP 176 (config)# vlan profile a vlan 2 interface gigabitethernet 2	Associates the SVLAN profile to a SVLAN on a port.
Step 6	Return to your originating procedure (NTP).	—

NTP-G220 Enable IGMP Snooping on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI

Purpose	This procedure explains how to enable IGMP snooping on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards using PCLI.
Tools/Equipment	None
Prerequisite Procedures	None
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher


Note

For detailed information on PCLI, see the *Cisco ONS 15454 DWDM Reference Manual*.

- Step 1** Complete the “[NTP-G222 Access PCLI Text Interface](#)” task on page B-2 at the node where you want to enable IGMP snooping. If you are already logged in, continue with [Step 2](#).
- Step 2** Complete the following tasks, as needed:

	Command or Action	Purpose
Step 1	<pre>configure terminal</pre> Example: MSTP 176# configure terminal	Enters global configuration mode.
Step 2	<pre>vlan <vlan-id></pre> Example: MSTP-176# (config)# vlan 2 MSTP-176# (config-vlan)#	Enters VLAN configuration mode.
Step 3	<pre>ip igmp snooping</pre> Example: MSTP-176(config-vlan)# ip igmp snooping	Enables IGMP snooping. Note To disable IGMP snooping, use the no ip igmp snooping command.
Step 4	<pre>exit</pre> Example: MSTP-176(config-vlan)# exit	Exits VLAN configuration mode.
Step 5	Return to your originating procedure (NTP)	—

NTP-G217 Enabling IGMP Fast-Leave Processing on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI

Purpose	This procedure explains how to enable fast-leave processing on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards using PCLI.
Tools/Equipment	None
Prerequisite Procedures	None
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher



Note For detailed information on PCLI, see the *Cisco ONS 15454 DWDM Reference Manual*.

- Step 1** Complete the “[NTP-G222 Access PCLI Text Interface](#)” task on page B-2 at the node where you want to enable IGMP fast-leave processing. If you are already logged in, continue with [Step 2](#).
- Step 2** Complete the following tasks, as needed:

	Command or Action	Purpose
Step 1	<pre>configure terminal</pre> Example: MSTP-176# configure terminal	Enters global configuration mode.
Step 2	<pre>vlan <vlan-id></pre> Example: MSTP-176# (config)# vlan 2 MSTP-176# (config-vlan)#	Enters VLAN configuration mode.
Step 3	<pre>ip igmp snooping immediate-leave</pre> Example: MSTP-176(config-vlan)# ip igmp snooping immediate-leave	Enables IGMP fast-leave processing. Note To disable fast-leave processing, use the no ip igmp snooping immediate-leave configuration command.
Step 4	<pre>exit</pre> Example: MSTP-176(config-vlan)# exit	Exits VLAN configuration mode.
	Stop. You have completed this procedure.	—

NTP-G218 Configure a Multicast Router Port on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI

Purpose	This procedure explains how to configure multicast router port on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards using PCLI.
Tools/Equipment	None
Prerequisite Procedures	None
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher

**Note**

For detailed information on PCLI, see the *Cisco ONS 15454 DWDM Reference Manual*.

- Step 1** Complete the “[NTP-G222 Access PCLI Text Interface](#)” task on page B-2 at the node where you want to configure multicast router ports. If you are already logged in, continue with [Step 2](#).
- Step 2** Complete the following tasks, as needed:

	Command or Action	Purpose
Step 1	configure terminal Example: MSTP 176# configure terminal	Enters global configuration mode.
Step 2	interface {gigabitethernet tengigabitethernet} port Example: MSTP-176(config)# interface gigabitethernet 1 MSTP-176(config-if)#	Enters interface configuration mode.
Step 3	ip igmp snooping mrouter Example: MSTP-176(config-if)# ip igmp snooping mrouter	Enables multicast router port functionality on a port. Note To disable multicast router functionality on the port, enter interface configuration mode, and use the no ip igmp snooping mrouter command.
Step 4	exit Example: MSTP-176(config-if)# exit	Exits interface configuration mode.
	Stop. You have completed this procedure.	—

NTP-G219 Enable IGMP Report Suppression on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI

Purpose	This procedure explains to how enable IGMP report suppression on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards using PCLI.
Tools/Equipment	None
Prerequisite Procedures	None
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher



Note For detailed information on PCLI, see the *Cisco ONS 15454 DWDM Reference Manual*.

- Step 1** Complete the “[NTP-G222 Access PCLI Text Interface](#)” task on page B-2 at the node where you want to enable report suppression. If you are already logged in, continue with [Step 2](#).
- Step 2** Complete the following tasks, as needed:

Before You Begin

	Command or Action	Purpose
Step 1	<pre>configure terminal</pre> Example: MSTP 176# configure terminal	Enters global configuration mode.
Step 2	<pre>vlan id</pre> Example: MSTP-176# (config)# vlan 2 MSTP-176# (config-vlan)#	Enters VLAN configuration mode.
Step 3	<pre>ip igmp snooping report-suppression</pre> Example: MSTP-176(config-vlan)# ip igmp snooping report-suppression	Globally enables IGMP snooping report suppression. Note To disable report suppression, use the no ip igmp snooping report-suppression in VLAN configuration mode.
Step 4	<pre>exit</pre> Example: MSTP-176(config-vlan)# exit	Exits VLAN configuration mode.
	Stop. You have completed this procedure.	—

NTP-G224 Enable MVR on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI

Purpose	This procedure explains how to enable MVR on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards using PCLI.
Tools/Equipment	None
Prerequisite Procedures	None
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher

**Note**

For detailed information on PCLI, see the *Cisco ONS 15454 DWDM Reference Manual*.

- Step 1** Complete the “[NTP-G222 Access PCLI Text Interface](#)” task on page B-2 at the node where you want to enable MVR. If you are already logged in, continue with [Step 2](#).
- Step 2** Complete the following tasks, as needed:

	Command or Action	Purpose
Step 1	<pre>configure terminal</pre> Example: MSTP 176# configure terminal	Enters global configuration mode.
Step 2	<pre>mvr group ip-address count</pre> Example: MSTP-176(config)# mvr group 228.1.23.4	Specify the starting IP address for a range of multicast group addresses for which MVR needs to be enabled. Use the count parameter to limit the number of groups. Note A maximum of 256 MVR multicast groups can be configured on the GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE card. Note MVR is applied only on multicast groups configured here. For multicast groups that are not in this range, normal IGMP processing occurs. Note Count can be set from 1 to 256. Use 1 to enable MVR on a single group. The IP address range must be 224.0.0.0 to 239.255.255.255.
Step 3	<pre>mvr vlan vlan-id</pre> Example: MSTP-176(config)# mvr vlan 2	Specifies the VLAN in which multicast data is received; all ports must belong to this VLAN. The VLAN range is 1 to 4093.
Step 4	<pre>mvr</pre> Example: MSTP-176(config)# mvr	Enables MVR. Note To disable MVR, use the no mvr in global configuration mode.
Step 5	<pre>exit</pre> Example: MSTP-176(config-if)# exit	Exits global configuration mode.
Step 6	Return to your originating procedure (NTP).	—

NTP-G227 Create SVLAN for GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE Cards Using PCLI

Purpose	This procedure explains how to create or delete SVLANs on GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards using PCLI.
Tools/Equipment	None
Prerequisite Procedures	None
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher

**Note**

For detailed information on PCLI, see the *Cisco ONS 15454 DWDM Reference Manual*.

- Step 1** Complete the “[NTP-G222 Access PCLI Text Interface](#)” task on page B-2 at the node where you want to create an SVLAN. If you are already logged in, continue with [Step 2](#).
- Step 2** Complete the following tasks, as needed:

	Command or Action	Purpose
Step 1	<code>configure terminal</code>	Enters global configuration mode.
	Example: <code>MSTP 176# configure terminal</code>	
Step 2	<code>vlan <vlan-id></code>	Creates a VLAN.
	Example: <code>MSTP-176# (config)# vlan 2</code>	Note To delete an SVLAN, use the no config vlan <vlan-id> command in global configuration mode.
Step 3	<code>exit</code>	Exits global configuration mode.
	Example: <code>MSTP-176(config)# exit</code>	
	Stop. You have completed this procedure.	—

NTP-G228 Create a Service Instance Using PCLI

Purpose	This procedure explains how to create a service instance that is used to define the VLAN configuration on the UNI and NNI ports of GE_XP, 10GE_XP, GE_XPE, or 10GE_XPE cards using PCLI.
Tools/Equipment	None
Prerequisite Procedures	Create SVLANs that you want to include in the service instance.
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher

**Note**

For detailed information on PCLI, see the *Cisco ONS 15454 DWDM Reference Manual*.

- Step 1** Complete the “[NTP-G222 Access PCLI Text Interface](#)” task on page B-2 at the node where you want to create an SVLAN. If you are already logged in, continue with [Step 2](#).
- Step 2** Complete the following tasks, as needed:

	Command or Action	Purpose
Step 1	<pre>configure terminal</pre> Example: MSTP 176# configure terminal	Enters global configuration mode.
Step 2	<pre>interface type port</pre> Example: MSTP 176# (config) interface giga 1 MSTP-176# (config-if)#	Enters interface configuration mode.
Step 3	<pre>service instance ethernet vlan</pre> Example: MSTP 176# (config-if)# service instance ethernet vlan10 MSTP-176# (config-if-srv)#	Enters service instance configuration mode. If the port is configured as a UNI, then go to Step 4. If the port is configured as an NNI port, go to step Step 14.
Step 4	<pre>encapsulation default</pre> Example: MSTP 176# (config-if-srv)# encapsulation default	Configures the port in transparent mode. Note Before executing this command, the ports must be in disabled state. Note The encapsulation and rewrite commands must be executed as pairs. Every rewrite command must be preceded by an encapsulation command. Only one encapsulation and rewrite command pair can be executed per port.
Step 5	<pre>rewrite ingress tag push dot1q <svlan></pre> Example: MSTP 176# (config-if-srv)# rewrite ingress tag push dot1q 10	Note Before executing this command, the ports must be in disabled state. Note The encapsulation and rewrite commands must be executed as pairs. Every rewrite command must be preceded by an encapsulation command. Only one encapsulation and rewrite command pair can be executed per port.
Step 6	<pre>encapsulation dot1q <first cvlan> <last cvlan></pre> Example: MSTP 176# (config-if-srv)# encapsulation dot1 20 30	Configures a port in selective add mode with a range of CVLANs mapped to a given SVLAN. Tagged frames with VLAN ID in the range between 20 to 30 (Inclusive of 20 and 30) are matched.
Step 7	<pre>rewrite ingress tag push dot1q <svlan></pre> Example: MSTP 176# (config-if-srv)# rewrite ingress tag push dot1q 10	Note Before executing this command, the ports must be in disabled state. Note The encapsulation and rewrite commands must be executed as pairs. Every rewrite command must be preceded by an encapsulation command. Only one encapsulation and rewrite command pair can be executed per port. Note Multiple encapsulation and rewrite commands can be configured as part of the same service instance.

Before You Begin

	Command or Action	Purpose
Step 8	<pre>encapsulation dot1q <first cvlan> <last cvlan></pre> Example: MSTP 176# (config-if-srv)# encapsulation dot1 20 20	Configures a port in selective translate mode. Tagged frames with VLAN ID 20 are matched.
Step 9	<pre>rewrite ingress tag translate 1-to-1 <svlan></pre> Example: MSTP 176# (config-if-srv)# rewrite ingress tag translate 1 10	Overwrites the Ingress tag 20 with the SVLAN tag value of 10. Note No two encapsulation and rewrite commands on the port that are configured either as part of a given service instance or as a different service instance can have the same SVLAN.
Step 10	<pre>encapsulation untagged</pre> Example: MSTP 176# (config-if-srv)# encapsulation untagged	Configures a port in double add mode. To match untagged packets specify CVLAN to be 0.
Step 11	<pre>rewrite ingress tag push dot1q <multipurpose vlan> second-dot1q <svlan></pre> Example: MSTP 176# (config-if-srv)# rewrite ingress tag push dot1q 10 second-dot1q 20	To add two SVLAN tags to the Ingress untagged packet. Note Only one encapsulation and rewrite command pair can be executed per port. Note This configuration is supported only on GE_XPE & 10 GE_XPE cards.
Step 12	<pre>encapsulation dot1q <first cvlan> <last cvlan></pre> Example: MSTP 176# (config-if-srv)# encapsulation dot1q 9 9	Matches tagged frames with VLAN ID, 9.
Step 13	<pre>rewrite ingress tag translate 1-to-1 <multipurpose vlan> push dot1q <svlan></pre> Example: MSTP 176# (config-if-srv)# rewrite ingress tag translate 1 25 push dot1 30	Translates CVLAN tag to SVLAN tag 25 and adds another SVLAN tag, 30. Note This configuration is supported only on GE_XPE & 10 GE_XPE cards.
Step 14	<pre>bridge-domain <svlan></pre> Example: MSTP 176# (config-if-srv)# bridge-domain 10	Adds the port to SVLAN 10.
Step 15	<pre>exit</pre> Example: MSTP 176# (config-if-srv)# exit MSTP 176# (config-if)#	Exits service instance configuration mode.

	Command or Action	Purpose
Step 16	exit	Exits interface configuration mode.
	Example: MSTP 176# (config-if)# exit MSTP-176(config)#	
Step 17	exit	Exits global configuration mode.
	Example: MSTP-176(config)# exit	
	Stop. You have completed this procedure.	—

