



Sample Network Deployments

This part of the software configuration guide presents a variety of possible Ethernet- and Digital Subscriber Line (DSL)-based network configurations using the Cisco 850 and Cisco 870 series access routers. Each scenario is described with a network topology, a step-by-step procedure that is used to implement the network configuration, and a configuration example that shows the results of the configuration. The Cisco 851 and Cisco 871 router models can be used in the Ethernet-based scenarios and the Cisco 857, Cisco 876, Cisco 877, and Cisco 878 router models can be used in the DSL-based scenarios.

The first network scenario provides a simple network configuration: point-to-point protocol (PPP) over the WAN interface with Network Address Translation (NAT). Each successive scenario builds on the previous scenario by configuring another key feature.

The scenarios do not address all of the possible network needs; instead, they provide models on which you can pattern your network. You can choose not to use features presented in the examples, or you can add or substitute features that better suit your needs.



Note

www.cisco.com > **Technical Support & Documentation** > **Tools &**

Resources

For Ethernet-Based Network Deployments

Use the following configuration examples to assist you in configuring your router for Ethernet-based networks.

- [Chapter 3, “Configuring PPP over Ethernet with NAT”](#)
[Chapter 5, “Configuring a LAN with DHCP and VLANs”](#)
[Chapter 6, “Configuring a VPN Using Easy VPN and an IPSec Tunnel”](#)
[Chapter 7, “Configuring VPNs Using an IPSec Tunnel and Generic Routing Encapsulation”](#)
[Chapter 8, “Configuring a Simple Firewall”](#)

For DSL-Based Network Deployments

- [Chapter 4, “Configuring PPP over ATM with NAT”](#)
[Chapter 5, “Configuring a LAN with DHCP and VLANs”](#)
[Chapter 6, “Configuring a VPN Using Easy VPN and an IPSec Tunnel”](#)

-
-