



## INDEX

---

### Numerics

3DES [B-3](#)

---

### A

ActiveX [B-3](#)

Advanced Endpoint Assessment [1-3](#)

Allow e-mail applications to work transparently, attribute [3-22](#)

---

### B

Basic Host Scan [1-2, 3-26](#)

bookmarks [3-23](#)

browser

    home page and favorites [3-23](#)

    restrict [3-20](#)

---

### C

Cache Cleaner

    description [B-3](#)

    instructions [3-15 to 3-17](#)

    Secure Session, when settings apply [B-4](#)

    Use Module, attribute [3-12](#)

    Windows [3-15](#)

character encoding [B-4](#)

Check for keystroke loggers, attribute [3-14, A-13](#)

Checksum, attribute [3-7](#)

Cipher Block Chaining (CBC) [B-3](#)

Clean the whole cache in addition to the current session cache, attribute [3-17](#)

command prompt, disable [3-22](#)

configuration settings, transfer to another security appliance [1-9](#)

Customize bookmarks, pane [3-23](#)

Customize bookmarks, window [3-23](#)

---

### D

data.xml [1-9](#)

Data Encryption Standard (DES) [B-3](#)

Default prelogin policy [1-8](#)

delete *See* Secure Delete

deleting files [3-22](#)

DES-CBC [B-3](#)

desktop switching [3-18](#)

Disable access to network drives and network folders, attribute [3-21](#)

Disable access to removable drives and removable folders, attribute [3-22](#)

Disable command prompt access [3-22](#)

Disable printing, attribute [3-22](#)

Disable registry modification, attribute [3-22](#)

DoD delete *See* Secure Delete

Does not exist, criterion for a registry key or file [3-5](#)

Do not encrypt files on network drives, attribute [3-21](#)

Do not encrypt files on removable drives, attribute [3-22](#)

drive access [3-21, 3-22](#)

Dword [3-4, 3-5](#)

---

### E

e-mail [3-22](#)

Enable Secure Desktop inactivity timeout, attribute [3-19](#)

Enable switching between Secure Desktop and local desktop, attribute [3-18](#)

Enable Vault Reuse, attribute [3-18](#)  
 encryption [3-19, 3-21, 3-22, B-3](#)  
 Endpoint Assessment [1-3](#)  
 Exists, criterion for a file [3-7](#)  
 Exists, criterion for a registry key or file [3-5](#)

---

## F

FAQs [B-1 to B-4](#)  
 fast user switching [B-4](#)  
 favorites [3-23](#)  
 file criteria [3-2](#)  
 firewall [B-4](#)  
 folders in favorites or bookmarks [3-23](#)  
 Force admin control on list of safe modules, attribute [3-14, A-13](#)  
 Force application uninstall upon Secure Desktop closing, attribute [3-19](#)  
 frequently asked questions [B-1 to B-4](#)

---

## H

Hidden URL, attribute [3-16](#)  
 hives [3-4, 3-27](#)  
 HKEY\_CLASSES\_ROOT [3-4, 3-27](#)  
 HKEY\_CURRENT\_USER [3-4, 3-27](#)  
 HKEY\_LOCAL\_MACHINE [3-4, 3-5, 3-6, 3-27](#)  
 HKEY\_USERS [3-4, 3-27](#)  
 Home Page, attribute [3-23](#)  
 home prelogin policy, example configuration [1-4, A-1](#)  
 Host Scan [1-8](#)

---

## I

inactivity timer [3-19](#)  
 installing Cisco Secure Desktop [2-1 to 2-3](#)  
 Internet Explorer settings on remote access device [B-3](#)  
 IP address [3-11](#)

---

## J

Japanese character encodings [B-4](#)  
 Java [B-3](#)  
 Java Virtual Machine [B-4](#)

---

## K

Keystroke Logger [1-8, 3-13 to 3-15, A-11 to A-13](#)

---

## L

Launch cleanup upon closing of all browser instances, attribute [3-17](#)  
 Launch cleanup upon timeout based on inactivity, attribute [3-16](#)  
 Launch hidden URL after installation, attribute [3-16](#)  
 List of Safe Modules, pane [3-14](#)  
 local desktop, switch [3-18](#)

---

## M

main.exe [B-4](#)  
 Microsoft Virtual Machine [B-3](#)

---

## N

navigation [1-7](#)  
 network card [B-4](#)  
 network drive access [3-21](#)

---

## O

Open following web page after Secure Desktop closes, attribute [3-19](#)

---

## P

password, Secure Session [B-3](#)

personal firewall [B-4](#)  
 prelogin policy  
     criteria [3-13](#)  
     example configuration [A-1](#)  
 Prelogin Policy, menu option [1-7](#)  
 printing [3-22](#)  
 public prelogin policy, example configuration [1-4, A-2](#)

---

## R

registry  
     criteria [3-2](#)  
     disable modification [3-22](#)  
 removable drive access [3-22](#)  
 Restrict application usage to the web browser only,  
 attribute [3-20](#)  
 restricted mode [3-20](#)  
 reusing CSD settings [1-9](#)

---

## S

safe modules [3-14, A-13](#)  
 secure, example configuration [1-4, 3-11, A-1](#)  
 Secure Delete  
     Cache Cleaner [3-17](#)  
     Secure Session [3-19](#)  
 Secure Desktop  
     Browser [1-8, 3-23](#)  
     configuring [3-1](#)  
     encryption type [B-3](#)  
     force uninstall [3-19](#)  
     General [1-8, 3-17 to 3-19](#)  
     inactivity timeout [3-19](#)  
     local desktop switch [3-18](#)  
 Manager  
     establishing a session [1-6](#)  
     multiple [B-3](#)  
     open web page when closing [3-19](#)  
     prompt to uninstall [3-19](#)

Settings window [1-8, 3-20 to 3-22](#)

Use Module, attribute [3-12](#)

Secure Session

Cache Cleaner, when settings apply [B-4](#)

description [B-3](#)

Suggest application uninstall, attribute [3-19](#)

Vault Reuse, attribute [3-18](#)

security settings [B-3](#)

Shift\_JIS [B-4](#)

Show success message at the end of successful installation,  
 attribute [3-16](#)

String value, attribute of a registry key as an endpoint  
 criterion [3-5](#)

Suggest application uninstall upon Secure Desktop  
 closing, attribute [3-19](#)

---

## T

Timeout after, attribute [3-17, 3-19](#)

transparent e-mail [3-22](#)

Triple DES [B-3](#)

---

## U

URLs on home page and favorites [3-23](#)

---

## W

whitelist *See* Restrict application usage to the web browser  
 only

---

## X

xml [1-9](#)

