



## A

### AAA

- configuring authorization services [2-16](#)
- deleting authorization caches [2-200](#)
- setting up accounting [2-2](#)
- setting up a server for [2-16](#)
- specifying a server [2-22](#)

### AAA challenge text

- See authorization prompt

### access group [2-30](#)

### access list

- adding comments [2-42, 2-51](#)
- binding a group to an interface [2-30](#)
- configuring CiscoSecure ACL attribute [2-42, 2-51](#)
- creating [2-35](#)
- creating for IPsec [2-40, 2-49](#)
- downloading [2-35, 2-42, 2-51](#)
- generating denied packet syslog message [2-44, 2-52, 2-61](#)
- using RADIUS authorization [2-42, 2-51](#)
- using vendor-specific identifiers [2-42, 2-51](#)
- using with IPsec [2-45, 2-54](#)

### access-list

- adding comments [2-42, 2-51](#)

### access list entries [2-493](#)

### access lists

- adding
  - standard lists [2-65](#)
- adding EtherType access lists [2-36](#)
- deleting EtherType access lists [2-36](#)
- removing
  - standard lists [2-65](#)

### accounting

- providing user-based [2-2, 2-114, 2-489](#)
- setting up [2-2](#)
- using RADIUS [2-2, 2-114, 2-115, 2-489](#)
- using TACACS+ [2-114, 2-115, 2-116, 2-489](#)

### ACL

- See access list

### activation key

- displaying [2-495](#)
- updating [2-67](#)

### addressing

- assigning global pools [2-416](#)
- translations [2-416, 2-417](#)

### address mask reply, ICMP message [2-45, 2-53, 2-62](#)

### address mask request, ICMP message [2-44, 2-53, 2-62](#)

### Address Resolution Protocol

- See ARP

### Address Resolution Protocol, setting parameters [2-82](#)

### aliasing

- configuring [2-69](#)
- setting overlapping addresses for NAT [2-69](#)
- specifying for a network [2-70](#)

### alternate address, ICMP message [2-44, 2-53, 2-62, 2-344](#)

### application inspection

- See fixup protocol

### ARP

- adding
  - static entry [2-80](#)
- changing [2-80, 2-82](#)
- configuring
  - parameters [2-80](#)
  - persistence timer [2-80](#)
  - static proxy ARP mapping [2-80](#)
- disabling

- ARP inspection [2-80](#)
  - displaying the cache [2-80, 2-82](#)
  - physical addressing [2-80](#)
  - removing
    - cache timeout [2-80](#)
  - setting
    - hardware MAC address [2-80](#)
    - setting the timeout value [2-80, 2-82](#)
  - audience [xvii](#)
  - authentication
    - disabling
      - authentication verification [2-11](#)
      - globally [2-6](#)
      - on a specific access list [2-13, 2-14](#)
    - enabling
      - authentication verification [2-11](#)
      - globally [2-6](#)
      - on a specific access list [2-13, 2-14](#)
    - using certification authorities [2-88](#)
    - using LOCAL [2-6](#)
    - using RADIUS [2-6, 2-9](#)
    - using TACACS+ [2-9](#)
    - using token-based [2-243](#)
    - using with crypto maps [2-243](#)
    - using with IPsec [2-243](#)
  - authentication, authorization, and accounting
    - See AAA
  - authorization
    - disabling [2-18](#)
      - for a specific access-list command name [2-19](#)
      - services [2-15](#)
    - enabling
      - for a specific access-list command name [2-19](#)
      - local or TACACS server [2-18](#)
      - service [2-15](#)
    - setting AAA challenge text [2-84](#)
- 
- ## B
- buffer
    - packet capture [2-105](#)
  - buffering, circular [2-106](#)
- 
- ## C
- caching
    - URL [2-752](#)
  - capture
    - enabling [2-105](#)
    - selecting options [2-106](#)
  - capturing
    - buffering [2-106](#)
  - certificate revocation list
    - See CRL, using
  - certification authority
    - authenticating [2-88](#)
    - See CA
  - certification authority (CA)
    - configuring the server [2-98](#)
    - declaring [2-98](#)
    - deleting RSA keys [2-104](#)
    - including serial number in certificate [2-95](#)
    - obtaining an updated certificate revocation list (CRL) [2-93](#)
    - obtaining an updated CRL [2-92](#)
    - obtaining certificates [2-94](#)
    - querying a certificate or CRL [2-98](#)
    - revoking certificates [2-95](#)
    - saving data to the Flash memory [2-100](#)
    - saving RSA key pairs and certificates [2-100](#)
    - sending enrollment request [2-94](#)
    - using LDAP [2-98](#)
    - using PKI protocol [2-98](#)
    - using RA mode [2-89](#)
    - using RSA public key record [2-89](#)
  - changing

- firewall prompt label [2-341](#)
- host name [2-341](#)
- CiscoSecure 2.1, showing timeout values [2-703](#)
- Cisco VPN 3000 Client, configuring support for [2-762](#)
- Cisco VPN Client, setting up support for [2-716, 2-761](#)
- clear [2-112, 2-114, 2-149, 2-150](#)
- clearing
  - aaa accounting configuration [2-114](#)
  - AAA server configuration [2-113, 2-118](#)
  - access group configuration [2-119](#)
  - alias configuration [2-122](#)
  - authentication prompt [2-125](#)
  - clock settings [2-210](#)
  - commands [2-112, 2-149, 2-150](#)
  - configurations [2-112, 2-149, 2-150](#)
  - counters [2-112, 2-149, 2-150](#)
  - ISAKMP configuration [2-360](#)
  - local host network states [2-165](#)
  - logging [2-166, 2-619](#)
  - system buffer [2-503](#)
  - timeout values [2-199](#)
- CLI
  - prompt, changing
- clients
  - Oracle SQL\*Net [2-270](#)
  - SQL\*Net [2-270](#)
  - VPN [2-244](#)
- clock
  - setting [2-210](#)
  - setting Daylight Saving time [2-210](#)
  - setting time zone [2-210](#)
- command-line interface
  - See CLI
- command modes
  - changing [1-2](#)
  - configuration [1-3](#)
  - enabling [2-295](#)
  - exiting [2-447](#)
  - privileged [1-2](#)
  - subconfiguration [1-3](#)
  - unprivileged [1-2](#)
- commands
  - abbreviating [1-2](#)
  - changing modes [1-2](#)
  - completing [1-2](#)
  - firewall CLI help [1-2](#)
- compatible [2-210](#)
- conduit
  - adding or deleting [2-211](#)
- configuration
  - designating a TFTP server [2-212](#)
  - displaying [2-667](#)
  - entering configure mode [2-211](#)
  - synchronization [2-769](#)
  - using configure factory-default command [2-213](#)
  - using IKE mode [2-242, 2-244](#)
  - using the configure command [2-211](#)
- configuring
  - Diffie-Hellman groups [2-361](#)
  - FWSM [2-213](#)
  - interfaces [2-413](#)
  - interface security level [2-413](#)
  - IP addresses [2-349, 2-351](#)
  - NAT [2-417](#)
  - network address translation [2-416](#)
  - object groups [2-422](#)
  - privilege levels [2-646](#)
  - reverse path verification [2-353](#)
  - saving configuration [2-766](#)
  - showing running configuration [2-667](#)
  - showing start up configuration [2-679](#)
  - Unicast RPF IP [2-353](#)
  - URL filtering server [2-754](#)
  - VPN support [2-716, 2-761](#)
- connecting
  - embryonic process limit [2-418](#)
- connection flags
  - H.225 [2-520](#)

H.323 [2-520](#)

console

- changing settings [2-739](#)
- setting a timeout [2-214](#)
- using a session [2-271](#)

conversion error, ICMP message [2-45, 2-53, 2-62, 2-344](#)

copy

- image or file [2-222](#)
- running configuration [2-229](#)

CRL

See certificate revocation list

cryptography engine, running Known Answer Test [2-535](#)

crypto ipsec

- clearing security associations [2-141](#)
- creating dynamic map entries [2-234](#)
- creating security associations [2-237](#)
- deleting security association [2-237](#)
- reinitializing security associations [2-141](#)
- specifying the SPI [2-140](#)

crypto map

- creating dynamic entry [2-234](#)
- deleting dynamic entry [2-234](#)

---

## D

daisy-chaining [2-7](#)

debugging

- packet [2-264](#)

deleting

- authorization caches [2-200](#)

DHCP

- configuring a relay agent [2-286](#)
- polling [2-349, 2-351](#)
- relaying requests between interfaces [2-286](#)

Diffie-Hellman

- Group 5 [2-272](#)
- selecting a group [2-253](#)

Diffie-Hellman groups

- configuring [2-361](#)

- Group 1 [2-360](#)
- Group 2 [2-360](#)
- Group 5 [2-613](#)

disabling

- command modes [2-291](#)

disk

- copying files [2-231](#)

displaying

- See also showing
- software version [2-712](#)

documentation

- organization [xvii](#)

domain name, changing [2-293, 2-557](#)

dynamic map

- creating [2-294](#)
- viewing [2-294](#)

---

## E

Easy VPN Remote

- setting up support for [2-761](#)

echo literal [2-44, 2-53](#)

echo reply, ICMP message [2-44, 2-53, 2-62, 2-344](#)

EIGRP

- not supported [A-2](#)

EMBLEM, syslog message formatting [2-373](#)

embryonic connection limit [2-418](#)

enable [2-295](#)

enabling

- privileged mode [2-295](#)
- resetting default password [2-295](#)

encryption

- enabling IPsec [2-360](#)

encryption, key [2-22](#)

Enhanced Interior Gateway Routing Protocol

- See EIGRP

erasing configuration [2-766](#)

established connections

- using to permit connections [2-297](#)

- exiting
    - command modes [2-300](#)
  - extended access lists
    - adding EtherType access lists [2-36](#)
    - deleting EtherType access lists [2-36](#)
- 
- F**
- failover
    - debugging [2-270](#)
    - display [2-562](#)
    - saving crash information [2-232](#)
    - stateful failover
      - statistics [2-564](#)
  - filtering
    - HTTPS [2-319](#)
    - server [2-752](#)
  - firewall modules
    - daisy chaining [2-7](#)
  - Firewall Services Module
    - See also FWSM
  - fixup protocol
    - CTIQBE [2-324](#)
    - FTPSQL\*Net [2-324](#)
    - H.323 [2-324](#)
    - HTTP [2-324](#)
    - RSH [2-324](#)
    - session initiation protocol, enabling [2-328](#)
    - SIP
    - SMTP [2-324](#)
  - fixup protocols
    - FTP [2-324](#)
  - Flash memory
    - writing a configuration to [2-767](#)
  - Flood Defender
    - See flood guard
  - flood guard
    - disabling [2-332](#)
    - enabling [2-332](#)
  - fragments
    - managing [2-155, 2-334, 2-336, 2-575, 2-576](#)
    - NFS compatibility [2-155, 2-334, 2-336, 2-575, 2-576](#)
  - free memory, showing [2-624](#)
  - FTP
    - filtering [2-317](#)
    - fixup protocol [2-325](#)
  - FWSM [1-1](#)
    - ACEs [2-58](#)
    - AES support [2-240](#)
    - cache [2-752](#)
    - commands [1-1](#)
    - configuration [2-766](#)
    - configuring [2-213](#)
      - route maps [2-705](#)
    - configuring factory default [2-213](#)
    - console [2-12](#)
    - copying image or file [2-222](#)
    - CPU [2-527](#)
    - crashdump [2-232](#)
    - displaying
      - configuration [2-667](#)
    - factory default [2-213](#)
    - file copy from disk [2-231](#)
    - FTP filtering [2-317](#)
    - global [2-337, 2-417, 2-729](#)
    - HTTPS filtering [2-319](#)
    - interface monitoring [2-313](#)
    - mode [2-403](#)
    - modes [1-2](#)
    - packet debugging [2-264](#)
    - PDM [2-437](#)
    - port values [B-1](#)
    - preconfiguring [2-483](#)
    - protocol values [B-5](#)
    - running configuration [2-229](#)
    - software version [2-712](#)
    - synchronizing configurations [2-769](#)

**G**

global IP addresses, associating a network with [2-416](#)

**H**

H.225

connection flag [2-520](#)

hardware

ARP addressing [2-80](#)

Help, firewall CLI [2-339](#)

history, command [2-581](#)

host name

changing [2-341](#)

**I**

ICMP

debugging [2-269](#)

tracing [2-270](#)

ICMP messages

information reply [2-44, 2-53, 2-62](#)

information request [2-44, 2-53, 2-62](#)

network address translation of [2-326](#)

ICMP message type [2-44, 2-53](#)

ICMP redirection, ICMP message [2-344](#)

ICMP types

interpreting [2-425](#)

selecting [2-344](#)

specifying selective access [2-44, 2-53, 2-62](#)

using in access lists [2-44, 2-53, 2-62](#)

IKE mode, configuring [2-242, 2-244](#)

information reply, ICMP message [2-344](#)

information request, ICMP message [2-344](#)

interactive prompts [2-483](#)

interfaces, firewall

binding an access list to [2-30](#)

configuring [2-347](#)

displaying parameters [2-347](#)

static or default route [2-461](#)

Internet Control Message Protocol

See ICMP

Internet Group Management Protocol

See IGMP

IP address

using in certificates [2-95](#)

ISAKMP

enabling IPsec [2-355, 2-360](#)

negotiating security associations [2-355, 2-360](#)

setting keepalive interval [2-355](#)

specifying the keepalive lifetime [2-355](#)

ISAKMP policy

See ISAKMP

**K**

KAT, running [2-535](#)

key, authentication [2-22](#)

killing

Telnet session [2-363](#)

Known Answer Test

See KAT [2-535](#)

**L**

LDAP [2-98](#)

using with a certification authority (CA)

Lightweight Directory Access Protocol

See LDAP

line numbers

setting [2-46, 2-55](#)

literal names [B-1](#)

local host

displaying detailed information [2-614](#)

network states [2-614](#)

local or TACACS server [2-18](#)

logging

- changing message levels [2-375](#)
- changing system message level [2-374](#)
- configuring time stamps [2-371](#)
- disabling [2-371](#)
- enabling [2-371](#)
- messages [2-617](#)
- monitoring [2-371](#)
- queue size [2-371](#)
- sending messages to console [2-373](#)
- setting facilities [2-371](#)
- SNMP
  - specifying a system log (syslog) server [2-371](#)
  - specifying a system log server [2-371, 2-373](#)

---

## M

- MAC address
  - configuring ARP [2-80](#)
  - exempting a device based on [2-381](#)
  - setting as ARP table entry [2-80](#)
- MAC address table
  - resource management [2-366](#)
- managing
  - with PDM [2-437](#)
- mask reply, ICMP message [2-344](#)
- mask request, ICMP message [2-344](#)
- maximum transmission unit
  - See MTU
- maximum transmission unit (MTU)
  - specifying [2-409](#)
- message types [2-44, 2-53](#)
- mobile redirection, ICMP message [2-45, 2-53, 2-62, 2-344](#)
- modes [2-403](#)
- modes, command [1-2](#)
- monitoring
  - firewall performance [2-440](#)
- MTU
  - showing
  - specifying

- multicasting
  - configuring a static route [2-403, 2-405](#)
- multiple mode [2-403](#)

---

## N

- N2H2
  - caching server requests [2-752](#)
  - specifying server parameters [2-754](#)
  - URL filtering [2-752](#)
- naming
  - interfaces [2-413](#)
- NAT
  - aliasing [2-69](#)
  - configuring [2-416](#)
  - of ICMP messages [2-326](#)
  - setting overlapping addresses [2-69](#)
- network alias, specifying [2-70](#)

---

## O

- object grouping
  - defining [2-422](#)
- object groups
  - configuring [2-422](#)
  - grouping [2-426](#)
  - ICMP [2-422, 2-425](#)
  - network [2-422, 2-426](#)
  - protocol [2-422, 2-426](#)
  - removing [2-424](#)
  - services [2-422, 2-426](#)

---

## P

- packet capture, enabling [2-105](#)
- packets
  - tracing [2-269](#)
- paging, screen

- enabling or disabling [2-432](#)
- parameter-problem [2-44](#)
- parameter problem, ICMP message [2-44, 2-53, 2-62, 2-344](#)
- password
  - setting for console access [2-433](#)
  - setting for Telnet [2-433](#)
- PAT
  - disabling [2-337](#)
  - enabling [2-337](#)
  - limitations [2-327](#)
- PDM
  - commands in firewall configuration [2-435](#)
  - disconnecting [2-436](#)
  - logging [2-435](#)
  - showing PDM sessions [2-436](#)
- permitting
  - return connections on established connections [2-297](#)
- physical addressing, ARP [2-80](#)
- pinging
  - IP addresses [2-442](#)
  - using with user authorization [2-17](#)
- ping message types [2-44, 2-53](#)
- Port Address Translation
  - See PAT
- port literal names [B-1](#)
- port literals [B-1](#)
- port values for FWSM [B-1](#)
- prefix list [2-352](#)
- preshared key
  - configuring for VPN [2-763](#)
- privileged mode
  - starting [2-295](#)
- privilege levels
  - changing between [2-444](#)
  - showing current [2-544](#)
- prompt
  - "(config)#" [1-3](#)
- protocols
  - using with port literals [B-5](#)

- protocol values [B-5](#)
- proxy server
  - using with VoIP [2-328](#)

---

## Q

- quitting
  - configuration or privileged mode [2-447](#)

---

## R

- RADIUS [2-6](#)
- randomizing, sequence numbers [2-416](#)
- rebooting
  - See reloading
- redirect, ICMP message [2-44, 2-53, 2-62](#)
- redirection, ICMP message [2-344](#)
- Related Documentation [xviii](#)
- reloading
  - firewall configuration from Flash memory [2-450](#)
  - saving configuration changes [2-450](#)
  - without confirmation [2-450](#)
- resource management
  - resource types [2-366](#)
- RIP
  - broadcasting a default route [2-457](#)
  - changing settings [2-457](#)
  - enabling routing table updates
  - MD5 authentication [2-458](#)
  - version 2 support [2-457](#)
- route
  - map configuration [2-705](#)
- route, static or default [2-461](#)
- router
  - changing default address sent [2-286, 2-287](#)
  - router advertisement [2-44](#)
  - router advertisement, ICMP message [2-44, 2-53, 2-62, 2-344](#)
  - router solicitation [2-44](#)

router solicitation, ICMP message [2-44](#), [2-53](#), [2-62](#), [2-344](#)

Routing Information Protocol

See RIP

RSA public key record, using with a certification authority (CA) [2-89](#)

running configuration, showing [2-667](#)

## S

saving

configuration to another location [2-766](#)

configuration to Flash memory [2-766](#), [2-769](#)

Secure Socket Layer

See SSH

security associations

creating [2-237](#)

deleting [2-237](#)

negotiating [2-355](#), [2-360](#)

viewing [2-237](#)

security level

assigning [2-413](#)

Security Parameter Index

See SPI

sequence numbers, randomizing [2-416](#)

server

specifying a TFTP server [2-766](#)

specifying for AAA [2-22](#)

services

enabling [2-475](#)

handling IDENT connections [2-475](#)

session, AccessPro [2-485](#)

Session initiation protocol

See SIP

setting

DHCP polling [2-349](#), [2-351](#)

IP addresses [2-349](#), [2-351](#)

show [2-501](#)

showing

AAA configuration [2-489](#)

AAA proxy limit [2-490](#)

AAA server configuration [2-491](#)

aaa-server configuration [2-491](#)

access-group configuration [2-492](#)

access-list configuration [2-493](#), [2-494](#)

active connections [2-518](#)

alias configuration [2-497](#), [2-498](#)

ARP timeout [2-500](#)

authentication prompt [2-501](#)

buffer utilization [2-503](#)

CA certificates [2-506](#)

checksum [2-511](#)

command history [2-581](#)

command information [2-485](#)

current configuration [2-766](#), [2-769](#)

current privilege levels [2-544](#)

filtering displayed output [2-485](#)

firewall performance [2-440](#)

free memory [2-624](#)

interface names [2-413](#)

local host network states [2-614](#)

MTU [2-631](#)

privilege levels [2-646](#)

processes [2-647](#)

running configuration [2-667](#)

software versions [2-712](#)

start up configuration [2-679](#)

system memory utilization [2-624](#)

technical support output [2-685](#)

Telnet sessions [2-765](#)

timeout values [2-743](#)

URL server [2-709](#)

Simple Network Translation Protocol

See SNMP

single context [2-403](#)

SIP [2-328](#)

fixup protocol

session initiation protocol [2-328](#)

setting protocol timer values [2-743](#)

- setting timeout values [2-743](#)
- SNMP
  - configuring contact, location, and host information [2-724](#)
  - configuring on the firewall [2-724](#)
  - logging
  - software version, showing [2-712](#)
  - source [2-44, 2-53, 2-62](#)
  - source quench, ICMP message [2-44, 2-53, 2-62, 2-344](#)
- SPI
  - coordinating with peer
  - specifying [2-140](#)
- split tunneling, using [2-762](#)
- SSH
  - debugging [2-270](#)
  - specifying a host
  - supporting secure shell [2-726](#)
- standard access lists
  - adding [2-65](#)
  - deleting [2-65](#)
- start up configuration, showing [2-679](#)
- storing configuration [2-766](#)
- synchronizing
  - configuration [2-769](#)
- syslog [2-44, 2-52, 2-61](#)
- syslog server
  - EMBLEM formatting [2-372, 2-373](#)
- system logging
  - See logging
- system options
  - changing [2-733](#)
  - disabling DNS A record replies [2-733](#)
- randomizing packet sequence number [2-730](#)
- returning a reset flag (RST) to the source [2-475](#)
- Telnet
  - console debugging [2-270](#)
  - icmp tracing [2-270](#)
  - setting the console timeout [2-195, 2-736](#)
  - setting the password [2-433](#)
  - showing active sessions [2-765](#)
  - terminating [2-363](#)
  - terminating a session [2-363](#)
  - using a Trace Channel [2-270](#)
- terminal
  - changing console settings [2-739](#)
- terminating
  - Telnet session [2-363](#)
- TFTP
  - configuring a server [2-212](#)
  - saving configuration to another location [2-766](#)
  - specifying a server [2-741](#)
- time-exceeded [2-44](#)
- time exceeded, ICMP message [2-44, 2-53, 2-62, 2-344](#)
- timestamp
  - reply, ICMP message [2-44, 2-53, 2-62, 2-344](#)
  - request, ICMP message [2-44, 2-53, 2-62, 2-344](#)
- timestamp-reply [2-44](#)
- timing out
  - freeing an RPC slot [2-743](#)
  - setting maximum idle time [2-743](#)
  - setting translation slot value [2-743](#)
- tracing
  - ICMP, SQL\*Net, and packets [2-269](#)
- translating
  - addresses [2-417](#)
- translation
  - setting timeout values [2-743](#)
  - setting UDP, RPC, and H.323 timeout values [2-744](#)
- transparent mode [2-403](#)
- Trivial File Transfer Protocol
  - See TFTP

---

**T**

TACACS [2-114, 2-115, 2-116, 2-489](#)

TCP

port literals [B-1](#)

preventing packet randomization [2-728](#)

## TurboACL

- disabling [2-35](#)
- enabling [2-35](#)

---

**U**

## UDP

- port literals [B-1](#)
- setting idle time until slot is freed [2-743](#)

## Unicast RPF IP

- implementing [2-353](#)
- spoofing [2-353](#)

unreachable, ICMP message [2-44](#), [2-53](#), [2-62](#), [2-344](#)

## URL

- caching [2-752](#)
- configuring filtering server [2-754](#)
- filtering [2-321](#), [2-753](#)

user accounting [2-2](#), [2-114](#), [2-489](#)

## user authentication

See authentication

## utilization

- CPU [2-527](#)

---

**V**

## version

- displaying [2-712](#)

## viewing

Seeshowing

## Virtual Private Network

See VPN

## Voice over IP

See VoIP

## VoIP

- SIP fixup
- using proxy servers [2-328](#)

## VPN

- configuring a preshared key [2-763](#)

configuring support [2-716](#), [2-761](#)

creating a group policy [2-762](#)

downloading group names [2-762](#)

global lifetime timeout values [2-763](#)

setting up support for Cisco VPN Client [2-761](#)

setting up support for Easy VPN Remote [2-761](#)

using remote clients [2-244](#)

using split tunneling [2-762](#)

---

**W**

## Websense

caching server request [2-752](#)

specifying as URL filtering server [2-754](#)

specifying server parameters [2-754](#)

specifying URL filtering server [2-755](#)

URL filtering [2-752](#)

## web server

caching responses [2-752](#)

## writing

configuration to Flash memory [2-766](#), [2-769](#)

writing a configuration [2-766](#)

---

**X**

## xlate

See translation

