



## INDEX

---

## Symbols

---

## Numerics

- 16-port modules
  - BB\_credits **9-9**
  - LEDs **9-11**
  - preserving configurations **6-6**
  - See also switching modules
- 32-port modules
  - configuration guidelines **9-7**
  - preserving configurations **6-6**
  - SPAN guidelines **22-6**
  - See also switching modules

---

## A

- AAA
  - authorization and authentication process **14-4**
  - setting authentication **14-5**
  - usage **1-7**
  - user accountability **14-11**
- accounting **14-11**
- active
  - modules **6-2**
  - states **4-7**
  - zones **12-6**
  - zone sets **12-10**
- adding
  - IP addresses **16-14**
  - ports to a PortChannel **11-6**

- SNMP communities **14-23**
- switches **3-4**
- address-allocation cache **18-12**
- Address Resolution Protocol
  - See ARP
- administrative speed
  - configuring **9-9**
- administrative states
  - description **9-5**
- administrator passwords
  - configuring **3-9**
  - configuring switch **3-3**
  - creating additional accounts **3-5**
  - default **3-5**
  - recovering **14-12**
  - requirements (note) **3-6, 3-10**
- advertisement packets
  - setting time intervals **16-15**
- aggregated flow statistics **15-13**
- aliases
  - configuring **12-4**
- ALPA **9-21**
- ARP
  - clearing and viewing entries **16-6**
  - IP services **1-5**
  - assigning
    - alias names **12-4**
    - contact information **17-2**
    - domain IDs **18-4**
    - FC IDs **15-8**
    - global keys **14-14**
    - host key **14-13**
    - users **14-23**

zone members **12-4**

authentication

  See MD5 authentication

  See simple text authentication

authentication, authorization, and accounting

  See AAA

automatic synchronization

  conditions **4-7**

  modules **4-6**

AutoNotify

  destination profile (note) **17-5**

  registration **17-3**

  service contract **17-2**

auto port mode

  configuring **9-8**

  description **9-4**

  interface configuration **9-2**

---

**B**

basic input/output system

  See BIOS

BB\_credits

  configuring **9-9**

  reason codes **9-6**

beacon mode

  configuring **9-10**

  identifying LEDs **9-11**

  LEDs **6-9**

Berkeley Packet Filter

  See BPF

BIOS

  boot sequence **5-14**

  recovering corrupted bootflash **5-16**

  recovery sequence **5-15**

  setup (figure) **5-17**

boot

  sequence **5-14**

  variable synchronization **4-6**

bootflash

  copying to **5-5**

  description **2-10**

  device **5-5**

  file system **5-1**

  initializing **5-4**

  recovering corrupted **5-14 to 5-15**

  space requirements **5-3**

  See also internal bootflash

bootloader

  loading kickstart **5-14**

  skipping phases **5-19**

  upgrading **5-24**

bootup diagnostics **6-3**

BPF

  library **23-11**

  See also libpcap freeware

broadcast

  in-band addresses default **6-10**

  routing **15-9**

buffer-to-buffer credits

  See BB\_credits

build fabric frames **18-3**

---

**C**

cache

  See address-allocation cache

Call Home

  configuring **17-3 to 17-7**

Call Home

  functionality **1-5**

  message format options **17-2**

capture filters **23-11**

chassis

  types **6-1**

checks

  See compatibility checks

  See heartbeat checks

- See watchdog checks
- Cisco MDS 9200 Series
- configuring interoperability **23-18**
  - LEDs **6-7**
  - mgmt0 LEDs **6-9**
  - supervisor modules **6-2**
  - verifying interoperability **23-22**
- Cisco MDS 9216 switches
- high availability **1-3, 4-2**
  - modules **1-6, 6-1**
  - overview **1-1**
  - supervisor module **6-4**
- Cisco MDS 9500 Series
- configuring interoperability **23-17**
  - high availability **1-3, 4-2**
  - LEDs **6-8**
  - overview **1-1**
  - supervisor modules **6-2**
  - verifying interoperability **23-19**
- Cisco MDS 9509 Directors
- modules **1-6, 6-1**
  - overview **1-1, 1-2**
- clearing
- FIB statistics **15-13**
  - FSPF counters **15-9**
  - zone sets **12-10**
- CLI
- accessing submodes **2-2**
  - alternative **1-8**
  - command modes **2-2**
  - syslog provisioning **1-7**
  - updating SNMPv3 passwords **14-22**
- clock modules
- monitoring status **7-9**
- CMOS
- configuration **5-17**
  - saving changes **5-18**
- command-line interface
- See CLI
- commands
- saving output to files **2-16**
- CompactFlash
- devices **5-2, 5-4, 5-5**
  - disk **5-1**
  - slot 0 **5-5**
  - space requirements **5-3**
- compatibility checks **11-7**
- computing routes **15-1**
- congestion control methods
- See edge quench congestion control
  - See FCC
  - See path quench congestion control
- consistent switch states **11-6**
- console port
- logging in **5-8**
- console session
- severity levels **20-5**
- control traffic
- disabling **19-4**
- cores **25-6**
- 
- D**
- databases
- See zone databases
- data field
- configuring size **9-10**
- dead time interval **15-6**
- default gateway
- BIOS setup configuration **5-17**
  - configuring mgmt0 Ethernet interfaces **9-13**
  - recovering loader> prompt **5-19**
  - recovering switch(boot)# prompt **5-21**
- default groups **14-22**
- default zones
- description **12-8**
  - interoperability **23-16**
- deleting

- FSPF configurations **15-4**
  - PortChannels **11-6**
  - destination IDs
    - exchange based **11-5**
    - flow based **11-4**
    - frame identification **19-2**
    - frame loop back **23-3**
    - in-order delivery **15-10, 19-2**
    - load balancing **1-5, 11-1**
    - path selection **8-6**
  - destination profiles
    - configuring **17-5**
  - device IDs
    - Call Home format **17-12, 17-13, 17-14, 17-15**
    - copying files **14-22**
    - report capacity **21-1**
  - Device View
    - description **1-8**
  - digital signature algorithm
    - See DSA key pairs
  - Dijkstra's algorithm **15-2**
  - disabling routing protocols **15-4**
  - discovered
    - LUNs **21-3**
    - targets **21-2**
  - display filters
    - selective viewing **23-10**
  - disruptive
    - switchover **4-4**
    - upgrades **5-3**
  - distribution tree **15-9**
  - documentation
    - related documents **xx**
  - domain IDs
    - configuring **18-4**
    - distributing **18-2**
    - failure **9-6**
    - interoperability **23-16**
    - preferred **18-5**
  - range **2-18**
  - static **18-5**
  - domain manager
    - isolation **9-6**
  - domain names
    - defining **16-19**
  - Domain Name System servers
    - See DNS servers
  - domain overlap
    - isolation **9-6**
  - drop latency time
    - configuring **15-12**
  - dsa key pairs
    - generating **14-18**
- 

**E**

- edge quench congestion control
  - description **19-2**
- egress port **22-10**
- EISL
  - functionality **1-4**
  - PortChannel links **11-1**
- ELP failure **9-6**
- e-mail notification
  - Call Home **17-1**
- environmental monitors **6-7, 6-8**
- environment variables
  - image usage **5-7**
  - updating **5-6**
- E ports
  - 32-port guidelines **9-7**
  - classes of service **9-3**
  - configuring **9-8**
  - FSPF topology **15-2**
  - interface modes **9-2**
  - isolation **9-6**
  - recovering from isolation **12-9**
  - SPAN **22-3**

trunking **1-4**  
 trunking configuration **10-3**  
 error disabled code **9-6**  
 error messages  
     description **20-2**  
 error state **5-23**  
 ESC failure **9-6**  
 Ethereal freeware  
     analyzer **23-6**  
     information **23-5**  
 exchange IDs  
     in-order delivery **15-10**  
     load balancing **1-5, 11-1, 23-3**  
     path selection **8-6**  
 exchange link parameter  
     See ELP failure  
 exporting  
     zone databases **12-9**  
 extended ISL  
     See EISL  
 external CompactFlash  
     See CompactFlash

---

**F**

fabric  
     See build fabric frames  
     See reconfigure fabric frames  
 Fabric Analyzer  
     capture range **2-18**  
     configuring **23-7**  
     description **23-5**  
     frame range **2-18**  
 Fabric Configuration Server  
     See FCS  
 fabric login  
     See FLOGI  
 Fabric Manager  
     description **1-7**  
     Device View **1-8**  
     Fabric View **1-8**  
     fabric names  
         setting **18-7**  
     fabric pWWNs  
         configuring zones **12-4**  
         zone membership **12-2**  
     fabric reconfiguration  
         fcdomain phase **18-2**  
     fabric shortest path first  
         See FSPF  
     Fabric View  
         description **1-8**  
     fan modules  
         monitoring status **7-9**  
     fan trays  
         overview **1-2**  
     fault tolerant fabric  
         example (figure) **15-2**  
     FC aliases  
         configuring zones **12-4**  
     fcanalyzer  
         clearing hosts **23-9**  
         displaying filters **23-10**  
     FCC  
         benefits **19-2**  
         default settings **19-4**  
         enabling **19-3**  
         frame handling **19-2**  
         logging facility **20-2**  
     fcdomain  
         configuring **18-1**  
         default settings **18-12**  
     FC IDs  
         address format **2-18**  
         allocating **18-2, 23-15**  
         allocating areas **23-15**  
         configuring zones **12-4**  
     Fcot not present **9-6**

fcping  
  invoking **23-4**

FCS  
  configuring **24-3**  
  description **24-2**  
  logging facility **20-2**  
  significance **24-3**

fctrace  
  invoking **23-3**

Fibre Channel analyzers **22-8**

Fibre Channel Congestion Control  
  See FCC

Fibre Channel domain  
  See fcdomain

Fibre Channel traffic  
  SPAN sources **22-3**

file system  
  formatting **5-4**  
  redirection **2-16**  
  volatile **2-10**

File Transfer Protocol  
  See FTP

filters  
  capture **23-11**  
  defining display **23-11**

FLOGI  
  displaying details **13-1**  
  logging facility **20-2**  
  flow statistics **15-13**

FL ports  
  classes of service **9-3**  
  configuring **9-8**  
  fctrace **23-3**  
  interface modes **9-2**  
  nonparticipating code **9-7**  
  persistent FC IDs **18-8**  
  SPAN **22-3**

F ports  
  classes of service **9-3**

configuring **9-8**  
  interface modes **9-2**  
  nonparticipating code **9-7**  
  persistent FC IDs **18-8**  
  SPAN **22-3**

frames  
  encapsulation **22-7**  
  flow **1-6**  
  reordering **15-10**

FSPF  
  alternative paths **15-1**  
  clearing counters **15-9**  
  computing link cost **15-5**  
  configuring globally **15-3**  
  configuring on interfaces **15-5**  
  default settings **15-20**  
  disabling on interfaces **15-6**  
  disabling routing protocols **15-4**  
  hold time range **2-18, 15-1**  
  interoperability **23-17**  
  link state protocol **15-2**  
  reconvergence time **15-2**  
  routing services **15-1**  
  topologies example **15-2**

FTP  
  logging facility **20-2**

full zone set  
  considerations **12-6**  
  distribution **12-10**

Fx ports  
  32-port default **9-7**  
  configuring **9-8**  
  FCS **24-2**  
  interface modes **9-4**

---

**H**

HA policy **25-7**

hardware  
  displaying inventory **7-2**  
  status description **6-3**

hard zoning **12-5**  
 HA-standby **4-5, 6-2**  
 HA switchover **4-3, 4-6**  
 heartbeat checks **25-8**  
 hello time interval **15-5**  
 hidden routes **15-15**  
 high availability  
   default setting **4-8**  
   functionality **1-3, 4-2**  
   process restartability **4-5**  
   software upgrade **5-3**  
   status **4-6**  
   See also HA policy  
   See also HA standby  
   See also HA switchover

See user IDs  
 See VR IDs  
 See VSAN IDs  
 images  
   See kickstart images  
   See software images  
   See system images  
 importing database **12-9**  
 inactive code **9-6**  
 inconsistent switch states **11-6**  
 ingress port **22-8**  
 in-order delivery **15-10**  
   enabling **15-11**  
   in-order guarantee **15-10**  
   insufficient power **6-3**  
 interface  
   adding to PortChannels **11-7**  
   configuring FSPF **15-5**  
   suspended states **11-7**  
 interfaces  
   characteristics **9-2**  
   configuring **9-7**  
   data field size **9-10**  
   default settings **9-12**  
   description **9-9**  
   modes **9-2, 9-8**  
   reason codes **9-5**  
   states **9-5**  
 internal bootflash  
   description **2-10**  
   flash devices **5-2**  
   See also bootflash  
 internal switch states  
   description **4-8**  
 interoperability  
   configuring **23-16**  
   verifying status **23-19 to 23-24**  
 inter-switch links  
   See ISL

identical passwords  
 CLI and SNMP **14-22**

IDs  
 CCO IDs **17-3**  
 contract IDs **17-4, 17-12**  
 customer IDs **17-4**  
 image version and IDs **5-1, 5-2**  
 login IDs **3-5**  
 process IDs **3-25, 25-2, 25-6**  
 profile IDs **17-5**  
 region ID **15-4**  
 serial IDs **17-13, 17-14, 17-15**  
 server IDs **17-13, 17-14, 17-15**  
 site IDs **17-4, 17-12**  
 See destination IDs  
 See device IDs  
 See domain IDs  
 See exchange IDs  
 See FC IDs  
 See port IDs  
 See source IDs

invoking fcping **23-4**  
 IP address  
   address format **2-18**  
   SMTP server **17-7**  
 IP addresses  
   configuring in VSANs **16-5**  
 IPFC  
   logging facility **20-2**  
 IP features  
   default settings **16-20**  
 IP forwarding  
   disabling **16-5**  
 IP over Fibre Channel  
   See IPFC  
 IP routing  
   static **1-5**  
 IP services  
   default settings **16-19**  
 ISL  
   PortChannel links **11-1**  
 isolation  
   reason codes **9-6**

---

**K**

kickstart images  
   comparison **5-11**  
   compatibility (note) **5-10**  
   description **5-2**  
   downloading **5-4**  
   KICKSTART variable **5-2**  
   loading system images **5-14**  
   overview **5-1**  
   recovering corrupted **5-19**  
   recovery **5-21**  
   recovery interruption **5-15**  
   specifying **5-11**  
   verifying integrity **5-12**

---

**L**  
 LEDs  
   identifying beacon **9-11**  
 libpcap freeware **23-5**  
 link cost **15-2**  
 link failure **9-6**  
   high availability **4-2**  
 load balancing **11-1**  
   attributes **8-6**  
   guarantee **8-7**  
   mechanisms **11-4**  
 local capture **23-7**  
 log files **25-6**  
   configuring **20-6**  
 logging  
   default settings **20-12**  
   facilities **20-2**  
   severity levels **20-3**  
   system messages **20-2**  
 logical unit numbers  
   See LUNs

loop monitoring **23-15**  
 loop port **23-15**  
 LSR **15-17**  
 LUNs  
   address format **2-18**  
   displaying discovered, example **21-3**

---



---

**M**

MAC address  
   format **2-18**  
   major threshold **6-8**  
 Management Information Base  
   See MIB  
 management module **6-7**  
 management redundancy  
   high availability **4-2**

MD5 authentication **16-16**  
memory test **5-15, 5-16**  
mgmt0 interfaces  
  autosensing port **9-13**  
  configuring **9-13**  
  configuring ethernet ports **16-3**  
  overview **9-1**  
  recovery from switch(boot)# prompt **5-21**  
  upgrading switches **5-3**  
minor threshold **6-8**  
modify existing users **14-21**  
module  
  configuring logging **20-6**  
module configuration  
  sample scenarios **6-6**  
module status **9-1**  
module temperature **7-8**  
monitoring traffic **22-6**  
multicast routing **15-9**

---

**N**

name server  
  interoperability **23-17**  
name server proxy **13-3**  
network administrator **2-18**  
network operator **2-18**  
Network Time Protocol  
  See NTP  
network traffic  
  monitoring **22-6**  
next hop domain ID **15-8**

NL ports  
  fctrace **23-3**  
  interface modes **9-4**  
  zone enforcement **12-5**  
node WWNs  
  See nWWNs  
nondisruptive

restart **4-2**  
switchover **4-4**  
upgrades **5-3, 5-7, 5-10**  
nondisruptive restart **4-2**  
nonparticipating code **9-7**  
non-trunking ISL **10-2**  
nonvolatile storage **6-6**  
N ports  
  fctrace **23-3**  
  zone enforcement **12-5**  
  zone membership **12-2**  
NTP  
  logging facility **20-3**  
nWWNs  
  address format **2-18**  
Nx ports  
  hard zoning **12-5**

---

**O**

offline code **9-6**  
operational interfaces  
  viewing PortChannels **11-9**  
operational state **9-8**  
operational state setting  
  description **9-5**  
originator exchange IDs  
  See exchange IDs  
out-of-order delivery **15-10**

---

**P**

password recovery **14-12**  
path discovery **23-3**  
path quench congestion control  
  description **19-2**  
permitted filters **23-12**  
persistent FC ID **18-8**

persistent FC IDs  
     displaying **18-11**  
 port aggregation **4-2**  
 PortChannel  
     configuring FC routes **15-8**  
     functionality **1-5**  
     high availability **4-2**  
     in-order guarantee **15-11**  
     link changes **15-11**  
     link failure **15-3**  
     load balancing **1-5**  
     logging facility **20-3**  
     membership **11-8**  
     range **2-18**  
     reason codes **9-7**  
 PortChannels  
     adding interfaces **11-6**  
     configuring **11-5**  
     default settings **11-11**  
     deleting **11-6**  
     examples **11-2**  
     forcing additions **11-7**  
     guidelines **11-8**  
     interoperability **23-16**  
     SPAN **22-3**  
     trunking comparison **11-3**  
 port group **9-7**  
 port IDs  
     configuring zones **12-4**  
     registering objects **23-13**  
 port modes  
     auto **9-4**  
 Port world wide name  
     See pWWN  
 port WWNs  
     See pWWNs  
 power supplies **1-2, 6-7, 6-8**  
     configuring **7-5**  
     displaying configuration **7-5**

guidelines **7-5**  
 modes **7-5**  
 power usage  
     displaying details **7-4**  
 preempt option **16-16**  
 preferred domain IDs **18-5**  
 preshared key **14-14**  
 principle switch **18-4, 18-5**  
     selecting **18-1**  
 private device **9-21**  
 process ID **25-6**  
 Process Logs **25-4**  
 process restartability **4-5**  
 protocol analysis **23-5**  
 pWWNs  
     address format **2-18**  
     configuring zones **12-4**  
     zone membership **12-2**

## Q

QoS  
     default settings **19-4**  
     displaying information **19-4**  
     enabling control traffic **19-4**  
     logging facilities **20-3**  
     priority queuing **1-6**  
 quality of service  
     See QoS

## R

R\_A\_TOV time **9-6**  
 RADIUS  
     AAA solutions **1-7**  
     authorization process **14-16**  
     configured parameters **14-17**  
     secret key **1-7**

setting preshared key **14-14**  
 specifying servers **14-13**  
 specifying time-out **14-14**  
 rebooting switch **6-5**  
 reconfigure fabric **9-6**  
 reconfigure fabric frames **18-3**  
 reconvergence time  
     FSPF **15-2**  
 recovering passwords **14-12**  
 recovery sequence **5-15**  
 redundancy states **4-7**  
 redundant physical links **15-3**  
 Registered State Change Notification  
     See RSCN  
 remote capture **23-7, 23-9**  
 remote capture daemon **23-6**  
 Remote Capture Protocol  
     See RPCAP  
 Remote Monitoring  
     See RMON  
 retransmit intervals **15-7**  
 route cost  
     computing **15-5**  
 routing  
     See broadcast routing  
     See IP routing  
 RPCAP  
     Ethereal communication **23-6**  
 rsa1 key pairs  
     generating **14-18**  
 rsa key pairs  
     generating **14-18**  
 RSCN  
     logging facility **20-3**  
 run time checks **15-8**

---

**S**  
 SAN operating system

See SAN-OS  
 SAN-OS **5-2**  
 SCSI LUNs  
     discovering targets **21-1**  
 SD ports  
     bidirectional traffic **22-10**  
     configuring **9-8, 22-6**  
     interface modes **9-2, 9-4**  
     secondary MAC address **23-13**  
 Secure Shell  
     See SSH  
 security features  
     default settings **14-24**  
 security parameter index  
     See SPI  
 See MAC address  
     See also WWNs  
 selective purging  
     persistent FC IDs **18-9**  
 severity levels  
     logging **20-6**  
 shutdown state **9-7**  
 Simple Network Management Protocol  
     See SNMP  
 simple text authentication **16-16**  
 simulating  
     Call Home **17-8**  
 slot0  
     formatting **5-4**  
 small computer system interface  
     See SCSI  
 SMARTnet **17-3**  
 SMTP  
     server address **17-6**  
 SNMP  
     access control **14-20**  
     access groups **14-21**  
     CLI configuration **14-20**

- community strings **14-20**
- configuring from CLI **14-22**
- counter Information **14-24**
- displaying information **14-23**
- groups **14-21**
- read-write access **14-23**
- server contact **17-2**
- versions **14-20**
- SNMP manager
  - FCS **24-3**
- SNMPv3
  - security features **14-20**
- software image
  - startup configuration **5-9**
  - synchronizing **5-8**
- software images
  - bootflash corruption **5-14**
  - copying **5-13**
  - corruption **5-14**
  - errors **5-7**
  - installing **5-7**
  - kickstart images **5-2**
  - nondisruptive upgrades **5-7**
  - recovery procedure **5-15**
  - reloading **5-6**
  - replacing **5-10**
  - saving **5-9**
  - space requirement **5-3, 5-5**
  - synchronizing **4-6**
  - system image **5-2**
  - upgrade requirements **5-3**
  - upgrading **5-1, 5-2, 5-8**
  - variables **5-2**
- software upgrade
  - high availability **4-2**
- software upgrades
  - disruptive **5-5**
- soft zoning **12-5**
- source IDs
- Call Home event format **17-12**
- exchange based **11-5**
- flow based **11-4**
- frame identification **19-2**
- frame loop back **23-3**
- in-order delivery **15-10**
- load balancing **1-5, 11-1**
- path selection **8-6**
- SPAN
  - configuring sessions **22-4**
  - default settings **22-12**
  - egress source **22-2**
  - encapsulating frames **22-7**
  - FC analyzers **22-8**
  - ingress source **22-2**
  - monitoring traffic **22-2**
  - source configuration **22-4**
  - sources **22-3**
- speed
  - LEDs **6-9**
- SPI
  - configuring virtual router **16-16**
- SSH
  - default service **14-17**
  - force option **14-18**
  - host key pair **14-18**
  - protocol status **14-19**
  - session **5-5, 5-8**
- SSH session
  - message logging **20-5**
- standby module **6-2**
  - monitoring **4-2**
- standby supervisor **4-6**
- startup configuration
  - saving **5-6**
- startup configuration files **5-2**
- stateful
  - HA-switchover **4-3**
- stateless

warm switchover **4-3**  
 static domain IDs **18-5**  
 static routes **8-8**  
   run time checks **15-8**  
 status  
   LEDs **6-9**  
 storage  
   permanent and temporary **2-10**  
 storage devices  
   access control **12-1**  
 subnet mask  
   BIOS setup configuration **5-17**  
   configuring IP routes **16-6**  
   configuring mgmt0 **3-19**  
   configuring mgmt0 interfaces **9-13, 16-2**  
   configuring switch **3-3**  
   default setting **6-10**  
   initial configuration **3-6, 3-10**  
   loader> prompt recovery **5-19**  
   switch(boot)# prompt recovery **5-21**  
 subordinate switch **18-6**  
 supervisor module  
   default settings **6-10**  
 supervisor modules  
   active **1-6, 4-2**  
   active state **4-7, 4-8, 6-3**  
   automatic synchronization **4-5**  
   default settings **6-10**  
   dual modules **6-2**  
   high availability **4-2**  
   major threshold **6-8**  
   reloading image **5-6**  
   resetting **6-5**  
   standby **5-10**  
   standby access **5-4**  
   standby module **1-6**  
   standby state **4-7, 4-8, 6-3**  
   standby status **4-5, 6-3**  
   states **4-7**  
 switch options **1-6**  
 switchover **4-3**  
 synchronizing images **4-5**  
 upgrading **5-8**  
 viewing information **6-4**  
 suspended state **11-7**  
 switch  
   dual supervisor **5-22**  
   reliability service **1-3**  
   reloading **6-5**  
   role-based access **1-7**  
   secure access **1-7**  
   security management **1-7**  
   single supervisor **5-21**  
   SNMPv3 access **1-7**  
   verifying modules **6-2**  
 switchability  
   high availability **4-2**  
 switched port analyzer  
   See SPAN  
 switching module  
   16-port **6-6**  
   32-port **6-6**  
   image **6-2**  
   LEDs **6-7**  
   power cycle **6-5**  
   powering off **6-7**  
   reloading **6-5**  
   status **6-2**  
   viewing states **6-3**  
 switching modules  
   connecting to **6-4**  
   internal details **6-4**  
   LEDs **6-7**  
   LEDs (table) **6-9**  
   managing **6-1**  
   powering off **6-7**  
   preserving configuration **6-6**  
   progression states **6-3**

reloading **6-5**  
 reset **4-3**  
 resetting **5-10, 6-5**  
 states **6-1**  
 thresholds **7-8**  
 switchover mechanism  
     HA **4-5, 4-7, 4-8, 6-3**  
     warm **4-5, 4-7, 4-8, 6-3**  
 switch priority  
     configuring **18-5**  
     range **2-18**  
 switch redundancy states **4-7**  
 switch states **11-6**  
 synchronization  
     See automatic synchronization  
 syslogs  
     viewing **1-7**  
 syslog server **20-2**  
     configuring **20-7**  
 system image **5-1, 5-4, 5-10**  
     function **5-2**  
     reading configuration **5-14**  
     recovery interruption **5-15**  
     switching module **6-2**  
     SYSTEM variable **5-2**  
     updating variables **5-6**  
 system messages  
     configuring **20-5**  
     default settings **20-12**  
     displaying configuration **20-8**  
     format **20-4**  
     logging **20-2**  
 system processes  
     displaying **25-2**  
     status **25-5**  
 system switchover  
     configuring **4-4**  
     guidelines **4-4**  
     mechanisms **4-3**

SYSTEM variable **5-11**  
     clearing **5-12**  
     switch installation **4-6**

---

**T**

target disks **21-3**  
 Telnet  
     default service **14-17**  
     session **5-5, 5-8**  
 Telnet session  
     message logging **20-5**  
 temporary storage **2-10**  
 TE port  
     trunking **1-4**  
 TE ports  
     classes of service **9-4**  
     fctrace **23-3**  
     FSPF topology **15-2**  
     interface modes **9-2**  
     interoperability **23-16**  
     recovering from isolation **12-9**  
     SPAN **22-3**  
     trunking restrictions **10-1**  
 TFTP  
     boot **5-17**  
     copying images **5-5**  
     server **5-17**  
 TFTP server **25-6**  
     copying images **5-13**  
     upgrade requirements **5-3**  
     verifying connectivity **5-3**  
 threshold  
     major and minor **7-8**  
 time interval  
     configuring **15-5**  
 time out value  
     See TOV  
 Timers

range **2-18**

TL Ports

  logging facility **20-3**

TL ports

  classes of service **9-3**

  configuring **9-8**

  displaying **9-21**

  FCS **24-2, 24-3**

  interface modes **9-2**

  SPAN **22-3**

TOV

  interoperability **23-16**

  ranges **23-2**

troubleshooting

  error messages **20-2**

trunk-allowed list

  configuring **10-4**

Trunking

  PortChannels comparison **11-3**

trunking

  configuration guidelines **10-6**

  functionality **1-4**

  interoperability **23-16**

  link state **10-3**

  restrictions **10-1**

trunking ports **8-5**

trunking protocol **10-2, 10-6**

  default **10-2**

  default settings **10-8**

trunk mode

  administrative default **9-12**

  configuring **10-3**

  default settings **10-8**

  status **10-3**

trunk ports

  displaying information **10-7**

## U

upgrade-reset feature **25-8**

upgrades

  See disruptive upgrades

  See nondisruptive upgrades

upgrading

  software **5-5 to 5-10**

user ID

  authentication **14-2**

  authorization process **14-4**

user IDs

  security management **1-7**

user roles **1-7**

users

  creating **14-21**

## V

version compatibility

  switch images **4-3**

virtual devices **9-21**

Virtual Router Redundancy Protocol

  See VRRP

virtual SANs

  See VSANs

VR IDs

  configuring **16-14**

  mapping **16-12**

VRRP

  characteristics **16-12**

  clearing statistics **16-18**

  logging facility **20-3**

  master and backup **16-13**

  primary IP **16-14**

  priority tracking **16-17**

  security authentication **16-16**

  setting priority **16-15**

  tracking priority **16-16**

## VSA

- communicating attributes **14-15**
- protocol options **14-16**

## VSAN

- address format **2-18**
- configuring **1-4**
- domain IDs **18-6**
- functionality **1-4**
- gateway switch **16-3**
- overlaid routes **16-4**
- reason codes **9-6**
- redundancy **1-4**
- scalability **1-4**
- traffic isolation **1-4**

## VSAN IDs

- allowed list **10-8**
- attributes **8-6**
- FCS registration **2-6**
- membership **8-4**
- multiplexing traffic **9-4**
- name **8-10**
- range **8-5**
- trunking **11-3**

## VSANs

- allowed-active **10-1, 10-4**
- allowed list **22-3**
- allowed-list **10-8**
- attributes **8-6, 8-8**
- availability **8-1**
- broadcast address **15-9**
- cache contents **18-12**
- configuring **8-1, 8-6**
- configuring domains **18-1**
- configuring FSPF **15-3**
- configuring overlay **16-10**
- database submode **2-6**
- default setting **8-10**
- default VSAN **8-5**
- deleting **8-8**

- FCC protocol **19-2**
- FCIDs **8-2**
- FCS **24-2**
- features **8-2**
- flow statistics **15-13**
- FSPF connectivity **15-2**
- functionality **1-4**
- interface **9-12, 9-14**
- interop mode **23-16**
- IP addresses **16-5**
- IPFC interface **23-3**
- isolated VSAN **8-5**
- logical interface **3-9**
- loop devices **9-21**
- management interfaces **16-2**
- managing traffic **19-1**
- membership **8-5, 8-9**
- merging traffic **10-6**
- mismatch **9-6, 10-2**
- multiple zones **8-4, 12-6**
- name **8-6**
- name server **13-3**
- overlaid routes **16-8**
- port granularity **8-3**
- port isolation **10-6**
- Rules and features **14-7**
- sate **8-6**
- scalability **8-1**
- SPAN source **22-2, 22-3**
- static routing **16-6**
- syslog **20-3**
- TOVs **23-2**
- traffic isolation **8-1, 8-3**
- traffic routing **16-1**
- trunk allowed **9-12**
- trunk-allowed **10-1, 10-2**
- trunk-allowed list **10-4**
- trunking port **9-4**
- trunking ports **8-5**

usage [8-9](#)  
 VRRP [16-12](#)  
 VRRP submode [2-6](#)  
 VSAN trunking  
   See trunking

---

**W**

warm switchovers  
   defining [4-4](#)  
   description [4-3](#)  
   guidelines [4-4](#)  
 watchdog checks [25-8](#)  
 world wide names

  See WWNs

WWNs  
   configuring [23-13](#)  
   displaying configurations [23-14](#)  
   suspended connection [9-7](#)  
 See also nWWNs  
 See also pWWNs

---

**Z**

zone database [12-9](#)  
 zones  
   access control [12-5](#)  
   accesses between devices [1-4](#)  
   configuring [12-4](#)  
   configuring guidelines [12-6](#)  
   default policy [12-2, 12-8](#)  
   default settings [12-14](#)  
   enforcing [12-5](#)  
   examples [12-3](#)  
   functionality [1-4](#)  
   See also default zones  
   See also hard zoning  
   See also soft zoning

