



INDEX

Symbols

- * (asterisk)
 - host time stamps [10-30](#)
- +153646 [10-38](#)
- +840266 [10-36](#)

A

- active zone sets
 - considerations [3-4](#)
 - enabling distribution [3-15](#)

B

- BB_credits
 - FICON port swapping [10-37](#)
- broadcast
 - routing [6-12](#)
- Brocade
 - native interop mode [11-14](#)

C

- CIM
 - configuring [11-1](#)
 - description [11-1](#)
 - displaying information [11-3](#)
- CIM servers
 - displaying information [11-3, 11-5](#)
- code pages
 - FICON text string formatting [10-20](#)
- Common Information Model. See CIM

- company IDs
 - FC ID allocations [11-11](#)
- configuration
 - saving automatically for FICON [10-22](#)
- configuration files
 - FICON [10-33](#)
- Control Unit Port. See CUP in-band management
- CUP in-band management
 - blocking restriction [10-25](#)
 - description [10-42](#)
 - displaying information [10-43](#)
 - placing CUPs in zones [10-43](#)

D

- dead time intervals
 - configuring for FSPF [6-8](#)
 - description [6-7](#)
- default VSANs
 - description [2-9](#)
- default zones
 - configuring access permissions [3-11](#)
 - configuring QoS priorities [3-20](#)
 - description [3-10](#)
 - interoperability [11-14](#)
 - policies [3-10](#)
- destination IDs
 - in-order delivery [6-13](#)
 - path selection [2-11](#)
- device alias database
 - committing changes [5-6](#)
 - disabling distribution [5-7](#)
 - discarding changes [5-6](#)

Send documentation comments to mdsfeedback-doc@cisco.com

- distribution to fabric [5-5](#)
- enabling distribution [5-7](#)
- merging [5-9](#)
- overriding fabric lock [5-7](#)

device aliases

- clearing statistics [5-9](#)
- comparison with zones (table) [5-4](#)
- creating [5-5](#)
- default settings [5-12](#)
- description [5-1](#)
- displaying information [5-9 to 5-11](#)
- features [5-3](#)
- modifying the database [5-4](#)
- requirements [5-3](#)

device allegiance

- FICON [10-22](#)

domain IDs

- configuring fcalias members [3-11](#)
- interoperability [11-14](#)

DPVM

- default settings [4-14](#)
- description [4-1](#)
- displaying configurations [4-10](#)
- enabling [4-2](#)
- requirements [4-2](#)
- sample configuration [4-11 to 4-14](#)

DPVM databases

- autolearned entries [4-4](#)
- clearing [4-5](#)
- comparing differences [4-9](#)
- configuring CFS distribution [4-5 to ??](#)
- copying [4-9](#)
- description [4-3](#)
- displaying [4-11](#)
- enabling autolearning [4-5](#)
- merging guidelines [4-8](#)

drop latency time

- configuring for FSPF in-order delivery [6-16](#)
- displaying information [6-17](#)

Dynamic Port VSAN Membership. See DPVM

E

EBCDIC

- FICON string format [10-20](#)

enhanced zones

- advantages over basic zones [3-33](#)
- broadcast frames [3-38](#)
- changing from basic zones [3-34](#)
- configuring default full database distribution [3-39](#)
- configuring default switch-wide zone policies [3-39](#)
- creating attribute groups [3-36](#)
- default settings [3-45](#)
- description [3-32](#)
- displaying information [3-40 to 3-43](#)
- enabling [3-34](#)
- merging databases [3-36](#)
- modifying database [3-35](#)

E ports

- FSPF topologies [6-2](#)
- recovering from link isolations [3-15](#)

exchange IDs

- in-order delivery [6-13](#)
- path selection [2-11](#)

Extended Binary-Coded Decimal Interchange Code. See EBCDIC [10-20](#)

F

Fabric-Device Management Interface. See FDMI

fabric login. See FLOGI

fabric pWWNs

- zone membership [3-2](#)

Fabric Shortest Path First. See FSPF

fabric WWNs. See fWWNs

fault tolerant fabrics

- example (figure) [6-2](#)

fcalias

Send documentation comments to mdsfeedback-doc@cisco.com

- cloning [3-18](#)
- configuring for zones [3-11](#)
- creating [3-11](#)
- renaming [3-18](#)
- FC ID allocation
 - FICON implementation [10-14](#)
- FC IDs
 - allocating [11-11](#)
 - allocating default company ID lists [11-11](#)
 - allocating for FICON [10-14](#)
 - allocation for HBAs [11-11](#)
 - configuring fcalias members [3-11](#)
- FCIP
 - FICON support [10-4](#)
 - reserving ports for FICON [10-13](#)
- FCIP interfaces
 - binding to FICON port numbers [10-24](#)
- FCP
 - intermixing protocols [10-5](#)
- fctimers
 - displaying configured values [11-9](#)
 - distribution [11-7](#)
- FDMI
 - description [8-6](#)
 - displaying database information [8-6](#)
- Fibre Channel
 - time out values [11-5 to 11-9](#)
- Fibre Channel interfaces
 - displaying VSAN membership [2-8](#)
- Fibre Channel Protocol. See FCP
- Fibre Connection. See FICON
- FICON
 - advantages on MDS switches [10-3 to 10-7](#)
 - automatic configuration save [10-23](#)
 - basic configuration [10-16](#)
 - cascading [10-7](#)
 - clearing device allegiance [10-22](#)
 - configuration files [10-32](#)
 - configuring [10-15](#)
 - configuring ports [10-24 to 10-32](#)
 - CUP in-band management [10-42](#)
 - default settings [10-51](#)
 - description [10-1 to 10-7](#)
 - displaying information [10-44 to 10-51](#)
 - FC4 protocols [10-2](#)
 - FC ID allocations [10-14](#)
 - FCIP support [10-4](#)
 - host timestamp control [10-21](#)
 - implemented ports [10-11](#)
 - installed ports [10-11](#)
 - manually enabling [10-19](#)
 - MDS-supported features [10-5](#)
 - PortChannel support [10-4](#)
 - port numbering [10-7 to 10-14](#)
 - port swapping [10-36 to 10-38](#)
 - prohibited ports [10-48](#)
 - RLIRs [10-27](#)
 - saving configuration changes [10-22](#)
 - tape acceleration [10-38 to ??, 10-40 to ??, 10-42 to ??](#)
 - text string formatting codes [10-20](#)
 - unimplemented port [10-11](#)
 - VSAN offline state [10-42](#)
- FICON configuration files
 - applying to running configuration [10-33](#)
 - copying [10-35](#)
 - description [10-33](#)
 - displaying [10-34](#)
 - displaying information [10-46](#)
 - editing [10-33](#)
- FICON port numbers
 - assigning to slots [10-12](#)
 - default numbering scheme [10-8](#)
 - displaying assignments [10-12](#)
 - FCIP interfaces [10-13](#)
 - implemented addresses [10-11](#)
 - installed ports [10-11](#)
 - logical interfaces [10-13](#)
 - numbering guidelines [10-12](#)

Send documentation comments to mdsfeedback-doc@cisco.com

- PortChannel interfaces [10-13](#)
- port swapping [10-10](#)
- reserved numbering scheme [10-11](#)
- unimplemented addresses [10-11](#)
- uninstalled ports [10-11](#)
- FICON ports
 - assigning address names [10-27](#)
 - binding to FCIP interfaces [10-24](#)
 - binding to PortChannels [10-24](#)
 - blocking [10-25](#)
 - configuring prohibiting default state [10-26](#)
 - displaying address information [10-45](#)
 - displaying administrative states [10-48](#)
 - prohibiting [10-25](#)
 - swapping configurations [10-37](#)
- FICON port swapping
 - guidelines [10-37](#)
- FICON tape acceleration
 - configuration considerations [10-40](#)
 - configuring [10-40](#)
 - description [10-38, 10-40, 10-42](#)
- FICON tape read acceleration
 - configuring [10-41](#)
- FLOGI
 - description [8-1](#)
 - displaying details [8-1](#)
- flow statistics
 - clearing [6-18](#)
 - counting [6-18](#)
 - description [6-17](#)
 - displaying [6-18](#)
- FL ports
 - DPVM support [4-4](#)
- F ports
 - DPVM support [4-4](#)
- FSCN
 - displaying databases [9-3](#)
- FSPF
 - clearing counters [6-9](#)
 - clearing VSAN counters [6-6](#)
 - computing link cost [6-7](#)
 - configuring globally [6-4 to 6-6](#)
 - configuring Hello time intervals [6-7](#)
 - configuring link cost [6-6](#)
 - configuring on a VSAN [6-5](#)
 - configuring on interfaces [6-6 to 6-9](#)
 - dead time intervals [6-7](#)
 - default settings [6-21](#)
 - description [6-2](#)
 - disabling [6-6](#)
 - disabling on interfaces [6-9](#)
 - disabling routing protocols [6-6](#)
 - displaying database information [6-20](#)
 - displaying global information [6-19](#)
 - displaying information [?? to 6-21](#)
 - enabling [6-6](#)
 - fail-over with PortChannels [6-3](#)
 - fault tolerant fabrics [6-2](#)
 - flow statistics [6-17 to 6-19](#)
 - in-order delivery [6-13 to 6-17](#)
 - interoperability [11-15](#)
 - link state record defaults [6-4](#)
 - multicast root switches [6-12](#)
 - reconvergence times [6-2](#)
 - redundant links [6-3](#)
 - resetting configuration [6-5](#)
 - resetting to defaults [6-5](#)
 - retransmitting intervals [6-8](#)
 - routing services [6-1](#)
 - topology examples [6-2 to 6-4](#)
- FSPF multicast roots
 - configuring switches [6-12](#)
- FSPF routes
 - configuring [6-10](#)
 - description [6-10](#)
- FSPF routing
 - multicast [6-12](#)
- full zone sets

Send documentation comments to mdsfeedback-doc@cisco.com

considerations [3-4](#)

enabling distribution [3-15](#)

fWWNs

configuring fcalias members [3-11](#)

Fx ports

VSAN membership [2-4](#)

H

hard zoning

description [3-14](#)

HBAs

device aliases [5-1](#)

FC ID allocations [11-11](#)

Hello time intervals

configuring for FSPF [6-7](#)

description [6-7](#)

host control

FICON [10-20](#)

I

IBM PPRC

FICON support [10-4](#)

in-band management

CUP [10-42](#)

in-order delivery

configuring drop latency time [6-16](#)

displaying status [6-15](#)

enabling for VSANs [6-15](#)

enabling globally [6-15](#)

guidelines [6-14](#)

reordering network frames [6-13](#)

reordering PortChannel frames [6-14](#)

interfaces

assigning to VSANs [2-7](#)

configuring fcalias members [3-11](#)

VSAN membership [2-7](#)

interoperability

configuring interop mode 1 [11-16](#)

description [11-13](#)

VSANs [2-11](#)

interop modes

configuring mode 1 [11-16](#)

default settings [11-20](#)

description [11-13](#)

IOD. See in-order delivery

IPv4 addresses

configuring fcalias members [3-11](#)

IPv6 addresses

configuring fcalias members [3-2, 3-11](#)

isolated VSANs

description [2-9](#)

displaying membership [2-9](#)

L

link costs

configuring for FSPF [6-7](#)

description [6-6](#)

Link Incident Records. See LIRs

LIRs

description [10-27](#)

load balancing

attributes [2-11](#)

attributes for VSANs [2-5](#)

configuring [2-11](#)

description [2-11](#)

guarantees [2-11](#)

logical unit numbers. See LUNs

LUNs

displaying automatically discovered SCSI targets [9-4](#)

displaying customized discovered SCSI targets [9-4](#)

displaying discovered SCSI targets [9-3](#)

LUN zoning

configuring [3-24](#)

description [3-23](#)

Send documentation comments to mdsfeedback-doc@cisco.com

M

MAC addresses

configuring secondary [11-11](#)

mainframes

FICON parameters [10-21](#)

VSAN clock [10-21](#)

McData

native interop mode [11-14](#)

multicast root switches

configuring [6-12](#)

description [6-12](#)

N

name servers

displaying database entries [8-4](#)

interoperability [11-15](#)

LUN information [9-1](#)

proxy feature [8-3](#)

registering proxies [8-3](#)

rejecting duplicate pWWNs [8-4](#)

NL ports

hard zoning [3-14](#)

zone enforcement [3-14](#)

node world wide names. See nWWNs

N ports

hard zoning [3-14](#)

zone enforcement [3-14](#)

zone membership [3-2](#)

See also Nx ports

nWWNs

DPVM [4-1](#)

FICON [10-10](#)

PortChannels

binding to FICON port numbers [10-24](#)

configuring Fibre Channel routes [6-11](#)

FICON support [10-4](#)

in-order guarantee [6-14](#)

interoperability [11-15](#)

link changes [6-14](#)

link failures [6-3](#)

reserving ports for FICON [10-13](#)

port numbers. See FICON port numbers

ports

VSAN membership [2-7](#)

port swapping. See FICON port swapping

port world wide names. See pWWNs

prohibited ports

FICON [10-48](#)

proxies

registering for name servers [8-3](#)

pWWNs

configuring fcalias members [3-11](#)

DPVM [4-1](#)

rejecting duplicates [8-4](#)

zone membership [3-2](#)

R

read-only zones

configuration guidelines [3-25](#)

configuring [3-26](#)

default settings [3-45](#)

description [3-25](#)

redundancy

VSANs [2-4](#)

redundant physical links

example (figure) [6-3](#)

Registered Link Incident Reports. See RLIRs

Registered State Change Notifications. See RSCNs

retransmitting intervals

P

PLOGI

name server [8-4](#)

port addresses

Send documentation comments to mdsfeedback-doc@cisco.com

configuring for FSPF [6-8](#)

description [6-8](#)

RLIRs

clearing information [10-32](#)

conditional receive [10-30](#)

description [10-27](#)

displaying information [10-28 to 10-32](#)

specifying preferred host [10-27](#)

route costs

computing [6-6](#)

routing

multicast [6-12](#)

See also broadcast routing

See also IP routing

routing protocols

disabling [6-6](#)

RSCNs

clearing statistics [8-10](#)

default settings [8-15](#)

description [8-8](#)

displaying information [8-8](#)

multiple port IDs [8-9](#)

suppressing domain format SW-RSCNs [8-10](#)

RSCN timers

configuration distribution using CFS [8-12 to 8-15](#)

configuring [8-11](#)

displaying configuration [8-12](#)

runtime checks

static routes [6-10](#)

secondary MAC addresses

configuring [11-11](#)

small computer system interface. See SCSI

smart zoning [3-22](#)

SNMP

FICON control [10-22](#)

soft zoning

description [3-14](#)

See also zoning

source IDs

in-order delivery [6-13](#)

path selection [2-11](#)

SPF

computational hold times [6-4](#)

static routes

runtime checks [6-10](#)

storage devices

access control [3-1](#)

T

tape acceleration

FICON [10-38 to 10-40](#), [?? to 10-42](#)

TE ports

FSPF topologies [6-2](#)

interoperability [11-15](#)

recovering from link isolations [3-15](#)

time out values. See TOVs

timestamps

FICON host control [10-21](#)

TOVs

configuring across all VSANs [11-6](#)

configuring for a VSAN [11-6](#)

default settings [11-20](#)

interoperability [11-14](#)

ranges [11-5](#)

traffic isolation

VSANs [2-4](#)

trunking

S

scalability

VSANs [2-4](#)

SCSI LUNs

customized discovery [9-2](#)

discovering targets [9-1](#)

displaying information [9-2](#)

starting discoveries [9-2](#)

Send documentation comments to mdsfeedback-doc@cisco.com

interoperability [11-14](#)
trunking ports
 associated with VSANs [2-7](#)

V

VSAN IDs

description [2-5](#)
range [2-4](#)
VSAN membership [2-4](#)

VSANs

advantages [2-3](#)
broadcast addresses [6-12](#)
clocks [10-21](#)
comparison with zones (table) [2-4](#)
configuring [2-6 to 2-7](#)
configuring FSPF [6-4](#)
default settings [2-12](#)
default VSANs [2-9](#)
deleting [2-9](#)
description [2-1 to 2-4](#)
displaying configuration [2-11](#)
displaying membership [2-8](#)
displaying usage [2-12](#)
fabric optimization for FICON [10-3](#)
FC IDs [2-1](#)
features [2-1](#)
FICON-enabled [2-11, 10-42](#)
flow statistics [6-17](#)
FSPF [6-5](#)
FSPF connectivity [6-2](#)
interop mode [11-14](#)
isolated [2-9](#)
load balancing [2-11](#)
load balancing attributes [2-5](#)
multiple zones [3-4](#)
names [2-5](#)
name server [8-3](#)
operational states [2-9](#)

port membership [2-7](#)
states [2-5](#)
timer configuration [11-6](#)
TOVs [11-6](#)
traffic isolation [2-3](#)
trunking ports [2-7](#)

W

world wide names. See WWNs

WWNs

configuring [11-9](#)
displaying information [11-10](#)
link initialization [11-10](#)
secondary MAC addresses [11-11](#)

X

XRC

FICON support [10-4](#)

Z

zone attribute groups

cloning [3-18](#)

zone databases

release locks [3-35](#)

zones

access control [3-7](#)
adding to zone sets [3-12](#)
analyzing [3-43](#)
assigning LUNs to storage subsystems [3-25](#)
backing up (procedure) [3-17](#)
changing from enhanced zones [3-34](#)
cloning [3-18](#)
compacting for downgrading [3-43](#)
comparison with device aliases (table) [5-4](#)
comparison with VSANs (table) [2-4](#)

Send documentation comments to mdsfeedback-doc@cisco.com

- configuring [3-6 to 3-7](#)
- configuring aliases [3-11](#)
- configuring broadcasting [3-21](#)
- configuring fcaliases [3-11](#)
- CUPs [10-43](#)
- default policies [3-2](#)
- default settings [3-45](#)
- displaying information [3-26 to 3-32](#)
- enforcing restrictions [3-14](#)
- exporting databases [3-15](#)
- features [3-1, 3-3](#)
- importing databases [3-15](#)
- LUN-based [3-23](#)
- membership using pWWNs [2-4](#)
- renaming [3-18](#)
- restoring (procedure) [3-17](#)
- See also default zones
- See also enhanced zones
- See also hard zoning; soft zoning
- See also LUN zoning
- See also read-only zones
- See also zoning; zone sets
- zone server databases
 - clearing [3-18](#)
- zone sets
 - activating [3-10](#)
 - adding member zones [3-12](#)
 - analyzing [3-43](#)
 - cloning [3-18](#)
 - configuring [3-7 to 3-10](#)
 - considerations [3-4](#)
 - copying [3-16](#)
 - creating [3-8, 3-12](#)
 - default settings [3-45](#)
 - displaying information [3-26 to 3-32](#)
 - distributing configuration [3-14](#)
 - enabling distribution [3-14](#)
 - exporting [3-16](#)
 - exporting databases [3-15](#)
 - features [3-1](#)
 - importing [3-16](#)
 - importing databases [3-15](#)
 - one-time distribution [3-15](#)
 - recovering from link isolations [3-15](#)
 - renaming [3-18](#)
 - See also active zone sets
 - See also active zone sets; full zone sets
 - See also zones; zoning
 - zone traffic priorities
 - configuring [3-19](#)
 - description [3-19](#)
 - zoning
 - configuring broadcasting [3-21](#)
 - description [3-1](#)
 - example [3-2](#)
 - implementation [3-3](#)
 - See also LUN zoning
 - See also zones; zone sets

Send documentation comments to mdsfeedback-doc@cisco.com