



CHAPTER 20

Configuring Control Plane Policing

This chapter describes how to configure control plane policing (CoPP) on the NX-OS device.

This chapter includes the following sections:

- [Information About CoPP, page 20-1](#)
- [Guidelines and Limitations, page 20-8](#)
- [Configuring CoPP, page 20-9](#)
- [Displaying the CoPP Statistics, page 20-17](#)
- [Verifying CoPP Configuration, page 20-19](#)
- [CoPP Example Configurations, page 20-19](#)
- [Default Settings, page 20-21](#)
- [Additional References, page 20-22](#)
- [Feature History for CoPP, page 20-23](#)

Information About CoPP

The NX-OS device provides control plane policing to prevent denial-of-service (DoS) attacks from impacting performance.

The supervisor module divides the traffic that it manages into three functional components or *planes*:

- **Data plane**—Handles all the data traffic. The basic functionality of a NX-OS device is to forward packets from one interface to another. The packets that are not meant for the switch itself are called the transit packets. These packets are handled by the data plane.
- **Control plane**—Handles all routing protocol control traffic. These protocols, such as the Border Gateway Protocol (BGP) and the Open Shortest Path First (OSPF) Protocol, send control packets between devices. These packets are destined to router addresses and are called control plane packets.
- **Management plane**—Runs the components meant for NX-OS device management purposes such as the command-line interface (CLI) and Simple Network Management Protocol (SNMP).

The supervisor module has both the management plane and control plane and is critical to the operation of the network. Any disruption or attacks to the supervisor module will result in serious network outages. For example, excessive traffic to the supervisor module could overload and slow down the performance of the entire NX-OS device. Attacks on the supervisor module can be of various types such as DoS that

Send document comments to nexus7k-docfeedback@cisco.com

generates IP traffic streams to the control plane at a very high rate. These attacks force the control plane to spend a large amount of time in handling these packets and prevents the control plane from processing genuine traffic.

Examples of DoS attacks are as follows:

- Internet Control Message Protocol (ICMP) echo requests
- IP fragments
- TCP SYN flooding

These attacks can impact the device performance and have the following negative effects:

- High supervisor CPU utilization.
- Loss of line protocol keep-alive messages and routing protocol updates, which lead to route flaps and major network outages.
- Interactive sessions using the CLI become slow or completely unresponsive due to high CPU utilization.
- Resources, such as the memory and buffers, might be unavailable for legitimate IP data packets.
- Packet queues fill up, which can cause indiscriminate packet drops.

**Caution**

It is important to ensure that you protect the supervisor module from accidental or malicious attacks by setting appropriate control plane protection.

This section includes the following topics:

- [Control Plane Protection, page 20-2](#)
- [Modular QoS Command-Line Interface, page 20-8](#)
- [CoPP and the Management Interface, page 20-8](#)
- [Virtualization Support, page 20-8](#)

Control Plane Protection

To protect the control plane, the NX-OS device segregates different packets destined to the control plane into different classes. Once these classes are identified, the NX-OS device polices or marks down packets, which ensure that the supervisor module is not overwhelmed.

This section includes the following topics:

- [Control Plane Packet Types, page 20-3](#)
- [Classification, page 20-3](#)
- [Rate Controlling Mechanisms, page 20-3](#)
- [Default Policing Policies, page 20-4](#)

Send document comments to nexus7k-docfeedback@cisco.com

Control Plane Packet Types

Different types of packets can reach the control plane:

- Receive packets—Packets that have the destination address of a router. The destination address can be a Layer 2 address (such as a router MAC address) or a Layer 3 address (such as the IP address of a router interface). These packets include router updates and keepalive messages. Multicast packets can also be in this category where packets are sent to multicast addresses that are used by a router.
- Exception packets—Packets that need special handling by the supervisor module. For example, if a destination address is not present in the Forwarding Information Base (FIB) and results in a miss, then the supervisor module sends an ICMP unreachable packet back to the sender. Another example is a packet with IP options set.
- Redirected packets—Packets that are redirected to the supervisor module. Features like Dynamic Host Configuration Protocol (DHCP) snooping or dynamic Address Resolution Protocol (ARP) inspection redirect some packets to the supervisor module.
- Glean packets—If a Layer 2 MAC address for a destination IP address is not present in the FIB, the supervisor module receives the packet and sends an ARP request to the host.

All of these different packets could be maliciously used to attack the control plane and overwhelm the NX-OS device. CoPP classifies these packets to different classes and provides a mechanism to individually control the rate at which the supervisor module receives these packets.

Classification

For effective protection, the NX-OS device classifies the packets that reach the supervisor modules to allow you to apply different rate controlling policies based on the type of the packet. For example, you might want to be less strict with a protocol packet such as Hello messages but more strict with a packet that is sent to the supervisor module because the IP option is set. The following parameters that can be used for classifying a packet:

- Source IP address
- Destination IP address
- Source MAC address
- Destination MAC address
- VLAN
- Source port
- Destination port
- Exception cause

Rate Controlling Mechanisms

Once the packets are classified, the NX-OS device has different mechanisms to control the rate at which packets arrive at the supervisor module. Two mechanisms control the rate of traffic to the supervisor module. One is called policing and the other is called rate limiting.

Using hardware policers, you can define separate actions for traffics that conforms to, exceeds, or violates certain conditions. The actions can transmit the packet, mark down the packet, or drop the packet.

Send document comments to nexus7k-docfeedback@cisco.com

You can configure the following parameters for policing:

- Committed information rate (CIR)—Desired bandwidth, specified as a bit rate or a percentage of the link rate.
- Peak information rate (PIR)—Rate above which data traffic is negatively affected.
- Committed burst (BC)—Size of a traffic burst that can exceed the CIR within a given unit of time and not impact scheduling.
- Extended burst (BE)—Size that a traffic burst can reach before all traffic exceeds the PIR.

In addition you can set separate actions such as transmit or drop for conform, exceed, and violate traffic.

For more information on policing parameters, see the *Cisco Nexus 7000 Series NX-OS Quality of Service Configuration Guide, Release 4.0*.

Default Policing Policies

When you bring up your NX-OS device for the first time, the NX-OS software installs the default `copp-system-policy` policy to protect the supervisor module from DoS attacks. You can set the level of protection by choosing one of the following CoPP policy options from the initial setup utility:

- Strict (1 rate and two color)
- Moderate (2 rate and 3 color where the PIR is 25 percent higher than the CIR of the strict default policy)
- Lenient (2 rate and 3 color where the PIR is 50 percent higher than the CIR of the strict default policy)
- None (no control plane policy is applied)

If you do not select an option or choose not to execute the setup utility, the NX-OS software applies strict policing. You can change the CoPP policies as needed from the CLI. You can also remove the default `copp-system-policy` from the CLI.

The `copp-system-policy` policy has optimized values suitable for basic device operations. You must add specific class and access-control list (ACL) rules that meet your DoS protection requirements. The default CoPP policy does not change when you upgrade the NX-OS software on your device.



Caution

Selecting the none option and not subsequently configuring CoPP protection can leave your NX-OS device vulnerable to DoS attacks.

In Cisco NX-OS Release 4.0(2) and later releases, you can reassign the CoPP default policy by entering the setup utility again using the **setup** command from the CLI prompt. Any changes you have made to the CoPP configuration are lost. For an example of using the setup utility, see the [“Changing or Reapplying the Default CoPP Policy”](#) section on page 20-20.



Note

If you are using a CoPP default policy, we recommend that you reapply the CoPP default policy using the **setup** command after you upgrade to Cisco NX-OS Release 4.0(2) or later releases (see the [“Changing or Reapplying the Default CoPP Policy”](#) section on page 20-16).

Send document comments to nexus7k-docfeedback@cisco.com

This section includes the following topics:

- [Default Classes, page 20-5](#)
- [Strict Default CoPP Policy, page 20-6](#)
- [Moderate Default CoPP Policy, page 20-6](#)
- [Lenient Default CoPP Policy, page 20-7](#)

Default Classes

The `copp-system-class-critical` class has the following configuration:

```
class-map type control-plane match-any copp-system-class-critical
  match access-group name copp-system-acl-igmp
  match access-group name copp-system-acl-msdp
  match access-group name copp-system-acl-bgp
  match access-group name copp-system-acl-eigrp
  match access-group name copp-system-acl-rip
  match access-group name copp-system-acl-ospf
  match access-group name copp-system-acl-pim
```

The `copp-system-class-important` class has the following configuration:

```
class-map type control-plane match-any copp-system-class-important
  match access-group name copp-system-acl-hsrp
  match access-group name copp-system-acl-vrrp
  match access-group name copp-system-acl-glbp
  match access-group name copp-system-acl-pim-reg
```

The `copp-system-class-management` class has the following configuration:

```
class-map type control-plane match-any copp-system-class-management
  match access-group name copp-system-acl-tacacs
  match access-group name copp-system-acl-radius
  match access-group name copp-system-acl-ntp
  match access-group name copp-system-acl-ftp
  match access-group name copp-system-acl-tftp
  match access-group name copp-system-acl-sftp
  match access-group name copp-system-acl-ssh
  match access-group name copp-system-acl-snmp
  match access-group name copp-system-acl-telnet
```

The `copp-system-class-normal` class has the following configuration:

```
class-map type control-plane match-any copp-system-class-normal
  match protocol arp
```

The `copp-system-class-redirect` class has the following configuration:

```
class-map type control-plane match-any copp-system-class-redirect
  match redirect arp-inspect
  match redirect dhcp-snoop
```

The `copp-system-class-monitoring` class has the following configuration:

```
class-map type control-plane match-any copp-system-class-monitoring
  match access-group name copp-system-acl-icmp
  match access-group name copp-system-acl-traceroute
```

The `copp-system-class-exception` class has the following configuration:

```
class-map type control-plane match-any copp-system-class-exception
  match exception ip option
  match exception ip icmp unreachable
```

Send document comments to nexus7k-docfeedback@cisco.com

```
match exception ipv6 option
match exception ipv6 icmp unreachable
```

The copp-system-class-undesirable class has the following configuration:

```
class-map type control-plane match-any copp-system-class-undesirable
  match access-group name copp-system-acl-undesirable
```

Strict Default CoPP Policy

The strict default CoPP policy has the following configuration:

```
policy-map type control-plane copp-system-policy

  class copp-system-class-critical
    police cir 40900 kbps bc 250 ms conform transmit violate drop

  class copp-system-class-important
    police cir 1060 kbps bc 1000 ms conform transmit violate drop

  class copp-system-class-management
    police cir 10000 kbps bc 250 ms conform transmit violate drop

  class copp-system-class-normal
    police cir 680 kbps bc 250 ms conform transmit violate drop

  class copp-system-class-redirect
    police cir 280 kbps bc 250 ms conform transmit violate drop

  class copp-system-class-monitoring
    police cir 100 kbps bc 250 ms conform transmit violate drop

  class copp-system-class-exception
    police cir 360 kbps bc 250 ms conform transmit violate drop

  class copp-system-class-undesirable
    police cir 32 kbps bc 250 ms conform drop violate drop

  class class-default
    police cir 100 kbps bc 250 ms conform transmit violate drop
```

Moderate Default CoPP Policy

The moderate default CoPP policy has the following configuration:

```
class copp-system-class-critical
  police cir 40900 kbps bc 250 ms pir 51200 kbps be 250 ms conform transmit exceed
  transmit violate drop

class copp-system-class-important
  police cir 1060 kbps bc 1000 ms pir 1325 kbps be 1000 ms conform transmit exceed
  transmit violate drop

class copp-system-class-management
  police cir 10000 kbps bc 250 ms pir 12500 kbps be 250 ms conform transmit exceed
  transmit violate drop

class copp-system-class-normal
  police cir 680 kbps bc 250 ms pir 850 kbps be 250 ms conform transmit exceed transmit
  violate drop
```

Send document comments to nexus7k-docfeedback@cisco.com

```
class copp-system-class-redirect
  police cir 280 kbps bc 250 ms pir 350 kbps be 250 ms conform transmit exceed transmit
  violate drop

class copp-system-class-monitoring
  police cir 100 kbps bc 250 ms pir 125 kbps be 250 ms conform transmit exceed transmit
  violate drop

class copp-system-class-exception
  police cir 360 kbps bc 250 ms pir 450 kbps be 250 ms conform transmit exceed transmit
  violate drop

class copp-system-class-undesirable
  police cir 32 kbps bc 250 ms conform drop violate drop

class class-default
  police cir 100 kbps bc 250 ms pir 125 kbps be 250 ms conform transmit exceed transmit
  violate drop
```

Lenient Default CoPP Policy

The lenient default CoPP policy has the following configuration:

```
class copp-system-class-critical
  police cir 40900 kbps bc 250 ms pir 61350 kbps be 250 ms conform transmit exceed
  transmit violate drop

class copp-system-class-important
  police cir 1060 kbps bc 1000 ms pir 1500 kbps be 1000 ms conform transmit exceed
  transmit violate drop

class copp-system-class-management
  police cir 10000 kbps bc 250 ms pir 15000 kbps be 250 ms conform transmit exceed
  transmit violate drop

class copp-system-class-normal
  police cir 680 kbps bc 250 ms pir 1020 kbps be 250 ms conform transmit exceed transmit
  violate drop

class copp-system-class-redirect
  police cir 280 kbps bc 250 ms pir 420 kbps be 250 ms conform transmit exceed transmit
  violate drop

class copp-system-class-monitoring
  police cir 100 kbps bc 250 ms pir 150 kbps be 250 ms conform transmit exceed transmit
  violate drop

class copp-system-class-exception
  police cir 360 kbps bc 250 ms pir 550 kbps be 250 ms conform transmit exceed transmit
  violate drop

class copp-system-class-undesirable
  police cir 32 kbps bc 250 ms conform drop violate drop

class class-default
  police cir 100 kbps bc 250 ms pir 150 kbps be 250 ms conform transmit exceed transmit
  violate drop
```

Send document comments to nexus7k-docfeedback@cisco.com

Modular QoS Command-Line Interface

CoPP uses the Modular Quality of Service Command-Line Interface (MQC). MQC is a CLI structure that allows you to define a traffic class, create a traffic policy (policy map), and attach the traffic policy to an interface. The traffic policy contains the CoPP feature that will be applied to the traffic class.

The MQC structure consists of the following high-level steps:

-
- Step 1** Define a traffic class using the **class-map** command. A traffic class is used to classify traffic.
 - Step 2** Create a traffic policy using the **policy-map** command. A traffic policy (policy map) contains a traffic class and one or more CoPP features that will be applied to the traffic class. The CoPP features in the traffic policy determine how to treat the classified traffic.
 - Step 3** Attach the traffic policy (policy map) to the control plane using the **control-plane** and **service-policy** commands.
-

CoPP and the Management Interface

The NX-OS device supports only hardware-based CoPP which does not support the management interface (mgmt0). The out-of-band mgmt0 interface connects directly to the CPU and not pass through the in-band traffic hardware where CoPP is implemented. To limit traffic on the mgmt0 interface, use ACLs (see [Chapter 10, “Configuring IP ACLs”](#) and [Chapter 11, “Configuring MAC ACLs”](#)).

Virtualization Support

You can configure CoPP only in the default virtual device context (VDC), but the CoPP configuration applies to all VDCs on the NX-OS device. For more information on VDCs, see the [Cisco Nexus 7000 Series NX-OS Virtual Device Context Configuration Guide, Release 4.0](#).

Licensing Requirements for CoPP

The following table shows the licensing requirements for this feature:

Product	License Requirement
NX-OS	CoPP requires no license. Any feature not included in a license package is bundled with the Cisco NX-OS system images and is provided at no extra charge to you. For a complete explanation of the NX-OS licensing scheme, see the Cisco Nexus 7000 Series NX-OS Licensing Guide, Release 4.0 .

Guidelines and Limitations

CoPP has the following configuration guidelines and limitations:

- You must use the setup utility to change or reapply the default copp-system-policy policy. You can access the setup utility using the **setup** command at the CLI.

Send document comments to nexus7k-docfeedback@cisco.com

- CoPP does not support non-IP classes except for the default non-IP class. You can use ACLs instead of non-IP classes to drop non-IP traffic, and use the default non-IP CoPP class to limit to non-IP traffic that reaches the supervisor module.
- You cannot enable logging in CoPP policy ACLs.
- You must ensure that the CoPP policy does not filter critical traffic such as routing protocols or interactive access to the switches. Filtering this traffic could prevent remote access to the NX-OS device and require a console connection.
- The NX-OS software does not support egress CoPP or silent mode. CoPP is supported only on ingress (service-policy output CoPP cannot be applied to the control plane interface).
- You can use the access control entry (ACE) hit counters in the hardware only for ACL logic. Use the software ACE hit counters and the **show access-lists** and **show policy-map type control-plane** commands to evaluate CPU traffic.
- The NX-OS device hardware performs CoPP on a per-forwarding-engine basis. CoPP does not support distributed policing. Therefore, you should choose rates so that the aggregate traffic does not overwhelm the supervisor module.

**Note**

If you are familiar with the Cisco IOS CLI, be aware that the Cisco NX-OS commands for this feature might differ from the Cisco IOS commands that you would use.

Configuring CoPP

This section includes the following topics:

- [Configuring a Control Plane Class Map, page 20-9](#)
- [Configuring a Control Plane Policy Map, page 20-12](#)
- [Configuring the Control Plane Service Policy, page 20-15](#)
- [Changing or Reapplying the Default CoPP Policy, page 20-16](#)

Configuring a Control Plane Class Map

You must configure control plane class maps for control plane policies.

You can classify traffic by matching packets based on existing ACLs. The permit and deny ACL keywords are ignored in the matching.

BEFORE YOU BEGIN

Ensure that you are in the default VDC (or use the **switchto vdc** command).

Ensure that you have configured the IP ACLs (see [Chapter 10, “Configuring IP ACLs”](#)) or MAC ACLs (see [Chapter 11, “Configuring MAC ACLs”](#)) if you want to use ACE hit counters in the class maps.

SUMMARY STEPS

1. **config t**
2. **class-map type control-plane [match-all | match-any] class-map-name**

Send document comments to nexus7k-docfeedback@cisco.com

3. **match access-group name** *access-list-name*
match exception {ip | ipv6} icmp redirect
match exception {ip | ipv6} icmp unreachable
match exception {ip | ipv6} option
match protocol arp
match redirect arp-inspect
match redirect dhcp-snoop
4. **exit**
5. **show class-map type control-plane** [*class-map-name*]
6. **copy running-config startup-config**

DETAILED STEPS

	Command	Purpose
Step 1	config t Example: switch# config t switch(config)#	Enters global configuration mode.
Step 2	class-map type control-plane [match-all match-any] <i>class-map-name</i> Example: switch(config)# class-map type control-plane ClassMapA switch(config-cmap)#	Specifies a control plane class map and enters class map configuration mode. The default class matching is match-any . The name can be a maximum of 64 characters long and is case sensitive. Note You cannot use class-default, match-all, or match-any as class map names.

Send document comments to nexus7k-docfeedback@cisco.com

	Command	Purpose
Step 3	match access-group name <i>access-list-name</i> Example: switch(config-cmap)# match access-group name MyAccessList	Specifies matching for an IP ACL. You can repeat this step to match more than one IP ACL. Note The permit and deny ACL keywords are ignored in the control plane policing matching.
	match exception {ip ipv6} icmp redirect Example: switch(config-cmap)# match exception ip icmp redirect	Specifies matching for IPv4 or IPv6 ICMP redirect exception packets.
	match exception {ip ipv6} icmp unreachable Example: switch(config-cmap)# match exception ip icmp unreachable	Specifies matching for IPv4 or IPv6 ICMP unreachable exception packets.
	match exception {ip ipv6} option Example: switch(config-cmap)# match exception ip option	Specifies matching for IPv4 or IPv6 option exception packets.
	match protocol arp Example: switch(config-cmap)# match protocol arp	Specifies matching for IP Address Resolution Protocol (ARP) packets.
	match redirect arp-inspect Example: switch(config-cmap)# match redirect arp-inspect	Specifies matching for ARP inspection redirected packets.
	match redirect dhcp-snoop Example: switch(config-cmap)# match redirect dhcp-snoop	Specifies matching for Dynamic Host Configuration Protocol (DHCP) snooping redirected packets.
Step 4	exit Example: switch(config-cmap)# exit switch(config)#	Exits class map configuration mode.
Step 5	show class-map type control-plane [<i>class-map-name</i>] Example: switch(config)# show class-map type control-plane	(Optional) Displays the control plane class map configuration.
Step 6	copy running-config startup-config Example: switch(config)# copy running-config startup-config	(Optional) Copies the running configuration to the startup configuration.

Send document comments to nexus7k-docfeedback@cisco.com

Configuring a Control Plane Policy Map

You must configure a policy map for CoPP, which include policing parameters. If you do not configure a policer for a class, then the default policer conform action is drop. Glean packets are policed using the default-class. The NX-OS software supports 1-rate 2-color and 2-rate 3-color policing.

BEFORE YOU BEGIN

Ensure that you are in the default VDC (or use the **switchto vdc** command).

Ensure that you have configured a control plane class map (see the “[Configuring a Control Plane Class Map](#)” section on page 20-9).

SUMMARY STEPS

1. **config t**
2. **policy-map type control-plane *policy-map-name***
3. **class {*class-map-name* [insert-before *class-map-name*] | class-default }**
4. **police [cir] *cir-rate* [bps | gbps | kbps | mbps | pps]**
police [cir] *cir-rate* [bps | gbps | kbps | mbps | pps] [bc] *burst-size* [bytes | kbytes | mbytes | ms | packets | us]
police [cir] *cir-rate* [bps | gbps | kbps | mbps | pps]
conform {drop | set-cos-transmit *cos-value* | set-dscp-transmit *dscp-value* | set-prec-transmit *prec-value* | transmit} [exceed {drop | set dscp dscp table *cir-markdown-map* | transmit}] [violate {drop | set dscp dscp table *pir-markdown-map* | transmit}]
police [cir] *cir-rate* [bps | gbps | kbps | mbps | pps]
pir *pir-rate* [bps | gbps | kbps | mbps | pps] [[be] *extended-burst-size* [bytes | kbytes | mbytes | ms | packets | us]]
5. (Optional) **set cos [inner] *cos-value***
6. (Optional) **set dscp [tunnel] {*dscp-value* | af11 | af12 | af13 | af21 | af22 | af23 | af31 | af32 | af33 | af41 | af42 | af43 | cs1 | cs2 | cs3 | cs4 | cs5 | cs6 | cs7 | sf | default }**
7. (Optional) **set precedence [tunnel] *prec-value***
8. **exit**
9. **exit**
10. **show policy-map type control-plane [expand] [name *policy-map-name*]**
11. **copy running-config startup-config**

Send document comments to nexus7k-docfeedback@cisco.com

DETAILED STEPS

	Command	Purpose
Step 1	<pre>config t</pre> <p>Example: switch# config t switch(config)#</p>	Enters global configuration mode.
Step 2	<pre>policy-map type control-plane policy-map-name</pre> <p>Example: switch(config)# policy-map type control-plan ClassMapA switch(config-pmap)#</p>	Specifies a control plane policy map and enters policy map configuration mode. The policy map name can have a maximum of 64 characters and is case sensitive.
Step 3	<pre>class {class-map-name [insert-before class-map-name2] class-default}</pre> <p>Example: switch(config-pmap)# class ClassMapA switch(config-pmap-c)#</p>	<p>Specifies a control plane class map name or the class default and enters control plane class configuration mode.</p> <p>Note The class-default class map is always at the end of the class map list for a policy map.</p>

Send document comments to nexus7k-docfeedback@cisco.com

	Command	Purpose
Step 4	<pre>police [cir] {cir-rate [bps gbps kbps mbps pps] percent percent}</pre> <p>Example: switch(config-pmap-c)# police cir 52000</p>	Specifies the committed information rate (CIR). The rate range is from 0 to 80000000000. The default CIR unit is bps .
	<pre>police [cir] {cir-rate [bps gbps kbps mbps pps] percent percent} [bc] burst-size [bytes kbytes mbytes ms packets us]</pre> <p>Example: switch(config-pmap-c)# police cir 52000 bc 1000</p>	Specifies the CIR with the committed burst (BC). The CIR range is from 0 to 80000000000 and the BC range is from 0 to 512000000. The default CIR unit is bps and the default BC size unit is bytes .
	<pre>police [cir] {cir-rate [bps gbps kbps mbps pps] percent percent} conform {drop set-cos-transmit cos-value set-dscp-transmit dscp-value set-prec-transmit prec-value transmit} [exceed {drop set dscp dscp table cir-markdown-map transmit}] [violate {drop set dscp dscp table pir-markdown-map transmit}]</pre> <p>Example: switch(config-pmap-c)# police cir 52000 conform transmit exceed drop</p>	<p>Specifies the CIR with the conform action. The CIR range is from 0 to 80000000000. The default rate unit is bps. The range for the <i>cos-value</i> and <i>prec-value</i> arguments is from 0 to 7. The range for the <i>dscp-value</i> argument is from 0 to 63.</p> <p>The options are as follows:</p> <ul style="list-style-type: none"> • drop—Drops the packet. • set-cos-transmit—Sets the cost of service value. • set-dscp-transmit—Sets the differentiated services code point value. • set-prec-transmit—Sets the precedence value. • transmit—Transmits the packet. • set dscp dscp table cir-markdown-map—Sets the exceed action to the CIR markdown map. • set dscp dscp table pir-markdown-map—Sets the violate action to the PIR markdown map. <p>Note You can specify the BC and conform action for the same CIR.</p>
Step 5	<pre>police [cir] {cir-rate [bps gbps kbps mbps pps] percent percent} pir pir-rate [bps gbps kbps mbps] [[be] burst-size [bytes kbytes mbytes ms packets us]]</pre> <p>Example: switch(config-pmap-c)# police cir 52000 pir 78000 be 2000</p>	<p>Specifies the CIR with the peak information rate (PIR). The CIR range is from 0 to 80000000000 and the PIR range is from 1 to 80000000000. You can optional set an extended burst (BE) size. The BE range is from 1 to 512000000. The default CIR unit is bps, the default PIR unit is bps, and the default BE size unit is bytes.</p> <p>Note You can specify the BC, conform action, and PIR for the same CIR.</p>
	<pre>set cos [inner] cos-value</pre> <p>Example: switch(config-pmap-c)# set cos 1</p>	(Optional) Specifies the 802.1Q class of service (CoS) value. Use the inner keyword in a Q-in-Q environment. The range is from 0 to 7. The default value is 0.

Send document comments to nexus7k-docfeedback@cisco.com

	Command	Purpose
Step 6	<pre>set dscp [tunnel] {dscp-value af11 af12 af13 af21 af22 af23 af31 af32 af33 af41 af42 af43 cs1 cs2 cs3 cs4 cs5 cs6 cs7 ef default}</pre> <p>Example: switch(config-pmap-c)# set dscp 10</p>	(Optional) Specifies the differentiated services code point value in IPv4 and IPv6 packets. Use the tunnel keyword to set tunnel encapsulation. The range is from 0 to 63. The default value is 0.
Step 7	<pre>set precedence [tunnel] {prec-value critical flash flash-override immediate internet network priority routine}</pre> <p>Example: switch(config-pmap-c)# set precedence 2</p>	(Optional) Specifies the precedence value in IPv4 and IPv6 packets. Use the tunnel keyword to set tunnel encapsulation. The range is from 0 to 7. The default value is 0.
Step 8	<pre>exit</pre> <p>Example: switch(config-pmap-c)# exit switch(config-pmap)#</p>	Exits policy map class configuration mode.
Step 9	<pre>exit</pre> <p>Example: switch(config-pmap)# exit switch(config)#</p>	Exits policy map configuration mode.
Step 10	<pre>show policy-map type control-plane [expand] [name class-map-name]</pre> <p>Example: switch(config)# show policy-map type control-plane</p>	(Optional) Displays the control plane policy map configuration.
Step 11	<pre>copy running-config startup-config</pre> <p>Example: switch(config)# copy running-config startup-config</p>	(Optional) Copies the running configuration to the startup configuration.

Configuring the Control Plane Service Policy

You can configure one or more policy maps for the CoPP service policy.

BEFORE YOU BEGIN

Ensure that you are in the default VDC (or use the **switchto vdc** command).

Ensure that you have configured a control plan policy map (see the [“Configuring a Control Plane Policy Map”](#) section on page 20-12).

SUMMARY STEPS

1. **config t**
2. **control-plane**
3. **service-policy input *policy-map-name***

Send document comments to nexus7k-docfeedback@cisco.com

4. `exit`
5. `show running-config copp [all]`
6. `copy running-config startup-config`

DETAILED STEPS

	Command	Purpose
Step 1	<code>config t</code> Example: switch# <code>config t</code> switch(config)#	Enters global configuration mode.
Step 2	<code>control-plane</code> Example: switch(config)# <code>control-plane</code> switch(config-cp)#	Enters control plane configuration mode.
Step 3	<code>service-policy input policy-map-name</code> Example: switch(config-cp)# <code>service-policy input</code> PolicyMapA	Specify a policy map for the input traffic. Repeat this step if you have more than one policy map. Use the no service-policy input <i>policy-map-name</i> command to remove the policy from the control plane.
Step 4	<code>exit</code> Example: switch(config-cp)# <code>exit</code> switch(config)#	Exits control plane configuration mode.
Step 5	<code>show running-config copp [all]</code> Example: switch(config)# <code>show running-config copp</code>	(Optional) Displays the CoPP configuration.
Step 6	<code>copy running-config startup-config</code> Example: switch(config)# <code>copy running-config</code> startup-config	(Optional) Copies the running configuration to the startup configuration.

Changing or Reapplying the Default CoPP Policy

In Cisco NX-OS Release 4.0(2) and later releases, you can change to a different default CoPP policy using the `setup` utility. You can also reapply the same CoPP default policy. For an example of changing the default CoPP policy, see the [“Changing or Reapplying the Default CoPP Policy”](#) section on page 20-20.

BEFORE YOU BEGIN

Ensure that you are in the default VDC (or use the `switchto vdc` command).

SUMMARY STEPS

1. `setup`

Send document comments to nexus7k-docfeedback@cisco.com

DETAILED STEPS

	Command	Purpose
Step 1	setup Example: switch# setup	Enters the setup utility.

Displaying the CoPP Configuration Status

In Cisco NX-OS Release 4.0(2) and later releases, you can display the CoPP feature configuration status information.

BEFORE YOU BEGIN

Ensure that you are in the default VDC (or use the **switchto vdc** command).

SUMMARY STEPS

1. **show copp status**

DETAILED STEPS

	Command	Purpose
Step 1	show copp status Example: switch# show copp status	Displays CoPP feature configuration status information.

For detailed information about the fields in the output from this command, see to the [Cisco Nexus 7000 Series NX-OS Security Command Reference, Release 4.0](#).

Displaying the CoPP Statistics

You can display the CoPP statistics.

BEFORE YOU BEGIN

Ensure that you are in the default VDC (or use the **switchto vdc** command).

SUMMARY STEPS

1. **show policy-map interface control-plane**

Send document comments to nexus7k-docfeedback@cisco.com

DETAILED STEPS

	Command	Purpose
Step 1	show policy-map interface control-plane Example: switch# show policy-map interface control-plane	Displays control plane statistics.

For detailed information about the fields in the output from this command, see to the [Cisco Nexus 7000 Series NX-OS Security Command Reference, Release 4.0](#).

Clearing the CoPP Statistics

You can clear the CoPP statistics.

BEFORE YOU BEGIN

Ensure that you are in the default VDC (or use the **switchto vdc** command).

SUMMARY STEPS

1. **show policy-map interface control-plane**
2. **clear copp statistics**

DETAILED STEPS

	Command	Purpose
Step 1	show policy-map interface control-plane Example: switch# show policy-map interface control-plane	(Optional) Displays control plane statistics.
Step 2	clear copp statistics Example: switch# clear copp statistics	Clears the CoPP statistics.

[Send document comments to nexus7k-docfeedback@cisco.com](mailto:nexus7k-docfeedback@cisco.com)

Verifying CoPP Configuration

To display CoPP configuration information, perform one of the following tasks:

Command	Purpose
show class-map type control-plane [<i>class-map-name</i>]	Displays the control plane class map configuration.
show policy-map type control-plane [expand] [name <i>policy-map-name</i>]	Displays the control plane policy map configuration.
show running-config copp [all]	Displays the CoPP configuration in the running configuration.
show startup-config copp	Displays the CoPP configuration in the startup configuration.

For detailed information about the fields in the output from these commands, see to the [Cisco Nexus 7000 Series NX-OS Security Command Reference, Release 4.0](#).

CoPP Example Configurations

This section includes the following topics:

- [CoPP Configuration Example, page 20-19](#)
- [Changing or Reapplying the Default CoPP Policy, page 20-20](#)

CoPP Configuration Example

The following example shows how to configure CoPP using IP ACLs and MAC ACLs:

```
configure terminal
ip access-list copp-system-acl-igmp
permit igmp any 10.0.0.0/24

ip access-list copp-system-acl-msdp
permit tcp any any eq 639

mac access-list copp-system-acl-arp
permit any any 0x0806

ip access-list copp-system-acl-tacas
permit udp any any eq 49

ip access-list copp-system-acl-gre
permit 47 any any

ip access-list copp-system-acl-ntp
permit udp any 10.0.1.1/23 eq 123

ip access-list copp-system-acl-icmp
permit icmp any any

class-map type control-plane match-any copp-system-class-critical
```

Send document comments to nexus7k-docfeedback@cisco.com

```

match access-group name copp-system-acl-igmp
match access-group name copp-system-acl-msdp
match access-group name copp-system-acl-arp

class-map type control-plane match-any copp-system-class-important
match access-group name copp-system-acl-tacas
match access-group name copp-system-acl-gre

class-map type control-plane match-any copp-system-class-normal
match access-group name copp-system-acl-icmp
match exception ip icmp redirect
match exception ip icmp unreachable
match exception ip option
match redirect arp-inspect
match redirect dhcp-snoop

policy-map type control-plane copp-system-policy
class copp-system-class-critical
police cir 2000 kbps bc 1500 bytes pir 3000 kbps be 1500 bytes conform transmit exceed
transmit violate drop

class copp-system-class-important
police cir 1000 kbps bc 1500 bytes pir 1500 kbps be 1500 bytes conform transmit exceed
transmit violate drop

class copp-system-class-normal
police cir 400 kbps bc 1500 bytes pir 600 kbps be 1500 bytes conform transmit exceed
transmit violate drop

class class-default
police cir 200 kbps bc 1500 bytes pir 300 kbps be 1500 bytes conform transmit exceed
transmit violate drop

control-plane
service-policy input copp-system-policy

```

Changing or Reapplying the Default CoPP Policy

This following example shows how to change or reapply the default CoPP policy using the setup utility:

```

switch# setup

----- Basic System Configuration Dialog VDC: 1 -----

This setup utility will guide you through the basic configuration of
the system. Setup configures only enough connectivity for management
of the system.

*Note: setup is mainly used for configuring the system initially,
when no configuration is present. So setup always assumes system
defaults and not the current system configuration values.

Press Enter at anytime to skip a dialog. Use ctrl-c at anytime
to skip the remaining dialogs.

Would you like to enter the basic configuration dialog (yes/no): yes

Create another login account (yes/no) [n]: n

```

Send document comments to nexus7k-docfeedback@cisco.com

```

Configure read-only SNMP community string (yes/no) [n]: n
Configure read-write SNMP community string (yes/no) [n]: n
Enter the switch name : <CR>
Enable license grace period? (yes/no) [n]: n
Continue with Out-of-band (mgmt0) management configuration? (yes/no) [y]: n
Configure the default gateway? (yes/no) [y]: n
Configure advanced IP options? (yes/no) [n]: <CR>
Enable the telnet service? (yes/no) [n]: y
Enable the ssh service? (yes/no) [y]: <CR>
    Type of ssh key you would like to generate (dsa/rsa) : <CR>
Configure the ntp server? (yes/no) [n]: n
Configure default interface layer (L3/L2) [L3]: <CR>
Configure default switchport interface state (shut/noshut) [shut]: <CR>
Configure best practices CoPP profile (strict/moderate/lenient/none) [strict]: strict
Configure CMP processor on current sup (slot 6)? (yes/no) [y]: n
Configure CMP processor on redundant sup (slot 5)? (yes/no) [y]: n

The following configuration will be applied:
    no license grace-period
    no telnet server enable
    no system default switchport
    system default switchport shutdown
    policy-map type control-plane copp-system-policy

Would you like to edit the configuration? (yes/no) [n]: <CR>

Use this configuration and save it? (yes/no) [y]: y

switch#

```

Default Settings

Table 20-1 lists the default settings for CoPP parameters.

Table 20-1 **Default CoPP Parameters**

Parameters	Default
Default policy	Strict

[Send document comments to nexus7k-docfeedback@cisco.com](mailto:nexus7k-docfeedback@cisco.com)

Additional References

For additional information related to implementing CoPP, see the following sections:

- [Related Documents, page 20-22](#)
- [Standards, page 20-22](#)

Related Documents

Related Topic	Document Title
Licensing	Cisco Nexus 7000 Series NX-OS Licensing Guide, Release 4.0
Command reference	Cisco Nexus 7000 Series NX-OS Security Command Reference, Release 4.0
IP ACLs	Configuring IP ACLs
MAC ACLs	Configuring MAC ACLs

Standards

Standards	Title
RFC 2698	A Two Rate Three Color Marker

Send document comments to nexus7k-docfeedback@cisco.com

Feature History for CoPP

Table 20-2 lists the release history for this feature.

Table 20-2 Feature History for CoPP

Feature Name	Releases	Feature Information
Changing default policies	4.0(2)	You can use setup command to change the default CoPP policy.
Changes to the default policies	4.0(2)	The CoPP default policies have the following changes: <ul style="list-style-type: none"> • Added Secure Shell FTP (SFTP) to <code>copp-system-class-management</code>. • Added access-control lists (ACLs) to match the source ports for TACACS+, RADIUS, Network Time Protocol (NTP), FTP, TFTP, SFTP, Secure Shell (SSH), and Telnet. • Increased the policing bandwidth to 10 Mbps for the <code>copp-system-class-management</code> class. • Added an exception for IPv6 in the <code>copp-system-class-exception</code> class. • Added <code>pim-reg</code> in the <code>copp-system-class-important</code> class. • Enhanced the CoPP policies for HSRP and GLBP to improve scalability.

Send document comments to nexus7k-docfeedback@cisco.com