



M Commands

This chapter describes the Cisco NX-OS system management commands that begin with the letter M.

Send document comments to nexus7k-docfeedback@cisco.com.

match datalink

To configure the match data link (or Layer 2) attributes option in a flow record, use the **match datalink** command. To remove the data link configuration, use the **no** form of this command.

```
match datalink { mac source-address | mac destination-address | ethertype | vlan }
```

```
no match datalink { mac source-address | mac destination-address | ethertype | vlan }
```

Syntax Description	mac	Specifies the MAC address.
	source-address	Specifies the source MAC address.
	destination-address	Specifies the destination MAC address.
	ethertype	Specifies the EtherType.
	vlan	Specifies the VLAN ID.

Defaults None

Command Modes NetFlow record configuration (config-flow-record)

SupportedUserRoles network-admin
vdc-admin

Command History	Release	Modification
	4.1	This command was introduced.

Usage Guidelines This command does not require a license.

Examples This example shows how to configure the match data link attributes option in a flow record:

```
switch(config)# flow record NetFlow1
switch(config-flow-record)# match datalink mac source-address
switch(config-flow-record)#
```

This example shows how to remove the data link match option from a flow record:

```
switch(config-flow-record)# no match datalink mac source-address
switch(config-flow-record)#
```

Send document comments to nexus7k-docfeedback@cisco.com.

Related Commands	Command	Description
	match ip	Configures the match IP option for defining a NetFlow record map.
	match ipv4	Configures the match IPv4 option for defining a NetFlow record map.

Send document comments to nexus7k-docfeedback@cisco.com.

match ip

To configure the match IP option for defining a NetFlow record map, use the **match ip** command. To remove this option, use the **no** form of this command.

```
match ip {protocol | tos}
```

```
no match ip {protocol | tos}
```

Syntax Description	protocol	Specifies the protocol.
	tos	Specifies the type of service (ToS).
Defaults	None	
Command Modes	NetFlow record configuration (config-flow-record)	
Supported User Roles	network-admin vdc-admin	
Command History	Release	Modification
	4.0(1)	This command was introduced.
Usage Guidelines	This command does not require a license.	
Examples	<p>This example shows how to configure the match IP option for defining a NetFlow record map:</p> <pre>switch(config)# flow record Custom-NetFlow-Record-1 switch(config-flow-record)# match ip protocol switch(config-flow-record)# match ip tos switch(config-flow-record)#</pre> <p>This example shows how to remove the match option:</p> <pre>switch(config-flow-record)# no match ip protocol switch(config-flow-record)# no match ip tos switch(config-flow-record)#</pre>	
Related Commands	Command	Description
	show flow record	Displays information about NetFlow records.

Send document comments to nexus7k-docfeedback@cisco.com.

match ipv4

To configure the match IPv4 option for defining a NetFlow record map, use the **match ipv4** command. To remove this option, use the **no** form of this command.

```
match ipv4 {source | destination} address
```

```
no match ipv4 {source | destination} address
```

Syntax Description		
	source	Specifies the source address.
	destination	Specifies the destination address.
	address	Specifies the address.

Defaults None

Command Modes NetFlow record configuration (config-flow-record)

Supported User Roles network-admin
vdc-admin

Command History	Release	Modification
	4.0(1)	This command was introduced.

Usage Guidelines This command does not require a license.

Examples This example shows how to configure the match IPv4 option for defining a NetFlow record map:

```
switch(config)# flow record Custom-NetFlow-Record-1
switch(config-flow-record)# match ipv4 source address
switch(config-flow-record)# match ipv4 destination address
switch(config-flow-record)#
```

This example shows how to remove the match IPv4 configuration:

```
switch(config-flow-record)# no match ipv4 source address
switch(config-flow-record)# no match ipv4 destination address
switch(config-flow-record)#
```

Related Commands	Command	Description
	show flow record	Displays information about NetFlow records.

Send document comments to nexus7k-docfeedback@cisco.com.

match (NetFlow)

To specify match criteria for Flexible NetFlow flow records, use the **match** command. To remove match criteria for flow records, use the **no** form of this command.

```
match { flow direction | interface { input | output } | ip { protocol | tos } | ipv4 { destination address
| source address } | transport { destination-port | source-port } }
```

```
match { flow direction | interface { input | output } | ip { protocol | tos } | ipv4 { destination address
| source address } | transport { destination-port | source-port } }
```

Syntax Description		
flow direction		Specifies the direction of the flow to be matched.
interface input		Specifies that the match criterion is based on the input interface.
interface output		Specifies that the match criterion is based on the output interface.
ip protocol		Specifies that the match criterion is based on protocol.
ip tos		Specifies that the match criterion is based on type of service (ToS).
ipv4 destination address		Specifies that the match criterion is based on the destination IPv4 address.
ipv4 source address		Specifies that the match criterion is based on the source IPv4 address.
transport destination-port		Specifies that the match criterion for transport layer fields is based on the destination port.
transport source-port		Specifies that the match criterion for transport layer fields is based on the destination port.

Defaults No matching criteria are specified by default.

Command Modes Flow record configuration

Supported User Roles network-admin
vdc-admin

Command History	Release	Modification
	4.0(1)	This command was introduced.

Usage Guidelines A Flexible NetFlow flow record must be enabled before you can use the **match** command. This command does not require a license.

Send document comments to nexus7k-docfeedback@cisco.com.

Examples

This example shows how to specify the direction of the flow to be matched:

```
switch(config)# flow record FLOW-RECORD-1
switch(config-flow-record)# match flow direction
```

This example shows how to specify the match criterion is based on the input interface:

```
switch(config)# flow record FLOW-RECORD-1
switch(config-flow-record)# match interface input
```

This example shows how to specify that the match criterion is based on the output interface:

```
switch(config)# flow record FLOW-RECORD-1
switch(config-flow-record)# match interface output
```

This example shows how to specify that the match criterion is based on protocol:

```
switch(config)# flow record FLOW-RECORD-1
switch(config-flow-record)# match ip protocol
```

This example shows how to specify that the match criterion is based on type of service (ToS):

```
switch(config)# flow record FLOW-RECORD-1
switch(config-flow-record)# match ip tos
```

This example shows how to specify that the match criterion is based on the destination IPv4 address:

```
switch(config)# flow record FLOW-RECORD-1
switch(config-flow-record)# match ipv4 destination address
```

This example shows how to specify that the match criterion is based on the source IPv4 address:

```
switch(config)# flow record FLOW-RECORD-1
switch(config-flow-record)# match ipv4 source address
```

This example shows how to specify that the match criterion for transport layer fields is based on the destination port:

```
switch(config)# flow record FLOW-RECORD-1
switch(config-flow-record)# match ipv4 transport destination-port
```

This example shows how to specify that the match criterion for transport layer fields is based on the source port:

```
switch(config)# flow record FLOW-RECORD-1
switch(config-flow-record)# match ipv4 transport source-port
```

Related Commands

Command	Description
flow record	Creates a flow record.

Send document comments to nexus7k-docfeedback@cisco.com.

match transport

To configure the match transport option for defining a NetFlow record map, use the **match transport** command. To remove the match transport option, use the **no** form of this command.

```
match transport { destination-port | source-port }
```

```
no match transport { destination-port | source-port }
```

Syntax Description	destination-port Specifies the transport destination port.				
	source-port Specifies the transport source port.				
Defaults	None				
Command Modes	NetFlow record configuration (config-flow-record)				
Supported User Roles	network-admin vdc-admin				
Command History	<table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>4.0(1)</td> <td>This command was introduced.</td> </tr> </tbody> </table>	Release	Modification	4.0(1)	This command was introduced.
Release	Modification				
4.0(1)	This command was introduced.				
Usage Guidelines	This command does not require a license.				
Examples	<p>This example shows how to configure the match transport option for defining a NetFlow record map:</p> <pre>switch(config)# flow record Custom-NetFlow-Record-1 switch(config-flow-record)# match transport source-port</pre> <p>This example shows how to remove the configuration:</p> <pre>switch(config-flow-record)# no match transport source-port switch(config-flow-record)</pre>				
Related Commands	<table border="1"> <thead> <tr> <th>Command</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>show flow record</td> <td>Displays information about NetFlow records.</td> </tr> </tbody> </table>	Command	Description	show flow record	Displays information about NetFlow records.
Command	Description				
show flow record	Displays information about NetFlow records.				

Send document comments to nexus7k-docfeedback@cisco.com.

mode

To specify the mode in a NetFlow sampler, use the **mode** command. To remove the mode, use the **no** form of this command.

mode *samples*

no mode [*samples*]

Syntax Description	<i>samples</i> Number of samples per sampling. The range is from 1 to 64.				
Defaults	None				
Command Modes	NetFlow sampler configuration (config-flow-sampler)				
Supported User Roles	network-admin vdc-admin				
Command History	<table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>4.0(1)</td> <td>This command was introduced.</td> </tr> </tbody> </table>	Release	Modification	4.0(1)	This command was introduced.
Release	Modification				
4.0(1)	This command was introduced.				
Usage Guidelines	This command does not require a license.				
Examples	<p>This example shows how to specify the mode in a NetFlow sampler:</p> <pre>switch(config)# sampler Custom-NetFlow-Sampler-1 switch(config-flow-sampler)# mode 1 out-of 1000 switch(config-flow-sampler)#</pre> <p>This example shows how to remove the mode configuration:</p> <pre>switch(config-flow-sampler)# no mode</pre>				
Related Commands	<table border="1"> <thead> <tr> <th>Command</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>show sampler</td> <td>Displays information about NetFlow samplers.</td> </tr> </tbody> </table>	Command	Description	show sampler	Displays information about NetFlow samplers.
Command	Description				
show sampler	Displays information about NetFlow samplers.				

[Send document comments to nexus7k-docfeedback@cisco.com.](mailto:nexus7k-docfeedback@cisco.com)

monitor counter

To configure a Simple Network Management Protocol (SNMP) monitor counter, use the **monitor counter** command. To remove a monitor counter configuration, use the **no** form of this command.

```
monitor counter { invalid-crc | invalid-words | link-loss | protocol-error | rx-performance |
signal-loss | state-change | sync-loss | tx-performance }
```

```
no monitor counter { invalid-crc | invalid-words | link-loss | protocol-error | rx-performance |
signal-loss | state-change | sync-loss | tx-performance }
```

Syntax Description

invalid-crc	Configures the invalid-crc counter.
invalid-words	Configures the invalid-words counter.
link-loss	Configures the link-loss counter.
protocol-error	Configures the protocol-error counter.
rx-performance	Configure the ingress (rx) performance counter.
signal-loss	Configures the signal-loss counter.
state-change	Configures the state-change counter.
sync-loss	Configures the sync-loss counter.
tx-performance	Configures the egress (tx) performance counter.

Defaults

None

Command Modes

Port-monitor configuration (config-port-monitor)

Supported User Roles

network-admin
vdc-admin

Command History

Release	Modification
4.1(2)	This command was introduced.

Usage Guidelines

This command does not require a license.

Examples

This example shows how to configure an SNMP counter:

```
switch(config) port-monitor name PM1
switch(config-port-monitor)# monitor counter signal-loss
switch(config-port-monitor)#
```

This example shows how to remove a counter configuration:

Send document comments to nexus7k-docfeedback@cisco.com.

```
switch(config)# no monitor counter signal-loss  
switch(config-port-monitor)#
```

Related Commands

Command	Description
counter	Configures an individual counter.

Send document comments to nexus7k-docfeedback@cisco.com.

monitor erspan origin ip-address

To configure the Encapsulated Remote Switched Port Analyzer (ERSPAN) origin IP address, use the **monitor erspan origin ip-address** command. To remove the ERSPAN origin IP address configuration, use the **no** form of this command.

monitor erspan origin ip-address *ip-address* **global**

no monitor erspan origin ip-address *ip-address* **global**

Syntax Description	<i>ip-address</i>	IP address.
	global	(Optional) Specifies the default virtual device context (VDC) configuration across all VDCs.

Defaults None

Command Modes Global configuration (config)

Supported User Roles network-admin
vdc-admin

Command History	Release	Modification
	5.1(1)	This command was introduced.

Usage Guidelines When you change the origin IP address in the default VDC, it impacts of all the sessions.
This command does not require a license.

Examples This example shows how to configure the ERSPAN origin IP address:

```
switch# configure terminal
switch(config)# monitor erspan origin ip-address 10.1.1.1 global
switch(config)#
```

This example shows how to remove the ERSPAN IP address:

```
switch# configure terminal
switch(config)# no monitor erspan origin ip-address 10.1.1.1 global
switch(config)#
```

Send document comments to nexus7k-docfeedback@cisco.com.

monitor session

To enter the monitor configuration mode for configuring Encapsulated Remote Switched Port Analyzer (ERSPAN) or an Ethernet switched port analyzer (SPAN) session for analyzing traffic between ports, use the **monitor session** command. To disable an ERSPAN or an SPAN session(s), use the **no** form of this command.

monitor session {*session_number* | **type** [erspan-source | erspan-destination | local]}

no monitor session [{*session_number* | **type** [erspan-source | erspan-destination | local]} | {all}]

Syntax Description	
<i>session_number</i>	Session number to use for monitoring a switched port. The range is from 1 to 18.
type	Specifies a session type. A session type can be local, erspan-source, or erspan-destination.
erspan-source	(Optional) Creates an ERSPAN source session.
erspan-destination	(Optional) Creates an ERSPAN destination session.
local	(Optional) Creates a local session.
all	Specifies all sessions for monitoring a switched port.

Defaults None

Command Modes Global configuration (config)

SupportedUserRoles Super user
VDC administrator
VDC user

Command History	Release	Modification
	5.1(1)	The number of sessions has been increased to 48.
	4.0(1)	This command was introduced.

Usage Guidelines While configuring an ERSPAN source session, if rx, tx, or both are not entered, the source is configured for both direction.

For more information about the ERSPAN configuration, see the *Cisco Nexus 7000 Series NX-OS System Management Configuration Guide, Release 5.x*.

This command does not require a license.

Send document comments to nexus7k-docfeedback@cisco.com.

Examples

This example shows how to enter the monitor configuration mode for configuring SPAN session number 9 for analyzing traffic between ports:

```
switch(config)# monitor session 9 type local
switch(config-monitor)# description A Local SPAN session
switch(config-monitor)# source interface ethernet 1/1
switch(config-monitor)# destination interface ethernet 1/2
switch(config-monitor)# no shut
```

This example shows how to configure any SPAN destination interfaces as Layer 2 SPAN monitor ports before activating the SPAN session:

```
switch(config)# interface ethernet 1/2
switch(config-if)# switchport
switch(config-if)# switchport monitor
switch(config-if)# no shutdown
```

This example shows how to configure a typical SPAN destination trunk interface:

```
switch(config)# interface Ethernet1/2
switch(config-if)# switchport
switch(config-if)# switchport mode trunk
switch(config-if)# switchport monitor
switch(config-if)# switchport trunk allowed vlan 10-12
switch(config-if)# no shutdown
```

This example shows how to terminate or extend RSPAN:

```
switch(config)# vlan 200
switch(config-vlan)# remote-span
switch(config-vlan)#
```

This example shows how to monitor RSPAN VLAN traffic using a local SPAN:

```
switch(config)# monitor session 1 type local
switch(config-monitor)# description RSPAN VLAN as source
switch(config-monitor)# source vlan 200
switch(config-monitor)# destination interface ethernet 1/2
switch(config-monitor)# no shut
switch(config-monitor)#
```

This example shows how to disable a SPAN session:

```
switch(config)# no monitor session 9 type local
```

This example show how to create an ERSPAN source:

```
switch# configure terminal
switch(config)# monitor session 1 type erspan-source
switch(config-monitor-erspan-src)# source int eth1/1
switch(config-monitor-erspan-src)# destination ip address 10.1.1.1
switch(config-monitor-erspan-src)# erspan-id 101
switch(config-monitor-erspan-src)# vrf erspan-vrf
switch(config-monitor-erspan-src)# filter vlan 100
switch(config-monitor-erspan-src)# no shut
```

This example show how to create an ERSPAN destination:

```
switch# configure terminal
switch(config)# monitor session 1 type erspan-destination
switch(config-monitor-erspan-dst)# destination interface eth1/5
switch(config-monitor-erspan-dst)# vrf foo
switch(config-monitor-erspan-dst)# erspan-id 12
switch(config-monitor-erspan-dst)# source ip 10.1.1.1
```

Send document comments to nexus7k-docfeedback@cisco.com.

```
switch(config-monitor-erspan-dst)# no shut
```

This example show how to create an access control list (ACL) filter and associate it with the ERSPAN source, IP time-to-leave (TTL), and differentiated services code point (DSCP) value:

```
switch# configure terminal
switch(config)# monitor session 3 type erspan-source
switch(config-monitor)# description erspan_src_session_3
switch(config-monitor-erspan-src)# source interface port-channel 2
switch(config-monitor-erspan-src)# filter vlan 3-5, 7
switch(config-monitor-erspan-src)# filter access-group ACL1
switch(config-monitor-erspan-src)# destination ip-address 10.1.1.1
switch(config-monitor-erspan-src)# erspan-id 5
switch(config-erspan-src)# vrf default
switch(config-erspan-src)# ip ttl 25
switch(config-erspan-src)# ip dscp 42
switch(config-monitor-erspan-src)# exit
```

Related Commands

Command	Description
show monitor session	Displays the specified SPAN session configuration.
description	Adds a comment or a description of up to 32 characters to a SPAN session.
destination	Adds a SPAN destination where source packets are copied.
source	Configures the source and the traffic direction in which to copy packets for a SPAN and ERSPAN session.

[Send document comments to nexus7k-docfeedback@cisco.com.](mailto:nexus7k-docfeedback@cisco.com)

mtu

To configure the maximum transmission unit (MTU) truncation size for packets in the specified Ethernet Switched Port Analyzer (SPAN) session, use the **mtu** command. To remove the MTU truncation size configuration, use the **no** form of this command.

mtu *mtu-size*

no mtu

Syntax Description	<i>mtu-size</i>	MTU truncation size. The range is from 64 to 1500.
---------------------------	-----------------	--

Defaults	Disabled
-----------------	----------

Command Modes	Monitor configuration (config-monitor)
----------------------	--

Supported User Roles	network-admin vdc-admin
-----------------------------	----------------------------

Command History	Release	Modification
	5.2(1)	This command was introduced.

Usage Guidelines	Make sure that you are in the correct virtual device context (VDC). To change the VDC, use the switchto vdc command.
-------------------------	---

MTU truncation and the SPAN rate limit cannot be enabled for the same SPAN session. If you configure both for one session, only the rate limit is allowed on F1 Series modules, and MTU truncation is disabled until you disable the rate limit configuration.



Note	MTU truncation is supported only on F1 Series modules.
-------------	--

This command does not require a license.

Examples	This example shows how to configure the MTU truncation size for packets in the specified SPAN session:
-----------------	--

```
switch# configure terminal
switch(config)# monitor session 5
switch(config-monitor)# mtu 128
switch(config-monitor)#
```


Send document comments to nexus7k-docfeedback@cisco.com.

This example shows how to remove the MTU truncation size configuration for packets in the specified SPAN session:

```
switch# configure terminal  
switch(config)# monitor session 5  
switch(config-monitor)# no mtu
```

Related Commands

Command	Description
monitor session	Places you in the monitor configuration mode for configuring a SPAN session.
show monitor session	Displays the status of the SPAN session.

Send document comments to nexus7k-docfeedback@cisco.com.

multicast best-effort

To configure the multicast best effort mode for the specified Encapsulated Remote Switched Port Analyzer (ERSPAN) or the Ethernet Switched Port Analyzer (SPAN) session, use the **multicast best-effort** command. To remove the multicast best effort mode for an ERSPAN or SPAN session, use the **no** form of this command.

multicast best-effort

no multicast best-effort

Syntax Description This command has no arguments or keywords.

Defaults Disabled

Command Modes Monitor configuration (config-monitor)

SupportedUserRoles network-admin
vdc-admin

Command History	Release	Modification
	5.2(1)	This command was introduced.

Usage Guidelines By default, SPAN replication occurs on both the ingress and egress line card. When you enable the multicast best effort mode, SPAN replication occurs only on the ingress line card for multicast traffic or on the egress line card for packets egressing out of Layer 3 interfaces (that is, on the egress line card, packets egressing out of Layer 2 interfaces are not replicated for SPAN).

Make sure that you are in the correct virtual device context (VDC). To change the VDC, use the **switchto vdc** command.



Note Multicast best effort mode applies only to M1 Series modules

This command does not require a license.

Examples This example shows how to configure the multicast best effort mode for the specifies ERSPAN or SPAN session:

```
switch# configure terminal
switch(config)# monitor session 3
switch(config-monitor)# multicast best-effort
switch(config-monitor)#
```

Send document comments to nexus7k-docfeedback@cisco.com.

This example shows how to remove the multicast best effort mode for the specified ERSPAN or SPAN session:

```
switch# configure terminal
switch(config)# monitor session 3
switch(config-monitor)# no multicast best-effort
switch(config-monitor)#
```

Related Commands

Command	Description
monitor session	Places you in the monitor configuration mode for configuring a SPAN session.
show monitor session	Displays the status of the SPAN session.

Send document comments to nexus7k-docfeedback@cisco.com.